Report on the RF Testing of:

MORITEX Corporation
Handy Skin Sensor Ⅱ, Model: HSS Ⅱ
FCC ID: 2AO35-HSS2

In accordance with FCC Part15 Subpart C
Class II Permissive Change

Japan

Add value.
Inspire trust.

Prepared for: MORITEX Corporation
3-13-45, Senzui, Asaka-shi, Saitama 351-0024
Japan
Phone: +81-48-218-2907 Fax: +81-48-467-3720

COMMERCIAL-IN-CONFIDENCE

Document Number: JPD-TR-19082-0

SIGNATURE			
Hiro Suzuki			
NAME	**JOB TITLE**	**RESPONSIBLE FOR**	**ISSUE DATE**
Hiroaki Suzuki	Deputy Manager of RF Group	Approved Signatory	17 JUN 2019

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Japan Ltd. document control rules.

EXECUTIVE SUMMARY

A sample(s) of this product was tested and found to be compliant with FCC Part15 Subpart C.

NVLAP® TESTING
NVLAP LAB CODE 200306-0

ilac-MRA

DISCLAIMER AND COPYRIGHT

The results in this report are applicable only to the equipment tested.
This report shall not be re-produced except in full without the written approval of TÜV SÜD Japan Ltd.

ACCREDIATION

This test report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TÜV SÜD Japan Ltd.
Yonezawa Testing Center
5-4149-7 Hachimanpara,
Yonezawa-shi, Yamagata,
992-1128 Japan

Phone: +81 (0) 238 28 2881
Fax: +81 (0) 238 28 2888
www.tuv-sud.jp

Contents

1 Summary of Test 3

1.1 Modification history of the test report 3
1.2 Standards 3
1.3 Test methods 3
1.4 Deviation from standards 3
1.5 List of applied test(s) of the EUT 3
1.6 Test information 3
1.7 Test set up 3
1.8 Test period 3

2 Equipment Under Test 4

2.1 EUT information 4
2.2 Modification to the EUT 5
2.3 Variation of family model(s) 5
2.4 Operating channels and frequencies 5
2.5 Description of test mode 6
2.6 Operating flow 6

3 Configuration of Equipment 7

3.1 Equipment used 7
3.2 Cable(s) used 7
3.3 System configuration 7

4 Test Result 8

4.1 DTS Bandwidth / Occupied Bandwidth (99%) 8
4.2 Maximum Conducted Output Power 13
4.3 Band Edge Compliance of RF Conducted Emissions 15
4.4 Spurious emissions - Conducted - 20
4.5 Spurious Emissions - Radiated - 31
4.6 Restricted Band of Operation 41
4.7 Transmitter Power Spectral Density 49
4.8 AC Power Line Conducted Emissions 54

5 Antenna requirement 57

6 Measurement Uncertainty 58

7 Laboratory Information 59

Appendix A. Test Equipment 60

Appendix B. Duty Cycle 61

1 Summary of Test

1.1 Modification history of the test report

Document Number	Modification History	Issue Date
JPD-TR-19082-0	First Issue	Refer to the cover page

1.2 Standards

CFR47 FCC Part 15 Subpart C

1.3 Test methods

ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

1.4 Deviation from standards

None

1.5 List of applied test(s) of the EUT

Test item section	Test item	Condition	Result	Remark
15.247(a)(2)	DTS Bandwidth / Occupied Bandwidth (99%)	Conducted	PASS	-
15.247(b)(3)	Maximum conducted (average) output power	Conducted	PASS	-
15.247(d)	Band Edge Compliance of RF Conducted Emissions	Conducted	PASS	-
15.247(d) 15.205 15.209	Spurious Emissions	Conducted Radiated	PASS	-
15.247(d) 15.205 15.209	Restricted Bands of Operation	Radiated	PASS	-
15.247(e)	Transmitter Power Spectral Density	Conducted	PASS	-
15.207	AC Power Line Conducted Emissions	Conducted	PASS	-

1.6 Test information

None

1.7 Test set up

Table-top

1.8 Test period

10-May-2019 - 17-May-2019

2 Equipment Under Test

2.1 EUT information

Applicant	MORITEX Corporation 3-13-45, Senzui, Asaka-shi, Saitama 351-0024 Japan Phone: +81(0)48-218-2907 Fax: +81(0)48-467-3720
Equipment Under Test (EUT)	Handy Skin Sensor Ⅱ
Model number	HSSⅡ
Serial number	9007C (Radiated), 9008C (Conducted)
Trade name	SHISEIDO
Number of sample(s)	1
EUT condition	Production
Power rating	Battery: DC 3.6 V
Size	(W) 64.0 mm×(D) 58.6 mm×(H) 171.0 mm
Environment	Indoor and Outdoor use
Terminal limitation	5˚C to 35˚C
Hardware Version	HV1.04
Software Version	Ampak RFTestTool, Ver：5.6
Firmware Version	FW_B20190105_WT1
RF Specification	
Protocol	IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20),
Frequency range	IEEE802.11b /11g/11n (HT20): 2412 MHz-2462 MHz
Number of RF Channels	11 Channels
Modulation type	IEEE802.11b: DSSS (DBPSK, DQPSK, CCK) IEEE802.11g /11n (HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Data rate	IEEE802.11b: 1, 2, 5.5, 11Mbps IEEE802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps IEEE802.11n (HT20 LGI): 6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps IEEE802.11n (HT20 SGI): 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2Mbps
Channel separation	5 MHz
Output power	39.264mW (IEEE802.11b) 119.674mW (IEEE802.11g) 116.681mW (IEEE802.11n: HT20)
Antenna type	Internal antenna
Antenna gain	2.16 dBi

2.2 Modification to the EUT

The table below details modifications made to the EUT during the test project.

Modification State	Description of Modification	Modification fitted by	Date of Modification
Model: HSSⅡ, Serial Number: 9007C, 9008C			
0	As supplied by the applicant	Not Applicable	Not Applicable

2.3 Variation of family model(s)

2.3.1 List of family model(s)

Not applicable

2.3.2 Reason for selection of EUT

Not applicable

2.4 Operating channels and frequencies

Channel	Frequency [MHz]
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

2.5 Description of test mode

The EUT had been tested under operating condition.
There are three channels have been tested as following:

Tested Channel [11b, 11g, 11n(HT20)]	Frequency [MHz]
Low	2412
Middle	2437
High	2462

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

Tested Channel	Modulation Type	Data Rate
Low, Middle, High	IEEE802.11b: DSSS	1Mbps
Low, Middle, High	IEEE802.11g: OFDM	6Mbps
Low, Middle, High	IEEE802.11n (HT20 LGI): OFDM	MCS0 (6.5Mbps)

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.
The worst emission was found in Z-axis and the worst case recorded.
Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports.

2.6 Operating flow

- Tx mode

i) Test program setup to the Software
ii) Select a Test mode
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
iii) Start test mode

- Rx mode

i) Test program setup to the Software
ii) Select a Test mode
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
iii) Start test mode

3 Configuration of Equipment

Numbers assigned to equipment on the diagram in “3.3 System configuration” correspond to the lists in “3.1 Equipment used” and “3.2 Cable(s) used”.
Cabling and setup(s) were taken into consideration and test data was taken under worse case condition.

3.1 Equipment used

No.	Equipment	Company	Model No.	Serial No.	FCC ID / DoC	Comment
1	Handy Skin Sensor Ⅱ	MORITEX Corporation	HSS Ⅱ	9007C, 9008C	2AO35-HSS2	EUT
2	Sensor Stand	MORITEX Corporation	HSS Ⅱ Stand	9007C	N/A	*
3	AC Adapter	MORITEX Corporation	UBX310-0520	H05-0558798	N/A	*

*: AC power line Conducted Emission Test.

3.2 Cable(s) used

No.	Cable	Length[m]	Shield	Connector	Comment
a	Micro USB cable (for AC Adapter)	1.6	Yes	Metal	*

*: AC power line Conducted Emission Test.

3.3 System configuration



4 Test Result

4.1 DTS Bandwidth / Occupied Bandwidth (99%)

4.1.1 Measurement procedure

[FCC 15.247(a)(2), KDB 558074 D01 v05r02, Section 8.2]

The bandwidth at 6dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;
a) RBW = 100kHz.
b) VBW ≥ 3 x RBW.
c) Sweep time = auto-couple.
d) Detector = peak.
e) Trace mode = max hold.

- Test configuration



4.1.2 Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

4.1.3 Measurement result

Date : 10-May-2019
Temperature : 23.0 [˚C]
Humidity : 24.1 [%]
Test place : Shielded room No.4

Test engineer : Taiki Watanabe

Channel	DTS Bandwidth [MHz]		
	IEEE802.11b	IEEE802.11g	IEEE802.11n (HT20)
Low	8.095	15.012	15.142
Middle	8.099	15.105	15.137
High	8.790	15.143	15.136

Channel	Occupied Bandwidth (99%) [MHz]		
	IEEE802.11b	IEEE802.11g	IEEE802.11n (HT20)
Low	12.113	16.320	17.471
Middle	12.075	16.302	17.476
High	12.043	16.309	17.477

4.1.4 Trace data

[IEEE802.11b]

Channel Low



Channel Middle



Channel High



[IEEE802.11g]

Channel Low



Channel Middle



Channel High



[IEEE802.11n (HT20)]

Channel Low



Channel Middle



Channel High



4.2 Maximum Conducted Output Power

4.2.1 Measurement procedure

[FCC 15.247(b)(3), KDB 558074 D01 v05r02, Section 8.3.1.3]

The peak power is measured with a power sensor connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

- Test configuration



4.2.2 Limit

1 W (1000 mW) or less

4.2.3 Measurement result

Date : 10-May-2019
Temperature : 23.0 [˚C]
Humidity : 24.1 [%]
Test place : Shielded room No.4

Test engineer : Taiki Watanabe

[IEEE802.11b]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	5.29	10.49	15.78	37.844	≦1000	PASS
Middle	2437	5.40	10.49	15.89	38.815	≦1000	PASS
High	2462	5.45	10.49	15.94	39.264	≦1000	PASS

[IEEE802.11g]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	10.29	10.49	20.78	119.674	≦1000	PASS
Middle	2437	10.11	10.49	20.60	114.815	≦1000	PASS
High	2462	10.25	10.49	20.74	118.577	≦1000	PASS

[IEEE802.11n (HT20)]
Battery Full

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Output Power (mW)	Limit (mW)	Result
Low	2412	9.59	10.49	20.08	101.859	≦1000	PASS
Middle	2437	10.18	10.49	20.67	116.681	≦1000	PASS
High	2462	9.77	10.49	20.26	106.170	≦1000	PASS

Calculation;
Reading (dBm) + Factor (dB) = Level (dBm)
10logP = Level (dBm)
$P = 10^{(\text{Maximum Peak Output Power} / 10)}$ (mW)

4.3 Band Edge Compliance of RF Conducted Emissions

4.3.1 Measurement procedure

[FCC 15.247(d), KDB 558074 D01 v05r02, Section 8.5]

The Band Edge is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;
a) Span = Arbitrary setting. (Setting suitable for measurement.)
b) RBW = 100kHz.
c) VBW ≥ 3 x RBW
d) Sweep time = auto-couple.
e) Detector = peak.
f) Trace mode = max hold.

- Test configuration



4.3.2 Limit

In any 100 kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

4.3.3 Measurement result

Date : 15-May-2019
Temperature : 23.6 [˚C]
Humidity : 44.2 [%]
Test place : Shielded room No.4

Test engineer : Kazunori Saito

[IEEE802.11b]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-5.96	2397.44	-45.60	39.64	At least 20dB below from peak of RF	PASS
High	2462.00	-5.53	2487.98	-60.26	54.73	At least 20dB below from peak of RF	PASS

[IEEE802.11g]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-8.92	2398.80	-42.06	33.14	At least 20dB below from peak of RF	PASS
High	2462.00	-8.66	2483.82	-47.29	38.63	At least 20dB below from peak of RF	PASS

[IEEE802.11n (HT20)]

Channel	Frequency (MHz)	RF Power Level (dBm)	Band-edge Frequency (MHz)	Band-edge Level (dBm)	Difference Level (dBm)	Limit (dBm)	Result
Low	2412.00	-9.93	2399.20	-45.87	35.94	At least 20dB below from peak of RF	PASS
High	2462.00	-9.63	2484.06	-50.48	40.85	At least 20dB below from peak of RF	PASS

4.3.4 Trace data

[IEEE802.11b]

Channel Low



Channel High



[IEEE802.11g]

Channel Low



Channel High



[IEEE802.11n (HT20)]

Channel Low



Channel High



4.4 Spurious emissions - Conducted -

4.4.1 Measurement procedure

[FCC 15.247(d), KDB 558074 D01 v05r02, Section 8.5]

The spurious emissions (Conducted) are measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;
a) Span = wide enough to fully capture the emission being measured.
b) RBW = 100 kHz.
c) VBW ≥ RBW.
d) Sweep time = auto-couple.
e) Detector = peak.
f) Trace mode = max hold.

- Test configuration



4.4.2 Limit

In any 100 kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

4.4.3 Measurement result

Date : 15-May-2019
Temperature : 23.6 [˚C]
Humidity : 44.2 [%]
Test place : Shielded room No.4
Test engineer : Kazunori Saito

[IEEE802.11b、IEEE802.11g、IEEE802.11n (HT20)]

Channel	Frequency [MHz]	Limit [dB]	Results Chart	Result
Low	2412	At least 20dB below from peak of RF	See the trace Data	PASS
Middle	2437	At least 20dB below from peak of RF	See the trace Data	PASS
High	2462	At least 20dB below from peak of RF	See the trace Data	PASS

4.4.4 Trace data

[IEEE802.11b]
Channel Low

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel Middle

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel High

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



[IEEE802.11g]
Channel Low

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel Middle

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel High

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



[IEEE802.11n (HT20)]

Channel Low

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel Middle

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



Channel High

30MHz-1GHz



1GHz-5GHz



5GHz-10GHz



10GHz-15GHz



15GHz-20GHz



20GHz-25GHz



4.5 Spurious Emissions - Radiated -

4.5.1 Measurement procedure

[FCC 15.247(d), 15.205, 15.209, KDB 558074 D01 v05r02, Section 8.6]

Test was applied by following conditions.

Test method	:	ANSI C63.10
Frequency range	:	9 kHz to 25 GHz
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	Styrofoam table / (W) 1.0 × (D) 1.0 × (H) 0.8 m (below 1 GHz) Styrofoam table / (W) 0.6 × (D) 0.6 ×(H)1.5 m (above 1 GHz)
Antenna distance	:	3 m
Test receiver setting		Below 1 GHz
- Detector	:	Average (9 kHz-90 kHz, 110 kHz-490 kHz), Quasi-peak
- Bandwidth	:	200 Hz, 120 kHz
Spectrum analyzer setting		Above 1 GHz
- Peak	:	RBW=1 MHz, VBW=3 MHz, Span=0 Hz, Sweep=auto
- Average	:	RBW=1 MHz, VBW=10 Hz, Span=0 Hz, Sweep=auto Display mode=Linear

Average Measurement Setting [VBW]

Mode	Duty Cycle (%)	T_{on} (us)	T_{off} (us)	$1/T_{on}$ (kHz)	Determined VBW Setting
IEEE802.11b	99.41	8410	50	0.119	10Hz (Duty Cycle ≧ 98%)
IEEE802.11g	97.29	1398	39	0.715	1kHz
IEEE802.11n(HT20)	97.10	1308	39	0.765	1kHz

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

Radiated emission measurements are performed at 3m distance with the broadband antenna (Loop antenna, Biconical antenna, Log periodic antenna and Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission. As for the Loop antenna, it is positioned with its plane vertical, and the center of the Loop antenna is 1m above the ground plane.
The EUT is Placed on a turntable, which is 0.8m/1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



4.5.2 Calculation method

[9 kHz to 150 kHz]
Emission level = Reading + (Ant factor + Cable system loss)
Margin = Limit – Emission level

[150 kHz to 25 GHz]
Emission level = Reading + (Ant factor + Cable system loss - Amp. Gain)
Margin = Limit – Emission level

Example:
Limit @ 4824.0 MHz : 74.0 dBuV/m (Peak Limit)
S.A Reading = 49.5 dBuV Cable system loss = 8.4 dB
Result = 49.5 + 8.4 = 45.1 dBuV/m
Margin = 74.0 - 45.1 = 16.1 dB

4.5.3 Limit

Frequency [MHz]	Field strength		Distance [m]
	[uV/m]	[dBuV/m]	
0.009-0.490	2400 / F [kHz]	20logE [uV/m]	300
0.490-1.705	24000 / F [kHz]	20logE [uV/m]	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Note:
1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition modulation.

4.5.4 Test data

Date	:	15-May-2019			
Temperature	:	20.3 [˚C]			
Humidity	:	39.1 [%]	Test engineer	:	
Test place	:	3m Semi-anechoic chamber			Chiaki Kanno

Date	:	15-May-2019			
Temperature	:	20.0 [˚C]			
Humidity	:	56.6 [%]	Test engineer	:	
Test place	:	3m Semi-anechoic chamber			Chiaki Kanno

4.5.4.1 Transmission mode

[11b]
Channel Low
BELOW 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. <<DATA Sheet No.01>> 16 May,2019 01:22

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpartC
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum	: 20.0[℃] 56.6[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11b_Tx_ch:Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]
1	210.900	H	25.5	-8.2	17.3	43.5	26.2	100.0	210.0
2	480.000	H	37.4	-9.6	27.8	46.0	18.2	200.0	344.0
3	528.000	H	40.2	-9.1	31.1	46.0	14.9	180.0	342.0
4	544.500	H	42.2	-8.7	33.5	46.0	12.5	174.0	0.0
5	594.000	H	37.0	-7.7	29.3	46.0	16.7	349.0	0.0
6	792.000	H	44.1	-5.3	38.8	46.0	7.2	112.0	174.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11b]
Channel Low
ABOVE 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. | <<DATA Sheet No.02>> | 15 May,2019 00:53

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpart C
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum,Atm	: 20.3[℃] 39.1[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11b_Tx_Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading AV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [°]
1	4824.000	H	49.2	36.3	10.3	59.5	46.6	74.0	54.0	14.5	7.4	100.0	227.0
2	4824.000	V	49.2	36.4	10.3	59.5	46.7	74.0	54.0	14.5	7.3	204.0	126.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11g]
Channel Low
BELOW 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. <<DATA Sheet No.03>> 16 May,2019 02:22

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpartC
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum	: 20.0[℃] 56.6[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11g_Tx_ch:Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]
1	194.900	H	24.4	-8.5	15.9	43.5	27.6	100.0	285.0
2	456.000	H	40.8	-10.2	30.6	46.0	15.4	206.0	348.0
3	504.000	H	41.2	-9.4	31.8	46.0	14.2	201.0	342.0
4	544.500	H	42.3	-8.7	33.6	46.0	12.4	178.0	348.0
5	552.000	H	41.8	-8.4	33.4	46.0	12.6	170.0	0.0
6	792.000	H	43.2	-5.3	37.9	46.0	8.1	113.0	168.0
7	984.000	H	35.7	-1.6	34.1	54.0	19.9	155.0	266.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11g]
Channel Low
ABOVE 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. | <<DATA Sheet No.04>> | 15 May,2019 01:38

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpart C
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum,Atm	: 20.3[℃] 39.1[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11g_Tx_Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading AV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [°]
1	4824.000	H	49.1	36.7	10.3	59.4	47.0	74.0	54.0	14.6	7.0	100.0	118.0
2	4824.000	V	48.9	37.1	10.3	59.2	47.4	74.0	54.0	14.8	6.6	201.0	124.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

[11n(HT20)]
Channel Low
BELOW 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. | <<DATA Sheet No.05>> | 16 May,2019 03:03

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpartC
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum	: 20.0[℃] 56.6[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11n(HT20)_Tx_ch:Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]
1	456.000	H	40.9	-10.2	30.7	46.0	15.3	232.0	341.0
2	504.000	H	41.2	-9.4	31.8	46.0	14.2	201.0	329.0
3	544.500	H	42.5	-8.7	33.8	46.0	12.2	164.0	0.0
4	552.000	H	41.6	-8.4	33.2	46.0	12.8	161.0	333.0
5	792.000	H	43.1	-5.3	37.8	46.0	8.2	116.0	197.0
6	984.000	H	35.2	-1.6	33.6	54.0	20.4	153.0	261.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT20)]
Channel Low
ABOVE 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. <<DATA Sheet No.06>> 15 May,2019 02:05

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpart C
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum,Atm	: 20.3[℃] 39.1[%]
Serial No.	: 9007C	Note1	:
Test mode	: 11n(HT20)_Tx_Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading AV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [°]
1	4824.000	H	48.7	36.8	10.3	59.0	47.1	74.0	54.0	15.0	6.9	100.0	119.0
2	4824.000	V	49.0	36.8	10.3	59.3	47.1	74.0	54.0	14.7	6.9	161.0	126.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

4.5.4.2 Receive mode

Channel Low
BELOW 1GHz

******* RADIATED EMISSION *******
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. | <<DATA Sheet No.07 >> | 16 May,2019 03:41

Company name	: Moritex Corporation	Standard	: FCC Part.15 subpartC
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum	: 20.0[℃] 56.6[%]
Serial No.	: 9007C	Note1	:
Test mode	: Rx_ch:Low	Note2	:



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [°]
1	456.000	H	40.9	-10.2	30.7	46.0	15.3	232.0	341.0
2	480.000	H	41.3	-9.6	31.7	46.0	14.3	192.0	343.0
3	504.000	H	41.2	-9.4	31.8	46.0	14.2	201.0	329.0
4	528.000	H	44.1	-9.1	35.0	46.0	11.0	176.0	0.0
5	544.500	H	42.2	-8.7	33.5	46.0	12.5	169.0	5.0
6	552.000	H	40.1	-8.4	31.7	46.0	14.3	177.0	344.0
7	792.000	H	43.8	-5.3	38.5	46.0	7.5	108.0	176.0

Note:
1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.

4.6 Restricted Band of Operation

4.6.1 Measurement procedure

[FCC 15.247(d), 15.205, 15.209, KDB 558074 D01 v05r02, Section 8.6]

Test was applied by following conditions.

Test method	:	ANSI C63.10
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	Styrofoam table / (W) 1.0 × (D) 1.0 × (H) 0.8 m (below 1 GHz) Styrofoam table / (W) 0.6 × (D) 0.6 ×(H) 1.5 m (above 1 GHz)
Antenna distance	:	3m
Spectrum analyzer setting		
- Peak	:	RBW=1 MHz, VBW=3 MHz, Span=Arbitrary setting, Sweep=auto
- Average	:	RBW=1 MHz, VBW=10 Hz, Span=Arbitrary setting, Sweep=auto Display mode=Linear

Average Measurement Setting [VBW]

Mode	Duty Cycle (%)	T_{on} (us)	T_{off} (us)	$1/T_{on}$ (kHz)	Determined VBW Setting
IEEE802.11b	99.41	8410	50	0.119	10Hz (Duty Cycle ≧ 98%)
IEEE802.11g	97.29	1398	39	0.715	1kHz
IEEE802.11n(HT20)	97.10	1308	39	0.765	1kHz

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

Radiated emission measurements are performed at 3m distance with the broadband antenna (Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission.
The EUT is Placed on a turntable, which is 0.8m/1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

- Test configuration



4.6.2 Limit

Emission at the boundary of the restricted band provided by 15.205 shall be lower than 15.209 limit.

4.6.3 Measurement Result

[IEEE802.11b、IEEE802.11g、IEEE802.11n (HT20)]

Channel	Frequency [MHz]	Results Chart	Result
Low	2412	See the Trace Data	Pass
High	2462	See the Trace Data	Pass

4.6.4 Test data

Date : 16-May-2019
Temperature : 20.3 [˚C]
Humidity : 39.1 [%]
Test place : 3m Semi-anechoic chamber
Test engineer : Chiaki Kanno

[IEEE802.11b]

Channel Low
Horizontal
Peak



Average



Vertical
Peak



Average



Channel High
Horizontal
Peak



Average



Vertical
Peak



Average



[IEEE802.11g]

Channel Low
Horizontal
Peak



Average



Vertical
Peak



Average



Channel High
Horizontal
Peak



Average



Vertical
Peak



Average



[IEEE802.11n (HT20)]

Channel Low
Horizontal
Peak



Average



Vertical
Peak



Average



Channel High
Horizontal
Peak



Average



Vertical
Peak



Average



4.7 Transmitter Power Spectral Density

4.7.1 Measurement procedure

[FCC 15.247(e), KDB 558074 D01 v05r02, Section 8.4]

The peak power is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;
a) Span = 1.5 times the 6 dB bandwidth.
b) RBW = 3kHz - 100kHz.
c) VBW ≥ 3 x RBW.
d) Sweep time = auto-couple.
e) Detector = peak.
f) Trace mode = max hold.

- Test configuration



4.7.2 Limit

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band.

4.7.3 Measurement result

Date	:	15-May-2019		
Temperature	:	23.6 [˚C]		
Humidity	:	44.2 [%]	Test engineer	:
Test place	:	Shielded room No.4		Kazunori Saito

[IEEE802.11b]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412	-19.27	10.49	-8.78	8.00	16.78	PASS
Middle	2437	-19.64	10.49	-9.15	8.00	17.15	PASS
High	2462	-19.88	10.49	-9.39	8.00	17.39	PASS

Calculation;
Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)

[IEEE802.11g]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412	-23.82	10.49	-13.33	8.00	21.33	PASS
Middle	2437	-22.99	10.49	-12.50	8.00	20.50	PASS
High	2462	-23.12	10.49	-12.63	8.00	20.63	PASS

Calculation;
Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)

[IEEE802.11n (HT20)]

Channel	Center Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dBm)	Result
Low	2412	-24.65	10.49	-14.16	8.00	22.16	PASS
Middle	2437	-23.97	10.49	-13.48	8.00	21.48	PASS
High	2462	-23.66	10.49	-13.17	8.00	21.17	PASS

Calculation;
Transmitter Power Spectral Density Level (Margin) = Limit – (Reading + Factor)

10.4 Trace data
[IEEE802.11b]

Channel Low



Channel Middle



Channel High



[IEEE802.11g]

Channel Low



Channel Middle



Channel High



[IEEE802.11n (HT20)]

Channel Low



Channel Middle



Channel High



4.8 AC Power Line Conducted Emissions

4.8.1 Measurement procedure

[FCC 15.207]

Test was applied by following conditions.

Test method	:	ANSI C63.10
Frequency range	:	0.15 MHz to 30 MHz
Test place	:	3m Semi-anechoic chamber
EUT was placed on	:	FRP table / (W) 2.0 × (D) 1.0 × (H) 0.8 m
Vertical Metal Reference Plane	:	(W) 2.0 × (H) 2.0 m, 0.4 m away from EUT
Test receiver setting		
- Detector	:	Quasi-peak, Average
- Bandwidth	:	9 kHz

EUT and peripherals are connected to 50Ω/50 μH Line Impedance Stabilization Network (LISN) which are connected to reference ground plane, and are placed 80cm away from EUT. Excess of AC power cable is bundled in center.
LISN for peripheral is terminated in 50Ω.
EUT operating mode is selected to emit the maximum noise. Overall frequency range is investigated with spectrum analyzer using peak detector. Maximum emission configuration is determined by manipulating the EUT, peripherals, interconnecting cables. Then, emission measurements are performed with test receiver in above setting to each current-carrying conductor of the mains port. Sufficient time for EUT, peripherals and test equipment is provided in order for them to warm up to their normal operating condition. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits.

- Test configuration



4.8.2 Calculation method

Emission level = Reading + (LISN. Factor + Cable system loss)
Margin = Limit – Emission level

Example:
Limit @ 0.403 MHz: 57.8 dBµV(Quasi-peak)
: 47.8 dBµV(Average)
(Quasi peak)Reading = 22.7 dBµV c.f. = 10.4 dB
Emission level = 22.7 + 10.4 = 33.1 dBµV
Margin = 57.8 – 33.1 = 24.7 dB
(Average) Reading = 6.5 dBµV c.f. = 10.4 dB
Emission level = 6.5 + 10.4 = 16.9 dBµV
Margin = 47.8 – 16.9 = 30.9 dB

4.8.3 Limit

Frequency [MHz]	Limit	
	QP [dBuV]	AV [dBuV]
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

*: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

4.8.4 Test data

***** CONDUCTED EMISSION at MAINS PORT *****
[3m Semi-anechoic chamber]

TUV SUD Japan Ltd. <<Data Sheet No.01>> 17 May,2019 01:53

Company Name	: Moritex Corporation	Standard	: FCC Part.15 Class B
EUT	: Handy Skin Sensor	Operator	: C.Kanno
Model No.	: HSS II	Temp,Hum,Atm	: 20.0[℃] 51.2[%]
Serial No.	: 9007C	Note1	:
Test mode	: WLAN_11b_Tx	Note2	:



Final Result

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.448	15.9	0.9	10.3	26.2	11.2	56.9	46.9	30.7	35.7
2	0.474	20.2	5.7	10.3	30.5	16.0	56.4	46.4	25.9	30.4
3	0.491	16.3	3.4	10.3	26.6	13.7	56.2	46.2	29.6	32.5
4	0.654	11.1	0.1	10.3	21.4	10.4	56.0	46.0	34.6	35.6
5	7.798	10.8	0.2	10.6	21.4	10.8	60.0	50.0	38.6	39.2
6	24.980	10.4	-1.3	11.2	21.6	9.9	60.0	50.0	38.4	40.1

--- L2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.451	19.3	6.4	10.3	29.6	16.7	56.9	46.9	27.3	30.2
2	0.469	26.0	12.4	10.3	36.3	22.7	56.5	46.5	20.2	23.8
3	0.499	14.0	4.7	10.3	24.3	15.0	56.0	46.0	31.7	31.0
4	0.944	9.1	0.3	10.3	19.4	10.6	56.0	46.0	36.6	35.4
5	3.495	6.7	-0.3	10.5	17.2	10.2	56.0	46.0	38.8	35.8
6	25.560	17.1	4.7	11.2	28.3	15.9	60.0	50.0	31.7	34.1

5 Antenna requirement

According to FCC section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
The antenna is a special antenna mounted inside of the EUT. Therefore, the EUT complies with the antenna requirement of FCC section 15.203.

6 Measurement Uncertainty

Expanded uncertainties stated are calculated with a coverage Factor k=2.
Please note that these results are not taken into account when measurement uncertainty considerations contained in ETSI TR 100 028 Parts 1 and 2 determining compliance or non-compliance with test result.

Test item	Measurement uncertainty
Conducted emission, AMN (9 kHz – 150 kHz)	±3.8 dB
Conducted emission, AMN (150 kHz – 30 MHz)	±3.3 dB
Radiated emission (9kHz – 30 MHz)	±3.1 dB
Radiated emission (30 MHz – 1000 MHz)	±4.9 dB
Radiated emission (1 GHz – 6 GHz)	±4.8 dB
Radiated emission (6 GHz – 18 GHz)	±5.1 dB
Radiated emission (18 GHz – 40 GHz)	±5.8 dB
Radio Frequency	$\pm 1.4 * 10^{-8}$
RF power, conducted	±0.6 dB
Temperature	±0.6 °C
Humidity	±1.2 %
Voltage (DC)	±0.4 %
Voltage (AC, <10kHz)	±0.2 %

Judge	Measured value and standard limit value
PASS	**Case1**  Even if it takes uncertainty into consideration, a standard limit value is fulfilled.
	Case2  Although measured value is in a standard limit value, a limit value won't be fulfilled if uncertainty is taken into consideration.
FAIL	**Case3**  Although measured value exceeds a standard limit value, a limit value will be fulfilled if uncertainty is taken into consideration.
	Case4  Even if it takes uncertainty into consideration, a standard limit value isn't fulfilled.

7 Laboratory Information

Testing was performed and the report was issued at:

TÜV SÜD Japan Ltd. Yonezawa Testing Center

Address: 5-4149-7 Hachimanpara, Yonezawa-shi, Yamagata, 992-1128 Japan
Phone: +81-238-28-2881
Fax: +81-238-28-2888

Accreditation and Registration
NVLAP
LAB CODE: 200306-0

VLAC
Accreditation No.: VLAC-013

BSMI
Laboratory Code: SL2-IN-E-6018, SL2-A1-E-6018

Innovation, Science and Economic Development Canada

Site number	Facility	Expiration date
4224A-4	3 m Semi-anechoic chamber	27-November-2020
4224A-5	10 m Semi-anechoic chamber No. 1	27-November-2020
4224A-6	10 m Semi-anechoic chamber No. 2	14-December-2019

VCCI Council

Registration number	Expiration date
A-0166	03-July-2019

Appendix A. Test Equipment

Antenna port conducted test

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
Spectrum analyzer	Agilent Technologies	E4440A	US44302655	31-Jul-2019	02-Jul-2018
Attenuator	Weinschel	56-10	J4180	31-Jul-2019	12-Jul-2018
Power meter	ROHDE&SCHWARZ	NRP2	103269	31-Aug-2019	01-Aug-2018
Power sensor	ROHDE&SCHWARZ	NRP-Z81	102467	31-Aug-2019	01-Aug-2018

Radiated emission

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100765	30-Sep-2019	20-Sep-2018
Spectrum analyzer	Agilent Technologies	E4447A	MY46180188	30-Apr-2020	16-Apr-2019
Spectrum analyzer	Agilent Technologies	E4440A	US40420937	31-Oct-2019	12-Oct-2018
Spectrum analyzer	ROHDE&SCHWARZ	FSV40	101731	31-Dec-2019	07-Dec-2018
Preamplifier	SONOMA	310	372170	30-Sep-2019	20-Sep-2018
Loop antenna	ROHDE&SCHWARZ	HFH2-Z2	100515	28-Mar-2020	07-Mar-2019
Attenuator	TDC	TAT-43B-06	N/A(S209)	31-Jul-2019	11-Jul-2018
Biconical antenna	Schwarzbeck	VHA9103/BBA9106	VHA91032155	31-Aug-2019	06-Aug-2018
Log periodic antenna	Schwarzbeck	UHALP9108A	0560	31-Aug-2019	06-Aug-2018
Attenuator	TAMAGAWA.ELEC	CFA-01/6dB	N/A(S465)	31-May-2020	17-May-2019
Attenuator	TAMAGAWA.ELEC	CFA-10/3dB	N/A(S503)	31-Jul-2019	11-Jul-2018
Preamplifier	TSJ	MLA-100M18-B02-40	1929118	31-Jan-2020	17-Jan-2019
Attenuator	AEROFLEX	26A-10	081217-08	31-Jan-2020	17-Jan-2019
Double ridged guide antenna	ETS LINDGREN	3117	00224193	31-Jan-2020	23-Jan-2019
Attenuator	Agilent Technologies	8491B	MY39268633	31-Mar-2020	08-Mar-2019
DRGH antenna	A.H.Systems Inc.	SAS-574	469	31-Aug-2019	24-Aug-2018
Preamplifier	TSJ	MLA-1840-B03-35	1240332	31-Aug-2019	24-Aug-2018
Notch filter	Micro-Tronics	BRM50702	045	31-May-2019	24-May-2018
Microwave cable	HUBER+SUHNER	SUCOFLEX104/9m	MY30037/4	31-Jan-2020	16-Jan-2019
		SUCOFLEX104/1m	my24610/4	31-Jan-2020	16-Jan-2019
		SUCOFLEX104/8m	SN MY30031/4	31-Jan-2020	16-Jan-2019
		SUCOFLEX104	MY32976/4	31-Jan-2020	16-Jan-2019
		SUCOFLEX104/1.5m	MY19309/4	31-Jan-2020	16-Jan-2019
		SUCOFLEX104/7m	41625/6	31-Jan-2020	16-Jan-2019
PC	DELL	DIMENSION E521	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.6.0	N/A	N/A
Absorber	RIKEN	PFP30	N/A	N/A	N/A
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-NSA)	31-May-2019	21-May-2018
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-SVSWR)	31-May-2019	22-May-2018

Conducted emission at mains port

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100765	30-Sep-2019	20-Sep-2018
Attenuator	HUBER+SUHNER	6810.01.A	N/A (S411)	31-Jan-2020	17-Jan-2019
Line impedance stabilization network	Kyoritsu Electrical Works, Ltd.	KNW-407F2	12-17-110-2	31-May-2020	16-May-2019
Coaxial cable	FUJIKURA	5D-2W/4m	N/A (S350)	31-Jan-2020	16-Jan-2019
Coaxial cable	FUJIKURA	5D-2W/1m	N/A (S193)	31-Jan-2020	16-Jan-2019
Coaxial cable	HUBER+SUHNER	RG214/U/10m	N/A (S194)	31-Jan-2020	16-Jan-2019
PC	DELL	DIMENSION	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/CE-AJ	0611193/V5.4.11	N/A	N/A

*: The calibrations of the above equipment are traceable to NIST or equivalent standards of the reference organizations.

Appendix B. Duty Cycle

[Plot & Calculation]

11b



Duty Cycle = Ton / (Ton + Toff) = 8410[µs] / (8410[µs] + 50[µs]) =99.41[%]

11g



Duty Cycle = Ton / (Ton + Toff) = 1398[µs] / (1398[µs] + 39[µs]) =97.29[%]

11n (HT20)



Duty Cycle = Ton / (Ton + Toff) = 1308[µs] / (1308[µs] + 39[µs]) =97.1[%]