



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20211001781E
Applicant: GANZHOU DEHUIDA TECHNOLOGY CO., LTD
Address of Applicant: Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province. P.R China.
Equipment Under Test (EUT)
EUT Name: LED Speaker
All Model No.: AAGRY100076371, AABLU100076371, AALAV100076371, AAYLW100076371
Test Model No.: AAGRY100076371
Brand Name: onn.
FCC ID: 2AO5X-BM1020
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-10-19
Date of Test: 2021-10-19 to 2021-10-28
Date of Issue: 2021-11-03
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou

(Lewis Zhou)

Reviewed By: Rock Huang

(Rock Huang)

Approved By: Jack ai

(Jack ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20211001781E	Rev.01	Initial report	2021-11-03

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 GENERAL DESCRIPTION OF BT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD
Address of Applicant:	Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province. P.R China.
Manufacturer:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD
Address of Manufacturer:	Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province. P.R China.
Factory:	GANZHOU DEHUIDA TECHNOLOGY CO., LTD
Address of Factory:	Dehuida Science and Technology Park, Huoyanshan Road, Anyuan District, Ganzhou City, Jiangxi Province. P.R China.

3.2 General Description of EUT

Product Name:	LED Speaker
Model No.:	AAGRY100076371, AABLU100076371, AALAV100076371, AAYLW100076371
Test Model No	AAGRY100076371
Trade Mark:	onn.
EUT Supports Radios application:	Bluetooth mode 2402-2480MHz
Hardware Version:	V5.3
Software Version:	D4A3
Sample Type:	☐ Mobile ☒ Portable ☐ Fix Location
EUT Power Supply:	lithium battery:DC3.7V 1500mAh, Charge by DC5.0V

3.3 General Description of BT

Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	V5.0	
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)	
Modulation Type:	GFSK, $\pi/4$ DQPSK	
Number of Channel:	79	
Transfer Rate:	1Mbps/2Mbps	
Hopping Channel Type:	Adaptive Frequency Hopping systems	
Test Software of EUT:	FCC Assist 1.0.0.2	
Antenna Type:	PCB antenna	
Antenna Gain:	BT	-0.58 dBi

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

1) For BT

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.730	0.5±1	1.5	1.413
Middle(2441MHz)	1.680	1.5±1	2.5	1.778
Highest(2480MHz)	2.060	2.0±1	3.0	1.995
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.290	1.0±1	2.0	1.585
Middle(2441MHz)	2.230	2.0±1	3.0	1.995
Highest(2480MHz)	2.530	2.5±1	3.5	2.239

Worst case: $\pi/4$ DQPSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.290	1.0±1	2.0	1.585	0.491	3.0
Middle (2441MHz)	2.230	2.0±1	3.0	1.995	0.623	
Highest (2480MHz)	2.530	2.5±1	3.5	2.239	0.705	
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20211001781E-01