FCC PART 15.247

TEST REPORT

For

Epik One America Corporation

170 Ocean Lane Dr. #705, Key Biscayne, FL 33149, United States

FCC ID: 2AO6ZRS550

Report Type:	**Product Type:**
Original Report	Smart phone

Report Number: RSZ180724002-00C

Report Date: 2018-08-22

Reviewed By: Rocky Kang, RF Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)
6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China
Tel: +86-755-33320018
Fax: +86-755-33320008
www.baclcorp.com.cn

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*".

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 7
EUT EXERCISE SOFTWARE 7
DUTY CYCLE 8
SUPPORT EQUIPMENT LIST AND DETAILS 10
EXTERNAL I/O CABLE 10
BLOCK DIAGRAM OF TEST SETUP 11
SUMMARY OF TEST RESULTS **12**
TEST EQUIPMENT LIST **13**
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE **15**
APPLICABLE STANDARD 15
FCC §15.203 - ANTENNA REQUIREMENT **16**
APPLICABLE STANDARD 16
ANTENNA CONNECTOR CONSTRUCTION 16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER SETUP 17
TEST PROCEDURE 17
CORRECTED FACTOR & MARGIN CALCULATION 18
TEST RESULTS SUMMARY 18
TEST DATA 18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **23**
APPLICABLE STANDARD 23
EUT SETUP 23
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 24
TEST PROCEDURE 24
CORRECTED AMPLITUDE & MARGIN CALCULATION 24
TEST RESULTS SUMMARY 24
TEST DATA 25
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH **37**
APPLICABLE STANDARD 37
TEST PROCEDURE 37
TEST DATA 37
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER **47**
APPLICABLE STANDARD 47

TEST PROCEDURE 47
TEST DATA 47

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....49

APPLICABLE STANDARD 49
TEST PROCEDURE 49
TEST DATA 49

FCC §15.247(e) - POWER SPECTRAL DENSITY 55

APPLICABLE STANDARD 55
TEST PROCEDURE 55
TEST DATA 55

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Epik One America Corporation's* product, model number: *RS550 (FCC ID: 2AO6ZRS550)* or the "EUT" in this report was a *Smart phone,* which was measured approximately: 155.2 mm (L) × 74.6 mm (W) × 11.9 mm (H), rated with input voltage: DC 3.8V from battery or DC 5.0V from adapter.

Adapter Information:
Model: TPA-46B050100UU
Input: AC 100-240V, 50/60Hz, 0.2A
Output: DC 5.0V, 1000 mA

**All measurement and test data in this report was gathered from production sample serial number: 180724002 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2018-07-24.*

Objective

This report is prepared on behalf of *Epik One America Corporation* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 22H&24E&27 PCE, Part 15.225 DXX and Part 15.407 NII submissions with FCC ID: 2AO6ZRS550.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 DTS Meas Guidance v04 .

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3℃
Humidity		±6%
Supply voltages		±0.4%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

BLE & Wi-Fi test in the engineer mode.

The worst case was performed as below:

Mode	Data rate	Power level		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	10	10	10
802.11g	6 Mbps	7	7	7
802.11n-HT20	MCS0	7	7	7
802.11n-HT40	MCS0	7	7	6
BLE	/	Default	Default	Default

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

Duty cycle

802.11b mode



Date: 3.AUG.2018 17:35:01

802.11g mode



Date: 5.AUG.2018 13:38:34

802.11n-HT20 Mode



Date: 3.AUG.2018 17:36:22

802.11n-HT40 Mode



Date: 3.AUG.2018 17:36:53

BLE Mode



Date: 3.AUG.2018 15:23:48

Mode	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting	10log(1/ Duty Cycle)
802.11b	100	-	-	10Hz	-
802.11g	100	-	-	10Hz	-
802.11n-HT20	100	-	-	10Hz	-
802.11n-HT40	100	-	-	10Hz	-
BLE	65	407	2.46	3kHz	1.87

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2017-12-21	2018-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-05-21	2018-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2018-05-12	2018-11-12
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2018-05-21	2019-05-21
HP	Amplifier	HP8447E	1937A01046	2018-05-21	2018-11-19
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2018-01-11	2019-01-11
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-04-01	2018-10-01
Ducommun technologies	RF Cable	104PEA	218124002	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	1	2018-05-21	2018-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-05-22	2018-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2016-11-18	2019-11-18
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2018-08-03	2019-08-03
Sinoscite	Notch Filter	BSF2402-2480MN-0898-001	N/A	2018-05-21	2019-05-21
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	P-Series Power Meter	N1912A	MY5000448	2018-01-02	2019-01-02
Agilent	Wideband Power Sensor	N1921A	MY54210016	2018-01-02	2019-01-02
WEINSCHEL	10dB Attenuator	5324	AU 3842	Each Time	
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-24	2018-12-24
Ducommun technologies	RF Cable	RG-214	3	Each Time	

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	6.0	3.98	5	1.25	3.0	Yes
Wi-Fi	2472	9.5	8.91	5	2.80	3.0	Yes

Result: No SAR test is required

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 1.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-11.

EUT operation mode: Transmitting

BLE Mode:

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.223610	46.9	19.7	56.0	9.1	QP
1.381270	46.8	19.8	56.0	9.2	QP
1.460070	46.7	19.8	56.0	9.3	QP
2.385250	52.0	19.9	56.0	4.0	QP
2.480890	51.5	19.9	56.0	4.5	QP
2.586610	50.8	19.9	56.0	5.2	QP
1.223610	32.5	19.7	46.0	13.5	Ave.
1.381270	32.4	19.8	46.0	13.6	Ave.
1.460070	31.7	19.8	46.0	14.3	Ave.
2.385250	37.7	19.9	46.0	8.3	Ave.
2.480890	35.1	19.9	46.0	10.9	Ave.
2.586610	36.7	19.9	46.0	9.3	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
1.211550	41.6	19.7	56.0	14.4	QP
1.444190	39.4	19.9	56.0	16.6	QP
1.522810	36.1	19.9	56.0	19.9	QP
2.279350	46.8	19.9	56.0	9.2	QP
2.504890	49.0	19.9	56.0	7.0	QP
27.234450	44.0	20.4	60.0	16.0	QP
1.211550	38.3	19.7	46.0	7.7	Ave.
1.444190	35.6	19.9	46.0	10.4	Ave.
1.522810	31.6	19.9	46.0	14.4	Ave.
2.279350	41.3	19.9	46.0	4.7	Ave.
2.504890	42.0	19.9	46.0	4.0	Ave.
27.234450	35.5	20.4	50.0	14.5	Ave.

Wi-Fi Mode:

AC 120 V/60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.158000	51.4	19.8	65.6	14.2	QP
1.377210	46.1	19.8	56.0	9.9	QP
1.456070	46.4	19.8	56.0	9.6	QP
2.378630	51.0	19.9	56.0	5.0	QP
2.519870	52.7	19.9	56.0	3.3	QP
2.610250	50.9	19.9	56.0	5.1	QP
0.158000	35.4	19.8	55.6	20.2	Ave.
1.377210	32.1	19.8	46.0	13.9	Ave.
1.456070	31.7	19.8	46.0	14.3	Ave.
2.378630	37.6	19.9	46.0	8.4	Ave.
2.519870	38.8	19.9	46.0	7.2	Ave.
2.610250	34.7	19.9	46.0	11.3	Ave.

AC 120V/ 60 Hz, Neutral:



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.995090	44.0	19.8	56.0	12.0	QP
1.215670	44.0	19.7	56.0	12.0	QP
1.377270	43.7	19.8	56.0	12.3	QP
1.546930	45.2	19.9	56.0	10.8	QP
2.378750	46.3	19.9	56.0	9.7	QP
2.469130	46.2	19.9	56.0	9.8	QP
0.995090	28.7	19.8	46.0	17.3	Ave.
1.215670	30.6	19.7	46.0	15.4	Ave.
1.377270	30.8	19.8	46.0	15.2	Ave.
1.546930	26.1	19.9	46.0	19.9	Ave.
2.378750	31.3	19.9	46.0	14.7	Ave.
2.469130	29.1	19.9	46.0	16.9	Ave.

Note:
1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
2) Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz Note 1	/	Average
	1MHz	＞1/T Note 2	/	Average

Note 1: when duty cycle is no less than 98%
Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-11.

EUT operation mode: Transmitting

BLE Mode:

30 MHz~1 GHz:



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.148401	26.96	151.0	V	0.0	-4.8	40.00	13.04
52.041750	24.16	162.0	V	140.0	-16.6	40.00	15.84
131.639500	27.16	188.0	H	85.0	-10.5	43.50	16.34
156.140250	24.68	239.0	H	96.0	-11.1	43.50	18.82
229.594000	15.46	178.0	H	240.0	-10.6	46.00	30.54
837.833375	23.74	160.0	H	92.0	0.1	46.00	22.26

1 GHz-25 GHz (BLE):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2402.00	60.28	PK	354	2.4	H	33.92	94.2	/	/
2402.00	59.19	Ave.	354	2.4	H	33.92	93.11	/	/
2402.00	58.16	PK	198	1.5	V	33.92	92.08	/	/
2402.00	56.91	Ave.	198	1.5	V	33.92	90.83	/	/
2389.00	26.96	PK	45	1.7	H	33.92	60.88	74	13.12
2389.00	13.24	Ave.	45	1.7	H	33.92	47.16	54	6.84
2479.43	27.35	PK	182	1.6	H	34.08	61.43	74	12.57
2479.43	13.25	Ave.	182	1.6	H	34.08	47.33	54	6.67
4804.00	42.24	PK	250	2.2	H	5.84	48.08	74	25.92
4804.00	28.56	Ave.	250	2.2	H	5.84	34.40	54	19.60
Middle Channel (2440 MHz)									
2440.00	61.85	PK	70	1.3	H	33.92	95.77	/	/
2440.00	60.46	Ave.	70	1.3	H	33.92	94.38	/	/
2440.00	60.21	PK	56	1.9	V	33.92	94.13	/	/
2440.00	58.92	Ave.	56	1.9	V	33.92	92.84	/	/
4880.00	42.53	PK	210	1.7	H	6.21	48.74	74	25.26
4880.00	28.30	Ave.	210	1.7	H	6.21	34.51	54	19.49
High Channel (2480 MHz)									
2480.00	63.03	PK	296	2.1	H	34.08	97.11	/	/
2480.00	61.76	Ave.	296	2.1	H	34.08	95.84	/	/
2480.00	60.52	PK	139	2.2	V	34.08	94.6	/	/
2480.00	59.12	Ave.	139	2.2	V	34.08	93.2	/	/
2389.00	27.16	PK	83	2.4	H	33.92	61.08	74	12.92
2389.00	13.21	Ave.	83	2.4	H	33.92	47.13	54	6.87
2483.50	27.19	PK	37	2.0	H	34.08	61.27	74	12.73
2483.50	13.35	Ave.	37	2.0	H	34.08	47.43	54	6.57
4960.00	42.81	PK	359	2.0	H	7.82	50.63	74	23.37
4960.00	28.71	Ave.	359	2.0	H	7.82	36.53	54	17.47

Wi-Fi Mode:

30 MHz~1 GHz:



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.165875	26.93	162.0	V	357.0	-4.8	40.00	13.07
35.881375	21.35	151.0	V	120.0	-8.2	40.00	18.65
136.219125	25.91	183.0	H	87.0	-10.7	43.50	17.59
153.822000	23.04	195.0	H	92.0	-11.1	43.50	20.46
231.095375	21.88	153.0	H	244.0	-10.6	46.00	24.12
834.358375	23.41	108.0	V	126.0	0.1	46.00	22.59

1 GHz-25 GHz (Wi-Fi):

802.11b Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	52.73	PK	89	1.8	H	33.92	86.65	/	/
2412.00	47.84	Ave.	89	1.8	H	33.92	81.76	/	/
2412.00	51.32	PK	325	1.5	V	33.92	85.24	/	/
2412.00	46.05	Ave.	325	1.5	V	33.92	79.97	/	/
2380.00	27.48	PK	43	2.5	H	33.92	61.40	74	12.60
2380.00	13.35	Ave.	43	2.5	H	33.92	47.27	54	6.73
2483.50	27.01	PK	1	2.4	H	34.08	61.09	74	12.91
2483.50	13.12	Ave.	1	2.4	H	34.08	47.20	54	6.80
4824.00	42.97	PK	247	2.5	H	5.84	48.81	74	25.19
4824.00	28.36	Ave.	247	2.5	H	5.84	34.20	54	19.80
Middle Channel (2442MHz)									
2442.00	54.15	PK	291	1.7	H	33.92	88.07	/	/
2442.00	49.02	Ave.	291	1.7	H	33.92	82.94	/	/
2442.00	52.26	PK	252	1.5	V	33.92	86.18	/	/
2442.00	46.97	Ave.	252	1.5	V	33.92	80.89	/	/
4884.00	42.56	PK	316	1.1	H	6.21	48.77	74	25.23
4884.00	28.48	Ave.	316	1.1	H	6.21	34.69	54	19.31
High Channel (2472 MHz)									
2472.00	55.29	PK	359	1.8	H	34.08	89.37	/	/
2472.00	49.85	Ave.	359	1.8	H	34.08	83.93	/	/
2472.00	53.11	PK	158	1.9	V	34.08	87.19	/	/
2472.00	47.92	Ave.	158	1.9	V	34.08	82.00	/	/
2390.00	27.24	PK	345	1.9	H	33.92	61.16	74	12.84
2390.00	13.36	Ave.	345	1.9	H	33.92	47.28	54	6.72
2483.50	27.62	PK	71	1.0	H	34.08	61.70	74	12.30
2483.50	13.24	Ave.	71	1.0	H	34.08	47.32	54	6.68
4944.00	42.83	PK	310	1.4	H	6.21	49.04	74	24.96
4944.00	28.71	Ave.	310	1.4	H	6.21	34.92	54	19.08

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	54.37	PK	272	1.7	H	33.92	88.29	/	/
2412.00	42.96	Ave.	272	1.7	H	33.92	76.88	/	/
2412.00	51.87	PK	138	1.1	V	33.92	85.79	/	/
2412.00	40.54	Ave.	138	1.1	V	33.92	74.46	/	/
2358.00	27.37	PK	76	1.2	H	33.92	61.29	74	12.71
2358.00	13.36	Ave.	76	1.2	H	33.92	47.28	54	6.72
2483.50	26.98	PK	354	1.4	H	34.08	61.06	74	12.94
2483.50	13.14	Ave.	354	1.4	H	34.08	47.22	54	6.78
4824.00	42.76	PK	297	2.2	H	5.84	48.60	74	25.40
4824.00	28.59	Ave.	297	2.2	H	5.84	34.43	54	19.57
Middle Channel (2442MHz)									
2442.00	54.67	PK	311	1.3	H	33.92	88.59	/	/
2442.00	43.52	Ave.	311	1.3	H	33.92	77.44	/	/
2442.00	51.96	PK	359	2.1	V	33.92	85.88	/	/
2442.00	40.85	Ave.	359	2.1	V	33.92	74.77	/	/
4884.00	42.51	PK	29	2.4	H	6.21	48.72	74	25.28
4884.00	28.40	Ave.	29	2.4	H	6.21	34.61	54	19.39
High Channel (2472 MHz)									
2472.00	55.58	PK	138	2.3	H	34.08	89.66	/	/
2472.00	44.23	Ave.	138	2.3	H	34.08	78.31	/	/
2472.00	52.84	PK	148	1.5	V	34.08	86.92	/	/
2472.00	41.59	Ave.	148	1.5	V	34.08	75.67	/	/
2390.00	27.15	PK	357	2.0	H	33.92	61.07	74	12.93
2390.00	13.36	Ave.	357	2.0	H	33.92	47.28	54	6.72
2483.50	27.34	PK	233	1.5	H	34.08	61.42	74	12.58
2483.50	13.25	Ave.	233	1.5	H	34.08	47.33	54	6.67
4944.00	43.89	PK	306	1.9	H	6.21	50.10	74	23.90
4944.00	28.81	Ave.	306	1.9	H	6.21	35.02	54	18.98

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2412.00	54.22	PK	270	1.2	H	33.92	88.14	/	/
2412.00	42.75	Ave.	270	1.2	H	33.92	76.67	/	/
2412.00	51.46	PK	41	2.0	V	33.92	85.38	/	/
2412.00	40.31	Ave.	41	2.0	V	33.92	74.23	/	/
2390.00	27.05	PK	335	2.3	H	33.92	60.97	74	13.03
2390.00	13.16	Ave.	335	2.3	H	33.92	47.08	54	6.92
2487.00	26.95	PK	149	2.3	H	34.08	61.03	74	12.97
2487.00	13.25	Ave.	149	2.3	H	34.08	47.33	54	6.67
4824.00	42.95	PK	355	1.7	H	5.84	48.79	74	25.21
4824.00	28.67	Ave.	355	1.7	H	5.84	34.51	54	19.49
Middle Channel (2442MHz)									
2442.00	54.62	PK	50	1.7	H	33.92	88.54	/	/
2442.00	43.26	Ave.	50	1.7	H	33.92	77.18	/	/
2442.00	52.17	PK	138	2.2	V	33.92	86.09	/	/
2442.00	41.28	Ave.	138	2.2	V	33.92	75.20	/	/
4884.00	42.59	PK	175	1.3	H	6.21	48.80	74	25.20
4884.00	28.37	Ave.	175	1.3	H	6.21	34.58	54	19.42
High Channel (2472 MHz)									
2472.00	54.96	PK	301	1.3	H	34.08	89.04	/	/
2472.00	43.65	Ave.	301	1.3	H	34.08	77.73	/	/
2472.00	52.58	PK	69	1.7	V	34.08	86.66	/	/
2472.00	41.46	Ave.	69	1.7	V	34.08	75.54	/	/
2390.00	27.25	PK	211	2.4	H	33.92	61.17	74	12.83
2390.00	13.20	Ave.	211	2.4	H	33.92	47.12	54	6.88
2487.00	27.28	PK	139	1.4	H	34.08	61.36	74	12.64
2487.00	13.14	Ave.	139	1.4	H	34.08	47.22	54	6.78
4944.00	42.78	PK	311	1.7	H	6.21	48.99	74	25.01
4944.00	28.50	Ave.	311	1.7	H	6.21	34.71	54	19.29

802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2422 MHz)									
2422.00	54.08	PK	17	1.7	H	33.92	88.00	/	/
2422.00	42.87	Ave.	17	1.7	H	33.92	76.79	/	/
2422.00	51.94	PK	345	1.2	V	33.92	85.86	/	/
2422.00	40.67	Ave.	345	1.2	V	33.92	74.59	/	/
2389.00	26.98	PK	288	2.3	H	33.92	60.90	74	13.10
2389.00	13.14	Ave.	288	2.3	H	33.92	47.06	54	6.94
2489.00	27.06	PK	284	1.2	H	34.08	61.14	74	12.86
2489.00	13.14	Ave.	284	1.2	H	34.08	47.22	54	6.78
4844.00	42.18	PK	71	1.2	H	5.84	48.02	74	25.98
4844.00	28.50	Ave.	71	1.2	H	5.84	34.34	54	19.66
Middle Channel (2442 MHz)									
2442.00	54.38	PK	155	1.1	H	33.92	88.30	/	/
2442.00	42.67	Ave.	155	1.1	H	33.92	76.59	/	/
2442.00	52.36	PK	116	2.5	V	33.92	86.28	/	/
2442.00	41.15	Ave.	116	2.5	V	33.92	75.07	/	/
4884.00	42.67	PK	202	1.8	H	6.21	48.88	74	25.12
4884.00	28.41	Ave.	202	1.8	H	6.21	34.62	54	19.38
High Channel (2462 MHz)									
2462.00	53.27	PK	107	2.3	H	34.08	87.35	/	/
2462.00	41.56	Ave.	107	2.3	H	34.08	75.64	/	/
2462.00	51.46	PK	277	1.6	V	34.08	85.54	/	/
2462.00	40.13	Ave.	277	1.6	V	34.08	74.21	/	/
2390.00	27.15	PK	165	1.9	H	33.92	61.07	74	12.93
2390.00	13.24	Ave.	165	1.9	H	33.92	47.16	54	6.84
2390.00	27.25	PK	327	1.0	H	33.92	61.17	74	12.83
2390.00	13.24	Ave.	327	1.0	H	33.92	47.16	54	6.84
4924.00	42.02	PK	3	1.4	H	6.21	48.23	74	25.77
4924.00	27.95	Ave.	3	1.4	H	6.21	34.16	54	19.84

Note:
Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude
The other spurious emission which is 20dB to the limit was not recorded.
And for the pre-scan is performed with the 2400-2483.5MHz band filter.

Pre-scan with 802.11b Mode, High channel
Horizontal





Vertical


Marker 1 [T1]
Ref Lvl
97 dBµV
61.18 dBµV
15.34268537 GHz
RBW 1 MHz
VBW 3 MHz
SWT 98 ms
RF Att 0 dB
Unit dBµV
▼1 [T1] 61.18 dBµV
15.34268537 GHz
▽2 [T1] 49.48 dBµV
D1 74 dBµV
1MAX
1MA
TDF
Start 1 GHz
1.7 GHz/
Stop 18 GHz
Date: 11.AUG.2018 17:02:03


Marker 1 [T1]
Ref Lvl
97 dBµV
65.73 dBµV
24.87374749 GHz
RBW 1 MHz
VBW 3 MHz
SWT 40 ms
RF Att 0 dB
Unit dBµV
▼1 [T1] 65.73 dBµV
24.87374749 GHz
D1 74 dBµV
1MAX
1MA
TDF
Start 18 GHz
700 MHz/
Stop 25 GHz
Date: 11.AUG.2018 17:51:07

Pre-scan for Average
Horizontal





Vertical



Date: 11.AUG.2018 17:11:09



Date: 11.AUG.2018 17:57:17

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-03.

Test Result: Pass.

Please refer to the following table and plots.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	9.66	≥500
Middle	2442	9.66	≥500
High	2472	10.14	≥500
802.11g			
Low	2412	16.66	≥500
Middle	2442	16.53	≥500
High	2472	16.69	≥500
802.11n-HT20 mode			
Low	2412	17.85	≥500
Middle	2442	17.79	≥500
High	2472	17.88	≥500
802.11n-HT40 mode			
Low	2422	36.58	≥500
Middle	2442	36.59	≥500
High	2462	36.51	≥500

Channel	Frequency (MHz)	6 dB Emission Bandwidth(MHz)	Limit (kHz)
BLE mode			
Low	2402	0.713	≥500
Middle	2440	0.723	≥500
High	2480	0.715	≥500

802.11b Low Channel



Date: 3.AUG.2018 16:41:41

802.11b Middle Channel



Date: 3.AUG.2018 16:43:26

802.11b High Channel



Date: 3.AUG.2018 16:44:32

802.11g Low Channel



Date: 3.AUG.2018 16:49:12

802.11g Middle Channel



Date: 3.AUG.2018 16:48:08

802.11g High Channel



Date: 3.AUG.2018 16:46:44

802.11n-HT20 Low Channel



Date: 3.AUG.2018 16:50:36

802.11n-HT20 Middle Channel



Date: 3.AUG.2018 16:51:42

802.11n-HT20 High Channel



Date: 3.AUG.2018 16:52:42

802.11n-HT40 Low Channel



Date: 3.AUG.2018 16:58:16

802.11n-HT40 Middle Channel



Date: 3.AUG.2018 16:56:45

802.11n-HT40 High Channel



Date: 3.AUG.2018 16:54:41

BLE Low Channel



Date: 3.AUG.2018 14:57:44

BLE Middle Channel



Date: 3.AUG.2018 14:56:06

BLE High Channel



Date: 3.AUG.2018 14:54:27

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-03.

EUT operation mode: Transmitting

Wi-Fi mode

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b				
Low	2412	11.97	8.65	30
Middle	2442	11.43	8.99	30
High	2472	11.25	8.58	30
802.11g				
Low	2412	14.72	8.76	30
Middle	2442	14.71	8.78	30
High	2472	14.58	8.96	30
802.11n-HT20				
Low	2412	14.88	8.80	30
Middle	2442	14.96	8.88	30
High	2472	14.99	9.01	30
802.11n-HT40				
Low	2422	14.69	8.73	30
Middle	2442	14.99	8.90	30
High	2462	14.27	8.55	30

BLE mode

Channel	Frequency (MHz)	Max Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	5.85	30	Pass
Middle	2440	5.96	30	Pass
High	2480	4.58	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-03 and 2018-08-05.

EUT operation mode: Transmitting

Test Result: Compliance

Please refer to the following plots.

802.11b: Band Edge, Left Side



Date: 5.AUG.2018 13:44:23

802.11b: Band Edge, Right Side



Date: 5.AUG.2018 13:46:37

802.11g: Band Edge, Left Side



Date: 5.AUG.2018 13:50:52

802.11g: Band Edge, Right Side



Date: 5.AUG.2018 13:49:48

802.11n-HT20: Band Edge, Left Side



Date: 5.AUG.2018 13:51:59

802.11n-HT20: Band Edge, Right Side



Date: 5.AUG.2018 13:53:01

802.11n-HT40: Band Edge, Left Side



Date: 5.AUG.2018 13:55:31

802.11n-HT40: Band Edge, Right Side



Date: 5.AUG.2018 13:54:43

BLE: Band Edge, Left Side



Date: 3.AUG.2018 15:02:40

BLE: Band Edge, Right Side



Date: 3.AUG.2018 15:05:44

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: 3kHz≤ RBW≤100 kHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2018-08-03.

EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-20.66	≤8
Middle	2442	-20.42	≤8
High	2472	-21.03	≤8
802.11g mode			
Low	2412	-21.47	≤8
Middle	2442	-21.73	≤8
High	2472	-22.10	≤8
802.11n-HT20 mode			
Low	2412	-21.88	≤8
Middle	2442	-21.45	≤8
High	2472	-20.89	≤8
802.11n-HT40 mode			
Low	2422	-23.35	≤8
Middle	2442	-22.92	≤8
High	2462	-23.30	≤8
BLE mode			
Low	2402	-9.61	≤8
Middle	2440	-9.70	≤8
High	2480	-10.84	≤8

Power Spectral Density, 802.11b Low Channel



Date: 3.AUG.2018 17:09:06

Power Spectral Density, 802.11b Middle Channel



Date: 3.AUG.2018 17:10:27

Power Spectral Density, 802.11b High Channel



Date: 3.AUG.2018 17:12:21

Power Spectral Density, 802.11g Low Channel



Date: 3.AUG.2018 17:15:55

Power Spectral Density, 802.11g Middle Channel



Date: 3.AUG.2018 17:14:53

Power Spectral Density, 802.11g High Channel



Date: 3.AUG.2018 17:13:32

Power Spectral Density, 802.11n-HT20 Low Channel



Date: 3.AUG.2018 17:18:01

Power Spectral Density, 802.11n-HT20 Middle Channel



Date: 3.AUG.2018 17:20:14

Power Spectral Density, 802.11n-HT20 High Channel



Date: 3.AUG.2018 17:21:38

Power Spectral Density, 802.11n-HT40 Low Channel



Date: 3.AUG.2018 17:02:04

Power Spectral Density, 802.11n-HT40 Middle Channel



Date: 3.AUG.2018 17:07:03

Power Spectral Density, 802.11n-HT40 High Channel



Date: 3.AUG.2018 17:05:14

Power Spectral Density, BLE Low Channel



Date: 3.AUG.2018 15:18:50

Power Spectral Density, BLE Middle Channel



Date: 3.AUG.2018 15:19:39

Power Spectral Density, BLE High Channel



Date: 3.AUG.2018 15:16:02

******* END OF REPORT *******