



FCC PART 27
FCC PART 22H, PART 24E
TEST REPORT

For

Epik One America Corporation

801 Brickell Ave. #900, Miami, FL, United States 33131

FCC ID: 2AO6ZTX800

Report Type: Original Report	Product Type: 4G LTE Tablet
Report Number: <u>RSZ190827005-00D</u>	
Report Date: <u>2019-09-10</u>	
Nancy Wang	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
FCC §1.1307(B) & §2.1093 - RF EXPOSURE INFORMATION.....	10
APPLICABLE STANDARD	10
TEST RESULT	10
FCC §2.1047 - MODULATION CHARACTERISTIC	11
FCC §2.1046, §22.913 (A) & §24.232 (C); §27.50 (D) (H) - RF OUTPUT POWER	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST DATA	12
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	67
APPLICABLE STANDARD	67
TEST PROCEDURE	67
TEST DATA	67
FCC §2.1053; §22.917 (A); §24.238 (A); §27.53 SPURIOUS RADIATED EMISSIONS	93
APPLICABLE STANDARD	93
TEST PROCEDURE	93
TEST DATA	93
FCC §22.917 (A); §24.238 (A); §27.53 (H)(M) - BAND EDGES	97
APPLICABLE STANDARD	97
TEST PROCEDURE	97
TEST DATA	97

FCC § 2.1055; § 22.355; § 24.235; §27.54 - FREQUENCY STABILITY148
APPLICABLE STANDARD148
TEST PROCEDURE148
TEST DATA149

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	4G LTE Tablet
Model	TX800
Frequency Range	Cellular: 824-849 MHz PCS: 1850-1910 MHz WCDMA B2/LTE B2: 1850-1910 MHz WCDMA B5/LTE B5: 824-849 MHz LTE B4: 1710- 1755 MHz LTE B7: 2500-2570 MHz
Transmit Power	GSM850: 32.68dBm(GMSK), 27.62dBm(8PSK) PCS1900: 29.45dBm(GMSK), 26.56dBm(8PSK) WCDMA Band 2: 22.45dBm WCDMA Band 5: 22.62dBm LTE Band 2: 22.65dBm LTE Band 4: 22.65dBm LTE Band 5: 22.67dBm LTE Band 7: 22.59dBm
Modulation Technique	2G: GMSK,8PSK 3G: BPSK, QPSK, 16QAM 4G: QPSK, 16QAM
Antenna Specification	2G/3G/4G: FPC Antennas
Voltage Range	DC 3.7V from battery or DC 5.0V from Adapter
Date of Test	2019-08-29 to 2019-09-05
Sample serial number	190827005
Received date	2019-08-27
Sample/EUT Status	Good condition
Adapter information	Model:GLY-G19UA-050150-540A Input: AC 100-240V, 50/60Hz,0.3A Output: DC 5.0V, 1500mA

Objective

This test report is prepared on behalf of *Epik One America Corporation* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E and Subpart 27 of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 15.247 DTS submissions with FCC ID: 2AO6ZTX800.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		±0.73dB
Unwanted Emission, conducted		±1.6dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-116218-UY
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 1.1307 , §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53(h) (m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

Note: * Please refer to SAR report released by BACL, report number: RSZ190827005-SA.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017-12-22	2020-12-21
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019-07-22	2020-07-21
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Agilent	Signal Generator	N5183A	MY51040755	2018-12-03	2019-12-03
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2019-07-09	2020-07-08
COM-POWER	Dipole Antenna	AD-100	41000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-03	2016-11-18	2019-11-18
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Unknown	High Pass filter	2.8GHz	Unknown	2019-04-20	2020-04-20
Unknown	High Pass filter	1.3GHz	Unknown	2019-04-20	2020-04-20

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2019-03-02	2020-03-01
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2019-01-05	2020-01-05
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
Fluke	Digital Multimeter	287	19000011	2019-04-12	2020-04-12
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2019-01-15	2020-01-15
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2019-07-09	2020-07-09
Wainwright Germany	Band Reject Filter	WRCG1850/1910-1835/1925-40/8SS	22	2019-03-02	2020-03-01
Wainwright Germany	Band Reject Filter	WRCG1786-1689/1806	2	2019-03-02	2020-03-01
Chengdu Oulitong	Band Reject Filter	OBSF-2500-2570-S	OE01601523	2019-03-02	2020-03-01
Unknown	High Pass filter	1.3GHz	Unknown	2019-04-20	2020-04-20
Ducommun Technologies	RF Cable	RG-214	3	Each Time	
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2018-11-12	2019-11-12
WEINSCHTEL	3dB Attenuator	6231	666	Each Time	
Unknown	Power Splitter	1620	129	Each Time	

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ190827005-SA.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC §2.1047(d), Part 22H & 24E & 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50 (d) (h) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.


According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz.

According to §27.50(h), the maximum EIRP must not exceed 2Watts (33dBm) for 2500-2570MHz.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Kieron Luo on 2019-09-05.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.56	38.45
	190	836.6	32.51	38.45
	251	848.8	32.48	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.57	29.67	28.16	26.89	38.45
	190	836.6	32.68	29.49	28.21	26.84	38.45
	251	848.8	32.49	29.57	28.13	26.94	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	27.36	25.12	23.86	21.85	38.45
	190	836.6	27.34	25.26	23.89	21.89	38.45
	251	848.8	27.62	25.10	23.96	21.92	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.62	22.43	22.51
		HSDPA	1	21.48	21.53	21.57
			2	21.37	21.52	21.53
			3	21.29	21.59	21.49
			4	21.37	21.67	21.62
			5	21.56	21.58	21.54
		HSUPA	1	21.42	21.24	21.41
			2	21.51	21.38	21.28
			3	21.49	21.23	21.51
			4	21.61	21.30	21.43
			5	21.47	21.37	21.52

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.38	33
	661	1880.0	29.42	33
	810	1909.8	29.45	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	29.12	27.13	25.87	23.86	33
	661	1880.0	29.02	27.28	25.91	23.89	33
	810	1909.8	29.05	27.16	25.96	23.79	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	26.48	24.52	22.15	20.89	33
	661	1880.0	26.54	24.48	22.34	20.92	33
	810	1909.8	26.56	24.67	22.21	20.85	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.34	22.45	22.39
		HSDPA	1	21.54	21.62	21.58
			2	21.52	21.52	21.62
			3	21.48	21.34	21.74
			4	21.62	21.59	21.84
			5	21.58	21.48	21.59
		HSUPA	1	21.48	21.62	21.53
			2	21.52	21.62	21.49
			3	21.53	21.46	21.52
			4	21.42	21.52	21.49
			5	21.39	21.51	21.46

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	1.39	13
	Middle	1.46	13
	High	1.34	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	1.34	13
	Middle	1.52	13
	High	1.41	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.62	13
	Middle	3.43	13
	High	3.34	13
HSDPA (16QAM)	Low	3.84	13
	Middle	3.62	13
	High	3.45	13
HSUPA (BPSK)	Low	2.96	13
	Middle	3.26	13
	High	3.19	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	1.62	13
	Middle	1.41	13
	High	1.52	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	1.24	13
	Middle	1.37	13
	High	1.53	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.63	13
	Middle	3.38	13
	High	3.45	13
HSDPA (16QAM)	Low	3.48	13
	Middle	3.68	13
	High	3.82	13
HSUPA (BPSK)	Low	3.76	13
	Middle	3.91	13
	High	3.86	13

**Radiated Power
GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dBd/dBi)			
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	85.07	7	1.6	H	23.1	0.28	0.0	22.82	38.45	15.63
836.6	80.57	315	2.5	V	20.6	0.28	0.0	20.32	38.45	18.13
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	82.32	289	1.8	H	12.6	1.30	9.40	20.70	33	12.30
1880.00	80.18	69	2.3	V	10.3	1.30	9.40	18.40	33	14.60

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dBd/dBi)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	80.58	115	1.5	H	18.6	0.28	0.0	18.32	38.45	20.13
836.6	76.41	356	2.4	V	16.4	0.28	0.0	16.12	38.45	22.33
EIRP, PCS Band (Part 24E), Middle Channel										
1880.00	80.34	116	1.3	H	10.7	1.30	9.40	18.80	33	14.20
1880.00	75.52	26	1.8	V	5.6	1.30	9.40	13.70	33	19.30

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dBd/dBi)			
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	78.75	262	2.4	H	16.8	0.28	0.0	16.52	38.45	16.93
836.6	73.53	250	2.2	V	13.5	0.28	0.0	13.22	38.45	19.23
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.00	77.24	197	1.5	H	7.6	1.30	9.40	15.70	33	13.30
1880.00	74.34	232	1.3	V	4.4	1.30	9.40	12.50	33	15.70

Note:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

dBd is for the ERP, dBi is for EIRP.

LTE Band 2:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	21.93	22.16	21.68
		RB Size=1, RB Offset=2	22.02	21.78	22.12
		RB Size=1, RB Offset=5	21.62	22.02	21.31
		RB Size=3, RB Offset=0	21.29	21.55	21.7
		RB Size=3, RB Offset=1	21.64	22.11	21.86
		RB Size=3, RB Offset=2	21.78	21.57	22.14
		RB Size=6, RB Offset=0	21.12	21.41	21.21
	16QAM	RB Size=1, RB Offset=0	21.91	22.21	22.35
		RB Size=1, RB Offset=2	21.68	21.63	21.86
		RB Size=1, RB Offset=5	22.27	21.74	21.69
		RB Size=3, RB Offset=0	21.73	21.41	21.48
		RB Size=3, RB Offset=1	21.64	22.45	22.45
		RB Size=3, RB Offset=2	22.33	21.79	22.30
		RB Size=6, RB Offset=0	22.24	21.67	22.22
3.0	QPSK	RB Size=1, RB Offset=0	21.89	21.59	21.62
		RB Size=1, RB Offset=7	21.63	22.04	22.04
		RB Size=1, RB Offset=14	22.15	21.78	22.41
		RB Size=8, RB Offset=0	22.21	22.21	22.03
		RB Size=8, RB Offset=4	21.95	21.35	22.03
		RB Size=8, RB Offset=7	21.60	21.68	22.32
		RB Size=15, RB Offset=0	22.44	22.04	21.62
	16QAM	RB Size=1, RB Offset=0	22.65	22.51	21.95
		RB Size=1, RB Offset=7	22.36	22.45	21.82
		RB Size=1, RB Offset=14	22.14	21.87	21.9
		RB Size=8, RB Offset=0	21.54	21.42	21.86
		RB Size=8, RB Offset=4	21.70	22.22	21.84
		RB Size=8, RB Offset=7	21.49	21.7	22.02
		RB Size=15, RB Offset=0	21.70	22.17	22.16

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	21.88	21.73	21.92
		RB Size=1, RB Offset=12	22.02	22.31	22.16
		RB Size=1, RB Offset=24	21.29	21.19	21.62
		RB Size=12, RB Offset=0	21.26	21.77	22.07
		RB Size=12, RB Offset=6	22.16	22.47	22.07
		RB Size=12, RB Offset=11	21.84	22.43	22.32
		RB Size=25, RB Offset=0	22.03	21.36	22.09
	16QAM	RB Size=1, RB Offset=0	22.20	21.59	21.60
		RB Size=1, RB Offset=12	21.66	22.04	21.85
		RB Size=1, RB Offset=24	22.21	21.52	21.99
		RB Size=12, RB Offset=0	21.52	22.01	22.07
		RB Size=12, RB Offset=6	22.04	21.69	21.50
		RB Size=12, RB Offset=11	21.99	22.39	22.19
		RB Size=25, RB Offset=0	21.65	21.47	21.64
10.0	QPSK	RB Size=1, RB Offset=0	22.05	21.86	21.48
		RB Size=1, RB Offset=24	22.15	21.72	22.28
		RB Size=1, RB Offset=49	22.12	22.45	22.04
		RB Size=25, RB Offset=0	22.35	22.4	22.16
		RB Size=25, RB Offset=12	21.50	21.32	21.88
		RB Size=25, RB Offset=24	22.19	21.85	21.81
		RB Size=50, RB Offset=0	21.63	22.25	22.23
	16QAM	RB Size=1, RB Offset=0	22.61	21.82	22.47
		RB Size=1, RB Offset=24	22.50	21.91	22.51
		RB Size=1, RB Offset=49	21.74	21.68	21.99
		RB Size=25, RB Offset=0	21.74	21.55	22.27
		RB Size=25, RB Offset=12	22.42	21.92	22.04
		RB Size=25, RB Offset=24	22.13	21.55	21.72
		RB Size=50, RB Offset=0	22.05	21.30	21.29

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	21.64	21.62	21.59
		RB Size=1, RB Offset=37	22.17	21.56	21.6
		RB Size=1, RB Offset=74	21.73	21.18	21.32
		RB Size=36, RB Offset=0	21.14	21.34	21.39
		RB Size=36, RB Offset=18	22.04	21.75	21.67
		RB Size=36, RB Offset=37	22.09	21.71	21.75
		RB Size=75, RB Offset=0	21.50	21.36	21.35
	16QAM	RB Size=1, RB Offset=0	22.43	21.70	21.79
		RB Size=1, RB Offset=37	21.40	21.48	21.32
		RB Size=1, RB Offset=74	22.36	21.67	21.48
		RB Size=36, RB Offset=0	21.65	21.37	21.31
		RB Size=36, RB Offset=18	21.8	21.66	21.58
		RB Size=36, RB Offset=37	21.99	21.62	21.64
		RB Size=75, RB Offset=0	21.84	21.57	21.33
20.0	QPSK	RB Size=1, RB Offset=0	21.57	21.42	21.58
		RB Size=1, RB Offset=49	21.72	21.64	21.76
		RB Size=1, RB Offset=99	22.35	21.68	21.81
		RB Size=50, RB Offset=0	22.60	21.74	21.85
		RB Size=50, RB Offset=24	21.67	21.42	21.46
		RB Size=50, RB Offset=49	22.23	21.39	21.62
		RB Size=100, RB Offset=0	21.61	21.69	21.46
	16QAM	RB Size=1, RB Offset=0	22.10	21.94	21.84
		RB Size=1, RB Offset=49	22.37	21.72	21.92
		RB Size=1, RB Offset=99	22.04	21.95	21.71
		RB Size=50, RB Offset=0	21.46	21.6	21.42
		RB Size=50, RB Offset=24	21.84	21.88	21.85
		RB Size=50, RB Offset=49	21.31	21.29	21.5
		RB Size=100, RB Offset=0	21.86	21.29	21.44

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.73	13	Pass
QPSK (100RB Size)	4.44	13	Pass
16QAM (1RB Size)	4.79	13	Pass
16QAM (100RB Size)	4.52	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	77.52	94	2.3	H	7.8	1.30	9.40	15.90	33
1880.00	74.16	162	2.1	V	4.3	1.30	9.40	12.40	33
3 MHz Bandwidth									
1880.00	77.12	57	1.4	H	7.4	1.30	9.40	15.50	33
1880.00	74.03	173	2.2	V	4.1	1.30	9.40	12.20	33
5 MHz Bandwidth									
1880.00	76.72	32	2.2	H	7.0	1.30	9.40	15.10	33
1880.00	73.76	28	1.1	V	3.9	1.30	9.40	12.00	33
10 MHz Bandwidth									
1880.00	76.51	93	2.0	H	6.8	1.30	9.40	14.90	33
1880.00	73.43	72	1.7	V	3.5	1.30	9.40	11.60	33
15 MHz Bandwidth									
1880.00	76.24	312	1.7	H	6.6	1.30	9.40	14.70	33
1880.00	73.23	34	1.3	V	3.3	1.30	9.40	11.40	33
20 MHz Bandwidth									
1880.00	76.02	265	1.9	H	6.3	1.30	9.40	14.40	33
1880.00	73.03	9	2.5	V	3.1	1.30	9.40	11.20	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	77.68	269	1.9	H	8.0	1.30	9.40	16.10	33
1880.00	74.78	323	1.9	V	4.9	1.30	9.40	13.00	33
3 MHz Bandwidth									
1880.00	77.25	52	1.9	H	7.6	1.30	9.40	15.70	33
1880.00	74.13	171	1.8	V	4.2	1.30	9.40	12.30	33
5 MHz Bandwidth									
1880.00	76.93	34	1.7	H	7.3	1.30	9.40	15.40	33
1880.00	73.86	28	1.9	V	4.0	1.30	9.40	12.10	33
10 MHz Bandwidth									
1880.00	76.72	208	1.4	H	7.0	1.30	9.40	15.10	33
1880.00	73.68	280	2.2	V	3.8	1.30	9.40	11.90	33
15 MHz Bandwidth									
1880.00	76.46	184	1.4	H	6.8	1.30	9.40	14.90	33
1880.00	73.43	251	1.7	V	3.5	1.30	9.40	11.60	33
20 MHz Bandwidth									
1880.00	76.17	145	2.3	H	6.5	1.30	9.40	14.60	33
1880.00	73.13	191	1.5	V	3.2	1.30	9.40	11.30	33

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	21.53	21.51	21.64
		RB Size=1, RB Offset=2	21.99	21.72	21.56
		RB Size=1, RB Offset=5	21.67	21.34	21.30
		RB Size=3, RB Offset=0	21.52	21.42	21.32
		RB Size=3, RB Offset=1	22.51	21.82	21.75
		RB Size=3, RB Offset=2	22.03	21.64	21.66
		RB Size=6, RB Offset=0	22.01	21.14	21.25
	16QAM	RB Size=1, RB Offset=0	21.71	21.68	21.70
		RB Size=1, RB Offset=2	21.82	21.50	21.31
		RB Size=1, RB Offset=5	22.08	21.70	21.64
		RB Size=3, RB Offset=0	21.54	21.37	21.15
		RB Size=3, RB Offset=1	21.95	21.72	21.47
		RB Size=3, RB Offset=2	22.02	21.76	21.62
		RB Size=6, RB Offset=0	21.46	21.45	21.33
3.0	QPSK	RB Size=1, RB Offset=0	22.04	21.51	21.58
		RB Size=1, RB Offset=7	21.94	21.86	21.82
		RB Size=1, RB Offset=14	22.41	21.88	21.66
		RB Size=8, RB Offset=0	21.69	21.83	21.93
		RB Size=8, RB Offset=4	21.45	21.46	21.42
		RB Size=8, RB Offset=7	21.53	21.60	21.56
		RB Size=15, RB Offset=0	22.28	21.46	21.55
	16QAM	RB Size=1, RB Offset=0	22.39	21.85	21.73
		RB Size=1, RB Offset=7	22.32	21.85	21.94
		RB Size=1, RB Offset=14	22.30	21.91	21.96
		RB Size=8, RB Offset=0	21.50	21.48	21.59
		RB Size=8, RB Offset=4	22.08	21.69	21.69
		RB Size=8, RB Offset=7	21.22	21.29	21.39
		RB Size=15, RB Offset=0	21.85	21.42	21.47

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	21.59	21.45	21.55
		RB Size=1, RB Offset=12	22.21	21.51	21.73
		RB Size=1, RB Offset=24	21.98	21.31	21.41
		RB Size=12, RB Offset=0	21.68	21.32	21.29
		RB Size=12, RB Offset=6	21.72	21.83	21.74
		RB Size=12, RB Offset=11	21.56	21.57	21.52
		RB Size=25, RB Offset=0	21.89	21.19	21.36
	16QAM	RB Size=1, RB Offset=0	22.18	21.55	21.57
		RB Size=1, RB Offset=12	21.29	21.23	21.31
		RB Size=1, RB Offset=24	21.72	21.76	21.7
		RB Size=12, RB Offset=0	21.93	21.20	21.35
		RB Size=12, RB Offset=6	21.54	21.64	21.73
		RB Size=12, RB Offset=11	22.09	21.53	21.64
		RB Size=25, RB Offset=0	22.27	21.45	21.46
10.0	QPSK	RB Size=1, RB Offset=0	21.78	21.44	21.69
		RB Size=1, RB Offset=24	21.85	21.65	21.86
		RB Size=1, RB Offset=49	22.05	21.9	21.82
		RB Size=25, RB Offset=0	22.65	21.95	21.79
		RB Size=25, RB Offset=12	21.66	21.48	21.52
		RB Size=25, RB Offset=24	21.87	21.54	21.5
		RB Size=50, RB Offset=0	22.14	21.58	21.65
	16QAM	RB Size=1, RB Offset=0	21.79	21.85	21.89
		RB Size=1, RB Offset=24	22.62	21.98	21.90
		RB Size=1, RB Offset=49	22.08	21.71	21.82
		RB Size=25, RB Offset=0	22.31	21.51	21.40
		RB Size=25, RB Offset=12	22.14	21.89	21.63
		RB Size=25, RB Offset=24	21.25	21.22	21.46
		RB Size=50, RB Offset=0	22.21	21.29	21.27

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	21.45	21.43	21.50
		RB Size=1, RB Offset=37	22.28	21.75	21.58
		RB Size=1, RB Offset=74	21.29	21.37	21.25
		RB Size=36, RB Offset=0	22.08	21.36	21.13
		RB Size=36, RB Offset=18	21.83	21.71	21.87
		RB Size=36, RB Offset=37	21.74	21.51	21.75
		RB Size=75, RB Offset=0	21.63	21.19	21.18
	16QAM	RB Size=1, RB Offset=0	22.49	21.60	21.66
		RB Size=1, RB Offset=37	21.49	21.35	21.36
		RB Size=1, RB Offset=74	21.89	21.70	21.58
		RB Size=36, RB Offset=0	21.34	21.23	21.39
		RB Size=36, RB Offset=18	22.37	21.49	21.67
		RB Size=36, RB Offset=37	21.86	21.65	21.75
		RB Size=75, RB Offset=0	21.42	21.45	21.52
20.0	QPSK	RB Size=1, RB Offset=0	22.03	21.63	21.49
		RB Size=1, RB Offset=49	21.66	21.74	21.78
		RB Size=1, RB Offset=99	22.06	21.81	21.75
		RB Size=50, RB Offset=0	22.31	21.77	21.69
		RB Size=50, RB Offset=24	21.96	21.46	21.57
		RB Size=50, RB Offset=49	21.85	21.60	21.54
		RB Size=100, RB Offset=0	21.81	21.65	21.47
	16QAM	RB Size=1, RB Offset=0	21.93	21.67	21.87
		RB Size=1, RB Offset=49	22.45	21.72	21.88
		RB Size=1, RB Offset=99	22.01	21.95	21.78
		RB Size=50, RB Offset=0	21.91	21.41	21.63
		RB Size=50, RB Offset=24	22.40	21.90	21.73
		RB Size=50, RB Offset=49	21.74	21.44	21.26
		RB Size=100, RB Offset=0	22.05	21.28	21.31

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.43	13	Pass
QPSK (100RB Size)	4.37	13	Pass
16QAM (1RB Size)	4.44	13	Pass
16QAM (100RB Size)	4.69	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	80.76	233	2.5	H	7.4	1.30	8.90	15.00	30
1732.50	76.58	246	2.4	V	3.9	1.30	8.90	11.50	30
3 MHz Bandwidth									
1732.50	80.32	241	1.8	H	7.0	1.30	8.90	14.60	30
1732.50	76.39	357	1.8	V	3.7	1.30	8.90	11.30	30
5 MHz Bandwidth									
1732.50	80.13	102	1.8	H	6.8	1.30	8.90	14.40	30
1732.50	76.06	237	1.8	V	3.3	1.30	8.90	10.90	30
10 MHz Bandwidth									
1732.50	79.84	199	2.1	H	6.5	1.30	8.90	14.10	30
1732.50	75.67	136	1.4	V	2.9	1.30	8.90	10.50	30
15 MHz Bandwidth									
1732.50	79.62	177	2.2	H	6.3	1.30	8.90	13.90	30
1732.50	75.42	166	1.5	V	2.7	1.30	8.90	10.30	30
20 MHz Bandwidth									
1732.50	79.24	49	2.4	H	5.9	1.30	8.90	13.50	30
1732.50	75.16	123	1.4	V	2.4	1.30	8.90	10.00	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	80.95	26	1.6	H	7.6	1.30	8.90	15.20	30
1732.50	76.53	46	2.4	V	3.8	1.30	8.90	11.10	30
3 MHz Bandwidth									
1732.50	80.50	138	1.4	H	7.2	1.30	8.90	14.80	30
1732.50	76.31	156	1.0	V	3.6	1.30	8.90	11.20	30
5 MHz Bandwidth									
1732.50	80.10	353	2.3	H	6.8	1.30	8.90	14.40	30
1732.50	75.81	46	2.0	V	3.1	1.30	8.90	10.70	30
10 MHz Bandwidth									
1732.50	79.96	311	2.1	H	6.4	1.50	8.90	14.20	30
1732.50	75.89	232	2.4	V	3.0	1.50	8.90	10.80	30
15 MHz Bandwidth									
1732.50	79.65	150	1.5	H	6.3	1.30	8.90	13.90	30
1732.50	75.34	77	2.2	V	2.6	1.30	8.90	10.20	30
20 MHz Bandwidth									
1732.50	79.35	155	1.2	H	6.0	1.30	8.90	13.60	30
1732.50	75.12	85	1.4	V	2.4	1.30	8.90	10.00	30

LTE Band 5:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	21.42	21.63	21.62
		RB Size=1, RB Offset=2	21.68	21.51	21.66
		RB Size=1, RB Offset=5	21.72	21.24	21.37
		RB Size=3, RB Offset=0	22.02	21.25	21.27
		RB Size=3, RB Offset=1	22.09	21.78	21.74
		RB Size=3, RB Offset=2	21.96	21.67	21.79
		RB Size=6, RB Offset=0	21.82	21.23	21.16
	16QAM	RB Size=1, RB Offset=0	22.40	21.78	21.55
		RB Size=1, RB Offset=2	21.60	21.28	21.47
		RB Size=1, RB Offset=5	21.49	21.58	21.71
		RB Size=3, RB Offset=0	21.98	21.13	21.11
		RB Size=3, RB Offset=1	21.53	21.58	21.62
		RB Size=3, RB Offset=2	22.13	21.63	21.53
		RB Size=6, RB Offset=0	21.98	21.34	21.37
3.0	QPSK	RB Size=1, RB Offset=0	21.59	21.69	21.45
		RB Size=1, RB Offset=7	21.73	21.65	21.85
		RB Size=1, RB Offset=14	21.83	21.72	21.85
		RB Size=8, RB Offset=0	22.34	21.75	21.76
		RB Size=8, RB Offset=4	21.32	21.4	21.39
		RB Size=8, RB Offset=7	21.83	21.66	21.46
		RB Size=15, RB Offset=0	21.54	21.71	21.46
	16QAM	RB Size=1, RB Offset=0	22.03	21.84	21.87
		RB Size=1, RB Offset=7	22.67	21.94	21.85
		RB Size=1, RB Offset=14	21.80	21.89	21.79
		RB Size=8, RB Offset=0	21.95	21.42	21.43
		RB Size=8, RB Offset=4	22.31	21.64	21.65
		RB Size=8, RB Offset=7	21.65	21.5	21.28
		RB Size=15, RB Offset=0	21.84	21.39	21.31

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	21.41	21.54	21.62
		RB Size=1, RB Offset=12	22.28	21.69	21.65
		RB Size=1, RB Offset=24	21.16	21.39	21.33
		RB Size=12, RB Offset=0	22.02	21.25	21.26
		RB Size=12, RB Offset=6	22.28	21.76	21.85
		RB Size=12, RB Offset=11	22.16	21.65	21.78
		RB Size=25, RB Offset=0	21.32	21.32	21.19
	16QAM	RB Size=1, RB Offset=0	22.13	21.68	21.55
		RB Size=1, RB Offset=12	21.37	21.28	21.34
		RB Size=1, RB Offset=24	22.45	21.54	21.55
		RB Size=12, RB Offset=0	21.78	21.27	21.17
		RB Size=12, RB Offset=6	22.21	21.58	21.75
		RB Size=12, RB Offset=11	22.35	21.61	21.53
		RB Size=25, RB Offset=0	21.48	21.48	21.33
10.0	QPSK	RB Size=1, RB Offset=0	21.75	21.49	21.56
		RB Size=1, RB Offset=24	22.23	21.58	21.71
		RB Size=1, RB Offset=49	22.10	21.67	21.69
		RB Size=25, RB Offset=0	21.88	21.91	21.85
		RB Size=25, RB Offset=12	21.87	21.51	21.37
		RB Size=25, RB Offset=24	21.42	21.44	21.45
		RB Size=50, RB Offset=0	21.76	21.71	21.62
	16QAM	RB Size=1, RB Offset=0	21.75	21.87	21.78
		RB Size=1, RB Offset=24	21.81	21.78	21.72
		RB Size=1, RB Offset=49	22.44	21.75	21.77
		RB Size=25, RB Offset=0	21.95	21.61	21.62
		RB Size=25, RB Offset=12	21.93	21.89	21.63
		RB Size=25, RB Offset=24	21.59	21.26	21.48
		RB Size=50, RB Offset=0	21.97	21.24	21.39

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.37	13	Pass
QPSK (50RB Size)	4.89	13	Pass
16QAM (1RB Size)	4.47	13	Pass
16QAM (50RB Size)	4.45	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
836.6	78.52	252	2.0	H	16.5	0.28	0.0	16.22	38.45
836.6	73.42	231	1.1	V	13.4	0.28	0.0	13.12	38.45
3 MHz Bandwidth									
836.6	78.24	32	1.8	H	16.2	0.28	0.0	15.92	38.45
836.6	73.23	121	2.3	V	13.2	0.28	0.0	12.92	38.45
5 MHz Bandwidth									
836.6	78.05	10	2.0	H	16.1	0.28	0.0	15.82	38.45
836.6	73.03	227	1.7	V	13.0	0.28	0.0	12.72	38.45
10 MHz Bandwidth									
836.6	77.65	40	1.6	H	15.7	0.28	0.0	15.42	38.45
836.6	72.68	32	1.7	V	12.7	0.28	0.0	12.42	38.45

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
1.4 MHz Bandwidth									
836.6	77.61	329	2.5	H	15.6	0.28	0.0	15.32	38.45
836.6	72.62	53	2.4	V	12.6	0.28	0.0	12.32	38.45
3 MHz Bandwidth									
836.6	77.43	22	1.6	H	15.4	0.28	0.0	15.12	38.45
836.6	72.32	137	1.2	V	12.3	0.28	0.0	12.02	38.45
5 MHz Bandwidth									
836.6	77.15	181	1.9	H	15.2	0.28	0.0	14.92	38.45
836.6	72.03	155	2.5	V	12.0	0.28	0.0	11.72	38.45
10 MHz Bandwidth									
836.6	76.87	215	2.4	H	14.9	0.28	0.0	14.62	38.45
836.6	71.65	146	1.5	V	11.7	0.28	0.0	11.42	38.45

LTE Band 7:

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5	QPSK	RB Size=1, RB Offset=0	21.60	21.67	21.54
		RB Size=1, RB Offset=12	22.47	21.53	21.60
		RB Size=1, RB Offset=24	21.25	21.32	21.38
		RB Size=12, RB Offset=0	21.68	21.32	21.19
		RB Size=12, RB Offset=6	21.98	21.84	21.83
		RB Size=12, RB Offset=11	22.39	21.74	21.77
		RB Size=25, RB Offset=0	22.08	21.13	21.40
	16QAM	RB Size=1, RB Offset=0	21.64	21.61	21.80
		RB Size=1, RB Offset=12	21.83	21.5	21.26
		RB Size=1, RB Offset=24	22.45	21.58	21.56
		RB Size=12, RB Offset=0	22.03	21.13	21.15
		RB Size=12, RB Offset=6	21.59	21.63	21.51
		RB Size=12, RB Offset=11	22.18	21.63	21.48
		RB Size=25, RB Offset=0	21.89	21.54	21.39
10	QPSK	RB Size=1, RB Offset=0	22.12	21.68	21.68
		RB Size=1, RB Offset=24	22.02	21.82	21.67
		RB Size=1, RB Offset=49	22.23	21.81	21.74
		RB Size=25, RB Offset=0	21.97	21.90	21.89
		RB Size=25, RB Offset=12	22.02	21.38	21.53
		RB Size=25, RB Offset=24	21.80	21.41	21.60
		RB Size=50, RB Offset=0	22.16	21.69	21.55
	16QAM	RB Size=1, RB Offset=0	22.29	21.91	21.78
		RB Size=1, RB Offset=24	22.54	21.85	21.74
		RB Size=1, RB Offset=49	22.59	21.77	21.71
		RB Size=25, RB Offset=0	21.91	21.48	21.66
		RB Size=25, RB Offset=12	21.67	21.63	21.86
		RB Size=25, RB Offset=24	22.12	21.26	21.33
		RB Size=50, RB Offset=0	21.66	21.46	21.30

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15	QPSK	RB Size=1, RB Offset=0	21.46	21.58	21.67
		RB Size=1, RB Offset=37	22.31	21.66	21.70
		RB Size=1, RB Offset=74	22.06	21.30	21.26
		RB Size=36, RB Offset=0	21.82	21.42	21.37
		RB Size=36, RB Offset=18	22.25	21.76	21.62
		RB Size=36, RB Offset=37	22.03	21.68	21.7
		RB Size=75, RB Offset=0	22.09	21.14	21.39
	16QAM	RB Size=1, RB Offset=0	22.13	21.54	21.53
		RB Size=1, RB Offset=37	22.02	21.50	21.23
		RB Size=1, RB Offset=74	21.52	21.49	21.67
		RB Size=36, RB Offset=0	21.61	21.15	21.36
		RB Size=36, RB Offset=18	22.04	21.68	21.67
		RB Size=36, RB Offset=37	21.57	21.62	21.74
		RB Size=75, RB Offset=0	22.15	21.45	21.54
20	QPSK	RB Size=1, RB Offset=0	21.85	21.54	21.56
		RB Size=1, RB Offset=49	22.46	21.88	21.68
		RB Size=1, RB Offset=99	21.61	21.72	21.72
		RB Size=50, RB Offset=0	22.17	21.69	21.81
		RB Size=50, RB Offset=24	21.83	21.49	21.39
		RB Size=50, RB Offset=49	21.70	21.47	21.54
		RB Size=100, RB Offset=0	22.37	21.60	21.53
	16QAM	RB Size=1, RB Offset=0	21.85	21.92	21.88
		RB Size=1, RB Offset=49	22.35	21.79	21.81
		RB Size=1, RB Offset=99	22.37	21.86	21.74
		RB Size=50, RB Offset=0	21.55	21.39	21.54
		RB Size=50, RB Offset=24	21.84	21.66	21.8
		RB Size=50, RB Offset=49	21.58	21.21	21.21
		RB Size=100, RB Offset=0	21.50	21.52	21.3

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	4.92	13	Pass
QPSK (50RB Size)	4.91	13	Pass
16QAM (1RB Size)	4.78	13	Pass
16QAM (50RB Size)	4.64	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
5 MHz Bandwidth									
2535.00	77.24	39	2.3	H	7.1	2.60	10.20	14.70	33
2535.00	74.43	224	2.3	V	4.9	2.60	10.20	12.50	33
10 MHz Bandwidth									
2535.00	77.03	266	1.3	H	6.9	2.60	10.20	14.50	33
2535.00	74.13	331	1.5	V	4.6	2.60	10.20	12.20	33
15 MHz Bandwidth									
2535.00	76.78	158	2.0	H	6.6	2.60	10.20	14.20	33
2535.00	73.87	183	1.9	V	4.3	2.60	10.20	11.90	33
20 MHz Bandwidth									
2535.00	76.54	244	2.2	H	6.4	2.60	10.20	14.00	33
2535.00	73.62	75	2.3	V	4.1	2.60	10.20	11.70	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBi)		
Middle Channel									
5 MHz Bandwidth									
2535.00	77.76	57	1.9	H	7.6	2.60	10.20	15.20	33
2535.00	74.58	23	1.4	V	5.0	2.60	10.20	12.60	33
10 MHz Bandwidth									
2535.00	77.21	202	1.5	H	7.0	2.60	10.20	14.60	33
2535.00	74.32	357	1.6	V	4.8	2.60	10.20	12.40	33
15 MHz Bandwidth									
2535.00	76.84	168	2.2	H	6.7	2.60	10.20	14.30	33
2535.00	73.95	65	2.0	V	4.4	2.60	10.20	12.00	33
20 MHz Bandwidth									
2535.00	76.62	236	2.0	H	6.5	2.60	10.20	14.10	33
2535.00	73.74	218	1.5	V	4.2	2.60	10.20	11.80	33

Note:

All above data were tested with no amplifier

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Gavin Guo and Kieron Luo from 2019-08-29 to 2019-08-30.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	241.99	315.39
EGPRS(8PSK)	836.6	245.19	308.33

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.15	4.68
HSUPA (BPSK)	836.6	4.15	4.67
HSDPA (16QAM)	836.6	4.15	4.69


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	245.19	318.27
EGPRS(8PSK)	1880.0	245.19	308.33

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.15	4.70
HSUPA (BPSK)	1880.0	4.17	4.70
HSDPA (16QAM)	1880.0	4.15	4.68


Cellular Band (Part 22H)

26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode




Date: 29.AUG.2019 22:40:24


26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode




Date: 29.AUG.2019 22:53:04

26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode


Date: 29.AUG.2019 23:21:23

26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode

Date: 29.AUG.2019 23:24:31


26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode

Date: 29.AUG.2019 23:34:16

PCS Band (Part 24E)**26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**


Date: 29.AUG.2019 22:49:44

26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode




Date: 29.AUG.2019 22:53:04


26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode



Date: 29.AUG.2019 23:02:49

26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode


Date: 29.AUG.2019 23:02:49

26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode


Date: 29.AUG.2019 23:09:03

LTE Band 2: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.12	1.33
	16QAM	1.12	1.36
3.0	QPSK	2.71	3.01
	16QAM	2.71	3.02
5.0	QPSK	4.56	5.35
	16QAM	4.54	5.29
10.0	QPSK	8.96	9.74
	16QAM	8.96	9.70
15.0	QPSK	13.62	15.45
	16QAM	13.62	14.97
20.0	QPSK	18.00	20.04
	16QAM	18.08	20.12

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:25:00

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:25:30

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:25:56

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:26:20

QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:26:59

16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:27:38

QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:28:15

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:28:46

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:29:31

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:30:07

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:30:43


16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:31:26

LTE Band 4: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.11	1.34
	16QAM	1.12	1.33
3.0	QPSK	2.71	3.02
	16QAM	2.70	3.01
5.0	QPSK	4.56	5.27
	16QAM	4.54	5.25
10.0	QPSK	9.00	9.74
	16QAM	8.96	9.66
15.0	QPSK	13.56	15.33
	16QAM	13.56	14.97
20.0	QPSK	18.00	19.56
	16QAM	18.00	19.72

QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 30.AUG.2019 21:31:58


16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 30.AUG.2019 21:32:28


QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:33:01


16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:33:24




QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:35:16

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:35:47

QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 30.AUG.2019 21:36:26

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel



Date: 30.AUG.2019 21:37:02




Date: 30.AUG.2019 21:37:38




Date: 30.AUG.2019 21:38:14

LTE Band 5: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.11	1.32
	16QAM	1.12	1.31
3.0	QPSK	2.70	3.02
	16QAM	2.71	3.03
5.0	QPSK	4.56	5.45
	16QAM	4.56	5.39
10.0	QPSK	9.00	9.82
	16QAM	9.00	9.74


QPSK (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:38:52

16-QAM (1.4 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:39:34

QPSK (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 30.AUG.2019 21:40:06

16-QAM (3.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel




Date: 30.AUG.2019 21:40:33



QPSK (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:42:51

16-QAM (10.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:43:37

LTE Band 7: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.56	5.31
	16QAM	4.52	5.19
10.0	QPSK	9.00	9.82
	16QAM	8.96	9.82
15.0	QPSK	13.62	15.39
	16QAM	13.62	14.85
20.0	QPSK	18.00	19.64
	16QAM	18.00	19.88


QPSK (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:44:28


16-QAM (5.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:45:07




QPSK (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel


Date: 30.AUG.2019 21:46:47

16-QAM (15.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:47:32

QPSK (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:48:21

16-QAM (20.0 MHz) - 26 dB Bandwidth & 99% Occupied Bandwidth, Middle channel

Date: 30.AUG.2019 21:49:00

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53.

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in §2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by George Zhong from 2019-08-29 to 2019-09-05.

Test result: Compliance.

EUT operation mode: transmitting

Please refer to the following plots.

30 MHz – 1 GHz (GSM Mode)



Date: 29.AUG.2019 22:42:14

[illegible]

Date: 29.AUG.2019 22:41:38



Date: 29.AUG.2019 23:18:28




30 MHz – 1 GHz (GSM Mode)



Fundamental test


Date: 29.AUG.2019 22:46:05

2 GHz – 20 GHz (GSM Mode)




Date: 29.AUG.2019 22:46:22

30 MHz – 1 GHz (WCDMA Mode)




Date: 29.AUG.2019 23:16:14

1 GHz – 2 GHz (WCDMA Mode)




Fundamental test

2 GHz – 20 GHz (WCDMA Mode)




LTE Band 2:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




Date: 30.AUG.2019 22:39:03

1 GHz - 20 GHz (1.4 MHz, Middle Channel)




Date: 30.AUG.2019 22:39:12

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:39:32

1 GHz - 20 GHz (3.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:39:41

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:39:59

1 GHz - 20 GHz (5.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:40:09

30 MHz - 1 GHz (10.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:40:28


1 GHz - 20 GHz (10.0 MHz, Middle Channel)



Fundamental test


Date: 30.AUG.2019 22:40:38

30 MHz - 1 GHz (15.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:40:57


1 GHz - 20 GHz (15.0 MHz, Middle Channel)



Fundamental test


Date: 30.AUG.2019 22:41:06

30 MHz - 1 GHz (20.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:41:28

1 GHz - 20 GHz (20.0 MHz, Middle Channel)




Fundamental test

Date: 30.AUG.2019 22:41:37


LTE Band 4:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)



Date: 30.AUG.2019 22:41:52


1 GHz - 20 GHz (1.4 MHz, Middle Channel)



Fundamental test


Date: 30.AUG.2019 22:42:02

30 MHz - 1 GHz (3.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:42:20


1 GHz – 20 GHz (3.0 MHz, Middle Channel)



Fundamental test


Date: 30.AUG.2019 22:42:29

30 MHz - 1 GHz (5.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:42:47


1 GHz - 20 GHz (5.0 MHz, Middle Channel)



Fundamental test


Date: 30.AUG.2019 22:42:56

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:43:13

1 GHz - 20 GHz (10.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:43:22

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:43:41

1 GHz – 20 GHz (15.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:43:50

30 MHz - 1 GHz (20.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:44:09

1 GHz - 20 GHz (20.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:44:18

30 MHz - 1 GHz (3.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:45:01


1 GHz - 10 GHz (3.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:45:10




Date: 30.AUG.2019 22:45:26




Date: 30.AUG.2019 22:45:35

30 MHz - 1 GHz (10.0 MHz, Middle Channel)




Date: 30.AUG.2019 22:45:55


1 GHz - 10 GHz (10.0 MHz, Middle Channel)



Date: 30.AUG.2019 22:46:04


LTE Band 7:**30 MHz - 1 GHz (5 MHz, Middle Channel)**

Date: 5.SEP.2019 23:25:13

1 GHz – 26.5 GHz (5 MHz, Middle Channel)


Date: 5.SEP.2019 23:21:49

30 MHz - 1 GHz (10 MHz, Middle Channel)



Date: 5.SEP.2019 23:24:59


1 GHz – 26.5 GHz (10 MHz, Middle Channel)



Fundamental test


Date: 5.SEP.2019 23:22:09

30 MHz - 1 GHz (15 MHz, Middle Channel)



Date: 5.SEP.2019 23:24:41


1 GHz – 26.5 GHz (15 MHz, Middle Channel)



Fundamental test


Date: 5.SEP.2019 23:22:28

30 MHz - 1 GHz (20 MHz, Middle Channel)



Date: 5.SEP.2019 23:24:09

1 GHz – 26.5 GHz (20 MHz, Middle Channel)



Date: 5.SEP.2019 23:22:53

FCC § 2.1053; § 22.917 (a); § 24.238 (a); §27.53 SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917(a) and § 24.238(a) and § 27.53

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Curry Xiang on 2019-08-29.

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H	
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)		Limit (dBm)	Margin (dB)
GSM Mode, middle channel										
245.12	35.12	304	2.1	H	-61.90	0.31	0	-62.21	-13	49.21
245.12	32.16	338	2.2	V	-64.80	0.31	0	-65.11	-13	52.11
1673.00	75.70	168	1.4	H	-30.6	1.30	8.90	-23.00	-13	10.00
1673.00	75.04	60	1.0	V	-30.7	1.30	8.90	-23.10	-13	10.10
2509.50	59.94	288	1.0	H	-43.4	2.60	10.20	-35.80	-13	22.80
2509.50	59.13	145	1.4	V	-43.6	2.60	10.20	-36.00	-13	23.00
3346.00	59.78	291	1.9	H	-41.1	1.50	11.70	-30.90	-13	17.90
3346.00	56.33	207	1.3	V	-44.6	1.50	11.70	-34.40	-13	21.40
WCDMA Mode, Middle channel										
245.12	35.64	201	2.0	H	-61.40	0.31	0	-61.71	-13	48.71
245.12	32.27	347	2.0	V	-64.70	0.31	0	-65.01	-13	52.01
1673.20	51.65	98	1.1	H	-54.7	1.30	8.90	-47.10	-13	34.10
1673.20	50.28	282	1.2	V	-55.5	1.30	8.90	-47.90	-13	34.90
2509.80	46.66	298	2.2	H	-56.7	2.60	10.20	-49.10	-13	36.10
2509.80	46.85	169	2.3	V	-55.9	2.60	10.20	-48.30	-13	35.30
3346.40	47.93	284	1.8	H	-53.0	1.50	11.70	-42.80	-13	29.80
3346.40	44.87	49	2.2	V	-56.1	1.50	11.70	-45.90	-13	32.90

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)		Limit (dBm)	Margin (dB)
GSM Mode, middle channel										
245.12	35.76	33	2.4	H	-61.20	0.31	0	-61.51	-13	48.51
245.12	32.73	359	1.9	V	-64.30	0.31	0	-64.61	-13	51.61
3760.00	57.76	9	1.6	H	-44.3	1.50	11.80	-34.00	-13	21.00
3760.00	52.81	223	2.0	V	-48.8	1.50	11.80	-38.50	-13	25.50
WCDMA Mode Band II, Middle channel										
245.12	35.76	78	2.3	H	-61.20	0.31	0	-61.51	-13	48.51
245.12	32.07	268	1.7	V	-64.90	0.31	0	-65.21	-13	52.21
3760.00	52.30	144	1.1	H	-49.8	1.50	11.80	-39.50	-13	26.50
3760.00	47.23	88	1.9	V	-54.4	1.50	11.80	-44.10	-13	31.10
5640.00	54.22	16	2.5	H	-45.5	1.70	12.40	-34.80	-13	21.80
5640.00	51.65	270	2.0	V	-47.7	1.70	12.40	-37.00	-13	24.00

LTE Band: (Pre-scan with all the bandwidth, and worse case as below)

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level	Limit	Margin
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)	(dBm)	(dBm)	(dB)
Band 2 (1.4 MHz, Middle Channel)										
Test frequency range:30 MHz ~ 20 GHz										
245.12	35.34	285	2.4	H	-61.70	0.31	0	-62.01	-13	49.01
245.12	32.26	249	1.0	V	-64.70	0.31	0	-65.01	-13	52.01
3760.00	47.62	17	1.1	H	-54.4	1.50	11.80	-44.10	-13	31.10
3760.00	45.90	181	2.2	V	-55.7	1.50	11.80	-45.40	-13	32.40
Band 4 (1.4 MHz, Middle Channel)										
Test frequency range:30 MHz ~ 20 GHz										
245.12	35.81	6	1.6	H	-61.20	0.31	0	-61.51	-13	48.51
245.12	32.62	197	2.2	V	-64.40	0.31	0	-64.71	-13	51.71
3465.00	50.10	90	1.4	H	-50.6	1.50	12.00	-40.10	-13	27.10
3465.00	47.60	71	2.4	V	-53.9	1.50	12.00	-43.40	-13	30.40
Band 7 (5 MHz, Middle Channel)										
Test frequency range: 30 MHz ~ 26.5GHz										
245.12	35.62	1	2.5	H	-61.40	0.31	0	-61.71	-25	36.71
245.12	32.42	33	2.0	V	-64.60	0.31	0	-64.91	-25	39.91
5070.00	61.05	266	1.7	H	-39.0	1.60	12.10	-28.50	-25	3.50
5070.00	55.39	214	2.1	V	-44.6	1.60	12.10	-34.10	-25	9.10
Band 5(1.4 MHz, Middle Channel)										
Test frequency range: 30 MHz ~ 10GHz										
245.12	35.98	172	1.3	H	-61.00	0.31	0	-61.31	-13	48.31
245.12	32.13	127	1.2	V	-64.90	0.31	0	-65.21	-13	52.21
1673.00	47.34	246	1.9	H	-59.0	1.30	8.90	-51.40	-13	38.40
1673.00	47.86	172	2.2	V	-57.9	1.30	8.90	-50.30	-13	37.30
2509.50	46.67	274	1.2	H	-56.7	2.60	10.20	-49.10	-13	36.10
2509.50	45.47	43	1.8	V	-57.3	2.60	10.20	-49.70	-13	36.70
3346.00	45.90	87	2.0	H	-55.0	1.50	11.70	-44.80	-13	31.80
3346.00	44.03	164	1.3	V	-56.9	1.50	11.70	-46.70	-13	33.70

Note:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

dBd is for the ERP, dBi is for EIRP.

FCC § 22.917 (a); § 24.238 (a); §27.53 (h)(m) - BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to FCC §27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa


The testing was performed by George Zhong from 2019-08-29 to 2019-09-05.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following plots.




Cellular Band, Left Band Edge for EDGE Mode




Date: 29.AUG.2019 22:36:40

Cellular Band, Right Band Edge for EDGE Mode




Date: 29.AUG.2019 22:37:20

Cellular Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 29.AUG.2019 23:30:13


Cellular Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 29.AUG.2019 23:31:41

Cellular Band, Left Band Edge for HSDPA (16QAM) Mode


Date: 29.AUG.2019 23:28:41

Cellular Band, Right Band Edge for HSDPA (16QAM) Mode

Date: 29.AUG.2019 23:27:41

Cellular Band, Left Band Edge for HSUPA (BPSK) Mode

Date: 29.AUG.2019 23:25:34

Cellular Band, Right Band Edge for HSUPA (BPSK) Mode

Date: 29.AUG.2019 23:26:12

Ref 34.5 dBm * Att 20 dB * RBW 5 kHz * VBW 10 kHz * SWT 200 ms Marker 1 [T1] -16.87 dBm 1.849983974 GHz

Offset 9.5 dB

1 dB MAXdB

Q1 -13 dBm


Center 1.85 GHz 200 kHz/ Span 2 MHz

Date: 29.AUG.2019 22:47:41

[illegible]


Date: 29.AUG.2019 22:48:19

PCS Band, Left Band Edge for EDGE Mode




Date: 29.AUG.2019 22:54:10

PCS Band, Right Band Edge for EDGE Mode




Date: 29.AUG.2019 22:54:48

PCS Band, Left Band Edge for WCDMA (BPSK) Mode




Date: 29.AUG.2019 23:11:32

PCS Band, Right Band Edge for WCDMA (BPSK) Mode




Date: 29.AUG.2019 23:12:13

PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode






Band 2:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 21:49:43

QPSK (1.4 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 21:51:00

16-QAM (1.4 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 21:50:12

16-QAM (1.4 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 21:51:34

QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 21:52:06


QPSK (3.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 21:52:58


16-QAM (3.0 MHz, FULL RB) - Left Band Edge

Date: 30.AUG.2019 21:52:28

16-QAM (3.0 MHz, FULL RB) - Right Band Edge


Date: 30.AUG.2019 21:53:27

QPSK (5.0 MHz, FULL RB) - Left Band Edge



Date: 5.SEP.2019 23:30:43


QPSK (5.0 MHz, FULL RB) - Right Band Edge



Date: 5.SEP.2019 23:33:51




QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 21:56:17

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 21:57:20





QPSK (15.0 MHz, FULL RB) - Left Band Edge

Date: 1.SEP.2019 14:43:17


QPSK (15.0 MHz, FULL RB) - Right Band Edge

Date: 1.SEP.2019 14:41:18






16-QAM (20.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:01:44


16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 22:02:49

Band 4:**QPSK (1.4 MHz, FULL RB) - Left Band Edge**


Date: 30.AUG.2019 22:03:24

QPSK (1.4 MHz, FULL RB) - Right Band Edge

Date: 30.AUG.2019 22:04:29




QPSK (3.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:05:32

QPSK (3.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:06:21

16-QAM (3.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:05:58

16-QAM (3.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:06:44

QPSK (5.0 MHz, FULL RB) - Left Band Edge




Date: 1.SEP.2019 15:00:40


QPSK (5.0 MHz, FULL RB) - Right Band Edge



Date: 5.SEP.2019 23:35:24


16-QAM (5.0 MHz, FULL RB) - Left Band Edge

Date: 1.SEP.2019 15:00:04

16-QAM (5.0 MHz, FULL RB) - Right Band Edge


Date: 1.SEP.2019 14:58:29

QPSK (10.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:09:59

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:11:05

16-QAM (10.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:10:32

16-QAM (10.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:11:32

QPSK (15.0 MHz, FULL RB) - Left Band Edge




Date: 1.SEP.2019 15:10:41


QPSK (15.0 MHz, FULL RB) - Right Band Edge



Date: 1.SEP.2019 15:04:59




QPSK (20.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:14:23

QPSK (20.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:15:34

16-QAM (20.0 MHz, FULL RB) - Left Band Edge




Date: 30.AUG.2019 22:14:55


16-QAM (20.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 22:16:09


Band 5:**QPSK (1.4 MHz, FULL RB) - Left Band Edge**

Date: 1.SEP.2019 15:16:39

QPSK (1.4 MHz, FULL RB) - Right Band Edge


Date: 1.SEP.2019 15:13:37

16-QAM 1.4 MHz, FULL RB) - Left Band Edge




Date: 1.SEP.2019 15:16:00

16-QAM (1.4MHz, FULL RB) - Right Band Edge




Date: 1.SEP.2019 15:14:52

QPSK (3.0 MHz, FULL RB) - Left Band Edge



Date: 30.AUG.2019 22:18:40


QPSK (3.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 22:19:38




QPSK (5.0 MHz, FULL RB) - Left Band Edge



Date: 1.SEP.2019 15:21:47

QPSK (5.0 MHz, FULL RB) - Right Band Edge



Date: 1.SEP.2019 15:19:41

Ref 25 dBm * Att 25 dB

- * RBW 100 kHz
- * VBW 300 kHz
- * SWT 30 ms

Marker 1 [T1] -14.11 dBm
823.967948718 MHz

Offset 6 dB

1 dB MAX

01 -13 dBm

Center 824 MHz 1 MHz/ Span 10 MHz

Date: 1.SEP.2019 15:21:47

Ref 25 dBm * Att 25 dB * RBW 100 kHz Marker 1 [T1] -14.64 dBm
 * VBW 300 kHz * SWT 30 ms 849.096153846 MHz

Offset 6 dB


1 dB
MAX

01 -13 dBm

Center 849 MHz 1 MHz/ Span 10 MHz


Date: 1.SEP.2019 15:20:24

QPSK (10.0 MHz, FULL RB) - Left Band Edge






Date: 30.AUG.2019 22:23:07

QPSK (10.0 MHz, FULL RB) - Right Band Edge




Date: 30.AUG.2019 22:23:59




Band 7:**QPSK (5.0 MHz, FULL RB) - Left Band Edge**


Date: 1.SEP.2019 15:27:41

QPSK (5.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 22:26:05



16-QAM (5.0 MHz, FULL RB) - Left Band Edge

Date: 30.AUG.2019 22:25:44



16-QAM (5.0 MHz, FULL RB) - Right Band Edge

Date: 1.SEP.2019 15:25:34











QPSK (20.0 MHz, FULL RB) - Left Band Edge





Date: 30.AUG.2019 22:32:11

QPSK (20.0 MHz, FULL RB) - Right Band Edge



Date: 30.AUG.2019 22:33:23



FCC § 2.1055; § 22.355; § 24.235; § 27.54 - FREQUENCY STABILITY**Applicable Standard**

FCC § 2.1055, § 22.355, § 24.235 and § 27.54.

According to FCC § 2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to § 22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to § 24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by George Zhong on 2019-09-04.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_o = 836.6\text{MHz}$				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	5	0.005977	2.5
-20		2	0.002391	2.5
-10		-1	-0.001195	2.5
0		4	0.004781	2.5
10		-3	-0.003586	2.5
20		1	0.001195	2.5
30		5	0.005977	2.5
40		1	0.001195	2.5
50		-2	-0.002391	2.5
20	V min.= 3.5	5	0.005977	2.5
	V max.= 4.2	3	0.003586	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	3	0.003586	2.5
-20		-2	-0.002391	2.5
-10		5	0.005977	2.5
0		-6	-0.007172	2.5
10		1	0.001195	2.5
20		-4	-0.004781	2.5
30		1	0.001195	2.5
40		-5	-0.005977	2.5
50		2	0.002391	2.5
20	V min.= 3.5	4	0.004781	2.5
	V max.= 4.2	3	0.003586	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	4	0.004781	2.5
-20		2	0.002391	2.5
-10		-5	-0.005977	2.5
0		-8	-0.009563	2.5
10		4	0.004781	2.5
20		7	0.008367	2.5
30		-3	-0.003586	2.5
40		5	0.005977	2.5
50		6	0.007172	2.5
20	V min.= 3.5	5	0.005977	2.5
	V max.= 4.2	-2	-0.002391	2.5

PCS Band (Part 24E)

GSM Mode

Middle Channel, $f_o = 1880.0$ MHz				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	3	0.001596	pass
-20		-2	-0.001064	pass
-10		5	0.002660	pass
0		1	0.000532	pass
10		-4	-0.002128	pass
20		6	0.003191	pass
30		-5	-0.002660	pass
40		3	0.001596	pass
50		2	0.001064	pass
20	V min.= 3.5	-4	-0.002128	pass
	V max.= 4.2	2	0.001064	pass

EDGE Mode

Middle Channel, $f_o = 1880.0$ MHz				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-5	-0.002660	pass
-20		2	0.001064	pass
-10		-6	-0.003191	pass
0		-1	-0.000532	pass
10		2	0.001064	pass
20		5	0.002660	pass
30		7	0.003723	pass
40		9	0.004787	pass
50		-3	-0.001596	pass
20	V min.= 3.5	5	0.002660	pass
	V max.= 4.2	1	0.000532	pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	6	0.003191	pass
-20		2	0.001064	pass
-10		3	0.001596	pass
0		-5	-0.002660	pass
10		6	0.003191	pass
20		-4	-0.002128	pass
30		-8	-0.004255	pass
40		2	0.001064	pass
50		5	0.002660	pass
20	V min.= 3.5	1	0.000532	pass
	V max.= 4.2	-3	-0.001596	pass

LTE:
QPSK:

Band 2:

10.0 MHz Middle Channel, $f_0 = 1880\text{MHz}$				
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-7	-0.003723	pass
-20		-6	-0.003191	pass
-10		-4	-0.002128	pass
0		-8	-0.004255	pass
10		-6	-0.003191	pass
20		-5	-0.002660	pass
30		-6	-0.003191	pass
40		-3	-0.001596	pass
50		-4	-0.002128	pass
20	V min.= 3.5	-7	-0.003723	pass
	V max.= 4.2	-5	-0.002660	pass

Band 4:

10 MHz Bandwidth					
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30	3.7	1710.5262	1754.7568	1710	1755
-20		1710.5254	1754.7571	1710	1755
-10		1710.5257	1754.7574	1710	1755
0		1710.5275	1754.7564	1710	1755
10		1710.5249	1754.7575	1710	1755
20		1710.5263	1754.7568	1710	1755
30		1710.5247	1754.7574	1710	1755
40		1710.5247	1754.7593	1710	1755
50		1710.5254	1754.7569	1710	1755
20	V min.= 3.5	1710.5259	1754.7585	1710	1755
	V max.= 4.2	1710.5246	1754.7581	1710	1755

Band 5:

10.0 MHz Middle Channel, $f_o = 836.5\text{MHz}$				
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-4	-0.004781	2.5
-20		-3	-0.003586	2.5
-10		-4	-0.004781	2.5
0		-3	-0.003586	2.5
10		-5	-0.005977	2.5
20		-3	-0.003586	2.5
30		-2	-0.002391	2.5
40		-1	-0.001195	2.5
50		-3	-0.003586	2.5
20	V min.= 3.5	-3	-0.003586	2.5
	V max.= 4.2	-5	-0.005977	2.5

Band 7:

10 MHz Bandwidth					
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30	3.7	2500.4534	2569.7024	2500	2570
-20		2500.4546	2569.7031	2500	2570
-10		2500.4552	2569.7018	2500	2570
0		2500.4534	2569.7042	2500	2570
10		2500.4551	2569.7042	2500	2570
20		2500.4542	2569.7029	2500	2570
30		2500.4547	2569.7041	2500	2570
40		2500.4546	2569.7034	2500	2570
50		2500.4538	2569.7026	2500	2570
20	V min.= 3.5	2500.4536	2569.7045	2500	2570
	V max.= 4.2	2500.4536	2569.7020	2500	2570

16QAM:**Band 2:**

10.0 MHz Middle Channel, $f_0=1880\text{MHz}$				
Temperature (°C)	Voltage Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-2	-0.001064	pass
-20		-5	-0.002660	pass
-10		-4	-0.002128	pass
0		-8	-0.004255	pass
10		-5	-0.002660	pass
20		-4	-0.002128	pass
30		-2	-0.001064	pass
40		-4	-0.002128	pass
50		-2	-0.001064	pass
20	V min.= 3.5	-2	-0.001064	pass
	V max.= 4.2	-4	-0.002128	pass

Band 4:

10 MHz Bandwidth					
Temperature (°C)	Power Supplied (V _{DC})	F _L (MHz)	F _H (MHz)	F _L Limit (MHz)	F _H Limit (MHz)
-30	3.7	1710.4362	1754.7826	1710	1755
-20		1710.4387	1754.7831	1710	1755
-10		1710.4368	1754.7811	1710	1755
0		1710.4375	1754.7805	1710	1755
10		1710.4387	1754.7824	1710	1755
20		1710.4396	1754.7821	1710	1755
30		1710.4387	1754.7827	1710	1755
40		1710.4392	1754.7812	1710	1755
50		1710.4383	1754.7817	1710	1755
20	V min.= 3.5	1710.4385	1754.7816	1710	1755
	V max.= 4.2	1710.4396	1754.7830	1710	1755

Band 5:

10.0 MHz Middle Channel, $f_o = 836.5\text{MHz}$				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-6	-0.007172	2.5
-20		-1	-0.001195	2.5
-10		-2	-0.002391	2.5
0		-6	-0.007172	2.5
10		-1	-0.001195	2.5
20		-2	-0.002391	2.5
30		-2	-0.002391	2.5
40		-3	-0.003586	2.5
50		-1	-0.001195	2.5
20	V min.= 3.5	-2	-0.002391	2.5
	V max.= 4.2	-1	-0.001195	2.5

Band 7:

10 MHz Bandwidth					
Temperature (°C)	Power Supplied (V_{DC})	F_L (MHz)	F_H (MHz)	F_L Limit (MHz)	F_H Limit (MHz)
-30	3.7	2500.4524	2569.7031	2500	2570
-20		2500.4535	2569.7042	2500	2570
-10		2500.4541	2569.7019	2500	2570
0		2500.4551	2569.7061	2500	2570
10		2500.4529	2569.7074	2500	2570
20		2500.4537	2569.7034	2500	2570
30		2500.4544	2569.7024	2500	2570
40		2500.4534	2569.7019	2500	2570
50		2500.455	2569.7051	2500	2570
20	V min.= 3.5	2500.4534	2569.7047	2500	2570
	V max.= 4.2	2500.4562	2569.7061	2500	2570

***** END OF REPORT *****