

## MPE ESTIMATION

FCC ID: **2AO85-T532A**

### 1, Limit for General Population/ Uncontrolled Exposures

| Frequency        | Power density (mW/ cm <sup>2</sup> ) | Averaging time(minutes) |
|------------------|--------------------------------------|-------------------------|
| 300MHz----1.5GHz | F/1500                               | 30                      |
| 1.5GHz---100GHz  | 1.0                                  | 30                      |

### 2, Estimation Result

For BT:

| Mode                                                                       | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (linear) | MPE (mW/cm <sup>2</sup> ) |
|----------------------------------------------------------------------------|--------------------------|--------------------|-----------------------|-------------------|-----------------------|---------------------------|
| 2441                                                                       | -0.41                    | -0.5±1(0.5)        | 1.12                  | -0.47             | 0.90                  | 0.0002                    |
| $Pd = \frac{P_{out} * G}{4\pi r^2} ;$                                      |                          |                    |                       |                   |                       |                           |
| Note:                                                                      |                          |                    |                       |                   |                       |                           |
| Note: The estimation distance is 20cm                                      |                          |                    |                       |                   |                       |                           |
| Note: PK Output power= conducted power.                                    |                          |                    |                       |                   |                       |                           |
| Conducted power see the test report HK2402270809-E, antenna gain=-0.47dBi. |                          |                    |                       |                   |                       |                           |

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.0002 which is < 1.0, RF Exposure testing is not required.

-----The End-----