REPORT No.: SZ18060250W03

TEST REPORT

APPLICANT	:	Entel PCS Telecomunicaciones S.A.
PRODUCT NAME	:	Smartphone
MODEL NAME	:	Smart 9
BRAND NAME	:	ÖWN
FCC ID	:	2AO8VSMART9
STANDARD(S)	:	47 CFR Part 15 Subpart C
TEST DATE	:	2018-06-28 to 2018-07-05
ISSUE DATE	:	2018-07-09

Tested by: Tu Ya'nan

Tu Ya'nan (Test Engineer)

Approved by: Peng Hu

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525

Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Technical Information ····· 4
1.1. Applicant and Manufacturer Information ····· 4
1.2. Equipment Under Test (EUT) Description ····· 4
1.3. Test Standards and Results ····· 5
1.4. Environmental Conditions ····· 5
2. 47 CFR Part 15C Requirements ····· 6
2.1. Antenna requirement ····· 6
2.2. Peak Output Power ····· 6
2.3. Bandwidth ····· 9
2.4. Conducted Spurious Emissions and Band Edge ····· 18
2.5. Power spectral density (PSD) ····· 31
2.6. Conducted Emission ····· 40
2.7. Restricted Frequency Bands ····· 43
2.8. Radiated Emission ····· 55
Annex A Test Uncertainty ····· 71
Annex B Testing Laboratory Information ····· 72

Change History		
Issue	**Date**	**Reason for change**
1.0	2018-07-09	First edition

1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Entel PCS Telecomunicaciones S.A.
Applicant Address:	Costanera Sur 2760, Torre C, Piso 18, las condes,Santiago,Chile
Manufacturer:	Shenzhen Tinno Mobile Technology Corp.
Manufacturer Address:	4/F.,H-3 Building,OCT Eastern Industrial Park. NO.1 XiangShan East Road.,Nan Shan District,Shenzhen,P.R.China.

1.2. Equipment Under Test (EUT) Description

Product Name:	Smartphone
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	V1.0
Software Version:	OWN_SMART_9_8.0
Modulation Type:	DSSS, OFDM
Operating Frequency Range:	802.11b/g/n-20MHz: 2.412GHz - 2.462GHz 802.11n-40MHz: 2.422GHz - 2.452GHz
Channel Number:	802.11b/g/n-20MHz: 11 802.11n-40MHz: 7
Antenna Type:	PIFA Antenna
Antenna Gain:	-2.4dBi

Note 1: The EUT is operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

For 802.11b/g/n-20MHz (2.4GHz band), the frequencies allocated is F (MHz) =2412+5*(n-1) (1<=n<=11). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

For 802.11n-40MHz, the frequencies allocated is F (MHz) =2412+5*(n-1) (3<=n<=9). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).

Note 2: The EUT connected to the serial port of the computer with a serial communication cable, we use the dedicated software to control the EUT continuous transmission.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.203	Antenna Requirement	N/A	N/A	PASS
2	15.247(b)	Peak Output Power	Jul 01, 2018	Tu Ya'nan	PASS
3	15.247(a)	Bandwidth	Jul 01, 2018	Tu Ya'nan	PASS
4	15.247(d)	Conducted Spurious Emission and Band Edge	Jul 01, 2018	Tu Ya'nan	PASS
5	15.247(e)	Power spectral density (PSD)	Jul 01, 2018	Tu Ya'nan	PASS
6	15.207	Conducted Emission	Jun 28, 2018	Wu Zhongwen	PASS
7	15.247(d)	Restricted Frequency Bands	Jul 05, 2018	Wu Zhongwen	PASS
8	15.209, 15.247(d)	Radiated Emission	Jul 05, 2018	Wu Zhongwen	PASS
Note: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2013 and KDB558074 D01 v04 (04/05/2017).					

1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Peak Output Power

2.2.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed1 Watt.

2.2.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please refer ANNEX A(1.5).

2.2.3. Test Result

2.2.3.1 802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	19.10	0.0813	30	1	PASS
6	2437	20.59	0.1146			PASS
11	2462	18.89	0.0774			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	16.38	0.0435	30	1	PASS
6	2437	17.81	0.0604			PASS
11	2462	16.48	0.0445			PASS

2.2.3.2 802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	21.20	0.1318	30	1	PASS
6	2437	22.63	0.1832			PASS
11	2462	20.69	0.1172			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	12.51	0.0178	30	1	PASS
6	2437	13.86	0.0243			PASS
11	2462	12.97	0.0198			PASS

2.2.3.3 802.11n-20MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	21.38	0.1374	30	1	PASS
6	2437	22.62	0.1828			PASS
11	2462	20.76	0.1191			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	12.56	0.0180	30	1	PASS
6	2437	13.87	0.0244			PASS
11	2462	12.96	0.0198			PASS

2.2.3.4 802.11n-40MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	22.08	0.1614	30	1	PASS
6	2437	22.29	0.1694			PASS
9	2452	21.82	0.1521			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	13.08	0.0203	30	1	PASS
6	2437	13.55	0.0226			PASS
9	2452	12.76	0.0189			PASS

2.3. Bandwidth

2.3.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 8.1 Option 1 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX A(1.5).

2.3.3. Test Result

2.3.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.582	≥500	PASS
6	2437	9.052	≥500	PASS
11	2462	9.085	≥500	PASS

B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 6, 2437 MHz, 802.11b)



(Channel 11, 2462MHz, 802.11b)

2.3.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.39	≥500	PASS
6	2437	16.39	≥500	PASS
11	2462	15.80	≥500	PASS

B. Test Plots:



(Channel 1, 2412MHz, 802.11g)



(Channel 6, 2437MHz, 802.11g)



(Channel 11, 2462MHz, 802.11g)

2.3.3.3 802.11n-20 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.37	≥500	PASS
6	2437	17.37	≥500	PASS
11	2462	16.40	≥500	PASS

B. Test Plots:



(Channel 1, 2412MHz, 802.11n-20)



(Channel 6, 2437MHz, 802.11n-20)



(Channel 11, 2462MHz, 802.11n-20)

2.3.3.4 802.11n-40 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	35.16	≥500	PASS
6	2437	35.23	≥500	PASS
9	2452	35.17	≥500	PASS

B. Test Plots:



(Channel 3, 2422Mz, 802.11n-40)



(Channel 6, 2437MHz, 802.11n-40)



(Channel 9, 2452MHz, 802.11n-40)

2.4. Conducted Spurious Emissions and Band Edge

2.4.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 11.0 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX A(1.5).

2.4.3. Test Result

2.4.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-37.28	6.07	-13.93	PASS
6	2437	-41.37	7.50	-12.50	PASS
11	2462	-47.58	6.80	-13.20	PASS

B. Test Plots:

Note: The power of the Module transmitting frequency should be ignored.



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)

(Band Edge, Channel = 11)

2.4.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-50.68	1.45	-18.55	PASS
6	2437	-52.20	0.37	-19.63	PASS
11	2462	-53.63	2.09	-17.91	PASS

B. Test Plots:

Note: The power of the Module transmitting frequency should be ignored.



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)

(Band Edge, Channel = 11)

2.4.3.3 802.11n -20MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-50.48	2.95	-17.05	PASS
6	2437	-53.65	3.54	-16.46	PASS
11	2462	-53.58	3.25	-16.75	PASS

B. Test Plots:

Note: The power of the Module transmitting frequency should be ignored.



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)

(Band Edge, Channel = 11)

2.4.3.4 802.11n -40MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-50.37	-0.07	-20.07	PASS
6	2437	-53.75	1.90	-18.10	PASS
9	2452	-53.18	-0.55	-20.55	PASS

B. Test Plots:

Note: The power of the Module transmitting frequency should be ignored.



(Channel = 3, 30MHz to 25GHz)



(Band Edge, Channel = 3)



(Channel = 6, 30MHz to 25GHz)



(Channel = 9, 30MHz to 25GHz)

(Band Edge, Channel = 9)

2.5. Power spectral density (PSD)

2.5.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.5.2. Test Description

A. Test procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

a) Set analyzer center frequency to channel center frequency.
b) Set the span to 1.5 times DTS
c) Set the RBW to 3 kHz
d) Set the VBW to 10 kHz
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.

B. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

KDB 558074 Section 10.2 was used in order to prove compliance.

C. Equipments List:

Please refer ANNEX A(1.5).

2.5.3. Test Result

2.5.3.1 802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-5.52	8	PASS
6	2437	-3.56	8	PASS
11	2462	-5.40	8	PASS

B. Test Plots:

(Channel = 1, 802.11b)

(Channel = 6, 802.11b)

(Channel = 11, 802.11b)

2.5.3.2 802.11g Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-10.73	8	PASS
6	2437	-6.49	8	PASS
11	2462	-10.67	8	PASS

B. Test Plots:



(Channel = 1, 802.11g)



(Channel = 6, 802.11g)



(Channel = 11, 802.11g)

2.5.3.3 802.11n-20MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-10.37	8	PASS
6	2437	-9.71	8	PASS
11	2462	-10.68	8	PASS

B. Test Plots:



(Channel = 1, 802.11n-20MHz)



(Channel = 6, 802.11n-20MHz)



(Channel = 11, 802.11n-20MHz)

2.5.3.4 802.11n-40MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-12.76	8	PASS
6	2437	-12.68	8	PASS
9	2452	-13.86	8	PASS

B. Test Plots:



(Channel = 3, 802.11n-40MHz)



(Channel = 6, 802.11n-40MHz)



(Channel = 9, 802.11n-40MHz)

2.6. Conducted Emission

2.6.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.6.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.

B. Equipments List:

Please refer ANNEX A(1.5).

2.6.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test setup:

The EUT configuration of the emission tests is EUT + Link.

Note: The test voltage is AC 120V/60Hz.

B. Test Plots:



(Plot A: L Phase)

NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.30	31.19	25.40	60.11	50.11	Line	PASS
2	0.68	34.34	26.83	56.00	46.00		PASS
3	1.14	33.66	23.61	56.00	46.00		PASS
4	2.46	44.96	34.16	56.00	46.00		PASS
5	3.86	44.87	33.90	56.00	46.00		PASS
6	11.29	44.15	34.49	60.00	50.00		PASS



(Plot B: N Phase)

NO.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.17	35.95	30.15	64.96	54.96	Neutral	PASS
2	0.68	34.06	25.54	56.00	46.00		PASS
3	1.40	34.17	25.66	56.00	46.00		PASS
4	2.55	42.13	30.48	56.00	46.00		PASS
5	5.17	41.90	31.35	60.00	50.00		PASS
6	10.27	44.63	33.46	60.00	50.00		PASS

2.7. Restricted Frequency Bands

2.7.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.7.2. Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

KDB 558074 Section 12.1 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX A(1.5).

2.7.3. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:
E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]-G_{preamp} [dB]
A_T: Total correction Factor except Antenna
U_R: Receiver Reading
G_{preamp}: Preamplifier Gain
A_{Factor}: Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.6.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
1	2387.92	PK	49.78	-33.63	32.56	48.71	74	Pass
1	2387.81	AV	38.72	-33.63	32.56	37.65	54	Pass
11	2487.65	PK	48.56	-33.18	32.50	47.88	74	Pass
11	2484.71	AV	38.42	-33.18	32.50	37.74	54	Pass

B. Test Plots:

(Channel = 1 PEAK, 802.11b)

(Channel = 1 AVG, 802.11b)

(Channel = 11 PEAK, 802.11b)

(Channel = 11 AVG, 802.11b)

2.6.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
1	2389.82	PK	63.09	-33.63	32.56	62.02	74	Pass
1	2389.94	AV	45.78	-33.63	32.56	44.71	54	Pass
11	2483.53	PK	64.08	-33.18	32.50	63.40	74	Pass
11	2483.53	AV	45.12	-33.18	32.50	44.44	54	Pass

B. Test Plots:



(Channel = 1 PEAK, 802.11g)



(Channel = 1 AVG, 802.11g)

(Channel = 11 PEAK, 802.11g)

(Channel = 11 AVG, 802.11g)

2.6.3.3 802.11n-20MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBµV/m)	Limit (dBµV/m)	Verdict
1	2389.78	PK	65.67	-33.63	32.56	64.60	74	Pass
1	2389.82	AV	47.07	-33.63	32.56	46.00	54	Pass
11	2484.15	PK	66.78	-33.18	32.50	66.10	74	Pass
11	2483.62	AV	47.38	-33.18	32.50	46.70	54	Pass

B. Test Plots:



(Channel = 1 PEAK, 802.11n-20)



(Channel = 1 AVG, 802.11n-20)

(Channel = 11 PEAK, 802.11n-20)

(Channel = 11 AVG, 802.11n-20)

2.6.3.4 802.11n-40MHz Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector PK/ AV	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
3	2389.67	PK	61.63	-33.63	32.56	60.56	74	Pass
3	2389.43	AV	46.35	-33.63	32.56	45.28	54	Pass
9	2484.20	PK	66.95	-33.18	32.50	66.27	74	Pass
9	2483.65	AV	49.88	-33.18	32.50	49.20	54	Pass

B. Test Plots:



(Channel = 3 PEAK, 802.11n-40)



(Channel = 3 AVG, 802.11n-40)

(Channel = 9 PEAK, 802.11n-40)



(Channel = 9 AVG, 802.11n-40)

2.8. Radiated Emission

2.8.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)

2.8.2. Test Description

A. Test Setup:

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading

For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

A. Equipments List:

Please refere ANNEX A(1.5).

2.8.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]

A_T: Total correction Factor except Antenna

U_R: Receiver Reading

G_{preamp}: Preamplifier Gain

A_{Factor}: Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
Note2: For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.
Note3: For the frequency, which started from 25GHz to 40GHz, was pre-scanned and the result which was 10dB lower than the limit was not recorded.

2.8.3.1 802.11b Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	35.86	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
165.970	34.51	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1475.710	45.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2588.475	46.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4490.089	47.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
19989.634	49.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
56.708	37.85	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
165.970	29.23	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
549.599	30.86	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1629.372	44.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8575.777	46.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12897.727	46.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	32.25	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
165.970	33.08	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1834.254	45.91	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4608.220	46.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8649.100	47.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
20555.847	49.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
60.350	36.02	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
165.970	31.45	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1780.472	45.29	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4457.501	45.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9125.696	46.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
22270.777	49.32	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
136.834	30.59	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
238.811	32.77	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1517.327	44.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4734.497	46.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8962.757	46.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
21574.213	50.33	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	36.33	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
165.970	27.28	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1688.916	45.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5259.975	46.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9101.255	47.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20152.573	49.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

2.8.3.2 802.11g Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
165.970	33.66	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
238.811	31.35	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1625.530	43.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4465.648	44.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12180.797	46.85	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
18164.721	48.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
56.708	36.65	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
195.106	27.27	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1592.237	45.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4490.089	46.29	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8791.671	46.94	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20103.692	49.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
165.970	31.94	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
238.811	30.25	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1459.704	44.45	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5003.346	45.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9019.785	46.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
24042.735	51.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
51.852	31.22	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
240.025	31.99	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1948.860	44.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4473.795	46.14	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8583.924	46.29	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20124.059	49.00	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
136.834	31.02	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
240.025	32.35	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1715.166	44.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6196.872	45.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10408.838	46.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
21305.365	49.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
59.136	36.78	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
159.900	27.77	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1565.986	45.03	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5744.717	47.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9052.373	47.66	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
21456.083	49.81	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

2.8.3.3 802.11n-20MHz Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	34.43	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
165.970	34.64	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2491.797	48.29	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5667.321	47.29	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12127.841	47.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
22221.895	50.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
59.136	36.85	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
164.756	28.73	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1781.753	44.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3610.220	44.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8600.218	46.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20156.647	49.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
159.900	32.68	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
248.523	30.46	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1573.029	44.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5638.807	46.03	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12669.613	47.50	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
20026.296	49.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	35.81	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
165.970	28.82	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1724.770	44.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3345.445	45.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8877.214	46.57	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
23920.531	50.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
139.262	30.31	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
240.025	31.96	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1797.119	45.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3361.738	45.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12510.747	47.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
20201.455	49.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
61.564	36.74	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
293.442	28.03	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1391.196	45.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4722.277	45.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11753.082	46.83	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
22710.711	50.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

2.8.3.4 802.11n-40MHz Test mode

Plots for Channel = 3



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
136.834	31.11	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
243.667	33.10	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1665.226	45.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4465.648	45.33	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8600.218	47.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
18380.615	48.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	35.81	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
164.756	30.64	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1896.359	44.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4738.571	44.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12282.633	47.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20902.091	49.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
165.970	32.52	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
269.161	30.81	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2000.080	45.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5667.321	45.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12579.996	46.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
20095.545	48.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
61.564	35.92	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
180.538	27.20	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1738.856	45.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5398.472	46.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10364.030	47.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20087.398	49.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 9



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
165.970	33.86	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
243.667	34.21	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1722.849	44.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4640.807	45.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11056.519	48.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
21814.548	49.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
60.350	36.88	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
164.756	26.94	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1475.070	45.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4746.718	45.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9015.712	47.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20030.369	49.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	±2.22dB
Power spectral density (PSD)	±2.22dB
Bandwidth	±5%
Conducted Spurious Emission	±2.77 dB
Restricted Frequency Bands	±5%
Radiated Emission	±2.95dB
Conducted Emission	±2.44dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192.

4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Power Splitter	NW521	1506A	Weinschel	2018.04.17	2019.04.16
Attenuator 1	(N/A.)	10dB	Resnet	2018.04.17	2019.04.16
Attenuator 2	(N/A.)	3dB	Resnet	2018.04.17	2019.04.16
EXA Signal Analzyer	MY53470836	N9010A	Agilent	2017.12.03	2018.12.02
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2018.04.17	2019.04.16
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2017.07.13	2018.07.12
LISN	812744	NSLK 8127	Schwarzbeck	2018.05.08	2019.05.07
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2018.05.08	2019.05.07
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

4.3Auxiliary Test Equipment

Equipment Name	Model No.	Brand Name	Manufacturer	Cal.Date	Cal.Due Date
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.4 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0

4.5 Radiated Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
Receiver	MY54130016	N9038A	Agilent	2018.05.08	2019.05.07
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2018.05.08	2019.05.07
Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2017.09.13	2018.09.12
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2018.03.03	2019.03.02
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2017.09.13	2018.09.12
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable(N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

END OF REPORT