

INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a transmitter for a Toy RC Robot Jr operating at 49.890 MHz which is controlled by a crystal. The EUT is powered by one 9.0V 6F22 battery. For more detail information pls. refer to the user manual.

Antenna Type: integral antenna

Antenna Gain: 0dBi(Only radiated measurements are used to show compliance with FCC limits for fundamental and spurious emissions.)

Modulation Type: Pulse modulation

The nominal conducted output power specified: -56.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -58.15dBm (+/- 3dB)

According to the KDB 447498 V06:

The worst-case peak radiated emission for the EUT is 38.9dBuV/m at 3m in the frequency 49.89MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -56.33dBm

The ERP = EIRP - 2.15 = -58.48dBm

which is within the production variation.

The maximum conducted output power specified is -53.0dBm = 0.00001mW

The source-based time-averaging conducted output power = 0.00001mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level of 1mW, so the EUT is considered to comply with SAR requirement without testing.

FCC ID: 2A08XMXW2026A49