



TEST REPORT

Report No...... : **2021-90025**
FCC ID..... : **2AO94-H6**
Applicant..... : **MOKO TECHNOLOGY LIMITED**
Address..... : Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110
Manufacturer..... : MOKO TECHNOLOGY Ltd
Address..... : Factory 201, 107 Pinshun Rd Guixiang community, Guanlan Street, Longhua, Shenzhen, China 518110
Product Name..... : **H6 BLE Beacon**
Trade Mark..... : /
Model/Type reference..... : H6-PNCAX-P
Listed Model(s)..... : H6-PNCA-P, H6-PNCNX-P, H6-PNCN-P, H6-PNCAX, H6-PNCA, H6-PNCNX, H6-PNCN
Standard..... : **FCC 15.247**
Date of Receipt..... : November 08, 2021
Date of Test Date..... : November 08, 2021~ January 06, 2022
Date of issue..... : January 06, 2022
Test result..... : **Pass**

Compiled by:		
(Printed name + Signature)	Chen Zhijun	
Supervised by:		
(Printed name + Signature)	Liu Canhui	
Approved by:		
(Printed name + Signature)	Wang Weixiong	

Testing Laboratory Name..... : **KSIGN Testing Co., Ltd.**
Address..... : Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by KSIGN. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to KSIGN within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

TABLE OF CONTENTS

Page

1. TEST SUMMARY.....	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION.....	3
1.3. TEST DESCRIPTION.....	4
1.4. TEST FACILITY.....	5
1.5. MEASUREMENT UNCERTAINTY.....	6
1.6. ENVIRONMENTAL CONDITIONS.....	6
2. GENERAL INFORMATION.....	7
2.1. GENERAL DESCRIPTION OF EUT.....	7
2.2. OPERATION STATE.....	8
2.3. MEASUREMENT INSTRUMENTS LIST.....	9
2.4. TEST SOFTWARE.....	10
2.5. ANCILLARY EQUIPMENT LIST.....	10
2.6. DESCRIPTION OF SUPPORT UNITS.....	10
3. TEST ITEM AND RESULTS.....	11
3.1. ANTENNA REQUIREMENT.....	11
3.2. CONDUCTED EMISSION.....	12
3.3. SPURIOUS EMISSION (RADIATED).....	13
3.4. BAND EDGE EMISSIONS(RADIATED).....	24
3.5. PEAK OUTPUT POWER.....	29
3.6. POWER SPECTRAL DENSITY.....	33
3.7. 6dB BANDWIDTH.....	38
3.8. DUTY CYCLE.....	43
3.9. CONDUCTED BAND EDGE.....	47
3.10. SPURIOUS RF CONDUCTED EMISSION.....	49
4. EUT TEST PHOTOS.....	52
5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL.....	54

1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

KDB 558074 D01 : The measurement guidance provided herein is applicable only to Digital Transmission System (DTS) devices operating in the 902-928 MHz. 2400-2483.5 MHz and/or 5725-5850 MHz bands under §15.247 of the FCC rules (Title 47 of the Code of Federal Regulations)

ANSI C63.10-2020: American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report Version

Revised No.	Date of issue	Description
01	January 06, 2022	Original

1.3. Test Description

FCC Part 15 Subpart C(15.247)			
Test Item	Standard Section	Result	Test Engineer
	FCC		
Antenna Requirement	15.203	Pass	Chen Zhijun
Conducted Emission	15.207	N/A	N/A
Radiated Emission	15.205&15.209	Pass	Chen Zhijun
Radiated Band Edge	15.205&15.247(d)	Pass	Chen Zhijun
Peak Output Power	15.247(b)	Pass	Chen Zhijun
Power Spectral Density	15.247(e)	Pass	Chen Zhijun
6dB Bandwidth	15.247(a)(2)	Pass	Chen Zhijun
Duty Cycle	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Pass	Chen Zhijun
Conducted Band edge	15.247(d)	Pass	Chen Zhijun
Spurious RF Conducted Emission	15.247(d)	Pass	Chen Zhijun

Note:

The measurement uncertainty is not included in the test result.

1.4. Test Facility

Address of the report laboratory

KSIGN Testing Co., Ltd.

Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L0461

KSIGN Testing Co., Ltd. Has been assessed and proved to be in Compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 4749.01

KSIGN Testing Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence In the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: CN0036

The 3m alternate test site of KSIGN Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: CN0096

FCC-Registration No.: CN1254

KSIGN Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the KSIGN(Guangdong) Testing Co., Ltd. system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device. Below is the best measurement capability for KSIGN(Guangdong) Testing Co., Ltd.

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.42 dB	(1)
Transmitter power Radiated	2.14 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.20 dB	(1)
Radiated Emissions 30~1000MHz	4.70 dB	(1)
Radiated Emissions 1~18GHz	5.00 dB	(1)
Radiated Emissions 18~40GHz	5.54 dB	(1)
Occupied Bandwidth	2.80 dB	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

1.6. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

2. GENERAL INFORMATION

2.1. General Description Of EUT

Test Sample Number 1:	1-1-1(Normal Sample),1-1-2(Engineering Sample)
Product Name:	H6 BLE Beacon
Trade Mark:	/
Model/Type reference:	H6-PNCAX-P
Listed Model(s):	H6-PNCA-P, H6-PNCNX-P, H6-PNCN-P, H6-PNCAX, H6-PNCA H6-PNCNX, H6-PNCN
Model Difference:	The product appearance color and some PCB components in the series models are different, and other power supply methods, safety structures and key components are the same, and have been tested for differences, which will not affect safety and electromagnetic compatibility.
Power Supply(Battery):	DC 3V
Hardware Version:	V1.1
Software Version:	V1.0
Bluetooth	
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Max Peak Output Power:	-0.59dBm
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB Antenna
Antenna gain:	1.82dBi

2.2. Operation State

Operation Frequency List: The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. BLE, 40 channels are provided to the EUT. Channels 00/19/39 were selected for testing.

Operation Frequency List:

Channel	Frequency (MHz)
00	2402
01	2404
⋮	⋮
19	2440
20	2442
21	2444
⋮	⋮
38	2478
39	2480

Note: The display in grey were the channel selected for testing.

Test Channel

Channel	Channel	Frequency (MHz)
Low	00	2402
Middle	19	2440
High	39	2480

Test mode

NO.	TEST MODE DESCRIPTION
1	Low channel TX (2402MHz)
2	Middle channel TX (2440MHz)
3	High channel TX (2480MHz)

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The test software is the nRF_DTM_v0.9.1 which can set the EUT into the individual test modes.

2.3. Measurement Instruments List

Tonscend JS0806-2 Test system					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
1	Spectrum Analyzer	R&S	FSV40-N	101798	03/22/2022
2	Vector Signal Generator	Agilent	N5182A	MY50142520	03/18/2022
3	Analog Signal Generator	HP	83752A	3344A00337	03/18/2022
4	Power Sensor	Agilent	E9304A	MY50390009	03/18/2022
5	Power Sensor	Agilent	E9300A	MY41498315	03/18/2022
6	Wideband Radio Communication Tester	R&S	CMW500	157282	03/18/2022
7	Climate Chamber	Angul	AGNH80L	1903042120	03/18/2022
8	Dual Output DC Power Supply	Agilent	E3646A	MY40009992	03/18/2022
9	RF Control Unit	Tonscend	JS0806-2	/	03/18/2022

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
1	EMI Test Receiver	R&S	ESR	102525	03/18/2022
2	High Pass Filter	Chengdu E-Microwave	OHF-3-18-S	0E01901038	03/22/2022
3	High Pass Filter	Chengdu E-Microwave	OHF-6.5-18-S	0E01901039	03/22/2022
4	Spectrum Analyzer	HP	8593E	3831U02087	03/22/2022
5	Ultra-Broadband logarithmic period Antenna	Schwarzbeck	VULB 9163	01230	03/29/2023
6	Loop Antenna	Beijin ZHINAN	ZN30900C	18050	03/27/2022
7	Spectrum Analyzer	R&S	FSV40-N	101798	03/22/2022
8	Horn Antenna	Schwarzbeck	BBHA 9120 D	2023	03/29/2023
9	Pre-Amplifier	Schwarzbeck	BBV 9745	9745#129	03/22/2022
10	Pre-Amplifier	EMCI	EMC051835SE	980662	03/22/2022

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
1	LISN	R&S	ENV432	1326.6105.02	03/18/2022
2	EMI Test Receiver	R&S	ESR	102524	03/18/2022
3	Manual RF Switch	JS TOYO	/	MSW-01/002	03/18/2022

Note:

1)The Cal. Interval was one year.

2)The cable loss has calculated in test result which connection between each test instruments.

2.4. Test Software

Software name	Model	Version
Conducted emission Measurement Software	EZ-EMC	EMC-Con 3A1.1
Radiated emission Measurement Software	EZ-EMC	FA-03A.2.RE
Bluetooth and WIFI Test System	JS1120-3	2.5.77.0418

2.5. Ancillary Equipment list

Equipment	Model	S/N	Manufacturer	Certificate type
/	/	/	/	/

2.6. Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
1	Adapter	/	GA-QC810	/	
2	USB Cable	/	/	/	

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3. TEST ITEM AND RESULTS

3.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The EUT antenna is PCB antenna (1.82dBi), the directional gain of the antenna less than 6dBi. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

Antenna structure please refer to the EUT internal photographs antenna photo.

3.2. Conducted Emission

Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

1. *Decreasing linearly with logarithm of the frequency.
2. The lower limit shall apply at the transition frequencies.
3. The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Configuration



Test Procedure

1. The EUT was setup according to ANSI C63.10:2020 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

Test Mode:

Please refer to the clause 2.2.

Test Results

Note: The device is powered by an internal battery, so this item is not available.

3.3. Spurious Emission (Radiated)

Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance Meters(at 3m)	
	Peak	Average
Above 1000	74	54


Note:

1. The tighter limit applies at the band edges.
2. Emission Level (dBuV/m)=20log Emission Level (uV/m).


Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2020
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

- (3) From 1 GHz to 10th harmonic:
 RBW=1MHz, VBW=3MHz Peak detector for Peak value.
 RBW=1MHz, VBW=10Hz Peak detector for Peak value.

Test Mode

Please refer to the clause 2.2.

Test Result

9 KHz - 30 MHz

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:


- For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
- Limit line = specific limits (dBuV) + distance extrapolation factor.

Note:

- Measurement = Reading level + Correct Factor
 Correct Factor=Antenna Factor + Cable Loss -Preamplifier Factor
- The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz - 1GHz


Test voltage:	DC 3V
Ant. Pol.:	Horizontal
Test Mode:	TX BLE Mode 2402MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		48.5354	24.90	-15.76	9.14	40.00	-30.86	QP
2		104.8662	26.26	-18.01	8.25	43.50	-35.25	QP
3		265.5824	26.55	-15.45	11.10	46.00	-34.90	QP
4		400.0108	26.00	-10.91	15.09	46.00	-30.91	QP
5		631.0240	26.80	-7.48	19.32	46.00	-26.68	QP
6	*	937.1879	27.31	-3.90	23.41	46.00	-22.59	QP

Emission Level= Read Level+ Correct Factor

Test voltage:	DC 3V
Ant. Pol.:	Vertical
Test Mode:	TX BLE Mode 2402MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		66.5687	28.53	-18.99	9.54	40.00	-30.46	QP
2		97.6954	25.08	-18.02	7.06	43.50	-36.44	QP
3		400.0108	26.17	-10.91	15.26	46.00	-30.74	QP
4		600.1624	25.68	-7.67	18.01	46.00	-27.99	QP
5		666.7380	26.79	-7.29	19.50	46.00	-26.50	QP
6	*	914.4637	27.16	-4.07	23.09	46.00	-22.91	QP

Emission Level= Read Level+ Correct Factor

Note:

Please refer to Appendix A for the difference test results


Above 1GHz

Test voltage:	DC 3V
Ant. Pol.:	Horizontal
Test Mode:	TX BLE Mode 2402MHz




No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		4802.900	48.13	-5.92	42.21	74.00	-31.79	peak
2		5984.400	44.56	-3.84	40.72	74.00	-33.28	peak
3		8092.400	41.37	2.05	43.42	74.00	-30.58	peak
4		10885.500	39.69	5.53	45.22	74.00	-28.78	peak
5		14069.600	37.68	11.14	48.82	74.00	-25.18	peak
6	*	16514.200	36.88	13.79	50.67	74.00	-23.33	peak

Emission Level= Read Level+ Correct Factor




Test voltage:	DC 3V
Ant. Pol.:	Horizontal
Test Mode:	TX BLE Mode 2440MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		4879.400	46.38	-5.72	40.66	74.00	-33.34	peak
2		5987.800	44.17	-3.83	40.34	74.00	-33.66	peak
3		8148.500	40.69	2.04	42.73	74.00	-31.27	peak
4		10343.200	40.02	4.65	44.67	74.00	-29.33	peak
5		12169.000	39.11	8.25	47.36	74.00	-26.64	peak
6	*	17688.900	37.44	13.48	50.92	74.00	-23.08	peak

Emission Level= Read Level+ Correct Factor

Test voltage:	DC 3V
Ant. Pol.:	Vertical
Test Mode:	TX BLE Mode 2440MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		3731.900	52.97	-9.09	43.88	74.00	-30.12	peak
2		4665.200	48.45	-6.31	42.14	74.00	-31.86	peak
3		4984.800	46.68	-5.43	41.25	74.00	-32.75	peak
4		5999.700	50.04	-3.80	46.24	74.00	-27.76	peak
5		13982.900	36.96	11.22	48.18	74.00	-25.82	peak
6	*	16597.500	37.33	13.66	50.99	74.00	-23.01	peak

Emission Level= Read Level+ Correct Factor


Test voltage:	DC 3V
Ant. Pol.:	Horizontal
Test Mode:	TX BLE Mode 2480MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		4666.900	42.72	-6.30	36.42	74.00	-37.58	peak
2		5999.700	43.38	-3.80	39.58	74.00	-34.42	peak
3		8104.300	41.05	2.04	43.09	74.00	-30.91	peak
4		9843.400	39.77	3.73	43.50	74.00	-30.50	peak
5		13663.300	37.35	10.81	48.16	74.00	-25.84	peak
6	*	16419.000	36.48	13.62	50.10	74.00	-23.90	peak

Emission Level= Read Level+ Correct Factor

Test voltage:	DC 3V
Ant. Pol.:	Vertical
Test Mode:	TX BLE Mode 2480MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		3332.400	46.78	-9.98	36.80	74.00	-37.20	peak
2		3728.500	52.02	-9.12	42.90	74.00	-31.10	peak
3		4988.200	45.83	-5.43	40.40	74.00	-33.60	peak
4		5977.600	50.08	-3.85	46.23	74.00	-27.77	peak
5		13891.100	37.29	11.09	48.38	74.00	-25.62	peak
6	*	16524.400	36.54	13.77	50.31	74.00	-23.69	peak

Emission Level= Read Level+ Correct Factor

Note:

1. All modulation modes were tested, and only the worst data of GFSK-1M was recorded in the report.
2. 18GHz-26.5GHz is the background of the site, there is no radiated spurious.


3.4. Band Edge Emissions(Radiated)

Limit

Restricted Frequency Band (MHz)	(dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Note: All restriction bands have been tested, only the worst case is reported.

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2020 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2020 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=10Hz with Peak detector for Average value.

Test Mode


Please refer to the clause 2.2.

Test Results

Note:

1. Measurement = Reading level + Correct Factor
2. Correct Factor=Antenna Factor + Cable Loss -Preamplifier Factor


Test Voltage	DC 3V
Ant. Pol.:	Horizontal
Test Mode:	TX BLE Mode 2402MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		2386.576	51.45	-10.92	40.53	74.00	-33.47	peak
2		2389.803	53.16	-10.92	42.24	74.00	-31.76	peak
3		2390.000	48.33	-10.92	37.41	74.00	-36.59	peak
4		2393.887	55.95	-10.91	45.04	74.00	-28.96	peak
5		2397.079	62.65	-10.92	51.73	74.00	-22.27	peak
6	*	2400.000	62.95	-10.92	52.03	74.00	-21.97	peak

Emission Level= Read Level+ Correct Factor


Test Voltage	DC 3V
Ant. Pol.	Vertical
Test Mode:	TX BLE Mode 2402MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		2372.961	54.30	-10.92	43.38	74.00	-30.62	peak
2		2385.628	51.45	-10.92	40.53	74.00	-33.47	peak
3		2390.000	44.09	-10.92	33.17	74.00	-40.83	peak
4		2396.296	58.23	-10.92	47.31	74.00	-26.69	peak
5		2397.240	58.04	-10.92	47.12	74.00	-26.88	peak
6	*	2400.000	63.30	-10.92	52.38	74.00	-21.62	peak

Emission Level= Read Level+ Correct Factor


Test Voltage	DC 3V
Ant. Pol.	Horizontal
Test Mode:	TX BLE Mode 2480 MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1		2483.500	59.42	-10.88	48.54	74.00	-25.46	peak
2	*	2484.318	62.19	-10.88	51.31	74.00	-22.69	peak
3		2485.075	61.29	-10.88	50.41	74.00	-23.59	peak
4		2488.238	55.62	-10.88	44.74	74.00	-29.26	peak
5		2492.028	53.45	-10.89	42.56	74.00	-31.44	peak
6		2500.000	44.94	-10.88	34.06	74.00	-39.94	peak

Emission Level= Read Level+ Correct Factor

Test Voltage	DC 3V
Ant. Pol.	Vertical
Test Mode:	TX BLE Mode 2480 MHz



No.	Mk.	Freq. MHz	Reading Level (dBuV)	Correct Factor (dB/m)	Measure- ment (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
1	*	2483.500	60.52	-10.88	49.64	74.00	-24.36	peak
2		2484.290	57.48	-10.88	46.60	74.00	-27.40	peak
3		2487.365	56.25	-10.88	45.37	74.00	-28.63	peak
4		2488.335	58.83	-10.88	47.95	74.00	-26.05	peak
5		2489.483	55.55	-10.89	44.66	74.00	-29.34	peak
6		2500.000	42.21	-10.88	31.33	74.00	-42.67	peak

Emission Level= Read Level+ Correct Factor

Note:


All modulation modes were tested, and only the worst data of GFSK-1M was recorded in the report.

3.5. Peak Output Power

Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

Test Configuration



Test

Procedure

1. Connect EUT RF Output port to the Spectrum Analyzer through an RF attenuator.

2. Spectrum Setting:

Peak Detector: $RBW \geq DTS \text{ Bandwidth}$, $VBW \geq 3 * RBW$.

Sweep time=Auto.

Detector= Peak.

Trace mode= Maxhold.

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode

Please refer to the clause 2.2.

Test Result

GFSK-1M:

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK) (dBm)	Limit (dBm)	Result
CH00	2402	-0.59	30	Pass
CH19	2440	-1.04	30	Pass
CH39	2480	-1.45	30	Pass

GFSK - 2M :

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK) (dBm)	Limit (dBm)	Result
CH00	2402	-0.73	30	Pass
CH19	2440	-1.06	30	Pass
CH39	2480	-1.65	30	Pass


TRF No. FCC Part 15.247_R1

Add : Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China


Tel : +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail : info@gdksign.cn Web: www.gdksign.com

GFSK-1M:


2402 MHz



2440 MHz




2480 MHz




GFSK-2M:

2402 MHz




2440 MHz



Date: 9.NOV.2021 08:24:52

2480 MHz




Date: 9.NOV.2021 08:27:29

3.6. Power Spectral Density

Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

Test Configuration



Test Procedure

1. Connect EUT RF Output port to the Spectrum Analyzer through an RF attenuator.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.b-6.ii of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:
 - Set analyzer center frequency to DTS channel center frequency.
 - Set the span to 1.5 times the DTS bandwidth.
 - Set the RBW ≥ 3 kHz
 - Set the VBW $\geq 3 \times$ RBW
 - Detector: peak
 - Sweep time: auto couple
 - Allow trace to fully stabilize.
 - Use the peak marker function to determine the maximum amplitude level.
 - If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Mode

Please refer to the clause 2.2.

Test Result

Note:

 $\text{Power Density(dBm/3kHz)} = \text{Power Density(dBm/10kHz)} - 10 \cdot \log(10/3)$

GFSK-1M:


Frequency	Power Density (dBm/10kHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-11.10	-16.33	8	Pass
2440 MHz	-11.02	-16.25	8	Pass
2480 MHz	-11.49	-16.72	8	Pass

GFSK-2M:

Frequency	Power Density (dBm/10kHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-11.58	-16.81	8	Pass
2440 MHz	-11.94	-17.17	8	Pass
2480 MHz	-12.52	-17.75	8	Pass


GFSK-1M:

2402 MHz




Date: 9.NOV.2021 08:13:42

2440 MHz




Date: 9.NOV.2021 08:17:03

2480 MHz




GFSK-2M :

2402 MHz




2440 MHz



Date: 9.NOV.2021 08:24:59

2480 MHz




Date: 9.NOV.2021 08:27:36

3.7. 6dB Bandwidth

Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

Test Configuration



Test Procedure

1. Connect EUT RF Output port to the Spectrum Analyzer through an RF attenuator.
2. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
3. The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.
4. Spectrum Setting:
6dB bandwidth:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.
 - (6) Allow the trace to stabilize.
 - (7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Mode

Please refer to the clause 2.2.

Test Results**GFSK-1M:**


Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	680	500	Pass
Middle	2440	676	500	Pass
High	2480	672	500	Pass

GFSK-2M:


Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	912	500	Pass
Middle	2440	600	500	Pass
High	2480	1216	500	Pass

GFSK-1M:


2402 MHz



2440 MHz




2480 MHz



Date: 9.NOV.2021 08:18:20


GFSK-2M:

2402 MHz




Date: 9.NOV.2021 08:21:42

2440 MHz



Date: 9.NOV.2021 08:24:32

2480 MHz




Date: 9.NOV.2021 08:27:09

3.8. Duty Cycle

Limit

Test Item	Limit	Frequency Range(MHz)
Duty Cycle	No limit requirement	2400~2483.5

Test Configuration



Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz (the largest available value)

VBW = 8MHz ($\geq$ RBW)

Number of points in Sweep > 100

Detector function = peak

Trace = Clear write

Measure Total and Ton

Calculate Duty Cycle = Ton / Total


Test Mode

Please refer to the clause 2.2.

Test Results

GFSK-1M:





GFSK-2M:

