Report No.: DDT-R17080903-1E1

Issued Date: Dec. 05, 2017

FCC CERTIFICATION TEST REPORT

FOR

Applicant	**:**	Saturn Technology Group, LLC.
Address	**:**	2664-B Saturn St. Brea, Ca. 92821.
Equipment under Test	**:**	CareBaby
Model No.	**:**	BSCMK1
Trade Mark	**:**	/
FCC ID	**:**	2AOA5CCCC0117001
Manufacturer	**:**	Saturn Technology Group, LLC.
Address	**:**	2664-B Saturn St. Brea, Ca. 92821.

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-89201699, **E-mail:** ddt@dgddt.com, http://www.dgddt.com

REPORT

TABLE OF CONTENTS

Test report declares....4
1. Summary of test results.... 6
2. General test information 7
2.1. Description of EUT.... 7
2.2. Accessories of EUT 7
2.3. Assistant equipment used for test 7
2.4. Block diagram of EUT configuration for test.... 8
2.5. Deviations of test standard 8
2.6. Test environment conditions.... 8
2.7. Test laboratory.... 8
2.8. Measurement uncertainty.... 9
3. Equipment used during test 10
4. 6dB Bandwidth.... 11
4.1. Block diagram of test setup 11
4.2. Limits.... 11
4.3. Test Procedure 11
4.4. Test Result 11
4.5. original test data.... 12
5. Conducted peak Output Power 18
5.1. Block diagram of test setup 18
5.2. Limits.... 18
5.3. Test Procedure 18
5.4. Test Result 19
6. Power Spectral Density.... 19
6.1. Block diagram of test setup 19
6.2. Limits.... 19
6.3. Test Procedure 19
6.4. Test Result 20
6.5. original test data.... 20
7. Band Edge and Spurious Emissions (Conducted) 27
7.1. Block diagram of test setup 27
7.2. Limits.... 27
7.3. Test Procedure 27
7.4. Test Result 27
7.5. original test data.... 28
8. Radiated Spurious Emissions 45
8.1. Block diagram of test setup 45
8.2. Limit 46

8.3. Test Procedure 47
8.4. Test result 48
9. Radiated Band Edge Compliance 52
9.1. Block diagram of test setup 52
9.2. Limit 52
9.3. Test Procedure 52
9.4. Test result 52
10. Power Line Conducted Emission 69
10.1. Block diagram of test setup 69
10.2. Power Line Conducted Emission Limits(Class B) 69
10.3. Test Procedure 69
10.4. Test Result 70
11. Antenna Requirements 73
11.1. Limit 73
11.2. Result 73

TEST REPORT DECLARE

Applicant	:	Saturn Technology Group, LLC.
Address	:	2664-B Saturn St. Brea, Ca. 92821.
Equipment under Test	:	CareBaby
Model No	:	BSCMK1
Trade Mark	:	/
Manufacturer	:	Saturn Technology Group, LLC.
Address	:	2664-B Saturn St. Brea, Ca. 92821.

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C

Test procedure used: ANSI C63.10:2013, KDB558074 D01 DTS Meas Guidance V03r02

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-R17080903-1E1		
Date of Receipt:	Oct. 25, 2017	**Date of Test:**	Oct. 25, 2017 ~ Dec. 05, 2017

Prepared By: ***Approved By:***

Sam Li

Sam Li/Engineer ***Kevin Feng/EMC Manager***

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 05, 2017	

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	**Standard**	**Results**
6dB Bandwidth	FCC 15.247 (a) (2)	PASS
Conducted Output Power	FCC 15.247 (b) (3)	PASS
Power Spectral Density	FCC 15.247 (e)	PASS
Band-edge and Spurious Emissions (Conducted)	FCC 15.247 (d)	PASS
Radiated Spurious Emissions	FCC 15.247 (d) FCC 15.209 FCC 15.205	PASS
Radiated Band Edge Compliance	FCC 15.247 (d) FCC 15.209 FCC 15.205	PASS
Power Line Conducted Emission	FCC 15.207	PASS
Antenna requirement	FCC 15.203	PASS

2. General test information

2.1. Description of EUT

EUT* Name	:	CareBaby
Model Number	:	BSCMK1
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 5V/1A from external AC Adapter
Radio Technology	:	IEEE802.11b/g/n
FCC Operation frequency	:	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz
Modulation	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT2, HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Transmitter rate	:	IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps IEEE 802.11n HT40: up to 300 Mbps
Antenna Type	:	Integrated antenna: maximum PK gain 1dBi
Sample Type	:	Series production

Note: EUT is the ab.of equipment under test.

Channle information							
CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
1	2412	5	2432	9	2452	/	/
2	2417	6	2437	10	2457	/	/
3	2422	7	2442	11	2462	/	/
4	2427	8	2447	/	/	/	/

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
AC Adapter	DongGuan AoHai Power Technology Co., Ltd.	A18A-050100U-US2	N/A	Input: AC 100-240V -50/60Hz, Max. 0.2A; Output: DC 5V, 1A

2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN:
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
USB Cable	N/A	N/A	N/A	Length: 1m

2.4. Block diagram of EUT configuration for test



EUT was connected to control to provided by manufacturer which has a USB PORT connector to connect to Notebook, and the Notebook will run a special test software provided by manufacturer to control EUT work in Continuous TX mode (>98% duty cycle), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	/	11	LCH :CH1	2412
	/	11	MCH: CH6	2437
	/	11	HCH: CH11	2462
IEEE 802.11g	/	54	LCH :CH1	2412
	/	54	MCH: CH6	2437
	/	54	HCH: CH11	2462
IEEE 802.11n HT20	/	MCS 7	LCH :CH1	2412
	/	MCS 7	MCH: CH6	2437
	/	MCS 7	HCH: CH11	2462
IEEE 802.11n HT40	/	MCS 7	LCH :CH3	2422
	/	MCS 7	MCH: CH6	2437
	/	MCS 7	HCH: CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.				

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-89201699, E-mail: ddt@dgddt.com, http://www.dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Power Spectral Density	0.74dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz≤ f < 8GHz)
Frequencies Stability	6.7 x 10-8 (Antenna couple methed)
	5.5 x 10-8 (Conducted method)
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz≤ f < 8GHz)
	1.66dB(8GHz≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10-8
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-26GHz)	4.10dB(1-6GHz)
	4.40dB (6GHz-18GHz)
	3.54dB (18GHz-26GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test					
Spectrum analyzer	R&S	FSU26	200071	Oct. 23, 2017	1Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 16, 2017	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 23, 2017	1Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 16, 2017	1Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2017	1Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2017	1Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2017	1Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2017	1Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2017	1Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2017	1Year
Test Software	JS Tonscent	JS1120-3	Ver.2.7	N/A	N/A
USB Data acquisition	Agilent	U2531A	TW55043503	N/A	N/A
Radiated Emission Test 1#					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 16, 2017	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2017	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 17, 2017	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2017	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Nov. 09, 2017	1 Year
Pre-amplifier	TERA-MW	TRLA-0040G35	101303	Oct. 21, 2017	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2017	1Year
RF Cable	N/A	SMAJ-SMAJ-1M+ SMAJ-SMAJ-11M	17070133+17070131	Nov. 08, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESPI	101761	Oct. 21, 2017	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2017	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2017	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2017	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 KHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4. Test Result

Test Mode	Test Channel	Ant	6dB Bandwidth [MHz]	Limit	Verdict

11B	2412	Ant1	9.160	0.5	PASS
11B	2437	Ant1	9.680	0.5	PASS
11B	2462	Ant1	9.320	0.5	PASS
11G	2412	Ant1	16.440	0.5	PASS
11G	2437	Ant1	16.360	0.5	PASS
11G	2462	Ant1	16.360	0.5	PASS
11N20	2412	Ant1	17.320	0.5	PASS
11N20	2437	Ant1	16.800	0.5	PASS
11N20	2462	Ant1	17.640	0.5	PASS
11N40	2412	Ant1	35.360	0.5	PASS
11N40	2437	Ant1	35.600	0.5	PASS
11N40	2462	Ant1	35.360	0.5	PASS

4.5. original test data

6dB Bandwidth_11B_2412_Ant1



6dB Bandwidth_11B_2437_Ant1



Date: 4.DEC.2017 15:56:46

6dB Bandwidth_11B_2462_Ant1



Date: 4.DEC.2017 15:58:09

6dB Bandwidth_11G_2412_Ant1



Date: 4.DEC.2017 16:00:22

6dB Bandwidth_11G_2437_Ant1



Date: 4.DEC.2017 16:02:32

6dB Bandwidth_11G_2462_Ant1



Date: 4.DEC.2017 16:03:55

6dB Bandwidth_11N20SISO_2412_Ant1



Date: 4.DEC.2017 16:20:44

6dB Bandwidth_11N20SISO_2437_Ant1



Date: 4.DEC.2017 16:22:55

6dB Bandwidth_11N20SISO_2462_Ant1



Date: 4.DEC.2017 16:24:18

6dB Bandwidth_11N40SISO_2422_Ant1



Date: 4.DEC.2017 16:14:18

6dB Bandwidth_11N40SISO_2437_Ant1



Date: 4.DEC.2017 16:16:34

6dB Bandwidth_11N40SISO_2452_Ant1



5. Conducted peak Output Power

5.1. Block diagram of test setup

Same as scetion 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

Connect each EUT's antenna output to power sensor by RF cable and attenuator

Measure the PK output power of each antenna port by power sensor.

5.4. Test Result

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1	25.21	30	PASS
11B	2437	Ant1	25.38	30	PASS
11B	2462	Ant1	25.11	30	PASS
11G	2412	Ant1	22.69	30	PASS
11G	2437	Ant1	24.16	30	PASS
11G	2462	Ant1	23.71	30	PASS
11N20SISO	2412	Ant1	22.64	30	PASS
11N20SISO	2437	Ant1	23.72	30	PASS
11N20SISO	2462	Ant1	23.26	30	PASS
11N40SISO	2422	Ant1	22.45	30	PASS
11N40SISO	2437	Ant1	22.43	30	PASS
11N40SISO	2452	Ant1	22.30	30	PASS

6. Power Spectral Density

6.1. Block diagram of test setup

Same as scetion 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test Result

Test Mode	Test Channel	Ant	PSD[dBm/MHz]	Limit[dBm/MHz]	Verdict
11B	2412	Ant1	4.56	8.00	PASS
11B	2437	Ant1	3.86	8.00	PASS
11B	2462	Ant1	4.85	8.00	PASS
11G	2412	Ant1	-0.8	8.00	PASS
11G	2437	Ant1	0.23	8.00	PASS
11G	2462	Ant1	0.23	8.00	PASS
11N20SISO	2412	Ant1	-1.06	8.00	PASS
11N20SISO	2437	Ant1	0.01	8.00	PASS
11N20SISO	2462	Ant1	-0.28	8.00	PASS
11N40SISO	2422	Ant1	-4.62	8.00	PASS
11N40SISO	2437	Ant1	-4.51	8.00	PASS
11N40SISO	2452	Ant1	-4.61	8.00	PASS

6.5. original test data

Maximum Peak power spectral density_11B_2412_Ant1



Maximum Peak power spectral density_11B_2437_Ant1



Date: 4.DEC.2017 15:57:43

Maximum Peak power spectral density_11B_2462_Ant1



Date: 4.DEC.2017 15:59:07

Maximum Peak power spectral density_11G_2412_Ant1



Date: 4.DEC.2017 16:01:20

Maximum Peak power spectral density_11G_2437_Ant1



Date: 4.DEC.2017 16:03:29

Maximum Peak power spectral density_11G_2462_Ant1



Maximum Peak power spectral density_11N20SISO_2412_Ant1



Maximum Peak power spectral density_11N20SISO_2437_Ant1



Date: 4.DEC.2017 16:23:52

Maximum Peak power spectral density_11N20SISO_2462_Ant1



Date: 4.DEC.2017 16:25:16

Maximum Peak power spectral density_11N40SISO_2422_Ant1



Date: 4.DEC.2017 16:15:15

Maximum Peak power spectral density_11N40SISO_2437_Ant1



Date: 4.DEC.2017 16:17:32

Maximum Peak power spectral density_11N40SISO_2452_Ant1



Date: 4.DEC.2017 16:18:55

7. Band Edge and Spurious Emissions (Conducted)

7.1. Block diagram of test setup

Same as scetion 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100KHz
VBW:	300KHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Span	Encompass frequency range to be measured
Number of measurement points	⩾span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Ant1 Result (dBm)	EUT Set Mode	CH or Frequency	Ant1 Result Result (dBm)

EUT Set Mode	CH or Frequency	Ant1 Result (dBm)	EUT Set Mode	CH or Frequency	Ant1 Result Result (dBm)
11b	CH1	PASS	11n HT 20	CH1	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH11	PASS
11g	CH1	PASS	11n HT 40	CH3	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH9	PASS

7.5. original test data

Band Edge

Band-edge for RF Conducted Emissions_11B_2412_Ant1



Band-edge for RF Conducted Emissions_11B_2462_Ant1



Date: 4.DEC.2017 15:59:17

Band-edge for RF Conducted Emissions_11G_2412_Ant1



Date: 4.DEC.2017 16:01:30

Band-edge for RF Conducted Emissions_11G_2462_Ant1



Date: 4.DEC.2017 16:05:03

Band-edge for RF Conducted Emissions_11N20SISO_2412_Ant1



Date: 4.DEC.2017 16:21:52

Band-edge for RF Conducted Emissions_11N20SISO_2462_Ant1



Date: 4.DEC.2017 16:25:26

Band-edge for RF Conducted Emissions_11N40SISO_2422_Ant1



Date: 4.DEC.2017 16:15:25

Band-edge for RF Conducted Emissions_11N40SISO_2452_Ant1


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Marker 4 [T1]
-36.17 dBm
2.484500000 GHz
Ref 25 dBm
Att 20 dB
Offset 0.7 dB
Marker 1 [T1]
0.02 dBm
2.449500000 GHz
Marker 2 [T1]
-39.43 dBm
2.483500000 GHz
Marker 3 [T1]
-46.65 dBm
2.500000000 GHz
1 PK
VIEW
A
LVL
3DB
D1 -19.98 dBm
Center 2.4835 GHz
10 MHz/
Span 100 MHz
Date: 4.DEC.2017 16:19:06

Spurious Emissions

RF Conducted Spurious Emissions_11B_2412_Ant1



Date: 4.DEC.2017 16:29:23



Date: 4.DEC.2017 16:29:35



Date: 4.DEC.2017 16:29:47

RF Conducted Spurious Emissions_11B_2462_Ant1



Date: 4.DEC.2017 16:30:08



Date: 4.DEC.2017 16:30:20



Date: 4.DEC.2017 16:30:32

RF Conducted Spurious Emissions_11G_2412_Ant1



Date: 4.DEC.2017 16:30:54



Date: 4.DEC.2017 16:31:06



Date: 4.DEC.2017 16:31:18

RF Conducted Spurious Emissions_11G_2462_Ant1



Date: 4.DEC.2017 16:31:41



Date: 4.DEC.2017 16:31:53



Date: 4.DEC.2017 16:32:05

RF Conducted Spurious Emissions_11N20SISO_2412_Ant1



Date: 4.DEC.2017 16:32:29



Date: 4.DEC.2017 16:32:41



Date: 4.DEC.2017 16:32:52

RF Conducted Spurious Emissions_11N20SISO_2462_Ant1



Date: 4.DEC.2017 16:33:16



Date: 4.DEC.2017 16:33:28



Date: 4.DEC.2017 16:33:39

RF Conducted Spurious Emissions_11N40SISO_2422_Ant1



Date: 4.DEC.2017 16:34:02



Date: 4.DEC.2017 16:34:14



Date: 4.DEC.2017 16:34:25

RF Conducted Spurious Emissions_11N40SISO_2452_Ant1



Date: 4.DEC.2017 16:34:48



Date: 4.DEC.2017 16:35:00



Date: 4.DEC.2017 16:35:11

8. Radiated Spurious Emissions

8.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz.Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m)= Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

(1) EUT height should be 0.8m for below 1GHz at a semi - anechoic chamber while EUT height should be 1.5m for above 1GHz at full chamber or semi - anechoic chamber ground with absorbers.

(2) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9KHz-30MHz	Active Loop antenna	3 m
30MHz-1GHz	Trilog Broadband Antenna	3 m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6,5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of

Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it’s fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz,110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9KHz to 25GHz were comply with 15.209 limit.
Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in 11b, Tx CH6 mode.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 30-1G.EM6	
Test Date	: 2017-10-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2016 VULB9163 1#/3m/HORIZONTAL
Memo	: 2.4G WIFI		

Data: 1



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	37.55	4.46	12.08	3.77	20.31	40.00	-19.69	QP	HORIZONTAL
2	46.67	2.00	12.23	3.86	18.09	40.00	-21.91	QP	HORIZONTAL
3	100.93	1.28	11.92	4.31	17.51	43.50	-25.99	QP	HORIZONTAL
4	132.69	5.71	7.79	4.50	18.00	43.50	-25.50	QP	HORIZONTAL
5	283.98	2.63	12.84	5.30	20.77	46.00	-25.23	QP	HORIZONTAL
6	434.07	11.79	16.32	5.93	34.04	46.00	-11.96	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 30-1G.EM6	
Test Date	: 2017-10-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2016 VULB9163 1#/3m/VERTICAL
Memo	: 2.4G WIFI		

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	37.95	6.88	12.10	3.77	22.75	40.00	-17.25	QP	VERTICAL
2	63.54	5.49	10.13	4.01	19.63	40.00	-20.37	QP	VERTICAL
3	138.39	4.75	7.50	4.53	16.78	43.50	-26.72	QP	VERTICAL
4	239.99	1.09	11.90	5.09	18.08	46.00	-27.92	QP	VERTICAL
5	338.40	2.02	14.57	5.54	22.13	46.00	-23.87	QP	VERTICAL
6	444.85	13.56	16.40	5.97	35.93	46.00	-10.07	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBµV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBµV/m)	Limit (dBµ V/m)	Margin (dB)	Detector type	Polarization
11b CH1									
4315.00	34.33	33.66	29.12	7.96	46.83	74.00	-27.17	Peak	HORIZONTAL
7409.00	35.22	36.53	30.67	10.78	51.86	74.00	-22.14	Peak	HORIZONTAL
8820.00	31.64	36.72	32.18	11.75	47.93	74.00	-26.07	Peak	HORIZONTAL
10486.00	33.25	36.41	33.25	12.70	49.11	74.00	-24.89	Peak	HORIZONTAL
11370.00	32.22	36.98	34.41	13.56	48.35	74.00	-25.65	Peak	HORIZONTAL
12849.00	32.01	38.65	35.61	14.66	49.71	74.00	-24.29	Peak	HORIZONTAL
4825.00	40.98	33.73	29.32	8.50	53.89	74.00	-20.11	Peak	VERTICAL
6100.00	33.86	35.17	29.27	9.74	49.50	74.00	-24.50	Peak	VERTICAL
8735.00	32.81	36.35	32.07	11.73	48.82	74.00	-25.18	Peak	VERTICAL
9874.00	32.02	36.78	32.87	12.42	48.35	74.00	-25.65	Peak	VERTICAL
10656.00	32.53	36.84	33.43	12.97	48.91	74.00	-25.09	Peak	VERTICAL
13070.00	33.24	38.87	35.64	14.68	51.15	74.00	-22.85	Peak	VERTICAL
11b CH6									
4842.00	36.31	33.73	29.33	8.52	49.23	74.00	-24.77	Peak	HORIZONTAL
6066.00	34.21	35.11	29.24	9.72	49.80	74.00	-24.20	Peak	HORIZONTAL
7409.00	34.30	36.53	30.67	10.78	50.94	74.00	-23.06	Peak	HORIZONTAL
9755.00	31.67	36.66	32.82	12.40	47.91	74.00	-26.09	Peak	HORIZONTAL
10554.00	33.40	36.55	33.31	12.77	49.41	74.00	-24.59	Peak	HORIZONTAL
12356.00	33.43	38.10	35.08	14.52	50.97	74.00	-23.03	Peak	HORIZONTAL
4876.00	39.19	33.72	29.33	8.56	52.14	74.00	-21.86	Peak	VERTICAL
7290.00	33.79	36.44	30.55	10.68	50.36	74.00	-23.64	Peak	VERTICAL
7936.00	33.57	36.69	31.11	11.10	50.25	74.00	-23.75	Peak	VERTICAL
8854.00	31.77	36.87	32.22	11.76	48.18	74.00	-25.82	Peak	VERTICAL
10401.00	32.31	36.50	33.20	12.65	48.26	74.00	-25.74	Peak	VERTICAL
12288.00	31.97	38.01	35.01	14.46	49.43	74.00	-24.57	Peak	VERTICAL
11b CH11									
4910.00	32.99	33.72	29.33	8.58	45.96	54.00	-8.04	Average	HORIZONTAL
4910.00	47.22	33.72	29.33	8.58	60.19	74.00	-13.81	Peak	HORIZONTAL
7341.00	34.05	36.48	30.59	10.72	50.66	74.00	-23.34	Peak	HORIZONTAL
8854.00	32.77	36.87	32.22	11.76	49.18	74.00	-24.82	Peak	HORIZONTAL
10554.00	33.77	36.55	33.31	12.77	49.78	74.00	-24.22	Peak	HORIZONTAL
13104.00	34.30	38.91	35.64	14.70	52.27	74.00	-21.73	Peak	HORIZONTAL
4910.00	33.99	33.72	29.33	8.58	46.96	54.00	-7.04	Average	VERTICAL
4910.00	44.79	33.72	29.33	8.58	57.76	74.00	-16.24	Peak	VERTICAL
6695.00	33.52	35.96	30.14	10.14	49.48	74.00	-24.52	Peak	VERTICAL
8735.00	32.26	36.35	32.07	11.73	48.27	74.00	-25.73	Peak	VERTICAL
10809.00	32.36	37.27	33.64	13.19	49.18	74.00	-24.82	Peak	VERTICAL
12475.00	32.53	38.27	35.21	14.61	50.20	74.00	-23.80	Peak	VERTICAL

Note: 1.30MHz~25GHz: (Scan with 11b mode, 11g mode, 11n HT20 mode and 11n HT40 mode, the worst case is 11b mode)

2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. Radiated Band Edge Compliance

9.1. Block diagram of test setup



9.2. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

9.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2100MHz to 2450MHz and 2450MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

9.4. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 11B 2412MHz		

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2372.72	53.07	26.94	44.32	5.09	40.78	74.00	-33.22	Peak	HORIZONTAL
2	2390.00	52.99	27.00	44.32	5.11	40.78	74.00	-33.22	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 11B 2412MHz		

Data: 1



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2350.88	54.74	26.86	44.32	5.07	42.35	74.00	-31.65	Peak	VERTICAL
2	2390.00	53.21	27.00	44.32	5.11	41.00	74.00	-33.00	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 11B 2462MHz		

Data: 3



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.63	27.34	44.32	5.21	39.86	74.00	-34.14	Peak	HORIZONTAL
2	2488.10	54.56	27.36	44.32	5.22	42.82	74.00	-31.18	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 11B 2462MHz		

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	52.36	27.34	44.32	5.21	40.59	74.00	-33.41	Peak	VERTICAL
2	2489.40	55.02	27.36	44.32	5.22	43.28	74.00	-30.72	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 11G 2412MHz		

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2384.90	59.06	26.99	44.32	5.10	46.83	74.00	-27.17	Peak	HORIZONTAL
2	2389.94	60.73	27.00	44.32	5.11	48.52	74.00	-25.48	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	:	DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6		
Test Date	:	2017-11-30	**Tested By**	:	Sunny
EUT	:	Carebaby	**Model Number**	:	BSCMK1
Power Supply	:	AC 120V/60Hz	**Test Mode**	:	TX mode
Condition	:	Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	:	2017 HF907/3m/VERTICAL
Memo	:	11G 2412MHz			

Data: 5



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2388.40	62.61	27.00	44.32	5.11	50.40	74.00	-23.60	Peak	VERTICAL
2	2390.00	62.04	27.00	44.32	5.11	49.83	74.00	-24.17	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 11G 2462MHz		

Data: 7



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	59.41	27.34	44.32	5.21	47.64	74.00	-26.36	Peak	HORIZONTAL
2	2484.60	62.41	27.34	44.32	5.21	50.64	74.00	-23.36	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 11G 2462MHz		

Data: 8



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	64.44	27.34	44.32	5.21	52.67	74.00	-21.33	Peak	VERTICAL
2	2487.25	57.17	27.35	44.32	5.22	45.42	54.00	-8.58	Average	VERTICAL
3	2487.25	68.34	27.35	44.32	5.22	56.59	74.00	-17.41	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/HORIZONTAL
Memo	: 11N20 2412MHz		

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2387.00	61.27	26.99	44.32	5.11	49.05	74.00	-24.95	Peak	HORIZONTAL
2	2389.94	62.21	27.00	44.32	5.11	50.00	74.00	-24.00	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 11N20 2412MHz		

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2389.38	54.95	27.00	44.32	5.11	42.74	54.00	-11.26	Average	VERTICAL
2	2389.38	66.64	27.00	44.32	5.11	54.43	74.00	-19.57	Peak	VERTICAL
3	2389.94	63.53	27.00	44.32	5.11	51.32	74.00	-22.68	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	:	DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6		
Test Date	:	2017-11-30	**Tested By**	:	Sunny
EUT	:	Carebaby	**Model Number**	:	BSCMK1
Power Supply	:	AC 120V/60Hz	**Test Mode**	:	TX mode
Condition	:	Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	:	2017 HF907/3m/HORIZONTAL
Memo	:	11N20 2462MHz			

Data: 11



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	62.34	27.34	44.32	5.21	50.57	74.00	-23.43	Peak	HORIZONTAL
2	2484.10	64.08	27.34	44.32	5.21	52.31	74.00	-21.69	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G NEW.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2017 HF907/3m/VERTICAL
Memo	: 11N20 2462MHz		

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	64.00	27.34	44.32	5.21	52.23	74.00	-21.77	Peak	VERTICAL
2	2489.25	58.56	27.36	44.32	5.22	46.82	54.00	-7.18	Average	VERTICAL
3	2489.25	67.25	27.36	44.32	5.22	55.51	74.00	-18.49	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2016 HF907/3m/HORIZONTAL
Memo	: 11N40 2422MHz		

Data: 34



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2387.98	39.20	29.77	29.41	6.01	45.57	54.00	-8.43	Average	HORIZONTAL
2	2387.98	50.20	29.77	29.41	6.01	56.57	74.00	-17.43	Peak	HORIZONTAL
3	2390.00	48.31	29.78	29.42	6.03	54.70	74.00	-19.30	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2016 HF907/3m/VERTICAL
Memo	: 11N40 2422MHz		

Data: 33



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2387.70	33.80	29.77	29.41	6.01	40.17	54.00	-13.83	Average	VERTICAL
2	2387.70	48.83	29.77	29.41	6.01	55.20	74.00	-18.80	Peak	VERTICAL
3	2390.00	48.59	29.78	29.42	6.03	54.98	74.00	-19.02	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G.EM6	
Test Date	: 2017-11-30	**Tested By**	: Sunny
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: TX mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2016 HF907/3m/HORIZONTAL
Memo	: 11N40 2452MHz		

Data: 39



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	42.05	30.14	29.71	6.13	48.61	74.00	-25.39	Peak	HORIZONTAL
2	2490.75	40.73	30.17	29.73	6.17	47.34	74.00	-26.66	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	:	DDT 3m Chamber 1#	D:\2017 RE1# Report Data\Q17080903-1E\FCC 1-18G.EM6		
Test Date	:	2017-11-30	**Tested By**	:	Sunny
EUT	:	Carebaby	**Model Number**	:	BSCMK1
Power Supply	:	AC 120V/60Hz	**Test Mode**	:	TX mode
Condition	:	Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	:	2016 HF907/3m/VERTICAL
Memo	:	11N40 2452MHz			

Data: 40



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	37.70	30.14	29.71	6.13	44.26	74.00	-29.74	Peak	VERTICAL
2	2488.75	36.62	30.16	29.71	6.13	43.20	74.00	-30.80	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10. Power Line Conducted Emission

10.1. Block diagram of test setup



10.2. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

10.4. Test Result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.
Note2: "-----" means peak detection; "-----" means average detection
Note3:Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case (AC 120V/60Hz).

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2017 CE report data\Q17080903-1E\CE.EM6	
Test Date	: 2017-11-06	**Tested By**	: Aaron
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: WIFI mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**LISN**	: 2016 ENV216/LINE
Memo	:		

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.18	13.45	9.61	0.02	9.86	32.94	54.55	-21.61	Average	LINE
2	0.18	20.36	9.61	0.02	9.86	39.85	64.55	-24.70	QP	LINE
3	0.25	12.71	9.61	0.02	9.86	32.20	51.60	-19.40	Average	LINE
4	0.25	17.74	9.61	0.02	9.86	37.23	61.60	-24.37	QP	LINE
5	0.49	17.94	9.61	0.02	9.86	37.43	46.10	-8.67	Average	LINE
6	0.49	22.83	9.61	0.02	9.86	42.32	56.10	-13.78	QP	LINE
7	0.78	13.28	9.61	0.03	9.86	32.78	46.00	-13.22	Average	LINE
8	0.78	17.87	9.61	0.03	9.86	37.37	56.00	-18.63	QP	LINE
9	1.12	9.35	9.62	0.03	9.86	28.86	46.00	-17.14	Average	LINE
10	1.12	14.22	9.62	0.03	9.86	33.73	56.00	-22.27	QP	LINE
11	1.47	8.58	9.62	0.03	9.86	28.09	46.00	-17.91	Average	LINE
12	1.47	13.62	9.62	0.03	9.86	33.13	56.00	-22.87	QP	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2017 CE report data\Q17080903-1E\CE.EM6	
Test Date	: 2017-11-06	**Tested By**	: Aaron
EUT	: Carebaby	**Model Number**	: BSCMK1
Power Supply	: AC 120V/60Hz	**Test Mode**	: WIFI mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**LISN**	: 2016 ENV216/NEUTRAL
Memo	:		

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.23	12.67	9.61	0.02	9.86	32.16	52.48	-20.32	Average	NEUTRAL
2	0.23	18.19	9.61	0.02	9.86	37.68	62.48	-24.80	QP	NEUTRAL
3	0.31	12.14	9.61	0.02	9.86	31.63	50.06	-18.43	Average	NEUTRAL
4	0.31	17.39	9.61	0.02	9.86	36.88	60.06	-23.18	QP	NEUTRAL
5	0.49	18.18	9.61	0.02	9.86	37.67	46.14	-8.47	Average	NEUTRAL
6	0.49	22.52	9.61	0.02	9.86	42.01	56.14	-14.13	QP	NEUTRAL
7	0.78	13.08	9.61	0.03	9.86	32.58	46.00	-13.42	Average	NEUTRAL
8	0.78	17.70	9.61	0.03	9.86	37.20	56.00	-18.80	QP	NEUTRAL
9	0.98	9.60	9.61	0.03	9.86	29.10	46.00	-16.90	Average	NEUTRAL
10	0.98	14.44	9.61	0.03	9.86	33.94	56.00	-22.06	QP	NEUTRAL
11	1.35	7.96	9.61	0.03	9.86	27.46	46.00	-18.54	Average	NEUTRAL
12	1.35	12.89	9.61	0.03	9.86	32.39	56.00	-23.61	QP	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are integrated antenna and other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 1dBi.

END OF REPORT