

## **MPE Calculation / RF Exposure**

Product: MentalDoctor Ezbalance

Applicant: HUMAN-LINE

Model: MEZ-300

Address: 5F,sung-eun B/D, 396-4, Gyeongsu-daero, Gwonseon-gu, Suwon-si, Gyeonggi-do,  
Korea(16571)

FCC ID: 2AOBD-MEZ-300

Per KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) section 4.3.1 (a)

Stand alone SAR test exclusion threshold is applied;

a) For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR,

- ♦ where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- ♦ Power and distance are rounded to the nearest mW and mm before calculation
- ♦ The result is rounded to one decimal place for comparison
- ♦ The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

Freq: EDR / 2 480 MHz

Tune-up max. power : 9.00 dBm (7.943 mW)

Min. Test separation distance : 5 mm

SAR exclusion threshold:  $[7.943/5] \times [\sqrt{2.480}] = 2.502$  (=2.5, is rounded to one decimal place)

\* Tune-up tolerance : 8 dBm +/- 1.0 dB

Therefore, the EUT was not evaluated as the value of SAR exclusion threshold was less than 3 per KDB 447498 D01 v06 section 4.3.1(a)