FCC RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.

FOR

Smart Switch Gen3

ISSUED TO
Third Reality, Inc.

NO.9 Nanxu Road, RunZhou District, Zhenjiang, Jiangsu, China

Tested by: Ye Hongji
Date Dec. 09 2020

Approved by: Wei Yanquan
(Chief Engineer)
Date Dec. 09. 2020

Report No.:	BL-SZ2090882-601
EUT Name:	Smart Switch Gen3
Model Name:	3RSS009B (refer section 2.4)
Brand Name:	THIRDREALITY
Test Standard:	47 CFR Part 15 Subpart C
FCC ID:	2AOCT-3RSS009B
Test Conclusion:	Pass
Test Date:	Sep. 29, 2020 ~ Nov. 23, 2020
Date of Issue:	Dec. 09, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL,Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055
TEL: +86-755-66850100, FAX: +86-755-61824271
Email: qc@baluntek.com
www.baluntek.com

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Dec. 09, 2020	Initial Issue

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION) 5

1.1 Identification of the Testing Laboratory 5

1.2 Identification of the Responsible Testing Location 5

1.3 Laboratory Condition 5

1.4 Announce 5

2 PRODUCT INFORMATION 6

2.1 Applicant Information 6

2.2 Manufacturer Information 6

2.3 Factory Information 6

2.4 General Description for Equipment under Test (EUT) 6

2.5 Technical Information 7

2.6 Additional Instructions 8

3 SUMMARY OF TEST RESULTS 10

3.1 Test Standards 10

3.2 Verdict 10

3.3 Test Environments 11

3.4 Test Equipment List 11

3.5 Measurement Uncertainty 12

3.6 Description of Test Setup 13

3.6.1 For Antenna Port Test 13

3.6.2 For AC Power Supply Port Test 13

3.6.3 For Radiated Test (Below 30 MHz) 14

3.6.4 For Radiated Test (30 MHz-1 GHz) 14

3.6.5 For Radiated Test (Above 1 GHz) 15

3.7 Measurement Results Explanation Example 16

3.7.1 For conducted test items: 16

3.7.2 For radiated band edges and spurious emission test: 16

4 TEST ITEMS 17
4.1 Antenna Requirements 17
4.1.1 Relevant Standards 17
4.1.2 Antenna Anti-Replacement Construction 17
4.1.3 Antenna Gain 17
4.2 Output Power 18
4.2.1 Test Limit 18
4.2.2 Test Setup 18
4.2.3 Test Procedure 18
4.2.4 Test Result 19
4.3 Occupied Bandwidth 20
4.3.1 Limit 20
4.3.2 Test Setup 20
4.3.3 Test Procedure 20
4.3.4 Test Result 20
4.4 Conducted Spurious Emission 21
4.4.1 Limit 21
4.4.2 Test Setup 21
4.4.3 Test Procedure 21
4.4.4 Test Result 22
4.5 Band Edge (Authorized-band band-edge) 23
4.5.1 Limit 23
4.5.2 Test Setup 23
4.5.3 Test Procedure 23
4.5.4 Test Result 23
4.6 Conducted Emission 24
4.6.1 Limit 24
4.6.2 Test Setup 24
4.6.3 Test Procedure 24
4.6.4 Test Result 24
4.7 Radiated Spurious Emission 25
4.7.1 Limit 25
4.7.2 Test Setup 25

4.7.3 Test Procedure 25
4.7.4 Test Result 28
4.8 Band Edge (Restricted-band band-edge) 29
4.8.1 Limit 29
4.8.2 Test Setup 29
4.8.3 Test Procedure 29
1.1.1 Test Result 29
4.9 Power Spectral density (PSD) 30
4.9.1 Limit 30
4.9.2 Test Setup 30
4.9.3 Test Procedure 30
4.9.4 Test Result 30
ANNEX A TEST RESULT 31
A.1 Output Power, E.I.R.P, Duty Cycle 31
A.2 Occupied Bandwidth 34
A.3 Conducted Spurious Emissions 38
A.4 Band Edge (Authorized-band band-edge) 44
A.5 Conducted Emissions 47
A.6 Radiated Spurious Emission 47
A.7 Band Edge (Restricted-band band-edge) 65
A.8 Power Spectral Density (PSD) 67
ANNEX B TEST SETUP PHOTOS 69
ANNEX C EUT EXTERNAL PHOTOS 69
ANNEX D EUT INTERNAL PHOTOS 69

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20℃ to 25℃
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

(1) The test report reference to the report template version v6.9.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

(5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.

(6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Third Reality, Inc.
Address	NO.9 Nanxu Road, RunZhou District, Zhenjiang, Jiangsu, China

2.2 Manufacturer Information

Manufacturer	JiangSu HuiTong Group co., ltd
Address	No.24, Block 2, Taohuawu New District, Zhenjiang, Jiangsu, P.R.C

2.3 Factory Information

Factory	JiangSu HuiTong Group co., ltd
Address	No.24, Block 2, Taohuawu New District, Zhenjiang, Jiangsu, P.R.C

2.4 General Description for Equipment under Test (EUT)

EUT Name	Smart Switch Gen3
Model Name Under Test	3RSS009B
Series Model Name	3RSS009Z
Description of Model name differentiation	Only difference is that 3RSS009B and 3RSS009Z has different software and printing.
Serial Number	N/A
Hardware Version	GWA7.820.1069-1(V0.7)
Software Version	V3_v0.00.06
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	BLE, Zigbee

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	BLE: DTS Zigbee: DSSS(IEE802.15.4)
Modulation Type	BLE: GFSK Zigbee: O-QPSK
Product Type	☐ Mobile ☐ Portable ☒ Fix Location
Transfer Rate	BLE: 1 Mbps Zigbee: 250 KHz
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	BLE: 40 (at intervals of 2 MHz) Zigbee: 16 (at intervals of 5 MHz) F_{CH} = 2350 + 5K [MHz], for K=11, 12, …, 26
Tested Channel	BLE: 0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz) Zigbee: 11 (2405 MHz), 18 (2440 MHz), 25 (2475 MHz), 26 (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	2 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel list
Zigbee

Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	**2405**	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	**25**	**2475**
18	**2440**	**26**	**2480**

2.6 Additional Instructions

BLE

EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

During testing. Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	EMI_TEST v1.8		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH0	2402	10.5
	CH19	2440	9.8
	CH39	2480	9.0

Run Software



Zigbee

EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	EMI_TEST v1.8		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
O-QPSK	CH11	2405	10.5
	CH18	2440	10.5
	CH25	2475	9.0
	CH26	2480	-6.6

Run Software



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-17 Edition)	Miscellaneous Wireless Communications Services
2	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	--	Pass[Note1]
2	Output Power	15.247(b)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	Low/Middle/High	ANNEX A.5	N/A
7	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	Low/Middle/High	ANNEX A.8	Pass
10	Receiver Spurious Emissions	--	--	N/A	N/A[Note2]

Note [1]: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note [2]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

3.3 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.0 V

3.4 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2020.06.08	2021.06.07
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2020.06.08	2021.06.07
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2020.06.09	2021.06.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2020.06.09	2021.06.08
LISN	SCHWARZBECK	NSLK 8127	8127-687	2020.06.09	2021.06.08
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW270	100607	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2020.06.08	2021.06.07
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2020.06.08	2021.06.07
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2020.06.08	2021.06.07
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
Temperature Chamber	AHK	SP20	1412	2020.06.10	2021.06.09
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2021.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2021.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2019.01.06	2021.01.05
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2021.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2020.06.08	2021.06.07
Power Amplifier	OPHIR RF	5225F	1037	2020.02.19	2021.02.18
Power Amplifier	OPHIR RF	5273F	1016	2020.02.19	2021.02.18
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Ear Simulator	B&K	4192-L-001	3038758	2020.02.19	2021.02.18
Audio analyzer	B&K	UPL 16	100129	2020.02.28	2021.02.27

3.5 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

3.6 Description of Test Setup

3.6.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable loss is 0.5dB, then the conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

3.6.2 For AC Power Supply Port Test



(Diagram 2)

3.6.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

3.6.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

3.6.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

3.7 Measurement Results Explanation Example

3.7.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.

3.7.2 For radiated band edges and spurious emission test:

$$E = EIRP - 20\log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

4 TEST ITEMS

4.1 Antenna Requirements

4.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

4.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

4.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4.2 Output Power

4.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

4.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.2.3 Test Procedure

a) Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW ≥ DTS bandwidth.

Set VBW ≥ 3 x RBW.

Set span ≥ 3 x RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

4.2.4 Test Result

Please refer to ANNEX A.1.

4.3 Occupied Bandwidth

4.3.1 Limit

FCC §15.247(a); RSS-247, 5.2 (a); RSS-GEN, 6.7

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

4.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 Test Result

Please refer to ANNEX A.2.

4.4 Conducted Spurious Emission

4.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

4.4.4 Test Result

Please refer to ANNEX A.3.

4.5 Band Edge (Authorized-band band-edge)

4.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle ≥ 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥ 3 x RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

4.5.4 Test Result

Please refer to ANNEX A.4.

4.6 Conducted Emission

4.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

4.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

4.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

4.6.4 Test Result

Please refer to ANNEX A.5.

4.7 Radiated Spurious Emission

4.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

4.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands:

a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)

c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).

d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).

e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$E = EIRP – 20\log D + 104.8$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

f) Compare the resultant electric field strength level to the applicable limit.

g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure:

Peak emission levels are measured by setting the instrument as follows:

a) RBW = as specified in Table 1.

b) VBW ≥ 3 x RBW.

c) Detector = Peak.

d) Sweep time = auto.

e) Trace mode = max hold.

f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction:

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

a) The EUT shall be configured to operate at the maximum achievable duty cycle.

b) Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

c) RBW = 1 MHz (unless otherwise specified).

d) VBW ≥ 3 x RBW.

e) Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

f) Averaging type = power (i.e., RMS).

1) As an alternative, the detector and averaging type may be set for linear voltage averaging.

2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.

g) Sweep time = auto.

h) Perform a trace average of at least 100 traces.

i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is 10 log(1/x), where x is the duty cycle.

2) If linear voltage averaging mode was used in step f), then the applicable correction factor is 20 log(1/x), where x is the duty cycle.

3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain:

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test:

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

4.7.4 Test Result

Please refer to ANNEX A.6.

4.8 Band Edge (Restricted-band band-edge)

4.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.10; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

4.8.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

1.1.1 Test Result

Please refer to ANNEX A.7.

4.9 Power Spectral density (PSD)

4.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

4.9.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

4.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.9.4 Test Result

Please refer to ANNEX A.7.

ANNEX A TEST RESULT

A.1 Output Power, E.I.R.P, Duty Cycle

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK (BLE)		dBm	mW	
	dBm	mW			
CH0	12.39	17.34	30	1000	Pass
CH19	11.44	13.93			Pass
CH39	9.93	9.84			Pass

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	O-QPSK (Zigbee)		dBm	mW	
	dBm	mW			
CH11	11.44	13.93	30	1000	Pass
CH18	11.08	12.82			Pass
CH25	9.62	9.16			Pass
CH26	-5.47	0.28			Pass

BLE:

Test plots

GFSK (BLE) CH0

GFSK (BLE) CH19



GFSK (BLE) CH39



Zigbee:

Test plots

O-QPSK (Zigbee) CH11

O-QPSK (Zigbee) CH18



O-QPSK (Zigbee) CH25

O-QPSK (Zigbee) CH26



Duty Cycle Test Data

Band	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)
GFSK (BLE)	10	10	100.00
O-QPSK (Zigbee)	10	10	100.00

Test plots

GFSK (BLE)



O-QPSK (Zigbee)



A.2 Occupied Bandwidth

Test Data

Test Mode	GFSK (BLE)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
CH0	695.557	1028.944	≥500
CH19	695.557	1020.260	≥500
CH39	695.557	1020.260	≥500

Test Mode	O-QPSK (Zigbee)		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (kHz)	6 dB Bandwidth Limits (kHz)
CH11	1608.643	2340.936	≥500
CH18	1231.934	2340.936	≥500
CH25	1362.305	2340.936	≥500
CH26	1289.795	2346.939	≥500

Test plots

6 dB Bandwidth

GFSK (BLE) CH0



GFSK (BLE) CH19



GFSK (BLE) CH39



O-QPSK (Zigbee) CH11



Date: 12.NOV.2020 12:46:45

O-QPSK (Zigbee) CH18



Date: 12.NOV.2020 12:51:45

O-QPSK (Zigbee) CH25



Date: 20.NOV.2020 14:58:17

O-QPSK (Zigbee) CH26

Date: 20.NOV.2020 15:00:45

99% Bandwidth

GFSK (BLE) CH0

Date: 19.OCT.2020 07:54:57

GFSK (BLE) CH19



Date: 19.OCT.2020 07:57:35

GFSK (BLE) CH39



Date: 19.OCT.2020 08:02:44

O-QPSK (Zigbee) CH11



Date: 12.NOV.2020 12:47:32

O-QPSK (Zigbee) CH18



Date: 12.NOV.2020 12:51:54

O-QPSK (Zigbee) CH25



Date: 20.NOV.2020 14:58:26

O-QPSK (Zigbee) CH26



Date: 20.NOV.2020 15:00:54

A.3 Conducted Spurious Emissions

Test Data

GFSK (BLE)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
CH0	-33.63	12.28	-7.72	Pass
CH19	-32.50	11.39	-8.61	Pass
CH39	-33.19	9.57	-10.43	Pass

O-QPSK (Zigbee)				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
CH11	-35.81	9.88	-10.12	Pass
CH18	-35.77	8.78	-11.22	Pass
CH25	-36.56	7.86	-12.14	Pass
CH26	-35.62	-7.05	-27.05	Pass

Test Plots

GFSK (BLE) CH0, CARRIER LEVEL



GFSK (BLE) CH0, SPURIOUS 30 MHz ~ 3 GHz



GFSK (BLE) CH0, SPURIOUS 2 GHz ~ 25 GHz



GFSK (BLE) CH19 CHANNEL, CARRIER LEVEL

GFSK (BLE) CH19, SPURIOUS 30 MHz ~ 3 GHz



Date: 19.OCT.2020 07:58:13

GFSK (BLE) CH19, SPURIOUS 2 GHz ~ 25 GHz



Date: 19.OCT.2020 07:58:31

GFSK (BLE) CH39, CARRIER LEVEL

Date: 19.OCT.2020 08:02:57

GFSK (BLE) CH39, SPURIOUS 30 MHz ~ 3 GHz



Date: 19.OCT.2020 08:03:34

GFSK (BLE) CH39, SPURIOUS 2 GHz ~ 25 GHz



Date: 19.OCT.2020 08:03:48

O-QPSK (Zigbee) CH11, CARRIER LEVEL



O-QPSK (Zigbee) CH11, SPURIOUS 30 MHz ~ 3 GHz



O-QPSK (Zigbee) CH11, SPURIOUS 2 GHz ~ 25 GHz



O-QPSK (Zigbee) CH18, CARRIER LEVEL



O-QPSK (Zigbee) CH18, SPURIOUS 30 MHz ~ 3 GHz



Date: 12.NOV.2020 12:52:38

O-QPSK (Zigbee) CH18, SPURIOUS 2 GHz ~ 25 GHz



Date: 12.NOV.2020 12:52:50

O-QPSK (Zigbee) CH25, CARRIER LEVEL



Date: 20.NOV.2020 14:58:37

O-QPSK (Zigbee) CH25, SPURIOUS 30 MHz ~ 3 GHz



Date: 20.NOV.2020 14:58:53

O-QPSK (Zigbee) CH25, SPURIOUS 2 GHz ~ 25 GHz



Date: 20.NOV.2020 14:59:00

O-QPSK (Zigbee) CH26, CARRIER LEVEL



O-QPSK (Zigbee) CH26, SPURIOUS 30 MHz ~ 3 GHz



O-QPSK (Zigbee) CH26, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

BLE

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
CH0	-39.43	12.28	-7.72	Pass
CH39	-48.95	9.57	-10.43	Pass

Zigbee

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
CH11	-32.51	9.88	-10.12	Pass
CH25	-44.83	7.86	-12.14	Pass
CH26	-42.28	-7.05	-27.05	Pass

Test Plots

GFSK (BLE) CH0, Carrier level

GFSK (BLE) CH0, Reference level



GFSK (BLE) CH0, Band Edge



GFSK (BLE) CH39, Carrier level



GFSK (BLE) CH39, Reference level



GFSK (BLE) CH39, Band Edge



O-QPSK (Zigbee) CH11, Band Edge



Date: 12.NOV.2020 12:49:28

O-QPSK (Zigbee) CH25, Band Edge



Date: 20.NOV.2020 14:59:22

O-QPSK (Zigbee) CH26, Band Edge



Date: 20.NOV.2020 15:01:54

A.5 Conducted Emissions

Note: The EUT only powered by battery, so the Conducted Emission test is not applicable.

A.6 Radiated Spurious Emission

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note [4]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and BLE 1M-Low channel mode is the worst.

Note [5]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Note [6]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots

GFSK (BLE) 30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	51.092	8.49	-27.23	30.0	-21.51	Peak	0.00	200	Horizontal	Pass
2	127.946	13.22	-27.34	33.5	-20.28	Peak	38.00	100	Horizontal	Pass
3	287.956	12.66	-26.09	36.0	-23.34	Peak	161.00	200	Horizontal	Pass
4	319.958	15.20	-25.31	36.0	-20.80	Peak	0.00	200	Horizontal	Pass
5	698.163	20.98	-16.17	36.0	-15.02	Peak	0.00	200	Horizontal	Pass
6	905.691	24.40	-12.46	36.0	-11.60	Peak	0.00	200	Horizontal	Pass

GFSK (BLE) 30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	50.850	9.69	-27.24	30.0	-20.31	Peak	63.00	100	Vertical	Pass
2	156.311	9.80	-25.72	33.5	-23.70	Peak	9.00	200	Vertical	Pass
3	287.956	12.16	-26.09	36.0	-23.84	Peak	48.00	100	Vertical	Pass
4	456.451	16.35	-21.29	36.0	-19.65	Peak	24.00	200	Vertical	Pass
5	725.801	20.72	-15.52	36.0	-15.28	Peak	171.00	200	Vertical	Pass
6	992.484	24.74	-11.24	44.0	-19.26	Peak	0.00	200	Vertical	Pass

O-QPSK (Zigbee) 30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	40.910	10.44	-26.78	30.0	-19.56	Peak	307.00	200	Horizontal	Pass
2	120.187	11.49	-28.00	33.5	-22.01	Peak	351.00	300	Horizontal	Pass
3	127.946	11.77	-27.34	33.5	-21.73	Peak	215.00	100	Horizontal	Pass
4	287.956	13.18	-26.09	36.0	-22.82	Peak	0.00	200	Horizontal	Pass
5	319.958	13.84	-25.31	36.0	-22.16	Peak	0.00	200	Horizontal	Pass
6	934.056	25.72	-11.83	36.0	-10.28	Peak	360.00	200	Horizontal	Pass

O-QPSK (Zigbee) 30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	57.153	9.44	-27.71	30.0	-20.56	Peak	267.00	100	Vertical	Pass
2	150.977	10.94	-26.02	33.5	-22.56	Peak	292.00	100	Vertical	Pass
3	287.956	12.78	-26.09	36.0	-23.22	Peak	360.00	200	Vertical	Pass
4	421.055	15.25	-22.32	36.0	-20.75	Peak	240.00	200	Vertical	Pass
5	607.491	19.00	-17.75	36.0	-17.00	Peak	247.00	100	Vertical	Pass
6	935.996	24.33	-11.71	36.0	-11.67	Peak	9.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK (BLE) CH0 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.300	43.02	-18.25	74.0	-30.98	Peak	251.00	150	Horizontal	Pass
1**	1199.300	30.98	-18.25	54.0	-23.02	AV	251.00	150	Horizontal	Pass
2	2401.700	102.80	-13.33	74.0	28.80	Peak	339.00	150	Horizontal	N/A
2**	2401.700	101.12	-13.33	54.0	47.12	AV	339.00	150	Horizontal	N/A
3	2778.400	50.55	-11.43	74.0	-23.45	Peak	165.00	150	Horizontal	Pass
3**	2778.400	40.72	-11.43	54.0	-13.28	AV	165.00	150	Horizontal	Pass
4	4803.600	51.84	-3.71	74.0	-22.16	Peak	360.00	150	Horizontal	Pass
4**	4803.600	49.24	-3.71	54.0	-4.76	AV	360.00	150	Horizontal	Pass
5	7206.712	50.37	-4.70	74.0	-23.63	Peak	276.00	150	Horizontal	Pass
5**	7206.712	44.99	-4.70	54.0	-9.01	AV	276.00	150	Horizontal	Pass
6	12009.113	52.72	-1.25	74.0	-21.28	Peak	34.00	150	Horizontal	Pass
6**	12009.113	45.93	-1.25	54.0	-8.07	AV	34.00	150	Horizontal	Pass

GFSK(BLE) CH0 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.500	47.73	-18.23	74.0	-26.27	Peak	299.00	150	Vertical	Pass
1**	1197.500	32.50	-18.23	54.0	-21.50	AV	299.00	150	Vertical	Pass
2	2402.300	87.45	-13.32	74.0	13.45	Peak	115.00	150	Vertical	N/A
2**	2402.300	87.25	-13.32	54.0	33.25	AV	115.00	150	Vertical	N/A
3	2805.900	49.72	-11.57	74.0	-24.28	Peak	306.00	150	Vertical	Pass
3**	2805.900	40.18	-11.57	54.0	-13.82	AV	306.00	150	Vertical	Pass
4	4844.400	49.61	-3.89	74.0	-24.39	Peak	360.00	150	Vertical	Pass
4**	4844.400	40.74	-3.89	54.0	-13.26	AV	360.00	150	Vertical	Pass
5	7206.138	51.05	-4.75	74.0	-22.95	Peak	275.00	150	Vertical	Pass
5**	7206.138	45.17	-4.75	54.0	-8.83	AV	275.00	150	Vertical	Pass
6	12244.862	51.89	-0.21	74.0	-22.11	Peak	312.00	150	Vertical	Pass
6**	12244.862	42.45	-0.21	54.0	-11.55	AV	312.00	150	Vertical	Pass

GFSK(BLE) CH19 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.400	42.63	-18.24	74.0	-31.37	Peak	250.00	150	Horizontal	Pass
1**	1199.400	31.79	-18.24	54.0	-22.21	AV	250.00	150	Horizontal	Pass
2	2439.700	102.66	-13.41	74.0	28.66	Peak	330.00	150	Horizontal	N/A
2**	2439.700	101.77	-13.41	54.0	47.77	AV	330.00	150	Horizontal	N/A
3	2926.800	49.98	-11.15	74.0	-24.02	Peak	219.00	150	Horizontal	Pass
3**	2926.800	40.91	-11.15	54.0	-13.09	AV	219.00	150	Horizontal	Pass
4	4880.200	52.74	-4.14	74.0	-21.26	Peak	266.00	150	Horizontal	Pass
4**	4880.200	50.73	-4.14	54.0	-3.27	AV	266.00	150	Horizontal	Pass
5	7319.700	48.31	-4.93	74.0	-25.69	Peak	163.00	150	Horizontal	Pass
5**	7319.700	44.40	-4.93	54.0	-9.60	AV	163.00	150	Horizontal	Pass
6	12201.450	51.66	-0.71	74.0	-22.34	Peak	25.00	150	Horizontal	Pass
6**	12201.450	44.78	-0.71	54.0	-9.22	AV	25.00	150	Horizontal	Pass

GFSK(BLE) CH19 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1195.900	47.06	-18.19	74.0	-26.94	Peak	312.00	150	Vertical	Pass
1**	1195.900	37.12	-18.19	54.0	-16.88	AV	312.00	150	Vertical	Pass
2	2439.700	89.74	-13.41	74.0	15.74	Peak	293.00	150	Vertical	N/A
2**	2439.700	87.97	-13.41	54.0	33.97	AV	293.00	150	Vertical	N/A
3	2723.900	50.50	-10.68	74.0	-23.50	Peak	243.00	150	Vertical	Pass
3**	2723.900	41.19	-10.68	54.0	-12.81	AV	243.00	150	Vertical	Pass
4	4880.000	51.49	-4.13	74.0	-22.51	Peak	162.00	150	Vertical	Pass
4**	4880.000	43.63	-4.13	54.0	-10.37	AV	162.00	150	Vertical	Pass
5	7319.700	49.01	-4.93	74.0	-24.99	Peak	97.00	150	Vertical	Pass
5**	7319.700	42.22	-4.93	54.0	-11.78	AV	97.00	150	Vertical	Pass
6	12243.425	51.20	-0.24	74.0	-22.80	Peak	179.00	150	Vertical	Pass
6**	12243.425	42.20	-0.24	54.0	-11.80	AV	179.00	150	Vertical	Pass

GFSK(BLE) CH39 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1556.700	41.77	-17.96	74.0	-32.23	Peak	0.00	150	Horizontal	Pass
1**	1556.700	32.42	-17.96	54.0	-21.58	AV	0.00	150	Horizontal	Pass
2	2479.800	99.92	-13.20	74.0	25.92	Peak	340.00	150	Horizontal	N/A
2**	2479.800	98.57	-13.20	54.0	44.57	AV	340.00	150	Horizontal	N/A
3	2722.000	50.33	-10.75	74.0	-23.67	Peak	59.00	150	Horizontal	Pass
3**	2722.000	41.25	-10.75	54.0	-12.75	AV	59.00	150	Horizontal	Pass
4	4960.000	53.30	-4.18	74.0	-20.70	Peak	168.00	150	Horizontal	Pass
4**	4960.000	50.53	-4.18	54.0	-3.47	AV	168.00	150	Horizontal	Pass
5	7439.587	49.14	-4.38	74.0	-24.86	Peak	101.00	150	Horizontal	Pass
5**	7439.587	42.32	-4.38	54.0	-11.68	AV	101.00	150	Horizontal	Pass
6	12398.963	51.85	-1.78	74.0	-22.15	Peak	41.00	150	Horizontal	Pass
6**	12398.963	45.42	-1.78	54.0	-8.58	AV	41.00	150	Horizontal	Pass

GFSK(BLE) CH39 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1196.400	45.94	-18.18	74.0	-28.06	Peak	292.00	150	Vertical	Pass
1**	1196.400	34.55	-18.18	54.0	-19.45	AV	292.00	150	Vertical	Pass
2	2479.800	84.02	-13.20	74.0	10.02	Peak	315.00	150	Vertical	N/A
2**	2479.800	82.61	-13.20	54.0	28.61	AV	315.00	150	Vertical	N/A
3	2711.700	50.16	-11.27	74.0	-23.84	Peak	71.00	150	Vertical	Pass
3**	2711.700	39.82	-11.27	54.0	-14.18	AV	71.00	150	Vertical	Pass
4	4960.000	51.75	-4.18	74.0	-22.25	Peak	274.00	150	Vertical	Pass
4**	4960.000	46.52	-4.18	54.0	-7.48	AV	274.00	150	Vertical	Pass
5	7440.450	49.74	-4.33	74.0	-24.26	Peak	116.00	150	Vertical	Pass
5**	7440.450	43.73	-4.33	54.0	-10.27	AV	116.00	150	Vertical	Pass
6	12296.325	51.18	0.04	74.0	-22.82	Peak	360.00	150	Vertical	Pass
6**	12296.325	40.71	0.04	54.0	-13.29	AV	360.00	150	Vertical	Pass

O-QPSK (Zigbee) CH11 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1992.800	47.08	-15.59	74.0	-26.92	Peak	65.00	150	Horizontal	Pass
1**	1992.800	32.68	-15.59	54.0	-21.32	AV	65.00	150	Horizontal	Pass
2	2404.500	103.24	-12.29	74.0	29.24	Peak	195.00	150	Horizontal	N/A
2**	2404.500	100.58	-12.29	54.0	46.58	AV	195.00	150	Horizontal	N/A
3	4811.000	54.20	-3.01	74.0	-19.80	Peak	312.00	150	Horizontal	Pass
3**	4811.000	50.07	-3.01	54.0	-3.93	AV	312.00	150	Horizontal	Pass
4	7213.900	51.99	-4.29	74.0	-22.01	Peak	165.00	150	Horizontal	Pass
4**	7213.900	49.03	-4.29	54.0	-4.97	AV	165.00	150	Horizontal	Pass
5	12022.912	52.51	0.86	74.0	-21.49	Peak	256.00	150	Horizontal	Pass
5**	12022.912	48.48	0.86	54.0	-5.52	AV	256.00	150	Horizontal	Pass
6	17431.425	54.85	3.40	74.0	-19.15	Peak	166.00	150	Horizontal	Pass
6**	17431.425	45.29	3.40	54.0	-8.71	AV	166.00	150	Horizontal	Pass

O-QPSK (Zigbee) CH11 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2006.100	51.59	-15.35	74.0	-22.41	Peak	92.00	150	Vertical	Pass
1**	2006.100	34.23	-15.35	54.0	-19.77	AV	92.00	150	Vertical	Pass
2	2405.500	95.78	-12.32	74.0	21.78	Peak	186.00	150	Vertical	N/A
2**	2405.500	92.99	-12.32	54.0	38.99	AV	186.00	150	Vertical	N/A
3	3645.800	46.36	-6.18	74.0	-27.64	Peak	325.00	150	Vertical	Pass
3**	3645.800	37.13	-6.18	54.0	-16.87	AV	325.00	150	Vertical	Pass
4	6066.800	52.32	-1.91	74.0	-21.68	Peak	23.00	150	Vertical	Pass
4**	6066.800	43.54	-1.91	54.0	-10.46	AV	23.00	150	Vertical	Pass
5	7213.325	50.19	-4.27	74.0	-23.81	Peak	182.00	150	Vertical	Pass
5**	7213.325	41.11	-4.27	54.0	-12.89	AV	182.00	150	Vertical	Pass
6	15775.050	53.96	1.27	74.0	-20.04	Peak	80.00	150	Vertical	Pass
6**	15775.050	44.02	1.27	54.0	-9.98	AV	80.00	150	Vertical	Pass

O-QPSK (Zigbee) CH18 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1994.000	47.57	-15.61	74.0	-26.43	Peak	73.00	150	Horizontal	Pass
1**	1994.000	40.18	-15.61	54.0	-13.82	AV	73.00	150	Horizontal	Pass
2	2439.500	102.85	-12.64	74.0	28.85	Peak	276.00	150	Horizontal	N/A
2**	2439.500	99.19	-12.64	54.0	45.19	AV	276.00	150	Horizontal	N/A
3	4881.000	50.76	-3.45	74.0	-23.24	Peak	163.00	150	Horizontal	Pass
3**	4881.000	44.09	-3.45	54.0	-9.91	AV	163.00	150	Horizontal	Pass
4	7321.713	50.61	-3.65	74.0	-23.39	Peak	180.00	150	Horizontal	Pass
4**	7321.713	47.90	-3.65	54.0	-6.10	AV	180.00	150	Horizontal	Pass
5	12197.713	51.02	0.67	74.0	-22.98	Peak	293.00	150	Horizontal	Pass
5**	12197.713	46.46	0.67	54.0	-7.54	AV	293.00	150	Horizontal	Pass
6	17472.375	55.31	2.87	74.0	-18.69	Peak	26.00	150	Horizontal	Pass
6**	17472.375	46.10	2.87	54.0	-7.90	AV	26.00	150	Horizontal	Pass

O-QPSK (Zigbee) CH18 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1990.700	49.85	-15.51	74.0	-24.15	Peak	89.00	150	Vertical	Pass
1**	1990.700	31.66	-15.51	54.0	-22.34	AV	89.00	150	Vertical	Pass
2	2440.500	97.15	-12.75	74.0	23.15	Peak	180.00	150	Vertical	N/A
2**	2440.500	93.53	-12.75	54.0	39.53	AV	180.00	150	Vertical	N/A
3	3452.400	45.32	-7.61	74.0	-28.68	Peak	268.00	150	Vertical	Pass
3**	3452.400	35.62	-7.61	54.0	-18.38	AV	268.00	150	Vertical	Pass
4	5715.600	51.14	-2.50	74.0	-22.86	Peak	360.00	150	Vertical	Pass
4**	5715.600	41.63	-2.50	54.0	-12.37	AV	360.00	150	Vertical	Pass
5	7321.713	49.40	-3.65	74.0	-24.60	Peak	180.00	150	Vertical	Pass
5**	7321.713	45.97	-3.65	54.0	-8.03	AV	180.00	150	Vertical	Pass
6	17427.751	54.65	3.53	74.0	-19.35	Peak	343.00	150	Vertical	Pass
6**	17427.751	45.52	3.53	54.0	-8.48	AV	343.00	150	Vertical	Pass

O-QPSK (Zigbee) CH25 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1990.700	45.44	-15.51	74.0	-28.56	Peak	55.00	150	Horizontal	Pass
1**	1990.700	30.06	-15.51	54.0	-23.94	AV	55.00	150	Horizontal	Pass
2	2475.200	102.62	-12.42	74.0	28.62	Peak	175.00	150	Horizontal	N/A
2**	2475.200	101.92	-12.42	54.0	47.92	AV	175.00	150	Horizontal	N/A
3	4950.600	52.91	-3.29	74.0	-21.09	Peak	191.00	150	Horizontal	Pass
3**	4950.600	50.04	-3.29	54.0	-3.96	AV	191.00	150	Horizontal	Pass
4	6674.400	52.43	-0.68	74.0	-21.57	Peak	82.00	150	Horizontal	Pass
4**	6674.400	43.22	-0.68	54.0	-10.78	AV	82.00	150	Horizontal	Pass
5	12374.237	51.04	1.34	74.0	-22.96	Peak	246.00	150	Horizontal	Pass
5**	12374.237	44.81	1.34	54.0	-9.19	AV	246.00	150	Horizontal	Pass
6	17474.738	54.11	2.82	74.0	-19.89	Peak	26.00	150	Horizontal	Pass
6**	17474.738	46.66	2.82	54.0	-7.34	AV	26.00	150	Horizontal	Pass

O-QPSK (Zigbee) CH25 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1995.100	51.52	-15.57	74.0	-22.48	Peak	76.00	150	Vertical	Pass
1**	1995.100	35.92	-15.57	54.0	-18.08	AV	76.00	150	Vertical	Pass
2	2475.200	93.56	-12.42	74.0	19.56	Peak	171.00	150	Vertical	N/A
2**	2475.200	92.78	-12.42	54.0	38.78	AV	171.00	150	Vertical	N/A
3	4799.400	49.64	-2.55	74.0	-24.36	Peak	67.00	150	Vertical	Pass
3**	4799.400	39.63	-2.55	54.0	-14.37	AV	67.00	150	Vertical	Pass
4	6719.400	52.34	-1.01	74.0	-21.66	Peak	291.00	150	Vertical	Pass
4**	6719.400	43.55	-1.01	54.0	-10.45	AV	291.00	150	Vertical	Pass
5	7424.062	49.17	-3.98	74.0	-24.83	Peak	148.00	150	Vertical	Pass
5**	7424.062	38.87	-3.98	54.0	-15.13	AV	148.00	150	Vertical	Pass
6	17423.286	55.55	3.67	74.0	-18.45	Peak	57.00	150	Vertical	Pass
6**	17423.286	46.19	3.67	54.0	-7.81	AV	57.00	150	Vertical	Pass

O-QPSK (Zigbee) CH26 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1991.900	46.86	-15.54	74.0	-27.14	Peak	158.00	150	Horizontal	Pass
1**	1991.900	33.00	-15.54	54.0	-21.00	AV	158.00	150	Horizontal	Pass
2	2480.500	102.73	-12.42	74.0	28.73	Peak	212.00	150	Horizontal	N/A
2**	2480.500	99.62	-12.42	54.0	45.62	AV	212.00	150	Horizontal	N/A
3	4959.400	54.03	-3.29	74.0	-19.97	Peak	311.00	150	Horizontal	Pass
3**	4959.400	50.43	-3.29	54.0	-3.57	AV	311.00	150	Horizontal	Pass
4	6679.600	52.40	-0.54	74.0	-21.60	Peak	33.00	150	Horizontal	Pass
4**	6679.600	42.82	-0.54	54.0	-11.18	AV	33.00	150	Horizontal	Pass
5	12402.700	51.95	1.52	74.0	-22.05	Peak	292.00	150	Horizontal	Pass
5**	12402.700	47.52	1.52	54.0	-6.48	AV	292.00	150	Horizontal	Pass
6	17418.301	56.07	3.72	74.0	-17.93	Peak	33.00	150	Horizontal	Pass
6**	17418.301	46.26	3.72	54.0	-7.74	AV	33.00	150	Horizontal	Pass

O-QPSK (Zigbee) CH26 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1993.900	50.34	-15.62	74.0	-23.66	Peak	96.00	150	Vertical	Pass
1**	1993.900	36.14	-15.62	54.0	-17.86	AV	96.00	150	Vertical	Pass
2	2479.500	93.29	-12.44	74.0	19.29	Peak	184.00	150	Vertical	N/A
2**	2479.500	89.51	-12.44	54.0	35.51	AV	184.00	150	Vertical	N/A
3	4961.000	50.10	-3.23	74.0	-23.90	Peak	287.00	150	Vertical	Pass
3**	4961.000	43.51	-3.23	54.0	-10.49	AV	287.00	150	Vertical	Pass
4	6595.400	52.17	-0.93	74.0	-21.83	Peak	0.00	150	Vertical	Pass
4**	6595.400	42.77	-0.93	54.0	-11.23	AV	0.00	150	Vertical	Pass
5	7441.600	48.31	-4.27	74.0	-25.69	Peak	179.00	150	Vertical	Pass
5**	7441.600	41.23	-4.27	54.0	-12.77	AV	179.00	150	Vertical	Pass
6	17431.425	54.87	3.40	74.0	-19.13	Peak	220.00	150	Vertical	Pass
6**	17431.425	46.33	3.40	54.0	-7.67	AV	220.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Data

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK (BLE)	CH0	2390	53.022	32.61	74	20.978	PEAK	Pass
		2390	N/A	N/A	54	N/A	AVERAGE	Pass
GFSK (BLE)	CH39	2483.5	52.973	32.54	74	21.027	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass
O-QPSK (Zigbee)	CH11	2390	53.481	32.61	74	20.519	PEAK	Pass
		2390	N/A	N/A	54	N/A	AVERAGE	Pass
O-QPSK (Zigbee)	CH25	2483.5	53.613	32.54	74	20.387	PEAK	Pass
		2483.5	N/A	N/A	54	N/A	AVERAGE	Pass
O-QPSK (Zigbee)	CH26	2483.5	58.561	32.54	74	15.439	PEAK	Pass
		2483.5	50.939	32.54	54	3.061	AVERAGE	Pass

Test plots

GFSK (BLE) CH0, PEAK



GFSK (BLE) CH39, PEAK



O-QPSK (Zigbee) CH11, PEAK



O-QPSK (Zigbee) CH25, PEAK



O-QPSK (Zigbee) CH26, PEAK



O-QPSK (Zigbee) CH26, AV

O-QPSK (Zigbee) CH26, AV



O-QPSK (Zigbee) CH26, AV



A.8 Power Spectral Density (PSD)

Test Data

BLE

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
CH0	3.46	8	Pass
CH19	2.58	8	Pass
CH39	1.22	8	Pass

Zigbee

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
CH11	-0.02	8	Pass
CH18	-1.70	8	Pass
CH25	-1.92	8	Pass
CH26	-18.78	8	Pass

Test plots

GFSK (BLE) CH0



GFSK (BLE) CH19



GFSK (BLE) CH39



O-QPSK (Zigbee) CH11



Date: 12.NOV.2020 12:50:38

O-QPSK (Zigbee) CH18



Date: 12.NOV.2020 12:53:03

O-QPSK (Zigbee) CH25

Date: 20.NOV.2020 14:59:57

O-QPSK (Zigbee) CH26

Date: 20.NOV.2020 15:02:12

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2090882-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2090882-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2090882-AI.PDF”.

--END OF REPORT--