Prüfbericht-Nr.: *Test Report No.*:	**50107050 001**	**Auftrags-Nr.:** *Order No.*:	114069800	Seite 1 von 31 *Page 1 of 31*
Kunden-Referenz-Nr.: *Client Reference No.*:	N/A	**Auftragsdatum:** *Order date*:	September 29, 2017	
Auftraggeber: *Client*:	Walt Technology Group Co., Ltd, No. 48 Shi Jing Road, Haining, Zhejiang, China 314400			
Prüfgegenstand: *Test item*:	I-CARE TAKER			
Bezeichnung / Typ-Nr.: *Identification / Type No.*:	ICT-17K01			
Auftrags-Inhalt: *Order content*:	FCC Test report			
Prüfgrundlage: *Test specification*:	FCC 47CFR Part 15: Subpart C Section 15.247(DTS)			
Wareneingangsdatum: *Date of receipt*:	10/11/2017			
Prüfmuster-Nr.: *Test sample No.*:	A000629535-005 A000629535-008			
Prüfzeitraum: *Testing period*:	19-Oct-2017 - 19-Oct-2017			
Ort der Prüfung: *Place of testing*:	EMC/RF Laboratory Taipei			
Prüflaboratorium: *Testing laboratory*:	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: *Test result**:	Pass			

geprüft von / *tested by*:			**kontrolliert von /** *reviewed by*:		
2017-11-22	Ryan W. T. Chen / Project Manager		2017-11-22	Arvin Ho/Vice General Manager	
Datum *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*

Sonstiges / *Other*:

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery*:	Prüfmuster vollständig und unbeschädigt *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT
RESULT: Passed

5.1.2 PEAK OUTPUT POWER
RESULT: Passed

5.1.3 6DB BANDWIDTH
RESULT: Passed

5.1.4 POWER DENSITY
RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100KHZ BANDWIDTH
RESULT: Passed

5.1.6 SPURIOUS EMISSION
RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS
RESULT: Passed

Contents

1. GENERAL REMARKS 5
1.1 COMPLEMENTARY MATERIALS 5
2. TEST SITES 6
2.1 TEST LABORATORY 6
2.2 TEST FACILITY 6
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS 7
2.4 TRACEABILITY 8
2.5 CALIBRATION 8
2.6 MEASUREMENT UNCERTAINTY 8
3. GENERAL PRODUCT INFORMATION 9
3.1 PRODUCT FUNCTION AND INTENDED USE 9
3.2 SYSTEM DETAILS AND RATINGS 9
3.3 INDEPENDENT OPERATION MODES 10
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 10
3.5 SUBMITTED DOCUMENTS 10
4. TEST SET-UP AND OPERATION MODES 11
4.1 PRINCIPLE OF CONFIGURATION SELECTION 11
4.2 TEST OPERATION AND TEST SOFTWARE 11
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 11
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 12
4.5 TEST SETUP DIAGRAM 12
5. TEST RESULTS 14
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 14
5.1.1 Antenna Requirement 14
5.1.2 Peak Output Power 15
5.1.3 6dB Bandwidth 16
5.1.4 Power Density 19
5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth 22
5.1.6 Spurious Emission 26
6. SAFETY HUMAN EXPOSURE 27
6.1 RADIO FREQUENCY EXPOSURE COMPLIANCE 27
6.1.1 Electromagnetic Fields 27
7. PHOTOGRAPHS OF THE TEST SET-UP 28

8. LIST OF TABLES 31

9. LIST OF PHOTOGRAPHS..... 31

1. General Remarks

1.1 Complementary Materials

These attachments are integral parts of this test report:

Appendix P: Photo Documentation internal view
(File Name: 50107050APPENDIX P)

Appendix D: Test Result of Radiated Emissions
(File Name: 50107050APPENDIX D)

Test Specifications

The following standards were applied.

Table 1: Applied Standard and Test Levels

Radio
FCC CFR47 Part 15: Subpart C Section 15.247 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r05

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facility

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 340738
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2016-Jul-1st to 2019-Jun-30th

Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manu-facturer	Type	S/N	Last Calibration	Next Calibration
Test Software	Farad	EZ_EMC	Ver. TUV3A1	N/A	N/A
EMI Test Receiver	R&S	ESCI 7	100797	2016/12/30	2017/12/30
Spectrum Analyzer	R&S	FSV 40	100921	2017/05/02	2018/05/01
Spectrum Analyzer	Agilent	N9010A	MY53470241	2017/05/23	2018/05/22
Preamplifier (30MHz -1GHz)	HP	8447D	2944A06641	2016/12/28	2017/12/28
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	2016/12/01	2017/12/01
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM01G18G	060558	2016/11/17	2017/11/17
Bilog Antenna	TESEQ	CBL6111D	29804	2017/08/18	2018/08/18
Horn Antenna	ETS-Lindgren	3117	201918	2017/08/18	2018/08/18
Horn Antenna (18GHz~40GHz)	COM-POWER	AH-840	101031	2016/11/22	2017/11/22
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	2017/06/14	2018/06/14
EMI Test Receiver	R&S	ESCI7	100797	2016/12/30	2017/12/30
LISN (1 phase)	R&S	ENV216	101243	2017/06/18	2018/06/18
LISN	R&S	ENV216	101262	2017/06/22	2018/06/21

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular schedule using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements .

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	± 1 x 10^{-7}
RF power, conducted	± 1.5 dB
RF power density, conducted	± 3 dB
spurious emissions, conducted	± 3 dB
all emissions, radiated	± 6 dB
Temperature	± 1 ºC
Humidity	± 5 %
DC and low frequency voltages	±3 %

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a diaper temperature/humid detector. It contains a Bluetooth 4.0 compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	I-CARE TAKER
Type Identification	ICT-17K01
FCC ID	2AODX-17K01

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequencies	2402~2480 MHz
Channel Spacing	2 MHz
Channel number	40
Operation Voltage	3Vdc
Modulation	GFSK
Antenna gain	0.8 dBi

3.3 Independent Operation Modes

Basic operation modes are:

A. Transmitting
   1. Low channel
   2. Middle channel
   3. High channel
B. Receiving
C. Standby
D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a modify software which makes it possible to control them through a switch.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:
Conducted: A000629535-008
Radiation: A000629535-005

Full test was applied on all test modes, but only worst case was shown

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m

Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Passed**

Test standard	:	LP0002(2016): 2.2, 3.10.1, (3) FCC Part 15.247(b)(4), Part 15.203 and RSS-Gen 8.3
Requirement	:	use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 0.8 dBi. The antenna is a Chip Antenna soldered to the PCB with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT: **Passed**

Test standard	:	LP0002(2016): 3.10.1, (2) FCC Part 15.247(b)(3), RSS-247 5.4(4)
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	1 Watt
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	20-24 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Table 6: Test result of Peak Output Power

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	2402	**-0.78**	0.00084	1
Middle Channel	2440	**-1.74**	0.00067	1
High Channel	2480	**-2.83**	0.00052	1

Pmax: 0.8364 mW

5.1.3 6dB Bandwidth

RESULT: **Passed**

Test standard	:	LP0002(2016): 3.10.1, (5) FCC Part 15.247(a)(2), RSS-247 5.2(1)
Basic standard	:	ANSI C63.10:2013, KDB558074
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 7: Test result of 6dB Bandwidth

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	2402	842.3	>500	Pass
Mid Channel	2440	675.3	>500	Pass
High Channel	2480	676.2	>500	Pass

Table 8: Test result of 99% Bandwidth,

Channel	Channel Frequency (MHz)	99% Bandwidth (kHz)
Mid Channel	2440	1214.6

Test Plot of 6dB Bandwidth

Low Channel

Middle Channel

High Channel

5.1.4 Power Density

RESULT: **Passed**

Test standard	:	LP0002(2016): 3.10.1, (6.2.2) FCC Part 15.247(e) , RSS-247 5.2(2)
Basic standard	:	ANSI C63.10:2013, KDB558074
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 9: Test result of Power Density

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	2402	-15.1	8
Middle Channel	2440	-15.55	8
High Channel	2480	-16.49	8

Test Plot of Power Density

Low Channel



Middle Channel



High Channel



5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT: **Passed**

Test standard	:	LP0002(2016): 3.10.1, (5) FCC part 15.247(d), RSS-247 5.5
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ High
Operation mode	:	A
Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.
Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot 100kHz Conducted Emissions

Low Channel

Middle Channel

High Channel

Test Plot 100kHz RBW of Band Edge

Low Channel



High Channel



5.1.6 Spurious Emission

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2016): 3.10.1, (5)
Basic standard	:	ANSI C63.10:2013
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2016): 2.7 , must comply with the radiated emission limits specified in LP0002(2016): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2016): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

For details refer to Appendix D.

Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: **Passed**

Test standard : FCC KDB Publication 447498 D01 v06
RSS-102 issue 5, Table 1

FCC:
Since maximum peak output power of the transmitter is 0.8364mW < 10mW, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498: Mobile Portable RF Exposure

Canada:

Maximum conducted peak power: 0.8364 mW

Antenna Gain: 0.8 db -> x 1.202

Maximum EIRP available 1.005 mW

==========
Maximum Power available: 1.005 mW
(higher of EIRP or conducted)

Since maximum output power of the transmitter is 1.005 mW < 4mW, hence the EUT is excluded from SAR evaluation according to Table 1 in RSS-102

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)



Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)



Photograph 4: Set-up for Conducted testing



8. List of Tables

Table 1: Applied Standard and Test Levels 5
Table 2: List of Test and Measurement Equipment 7
Table 3: Emission Measurement Uncertainty.....8
Table 4: Basic Information of EUT 9
Table 5: Technical Specification of EUT 9
Table 6: Test result of Peak Output Power 15
Table 7: Test result of 6dB Bandwidth 16
Table 8: Test result of 99% Bandwidth,.....16
Table 9: Test result of Power Density 19

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....28
Photograph 2: Set-up for Spurious Emissions (Back View 1).....29
Photograph 3: Set-up for Spurious Emissions (Back View 2).....29
Photograph 4: Set-up for Conducted testing.....30