

TEST REPORT

Applicant: Zhejiang Lierda Internet of Things Technology Co., Ltd.
Address: Room 1402, Building 1, No.1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov. China.
Equipment Type: DB35 Wi-Fi & BLE Module
Model Name: DB35 (refer to section 2.3)
Brand Name: lierda
FCC ID: 2AOFDL-DB35
Test Standard: 47 CFR Part 15 Subpart C (refer to section 3.1)
Sample Arrival Date: Sep. 30, 2025
Test Date: Oct. 11, 2025 - Nov. 05, 2025
Date of Issue: Nov. 24, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie zhu*Julie zhu***Checked by:** Ye Hongji*Ye Hongji***Approved by:** Tolan Tu
(Testing Director)*Tolan Tu*

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Nov. 24, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments.....	9
4.2	Test Equipment List.....	9
4.3	Test Software List.....	9
4.4	Measurement Uncertainty.....	10
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example.....	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Output Power	15
5.3	Occupied Bandwidth.....	17
5.4	Conducted Spurious Emission.....	18
5.5	Band Edge (Authorized-band band-edge).....	20

5.6	Conducted Emission.....	22
5.7	Radiated Spurious Emission.....	23
5.8	Band Edge (Restricted-band band-edge).....	28
5.9	Power Spectral density (PSD)	29
ANNEX A	TEST RESULT	30
A.1	Output Power	30
A.2	Occupied Bandwidth.....	33
A.3	Conducted Spurious Emissions	40
A.4	Band Edge (Authorized-band band-edge).....	53
A.5	Conducted Emissions	58
A.6	Radiated Emission.....	60
A.7	Band Edge (Restricted-band band-edge).....	92
A.8	Power Spectral Density (PSD).....	102
ANNEX B	TEST SETUP PHOTOS	106
ANNEX C	EUT EXTERNAL PHOTOS.....	106
ANNEX D	EUT INTERNAL PHOTOS.....	106

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Zhejiang Lierda Internet of Things Technology Co., Ltd.
Address	Room 1402, Building 1, No.1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov. China.

2.2 Manufacturer Information

Manufacturer	Zhejiang Lierda Internet of Things Technology Co., Ltd.
Address	Room 1402, Building 1, No.1326, Wenyi West Road, Cangqian street, Yuhang District, Hangzhou, Zhejiang Prov. China.

2.3 General Description for Equipment under Test (EUT)

EUT Name	DB35 Wi-Fi &BLE Module
Model Name Under Test	DB35
Series Model Name	L-NLEDB35-G5NN4-E1, L-NLEDB35-G5NN4-E4
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model names. (this information provided by the applicant)
Hardware Version	01
Software Version	01
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth BLE WIFI 802.11b, 802.11g, 802.11n(HT20/HT40), 802.11ax(HE20)
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n/ax(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11. 802.11n(40 MHz): 2.422 GHz - 2.452 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 3 to 9.
Modulation Technology	DSSS, OFDM, OFDMA
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	Single PCS Antenna
Antenna Gain	2.46 dBi
About the Product	Only the WIFI 802.11b, 802.11g, 802.11n (HT20/40), 802.11ax (HE20) was tested in this report.

802.11ax RU configuration table					
Mode	Full RU (SU)	RU_26	RU_52	RU_106	RU_242
802.11ax20	√	--	--	--	--

Modulation technology	Modulation Type	Transfer Rate (Mbps)(Single RF path)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n-20 MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM	BPSK	13.5/15

(802.11n-40 MHz)	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150
OFDMA (802.11ax-20 MHz)	BPSK	4
	QPSK	16/24/17/26
	16QAM	33/49/34/52
	64QAM	65/73/81/69/77/86
	256QAM	98/108/103/115
	1024QAM	122/135/129/143

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Occupied Bandwidth	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40/ 11ax20	1/6/6.5/13.5/ 4 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
3	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

3.2 Test Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	Pass ^{Note 1}
2	Output Power	15.247 (b)	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247 (a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247 (d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247 (d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247 (d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247 (d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247 (e)	ANNEX A.8	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	48% to 54%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.7℃ to +26.3℃
Working Voltage of the EUT	NV (Normal Voltage)	3.3V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420186	2025.05.21	2026.05.20
Power meter	R&S	NRP8S	101498	2025.07.07	2026.07.06
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Test Antenna-Bi-Log	Schwarzbeck	VULB 9163	01414	2023.11.03	2026.11.02
Test Antenna-Horn	Schwarzbeck	BBHA 9120D	02459	2023.10.26	2026.10.25
Anechoic Chamber	YIHENG	C8-966	N/A	2024.05.15	2027.05.11
EMI Receiver	Keysight	N9038A	MY55330121	2025.04.16	2026.04.15
Filtering unit	balun	SU319F	LW-SZ19D0001F01	N/A	N/A
Switching unit	BALUN	SU319	LW-SZ19D0001S01	N/A	N/A
EMI Receiver	keysight	N9038B	MY61380132	2025.04.01	2026.03.31
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK8127	01009	2025.07.15	2026.07.14
Shielded Enclosure	YiHeng Electronic Co., Ltd	4.3m*2.9m*2.4 m	235	2024.11.05	2027.11.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2025.06.16	2026.06.15
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7. 35m	130	2024.07.13	2027.07.12

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The EUT shall be transmitted at its maximum power control level.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between

bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be

longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Note: All the configurations were pre tested, only the worst configuration has been reported in this report.

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle	Duty Factor
802.11b	12.38	12.51	98.96%	0.05
802.11g	2.06	2.20	93.64%	0.29
802.11n-20 MHz	1.92	2.01	95.38%	0.21
802.11n-40 MHz	0.94	1.05	89.90%	0.46
802.11ax-20 MHz	1.92	2.03	94.92%	0.23

Peak Power Test Data**802.11b Mode:**

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.14	103.28	30	1000	Pass
Middle	22.00	158.49			Pass
High	20.39	109.40			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.56	143.22	30	1000	Pass
Middle	27.32	539.51			Pass
High	21.24	133.05			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.37	137.09	30	1000	Pass
Middle	27.15	518.80			Pass
High	16.59	45.60			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	18.30	67.61	30	1000	Pass
Middle	27.30	537.03			Pass
High	18.19	65.92			Pass

802.11ax-20 MHz(SU) Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.36	136.77	30	1000	Pass
Middle	26.97	497.74			Pass
High	20.13	103.04			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.24	52.97	30	1000	Pass
Middle	19.02	79.80			Pass
High	17.57	57.15			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	14.01	25.18	30	1000	Pass
Middle	19.21	83.37			Pass
High	13.30	21.38			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	13.34	21.58	30	1000	Pass
Middle	19.09	81.10			Pass
High	11.53	14.22			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	10.40	10.96	30	1000	Pass
Middle	19.31	85.31			Pass
High	10.27	10.64			Pass

802.11ax-20 MHz(SU) Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	11.74	14.93	30	1000	Pass
Middle	17.41	55.08			Pass
High	10.48	11.17			Pass

A.2 Occupied Bandwidth

Note: All the configurations were pre tested, only the worst configuration has been reported in this report.

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	10.200000	12.024000	≥500
Middle	10.200000	12.032000	≥500
High	10.200000	12.025000	≥500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	15.800000	17.087000	≥500
Middle	16.000000	17.125000	≥500
High	15.900000	17.030000	≥500

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	15.800000	17.817000	≥500
Middle	16.400000	17.826000	≥500
High	16.200000	17.820000	≥500

802.11n-40MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	35.200000	36.145000	≥500
Middle	35.200000	36.108000	≥500
High	35.200000	36.092000	≥500

802.11ax-20 MHz(SU) Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	19.000000	19.245000	≥500
Middle	18.900000	19.260000	≥500
High	19.000000	19.050000	≥500

Test Plots

6 dB Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL




802.11n-40 MHz MIDDLE CHANNEL




802.11n-40 MHz HIGH CHANNEL




802.11ax-20 MHz(SU) LOW CHANNEL



802.11ax-20 MHz(SU) MIDDLE CHANNEL



802.11ax-20 MHz(SU) HIGH CHANNEL



99% Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



802.11ax-20 MHz(SU) LOW CHANNEL



802.11ax-20 MHz(SU) MIDDLE CHANNEL



802.11ax-20 MHz(SU) HIGH CHANNEL



A.3 Conducted Spurious Emissions

Note ¹: All the configurations were pre tested, only the worst configuration has been reported in this report.

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-34.59	9.91	-10.09	Pass
Middle	-35.89	9.22	-10.78	Pass
High	-35.08	9.12	-10.88	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-34.45	9.26	-10.74	Pass
Middle	-34.77	9.08	-10.92	Pass
High	-33.74	8.90	-11.10	Pass

802.11n-20MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-30.55	9.29	-10.71	Pass
Middle	-37.15	9.18	-10.82	Pass
High	-44.87	9.09	-10.91	Pass

802.11n-40MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-44.36	4.00	-16.00	Pass
Middle	-45.50	6.20	-13.80	Pass
High	-43.70	3.81	-16.19	Pass

802.11ax-20 MHz(SU) Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-43.61	6.79	-13.21	Pass
Middle	-47.57	6.39	-13.61	Pass
High	-45.26	6.20	-13.80	Pass

Test Plots


802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11b MIDDLE CHANNEL CARRIER LEVEL



[illegible]

Keylight Spectrum Analyzer - Jungsik

File Edit View Settings Cursors Math Trace Markers Help

Marker 1 17.065000000000 GHz

Trig: Free Run Avg Type: Log-Pwr Avg Hold: >1/1

PMCP Fast IF Gen/Low #RBW: 40 dB

26.00 GHz 0.000000000000

Mkr1 17.065 00 GHz -37.220 dBm

10 dB/div Ref 26.00 dBm

Log

Start 2.00 GHz Stop 25.00 GHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.198 s (4001 pts)

MARKER	FREQ (GHz)	1	2	FUNCTION	FUNCTION (dBm)	FUNCTION (dBm)
1	N	1	F	17.065 00 GHz	-37.220 dBm	
2	N	1	F	21.147 50 GHz	-36.889 dBm	

SELECT MARKER

Marker 1

Marker 2

Marker 3

Marker 4

Marker 5

Marker 6

Marker 7

Marker 8

Marker 9

Marker 10

Marker 11

Marker 12

Marker 13

Marker 14

Marker 15

Marker 16

Marker 17

Marker 18

Marker 19

Marker 20

Marker 21

Marker 22

Marker 23

Marker 24

Marker 25

Marker 26

Marker 27

Marker 28

Marker 29

Marker 30

Marker 31

Marker 32

Marker 33

Marker 34

Marker 35

Marker 36

Marker 37

Marker 38

Marker 39

Marker 40

Marker 41

Marker 42

Marker 43

Marker 44

Marker 45

Marker 46

Marker 47

Marker 48

Marker 49

Marker 50

Marker 51

Marker 52

Marker 53

Marker 54

Marker 55

Marker 56

Marker 57

Marker 58

Marker 59

Marker 60

Marker 61

Marker 62

Marker 63

Marker 64

Marker 65

Marker 66

Marker 67

Marker 68

Marker 69

Marker 70

Marker 71

Marker 72

Marker 73

Marker 74

Marker 75

Marker 76

Marker 77

Marker 78

Marker 79

Marker 80

Marker 81

Marker 82

Marker 83

Marker 84

Marker 85

Marker 86

Marker 87

Marker 88

Marker 89

Marker 90

Marker 91

Marker 92

Marker 93

Marker 94

Marker 95

Marker 96

Marker 97

Marker 98

Marker 99

Marker 100

Marker 101

Marker 102

Marker 103

Marker 104

Marker 105

Marker 106

Marker 107

Marker 108

Marker 109

Marker 110

Marker 111

Marker 112

Marker 113

Marker 114

Marker 115

Marker 116

Marker 117

Marker 118

Marker 119

Marker 120

Marker 121

Marker 122

Marker 123

Marker 124

Marker 125

Marker 126

Marker 127

Marker 128

Marker 129

Marker 130

Marker 131

Marker 132

Marker 133

Marker 134

Marker 135

Marker 136

Marker 137

Marker 138

Marker 139

Marker 140

Marker 141

Marker 142

Marker 143

Marker 144

Marker 145

Marker 146

Marker 147

Marker 148

Marker 149

Marker 150

Marker 151

Marker 152

Marker 153

Marker 154

Marker 155

Marker 156

Marker 157

Marker 158

Marker 159

Marker 160

Marker 161

Marker 162

Marker 163

Marker 164

Marker 165

Marker 166

Marker 167

Marker 168

Marker 169

Marker 170

Marker 171

Marker 172

Marker 173

Marker 174

Marker 175

Marker 176

Marker 177

Marker 178

Marker 179

Marker 180

Marker 181

Marker 182

Marker 183

Marker 184

Marker 185

Marker 186

Marker 187

Marker 188

Marker 189

Marker 190

Marker 191

Marker 192

Marker 193

Marker 194

Marker 195

Marker 196

Marker 197

Marker 198

Marker 199

Marker 200

Marker 201

Marker 202

Marker 203

Marker 204

Marker 205

Marker 206

Marker 207

Marker 208

Marker 209

Marker 210

Marker 211

Marker 212

Marker 213

Marker 214

Marker 215

Marker 216

Marker 217

Marker 218

Marker 219

Marker 220

Marker 221

Marker 222

Marker 223

Marker 224

Marker 225

Marker 226

Marker 227

Marker 228

Marker 229

Marker 230

Marker 231

Marker 232

Marker 233

Marker 234

Marker 235

Marker 236

Marker 237

Marker 238

Marker 239

Marker 240

Marker 241

Marker 242

Marker 243

Marker 244

Marker 245

Marker 246

Marker 247

Marker 248

Marker 249

Marker 250

Marker 251

Marker 252

Marker 253

Marker 254

Marker 255

Marker 256

Marker 257

Marker 258

Marker 259

Marker 260

Marker 261

Marker 262

Marker 263

Marker 264

Marker 265

Marker 266

Marker 267

Marker 268

Marker 269

Marker 270

Marker 271

Marker 272

Marker 273

Marker 274

Marker 275

Marker 276

Marker 277

Marker 278

Marker 279

Marker 280

Marker 281

Marker 282

Marker 283

Marker 284

Marker 285

Marker 286

Marker 287

Marker 288

Marker 289

Marker 290

Marker 291

Marker 292

Marker 293

Marker 294

Marker 295

Marker 296

Marker 297

Marker 298

Marker 299

Marker 300

Marker 301

Marker 302

Marker 303

Marker 304

Marker 305

Marker 306

Marker 307

Marker 308

Marker 309

Marker 310

Marker 311

Marker 312

Marker 313

Marker 314

Marker 315

Marker 316

Marker 317

Marker 318

Marker 319

Marker 320

Marker 321

Marker 322

Marker 323

Marker 324

Marker 325

Marker 326

Marker 327

Keysight Spectrum Analyzer - Sample 34

Marker 1 2.4605000000 GHz

Trig: Free Run #Atten: 40 dB

Avg Type: Log Pwr Avg Hold: >1s

Center 2.46200 GHz Span 30.00 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.880 ms (601 pts)

Mkr1 2.460 50 GHz 9.123 dBm

Ref 25.00 dBm

10 dBm Log

15.0

10.0

5.00

0.00

-5.00

-10.0

-15.0

-20.0

-25.0

-30.0

-35.0

-40.0

Marker Table

Marker Count (0)

Coupled Markers

All Markers On

More

2 of 2

Keylight Spectrum Analyzer - Sweep 54

0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6 1.7 1.8 1.9 2.0 2.1 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.0 3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9 4.0 4.1 4.2 4.3 4.4 4.5 4.6 4.7 4.8 4.9 5.0 5.1 5.2 5.3 5.4 5.5 5.6 5.7 5.8 5.9 6.0 6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9 7.0 7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9 8.0 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8 8.9 9.0 9.1 9.2 9.3 9.4 9.5 9.6 9.7 9.8 9.9 10.0 10.1 10.2 10.3 10.4 10.5 10.6 10.7 10.8 10.9 11.0 11.1 11.2 11.3 11.4 11.5 11.6 11.7 11.8 11.9 12.0 12.1 12.2 12.3 12.4 12.5 12.6 12.7 12.8 12.9 13.0 13.1 13.2 13.3 13.4 13.5 13.6 13.7 13.8 13.9 14.0 14.1 14.2 14.3 14.4 14.5 14.6 14.7 14.8 14.9 15.0 15.1 15.2 15.3 15.4 15.5 15.6 15.7 15.8 15.9 16.0 16.1 16.2 16.3 16.4 16.5 16.6 16.7 16.8 16.9 17.0 17.1 17.2 17.3 17.4 17.5 17.6 17.7 17.8 17.9 18.0 18.1 18.2 18.3 18.4 18.5 18.6 18.7 18.8 18.9 19.0 19.1 19.2 19.3 19.4 19.5 19.6 19.7 19.8 19.9 20.0 20.1 20.2 20.3 20.4 20.5 20.6 20.7 20.8 20.9 21.0 21.1 21.2 21.3 21.4 21.5 21.6 21.7 21.8 21.9 22.0 22.1 22.2 22.3 22.4 22.5 22.6 22.7 22.8 22.9 23.0 23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 24.0 24.1 24.2 24.3 24.4 24.5 24.6 24.7 24.8 24.9 25.0 25.1 25.2 25.3 25.4 25.5 25.6 25.7 25.8 25.9 26.0 26.1 26.2 26.3 26.4 26.5 26.6 26.7 26.8 26.9 27.0 27.1 27.2 27.3 27.4 27.5 27.6 27.7 27.8 27.9 28.0 28.1 28.2 28.3 28.4 28.5 28.6 28.7 28.8 28.9 29.0 29.1 29.2 29.3 29.4 29.5 29.6 29.7 29.8 29.9 30.0 30.1 30.2 30.3 30.4 30.5 30.6 30.7 30.8 30.9 31.0 31.1 31.2 31.3 31.4 31.5 31.6 31.7 31.8 31.9 32.0 32.1 32.2 32.3 32.4 32.5 32.6 32.7 32.8 32.9 33.0 33.1 33.2 33.3 33.4 33.5 33.6 33.7 33.8 33.9 34.0 34.1 34.2 34.3 34.4 34.5 34.6 34.7 34.8 34.9 35.0 35.1 35.2 35.3 35.4 35.5 35.6 35.7 35.8 35.9 36.0 36.1 36.2 36.3 36.4 36.5 36.6 36.7 36.8 36.9 37.0 37.1 37.2 37.3 37.4 37.5 37.6 37.7 37.8 37.9 38.0 38.1 38.2 38.3 38.4 38.5 38.6 38.7 38.8 38.9 39.0 39.1 39.2 39.3 39.4 39.5 39.6 39.7 39.8 39.9 40.0 40.1 40.2 40.3 40.4 40.5 40.6 40.7 40.8 40.9 41.0 41.1 41.2 41.3 41.4 41.5 41.6 41.7 41.8 41.9 42.0 42.1 42.2 42.3 42.4 42.5 42.6 42.7 42.8 42.9 43.0 43.1 43.2 43.3 43.4 43.5 43.6 43.7 43.8 43.9 44.0 44.1 44.2 44.3 44.4 44.5 44.6 44.7 44.8 44.9 45.0 45.1 45.2 45.3 45.4 45.5 45.6 45.7 45.8 45.9 46.0 46.1 46.2 46.3 46.4 46.5 46.6 46.7 46.8 46.9 47.0 47.1 47.2 47.3 47.4 47.5 47.6 47.7 47.8 47.9 48.0 48.1 48.2 48.3 48.4 48.5 48.6 48.7 48.8 48.9 49.0 49.1 49.2 49.3 49.4 49.5 49.6 49.7 49.8 49.9 50.0 50.1 50.2 50.3 50.4 50.5 50.6 50.7 50.8 50.9 51.0 51.1 51.2 51.3 51.4 51.5 51.6 51.7 51.8 51.9 52.0 52.1 52.2 52.3 52.4 52.5 52.6 52.7 52.8 52.9 53.0 53.1 53.2 53.3 53.4 53.5 53.6 53.7 53.8 53.9 54.0 54.1 54.2 54.3 54.4 54.5 54.6 54.7 54.8 54.9 55.0 55.1 55.2 55.3 55.4 55.5 55.6 55.7 55.8 55.9 56.0 56.1 56.2 56.3 56.4 56.5 56.6 56.7 56.8 56.9 57.0 57.1 57.2 57.3 57.4 57.5 57.6 57.7 57.8 57.9 58.0 58.1 58.2 58.3 58.4 58.5 58.6 58.7 58.8 58.9 59.0 59.1 59.2 59.3 59.4 59.5 59.6 59.7 59.8 59.9 60.0 60.1 60.2 60.3 60.4 60.5 60.6 60.7 60.8 60.9 61.0 61.1 61.2 61.3 61.4 61.5 61.6 61.7 61.8 61.9 62.0 62.1 62.2 62.3 62.4 62.5 62.6 62.7 62.8 62.9 63.0 63.1 63.2 63.3 63.4 63.5 63.6 63.7 63.8 63.9 64.0 64.1 64.2 64.3 64.4 64.5 64.6 64.7 64.8 64.9 65.0 65.1 65.2 65.3 65.4 65.5 65.6 65.7 65.8 65.9 66.0 66.1 66.2 66.3 66.4 66.5 66.6 66.7 66.8 66.9 67.0 67.1 67.2 67.3 67.4 67.5 67.6 67.7 67.8 67.9 68.0 68.1 68.2 68.3 68.4 68.5 68.6 68.7 68.8 68.9 69.0 69.1 69.2 69.3 69.4 69.5 69.6 69.7 69.8 69.9 70.0 70.1 70.2 70.3 70.4 70.5 70.6 70.7 70.8 70.9 71.0 71.1 71.2 71.3 71.4 71.5 71.6 71.7 71.8 71.9 72.0 72.1 72.2 72.3 72.4 72.5 72.6 72.7 72.8 72.9 73.0 73.1 73.2 73.3 73.4 73.5 73.6 73.7 73.8 73.9 74.0 74.1 74.2 74.3 74.4 74.5 74.6 74.7 74.8 74.9 75.0 75.1 75.2 75.3 75.4 75.5 75.6 75.7 75.8 75.9 76.0 76.1 76.2 76.3 76.4 76.5 76.6 76.7 76.8 76.9 77.0 77.1 77.2 77.3 77.4 77.5 77.6 77.7 77.8 77.9 78.0 78.1 78.2 78.3 78.4 78.5 78.6 78.7 78.8 78.9 79.0 79.1 79.2 79.3 79.4 79.5 79.6 79.7 79.8 79.9 80.0 80.1 80.2 80.3 80.4 80.5 80.6 80.7 80.8 80.9 81.0 81.1 81.2 81.3 81.4 81.5 81.6 81.7 81.8 81.9 82.0 82.1 82.2 82.3 82.4 82.5 82.6 82.7 82.8 82.9 83.0 83

Keysight Spectrum Analyzer - Setup SA

18.7785 GHz

COARSE

INT RES

ALIGN DUT

18:08:36 PM Oct 31, 2025

Marker 1 18.778500000000 GHz

PMW: Fast

Trig: Free Run

Avg Type: Log-Pwr

Trace [1] 0.0

IF Gain: Low

#Att: 40 dB

Avg Hold: >1/1

TYPE: IN

UNIT: dBm

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Data

Mkr--C

Mkr--Ref Lvl

More

1 of

10 dB/Hz

Ref 25.00 dBm

Mkr1 18.778 50 GHz

-36.314 dBm

20.618 50 GHz

-35.084 dBm

Start 2.00 GHz

Stop 25.00 GHz


#Res BW 100 kHz

#VBW 300 kHz


Sweep 2.198 s (4001 pts)

PK INDEX	FREQ (GHz)	LEVEL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	18.778 50 GHz	-36.314 dBm			
2	20.618 50 GHz	-35.084 dBm			


802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11g MIDDLE CHANNEL CARRIER LEVEL



Keysight Spectrum Analyzer - Single Ch

AL F1 15.0 GHz 40 dB

Marker 2 2.664390000000 GHz

Trig: Free Run #Attenu: 40 dB

Avg Type: Log-Pwr Avg Hold: >1 s

DATE/TIME: 04/19/2022 PM 04:24.00

Trace 0 [2.664 GHz] 10.0 dBm

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delete

Mkr --CF

Mkr --Ref Lvl

More

1 of 2

10 dB/div Ref 23.00 dBm

Log

15.0

10.0

7.0

12.0

9.0

6.0

3.0

0.0

-3.0

-6.0

-9.0

-12.0

-15.0

Mkr2 2.664 GHz -40.481 dBm

23.000000

1

2

Start 0.030 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 283.9 ms (1001 pts) Stop 3.000 GHz

MARKER	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION (REF)	FUNCTION (VALUE)
1	N	1	F	2.129 5 GHz	-42.231 dBm
2	N	1	F	2.664 4 GHz	-40.481 dBm

MARKER

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

Keysight Spectrum Analyzer - Setup 24

21.38325 GHz 24.139.25 PW Oct 24, 2025

Marker 1 21.383250000000000 GHz

Trig: Free Run #A: 40 dB

Avg Type: Log-Pwr Avg Hold: 1/1

Trace 1 21.38325 GHz -34.767 dBm

Ref 23.00 dBm

Mkr1 21.38325 GHz -34.767 dBm

10 dB/Div

Log

Start 2.00 GHz Stop 25.00 GHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.198 s (4001 pts)

Marker	Freq (GHz)	Power (dBm)
1	21.38325 GHz	-34.767 dBm
2	6.693275 GHz	-40.658 dBm

Center 2.46200 GHz
 #Res BW 100 kHz
 #VBW 300 kHz
 Sweep 2.880 ms (601 pts)
 Span 30.00 MHz
 Mkr1 2.46325 GHz
 8.904 dBm

Playlight Spectrum Analyzer - Setup SA

Frequency: 2.922 GHz

Marker 2 2.922780000000 GHz

Trig: Free Run

Avg Type: Log-Pwr

Avg Hold: >1/1

66:59:25 PM Oct 24, 2022

Trace 1

Time 283.9 ms

Det 2

Next Peak

Next Pk Right

Next Pk Left

Marker Delete

Mkr--CF

Mkr--Ref Lvl

More

1 of 2

10 dBm/Hz Ref 23.00 dBm

Mkr2 2.922 GHz -40.473 dBm

Start 0.030 GHz Stop 3.000 GHz

#Res BW 100 kHz #VBW 300 kHz Sweep 283.9 ms (1001 pts)

PK INDEX	FREQ	AMPL	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	2.92278 GHz	-41.627 dBm			
2	2.92278 GHz	-40.473 dBm			

Keysight Spectrum Analyzer - Setup tab

Frequency: 24.321 GHz

Marker 1 24.321500000000 GHz

Trig: Free Run

Avg Type: Log-Pwr

Avg/Hold: >1/1

56.56-46 TH Oct 31, 2025

Trace 1

Time 00:00:00

Oct 31, 2025

Marker Table

Marker Counting [OFF]

Couple Markers On

Start 2.00 GHz

Stop 25.00 GHz




#Res BW 100 kHz

#VBW 300 kHz


Sweep 2.198 s (4001 pts)

MARKER	FREQ (GHz)	AMPL (dBm)
1	24.321 50 GHz	-33.736 dBm
2	20.911 75 GHz	-34.796 dBm


802.11n-20 MHz LOW CHANNEL CARRIER LEVEL

802.11n-20 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11n-20 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


802.11n-20 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL




802.11n-20 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-40 MHz LOW CHANNEL CARRIER LEVEL




802.11n-40 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz




802.11n-40 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz




802.11n-40 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-40 MHz HIGH CHANNEL CARRIER LEVEL






802.11n-40 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-40 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11ax-20 MHz(SU) LOW CHANNEL CARRIER LEVEL

802.11ax-20 MHz(SU) LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11ax-20 MHz(SU) LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


802.11ax-20 MHz(SU) MIDDLE CHANNEL CARRIER LEVEL




802.11ax-20 MHz(SU) MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11ax-20 MHz(SU) MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11ax-20 MHz(SU) HIGH CHANNEL CARRIER LEVEL



802.11ax-20 MHz(SU) HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



802.11ax-20 MHz(SU) HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Note¹: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

Note²: All the configurations were pre tested, only the worst configuration has been reported in this report.

Test Data

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-30.38	9.91	-10.09	Pass
High Channel	-45.81	9.12	-10.88	Pass

802.11g Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-17.78	9.26	-10.74	Pass
High Channel	-33.26	8.90	-11.10	Pass

802.11n-20 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-17.77	9.29	-10.71	Pass
High Channel	-29.40	9.09	-10.91	Pass

802.11n-40 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-24.90	4.00	-16.00	Pass
High Channel	-31.79	3.81	-16.19	Pass

802.11ax-20 MHz(SU) Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-19.98	6.79	-13.21	Pass
High Channel	-32.88	6.20	-13.80	Pass

Test Plots

802.11b LOW CHANNEL, CARRIER LEVEL




802.11b LOW CHANNEL, BAND EDGE




802.11b HIGH CHANNEL, CARRIER LEVEL



802.11b HIGH CHANNEL, BAND EDGE



802.11g LOW CHANNEL, CARRIER LEVEL



802.11g LOW CHANNEL, BAND EDGE




802.11g HIGH CHANNEL, CARRIER LEVEL




802.11g HIGH CHANNEL, BAND EDGE




802.11n-20 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-20 MHz LOW CHANNEL, BAND EDGE




802.11n-20 MHz HIGH CHANNEL, CARRIER LEVEL




802.11n-20 MHz HIGH CHANNEL, BAND EDGE




802.11n-40 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-40 MHz LOW CHANNEL, BAND EDGE




802.11n-40 MHz HIGH CHANNEL, CARRIER LEVEL




802.11n-40 MHz HIGH CHANNEL, BAND EDGE




802.11ax-20 MHz(SU) LOW CHANNEL, CARRIER LEVEL




802.11ax-20 MHz(SU) LOW CHANNEL, BAND EDGE



802.11ax-20 MHz(SU) HIGH CHANNEL, CARRIER LEVEL



802.11ax-20 MHz(SU) HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions


Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.158	40.02	10.30	65.57	25.55	Peak	L	Pass
1**	0.158	27.29	10.30	55.57	28.28	AV	L	Pass
2	0.256	38.53	10.26	61.56	23.03	Peak	L	Pass
2**	0.256	26.92	10.26	51.56	24.64	AV	L	Pass
3	0.552	36.71	10.28	56.00	19.29	Peak	L	Pass
3**	0.552	22.64	10.28	46.00	23.36	AV	L	Pass
4	2.092	32.92	10.45	56.00	23.08	Peak	L	Pass
4**	2.092	18.25	10.45	46.00	27.75	AV	L	Pass
5	6.748	31.20	11.19	60.00	28.80	Peak	L	Pass
5**	6.748	18.33	11.19	50.00	31.67	AV	L	Pass
6	22.166	37.46	14.86	60.00	22.54	Peak	L	Pass
6**	22.166	20.33	14.86	50.00	29.67	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.202	39.04	10.19	63.53	24.49	Peak	N	Pass
1**	0.202	25.94	10.19	53.53	27.59	AV	N	Pass
2	0.362	38.24	10.18	58.68	20.44	Peak	N	Pass
2**	0.362	24.53	10.18	48.68	24.15	AV	N	Pass
3	0.580	35.24	10.20	56.00	20.76	Peak	N	Pass
3**	0.580	22.79	10.20	46.00	23.21	AV	N	Pass
4	2.518	31.99	10.41	56.00	24.01	Peak	N	Pass
4**	2.518	15.52	10.41	46.00	30.48	AV	N	Pass
5	12.846	32.22	12.50	60.00	27.78	Peak	N	Pass
5**	12.846	18.50	12.50	50.00	31.50	AV	N	Pass
6	21.750	37.25	14.82	60.00	22.75	Peak	N	Pass
6**	21.750	23.86	14.82	50.00	26.14	AV	N	Pass

A.6 Radiated Emission

Note¹: The symbol of “--” in the table which means not application.


Note²: For the test data above 1 GHz, According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.


Test Data and Plots

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	39.409	15.38	-28.72	40.0	24.62	Peak	311.00	200	Horizontal	Pass
2	51.340	12.75	-24.19	40.0	27.25	Peak	291.00	200	Horizontal	Pass
3	163.957	16.91	-28.85	43.5	26.59	Peak	105.00	200	Horizontal	Pass
4	345.638	18.38	-21.43	46.0	27.62	Peak	217.00	200	Horizontal	Pass
5	557.534	23.25	-16.93	46.0	22.75	Peak	221.00	100	Horizontal	Pass
6	903.630	31.97	-8.76	46.0	14.03	Peak	67.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	38.876	16.58	-27.17	40.0	23.42	Peak	35.00	200	Vertical	Pass
2	53.425	17.25	-25.35	40.0	22.75	Peak	53.00	100	Vertical	Pass
3	153.626	19.03	-29.63	43.5	24.47	Peak	38.00	100	Vertical	Pass
4	227.444	16.35	-25.39	46.0	29.65	Peak	82.00	100	Vertical	Pass
5	585.519	23.83	-16.00	46.0	22.17	Peak	293.00	100	Vertical	Pass
6	912.603	30.77	-8.65	46.0	15.23	Peak	308.00	100	Vertical	Pass


Note¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note²: The spurious above 18G is noise only, do not show on the report.

Note³: All the configurations were pre tested, only the worst configuration has been reported in this report.

1 GHz to 18 GHz, ANT H 802.11b Low Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1272.400	42.21	-17.52	74.0	31.79	Peak	278.00	200	Horizontal	Pass
1**	1272.400	33.20	-17.52	54.0	20.80	AV	278.00	200	Horizontal	Pass
2	2413.300	102.07	-13.95	74.0	-28.07	Peak	309.00	150	Horizontal	N/A
2**	2413.300	98.87	-13.95	54.0	-44.87	AV	309.00	150	Horizontal	N/A
3	2996.500	48.42	-11.38	74.0	25.58	Peak	257.00	200	Horizontal	Pass
3**	2996.500	40.15	-11.38	54.0	13.85	AV	257.00	200	Horizontal	Pass
4	4951.200	48.59	-6.67	74.0	25.41	Peak	42.00	400	Horizontal	Pass
4**	4951.200	39.97	-6.67	54.0	14.03	AV	42.00	400	Horizontal	Pass
5	6973.800	54.28	-1.16	74.0	19.72	Peak	42.00	400	Horizontal	Pass
5**	6973.800	45.36	-1.16	54.0	8.64	AV	42.00	400	Horizontal	Pass
6	16840.537	54.89	6.24	74.0	19.11	Peak	168.00	300	Horizontal	Pass
6**	16840.537	45.66	6.24	54.0	8.34	AV	168.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Low Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1371.200	41.19	-17.26	74.0	32.81	Peak	234.00	100	Vertical	Pass
1**	1371.200	31.61	-17.26	54.0	22.39	AV	234.00	100	Vertical	Pass
2	2413.500	104.47	-14.06	74.0	-30.47	Peak	50.00	200	Vertical	N/A
2**	2413.500	101.71	-14.06	54.0	-47.71	AV	50.00	200	Vertical	N/A
3	2973.500	49.02	-11.01	74.0	24.98	Peak	245.00	400	Vertical	Pass
3**	2973.500	38.90	-11.01	54.0	15.10	AV	245.00	400	Vertical	Pass
4	4843.400	46.37	-6.43	74.0	27.63	Peak	360.00	400	Vertical	Pass
4**	4843.400	41.59	-6.43	54.0	12.41	AV	360.00	400	Vertical	Pass
5	7238.913	49.04	-1.71	74.0	24.96	Peak	64.00	300	Vertical	Pass
5**	7238.913	43.55	-1.71	54.0	10.45	AV	64.00	300	Vertical	Pass
6	16751.813	54.94	6.10	74.0	19.06	Peak	313.00	100	Vertical	Pass
6**	16751.813	46.19	6.10	54.0	7.81	AV	313.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1271.400	41.87	-17.57	74.0	32.13	Peak	178.00	300	Horizontal	Pass
1**	1271.400	32.19	-17.57	54.0	21.81	AV	178.00	300	Horizontal	Pass
2	2438.700	100.21	-13.48	74.0	-26.21	Peak	225.00	200	Horizontal	N/A
2**	2438.700	97.16	-13.48	54.0	-43.16	AV	225.00	200	Horizontal	N/A
3	2914.000	48.87	-10.99	74.0	25.13	Peak	359.00	100	Horizontal	Pass
3**	2914.000	39.81	-10.99	54.0	14.19	AV	359.00	100	Horizontal	Pass
4	4956.600	48.60	-6.26	74.0	25.40	Peak	15.00	300	Horizontal	Pass
4**	4956.600	39.19	-6.26	54.0	14.81	AV	15.00	300	Horizontal	Pass
5	6862.200	53.87	-0.70	74.0	20.13	Peak	190.00	200	Horizontal	Pass
5**	6862.200	44.80	-0.70	54.0	9.20	AV	190.00	200	Horizontal	Pass
6	16915.614	54.97	6.88	74.0	19.03	Peak	244.00	300	Horizontal	Pass
6**	16915.614	45.92	6.88	54.0	8.08	AV	244.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1347.900	41.00	-17.37	74.0	33.00	Peak	27.00	300	Vertical	Pass
1**	1347.900	31.62	-17.37	54.0	22.38	AV	27.00	300	Vertical	Pass
2	2438.700	105.65	-13.48	74.0	-31.65	Peak	99.00	200	Vertical	N/A
2**	2438.700	102.83	-13.48	54.0	-48.83	AV	99.00	200	Vertical	N/A
3	2944.700	48.31	-11.40	74.0	25.69	Peak	37.00	200	Vertical	Pass
3**	2944.700	38.53	-11.40	54.0	15.47	AV	37.00	200	Vertical	Pass
4	4989.800	48.23	-6.75	74.0	25.77	Peak	165.00	300	Vertical	Pass
4**	4989.800	39.55	-6.75	54.0	14.45	AV	165.00	300	Vertical	Pass
5	7312.800	47.28	-1.98	74.0	26.72	Peak	77.00	100	Vertical	Pass
5**	7312.800	42.58	-1.98	54.0	11.42	AV	77.00	100	Vertical	Pass
6	14447.588	54.76	4.31	74.0	19.24	Peak	106.00	400	Vertical	Pass
6**	14447.588	45.96	4.31	54.0	8.04	AV	106.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1431.300	41.95	-17.79	74.0	32.05	Peak	359.00	100	Horizontal	Pass
1**	1431.300	31.91	-17.79	54.0	22.09	AV	359.00	100	Horizontal	Pass
2	2460.400	99.99	-13.80	74.0	-25.99	Peak	301.00	100	Horizontal	N/A
2**	2460.400	97.03	-13.80	54.0	-43.03	AV	301.00	100	Horizontal	N/A
3	2950.700	48.86	-11.03	74.0	25.14	Peak	37.00	200	Horizontal	Pass
3**	2950.700	39.50	-11.03	54.0	14.50	AV	37.00	200	Horizontal	Pass
4	4956.800	49.10	-6.32	74.0	24.90	Peak	298.00	200	Horizontal	Pass
4**	4956.800	39.11	-6.32	54.0	14.89	AV	298.00	200	Horizontal	Pass
5	6978.000	54.64	-1.30	74.0	19.36	Peak	164.00	200	Horizontal	Pass
5**	6978.000	45.65	-1.30	54.0	8.35	AV	164.00	200	Horizontal	Pass
6	16291.912	55.01	3.42	74.0	18.99	Peak	0.00	200	Horizontal	Pass
6**	16291.912	43.84	3.42	54.0	10.16	AV	0.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1359.900	40.84	-17.45	74.0	33.16	Peak	0.00	200	Vertical	Pass
1**	1359.900	31.55	-17.45	54.0	22.45	AV	0.00	200	Vertical	Pass
2	2460.300	104.88	-13.81	74.0	-30.88	Peak	95.00	200	Vertical	N/A
2**	2460.300	102.03	-13.81	54.0	-48.03	AV	95.00	200	Vertical	N/A
3	2921.200	48.37	-11.55	74.0	25.63	Peak	45.00	150	Vertical	Pass
3**	2921.200	39.65	-11.55	54.0	14.35	AV	45.00	150	Vertical	Pass
4	4937.200	48.31	-6.82	74.0	25.69	Peak	50.00	300	Vertical	Pass
4**	4937.200	39.03	-6.82	54.0	14.97	AV	50.00	300	Vertical	Pass
5	7383.237	46.26	-1.64	74.0	27.74	Peak	77.00	100	Vertical	Pass
5**	7383.237	41.76	-1.64	54.0	12.24	AV	77.00	100	Vertical	Pass
6	16757.063	54.62	6.07	74.0	19.38	Peak	120.00	400	Vertical	Pass
6**	16757.063	45.42	6.07	54.0	8.58	AV	120.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Low Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1165.300	41.86	-18.18	74.0	32.14	Peak	0.00	100	Horizontal	Pass
1**	1165.300	31.97	-18.18	54.0	22.03	AV	0.00	100	Horizontal	Pass
2	2407.300	104.77	-13.96	74.0	-30.77	Peak	81.00	150	Horizontal	N/A
2**	2407.300	95.72	-13.96	54.0	-41.72	AV	81.00	150	Horizontal	N/A
3	2973.600	48.74	-11.09	74.0	25.26	Peak	216.00	200	Horizontal	Pass
3**	2973.600	39.54	-11.09	54.0	14.46	AV	216.00	200	Horizontal	Pass
4	4909.600	48.15	-6.62	74.0	25.85	Peak	155.00	400	Horizontal	Pass
4**	4909.600	38.53	-6.62	54.0	15.47	AV	155.00	400	Horizontal	Pass
5	7241.212	46.77	-1.66	74.0	27.23	Peak	2.00	100	Horizontal	Pass
5**	7241.212	41.23	-1.66	54.0	12.77	AV	2.00	100	Horizontal	Pass
6	16932.412	54.61	6.27	74.0	19.39	Peak	307.00	300	Horizontal	Pass
6**	16932.412	45.00	6.27	54.0	9.00	AV	307.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Low Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.300	41.74	-17.78	74.0	32.26	Peak	10.00	400	Vertical	Pass
1**	1327.300	32.23	-17.78	54.0	21.77	AV	10.00	400	Vertical	Pass
2	2413.000	107.91	-13.95	74.0	-33.91	Peak	295.00	100	Vertical	N/A
2**	2413.000	100.65	-13.95	54.0	-46.65	AV	295.00	100	Vertical	N/A
3	2975.400	48.34	-10.69	74.0	25.66	Peak	348.00	100	Vertical	Pass
3**	2975.400	39.18	-10.69	54.0	14.82	AV	348.00	100	Vertical	Pass
4	4951.000	48.34	-6.74	74.0	25.66	Peak	12.00	200	Vertical	Pass
4**	4951.000	38.80	-6.74	54.0	15.20	AV	12.00	200	Vertical	Pass
5	7243.225	47.90	-1.56	74.0	26.10	Peak	0.00	100	Vertical	Pass
5**	7243.225	42.76	-1.56	54.0	11.24	AV	0.00	100	Vertical	Pass
6	16842.375	54.73	6.29	74.0	19.27	Peak	95.00	200	Vertical	Pass
6**	16842.375	45.65	6.29	54.0	8.35	AV	95.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1240.900	42.10	-17.26	74.0	31.90	Peak	45.00	400	Horizontal	Pass
1**	1240.900	33.28	-17.26	54.0	20.72	AV	45.00	400	Horizontal	Pass
2	2440.100	102.51	-13.98	74.0	-28.51	Peak	221.00	100	Horizontal	N/A
2**	2440.100	94.72	-13.98	54.0	-40.72	AV	221.00	100	Horizontal	N/A
3	2975.300	48.99	-10.65	74.0	25.01	Peak	67.00	100	Horizontal	Pass
3**	2975.300	40.66	-10.65	54.0	13.34	AV	67.00	100	Horizontal	Pass
4	4934.200	48.35	-6.70	74.0	25.65	Peak	264.00	100	Horizontal	Pass
4**	4934.200	39.01	-6.70	54.0	14.99	AV	264.00	100	Horizontal	Pass
5	6984.600	54.14	-1.38	74.0	19.86	Peak	353.00	200	Horizontal	Pass
5**	6984.600	44.78	-1.38	54.0	9.22	AV	353.00	200	Horizontal	Pass
6	16709.287	54.94	6.88	74.0	19.06	Peak	321.00	400	Horizontal	Pass
6**	16709.287	45.85	6.88	54.0	8.15	AV	321.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1351.800	41.46	-17.11	74.0	32.54	Peak	0.00	300	Vertical	Pass
1**	1351.800	32.82	-17.11	54.0	21.18	AV	0.00	300	Vertical	Pass
2	2440.900	108.29	-13.56	74.0	-34.29	Peak	0.00	100	Vertical	N/A
2**	2440.900	100.91	-13.56	54.0	-46.91	AV	0.00	100	Vertical	N/A
3	2980.200	48.44	-10.91	74.0	25.56	Peak	178.00	150	Vertical	Pass
3**	2980.200	39.28	-10.91	54.0	14.72	AV	178.00	150	Vertical	Pass
4	5119.600	49.51	-6.29	74.0	24.49	Peak	344.00	100	Vertical	Pass
4**	5119.600	39.59	-6.29	54.0	14.41	AV	344.00	100	Vertical	Pass
5	7314.812	47.40	-1.97	74.0	26.60	Peak	103.00	300	Vertical	Pass
5**	7314.812	41.83	-1.97	54.0	12.17	AV	103.00	300	Vertical	Pass
6	16712.176	55.30	6.90	74.0	18.70	Peak	45.00	300	Vertical	Pass
6**	16712.176	45.21	6.90	54.0	8.79	AV	45.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1192.000	42.05	-17.30	74.0	31.95	Peak	0.00	200	Horizontal	Pass
1**	1192.000	32.11	-17.30	54.0	21.89	AV	0.00	200	Horizontal	Pass
2	2457.300	102.27	-14.00	74.0	-28.27	Peak	287.00	200	Horizontal	N/A
2**	2457.300	93.93	-14.00	54.0	-39.93	AV	287.00	200	Horizontal	N/A
3	2971.700	49.18	-11.36	74.0	24.82	Peak	265.00	200	Horizontal	Pass
3**	2971.700	39.19	-11.36	54.0	14.81	AV	265.00	200	Horizontal	Pass
4	4932.200	48.44	-6.65	74.0	25.56	Peak	125.00	200	Horizontal	Pass
4**	4932.200	39.46	-6.65	54.0	14.54	AV	125.00	200	Horizontal	Pass
5	6990.000	54.05	-1.23	74.0	19.95	Peak	103.00	200	Horizontal	Pass
5**	6990.000	45.67	-1.23	54.0	8.33	AV	103.00	200	Horizontal	Pass
6	16848.676	55.02	6.49	74.0	18.98	Peak	181.00	200	Horizontal	Pass
6**	16848.676	45.69	6.49	54.0	8.31	AV	181.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1174.900	40.98	-18.24	74.0	33.02	Peak	228.00	200	Vertical	Pass
1**	1174.900	30.58	-18.24	54.0	23.42	AV	228.00	200	Vertical	Pass
2	2459.700	107.70	-13.93	74.0	-33.70	Peak	49.00	150	Vertical	N/A
2**	2459.700	101.07	-13.93	54.0	-47.07	AV	49.00	150	Vertical	N/A
3	2957.400	48.60	-11.31	74.0	25.40	Peak	60.00	200	Vertical	Pass
3**	2957.400	39.58	-11.31	54.0	14.42	AV	60.00	200	Vertical	Pass
4	4936.400	48.64	-6.52	74.0	25.36	Peak	275.00	300	Vertical	Pass
4**	4936.400	39.08	-6.52	54.0	14.92	AV	275.00	300	Vertical	Pass
5	6972.400	54.27	-0.86	74.0	19.73	Peak	212.00	300	Vertical	Pass
5**	6972.400	45.13	-0.86	54.0	8.87	AV	212.00	300	Vertical	Pass
6	14447.588	54.52	4.31	74.0	19.48	Peak	32.00	100	Vertical	Pass
6**	14447.588	45.77	4.31	54.0	8.23	AV	32.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Low Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1397.400	42.16	-17.78	74.0	31.84	Peak	113.00	100	Horizontal	Pass
1**	1397.400	32.54	-17.78	54.0	21.46	AV	113.00	100	Horizontal	Pass
2	2413.200	103.30	-13.91	74.0	-29.30	Peak	69.00	150	Horizontal	N/A
2**	2413.200	96.19	-13.91	54.0	-42.19	AV	69.00	150	Horizontal	N/A
3	2991.900	49.47	-11.18	74.0	24.53	Peak	113.00	100	Horizontal	Pass
3**	2991.900	39.43	-11.18	54.0	14.57	AV	113.00	100	Horizontal	Pass
4	4989.600	48.08	-6.69	74.0	25.92	Peak	228.00	100	Horizontal	Pass
4**	4989.600	39.40	-6.69	54.0	14.60	AV	228.00	100	Horizontal	Pass
5	6990.600	54.74	-1.22	74.0	19.26	Peak	248.00	300	Horizontal	Pass
5**	6990.600	45.57	-1.22	54.0	8.43	AV	248.00	300	Horizontal	Pass
6	16854.974	55.76	6.59	74.0	18.24	Peak	86.00	400	Horizontal	Pass
6**	16854.974	46.16	6.59	54.0	7.84	AV	86.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Low Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1267.800	41.44	-17.75	74.0	32.56	Peak	321.00	100	Vertical	Pass
1**	1267.800	31.17	-17.75	54.0	22.83	AV	321.00	100	Vertical	Pass
2	2414.900	107.57	-14.36	74.0	-33.57	Peak	47.00	200	Vertical	N/A
2**	2414.900	99.95	-14.36	54.0	-45.95	AV	47.00	200	Vertical	N/A
3	2896.200	48.87	-11.15	74.0	25.13	Peak	354.00	200	Vertical	Pass
3**	2896.200	38.76	-11.15	54.0	15.24	AV	354.00	200	Vertical	Pass
4	5042.000	49.04	-6.52	74.0	24.96	Peak	360.00	200	Vertical	Pass
4**	5042.000	39.52	-6.52	54.0	14.48	AV	360.00	200	Vertical	Pass
5	7240.637	47.38	-1.68	74.0	26.62	Peak	239.00	200	Vertical	Pass
5**	7240.637	41.73	-1.68	54.0	12.27	AV	239.00	200	Vertical	Pass
6	16911.675	54.43	7.00	74.0	19.57	Peak	154.00	200	Vertical	Pass
6**	16911.675	46.23	7.00	54.0	7.77	AV	154.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1453.300	41.92	-17.82	74.0	32.08	Peak	0.00	400	Horizontal	Pass
1**	1453.300	32.48	-17.82	54.0	21.52	AV	0.00	400	Horizontal	Pass
2	2438.700	101.94	-13.48	74.0	-27.94	Peak	222.00	150	Horizontal	N/A
2**	2438.700	95.48	-13.48	54.0	-41.48	AV	222.00	150	Horizontal	N/A
3	2923.800	48.25	-11.40	74.0	25.75	Peak	145.00	200	Horizontal	Pass
3**	2923.800	39.11	-11.40	54.0	14.89	AV	145.00	200	Horizontal	Pass
4	4712.800	48.05	-7.80	74.0	25.95	Peak	239.00	150	Horizontal	Pass
4**	4712.800	39.72	-7.80	54.0	14.28	AV	239.00	150	Horizontal	Pass
5	6936.600	54.56	-1.63	74.0	19.44	Peak	260.00	200	Horizontal	Pass
5**	6936.600	44.49	-1.63	54.0	9.51	AV	260.00	200	Horizontal	Pass
6	16892.511	54.84	6.91	74.0	19.16	Peak	149.00	100	Horizontal	Pass
6**	16892.511	45.05	6.91	54.0	8.95	AV	149.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel


RSE (SRD)_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1351.000	41.10	-17.33	74.0	32.90	Peak	89.00	400	Vertical	Pass
1**	1351.000	31.82	-17.33	54.0	22.18	AV	89.00	400	Vertical	Pass
2	2440.100	108.25	-13.98	74.0	-34.25	Peak	342.00	150	Vertical	N/A
2**	2440.100	100.94	-13.98	54.0	-46.94	AV	342.00	150	Vertical	N/A
3	2984.800	48.49	-11.02	74.0	25.51	Peak	102.00	200	Vertical	Pass
3**	2984.800	39.38	-11.02	54.0	14.62	AV	102.00	200	Vertical	Pass
4	5051.600	49.33	-6.56	74.0	24.67	Peak	89.00	100	Vertical	Pass
4**	5051.600	38.87	-6.56	54.0	15.13	AV	89.00	100	Vertical	Pass
5	6972.800	54.95	-0.92	74.0	19.05	Peak	299.00	400	Vertical	Pass
5**	6972.800	45.56	-0.92	54.0	8.44	AV	299.00	400	Vertical	Pass
6	16864.162	54.77	6.59	74.0	19.23	Peak	174.00	200	Vertical	Pass
6**	16864.162	45.29	6.59	54.0	8.71	AV	174.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.200	42.44	-17.57	74.0	31.56	Peak	0.00	200	Horizontal	Pass
1**	1328.200	32.11	-17.57	54.0	21.89	AV	0.00	200	Horizontal	Pass
2	2459.600	101.63	-13.96	74.0	-27.63	Peak	302.00	200	Horizontal	N/A
2**	2459.600	94.55	-13.96	54.0	-40.55	AV	302.00	200	Horizontal	N/A
3	2999.300	48.90	-11.39	74.0	25.10	Peak	360.00	150	Horizontal	Pass
3**	2999.300	39.79	-11.39	54.0	14.21	AV	360.00	150	Horizontal	Pass
4	5236.200	49.60	-6.61	74.0	24.40	Peak	342.00	100	Horizontal	Pass
4**	5236.200	41.11	-6.61	54.0	12.89	AV	342.00	100	Horizontal	Pass
5	6957.000	54.21	-1.31	74.0	19.79	Peak	259.00	400	Horizontal	Pass
5**	6957.000	44.78	-1.31	54.0	9.22	AV	259.00	400	Horizontal	Pass
6	16873.875	54.83	6.56	74.0	19.17	Peak	1.00	400	Horizontal	Pass
6**	16873.875	45.22	6.56	54.0	8.78	AV	1.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1466.500	42.42	-17.89	74.0	31.58	Peak	261.00	100	Vertical	Pass
1**	1466.500	31.23	-17.89	54.0	22.77	AV	261.00	100	Vertical	Pass
2	2460.200	107.17	-13.82	74.0	-33.17	Peak	95.00	150	Vertical	N/A
2**	2460.200	99.85	-13.82	54.0	-45.85	AV	95.00	150	Vertical	N/A
3	2990.300	48.81	-11.30	74.0	25.19	Peak	72.00	200	Vertical	Pass
3**	2990.300	39.27	-11.30	54.0	14.73	AV	72.00	200	Vertical	Pass
4	5038.000	49.03	-6.30	74.0	24.97	Peak	81.00	300	Vertical	Pass
4**	5038.000	39.43	-6.30	54.0	14.57	AV	81.00	300	Vertical	Pass
5	6969.800	54.02	-1.07	74.0	19.98	Peak	0.00	400	Vertical	Pass
5**	6969.800	45.77	-1.07	54.0	8.23	AV	0.00	400	Vertical	Pass
6	16864.949	54.45	6.58	74.0	19.55	Peak	95.00	200	Vertical	Pass
6**	16864.949	45.10	6.58	54.0	8.90	AV	95.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Low Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2279.900	52.02	-14.10	74.0	21.98	Peak	72.00	200	Horizontal	Pass
1**	2279.900	46.61	-14.10	54.0	7.39	AV	72.00	200	Horizontal	Pass
2	2419.300	101.41	-13.80	74.0	-27.41	Peak	299.00	100	Horizontal	N/A
2**	2419.300	93.04	-13.80	54.0	-39.04	AV	299.00	100	Horizontal	N/A
3	2932.800	49.17	-11.48	74.0	24.83	Peak	354.00	100	Horizontal	Pass
3**	2932.800	39.59	-11.48	54.0	14.41	AV	354.00	100	Horizontal	Pass
4	4991.400	48.89	-6.92	74.0	25.11	Peak	188.00	200	Horizontal	Pass
4**	4991.400	38.70	-6.92	54.0	15.30	AV	188.00	200	Horizontal	Pass
5	6978.800	55.13	-1.06	74.0	18.87	Peak	341.00	100	Horizontal	Pass
5**	6978.800	45.35	-1.06	54.0	8.65	AV	341.00	100	Horizontal	Pass
6	16842.113	55.89	6.29	74.0	18.11	Peak	21.00	400	Horizontal	Pass
6**	16842.113	45.38	6.29	54.0	8.62	AV	21.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Low Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2279.000	52.81	-14.31	74.0	21.19	Peak	235.00	150	Vertical	Pass
1**	2279.000	46.99	-14.31	54.0	7.01	AV	235.00	150	Vertical	Pass
2	2415.100	105.59	-14.37	74.0	-31.59	Peak	0.00	150	Vertical	N/A
2**	2415.100	97.24	-14.37	54.0	-43.24	AV	0.00	150	Vertical	N/A
3	2898.800	48.73	-11.07	74.0	25.27	Peak	246.00	150	Vertical	Pass
3**	2898.800	38.72	-11.07	54.0	15.28	AV	246.00	150	Vertical	Pass
4	5135.800	49.56	-6.01	74.0	24.44	Peak	277.00	300	Vertical	Pass
4**	5135.800	40.26	-6.01	54.0	13.74	AV	277.00	300	Vertical	Pass
5	6991.200	54.00	-1.46	74.0	20.00	Peak	298.00	200	Vertical	Pass
5**	6991.200	45.67	-1.46	54.0	8.33	AV	298.00	200	Vertical	Pass
6	16865.739	54.72	6.56	74.0	19.28	Peak	305.00	200	Vertical	Pass
6**	16865.739	45.46	6.56	54.0	8.54	AV	305.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2293.300	51.88	-13.84	74.0	22.12	Peak	53.00	150	Horizontal	Pass
1**	2293.300	46.74	-13.84	54.0	7.26	AV	53.00	150	Horizontal	Pass
2	2443.000	99.60	-13.73	74.0	-25.60	Peak	294.00	200	Horizontal	N/A
2**	2443.000	91.36	-13.73	54.0	-37.36	AV	294.00	200	Horizontal	N/A
3	2769.100	48.57	-12.00	74.0	25.43	Peak	189.00	100	Horizontal	Pass
3**	2769.100	39.38	-12.00	54.0	14.62	AV	189.00	100	Horizontal	Pass
4	5486.800	48.84	-6.53	74.0	25.16	Peak	125.00	300	Horizontal	Pass
4**	5486.800	39.05	-6.53	54.0	14.95	AV	125.00	300	Horizontal	Pass
5	6991.200	54.70	-1.46	74.0	19.30	Peak	299.00	400	Horizontal	Pass
5**	6991.200	45.27	-1.46	54.0	8.73	AV	299.00	400	Horizontal	Pass
6	16850.512	54.58	6.54	74.0	19.42	Peak	344.00	400	Horizontal	Pass
6**	16850.512	45.57	6.54	54.0	8.43	AV	344.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel


RSE (SRD), FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1311.900	41.95	-18.05	74.0	32.05	Peak	219.00	300	Vertical	Pass
1**	1311.900	31.28	-18.05	54.0	22.72	AV	219.00	300	Vertical	Pass
2	2439.300	105.60	-13.82	74.0	-31.60	Peak	160.00	200	Vertical	N/A
2**	2439.300	97.57	-13.82	54.0	-43.57	AV	160.00	200	Vertical	N/A
3	2772.100	48.84	-11.95	74.0	25.16	Peak	243.00	100	Vertical	Pass
3**	2772.100	38.90	-11.95	54.0	15.10	AV	243.00	100	Vertical	Pass
4	5495.000	49.83	-6.40	74.0	24.17	Peak	187.00	200	Vertical	Pass
4**	5495.000	39.59	-6.40	54.0	14.41	AV	187.00	200	Vertical	Pass
5	6977.600	54.75	-1.52	74.0	19.25	Peak	120.00	100	Vertical	Pass
5**	6977.600	45.59	-1.52	54.0	8.41	AV	120.00	100	Vertical	Pass
6	16819.276	54.59	5.94	74.0	19.41	Peak	318.00	300	Vertical	Pass
6**	16819.276	45.27	5.94	54.0	8.73	AV	318.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 High Channel


RSE (SRD), FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2306.200	49.77	-13.93	74.0	24.23	Peak	135.00	150	Horizontal	Pass
1**	2306.200	44.27	-13.93	54.0	9.73	AV	135.00	150	Horizontal	Pass
2	2449.100	100.05	-14.38	74.0	-26.05	Peak	298.00	150	Horizontal	N/A
2**	2449.100	92.19	-14.38	54.0	-38.19	AV	298.00	150	Horizontal	N/A
3	2745.000	49.41	-11.66	74.0	24.59	Peak	360.00	200	Horizontal	Pass
3**	2745.000	38.87	-11.66	54.0	15.13	AV	360.00	200	Horizontal	Pass
4	5383.000	48.88	-5.76	74.0	25.12	Peak	66.00	400	Horizontal	Pass
4**	5383.000	39.58	-5.76	54.0	14.42	AV	66.00	400	Horizontal	Pass
5	6992.600	54.40	-1.10	74.0	19.60	Peak	20.00	400	Horizontal	Pass
5**	6992.600	45.31	-1.10	54.0	8.69	AV	20.00	400	Horizontal	Pass
6	16713.488	54.88	6.89	74.0	19.12	Peak	0.00	100	Horizontal	Pass
6**	16713.488	45.30	6.89	54.0	8.70	AV	0.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1250.700	41.69	-17.62	74.0	32.31	Peak	227.00	400	Vertical	Pass
1**	1250.700	32.58	-17.62	54.0	21.42	AV	227.00	400	Vertical	Pass
2	2445.000	105.57	-13.93	74.0	-31.57	Peak	0.00	200	Vertical	N/A
2**	2445.000	97.19	-13.93	54.0	-43.19	AV	0.00	200	Vertical	N/A
3	2953.700	49.58	-11.53	74.0	24.42	Peak	182.00	200	Vertical	Pass
3**	2953.700	38.65	-11.53	54.0	15.35	AV	182.00	200	Vertical	Pass
4	5008.000	48.92	-6.41	74.0	25.08	Peak	115.00	150	Vertical	Pass
4**	5008.000	39.72	-6.41	54.0	14.28	AV	115.00	150	Vertical	Pass
5	6972.000	54.18	-1.06	74.0	19.82	Peak	0.00	200	Vertical	Pass
5**	6972.000	45.75	-1.06	54.0	8.25	AV	0.00	200	Vertical	Pass
6	16838.963	54.66	6.19	74.0	19.34	Peak	319.00	100	Vertical	Pass
6**	16838.963	45.69	6.19	54.0	8.31	AV	319.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11ax20(SU) Low Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1443.100	41.93	-17.72	74.0	32.07	Peak	112.00	200	Horizontal	Pass
1**	1443.100	32.51	-17.72	54.0	21.49	AV	112.00	200	Horizontal	Pass
2	2409.200	104.37	-14.27	74.0	-30.37	Peak	48.00	200	Horizontal	N/A
2**	2409.200	96.08	-14.27	54.0	-42.08	AV	48.00	200	Horizontal	N/A
3	2744.800	49.14	-11.73	74.0	24.86	Peak	112.00	100	Horizontal	Pass
3**	2744.800	39.66	-11.73	54.0	14.34	AV	112.00	100	Horizontal	Pass
4	5496.200	49.65	-6.37	74.0	24.35	Peak	31.00	100	Horizontal	Pass
4**	5496.200	39.89	-6.37	54.0	14.11	AV	31.00	100	Horizontal	Pass
5	6991.600	54.51	-1.47	74.0	19.49	Peak	343.00	200	Horizontal	Pass
5**	6991.600	45.55	-1.47	54.0	8.45	AV	343.00	200	Horizontal	Pass
6	16839.750	55.61	6.21	74.0	18.39	Peak	85.00	100	Horizontal	Pass
6**	16839.750	44.79	6.21	54.0	9.21	AV	85.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V802.11ax20(SU) Low Channel


RSE (SRD), FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.400	43.13	-17.72	74.0	30.87	Peak	276.00	100	Vertical	Pass
1**	1332.400	31.48	-17.72	54.0	22.52	AV	276.00	100	Vertical	Pass
2	2404.600	108.68	-14.13	74.0	-34.68	Peak	92.00	150	Vertical	N/A
2**	2404.600	99.04	-14.13	54.0	-45.04	AV	92.00	150	Vertical	N/A
3	2527.000	55.32	-14.21	74.0	18.68	Peak	0.00	150	Vertical	Pass
3**	2527.000	36.80	-14.21	54.0	17.20	AV	0.00	150	Vertical	Pass
4	5485.200	49.64	-6.52	74.0	24.36	Peak	32.00	100	Vertical	Pass
4**	5485.200	39.14	-6.52	54.0	14.86	AV	32.00	100	Vertical	Pass
5	6472.000	54.22	-3.00	74.0	19.78	Peak	302.00	400	Vertical	Pass
5**	6472.000	43.71	-3.00	54.0	10.29	AV	302.00	400	Vertical	Pass
6	16776.488	54.95	5.96	74.0	19.05	Peak	345.00	400	Vertical	Pass
6**	16776.488	44.50	5.96	54.0	9.50	AV	345.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11ax20(SU) Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1179.900	42.10	-17.59	74.0	31.90	Peak	310.00	300	Horizontal	Pass
1**	1179.900	32.31	-17.59	54.0	21.69	AV	310.00	300	Horizontal	Pass
2	2445.900	103.18	-14.42	74.0	-29.18	Peak	287.00	150	Horizontal	N/A
2**	2445.900	94.41	-14.42	54.0	-40.41	AV	287.00	150	Horizontal	N/A
3	2944.600	49.49	-11.29	74.0	24.51	Peak	19.00	100	Horizontal	Pass
3**	2944.600	39.30	-11.29	54.0	14.70	AV	19.00	100	Horizontal	Pass
4	5137.600	49.45	-6.33	74.0	24.55	Peak	142.00	100	Horizontal	Pass
4**	5137.600	39.51	-6.33	54.0	14.49	AV	142.00	100	Horizontal	Pass
5	6988.400	54.14	-1.50	74.0	19.86	Peak	266.00	200	Horizontal	Pass
5**	6988.400	44.89	-1.50	54.0	9.11	AV	266.00	200	Horizontal	Pass
6	16904.324	54.89	7.07	74.0	19.11	Peak	109.00	200	Horizontal	Pass
6**	16904.324	44.67	7.07	54.0	9.33	AV	109.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11ax20(SU) Middle Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1345.500	41.31	-17.19	74.0	32.69	Peak	144.00	400	Vertical	Pass
1**	1345.500	32.26	-17.19	54.0	21.74	AV	144.00	400	Vertical	Pass
2	2442.100	109.14	-13.87	74.0	-35.14	Peak	111.00	100	Vertical	N/A
2**	2442.100	101.17	-13.87	54.0	-47.17	AV	111.00	100	Vertical	N/A
3	2913.900	48.23	-10.97	74.0	25.77	Peak	233.00	100	Vertical	Pass
3**	2913.900	39.54	-10.97	54.0	14.46	AV	233.00	100	Vertical	Pass
4	5099.600	49.09	-6.47	74.0	24.91	Peak	306.00	200	Vertical	Pass
4**	5099.600	39.98	-6.47	54.0	14.02	AV	306.00	200	Vertical	Pass
5	6960.600	54.88	-1.51	74.0	19.12	Peak	38.00	300	Vertical	Pass
5**	6960.600	45.09	-1.51	54.0	8.91	AV	38.00	300	Vertical	Pass
6	16860.225	54.53	6.66	74.0	19.47	Peak	346.00	100	Vertical	Pass
6**	16860.225	45.44	6.66	54.0	8.56	AV	346.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H802.11ax20(SU) High Channel


RSE (SRD), FCC Part 15C, FCC 15.247(2.4G), 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1259.300	41.62	-17.83	74.0	32.38	Peak	309.00	100	Horizontal	Pass
1**	1259.300	32.18	-17.83	54.0	21.82	AV	309.00	100	Horizontal	Pass
2	2453.900	102.31	-13.88	74.0	-28.31	Peak	275.00	100	Horizontal	N/A
2**	2453.900	93.55	-13.88	54.0	-39.55	AV	275.00	100	Horizontal	N/A
3	2982.600	48.95	-11.26	74.0	25.05	Peak	11.00	200	Horizontal	Pass
3**	2982.600	39.03	-11.26	54.0	14.97	AV	11.00	200	Horizontal	Pass
4	5143.000	48.98	-5.75	74.0	25.02	Peak	289.00	400	Horizontal	Pass
4**	5143.000	40.41	-5.75	54.0	13.59	AV	289.00	400	Horizontal	Pass
5	6965.800	54.26	-1.42	74.0	19.74	Peak	103.00	300	Horizontal	Pass
5**	6965.800	45.45	-1.42	54.0	8.55	AV	103.00	300	Horizontal	Pass
6	16879.387	54.59	6.65	74.0	19.41	Peak	354.00	300	Horizontal	Pass
6**	16879.387	45.91	6.65	54.0	8.09	AV	354.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11ax20(SU) High Channel

RSE (SRD), FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1263.800	41.38	-17.77	74.0	32.62	Peak	19.00	400	Vertical	Pass
1**	1263.800	31.15	-17.77	54.0	22.85	AV	19.00	400	Vertical	Pass
2	2462.800	108.89	-13.95	74.0	-34.89	Peak	51.00	150	Vertical	N/A
2**	2462.800	99.85	-13.95	54.0	-45.85	AV	51.00	150	Vertical	N/A
3	2735.700	48.48	-12.24	74.0	25.52	Peak	0.00	200	Vertical	Pass
3**	2735.700	39.37	-12.24	54.0	14.63	AV	0.00	200	Vertical	Pass
4	5112.800	49.54	-6.33	74.0	24.46	Peak	142.00	200	Vertical	Pass
4**	5112.800	40.74	-6.33	54.0	13.26	AV	142.00	200	Vertical	Pass
5	6971.200	54.12	-1.17	74.0	19.88	Peak	328.00	200	Vertical	Pass
5**	6971.200	45.56	-1.17	54.0	8.44	AV	328.00	200	Vertical	Pass
6	16686.450	54.85	6.63	74.0	19.15	Peak	212.00	100	Vertical	Pass
6**	16686.450	44.57	6.63	54.0	9.43	AV	212.00	100	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.


Note³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note⁴: All the configurations were pre tested, only the worst configuration has been reported in this report.

Note⁵: Both horizontal and vertical directions were pre tested, only the worst configuration has been reported in this report.


Test Data

802.11b LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2386.500	59.54	-1.55	74.0	14.46	Peak	202.00	100	Vertical	Pass
1**	2386.500	52.32	-1.55	54.0	1.68	AV	202.00	100	Vertical	Pass
2	2390.000	57.68	-2.16	74.0	16.32	Peak	53.00	200	Vertical	Pass
2**	2390.000	49.13	-2.16	54.0	4.87	AV	53.00	200	Vertical	Pass
3	2387.000	58.34	-1.58	74.0	15.66	Peak	247.00	150	Vertical	Pass
3**	2387.000	53.12	-1.58	54.0	0.88	AV	247.00	150	Vertical	Pass

802.11b HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.40	-1.04	74.0	17.60	Peak	28.00	300	Vertical	Pass
1**	2483.500	47.47	-1.04	54.0	6.53	AV	28.00	300	Vertical	Pass
2	2487.400	61.42	-1.15	74.0	12.58	Peak	326.00	400	Vertical	Pass
2**	2487.400	53.69	-1.15	54.0	0.31	AV	326.00	400	Vertical	Pass
3	2487.450	60.28	-1.11	74.0	13.72	Peak	326.00	150	Vertical	Pass
3**	2487.450	53.89	-1.11	54.0	0.11	AV	326.00	150	Vertical	Pass

802.11g LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2389.500	66.93	-2.02	74.0	7.07	Peak	248.00	100	Vertical	Pass
1**	2389.500	49.68	-2.02	54.0	4.32	AV	248.00	100	Vertical	Pass
2	2390.000	68.88	-2.16	74.0	5.12	Peak	295.00	400	Vertical	Pass
2**	2390.000	50.54	-2.16	54.0	3.46	AV	295.00	400	Vertical	Pass

802.11g HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	66.19	-1.03	74.0	7.81	Peak	253.00	400	Vertical	Pass
1**	2483.500	50.17	-1.03	54.0	3.83	AV	253.00	400	Vertical	Pass
2	2483.800	65.83	-0.99	74.0	8.17	Peak	13.00	200	Vertical	Pass
2**	2483.800	50.02	-0.99	54.0	3.98	AV	13.00	200	Vertical	Pass

802.11n20 LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2389.000	67.40	-1.99	74.0	6.60	Peak	70.00	400	Vertical	Pass
1**	2389.000	51.47	-1.99	54.0	2.53	AV	70.00	400	Vertical	Pass
2	2390.000	67.29	-2.16	74.0	6.71	Peak	248.00	200	Vertical	Pass
2**	2390.000	53.26	-2.16	54.0	0.74	AV	248.00	200	Vertical	Pass

802.11n20 HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	64.77	-1.03	74.0	9.23	Peak	312.00	100	Vertical	Pass
1**	2483.550	49.44	-1.03	54.0	4.56	AV	312.00	100	Vertical	Pass
2	2484.100	65.77	-1.04	74.0	8.23	Peak	35.00	100	Vertical	Pass
2**	2484.100	48.86	-1.04	54.0	5.14	AV	35.00	100	Vertical	Pass

802.11n40 LOW CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2389.167	66.77	-1.99	74.0	7.23	Peak	72.00	400	Vertical	Pass
1**	2389.167	52.77	-1.99	54.0	1.23	AV	72.00	400	Vertical	Pass
2	2390.000	64.84	-2.16	74.0	9.16	Peak	9.00	400	Vertical	Pass
2**	2390.000	53.31	-2.16	54.0	0.69	AV	9.00	400	Vertical	Pass

802.11n40 HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	62.12	-1.03	74.0	11.88	Peak	360.00	400	Vertical	Pass
1**	2483.550	50.33	-1.03	54.0	3.67	AV	360.00	400	Vertical	Pass
2	2484.500	62.41	-1.10	74.0	11.59	Peak	169.00	100	Vertical	Pass
2**	2484.500	49.97	-1.10	54.0	4.03	AV	169.00	100	Vertical	Pass
3	2483.650	61.60	-1.01	74.0	12.40	Peak	305.00	150	Vertical	Pass
3**	2483.650	50.83	-1.01	54.0	3.17	AV	305.00	150	Vertical	Pass

802.11ax20(SU) LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2387.500	71.05	-1.82	74.0	2.95	Peak	70.00	400	Vertical	Pass
1**	2387.500	50.08	-1.82	54.0	3.92	AV	70.00	400	Vertical	Pass
2	2390.000	69.44	-2.16	74.0	4.56	Peak	311.00	200	Vertical	Pass
2**	2390.000	53.37	-2.16	54.0	0.63	AV	311.00	200	Vertical	Pass

802.11ax20(SU) HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	63.60	-1.03	74.0	10.40	Peak	298.00	100	Vertical	Pass
1**	2483.500	50.24	-1.03	54.0	3.76	AV	298.00	100	Vertical	Pass
2	2487.100	64.78	-1.31	74.0	9.22	Peak	8.00	400	Vertical	Pass
2**	2487.100	46.41	-1.31	54.0	7.59	AV	8.00	400	Vertical	Pass
3	2483.600	64.84	-1.02	74.0	9.16	Peak	207.00	150	Vertical	Pass
3**	2483.600	50.30	-1.02	54.0	3.70	AV	207.00	150	Vertical	Pass

A.8 Power Spectral Density (PSD)

Note ¹: All the configurations were pre tested, only the worst configuration has been reported in this report.

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-7.330	8
Middle	-6.980	8
High	-7.535	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-14.104	8
Middle	-7.858	8
High	-14.693	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-13.028	8
Middle	-7.597	8
High	-15.082	8

802.11n-40 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-18.259	8
Middle	-10.101	8
High	-19.447	8

802.11ax-20 MHz(SU) Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-14.271	8
Middle	-8.396	8
High	-15.664	8

Test Plots

802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL




802.11n-40 MHz MIDDLE CHANNEL




802.11n-40 MHz HIGH CHANNEL




802.11ax-20 MHz(SU) LOW CHANNEL



802.11ax-20 MHz(SU) MIDDLE CHANNEL



802.11ax-20 MHz(SU) HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ25A0100-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ25A0100-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ25A0100-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--