TEST REPORT

Reference No.	:	WTN17S1196282E
FCC ID.....	:	2AOH2-005WL
Applicant	:	Ningbo Aotian Electrical Appliances Co.,Ltd
Address	:	East Industrial Zone Guanhaiwei Town, Cixi City Zhejiang 315314, P.R. China
Manufacturer	:	The same as above
Address	:	The same as above
Product.....	:	FAN
Model(s).....	:	ATF-005WL
Standards.....	:	FCC CFR47 Part 15.247: 2016
Date of Receipt sample....	:	2017-11-25
Date of Test.....	:	2017-11-26 to 2018-01-03
Date of Issue	:	2018-01-04
Test Result	:	**Pass**

Remarks:
The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Services (Shenzhen) Co., Ltd.
Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:

Jack Wen / Test Engineer

Approved by:

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.

Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

2.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Accreditation Body	Scope	Note
USA	**A2LA (Certificate No.: 4243.01)**	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India	**International Services**	WPC	-
Thailand		NTC	-
Singapore		IDA	-

Note:

1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.
2. IC Canada Registration No.: 7760A

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of …	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

Page

COVER PAGE 1
2 LABORATORIES INTRODUCTION 2
2.1 TEST FACILITY 3
3 CONTENTS 4
4 REVISION HISTORY 6
5 GENERAL INFORMATION 7
5.1 GENERAL DESCRIPTION OF E.U.T 7
5.2 DETAILS OF E.U.T 7
5.3 CHANNEL LIST 8
5.4 TEST MODE 8
6 EQUIPMENT USED DURING TEST 9
6.1 EQUIPMENTS LIST 9
6.2 DESCRIPTION OF SUPPORT UNITS 10
6.3 MEASUREMENT UNCERTAINTY 10
6.4 SUBCONTRACTED 10
7 TEST SUMMARY 11
8 CONDUCTED EMISSION 12
8.1 E.U.T. OPERATION 12
8.2 EUT SETUP 12
8.3 MEASUREMENT DESCRIPTION 12
8.4 CONDUCTED EMISSION TEST RESULT 13
9 RADIATED SPURIOUS EMISSIONS 15
9.1 EUT OPERATION 15
9.2 TEST SETUP 16
9.3 SPECTRUM ANALYZER SETUP 17
9.4 TEST PROCEDURE 18
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION 18
9.6 SUMMARY OF TEST RESULTS 19
10 CONDUCTED SPURIOUS EMISSIONS 22
10.1 TEST PROCEDURE 22
10.2 TEST RESULT 23
11 BAND EDGE MEASUREMENT 29
11.1 TEST PROCEDURE 29
11.2 TEST RESULT 30
12 BANDWIDTH MEASUREMENT 34
12.1 TEST PROCEDURE 34
12.2 TEST RESULT 34
13 MAXIMUM PEAK OUTPUT POWER 38
13.1 TEST PROCEDURE 38
13.2 TEST RESULT 38
14 HOPPING CHANNEL SEPARATION 42
14.1 TEST PROCEDURE 42
14.2 TEST RESULT 42
15 NUMBER OF HOPPING FREQUENCY 46

15.1 TEST PROCEDURE 46
15.2 TEST RESULT 46
16 DWELL TIME 48
16.1 TEST PROCEDURE 48
16.2 TEST RESULT 48
17 ANTENNA REQUIREMENT 53
18 RF EXPOSURE 54
19 PHOTOGRAPHS -TEST SETUP PHOTOS 55
19.1 PHOTOGRAPH-CONDUCTED EMISSIONS TEST SETUP 55
19.2 PHOTOGRAPH-RADIATED EMISSIONS 55
20 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS 58
20.1 EUT – EXTERNAL PHOTOS 58
20.2 EUT – INTERNAL PHOTOS 63

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTN17S1196282E	2017-11-25	2017-11-26 to 2018-01-03	2018-01-04	original	-	Valid

5 General Information

5.1 General Description of E.U.T

Product	:FAN
Model(s)	:ATF-005WL
Model Description	: N/A

5.2 Details of E.U.T

Operation Frequency	: 2402~2480MHz
The Lowest Oscillator:	: 8MHz
Max. RF output power	: -1.93dBm
Type of Modulation	: GFSK, Pi/4 DQPSK, 8DPSK
Bluetooth Version	: V3.0
Antenna installation	: PCB Printed Antenna
Antenna Gain	: -0.68dBi
Ratings	: Input: AC120V 60Hz 60W

5.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	-	-

5.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests; the worst data were recorded and reported.

Test mode	Low channel	Middle channel	High channel
Transmitting	2402MHz	2441MHz	2480MHz

Note: The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions (Waltek Services (Shenzhen) Co., Ltd.)						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	Laplace	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions (Waltek Services (Shenzhen) Co., Ltd.)						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1	Spectrum Analyzer	R&S	FSP	100091	2017-04-29	2018-04-28
2	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2017-04-09	2018-04-08
3	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-13	2018-04-12
4	Coaxial Cable (above 1GHz)	Top	1GHz-18GHz	EW02014-7	2017-04-13	2018-04-12
3m Semi-anechoic Chamber for Radiation Emissions (Waltek Services (Shenzhen) Co., Ltd.)						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No**	**Last Calibration Date**	**Calibration Due Date**
1	Test Receiver	R&S	ESCI	101296	2017-04-13	2018-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-13	2018-04-12
3	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-09	2018-04-08
4	Amplifier	ANRITSU	MH648A	M43381	2017-04-13	2018-04-12
5	Cable	HUBER+SUHNER	CBL2	525178	2017-04-13	2018-04-12
6	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
RF Conducted Testing (Waltek Services (Shenzhen) Co., Ltd.)						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	Spectrum Analyzer	R&S	FSL6	100959	2017-09-12	2018-09-11
2	Coaxial Cable	Top	10Hz-30GHz	-	2017-09-12	2018-09-11
3	Antenna Connector*	Realacc	45RSm	-	2017-09-12	2018-09-11
"*": The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.						

10m Semi-anechoic Chamber for Radiation Emissions (Above18GHz) (Shenzhen Balun Technology Co.,Ltd.)						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	Spectrum Analyzer	R&S	FSV-40	101544	2017-02-17	2018-02-16
2	Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2017-01-07	2018-01-06
3	Amplifier	COM-MV	ZLNA-18-40G-021	1608001	2017-02-17	2018-02-16
4	Cable	Top	18-40GHz	-	2017-02-17	2018-02-16

6.2 Description of Support Units

Equipment	Manufacturer	Model No.
/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	± 1 x 10^{-6}
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)
Confidence interval：95%. Confidence factor:k=2	

6.4 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

N/A

7 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	Pass
Conducted Spurious emissions	15.247(d)	Pass
Band edge	15.247(d) 15.205(a)	Pass
Conduct Emission	15.207	Pass
Bandwidth	15.247(a)(1)	Pass
Maximum Peak Output Power	15.247(b)(1)	Pass
Frequency Separation	15.247(a)(1)	Pass
Number of Hopping Frequency	15.247(a)(1)(iii)	Pass
Dwell time	15.247(a)(1)(iii)	Pass
Antenna Requirement	15.203	Pass
RF Exposure	1.1307(b)(1)	Pass
Note: Pass=Compliance; Fail=Not Compliance; N/A=Not Applicable.		

8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

Frequency (MHz)	Limit (dBμV)	
	Qsi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	50	60
5 to 30	60	50

8.1 E.U.T. Operation

Operating Environment **:**

Temperature: 22.8 °C

Humidity: 52.6 % RH

Atmospheric Pressure: 101.2kPa

Test Voltage: AC 120V, 60Hz

EUT Operation :

The test was performed in transmitting mode, the worst test data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



8.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

Remark: only the worst data (GFSK modulation Low channel mode) were reported.

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1620	44.81	9.64	54.45	65.36	-10.91	QP	
2	0.1620	40.75	9.64	50.39	55.36	-4.97	AVG	
3	0.1940	43.77	9.62	53.39	63.86	-10.47	QP	
4	0.1940	40.20	9.62	49.82	53.86	-4.04	AVG	
5	0.2380	42.41	9.64	52.05	62.16	-10.11	QP	
6	0.2380	39.13	9.64	48.77	52.16	-3.39	AVG	
7	0.2740	40.87	9.64	50.51	60.99	-10.48	QP	
8	0.2740	37.73	9.64	47.37	50.99	-3.62	AVG	
9	0.3140	38.94	9.64	48.58	59.86	-11.28	QP	
10	0.3140	35.93	9.64	45.57	49.86	-4.29	AVG	
11	0.7620	36.64	9.76	46.40	56.00	-9.60	QP	
12	0.7620	31.79	9.76	41.55	46.00	-4.45	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1580	44.84	9.64	54.48	65.56	-11.08	QP	
2	0.1580	40.87	9.64	50.51	55.56	-5.05	AVG	
3	0.1900	43.64	9.63	53.27	64.03	-10.76	QP	
4	0.1900	39.91	9.63	49.54	54.03	-4.49	AVG	
5	0.2260	42.26	9.63	51.89	62.59	-10.70	QP	
6	0.2260	38.91	9.63	48.54	52.59	-4.05	AVG	
7	0.2660	40.74	9.64	50.38	61.24	-10.86	QP	
8	0.2660	37.63	9.64	47.27	51.24	-3.97	AVG	
9	0.3140	38.74	9.64	48.38	59.86	-11.48	QP	
10	0.3140	35.75	9.64	45.39	49.86	-4.47	AVG	
11	0.7780	35.45	9.77	45.22	56.00	-10.78	QP	
12	0.7780	30.65	9.77	40.42	46.00	-5.58	AVG	

9 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment **:**

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa

Test Voltage: DC 3.7V

EUT Operation **:**

The test was performed in transmitting mode.

9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10:2013.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz

Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto
Detector ..... PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed ..... Auto
Detector ..... PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector ..... Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.
8. For the radiated emission test above 1GHz:

   Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Limit

9.6 Summary of Test Results

Test Frequency: 8MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency: 30MHz ~ 18GHz

Remark: only the worst data (GFSK modulation) were reported.

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel									
268.33	35.20	QP	296	1.8	H	-13.35	21.85	46.00	-24.15
268.33	40.18	QP	343	1.3	V	-13.35	26.83	46.00	-19.17
4804.00	46.20	PK	307	1.7	V	-1.06	45.14	74.00	-28.86
4804.00	43.13	Ave	307	1.7	V	-1.06	42.07	54.00	-11.93
7206.00	40.16	PK	75	1.8	H	1.33	41.49	74.00	-32.51
7206.00	35.02	Ave	75	1.8	H	1.33	36.35	54.00	-17.65
2326.83	45.05	PK	360	1.8	V	-13.19	31.86	74.00	-42.14
2326.83	37.87	Ave	360	1.8	V	-13.19	24.68	54.00	-29.32
2379.56	44.99	PK	226	1.6	H	-13.14	31.85	74.00	-42.15
2379.56	38.78	Ave	226	1.6	H	-13.14	25.64	54.00	-28.36
2486.34	42.47	PK	328	1.6	V	-13.08	29.39	74.00	-44.61
2486.34	36.65	Ave	328	1.6	V	-13.08	23.57	54.00	-30.43

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel									
268.33	34.03	QP	147	1.0	H	-13.35	20.68	46.00	-25.32
268.33	41.02	QP	313	1.8	V	-13.35	27.67	46.00	-18.33
4882.00	46.58	PK	200	1.8	V	-0.62	45.96	74.00	-28.04
4882.00	44.27	Ave	200	1.8	V	-0.62	43.65	54.00	-10.35
7323.00	40.03	PK	119	1.3	H	2.21	42.24	74.00	-31.76
7323.00	34.83	Ave	119	1.3	H	2.21	37.04	54.00	-16.96
2343.29	45.99	PK	263	1.2	V	-13.19	32.80	74.00	-41.20
2343.29	37.03	Ave	263	1.2	V	-13.19	23.84	54.00	-30.16
2374.65	44.27	PK	274	1.4	H	-13.14	31.13	74.00	-42.87
2374.65	37.56	Ave	274	1.4	H	-13.14	24.42	54.00	-29.58
2497.07	44.16	PK	291	1.9	V	-13.08	31.08	74.00	-42.92
2497.07	37.84	Ave	291	1.9	V	-13.08	24.76	54.00	-29.24

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel									
268.33	34.00	QP	246	2.0	H	-13.35	20.65	46.00	-25.35
268.33	38.34	QP	275	1.5	V	-13.35	24.99	46.00	-21.01
4960.00	46.55	PK	285	1.6	V	-0.24	46.31	74.00	-27.69
4960.00	43.27	Ave	285	1.6	V	-0.24	43.03	54.00	-10.97
7440.00	39.49	PK	222	1.3	H	2.84	42.33	74.00	-31.67
7440.00	33.63	Ave	222	1.3	H	2.84	36.47	54.00	-17.53
2348.16	45.58	PK	179	1.3	V	-13.19	32.39	74.00	-41.61
2348.16	39.72	Ave	179	1.3	V	-13.19	26.53	54.00	-27.47
2381.14	42.37	PK	7	1.6	H	-13.14	29.23	74.00	-44.77
2381.14	38.02	Ave	7	1.6	H	-13.14	24.88	54.00	-29.12
2497.23	43.25	PK	170	1.5	V	-13.08	30.17	74.00	-43.83
2497.23	37.34	Ave	170	1.5	V	-13.08	24.26	54.00	-29.74

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not recorded.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v04, April 5, 2017

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
   RBW = 100kHz, VBW = 300kHz, Sweep = auto
   Detector function = peak, Trace = max hold

10.2 Test Result

9K~30MHZ

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



π/4 DQPSK Low Channel



π/4 DQPSK Middle Channel



π/4 DQPSK High Channel



Above 30MHz

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



π/4 DQPSK Low Channel



π/4 DQPSK Middle Channel



π/4 DQPSK High Channel



11 Band Edge Measurement

Test Requirement:	Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10:2013
Test Limit:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

11.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
   Detector function = peak, Trace = max hold

11.2 Test Result

GFSK Transmitting Band edge-left side



GFSK Hopping Band edge-left side



GFSK Transmitting Band edge-right side



GFSK Hopping Band edge-right side



π/4 DQPSK Transmitting Band edge-left side



π/4 DQPSK Hopping Band edge-left side



π/4 DQPSK Transmitting Band edge-right side



π/4 DQPSK Hopping Band edge-right side



12 Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10:2013

Test Mode: Test in fixing operating frequency at low, Middle, high channel.

12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz

12.2 Test Result

Modulation	Test Channel	20dB Bandwidth(MHz)	99% Bandwidth(MHz)
GFSK	Low	0.916	0.844
GFSK	Middle	0.916	0.844
GFSK	High	0.916	0.844
π/4 DQPSK	Low	1.257	1.168
π/4 DQPSK	Middle	1.257	1.168
π/4 DQPSK	High	1.257	1.168

Test plots

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



π/4 DQPSK Low Channel



π/4 DQPSK Middle Channel



π/4 DQPSK High Channel



13 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10:2013

Test Limit: Regulation 15.247 (b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Test mode: Test in fixing frequency transmitting mode.

13.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

13.2 Test Result

Modulation	Test Channel	Output Power (dBm)	Limit (dBm)
GFSK	Low	-3.37	30
GFSK	Middle	-3.60	30
GFSK	High	-3.61	30
π/4 DQPSK	Low	-1.93	21
π/4 DQPSK	Middle	-2.14	21
π/4 DQPSK	High	-2.30	21

Test plots

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



π/4 DQPSK Low Channel



π/4 DQPSK Middle Channel



π/4 DQPSK High Channel



14 Hopping Channel Separation

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10:2013

Test Limit: Regulation 15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125W.

Test Mode: Test in hopping transmitting operating mode.

14.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

14.2 Test Result

Modulation	Test Channel	Separation (MHz)	Result
GFSK	Low	1.000	PASS
GFSK	Middle	1.000	PASS
GFSK	High	1.000	PASS
π/4 DQPSK	Low	1.000	PASS
π/4 DQPSK	Middle	1.000	PASS
π/4 DQPSK	High	1.000	PASS

Test plots

GFSK Low Channel



GFSK Middle Channel



GFSK High Channel



π/4 DQPSK Low Channel



π/4 DQPSK Middle Channel



π/4 DQPSK High Channel



15 Number of Hopping Frequency

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	ANSI C63.10:2013
Test Limit:	Regulation 15.247 (a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Test Mode:	Test in hopping transmitting operating mode.

15.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 300 KHz. VBW = 300 KHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.483GHz. Sweep=auto;

15.2 Test Result

Test Plots:

GFSK



Pi/4 DQPSK


Offs 0.50 dB
* Att 20 dB
Batt Ref 10.50 dBm
* RBW 100 kHz
* VBW 300 kHz
SWT 10ms
D1[1] -0.55 dB
78.250000000 MHz
M1[1] -3.48 dBm
2.401840000 GHz
1Pk
Max
M1
D1
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
Start 2.4 GHz
Stop 2.4835 GHz

16 Dwell Time

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: ANSI C63.10:2013

Test Limit: Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Mode: Test in hopping transmitting operating mode.

16.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz.Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

16.2 Test Result

DH5 Packet permit maximum 1600 / 79 / 6 hops per second in each channel (5 time slots RX, 1 time slot TX).

DH3 Packet permit maximum 1600 / 79 / 4 hops per second in each channel (3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum 1600 / 79 /2 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:

Data Packet	Dwell Time(s)
DH5	1600/79/6*0.4*79*(MkrDelta)/1000
DH3	1600/79/4*0.4*79*(MkrDelta)/1000
DH1	1600/79/2*0.4*79*(MkrDelta)/1000
Remark: Mkr Delta is once pulse time.	

Modulation	Data Packet	Channel	pulse time(ms)	Dwell Time(s)	Limits(s)
GFSK	DH5	Low	2.920	0.311	0.4
		middle	2.920	0.311	0.4
		High	2.920	0.311	0.4
π/4DQPSK	2DH5	Low	2.920	0.311	0.4
		middle	2.920	0.311	0.4
		High	2.920	0.311	0.4

Remark: Only the worst-case is recorded.

Test Plots
GFSK DH5 Low Channel



GFSK DH5 Middle Channel



GFSK DH5 High Channel



π/4DQPSK 2DH5 Low Channel



π/4DQPSK 2DH5 Middle Channel



π/4DQPSK 2DH5 High Channel



17 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has a PCB Printed Antenna. meets the requirements of FCC 15.203.



18 RF Exposure

Note: Please refer to attachment: RF Exposure Report.

19 Photographs -Test Setup Photos

19.1 Photograph-Conducted Emissions Test Setup



19.2 Photograph-Radiated Emissions

Test Frequency 30MHz to 1GHz





Test Frequency Above 1GHz





20 Photographs - Constructional Details

20.1 EUT – External photos



Fan
AC 120V 60Hz 60W
Model:ATF-005WL
Ningbo Aotian Electrical Appliances
Co.,Ltd.

ON/OFF
BLUETOOTH
SPEED
SWING
LIGHT ON/OFF
TIMER

20.2 EUT – Internal photos












ANT


YS_AC6905C_V1.0
20170311
1cm 2 3 4 5










1cm 2 3 4 5 6


1cm 2 3 4 5 6


1cm 2 3 4 5 6


1cm 2 3 4 5 6


ATF-006WL
AO TIAN
AC1
1cm 2 3 4 5 6 7


1cm 2 3 4 5 6 7 8


BT
ATF005WL-BT-LED
T=1.6MM
AO TIAN
2017.3.13
LM11855
1cm 2 3 4


1cm 2 3 4





======End of Report======