



Test Report No. 9612332870

For Theranica Bioelectronics Ltd.

Equipment Under Test:

Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

***From The Standards Institution
Of Israel***

Industry Division

Electronics & Telematics Laboratory

EMC Branch



Certificate Number: AT-1359



Test report No: 9612332870

Page 2 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

Table of Contents

1. Applicant information	3
2. Test performance	3
3. Summary of test:	5
4. Equipment under test description.	6
4.1 General description.....	6
5. Test results	8
5.1 Transmitter characteristics	8
5.1.1 Transmitter 6 dB occupied bandwidth.	8
5.1.2 Maximum conducted output power test.....	10
5.1.3 Power spectral density test	12
5.1.4 Radiated emissions test according to §§ 15.247(d), 15.205(a)	14
5.1.5 Radiated emissions test according to § 15.209	19
APPENDIX A Test equipment used.....	22
APPENDIX B Photo of the test setups.....	27
APPENDIX C Abbreviations and acronyms.....	28

**Test report No:** 9612332870**Page 3 of 28 Pages****Title:** Migra transceiver**Model:** Nerivio Migra1**FCC ID:** 2AOH8-NM1

1. Applicant information

Applicant:	Theranica Bioelectronics Ltd..
Address:	45 Hamelacha st., Entrance 3, 4250574, Netanya Israel
Sample for test selected by:	The customer
The date of tests:	5,14,19 November 2017

Equipment under test information

Description of Equipment Under Test (EUT):	Migra transceiver
Model:	Nerivio Migra1
Software version of radio unit:	FW Version 1.0.1.15, sub-version T7
Hardware version:	TI CC2564RVMT
Manufactured by:	Theranica Bioelectronics Ltd.

2. Test performance

Location:	SII EMC Section
Purpose of test:	Apparatus compliance verification in accordance with emission requirements
Test specifications:	47CFR part 15.247, 15.205, 15.207, 15.209 and part 1 §1.1310

This Test Report contains 28 pages and may be used only in full.

This Test Report applies only to the specimen tested and may not be applied to other specimens of the same product.



Test report No: 9612332870

Page 4 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

Normative References.

FCC 47 CFR Part 15, Subpart C, 2017	Radio Frequency Devices Subpart C – Intentional Radiators
ANSI C63.4: 2014	American National Standard for Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10: 2013	American National Standard for Testing of Unlicensed Wireless Devices.
FCC OET KDB 558074, April 2017	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

**Test report No: 9612332870****Page 5 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1**

3. Summary of test:

The EUT was found to comply with requirements of: 47CFR Part 15, §§ 15.247, 15.205, 15.207, 15.209.

Transmitter characteristics	Subclasses
Minimum 6 dB bandwidth	15.247(a)(2)
Maximum output power	15.247(b)(3)
Peak power spectral density	15.247(e)
Out of band spurious emissions radiated	15.205, 15.247(d)
Unwanted radiated emissions below 1 GHz	15.209

Electronics and
Telematics Laboratory

November 2017

Name: Eng. Yuri Rozenberg
Position: Head of EMC Branch.

Name: Michael Feldman.
Position: Test engineer.

Measurement uncertainty.

The test equipment was calibrated according to its recommended procedures and is within the manufacturer's published limit of error.

The laboratory calibrates its standards by a third party (traceable to NIST, USA) on a regular basis according to equipment manufacturer requirements.

In the following table the uncertainty calculation is given.

Test description	Calculated uncertainty U_{LAB}
Conducted measurements	
Frequency error	37.6 Hz
Spurious emission	± 2.98 dB
Radiated emissions	
Electric field strength in a SAR at 3 m distance 30 MHz – 1.0 GHz	± 4.32 dB
Electric field strength in a FAR at 3 m distance 1.0 GHz – 18 GHz	± 4.47
Substitution measurements	
In a FAR at 3 m distance 1.0 GHz – 18 GHz	± 3.41 dB

**Test report No: 9612332870****Page 6 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1**

4. Equipment under test description.

*The applicant provided description.

4.1 General description

Nerivio Migra1 (the EUT) is a wearable, battery-powered device for the acute treatment of migraines with or without aura. The transmitter operates with Bluetooth 4.1 communication standard via a mobile application.

EUT technical characteristics

Transmitter technical characteristics:		Note
Assigned frequency band	2400 MHz – 2483.5 MHz	-
Operating frequency range:	2402 MHz – 2480 MHz	-
DTS transmitter:	BLE 4.1	-
Types of modulation:	GFSK	-
Declare temperature range:	0°C - 35°C	Normal indoor use
Antenna information		
Type	Manufacturer/Model	Antenna gain, dBi
Internal SMD Ship antenna	Fractus. FR05-S1-N-0-102	1.7

Test report No: 9612332870

Page 7 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1




Figure 1. Nerivio Migra1 block diagram.




Fig.2. RE test setup above 1 GHz.

**Test report No: 9612332870****Page 8 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1**

5. Test results

5.1 Transmitter characteristics

5.1.1 Transmitter 6 dB occupied bandwidth.

Method of measurement	558074 D01 DTS Meas Guidance. Section 8.1				
Operating Frequency Range	2402– 2480 MHz				
Detector used	Peak				
Resolution bandwidth	100 kHz				
Video bandwidth	> 3 x RBW.				
Trace mode	Max Hold.				
Sweep time:	Auto couple.				
Ambient Temperature	22° C	Relative Humidity	53%	Air Pressure	1010 hPa

The minimum 6 dB occupied bandwidth shall be at least 500 kHz.

Carrier frequency, MHz	Measured 6 dB occupied bandwidth, kHz	6 dB occupied bandwidth limit, kHz	Reference to plot #
2402	547	500	1
2440	545	500	2
2480	519	500	3

TEST EQUIPMENT USED:

1	3	14				
---	---	----	--	--	--	--




Test report No: 9612332870

Page 9 of 28 Pages


Title: Migra transceiver

Model: Nerivio Migra1


FCC ID: 2AOH8-NM1



Plot # 1.



Plot # 2.



Plot # 3.

**Test report No: 9612332870****Page 10 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****5.1.2 Maximum conducted output power test.**

Operating Frequency Range	2402– 2480 MHz
Detector used	RMS
Resolution bandwidth	1 MHz
Video bandwidth	3 x RBW.
Trace mode	Max Hold.
Ambient Temperature	23 ⁰ C
Relative Humidity	53%
Air Pressure	1010 hPa

For Digital Transmit System the peak conducted output power in the 2400 – 2483.5 MHz band shall not exceed 1W (30 dBm) with antennas gain that do not exceed 6 dBi.

Carrier frequency, MHz	Field strength, dBμV/m	**EIR power, dBm	*Conducted output power, dBm	Conducted power limit, dBm	Reference to plot #
2402	88.9	-6.3	-8	30	4
2440	88.6	-6.6	-8.3	30	5
2480	86.6	-8.6	-10.3	30	6

*The maximum conducted output power = EIR power – Antenna gain. Antenna gain = 1.7 dBi.

**EIR power = E Field strength (dBμV/m@3m) - 95.2.

Measured field straight level was converted to EIRP level. The EIRP calculation provided after verification according to substitution test method. EUT was replaced by generator and substitution antenna. Result calculated from generator output level, substitution antenna gain and loss of connected cable was used for EIRP calculation.

Transmitter was operated at continuous transmit mode at bottom, middle and top of the 2402 – 2480 MHz frequency band and at maximum output power and maximum data bit rate.

TEST EQUIPMENT USED:

1	2	3	5	8	9	13
---	---	---	---	---	---	----




Test report No: 9612332870

Title: Migra transceiver


Model: Nerivio Migra1

Page 11 of 28 Pages


FCC ID: 2AOH8-NM1



Plot # 4. Carrier frequency – 2402 MHz



Plot # 5. Carrier frequency – 2440 MHz



Plot # 6. Carrier frequency – 2480 MHz

**Test report No: 9612332870****Page 12 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****5.1.3 Power spectral density test**

Operating Frequency Range 2402– 2480 MHz
Detector used Peak
Resolution bandwidth 100 kHz
Video bandwidth 3 x RBW.
Trace mode Max Hold.
Ambient Temperature 23⁰ C **Relative Humidity** 53% **Air Pressure** 1010 hPa

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Carrier frequency, MHz	Field strength, dBμV/m	*EIR power, dBm	**Conducted PSD, dBm	Conducted PSD limit, dBm/3 kHz	Reference to plot #
2402	85.6	-9.6	-26.5	8	7
2440	84.6	-10.6	-27.5	8	8
2480	82.9	-12.3	-29.2	8	9

**The conducted to antenna PSD:

EIR power – Antenna gain + 10 Log (3 kHz RBW/ 100 kHz RBW). Where antenna gain = 1.7 dBi.

*EIRP = E Field strength (dBμV/m@3m) - 95.2.

Calculation of EIRP performed after verification by substitution method.

TEST SUMMARY

EUT maximum output power result is below PSD limit per 47 CFR 15.247 (e).

The EUT was found complies with standard requirement.

TEST EQUIPMENT USED:

1	3	14				
---	---	----	--	--	--	--




Test report No: 9612332870

Title: Migra transceiver


Model: Nerivio Migra1

Page 13 of 28 Pages


FCC ID: 2AOH8-NM1



Plot # 7. Carrier frequency – 2402 MHz



Plot # 8. Carrier frequency – 2440 MHz



Plot # 9. Carrier frequency – 2480 MHz

**Test report No: 9612332870****Page 14 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****5.1.4 Radiated emissions test according to §§ 15.247(d), 15.205(a)**

Method of measurement	558074 D01 DTS Meas Guidance. Sec. 12.1.		
Operating Frequency Range	2402– 2480 MHz		
Detector used:	Trace 1 – Peak; Trace 2 - RMS		
Resolution bandwidth	1 MHz/100 kHz		
Video bandwidth	3x RBW.		
Trace mode:	Trace 1 – Max hold; Trace 2 – Power averaging.		
Ambient Temperature	23 ⁰ C	Relative Humidity	53% Air Pressure 1010 hPa

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

In addition, radiated emissions, which fall in the restricted bands, as, defined in Section 15.205(a) must also comply with the radiated emission limits specified in Section 15.209(a).

Carrier frequency 2402 MHz

Frequency, MHz	Radiated emissions, dBμV/m	Peak limit, dBμV/m	Avg limit, dBμV/m	Margin, dB	Note	Note	Reference to plot#
2380.3	50.7	74	-	>20	*RB	Detector peak	10
2380.3	40.1	-	54	13.9	RB	Detector average	10
2400.0	52.0	64.8	-	12.8	Band edge	Detector peak.	11
4786.0	51.0	74.0	-	>20	RB	Detector peak	12
4786.0	41.0	-	54	14.0	RB	Detector average	12
10887	55.8	74.0	-	18.2	RB	Detector peak	13
10887	45.7	-	54.0	8.3	RB	Detector average	13

*RB – restricted band

Carrier frequency 2440 MHz

Frequency, MHz	Radiated emissions, dBμV/m	Peak limit, dBμV/m	Avg limit, dBμV/m	Margin, dB	Note	Note	Reference to plot#
2380.3	50.7	74	-	>20	RB	Detector peak	15
2380.3	40.2	-	54	13.8	RB	Detector average	15
2400	52.0	64.8	-	12.8	Band edge	Detector peak.	16
4786	51.0	74	-	>20	RB	Detector peak	17
4786	41.0	-	54	13.0	RB	Detector average	17

**Test report No: 9612332870****Page 15 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1**

Carrier frequency 2480 MHz

Frequency, MHz	Radiated emissions, dB μ V/m	Peak limit, dB μ V/m	Avg limit, dB μ V/m	Margin, dB	Note	Note	Reference to plot#
2224.6	51.6	74	-	>20	*RB	Detector peak	20
2224.6	39.8	-	54	14.2	RB	Detector average.	20
2483.9	52.0	74	-	>20	RB	Detector peak	22
2483.9	39.9	-	54	14.1	RB	Detector average	22
5430	54.5	74	-	19.5	RB	Detector peak	23
5430	44.7	-	54	9.3	RB	Detector average	23

*RB – restricted band

TEST SUMMARY

All emissions outside of the 2400 – 2483.5 MHz frequency band were found below 15.247(d) limits.

TEST EQUIPMENT USED:

1	3	4	10	13	14	
---	---	---	----	----	----	--



Test report No: 9612332870


Title: Migra transceiver

Model: Nerivio Migra1


Page 16 of 28 Pages

FCC ID: 2AOH8-NM1


Carrier frequency – 2402 MHz.



Plot # 10




Plot # 11



Plot # 12



Plot # 13



Plot # 14.



Test report No: 9612332870


Title: Migra transceiver

Model: Nerivio Migra1


Page 17 of 28 Pages

FCC ID: 2AOH8-NM1


Carrier frequency - 2440 MHz.




Plot # 15




Plot # 16



Plot # 17



Plot # 18



Plot # 19.



Test report No: 9612332870

Title: Migra transceiver

Model: Nerivio Migra1

Page 18 of 28 Pages

FCC ID: 2AOH8-NM1

Carrier frequency 2480 MHz.




Plot # 20



Plot # 21




Plot # 22



Plot # 23



Plot # 24



Plot # 25

**Test report No: 9612332870****Page 19 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****5.1.5 Radiated emissions test according to § 15.209**

Method of measurement	ANSI C63.10 §6.5				
Detectors used	CISPR Quasi-Peak				
Resolution bandwidth	9 kHz/120 kHz				
Video bandwidth	>3 x RBW.				
Trace mode	Free run				
Ambient Temperature	24 ⁰ C	Relative Humidity	53%	Air Pressure	1010 hPa

TEST DESCRIPTION:

The measurements were performed at 3 m test distance in Anechoic chamber. The EUT was arranged on a polystyrene table 0.8 m height placed on the turn - table. The Active Loop antenna in 150 kHz to 30 MHz frequency band and Biconilog antenna in 30 MHz – 1.0 GHz frequency band were used. The emission level was maximized by initially rotating turntable through 360°, varying the antenna height between 1 m and 4 m, rerouting EUT cables and changing antenna polarization from vertical to horizontal.

REQUIREMENTS:

EUT radiated emission shall not exceed value required in section 15.209

TEST RESULT:

Test results are presented in a table below and in plots ## 70 - 71

TEST EQUIPMENT USED:

1	6	13	15			
---	---	----	----	--	--	--



Test report No: 9612332870

Page 20 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

Radiated emission test results.

Frequency (MHz)	Antenna polariz. V/H	Antenna Height m	Turn- table Angle (°)	Emission Level Note 1 dBμV/m	Limit @ 3m dBμV/m	Margin Note 2 dB	Results
36.8	V	1.0	227	17.2	40.0	>20	Pass
42.0	V	1.0	123	19.8	40.0	>20	Pass
44.3	V	1.0	327	21.9	40.0	18.1	Pass
544.4	H	1.7	149	30.9	46.0	15.1	Pass

Note 1: Emission level = E Reading (dBμV) + Cable loss (dB) + Antenna Factor (dB/m).
For Cable Loss and Antenna Factor refer to Appendix 2.

Note 2: Margin (dB) = Limit (dBμV/m) – Emission level (dBμV/m)




Test report No: 9612332870

Page 21 of 28 Pages


Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1



Plot # 26. Investigation result in 0.15 – 30 MHz frequency range.



Plot # 27. Investigation result in 30 - 1000 MHz frequency range.

**Test report No: 9612332870****Page 22 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****APPENDIX A Test equipment used.****Test equipment used**

No	Description	Manufacturer information			Due Calibration date
		Name	Model	Serial No	
1	MXE EMI Receiver 20 Hz -26.5 GHz	Agilent	N9038A	MY52130048	April 2018
2	Cable RF 1m	Huber-Suhner	Sucoflex 104	21325/4PE	October 2018
3	Double Ridged Guide Antenna 0.75 – 18 GHz	ETS-Lindgren	3115	00143138	December 2017
4	Broadband Horn antenna 15 – 40 GHz	Schwarzbeck Mess-Electronik	BBHA 9170	9170-341	December 2017
5	Double Ridged Waveguide Horn Antenna 1 – 18 GHz	ETS-Lindgren	3117	00139055	December 2017
6	Antenna Biconilog 26 – 6000 MHz	ETS-Lindgren	31142D	0146490	December 2017
7	Spectrum analyzer 20 Hz-40 GHz	Rohde&Schwarz	ESU 40	100168	November 2018
8	MXG Signal Generator 100 KHz - 20 GHz	Agilent	N5183A	6501148	May 2018
9	Attenuator 3 dB DC – 12.4 GHz	HP	8491A	50469	October 2018
10	USB preamplifier 2 GHz – 50 GHz	Keysight	U7227F	MY55380004	January 2018
11	LISN 9 kHz – 30 MHz	FCC	LISN 250-32-4-16	SII5023	October 2018
12	Transient limiter 0.009-200 MHz	HP	11947A	3107105	August 2018
13	Cable RF 4m	Huber-Suhner	Sucoflex 104PE	21329/4PE	October 2018
14	Cable RF 0.5m	Huber-Suhner	Multiflex 141	520201	October 2018
15	Active Loop antenna 1.0 kHz – 30 MHz	ETS-Lindgren	6507	00144641	December 2017



Test report No: 9612332870

Page 23 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

Cable Loss (Mast 6 m set cable.)

Point	Frequency (MHz)	Cable Loss (dB)	Point	Frequency (MHz)	Cable Loss (dB)
1	30	0.3	21	1000	2.5
2	50	0.4	22	1100	2.6
3	100	0.6	23	1200	2.8
4	150	0.8	24	1300	2.9
5	200	1.0	25	1400	3.1
6	250	1.1	26	1500	3.2
7	300	1.2	27	1600	3.3
8	350	1.3	28	1700	3.5
9	400	1.5	29	1800	3.6
10	450	1.6	30	1900	3.7
11	500	1.7	31	2000	3.9
12	550	1.8	32	2100	4.0
13	600	1.9	33	2200	4.1
14	650	1.9	34	2300	4.2
15	700	2.0	35	2400	4.4
16	750	2.1	36	2500	4.6
17	800	2.1	37	2600	4.7
18	850	2.2	38	2700	4.8
19	900	2.3	39	2800	4.9
20	950	2.4	40	2900	5.0



Test report No: 9612332870

Page 24 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

Antenna factor

Biconilog Antenna, ETS-Lindgren mod. 31142D, S/N: 0146490 3 m calibration.

f / MHz	AF / dB/m	f / MHz	AF / dB/m	f / MHz	AF / dB/m
30	18.7	250	12.0	2750	31.0
35	15.7	300	13.8	3000	31.2
40	12.9	400	16.2	3250	32.7
45	10.6	500	18.6	3500	34.5
50	9.0	600	20.2	3750	34.3
60	7.3	700	21.8	4000	34.5
70	7.7	800	22.9	4250	35.3
80	8.2	900	24.1	4500	35.5
90	9.2	1000	24.8	4750	36.1
100	9.4	1250	26.9	5000	37.4
120	8.5	1500	30.2	5250	38.4
140	8.5	1750	28.5	5000	39.9
160	9.1	2000	28.9	5750	38.2
180	10.5	2250	29.8	6000	39.1
200	10.9	2500	32.5	-	-

**Test report No: 9612332870****Page 25 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****Antenna Factor****Double Ridged Guide Antenna mfr ETS-Lindgren model 3115 1m calibration**

Point	Frequency (MHz)	Antenna Factor (dB/m)
1	1000	23.7
2	1500	25.5
3	2000	28.5
4	2500	28.1
5	3000	29.6
6	3500	31.1
7	4000	32.5
8	4500	32.5
9	5000	33.5
10	5500	34.7
11	6000	36.1
12	6500	36.5
13	7000	37.3
14	7500	38.0
15	8000	37.3
16	8500	37.9
17	9000	38.1
18	9500	38.5
19	10000	38.7
20	10500	38.8
21	11000	38.6
22	11500	38.8
23	12000	38.9
24	12500	39.3
25	13000	40.2
26	13500	40.6
27	14000	40.6
28	14500	40.4
29	15000	39.6
30	15500	39.5
31	16000	39.8
32	16500	40.4
33	17000	41.3
34	17500	42.6
35	18000	43.2

Cable Loss**Type: Sucoflex 104PE; Ser.No.21329/4PE; 4 m length**

Point	Frequency (GHz)	Cable Loss (dB)
0	0.0-1.8	1.67
1	1.8 – 3.6	2.39
2	3.6 – 5.4	3.04
3	5.4-7.2	3.58
4	7.2-9.0	4.06
5	9.0-10.8	4.49
6	10.8-12.6	4.91
7	12.6-14.4	5.31
8	14.4-16.2	5.66
9	16.2-18.00	6.01

**Test report No: 9612332870****Page 26 of 28 Pages****Title: Migra transceiver****Model: Nerivio Migra1****FCC ID: 2AOH8-NM1****Antenna Factor****Broadband Horn Antenna model BBHA 9170 1m calibration**

Point	Frequency (GHz)	Antenna Factor (dB/m)
1	15.0	38.5
2	16.0	37.7
3	17.0	38.1
4	18.0	37.9
5	19.0	38.0
6	20.0	38.0
7	21.0	37.9
8	22.0	38.2
9	23.0	39.6
10	24.0	39.6
11	25.0	39.3
12	26.0	39.5
13	27.0	39.6
14	28.0	39.6
15	30.0	40.1
16	32.0	41.2
17	34.0	41.5
18	35.0	41.9
19	36.0	42.2
20	38.0	43.8
21	40.0	43.2

Antenna Factor**For Antenna Loop MFR ETS Lindgren, Type/Model 6507, S/N: 00144641**

No.	Frequency MHz	Magnetic antenna factor, dBS/m	Electric antenna factor, dB/m
1	9	-21.5	30.0
2	10	-22.0	29.5
3	20	-27.7	23.8
4	50	-32.2	19.4
5	75	-33.0	18.5
6	100	-33.4	18.2
7	150	-33.6	17.9
8	250	-33.7	17.9
9	500	-33.8	17.8
10	750	-33.8	17.7
11	1000	-33.8	17.7
12	2000	-33.7	17.9
13	3000	-33.8	17.8
14	4000	-34.0	17.5
15	5000	-34.3	17.2
16	10000	-35.2	16.4
17	15000	-35.8	15.8
18	20000	-36.0	15.6
19	25000	-36.2	15.3
20	30000	-36.4	15.2



Test report No: 9612332870

Title: Migra transceiver

Model: Nerivio Migra1

Page 27 of 28 Pages

FCC ID: 2AOH8-NM1

APPENDIX B Photo of the test setups.




Photo 1.



Photo 2.



Photo 3.




Photo 4.



Test report No: 9612332870

Page 28 of 28 Pages

Title: Migra transceiver

Model: Nerivio Migra1

FCC ID: 2AOH8-NM1

APPENDIX C Abbreviations and acronyms.

The following abbreviations and acronyms are applicable to this test report:

AC	alternating current
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(μ V)	decibel referred to one microvolt
dB(μ V/m)	decibel referred to one microvolt per meter
EBW	emission bandwidth.
EMC	electromagnetic compatibility
EUT	equipment under test
GHz	gigahertz
H	height
Hz	hertz
kHz	kilohertz
L	length
LNA	low noise amplifier
m	meter
Mbps	megabit per second
MHz	megahertz
NA	not applicable
OFDM	Orthogonal Frequency Division Multiple Access
PRBS	pseudo random binary sequence
QP	quasi-peak
RF	radio frequency
RE	radiated emission
SA	spectrum analyzer
rms	root mean square
W	width