FCC RF Test Report

APPLICANT	:	Thundercomm Technology Co., Ltd
EQUIPMENT	:	Calculation Module
BRAND NAME	:	TurboX
MODEL NAME	:	C6125
FCC ID	:	2AOHHTURBOXC6125
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Sep. 06, 2021 ~ Sep. 21, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager

ACCREDITED Cert #5145.01

Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 5
1.6 Testing Location 6
1.7 Test Software 6
1.8 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency and Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB Bandwidth Measurement 12
3.2 Output Power Measurement 14
3.3 Power Spectral Density Measurement 15
3.4 Conducted Band Edges and Spurious Emission Measurement 17
3.5 Radiated Band Edges and Spurious Emission Measurement 30
3.6 AC Conducted Emission Measurement 34
3.7 Antenna Requirements 36
4 LIST OF MEASURING EQUIPMENT **37**
5 UNCERTAINTY OF EVALUATION **38**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR180601C	Rev. 01	Initial issue of report	Oct. 08, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 30dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.78 dB at 2483.520/2483.580 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.79 dB at 0.420 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Thundercomm Technology Co., Ltd
Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China

1.2 Manufacturer

Thundercomm Technology Co., Ltd
Building 4, No. 99, Data Valley Middle Road,Xiantao District, Yubei District Chongqing, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Calculation Module
Brand Name	TurboX
Model Name	C6125
FCC ID	2AOHHTURBOXC6125
SN Code	Radiation/Conduction/Conducted: MTR27M14003G
HW Version	DVT V03
SW Version	Turbox_C6125_LA1.0.FC.r001
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum Output Power to antenna	802.11b : 16.60 dBm (0.0457 W) 802.11g : 15.50 dBm (0.0355 W) 802.11n HT20 : 15.30 dBm (0.0339 W) 802.11n HT40 : 15.70 dBm (0.0372 W)
Antenna Type / Gain	Dipole Antenna type with gain 3.20 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN(2.4G) Link + Powered by Adapter
Remark: For Radiated Test Cases, The tests were performed with Adapter	

2.3 Connection Diagram of Test System

<For Radiated Emission >



<For Conducted Emission >



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Samsung	MG900	N/A	N/A	N/A
4.	Adapter	N/A	N/A	N/A	Shielded,1.2m	N/A
5.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 1.2 + 10 = 11.2 (dB)

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/3kHz)



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Chen Hong	**Temperature :**	21~25℃
		Relative Humidity :	51~54%

Test Mode :	802.11b	**Test Channel :**	01

100kHz PSD reference Level



Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11b	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Test Mode :	802.11b	Test Channel :	11

100kHz PSD reference Level	Channel Plot
	
Date: 6.SEP.2021 10:48:07	Date: 6.SEP.2021 10:48:19
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 6.SEP.2021 10:48:32	Date: 6.SEP.2021 10:48:43

Test Mode :	802.11g	Test Channel :	01

100kHz PSD reference Level	Channel Plot
	
Date: 6.SEP.2021 10:55:52	Date: 6.SEP.2021 10:57:31
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 6.SEP.2021 10:57:53	Date: 6.SEP.2021 10:58:10

Test Mode :	802.11g	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Test Mode :	802.11g	Test Channel :	11

100kHz PSD reference Level	Channel Plot
	
Date: 6.SEP.2021 11:23:11	Date: 6.SEP.2021 11:23:26
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 6.SEP.2021 11:23:51	Date: 6.SEP.2021 11:24:02

Test Mode :	802.11n HT20	Test Channel :	01

100kHz PSD reference Level	Channel Plot
	
Date: 6.SEP.2021 11:06:25	Date: 6.SEP.2021 16:07:18
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 6.SEP.2021 11:36:45	Date: 6.SEP.2021 11:37:03

Test Mode :	802.11n HT20	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Test Mode :	802.11n HT20	Test Channel :	11

100kHz PSD reference Level	Channel Plot
	
Date: 6.SEP.2021 12:00:12	Date: 6.SEP.2021 12:00:34
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 6.SEP.2021 12:00:49	Date: 6.SEP.2021 12:01:00

Test Mode :	802.11n HT40	Test Channel :	03

100kHz PSD reference Level	Channel Plot
	
Date: 10.SEP.2021 11:17:49	Date: 10.SEP.2021 11:19:38
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 10.SEP.2021 11:23:23	Date: 10.SEP.2021 11:23:53

Test Mode :	802.11n HT40	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Test Mode :	802.11n HT40	Test Channel :	09

100kHz PSD reference Level	Channel Plot
	
Date: 10.SEP.2021 11:33:28	Date: 10.SEP.2021 11:33:39
Spurious Emission 30MHz~3GHz	**Spurious Emission 2GHz~25GHz**
	
Date: 10.SEP.2021 11:36:58	Date: 10.SEP.2021 11:37:22

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 08, 2021	Sep. 06, 2021~ Sep. 10, 2021	Apr. 07, 2022	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 25, 2020	Sep. 06, 2021~ Sep. 10, 2021	Dec. 24, 2021	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 25, 2020	Sep. 06, 2021~ Sep. 10, 2021	Dec. 24, 2021	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 03, 2020	Sep. 21, 2021	Dec. 02, 2021	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 21, 2021	Sep. 21, 2021	Jul. 20, 2022	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 22, 2021	Sep. 21, 2021	Jun. 21, 2022	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Jul. 15, 2021	Sep. 21, 2021	Jul. 14, 2022	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 25, 2021	Sep. 21, 2021	Jul. 24, 2022	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 11, 2021	Sep. 21, 2021	Apr. 10, 2022	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 07, 2021	Sep. 21, 2021	Apr. 06, 2022	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 16, 2020	Sep. 21, 2021	Oct. 15, 2021	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 16, 2020	Sep. 21, 2021	Oct. 15, 2021	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 21. 2021	Sep. 21, 2021	Jul. 20. 2022	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Sep. 21, 2021	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Sep. 21, 2021	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Sep. 21, 2021	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Mar. 08, 2021	Sep. 06, 2021	Mar. 07, 2022	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2 LISN	00103912	9kHz~30MHz	Dec. 25, 2020	Sep. 06, 2021	Dec. 24, 2021	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 15, 2020	Sep. 06, 2021	Oct. 14, 2021	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 14, 2021	Sep. 06, 2021	Jul. 13, 2022	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.2dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.2dB**

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.0dB**

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.3dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Chen Hong	Temperature:	21~25	°C
Test Date:	2021/9/6~2021/9/10	Relative Humidity:	51~54	%

Report Number : FR180601C

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	13.99	-	9.02	-	0.50	Pass
11b	1Mbps	1	6	2437	13.94	-	9.06	-	0.50	Pass
11b	1Mbps	1	11	2462	13.94	-	9.02	-	0.50	Pass
11g	6Mbps	1	1	2412	17.78	-	15.71	-	0.50	Pass
11g	6Mbps	1	6	2437	17.88	-	15.75	-	0.50	Pass
11g	6Mbps	1	11	2462	17.83	-	15.46	-	0.50	Pass
HT20	MCS0	1	1	2412	18.83	-	16.42	-	0.50	Pass
HT20	MCS0	1	6	2437	18.88	-	16.88	-	0.50	Pass
HT20	MCS0	1	11	2462	18.88	-	15.45	-	0.50	Pass
HT40	MCS0	1	3	2422	36.46	-	35.45	-	0.50	Pass
HT40	MCS0	1	6	2437	36.56	-	35.42	-	0.50	Pass
HT40	MCS0	1	9	2452	36.46	-	35.14	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 1	Ant 1	Ant 1	Ant 1	Ant 1	
11b	1Mbps	1	1	2412	16.30	30.00	3.20	19.50	36.00	Pass
11b	1Mbps	1	6	2437	16.30	30.00	3.20	19.50	36.00	Pass
11b	1Mbps	1	11	2462	16.60	30.00	3.20	19.80	36.00	Pass
11g	6Mbps	1	1	2412	15.20	30.00	3.20	18.40	36.00	Pass
11g	6Mbps	1	6	2437	15.30	30.00	3.20	18.50	36.00	Pass
11g	6Mbps	1	11	2462	15.50	30.00	3.20	18.70	36.00	Pass
HT20	MCS0	1	1	2412	15.10	30.00	3.20	18.30	36.00	Pass
HT20	MCS0	1	6	2437	15.10	30.00	3.20	18.30	36.00	Pass
HT20	MCS0	1	11	2462	15.30	30.00	3.20	18.50	36.00	Pass
HT40	MCS0	1	3	2422	15.70	30.00	3.20	18.90	36.00	Pass
HT40	MCS0	1	6	2437	15.70	30.00	3.20	18.90	36.00	Pass
HT40	MCS0	1	9	2452	14.60	30.00	3.20	17.80	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.

Report Number : FR180601C

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-7.42	-	-	3.20	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-7.01	-	-	3.20	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-6.56	-	-	3.20	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-11.05	-	-	3.20	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-9.30	-	-	3.20	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-8.99	-	-	3.20	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-10.20	-	-	3.20	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-9.23	-	-	3.20	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-9.71	-	-	3.20	-	8.00	-	Pass
HT40	MCS0	1	3	2422	-12.66	-	-	3.20	-	8.00	-	Pass
HT40	MCS0	1	6	2437	-12.47	-	-	3.20	-	8.00	-	Pass
HT40	MCS0	1	9	2452	-11.44	-	-	3.20	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Xie YuQiang	**Temperature :**	22~25℃
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C QP LISN_20201030_L LINE

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.16	25.09	-30.51	55.60	15.00	0.08	10.01	Average
2		0.16	33.49	-32.11	65.60	23.40	0.08	10.01	QP
3		0.19	16.61	-37.45	54.06	6.50	0.08	10.03	Average
4		0.19	29.51	-34.55	64.06	19.40	0.08	10.03	QP
5		0.23	16.29	-36.06	52.35	6.21	0.05	10.03	Average
6		0.23	29.39	-32.96	62.35	19.31	0.05	10.03	QP
7		0.42	29.83	-17.59	47.42	19.70	0.08	10.05	Average
8	*	0.42	44.63	-12.79	57.42	34.50	0.08	10.05	QP
9		0.84	17.93	-28.07	46.00	7.80	0.10	10.03	Average
10		0.84	30.73	-25.27	56.00	20.60	0.10	10.03	QP
11		13.27	16.47	-33.53	50.00	5.80	0.43	10.24	Average
12		13.27	24.67	-35.33	60.00	14.00	0.43	10.24	QP

Test Engineer :	Xie YuQiang	**Temperature :**	22~25℃
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C QP LISN_20201030_N NEUTRAL

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.15	28.89	-27.11	56.00	18.80	0.08	10.01	Average
2		0.15	34.29	-31.71	66.00	24.20	0.08	10.01	QP
3		0.16	21.79	-33.73	55.52	11.70	0.08	10.01	Average
4		0.16	33.59	-31.93	65.52	23.50	0.08	10.01	QP
5		0.20	14.31	-39.31	53.62	4.20	0.08	10.03	Average
6		0.20	27.51	-36.11	63.62	17.40	0.08	10.03	QP
7		0.23	11.29	-41.06	52.35	1.21	0.05	10.03	Average
8		0.23	24.79	-37.56	62.35	14.71	0.05	10.03	QP
9		0.42	23.93	-23.44	47.37	13.79	0.09	10.05	Average
10	*	0.42	36.63	-20.74	57.37	26.49	0.09	10.05	QP
11		13.41	18.18	-31.82	50.00	7.49	0.44	10.25	Average
12		13.41	26.58	-33.42	60.00	15.89	0.44	10.25	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C. Radiated Spurious Emission

Test Engineer :	Zhao hui Liang	Temperature :	24~25 °C
		Relative Humidity :	48~49%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2330.37	54.93	-19.07	74	46.06	32	9.57	32.7	296	102	P	H
		2389.8	44.62	-9.38	54	35.68	32	9.64	32.7	296	102	A	H
		2412	110.52	-	-	101.46	32.1	9.66	32.7	296	102	P	H
		2412	107.33	-	-	98.27	32.1	9.66	32.7	296	102	A	H
		2336.56	54.96	-19.04	74	45.99	32.1	9.57	32.7	371	320	P	V
		2389.8	44.36	-9.64	54	35.42	32	9.64	32.7	371	320	A	V
		2412	108.68	-	-	99.62	32.1	9.66	32.7	371	320	P	V
		2412	105.47	-	-	96.41	32.1	9.66	32.7	371	320	A	V
802.11b CH 06 2437MHz		2364.04	54.83	-19.17	74	45.85	32.07	9.61	32.7	290	101	P	H
		2389.66	44.17	-9.83	54	35.23	32	9.64	32.7	290	101	A	H
		2437	109.82	-	-	100.53	32.3	9.69	32.7	290	101	P	H
		2437	106.76	-	-	97.47	32.3	9.69	32.7	290	101	A	H
		2483.58	54.93	-19.07	74	45.71	32.17	9.75	32.7	290	101	P	H
		2483.83	44.7	-9.3	54	35.48	32.17	9.75	32.7	290	101	A	H
		2319.38	55.02	-18.98	74	46.17	32	9.55	32.7	342	360	P	V
		2389.52	44.21	-9.79	54	35.27	32	9.64	32.7	342	360	A	V
		2437	108.31	-	-	99.02	32.3	9.69	32.7	342	360	P	V
		2437	105.08	-	-	95.79	32.3	9.69	32.7	342	360	A	V
		2483.97	54.87	-19.13	74	45.65	32.17	9.75	32.7	342	360	P	V
		2484.67	44.79	-9.21	54	35.57	32.17	9.75	32.7	342	360	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 11 2462MHz		2462	109.88	-	-	100.63	32.23	9.72	32.7	296	97	P	H
		2462	106.73	-	-	97.48	32.23	9.72	32.7	296	97	A	H
		2495.16	56.15	-17.85	74	46.99	32.1	9.76	32.7	296	97	P	H
		2483.52	45.07	-8.93	54	35.85	32.17	9.75	32.7	296	97	A	H
		2462	109.29	-	-	100.04	32.23	9.72	32.7	299	320	P	V
		2462	106.16	-	-	96.91	32.23	9.72	32.7	299	320	A	V
		2484.28	54.78	-19.22	74	45.56	32.17	9.75	32.7	299	320	P	V
		2483.52	44.85	-9.15	54	35.63	32.17	9.75	32.7	299	320	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	52.33	-21.67	74	58.61	33.85	12.01	52.14	400	107	P	H
		4824	45.7	-8.3	54	51.98	33.85	12.01	52.14	400	107	A	H
		4824	51.09	-22.91	74	57.37	33.85	12.01	52.14	176	356	P	V
		4824	43.96	-10.04	54	50.24	33.85	12.01	52.14	176	356	A	V
802.11b CH 06 2437MHz		4874	51.94	-22.06	74	58.27	33.73	12.04	52.1	392	91	P	H
		4874	44.5	-9.5	54	50.83	33.73	12.04	52.1	392	91	A	H
		7311	49.13	-24.87	74	51	35.76	14.16	51.79	-	-	P	H
		4874	51.17	-22.83	74	57.5	33.73	12.04	52.1	373	350	P	V
		4874	44.9	-9.1	54	51.23	33.73	12.04	52.1	373	350	A	V
		7311	48.47	-25.53	74	50.34	35.76	14.16	51.79	-	-	P	V
802.11b CH 11 2462MHz		4924	52.16	-21.84	74	58.45	33.7	12.07	52.06	374	79	P	H
		4924	46.05	-7.95	54	52.34	33.7	12.07	52.06	374	79	A	H
		7386	48.43	-25.57	74	50.14	35.78	14.21	51.7	-	-	P	H
		4924	52.16	-21.84	74	58.45	33.7	12.07	52.06	391	160	P	V
		4924	46.14	-7.86	54	52.43	33.7	12.07	52.06	391	160	A	V
		7386	49.47	-24.53	74	51.18	35.78	14.21	51.7	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.27	57.77	-16.23	74	53.03	27.8	9.64	32.7	384	17	P	H
		2389.90	46.81	-7.19	54	42.07	27.8	9.64	32.7	384	17	A	H
		2412	111.14	-	-	106.41	27.77	9.66	32.7	384	17	P	H
		2412	103.73	-	-	99	27.77	9.66	32.7	384	17	A	H
		2389.90	56.01	-17.99	74	51.27	27.8	9.64	32.7	339	128	P	V
		2389.8	43.87	-10.13	54	39.13	27.8	9.64	32.7	339	128	A	V
		2412	107.86	-	-	103.13	27.77	9.66	32.7	339	128	P	V
		2412	100.29	-	-	95.56	27.77	9.66	32.7	339	128	A	V
802.11g CH 06 2437MHz		2384.9	51.61	-22.39	74	46.85	27.83	9.63	32.7	332	46	P	H
		2389.8	40.72	-13.28	54	35.98	27.8	9.64	32.7	332	46	A	H
		2437	110.37	-	-	105.67	27.71	9.69	32.7	332	46	P	H
		2437	102.23	-	-	97.53	27.71	9.69	32.7	332	46	A	H
		2484.32	52.39	-21.61	74	47.68	27.66	9.75	32.7	332	46	P	H
		2483.5	43.02	-10.98	54	38.31	27.66	9.75	32.7	332	46	A	H
		2387.42	50.8	-23.2	74	46.07	27.8	9.63	32.7	370	315	P	V
		2389.66	40.08	-13.92	54	35.34	27.8	9.64	32.7	370	315	A	V
		2437	108.02	-	-	103.32	27.71	9.69	32.7	370	315	P	V
		2437	100.43	-	-	95.73	27.71	9.69	32.7	370	315	A	V
		2483.76	52.3	-21.7	74	47.59	27.66	9.75	32.7	370	315	P	V
		2483.55	41.64	-12.36	54	36.93	27.66	9.75	32.7	370	315	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 11 2462MHz		2462	111.01	-	-	106.3	27.69	9.72	32.7	375	43	P	H
		2462	103.17	-	-	98.46	27.69	9.72	32.7	375	43	A	H
		2483.52	55.06	-18.94	74	50.35	27.66	9.75	32.7	375	43	P	H
		2483.52	45.37	-8.63	54	40.66	27.66	9.75	32.7	375	43	A	H
		2462	108.4	-	-	103.69	27.69	9.72	32.7	372	125	P	V
		2462	100.84	-	-	96.13	27.69	9.72	32.7	372	125	A	V
		2483.96	52.91	-21.09	74	48.2	27.66	9.75	32.7	372	125	P	V
		2483.52	43.83	-10.17	54	39.12	27.66	9.75	32.7	372	125	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	45.71	-28.29	74	51.99	33.85	12.01	52.14	-	-	P	H
		4824	44.94	-29.06	74	51.22	33.85	12.01	52.14	-	-	P	V
802.11g CH 06 2437MHz		4874	45.71	-28.29	74	52.04	33.73	12.04	52.1	-	-	P	H
		7311	48.71	-25.29	74	50.58	35.76	14.16	51.79	-	-	P	H
		4874	45.89	-28.11	74	52.22	33.73	12.04	52.1	-	-	P	V
		7311	48.1	-25.9	74	49.97	35.76	14.16	51.79	-	-	P	V
802.11g CH 11 2462MHz		4924	46.17	-27.83	74	52.46	33.7	12.07	52.06	-	-	P	H
		7386	48.51	-25.49	74	50.22	35.78	14.21	51.7	-	-	P	H
		4924	46.54	-27.46	74	52.83	33.7	12.07	52.06	-	-	P	V
		7386	48.73	-25.27	74	50.44	35.78	14.21	51.7	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.27	59.65	-14.35	74	54.91	27.8	9.64	32.7	341	36	P	H
		2389.8	47.1	-6.9	54	42.36	27.8	9.64	32.7	341	36	A	H
		2412	111.45	-	-	106.72	27.77	9.66	32.7	341	36	P	H
		2412	102.73	-	-	98	27.77	9.66	32.7	341	36	A	H
		2389.38	56.13	-17.87	74	51.39	27.8	9.64	32.7	339	130	P	V
		2389.8	44.92	-9.08	54	40.18	27.8	9.64	32.7	339	130	A	V
		2412	107.56	-	-	102.83	27.77	9.66	32.7	339	130	P	V
		2412	99.64	-	-	94.91	27.77	9.66	32.7	339	130	A	V
802.11n HT20 CH 06 2437MHz		2388.26	51.89	-22.11	74	47.15	27.8	9.64	32.7	329	14	P	H
		2389.94	41.54	-12.46	54	36.8	27.8	9.64	32.7	329	14	A	H
		2437	113.05	-	-	108.35	27.71	9.69	32.7	329	14	P	H
		2437	104.8	-	-	100.1	27.71	9.69	32.7	329	14	A	H
		2483.83	54.69	-19.31	74	49.98	27.66	9.75	32.7	329	14	P	H
		2483.5	45.39	-8.61	54	40.68	27.66	9.75	32.7	329	14	A	H
		2329.18	51.3	-22.7	74	46.52	27.91	9.57	32.7	334	131	P	V
		2389.8	40.89	-13.11	54	36.15	27.8	9.64	32.7	334	131	A	V
		2437	108.55	-	-	103.85	27.71	9.69	32.7	334	131	P	V
		2437	100.36	-	-	95.66	27.71	9.69	32.7	334	131	A	V
		2484.04	51.74	-22.26	74	47.03	27.66	9.75	32.7	334	131	P	V
		2483.5	41.58	-12.42	54	36.87	27.66	9.75	32.7	334	131	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 11 2462MHz		2462	112.75	-	-	108.04	27.69	9.72	32.7	370	13	P	H
		2462	105.24	-	-	100.53	27.69	9.72	32.7	370	13	A	H
		2484.24	59.6	-14.4	74	54.89	27.66	9.75	32.7	370	13	P	H
		2483.52	50.22	-3.78	54	45.51	27.66	9.75	32.7	370	13	A	H
		2462	109.8	-	-	105.09	27.69	9.72	32.7	371	127	P	V
		2462	102	-	-	97.29	27.69	9.72	32.7	371	127	A	V
		2483.52	56.66	-17.34	74	51.95	27.66	9.75	32.7	371	127	P	V
		2483.52	46.93	-7.07	54	42.22	27.66	9.75	32.7	371	127	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	45.7	-28.3	74	51.98	33.85	12.01	52.14	-	-	P	H
		4824	45.39	-28.61	74	51.67	33.85	12.01	52.14	-	-	P	V
802.11n HT20 CH 06 2437MHz		4874	45.91	-28.09	74	52.24	33.73	12.04	52.1	-	-	P	H
		7311	49.74	-24.26	74	51.61	35.76	14.16	51.79	-	-	P	H
		4874	45.45	-28.55	74	51.78	33.73	12.04	52.1	-	-	P	V
		7311	48.63	-25.37	74	50.5	35.76	14.16	51.79	-	-	P	V
802.11n HT20 CH 11 2462MHz		4924	45.64	-28.36	74	51.93	33.7	12.07	52.06	-	-	P	H
		7386	48.31	-25.69	74	50.02	35.78	14.21	51.7	-	-	P	H
		4924	46.33	-27.67	74	52.62	33.7	12.07	52.06	-	-	P	V
		7386	48.92	-25.08	74	50.63	35.78	14.21	51.7	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.66	56.68	-17.32	74	51.94	27.8	9.64	32.7	336	104	P	H
		2389.94	48.74	-5.26	54	44	27.8	9.64	32.7	336	104	A	H
		2422	104.46	-	-	99.74	27.74	9.68	32.7	336	104	P	H
		2422	96.89	-	-	92.17	27.74	9.68	32.7	336	104	A	H
		2498.32	50.84	-23.16	74	46.14	27.63	9.77	32.7	336	104	P	H
		2483.69	42.44	-11.56	54	37.73	27.66	9.75	32.7	336	104	A	H
		2389.24	54.02	-19.98	74	49.28	27.8	9.64	32.7	351	360	P	V
		2389.94	45.62	-8.38	54	40.88	27.8	9.64	32.7	351	360	A	V
		2422	103.74	-	-	99.02	27.74	9.68	32.7	351	360	P	V
		2422	95.8	-	-	91.08	27.74	9.68	32.7	351	360	A	V
		2484.67	52.06	-21.94	74	47.35	27.66	9.75	32.7	351	360	P	V
		2483.55	42.58	-11.42	54	37.87	27.66	9.75	32.7	351	360	A	V
802.11n HT40 CH 06 2437MHz		2389.8	52.91	-21.09	74	48.17	27.8	9.64	32.7	340	99	P	H
		2389.94	43.61	-10.39	54	38.87	27.8	9.64	32.7	340	99	A	H
		2437	104.21	-	-	99.51	27.71	9.69	32.7	340	99	P	H
		2437	96.82	-	-	92.12	27.71	9.69	32.7	340	99	A	H
		2483.9	53.28	-20.72	74	48.57	27.66	9.75	32.7	340	99	P	H
		2484.48	44.03	-9.97	54	39.32	27.66	9.75	32.7	340	99	A	H
		2322.32	50.44	-23.56	74	45.67	27.91	9.56	32.7	330	318	P	V
		2389.66	43.13	-10.87	54	38.39	27.8	9.64	32.7	330	318	A	V
		2437	103.59	-	-	98.89	27.71	9.69	32.7	330	318	P	V
		2437	96.15	-	-	91.45	27.71	9.69	32.7	330	318	A	V
		2486.14	52.28	-21.72	74	47.57	27.66	9.75	32.7	330	318	P	V
		2483.76	43.78	-10.22	54	39.07	27.66	9.75	32.7	330	318	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 09 2452MHz		2372.16	50.67	-23.33	74	45.92	27.83	9.62	32.7	365	103	P	H
		2365.58	41.69	-12.31	54	36.93	27.85	9.61	32.7	365	103	A	H
		2452	103.83	-	-	99.11	27.71	9.71	32.7	365	103	P	H
		2452	95.89	-	-	91.17	27.71	9.71	32.7	365	103	A	H
		2484.6	58.15	-15.85	74	53.44	27.66	9.75	32.7	365	103	P	H
		2483.58	50.22	-3.78	54	45.51	27.66	9.75	32.7	365	103	A	H
		2382.38	50.91	-23.09	74	46.15	27.83	9.63	32.7	332	319	P	V
		2338.42	41.48	-12.52	54	36.72	27.88	9.58	32.7	332	319	A	V
		2452	101.86	-	-	97.14	27.71	9.71	32.7	332	319	P	V
		2452	94.29	-	-	89.57	27.71	9.71	32.7	332	319	A	V
		2483.55	56.14	-17.86	74	51.43	27.66	9.75	32.7	332	319	P	V
		2483.76	49.33	-4.67	54	44.62	27.66	9.75	32.7	332	319	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		4844	45.91	-28.09	74	52.2	33.8	12.03	52.12	-	-	P	H
HT40		7266	48.31	-25.69	74	50.23	35.76	14.14	51.82	-	-	P	H
CH 03		4844	46.02	-27.98	74	52.31	33.8	12.03	52.12	-	-	P	V
2422MHz		7266	48.37	-25.63	74	50.29	35.76	14.14	51.82	-	-	P	V
802.11n		4874	46.72	-27.28	74	53.05	33.73	12.04	52.1	-	-	P	H
HT40		7311	49.06	-24.94	74	50.93	35.76	14.16	51.79	-	-	P	H
CH 06		4874	45.51	-28.49	74	51.84	33.73	12.04	52.1	-	-	P	V
2437MHz		7311	48.34	-25.66	74	50.21	35.76	14.16	51.79	-	-	P	V
802.11n		4904	46.15	-27.85	74	52.46	33.7	12.06	52.07	-	-	P	H
HT40		7356	49.31	-24.69	74	51.09	35.77	14.19	51.74	-	-	P	H
CH 09		4904	45.59	-28.41	74	51.9	33.7	12.06	52.07	-	-	P	V
2452MHz		7356	49.76	-24.24	74	51.54	35.77	14.19	51.74	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30	23.69	-16.31	40	30.36	25.2	0.53	32.4	-	-	P	H
		75.59	17.27	-22.73	40	35.9	12.9	0.87	32.4	-	-	P	H
		141.55	17.96	-25.54	43.5	31.44	17.5	1.22	32.2	-	-	P	H
		261.83	20.15	-25.85	46	30.92	19.32	1.69	31.78	-	-	P	H
		597.45	28.13	-17.87	46	30.39	25.9	2.55	30.71	-	-	P	H
		963.14	32.94	-21.06	54	29.81	31.26	3.25	31.38	-	-	P	H
		30.97	26.97	-13.03	40	34.13	24.7	0.54	32.4	-	-	P	V
		65.89	25.37	-14.63	40	44.86	12.1	0.81	32.4	-	-	P	V
		137.67	21.22	-22.28	43.5	34.62	17.6	1.2	32.2	-	-	P	V
		260.86	20.24	-25.76	46	30.88	19.46	1.68	31.78	-	-	P	V
		713.85	30.56	-15.44	46	31.78	26.88	2.78	30.88	-	-	P	V
		967.02	33.9	-20.1	54	30.69	31.3	3.26	31.35	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	99.30	-	-	10Hz
802.11g	98.25	-	-	10Hz
802.11n HT20	98.12	-	-	10Hz
802.11n HT40	94.82	0.928	1.078	3kHz

802.11b



802.11g



802.11n HT20



802.11n HT40


Spectrum
Ref Level 30.00 dBm Offset 11.80 dB RBW 10 MHz
Att 30 dB SWT 2.5 ms VBW 10 MHz
SGL
1Pk Max
D3[1] -0.09 dB
978.26 µs
M1[1] 12.79 dBm
235.51 µs
20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
CF 2.422 GHz
691 pts
250.0 µs/
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 235.51 µs 12.79 dBm
D2 M1 1 927.54 µs 2.39 dB
D3 M1 1 978.26 µs -0.09 dB