

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	PW Smart Timing Mat
Model Name	PW Smart Mat-6m
FCC ID	2AOIRPWSMARTMAT6M

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

$$P_t = (E \times d)^2 / (30 \times g_t)$$

P_t =transmitter output power in watts

g_t =numeric gain of the transmitting antenna (5dBi=3.16)

E =electric field strength in V/m

d =measurement distance in meters (m)

According to the report WH-FCC-R180114116,
 $E_{\text{max}}=105.87\text{dBuV/m}=0.19656\text{V/m}$, $d=3\text{m}$, $g_t=3.16$
 $P_t = (E \times d)^2 / (30 \times g_t) = 0.00367\text{W} = 3.67\text{mW}$

The result for RF exposure evaluation

$\text{SAR} = (3.67\text{mW} / 5\text{mm}) \cdot [\sqrt{0.915(\text{GHz})}] = 0.70 < 3.0$ for 1-g SAR

4. CONCLUSION

The SAR evaluation is not required.