

ANKER INNOVATIONS LIMITED

TEST REPORT

SCOPE OF WORK

SAR Assessment– A1664

REPORT NUMBER

251201027SZN-002

ISSUE DATE

23 December 2025

[REVISED DATE]

[-----]

PAGES

5

DOCUMENT CONTROL NUMBER

RF Exposure

© 2017 INTERTEK



Test Report

Applicant: ANKER INNOVATIONS LIMITED
Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

Manufacturer: ANKER INNOVATIONS LIMITED
Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

FCC ID: 2AOKB-A1664A

Sample Descriptio: Anker MagGo Power Bank (10K, Slim)

Product Model No.: A1664

Brand Name: ANKER

Electrical Rating: Battery Energy: 7.74VDC/38.7Wh (5000mAh, Two Cells in Series)
Rated Voltage: 5VDC
Rated Capacity: 6400mAh (5V/3A)
USB-C Input: 5V/3A, 9V/3A, 15V/2A (30W Max)
USB-C Output: 5V/3A, 9V/3A, 12V/2.5A, 15V/2A, 20V/1.5A (30W Max)
Wireless Output: 5W/7.5W/15WMax
Total Output: USB-C: 5V/2.4A (12W Max) + Wireless: 5W Max

Date Received: 01 December 2025

Date Test Conducted: 01 December 2025 to 22 December 2025

Test Requested: Test for compliance with CFR 47 part 1

Test Method: Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310
KDB 680106 D01 Wireless Power Transfer v04

Test Result: Pass

Conclusion: When determining of test conclusion, measurement uncertainty of tests have been considered.

Prepared and Checked By:


Mandy Chen
Engineer**Approved By:**

Johnny Wang
Project Engineer
Date: 23 December 2025

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Test Report

Test Setup Configuration



Note

- The RF exposure test is performed in the shield room.
- The test distance is measured from the center of the test probe along all three axes of the device, from 0 cm to 20 cm, from the edge of the device coil in minimum 2 cm increments.

Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Cal. Date	Due Date
SZ186-06	The Magnetic Amplitude and Gradient Probe System	SPEAG	MAGPy-8H3D+E3D	2024-03-07	2026-03-07

This product was tested in the following configuration:

Description	Manufacturer	Detail
iPhone 16e	(Provided by Intertek)	Model: MD2D4CH/A
Adapter	(Provided by Intertek)	Model: A2604 Input: 100-240V~, 50/60Hz, 2.0A USBC1/C2/C3: 5V=3A, 9V=3A, 15V=3A, 20V=3.5A, 70.0W Max
USB-C to USB-C Cabel	N/A (Provided by Applicant)	(60cm length, without ferrite core, unshielded)

Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are Intertek Testing Services Shenzhen Ltd. Longhua Branch and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

Justification

The EUT was powered by an adapter with AC 120V, 60Hz input or DC 7.74V from battery during the test. The test system was pre-scanning tested based on the consideration of following EUT operation mode. and only the worst-case data was shown in this report.

Pertest mode	Description
Mode 1	Standby mode
Mode 2	Mobile phone is charging at 1% battery power
Mode 3	Mobile phone is charging at 50% battery power
Mode 4	Mobile phone is charging at 99% battery power

Notes:

- The EUT meets the following requirement: a “low-frequency” coil emitting structures that lead to dominant H-field near-field emissions with E/H ratio less than 1/10 of the 377-ohm free space wave impedance, typically frequencies less than 1 MHz, only H-field measurements are sufficient for demonstrating MPE limit compliance.
- H-field data are measured in minimal increments of 2 cm from the edge of the device along all three axes of the device, from 0 cm to 20 cm, one axis is consistent with the axis of the main coil, all modes and distances have been fully tested. The worst-case testing data were recorded in this report.

Reference Limit:

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: * = Plane wave equivalent power density

Test Result:

During test, the mobile phone is being charged.

Worst Case Operating Mode: Mode 2 for 2cm to 20cm distance

Center of the probe to the probe outer edge is 1.85 cm, so the test distance can only reach 2cm.

H-field strength measurement result at 2cm to 20 cm:

Test Position	Test distance(cm)										Limit (A/m)
	2	4	6	8	10	12	14	16	18	20	
Front	0.1	0.06	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	1.63
Rear	0.13	0.1	0.04	0.02	0.01	0.01	0.01	0.01	0.01	0.01	1.63
Left	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	1.63
Right	0.1	0.04	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	1.63
Top	0.08	0.05	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	1.63
Bottom	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01	1.63

H-field strength at 0cm:
Validation:

To determine the H-field strength of 0mm, an extrapolation function by setting to Probe tip in the software of MAGPy handheld system has been used.

The validation for this extrapolation is as follows:

Test mode	Distance (cm)	Estimated value (A/m)	30% tolerance (A/m)		Measured value (A/m)
			Min	Max	
Mode 2	1.85	0.410 (probe tip to EUT)	0.287	0.533	0.290 (probe center to EUT)
Mode 2	3.7	0.070 (probe tip to EUT)	0.049	0.091	0.070 (probe center to EUT)
Mode 2	5.55	0.030 (probe tip to EUT)	0.021	0.039	0.028 (probe center to EUT)
Conclusion: Estimated value has 30% agreement with actual measurement, verified the probe tip function.					

Note:

1. According to KDB 680106 D01 V04, the validation is considered sufficient if a 30% agreement between the Estimated value and the (E- and/ H-field) probe measurements is demonstrated.
2. Estimated value is obtained from the tip function of the probe.

Estimated H-field Result at 0 cm:

EUT Operation mode	Front (A/m)	Rear (A/m)	Left (A/m)	Right (A/m)	Top (A/m)	Bottom (A/m)	Limits (A/m)
Mode 2	1.28	0.02	1.08	0.58	0.95	0.12	1.63

Configuration photo of the test:

Please refer to RF Exposure setup photos.pdf.

***** End of Report*****