



东莞市启元电子有限公司

制造商 (Manufacture)	DONGGUAN QiYuan TECHNOLOGY CO., LTD.
部品名称 (Material Description)	BT antenna
型号 (Model)	200A0128A
部品规格 (Specifications)	RG1.13 Black double tin wire length 240mm gain 4.74dbi, shockproof sponge L=200mm FPCB BT antenna IPEX terminal
供应商料号 (Supplier's Part number)	/
送样日期 (Date)	2022 / 05 / 14

拟制 Prepared By	审核 Checked By	批准 Approved By
张炳相	伍前进	罗达勋

承认 Accepted By	审核 Checked By	批准 Approved By
☐ 完全接受 (Full Approval) ☐ 条件接受 (Conditional Approval) ☐ 不合格 (Unqualified) ☐ 其它 (Others) :		



Specification

客户料号

Customer P/N: /

规格描述

Specification: Antenna, 4.74dBi@2.4G internal
antenna, 50ohm, RG1.13 Black double tin
wire L=240mm, shockproofsponge
L=200mm, add IPEX terminal, black FPC
antenna

品名 Description: FPC ANTENNA

供应商 Supplier: QIYUAN

备注 Remark:

承认签章后请回复一份（或复印件）给我司，其余由贵公司留作存档。如果在签章的承认书（或复印件）回复给我司之前，下了有关此规格产品的订单且又无特别说明，那么我司就确定贵司已完全承认了。Please return one specification or one copy of it with your chop and signature of approval and retain the others for your record. In the event of an order being placed for this part number before the chop and signed with specification (or copy) is returned and without special explanation, it will be assumed that full approval have been given.

拟制/日期 CHECKED/DATE	审核/日期 AUDITOR/DATE	批准/日期 APPROVED/DATE
Zhang Bingxiang 2022.05.14	Wu Qianjin 2022.05.14	Luo Daxun 2022.05.14



一. 天线图片 (Picture) :



二. 电气参数 (Electrical parameters) :

Frequency 频率范围	2.4~2.5GHz
Impedance 特性阻抗	50Ω
S.W.R. 电压驻波比	≤2.0
Antenna Gain 增益	4.74dBi
Polarization 极化形式	vertical polarization
Return Loss 回波损耗	-9.5dB MAX

二. 机械参数(Mechanical parameters):

Antenna Colour 天线颜色	Black
RF Cable Model 射频线型号	RG1.13, Black
Connect Type 接口方式	IPEX A generation of terminal

三. 工作/储存温度 (Operating/ Storage Temperature) :

Operating Temperature 工作温度	-40~85℃
Storage Temperature 储存温度	-40~85℃