TEST REPORT

APPLICANT	:	Anker Innovations Limited
PRODUCT NAME	:	soundcore Front Surround Speaker
MODEL NAME	:	D2151FR
BRAND NAME	:	soundcore
FCC ID	:	2AOKB-D2040R
STANDARD(S)	:	47 CFR Part 15 Subpart C
RECEIPT DATE	:	2025-04-03
TEST DATE	:	2025-04-15 to 2025-04-22
ISSUE DATE	:	2025-09-15

Edited by: Zeng Xiaoying (Rapporteur)

Approved by: Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Summary of Test Result ····· 4
1.1. Testing Applied Standards ····· 5
1.2. Test Equipment List ····· 6
1.3. Measurement Uncertainty ····· 8
1.4. Testing Laboratory ····· 8
2. General Description ····· 9
2.1. Information of Applicant and Manufacturer ····· 9
2.2. Information of EUT ····· 9
2.3. Channel List of EUT ····· 11
2.4. Test Configuration of EUT ····· 12
2.5. Test Conditions ····· 12
2.6. Test Setup Layout Diagram ····· 12
3. Test Results ····· 15
3.1. Antenna Requirement ····· 15
3.2. Duty Cycle of Test Signal ····· 16
3.3. Maximum Peak Conducted Output Power ····· 17
3.4. Maximum Average Conducted Output Power ····· 18
3.5. 6 dB Bandwidth ····· 19
3.6. Conducted Spurious Emissions and Band Edge ····· 20
3.7. Power Spectral Density ····· 21
3.8. Conducted Emission ····· 22
3.9. Restricted Frequency Bands ····· 23
3.10. Radiated Emission ····· 24
Annex A Test Data and Result ····· 26

Change History		
Version	**Date**	**Reason for change**
1.0	2025-09-15	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS$_{Note3}$	/
2	N/A	Duty Cycle of Test Signal	Apr. 16, 2025	Li Xinpeng	PASS$_{Note3}$	/
3	15.247(b)	Maximum Peak Conducted Output Power	Apr. 17, 2025	Li Xinpeng	PASS$_{Note3}$	/
4	15.247(b)	Maximum Average Conducted Output Power	Apr. 17, 2025	Li Xinpeng	PASS$_{Note3}$	/
5	15.247(a)	Bandwidth	Apr. 19, 2025	Li Xinpeng	PASS$_{Note3}$	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Apr. 19, 2025	Li Xinpeng	PASS$_{Note3}$	/
7	15.247(e)	Power Spectral Density	Apr. 19, 2025	Li Xinpeng	PASS$_{Note3}$	/
8	15.207	Conducted Emission	Apr. 21, 2025	Fan Shengquan	PASS$_{Note3}$	/
9	15.247(d)	Restricted Frequency Bands	Apr. 23, 2025	Tian Xin	PASS$_{Note3}$	/
10	15.209, 15.247(d)	Radiated Emission	Apr. 23, 2025	Tian Xin	PASS$_{Note3}$	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark".

Note 3: The test results of these test items in this report refer to the test report (Report No.: SZ25040043W02).

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

• 47 CFR Part 15 Subpart C Radio Frequency Devices

1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analzyer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2025.01.06	2026.01.05
LISN	8127449	NSLK 8127	Schwarzbeck	2025.01.09	2026.01.08
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

1.2.4 Radiated Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L3802	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L3203	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.07.03	2025.07.02
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09

1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	±2.22dB	Confidence levels of 95%
Power Spectral Density	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Anker Innovations Limited
Applicant Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong

2.2. Information of EUT

Product Name:	soundcore Front Surround Speaker	
Sample No.:	2#, 4#, 42#	
Hardware Version:	V3	
Software Version:	V1.1.216	
Equipment Type:	Bluetooth LE	
Bluetooth Version:	5.1	
Modulation Type:	GFSK	
Data Rate:	1Mbps, 2Mbps	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	FPC Antenna	
Antenna Gain:	4.63dBi	
Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	C0914K5
	Serial No.:	N/A
	Capacity:	6000mAh
	Rated Voltage:	7.2V
	Charge Limit:	8.4V
	Manufacturer:	Guangdong Pow-Tech New Power Co., Ltd.

Note 1: This is a variant report of original report (Report No.: SZ25040043W02, FCC ID: 2AOKB-D2040R) to request a Class II Permissive change, based on the similarity between before, made the following changes:

1.Pogo pin charging capability

2.Mechanical latching switch on the housing

3.Updated product name, brand name, model name, hardware version and software version information.

The others RF features are the same as before. The changes do not affect the test results in this report.

Note 2: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3. Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	**2402**	10	2422	20	2442	30	2462
1	**2404**	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	**38**	**2478**
9	2420	**19**	**2440**	29	2460	**39**	**2480**

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

The EUT is controlled by dedicated software to transmit at the default maximum power level.

2.5. Test Conditions

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1.Conducted Measurement



2.6.2.Conducted Emission Measurement



2.6.3.Radiation Measurement

1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to1GHz



3) For radiated emissions above 1GHz



3. Test Results

3.1. Antenna Requirement

3.1.1.Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2.Test Result

Antenna location	Antenna Type	Coupling Method
☒Internal ☐External	☒FPC Antenna ☐Spring Antenna ☐Ceramic Antenna ☐Integrated Antenna ☐Dipole Antenna ☐PCB Antenna ☐PIFA Antenna ☐On-board Antenna	☒I-PEX Connector ☐SMA Connector ☐RP-SMA Connector ☐Metal Shrapnel ☐Layout

3.2. Duty Cycle of Test Signal

3.2.1.Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).
When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than ±2%; otherwise, the duty cycle is considered to be non constant.

3.2.2.Test Result

Refer to Annex A.1 in this report.

3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.

3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.

3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:
a) Set analyzer center frequency to channel center frequency
b) Set RBW to100kHz
c) Set VBW to 300kHz
d) Detector = peak.
e) Trace mode = max hold
f) Sweep time = auto couple
g) Allow the trace to fully stabilize
h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by6 dB relative to the maximum level measured in the fundamental emission
The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 ×RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥6 dB.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.

3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.

3.7. Power Spectral Density

3.7.1.Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2.Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:
a) Set analyzer center frequency to channel center frequency
b) Set span to1.5 times DTS
c) Set RBW to 3kHz
d) Set VBW to 10kHz
e) Detector = peak
f) Sweep time = auto couple
g) Trace mode = max hold
h) Allow trace to fully stabilize
i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4.Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1.Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

(a) The lower limit shall apply at the band edges.

(b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2.Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.8.3.Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4.Test Result

Refer to Annex A.8 in this report.

3.9. Restricted Frequency Bands

3.9.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.9.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.
For the Test Antenna:
Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1GHz, 100 kHz for f < 1GHz
VBW = 3 MHz
Sweep = auto
Detector function = peak/average
Trace = max hold
Allow the trace to stabilize

3.9.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4.Test Result

Refer to Annex A.9 in this report.

3.10. Radiated Emission

3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).

3.10.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz.The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.10.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.10.4.Test Result

Refer to Annex A.10 in this report.

Annex A Test Data and Result

A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	63.2	1.99	2.53
NVNT	BLE 1M	2440	Ant1	63.2	1.99	2.53
NVNT	BLE 1M	2480	Ant1	63.2	1.99	2.53
NVNT	BLE 2M	2404	Ant1	33.52	4.75	4.77
NVNT	BLE 2M	2440	Ant1	33.52	4.75	4.77
NVNT	BLE 2M	2478	Ant1	33.57	4.74	4.76

Test Graphs
Duty Cycle NVNT BLE 1M 2402MHz Ant1



Duty Cycle NVNT BLE 1M 2440MHz Ant1



Duty Cycle NVNT BLE 1M 2480MHz Ant1



Duty Cycle NVNT BLE 2M 2404MHz Ant1



Duty Cycle NVNT BLE 2M 2440MHz Ant1



Duty Cycle NVNT BLE 2M 2478MHz Ant1



A.2. Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	4.61	0	4.61	0.00289	30	Pass
NVNT	BLE 1M	2440	Ant1	4.99	0	4.99	0.00316	30	Pass
NVNT	BLE 1M	2480	Ant1	4.98	0	4.98	0.00315	30	Pass
NVNT	BLE 2M	2404	Ant1	4.78	0	4.78	0.00301	30	Pass
NVNT	BLE 2M	2440	Ant1	4.78	0	4.78	0.00301	30	Pass
NVNT	BLE 2M	2478	Ant1	4.98	0	4.98	0.00315	30	Pass

Test Graphs
Peak Power NVNT BLE 1M 2402MHz Ant1



Peak Power NVNT BLE 1M 2440MHz Ant1



Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2404MHz Ant1



Peak Power NVNT BLE 2M 2440MHz Ant1



Peak Power NVNT BLE 2M 2478MHz Ant1



A.3. Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	2.29	1.99	4.28	0.00268	30	Pass
NVNT	BLE 1M	2440	Ant1	2.61	1.99	4.6	0.00288	30	Pass
NVNT	BLE 1M	2480	Ant1	2.71	1.99	4.7	0.00295	30	Pass
NVNT	BLE 2M	2404	Ant1	-0.43	4.75	4.32	0.0027	30	Pass
NVNT	BLE 2M	2440	Ant1	-0.21	4.75	4.54	0.00284	30	Pass
NVNT	BLE 2M	2478	Ant1	0.13	4.74	4.87	0.00307	30	Pass

Test Graphs

Average Power NVNT BLE 1M 2402MHz Ant1



Average Power NVNT BLE 1M 2440MHz Ant1



Average Power NVNT BLE 1M 2480MHz Ant1



Average Power NVNT BLE 2M 2404MHz Ant1



Average Power NVNT BLE 2M 2440MHz Ant1



Average Power NVNT BLE 2M 2478MHz Ant1



A.4. 6 dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.6537	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.6408	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.6545	0.5	Pass
NVNT	BLE 2M	2404	Ant1	1.097	0.5	Pass
NVNT	BLE 2M	2440	Ant1	0.9954	0.5	Pass
NVNT	BLE 2M	2478	Ant1	1.057	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1

-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1

-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1

-6dB Bandwidth NVNT BLE 2M 2404MHz Ant1

-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1

-6dB Bandwidth NVNT BLE 2M 2478MHz Ant1

A.5. Conducted Spurious Emissions

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-43.46	-20	Pass
NVNT	BLE 1M	2440	Ant1	-44.47	-20	Pass
NVNT	BLE 1M	2480	Ant1	-44.34	-20	Pass
NVNT	BLE 2M	2404	Ant1	-43.67	-20	Pass
NVNT	BLE 2M	2440	Ant1	-43.66	-20	Pass
NVNT	BLE 2M	2478	Ant1	-43.45	-20	Pass

Test Graphs
Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Ref

Tx. Spurious NVNT BLE 2M 2404MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Ref

Tx. Spurious NVNT BLE 2M 2478MHz Ant1 Emission



A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-59.41	-20	Pass
NVNT	BLE 1M	2480	Ant1	-60.78	-20	Pass
NVNT	BLE 2M	2404	Ant1	-60.09	-20	Pass
NVNT	BLE 2M	2478	Ant1	-59.8	-20	Pass

Test Graphs
Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Band Edge NVNT BLE 1M 2480MHz Ant1 Ref

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Band Edge NVNT BLE 2M 2404MHz Ant1 Ref

Band Edge NVNT BLE 2M 2404MHz Ant1 Emission



Band Edge NVNT BLE 2M 2478MHz Ant1 Ref

Band Edge NVNT BLE 2M 2478MHz Ant1 Emission



A.7. Power Spectral Density

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-9.66	0	-9.66	8	Pass
NVNT	BLE 1M	2440	Ant1	-8.6	0	-8.6	8	Pass
NVNT	BLE 1M	2480	Ant1	-10.02	0	-10.02	8	Pass
NVNT	BLE 2M	2404	Ant1	-12.69	0	-12.69	8	Pass
NVNT	BLE 2M	2440	Ant1	-11.44	0	-11.44	8	Pass
NVNT	BLE 2M	2478	Ant1	-12.79	0	-12.79	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1

PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2404MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1



PSD NVNT BLE 2M 2478MHz Ant1

A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Microphone+Adapter+Charging cable+Projectort+Projector adapter+BLE Link

Test voltage: AC 120V/60Hz

The measurement results are obtained as below:

$E\ [dB\mu V] = U_R + L_{Cable\ loss}\ [dB] + A_{Factor}$

U_R: Receiver Reading

A_{Factor}: Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2220	32.16	22.67	62.74	52.74	Line	PASS
2	0.6360	35.89	21.86	56.00	46.00		PASS
3	1.5856	23.18	17.89	56.00	46.00		PASS
4	3.5517	24.12	19.74	56.00	46.00		PASS
5	5.9240	23.22	19.13	60.00	50.00		PASS
6	10.0640	22.98	18.67	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1950	31.30	22.97	63.82	53.82	Neutral	PASS
2	0.3075	27.60	21.67	60.04	50.04		PASS
3	0.5954	34.79	24.20	56.00	46.00		PASS
4	0.6450	37.58	24.16	56.00	46.00		PASS
5	1.2795	27.45	20.41	56.00	46.00		PASS
6	2.0714	22.85	15.31	56.00	46.00		PASS

A.9. Restricted Frequency Bands

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Vertical) was recorded in this test report.

1Mbps

Plot for Channel 0



Fre. (MHz)	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2350.12	3.5	35.92	32.400	54.00	18.08	150	260	AV	PASS
2351.56	16.8	49.18	32.400	74.00	24.82	150	4	PK	PASS
2365.14	3.6	36.00	32.450	54.00	18.00	150	230	AV	PASS
2368.02	16.4	48.82	32.470	74.00	25.18	150	2	PK	PASS
2386.76	16.2	48.76	32.530	74.00	25.24	150	49	PK	PASS
2387.48	3.9	36.42	32.530	54.00	17.58	150	190	AV	PASS

Plot for Channel 39



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.99	10.6	43.60	33.030	54.00	10.40	150	359	AV	PASS
2484.12	22.6	55.67	33.030	74.00	18.33	150	358	PK	PASS
2488.19	23.2	56.24	33.020	74.00	17.76	150	31	PK	PASS
2488.27	10.5	43.55	33.020	54.00	10.45	150	198	AV	PASS
2493.30	22.2	55.17	33.010	74.00	18.83	150	10	PK	PASS
2496.67	10.7	43.67	33.010	54.00	10.33	150	313	AV	PASS

2Mbps

Plot for Channel 1



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2336.67	16.6	48.84	32.270	74.00	25.16	150	144	PK	PASS
2339.91	3.5	35.78	32.300	54.00	18.22	150	251	AV	PASS
2360.57	16.7	49.17	32.440	74.00	24.83	150	340	PK	PASS
2363.93	3.6	36.06	32.450	54.00	17.94	150	173	AV	PASS
2388.92	3.9	36.44	32.540	54.00	17.56	150	183	AV	PASS
2389.40	16.4	48.90	32.540	74.00	25.10	150	85	PK	PASS

Plot for Channel 38



Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2483.82	22.3	55.30	33.030	74.00	18.70	150	50	PK	PASS
2484.29	10.7	43.69	33.030	54.00	10.31	150	81	AV	PASS
2489.99	22.3	55.31	33.020	74.00	18.69	150	353	PK	PASS
2490.32	10.6	43.61	33.020	54.00	10.39	150	360	AV	PASS
2495.05	10.7	43.71	33.010	54.00	10.29	150	277	AV	PASS
2495.60	23.1	56.08	33.010	74.00	17.92	150	356	PK	PASS

A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:
E [dBμV/m] $=U_R + A_T + A_{Factor}$ [dB]; $A_T = L_{Cable\ loss}$ [dB]$-G_{preamp}$ [dB]
A_T: Total correction Factor except Antenna
U_R: Receiver Reading
G_{preamp}: Preamplifier Gain
A_{Factor}: Antenna Factor at 3m
During the test, the total correction Factor A_T and A_{Factor} were built in test software.
Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.
Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.
Note 4: All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.

1Mbps

Plot for Channel 0



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
57.74	56.5	26.30	-30.150	40.00	13.70	150	349	PK	PASS
107.99	63.3	32.73	-30.600	43.50	10.77	150	0	PK	PASS
168.09	68.7	36.41	-32.330	43.50	7.09	150	307	PK	PASS
228.13	63.7	34.90	-28.800	46.00	11.10	150	281	PK	PASS
348.13	62.7	37.47	-25.270	46.00	8.53	150	158	PK	PASS
480.05	56.0	33.71	-22.330	46.00	12.29	150	239	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2402.09	54.1	54.87	0.750	74.00	19.13	150	187	PK	NA
2402.53	51.9	52.63	0.760	54.00	1.37	150	187	AV	NA
5078.07	53.5	44.57	-8.880	74.00	29.43	150	230	PK	PASS
6666.62	42.3	38.55	-3.780	54.00	15.45	150	299	AV	PASS
7596.15	53.1	49.12	-4.020	74.00	24.88	150	133	PK	PASS
13626.35	49.2	53.90	4.740	74.00	20.10	150	299	PK	PASS
13696.36	40.5	44.99	4.520	54.00	9.01	150	357	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
46.49	62.0	33.70	-28.310	40.00	6.30	150	360	PK	PASS
57.74	64.0	33.87	-30.150	40.00	6.13	150	67	PK	PASS
167.89	62.4	30.09	-32.330	43.50	13.41	150	360	PK	PASS
359.53	62.1	36.75	-25.360	46.00	9.25	150	190	PK	PASS
480.05	56.1	33.72	-22.330	46.00	12.28	150	231	PK	PASS
564.88	57.6	36.74	-20.840	46.00	9.26	150	231	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2402.09	48.3	49.05	0.750	74.00	24.95	150	140	PK	NA
2402.53	44.6	45.37	0.760	54.00	8.63	150	152	AV	NA
3589.52	56.7	41.70	-15.020	74.00	32.30	150	86	PK	PASS
6674.12	42.5	38.68	-3.800	54.00	15.32	150	348	AV	PASS
13475.35	40.0	44.74	4.720	54.00	9.26	150	157	AV	PASS
13511.35	49.4	54.08	4.720	74.00	19.92	150	157	PK	PASS

Plot for Channel 19



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
46.25	54.8	26.48	-28.310	40.00	13.52	150	120	PK	PASS
57.60	56.2	26.09	-30.110	40.00	13.91	150	314	PK	PASS
168.09	68.1	35.73	-32.330	43.50	7.77	150	271	PK	PASS
287.94	61.4	34.11	-27.320	46.00	11.89	150	51	PK	PASS
359.82	61.3	35.97	-25.350	46.00	10.03	150	120	PK	PASS
480.15	58.8	36.51	-22.330	46.00	9.49	150	256	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2439.88	51.2	52.25	1.010	74.00	21.75	150	187	PK	NA
2440.32	48.1	49.10	1.010	54.00	4.90	150	187	AV	NA
6673.62	42.4	38.58	-3.800	54.00	15.42	150	11	AV	PASS
6966.13	53.5	48.20	-5.250	74.00	25.80	150	36	PK	PASS
13599.85	50.6	55.44	4.830	74.00	18.56	150	359	PK	PASS
13884.36	40.4	45.09	4.710	54.00	8.91	150	60	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
46.49	62.8	34.48	-28.310	40.00	5.52	150	200	PK	PASS
57.60	63.5	33.40	-30.110	40.00	6.60	150	77	PK	PASS
300.11	60.3	33.34	-26.970	46.00	12.66	150	240	PK	PASS
360.16	61.9	36.56	-25.350	46.00	9.44	150	184	PK	PASS
480.83	55.9	33.57	-22.310	46.00	12.43	150	62	PK	PASS
624.25	53.1	33.72	-19.340	46.00	12.28	150	240	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2440.32	48.8	49.78	1.010	74.00	24.22	150	248	PK	NA
2440.76	42.7	43.73	1.020	54.00	10.27	150	248	AV	NA
6661.62	42.4	38.64	-3.770	54.00	15.36	150	133	AV	PASS
6689.62	52.1	48.21	-3.850	74.00	25.79	150	328	PK	PASS
13635.85	48.7	53.36	4.710	74.00	20.64	150	133	PK	PASS
13828.36	39.6	44.86	5.280	54.00	9.14	150	347	AV	PASS

Plot for Channel 39



(Antenna Horizontal, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
57.45	56.1	26.07	-30.070	40.00	13.93	150	349	PK	PASS
105.13	58.6	28.20	-30.420	43.50	15.30	150	22	PK	PASS
168.04	68.3	35.93	-32.330	43.50	7.57	150	268	PK	PASS
228.13	66.2	37.43	-28.800	46.00	8.57	150	349	PK	PASS
288.18	62.3	34.93	-27.320	46.00	11.07	150	22	PK	PASS
359.43	60.7	35.38	-25.360	46.00	10.62	150	130	PK	PASS



(Antenna Horizontal, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.88	51.3	52.22	0.920	74.00	21.78	150	186	PK	PASS
2480.33	47.7	48.66	0.920	54.00	5.34	150	186	AV	PASS
6457.62	42.8	38.09	-4.680	54.00	15.91	150	276	AV	PASS
6683.62	51.6	47.73	-3.820	74.00	26.27	150	154	PK	PASS
13533.35	49.7	54.42	4.750	74.00	19.58	150	154	PK	PASS
13593.85	40.1	44.93	4.820	54.00	9.07	150	360	AV	PASS



(Antenna Vertical, 30MHz to 1GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
47.02	62.1	33.76	-28.300	40.00	6.24	150	161	PK	PASS
57.84	63.7	33.47	-30.180	40.00	6.53	150	93	PK	PASS
96.16	59.3	28.77	-30.480	43.50	14.73	150	358	PK	PASS
300.16	60.9	33.88	-26.970	46.00	12.12	150	231	PK	PASS
360.01	62.2	36.89	-25.350	46.00	9.11	150	176	PK	PASS
491.84	59.1	37.03	-22.020	46.00	8.97	150	216	PK	PASS



(Antenna Vertical, 1GHz to 18GHz)

Fre. (MHz)	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Verdict
2479.44	48.9	49.83	0.920	74.00	24.17	150	163	PK	NA
2480.33	42.4	43.30	0.920	54.00	10.70	150	163	AV	NA
3589.02	58.1	43.04	-15.020	74.00	30.96	150	204	PK	PASS
6670.12	42.2	38.40	-3.790	54.00	15.60	150	14	AV	PASS
13755.86	48.7	53.83	5.100	74.00	20.17	150	349	PK	PASS
13780.86	39.4	44.80	5.370	54.00	9.20	150	227	AV	PASS

END OF REPORT