



REPORT No.: SZ26040370W01

# TEST REPORT

**APPLICANT** : Anker Innovations Limited

**PRODUCT NAME** : Nebula Capsule 3

**MODEL NAME** : D2425

**BRAND NAME** : NEBULA

**FCC ID** : 2AOKB-D2425C

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2026-04-09


**TEST DATE** : 2026-05-11 to 2026-06-07

**ISSUE DATE** : 2026-06-17

Edited by:

  
Zeng Xiaoying (Rapporteur)

Approved by:

  
Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





# DIRECTORY

|                                                 |           |
|-------------------------------------------------|-----------|
| <b>1. Summary of Test Result</b>                | <b>4</b>  |
| 1.1. Testing Applied Standards                  | 5         |
| 1.2. Test Equipment List                        | 5         |
| 1.3. Measurement Uncertainty                    | 7         |
| 1.4. Testing Laboratory                         | 7         |
| <b>2. General Description</b>                   | <b>8</b>  |
| 2.1. Information of Applicant and Manufacturer  | 8         |
| 2.2. Information of EUT                         | 8         |
| 2.3. Channel List of EUT                        | 9         |
| 2.4. Test Configuration of EUT                  | 10        |
| 2.5. Test Conditions                            | 10        |
| 2.6. Test Setup Layout Diagram                  | 10        |
| <b>3. Test Results</b>                          | <b>13</b> |
| 3.1. Antenna Requirement                        | 13        |
| 3.2. Duty Cycle of Test Signal                  | 14        |
| 3.3. Maximum Peak Conducted Output Power        | 15        |
| 3.4. Maximum Average Conducted Output Power     | 16        |
| 3.5. 6 dB Bandwidth                             | 17        |
| 3.6. Conducted Spurious Emissions and Band Edge | 18        |
| 3.7. Power Spectral Density                     | 19        |
| 3.8. Conducted Emission                         | 20        |
| 3.9. Restricted Frequency Bands                 | 21        |
| 3.10. Radiated Emission                         | 22        |
| <b>Annex A Test Data and Result</b>             | <b>24</b> |
| <b>Notes</b>                                    | <b>76</b> |



REPORT No.: SZ26040370W01

| Change History |            |                   |
|----------------|------------|-------------------|
| Version        | Date       | Reason for change |
| 1.0            | 2026-06-17 | First edition     |
|                |            |                   |



# 1. Summary of Test Result

| No. | Section              | Description                               | Test Date                           | Test Engineer | Result | Remark |
|-----|----------------------|-------------------------------------------|-------------------------------------|---------------|--------|--------|
| 1   | 15.203               | Antenna Requirement                       | N/A                                 | N/A           | PASS   | /      |
| 2   | N/A                  | Duty Cycle of Test Signal                 | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 3   | 15.247(b)            | Maximum Peak Conducted Output Power       | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 4   | 15.247(b)            | Maximum Average Conducted Output Power    | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 5   | 15.247(a)            | Bandwidth                                 | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 6   | 15.247(d)            | Conducted Spurious Emission and Band Edge | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 7   | 15.247(e)            | Power Spectral Density                    | May 11, 2026<br>to<br>Jun. 08, 2026 | Zhu Peihong   | PASS   | /      |
| 8   | 15.207               | Conducted Emission                        | May 14, 2026                        | Fan Zehang    | PASS   | /      |
| 9   | 15.247(d)            | Restricted Frequency Bands                | May 15, 2026                        | Gao Jianrou   | PASS   | /      |
| 10  | 15.209,<br>15.247(d) | Radiated Emission                         | May 15, 2026                        | Gao Jianrou   | PASS   | /      |

**Note 1:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

**Note 2:** Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.



## 1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices

## 1.2. Test Equipment List

### 1.2.1 Conducted Test Equipment

| Equipment              | Serial No. | Type   | Manufacturer | Cal. Date  | Due Date   |
|------------------------|------------|--------|--------------|------------|------------|
| EXA Signal Analyzer    | MY53470836 | N9010A | Agilent      | 2025.12.23 | 2026.12.22 |
| RF Cable (30MHz-26GHz) | CB01       | RF01   | Morlab       | N/A        | N/A        |
| SMA Connector          | CN01       | RF03   | HUBER-SUHNER | N/A        | N/A        |

### 1.2.2 Conducted Emission Test Equipment

| Equipment                    | Serial No.   | Type    | Manufacturer | Cal. Date  | Due Date   |
|------------------------------|--------------|---------|--------------|------------|------------|
| Receiver                     | 101052       | ESPI    | R&S          | 2026.05.07 | 2027.05.06 |
| LISN                         | 103131       | ENV 216 | R&S          | 2026.03.18 | 2027.03.17 |
| RF Coaxial Cable (DC-100MHz) | EMC-CE-00514 | N/A     | N/A          | 2026.05.06 | 2027.05.05 |

### 1.2.3 List of Software Used

| Description    | Manufacturer | Software Version |
|----------------|--------------|------------------|
| Test System    | MaiWei       | 2.0.0.0          |
| JS32-RE        | Tonscend     | 5.0.0            |
| TS+ -[JS32-CE] | Tonscend     | 2.5.0.0          |

**1.2.4 Radiated Test Equipment**

| Equipment                   | Serial No.    | Type                  | Manufacturer | Cal. Date  | Due Date   |
|-----------------------------|---------------|-----------------------|--------------|------------|------------|
| Signal Analyzer             | MY56060145    | N9020A                | Agilent      | 2026.04.28 | 2027.04.27 |
| Test Antenna - Bi-Log       | 9163-274      | VULB 9163             | Schwarzbeck  | 2025.06.28 | 2026.06.27 |
| Test Antenna - Loop         | 1519-022      | FMZB1519              | Schwarzbeck  | 2026.05.09 | 2027.05.08 |
| Test Antenna – Horn         | 01774         | BBHA 9120D            | Schwarzbeck  | 2025.06.20 | 2026.06.19 |
| Test Antenna – Horn         | BBHA9170 #773 | BBHA9170              | Schwarzbeck  | 2025.06.20 | 2026.06.19 |
| Preamplifier (10MHz-6GHz)   | 46732         | S10M100L38 02         | LUCIX CORP.  | 2026.05.07 | 2027.05.06 |
| Preamplifier (2GHz-18GHz)   | 61171/61172   | S020180L32 03         | LUCIX CORP.  | 2026.05.07 | 2027.05.06 |
| Preamplifier (18GHz-40GHz)  | DS77209       | DCLNA0118-40C-S       | Decentest    | 2026.05.07 | 2027.05.06 |
| RF Coaxial Cable (DC-18GHz) | MRE001        | PE330                 | Pasternack   | 2025.09.03 | 2026.09.02 |
| RF Coaxial Cable (DC-18GHz) | MRE002        | CLU18                 | Pasternack   | 2025.09.03 | 2026.09.02 |
| RF Coaxial Cable (DC-18GHz) | MRE003        | CLU18                 | Pasternack   | 2025.09.03 | 2026.09.02 |
| RF Coaxial Cable (DC-40GHz) | 22290045      | QA360-40-KK-0.5       | Qualwave     | 2025.09.03 | 2026.09.02 |
| RF Coaxial Cable (DC-40GHz) | 22290046      | QA360-40-KKF-2        | Qualwave     | 2025.09.03 | 2026.09.02 |
| RF Coaxial Cable (DC-18GHz) | 22120181      | QA500-18-NN-5         | Qualwave     | 2025.09.03 | 2026.09.02 |
| Notch Filter                | N/A           | WRCG-2400-2483.5-60SS | Wainwright   | N/A        | N/A        |
| Anechoic Chamber            | N/A           | 9m*6m*6m              | CRT          | 2025.06.21 | 2028.06.20 |
| Anechoic Chamber            | N/A           | 9m*6m*6m              | CRT          | 2025.04.19 | 2028.04.18 |



### 1.3. Measurement Uncertainty

| Test Items                  | Uncertainty         | Remark                   |
|-----------------------------|---------------------|--------------------------|
| Peak Output Power           | $\pm 2.22\text{dB}$ | Confidence levels of 95% |
| Power Spectral Density      | $\pm 2.22\text{dB}$ | Confidence levels of 95% |
| Bandwidth                   | $\pm 5\%$           | Confidence levels of 95% |
| Conducted Spurious Emission | $\pm 2.77\text{dB}$ | Confidence levels of 95% |
| Restricted Frequency Bands  | $\pm 5\%$           | Confidence levels of 95% |
| Radiated Emission           | $\pm 2.95\text{dB}$ | Confidence levels of 95% |
| Conducted Emission          | $\pm 2.44\text{dB}$ | Confidence levels of 95% |

### 1.4. Testing Laboratory

|                                    |                                                                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Laboratory Name:                   | Shenzhen Morlab Communications Technology Co., Ltd.                                                                                |
| Laboratory Address:                | FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |
| Telephone:                         | +86 755 36698555                                                                                                                   |
| Facsimile:                         | +86 755 36698525                                                                                                                   |
| FCC Designation Number:            | CN1192                                                                                                                             |
| FCC Test Firm Registration Number: | 226174                                                                                                                             |



## 2. General Description

### 2.1. Information of Applicant and Manufacturer

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| <b>Applicant:</b>            | Anker Innovations Limited                                                  |
| <b>Applicant Address:</b>    | Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong |
| <b>Manufacturer:</b>         | Anker Innovations Limited                                                  |
| <b>Manufacturer Address:</b> | Unit 56, 8th Floor, Tower 2, Admiralty Centre, 18 Harcourt Road, Hong Kong |

### 2.2. Information of EUT

|                                   |                  |
|-----------------------------------|------------------|
| <b>Product Name:</b>              | Nebula Capsule 3 |
| <b>Sample No.:</b>                | 1#, 2#, 3#       |
| <b>Hardware Version:</b>          | V5               |
| <b>Software Version:</b>          | V14.0.79.2       |
| <b>Equipment Type:</b>            | Bluetooth LE     |
| <b>Bluetooth Version:</b>         | 5.1              |
| <b>Modulation Type:</b>           | GFSK             |
| <b>Data Rate:</b>                 | 1Mbps, 2Mbps     |
| <b>Operating Frequency Range:</b> | 2402MHz-2480MHz  |
| <b>Antenna Type:</b>              | FPC Antenna      |
| <b>Antenna Gain:</b>              | 2.67dBi          |

**Note 1:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 2.3.Channel List of EUT

| Channel  | Frequency (MHz) | Channel   | Frequency (MHz) | Channel | Frequency (MHz) | Channel   | Frequency (MHz) |
|----------|-----------------|-----------|-----------------|---------|-----------------|-----------|-----------------|
| <b>0</b> | <b>2402</b>     | 10        | 2422            | 20      | 2442            | 30        | 2462            |
| 1        | 2404            | 11        | 2424            | 21      | 2444            | 31        | 2464            |
| 2        | 2406            | 12        | 2426            | 22      | 2446            | 32        | 2466            |
| 3        | 2408            | 13        | 2428            | 23      | 2448            | 33        | 2468            |
| 4        | 2410            | 14        | 2430            | 24      | 2450            | 34        | 2470            |
| 5        | 2412            | 15        | 2432            | 25      | 2452            | 35        | 2472            |
| 6        | 2414            | 16        | 2434            | 26      | 2454            | 36        | 2474            |
| 7        | 2416            | 17        | 2436            | 27      | 2456            | 37        | 2476            |
| 8        | 2418            | 18        | 2438            | 28      | 2458            | 38        | 2478            |
| 9        | 2420            | <b>19</b> | <b>2440</b>     | 29      | 2460            | <b>39</b> | <b>2480</b>     |

**Note 1:** The black bold channels were selected for test.

## 2.4. Test Configuration of EUT


The EUT is controlled by dedicated software to transmit at the default maximum power level.

## 2.5. Test Conditions


|                             |        |
|-----------------------------|--------|
| Temperature (°C):           | 15-35  |
| Relative Humidity (%):      | 30-60  |
| Atmospheric Pressure (kPa): | 86-106 |

## 2.6. Test Setup Layout Diagram

### 2.6.1. Conducted Measurement




### 2.6.2. Conducted Emission Measurement




### 2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





## 3. Test Results

### 3.1. Antenna Requirement

#### 3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 3.1.2. Test Result

| Antenna location                                                                  | Antenna Type                                                                                                                                                                                                                                                                                                                                                     | Coupling Method                                                                                                                                                                                                          |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> Internal<br><input type="checkbox"/> External | <input checked="" type="checkbox"/> FPC Antenna<br><input type="checkbox"/> Spring Antenna<br><input type="checkbox"/> Ceramic Antenna<br><input type="checkbox"/> Integrated Antenna<br><input type="checkbox"/> Dipole Antenna<br><input type="checkbox"/> PCB Antenna<br><input type="checkbox"/> PIFA Antenna<br><input type="checkbox"/> Inverted F Antenna | <input checked="" type="checkbox"/> I-PEX Connector<br><input type="checkbox"/> SMA Connector<br><input type="checkbox"/> RP-SMA Connector<br><input type="checkbox"/> Metal Shrapnel<br><input type="checkbox"/> Layout |



## 3.2. Duty Cycle of Test Signal

### 3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration(T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e.,no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be non constant.

### 3.2.2. Test Result

Refer to Annex A.1 in this report.



### **3.3. Maximum Peak Conducted Output Power**

#### **3.3.1. Requirement**

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

#### **3.3.2. Test Procedures**

KDB 558074 Section 8.3.1 was used in order to prove compliance.

#### **3.3.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

#### **3.3.4. Test Result**

Refer to Annex A.2 in this report.



## **3.4. Maximum Average Conducted Output Power**

### **3.4.1. Requirement**

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

### **3.4.2. Test Procedures**

KDB 558074 Section 8.3.2 was used in order to prove compliance.

### **3.4.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.4.4. Test Result**

Refer to Annex A.3 in this report.



## 3.5.6 dB Bandwidth

### 3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e.,  $RBW = 100\text{ kHz}$ ,  $VBW \geq 3 \times RBW$ , and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6\text{ dB}$ .

### 3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.5.3.Test Result

Refer to Annex A.4 in this report.



## **3.6. Conducted Spurious Emissions and Band Edge**

### **3.6.1. Requirement**

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### **3.6.2. Test Procedures**

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

### **3.6.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.6.4. Test Result**

Refer to Annex A.5 and A.6 in this report.



## **3.7. Power Spectral Density**

### **3.7.1. Requirement**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **3.7.2. Test Procedures**

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

### **3.7.3. Test Setup Layout**

Refer to chapter 2.6.1 in this report.

### **3.7.4. Test Result**

Refer to Annex A.7 in this report.

## 3.8. Conducted Emission

### 3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

| Frequency Range (MHz) | Conducted Limit (dB $\mu$ V) |          |
|-----------------------|------------------------------|----------|
|                       | Quai-peak                    | Average  |
| 0.15 - 0.50           | 66 to 56                     | 56 to 46 |
| 0.50 - 5              | 56                           | 46       |
| 5 - 30                | 60                           | 50       |

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

### 3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

### 3.8.4. Test Result

Refer to Annex A.8 in this report.



## **3.9. Restricted Frequency Bands**

### **3.9.1. Requirement**

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### **3.9.2. Test Procedures**

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

### **3.9.3. Test Setup Layout**

Refer to chapter 2.6.3 in this report.

### **3.9.4. Test Result**

Refer to Annex A.9 in this report.

## 3.10. Radiated Emission

### 3.10.1.Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu\text{V}/\text{m}$ ) | Measurement Distance (m) |
|-----------------|-------------------------------------------|--------------------------|
| 0.009 - 0.490   | 2400/F(kHz)                               | 300                      |
| 0.490 - 1.705   | 24000/F(kHz)                              | 30                       |
| 1.705 - 30.0    | 30                                        | 30                       |
| 30 - 88         | 100                                       | 3                        |
| 88 - 216        | 150                                       | 3                        |
| 216 - 960       | 200                                       | 3                        |
| Above 960       | 500                                       | 3                        |

**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:**For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



### **3.10.2.Test Procedures**

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

### **3.10.3.Test Setup Layout**

Refer to chapter 2.6.3 in this report.

### **3.10.4.Test Result**


Refer to Annex A.10 in this report.




## Annex A Test Data and Result

### A.1. Duty Cycle of Test Signal


| Condition | Mode   | Frequency (MHz) | Antenna | Duty Cycle (%) | Correction Factor (dB) | 1/T (kHz) |
|-----------|--------|-----------------|---------|----------------|------------------------|-----------|
| NVNT      | BLE 1M | 2402            | Ant1    | 64.43          | 1.91                   | 2.48      |
| NVNT      | BLE 1M | 2440            | Ant1    | 61.44          | 2.12                   | 2.6       |
| NVNT      | BLE 1M | 2480            | Ant1    | 61.44          | 2.12                   | 2.6       |
| NVNT      | BLE 2M | 2402            | Ant1    | 57.17          | 2.43                   | 0.93      |
| NVNT      | BLE 2M | 2440            | Ant1    | 57.17          | 2.43                   | 0.93      |
| NVNT      | BLE 2M | 2480            | Ant1    | 57.17          | 2.43                   | 0.93      |




Duty Cycle NVNT BLE 1M 2402MHz Ant1




Duty Cycle NVNT BLE 1M 2440MHz Ant1




Duty Cycle NVNT BLE 1M 2480MHz Ant1



Duty Cycle NVNT BLE 2M 2402MHz Ant1




Duty Cycle NVNT BLE 2M 2440MHz Ant1



Duty Cycle NVNT BLE 2M 2480MHz Ant1

**A.2. Maximum Peak Conducted Output Power**

| Condition | Mode   | Frequency (MHz) | Antenna | Conducted Power (dBm) | Duty Factor (dB) | Total Conducted Power (dBm) | Total Conducted Power (W) | Limit Conducted (dBm) | Verdict |
|-----------|--------|-----------------|---------|-----------------------|------------------|-----------------------------|---------------------------|-----------------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | 5.41                  | 0                | 5.41                        | 0.00348                   | 30                    | Pass    |
| NVNT      | BLE 1M | 2440            | Ant1    | 5.38                  | 0                | 5.38                        | 0.00345                   | 30                    | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | 5.46                  | 0                | 5.46                        | 0.00352                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | 5.55                  | 0                | 5.55                        | 0.00359                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2440            | Ant1    | 5.33                  | 0                | 5.33                        | 0.00341                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | 5.61                  | 0                | 5.61                        | 0.00364                   | 30                    | Pass    |



Peak Power NVNT BLE 1M 2402MHz Ant1



Peak Power NVNT BLE 1M 2440MHz Ant1



Peak Power NVNT BLE 1M 2480MHz Ant1



Peak Power NVNT BLE 2M 2402MHz Ant1




Peak Power NVNT BLE 2M 2440MHz Ant1




Peak Power NVNT BLE 2M 2480MHz Ant1

**A.3. Maximum Average Conducted Output Power**


| Condition | Mode   | Frequency (MHz) | Antenna | Conducted Power (dBm) | Duty Factor (dB) | Total Conducted Power (dBm) | Total Conducted Power (W) | Limit Conducted (dBm) | Verdict |
|-----------|--------|-----------------|---------|-----------------------|------------------|-----------------------------|---------------------------|-----------------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | 2.74                  | 1.91             | 4.65                        | 0.00292                   | 30                    | Pass    |
| NVNT      | BLE 1M | 2440            | Ant1    | 2.87                  | 2.12             | 4.99                        | 0.00316                   | 30                    | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | 3.04                  | 2.12             | 5.16                        | 0.00328                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | 2.57                  | 2.43             | 5                           | 0.00316                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2440            | Ant1    | 2.69                  | 2.43             | 5.12                        | 0.00325                   | 30                    | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | 2.93                  | 2.43             | 5.36                        | 0.00344                   | 30                    | Pass    |




Average Power NVNT BLE 1M 2402MHz Ant1




Average Power NVNT BLE 1M 2440MHz Ant1




Average Power NVNT BLE 1M 2480MHz Ant1



Average Power NVNT BLE 2M 2402MHz Ant1



Average Power NVNT BLE 2M 2440MHz Ant1



Average Power NVNT BLE 2M 2480MHz Ant1

**A.4. 6 dB Bandwidth**

| Condition | Mode   | Frequency (MHz) | Antenna | -6 dB Bandwidth (MHz) | Limit -6 dB Bandwidth (MHz) | Verdict |
|-----------|--------|-----------------|---------|-----------------------|-----------------------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | 0.6977                | 0.5                         | Pass    |
| NVNT      | BLE 1M | 2440            | Ant1    | 0.6817                | 0.5                         | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | 0.668                 | 0.5                         | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | 1.134                 | 0.5                         | Pass    |
| NVNT      | BLE 2M | 2440            | Ant1    | 1.253                 | 0.5                         | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | 1.243                 | 0.5                         | Pass    |



-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1




-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1

**A.5. Conducted Spurious Emissions**

| Condition | Mode   | Frequency (MHz) | Antenna | Max Value (dBc) | Limit (dBc) | Verdict |
|-----------|--------|-----------------|---------|-----------------|-------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | -43.66          | -20         | Pass    |
| NVNT      | BLE 1M | 2440            | Ant1    | -44.42          | -20         | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | -44.05          | -20         | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | -43.71          | -20         | Pass    |
| NVNT      | BLE 2M | 2440            | Ant1    | -43.19          | -20         | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | -44.41          | -20         | Pass    |




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission




Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission




Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission




REPORT No.: SZ26040370W01

#### A.6. Band Edge

| Condition | Mode   | Frequency (MHz) | Antenna | Max Value (dBc) | Limit (dBc) | Verdict |
|-----------|--------|-----------------|---------|-----------------|-------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | -58.75          | -20         | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | -60.34          | -20         | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | -34.75          | -20         | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | -53.69          | -20         | Pass    |




Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Band Edge NVNT BLE 1M 2402MHz Ant1 Emission




Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission




Band Edge NVNT BLE 2M 2402MHz Ant1 Ref



Band Edge NVNT BLE 2M 2402MHz Ant1 Emission





Band Edge NVNT BLE 2M 2480MHz Ant1 Ref




Band Edge NVNT BLE 2M 2480MHz Ant1 Emission

**A.7. Power Spectral Density**

| Condition | Mode   | Frequency (MHz) | Antenna | Conducted PSD (dBm/3kHz) | Duty Factor (dB) | Total PSD (dBm/3kHz) | Limit (dBm/3kHz) | Verdict |
|-----------|--------|-----------------|---------|--------------------------|------------------|----------------------|------------------|---------|
| NVNT      | BLE 1M | 2402            | Ant1    | -9.57                    | 0                | -9.57                | 8                | Pass    |
| NVNT      | BLE 1M | 2440            | Ant1    | -9.67                    | 0                | -9.67                | 8                | Pass    |
| NVNT      | BLE 1M | 2480            | Ant1    | -9.27                    | 0                | -9.27                | 8                | Pass    |
| NVNT      | BLE 2M | 2402            | Ant1    | -13.52                   | 0                | -13.52               | 8                | Pass    |
| NVNT      | BLE 2M | 2440            | Ant1    | -13.6                    | 0                | -13.6                | 8                | Pass    |
| NVNT      | BLE 2M | 2480            | Ant1    | -14.29                   | 0                | -14.29               | 8                | Pass    |





PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1



PSD NVNT BLE 2M 2440MHz Ant1



PSD NVNT BLE 2M 2480MHz Ant1



### A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test Setup:

Test Mode: EUT+Notebook+Notebook adapter+USB cable+BLE TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading


$A_{\text{Factor}}$ : Voltage division factor of LISN

## B. Test Plot:



(L Phase)

| No. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1500        | 53.51                 | 34.73   | 66.00        | 56.00   | Line       | PASS    |
| 2   | 0.1725        | 52.61                 | 35.75   | 64.84        | 54.84   |            | PASS    |
| 3   | 0.2130        | 45.67                 | 30.39   | 63.09        | 53.09   |            | PASS    |
| 4   | 0.2310        | 42.90                 | 29.60   | 62.41        | 52.41   |            | PASS    |
| 5   | 0.2985        | 37.43                 | 27.52   | 60.29        | 50.29   |            | PASS    |
| 6   | 0.4785        | 36.29                 | 31.22   | 56.37        | 46.37   |            | PASS    |



(N Phase)


| No. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1500        | 58.64                 | 38.63   | 66.00        | 56.00   | Neutral    | PASS    |
| 2   | 0.1905        | 52.27                 | 35.14   | 64.02        | 54.02   |            | PASS    |
| 3   | 0.2310        | 45.94                 | 30.32   | 62.41        | 52.41   |            | PASS    |
| 4   | 0.2490        | 38.97                 | 25.42   | 61.79        | 51.79   |            | PASS    |
| 5   | 0.4155        | 34.25                 | 26.90   | 57.54        | 47.54   |            | PASS    |
| 6   | 2.3414        | 35.40                 | 28.82   | 56.00        | 46.00   |            | PASS    |

## A.9. Restricted Frequency Bands

**Note:** Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition was recorded in this test report.


### 1Mbps

Plot for Channel 0



| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2343.45         | 21.7           | 59.09          | 37.400        | 74.00          | 14.91       | 160       | PK       | Vertical | PASS    |
| 2370.25         | 8.5            | 45.93          | 37.470        | 54.00          | 8.07        | 183       | AV       | Vertical | PASS    |
| 2370.43         | 22.2           | 59.67          | 37.470        | 74.00          | 14.33       | 343       | PK       | Vertical | PASS    |
| 2382.03         | 20.9           | 58.33          | 37.480        | 74.00          | 15.67       | 358       | PK       | Vertical | PASS    |
| 2383.12         | 8.7            | 46.17          | 37.480        | 54.00          | 7.83        | 23        | AV       | Vertical | PASS    |
| 2387.27         | 8.5            | 45.96          | 37.490        | 54.00          | 8.04        | 306       | AV       | Vertical | PASS    |

Plot for Channel 39




| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2483.86         | 20.3           | 58.56          | 38.270        | 74.00          | 15.44       | 45        | PK       | Vertical | PASS    |
| 2484.20         | 8.3            | 46.56          | 38.270        | 54.00          | 7.44        | 163       | AV       | Vertical | PASS    |
| 2485.30         | 20.9           | 59.18          | 38.270        | 74.00          | 14.82       | 257       | PK       | Vertical | PASS    |
| 2485.69         | 8.3            | 46.60          | 38.270        | 54.00          | 7.40        | 322       | AV       | Vertical | PASS    |
| 2487.63         | 8.2            | 46.44          | 38.270        | 54.00          | 7.56        | 92        | AV       | Vertical | PASS    |
| 2487.71         | 21.2           | 59.42          | 38.270        | 74.00          | 14.58       | 148       | PK       | Vertical | PASS    |




## 2Mbps

### Plot for Channel 0



| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2380.44         | 20.7           | 58.20          | 37.480        | 74.00          | 15.80       | 200       | PK       | Vertical | PASS    |
| 2380.44         | 8.5            | 45.94          | 37.480        | 54.00          | 8.06        | 41        | AV       | Vertical | PASS    |
| 2386.18         | 21.2           | 58.71          | 37.490        | 74.00          | 15.29       | 59        | PK       | Vertical | PASS    |
| 2386.72         | 8.5            | 46.02          | 37.490        | 54.00          | 7.98        | 299       | AV       | Vertical | PASS    |
| 2388.86         | 8.7            | 46.22          | 37.490        | 54.00          | 7.78        | 341       | AV       | Vertical | PASS    |
| 2388.98         | 21.8           | 59.25          | 37.490        | 74.00          | 14.75       | 261       | PK       | Vertical | PASS    |

Plot for Channel 39



| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2484.51         | 20.5           | 58.80          | 38.270        | 74.00          | 15.20       | 61        | PK       | Vertical | PASS    |
| 2484.70         | 8.1            | 46.37          | 38.270        | 54.00          | 7.63        | 297       | AV       | Vertical | PASS    |
| 2485.57         | 8.1            | 46.40          | 38.270        | 54.00          | 7.60        | 325       | AV       | Vertical | PASS    |
| 2485.59         | 20.8           | 59.04          | 38.270        | 74.00          | 14.96       | 5         | PK       | Vertical | PASS    |
| 2487.03         | 8.1            | 46.41          | 38.270        | 54.00          | 7.59        | 175       | AV       | Vertical | PASS    |
| 2487.51         | 21.0           | 59.28          | 38.270        | 74.00          | 14.72       | 241       | PK       | Vertical | PASS    |



#### A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


**Note2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note 4:** All test modes were considered and evaluated respectively by performing full test, only the worst data were recorded.


# 1Mbps

## Plot for Channel 0




(Antenna Horizontal, 30MHz to 1GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 61.72           | 57.1           | 28.47          | -28.610       | 40.00          | 11.53       | 78        | PK       | Horizontal | PASS    |
| 73.12           | 57.4           | 25.19          | -32.230       | 40.00          | 14.81       | 306       | PK       | Horizontal | PASS    |
| 104.31          | 63.7           | 34.13          | -29.520       | 43.50          | 9.37        | 313       | PK       | Horizontal | PASS    |
| 132.10          | 65.5           | 33.32          | -32.220       | 43.50          | 10.18       | 292       | PK       | Horizontal | PASS    |
| 167.99          | 65.1           | 34.17          | -30.900       | 43.50          | 9.33        | 354       | PK       | Horizontal | PASS    |
| 469.48          | 60.7           | 39.39          | -21.270       | 46.00          | 6.61        | 9         | PK       | Horizontal | PASS    |




(Antenna Horizontal, 1GHz to 18GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 2469.49         | 40.2           | 46.14          | 5.920         | 74.00          | 27.86       | 170       | PK       | Horizontal | PASS    |
| 2473.89         | 28.3           | 34.19          | 5.900         | 54.00          | 19.81       | 180       | AV       | Horizontal | PASS    |
| 7205.69         | 37.5           | 42.53          | 5.030         | 54.00          | 11.47       | 360       | AV       | Horizontal | PASS    |
| 7206.98         | 45.5           | 50.48          | 5.020         | 74.00          | 23.52       | 356       | PK       | Horizontal | PASS    |
| 14678.48        | 26.6           | 47.12          | 20.540        | 54.00          | 6.88        | 116       | AV       | Horizontal | PASS    |
| 14694.33        | 35.6           | 56.21          | 20.580        | 74.00          | 17.79       | 9         | PK       | Horizontal | PASS    |



(Antenna Vertical, 30MHz to 1GHz)


| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 31.41           | 64.1           | 33.46          | -30.620       | 40.00          | 6.54        | 212       | PK       | Vertical | PASS    |
| 38.29           | 61.2           | 31.74          | -29.480       | 40.00          | 8.26        | 289       | PK       | Vertical | PASS    |
| 63.32           | 57.4           | 28.31          | -29.080       | 40.00          | 11.69       | 178       | PK       | Vertical | PASS    |
| 132.00          | 60.9           | 28.65          | -32.260       | 43.50          | 14.85       | 351       | PK       | Vertical | PASS    |
| 174.49          | 59.7           | 28.88          | -30.810       | 43.50          | 14.62       | 40        | PK       | Vertical | PASS    |
| 468.56          | 61.3           | 39.90          | -21.440       | 46.00          | 6.10        | 33        | PK       | Vertical | PASS    |



(Antenna Vertical, 1GHz to 18GHz)


| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2402.28         | 29.6           | 34.88          | 5.250         | 54.00          | 19.12       | 105       | AV       | Vertical | PASS    |
| 2412.28         | 39.8           | 45.19          | 5.400         | 74.00          | 28.81       | 138       | PK       | Vertical | PASS    |
| 7203.12         | 44.1           | 49.13          | 5.070         | 74.00          | 24.87       | 9         | PK       | Vertical | PASS    |
| 7205.69         | 35.9           | 40.95          | 5.030         | 54.00          | 13.05       | 237       | AV       | Vertical | PASS    |
| 13953.31        | 38.5           | 56.76          | 18.250        | 74.00          | 17.24       | 129       | PK       | Vertical | PASS    |
| 14686.62        | 26.9           | 47.42          | 20.560        | 54.00          | 6.58        | 290       | AV       | Vertical | PASS    |

### Plot for Channel 19




(Antenna Horizontal, 30MHz to 1GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 64.05           | 55.0           | 25.82          | -29.220       | 40.00          | 14.18       | 86        | PK       | Horizontal | PASS    |
| 72.00           | 56.9           | 25.52          | -31.380       | 40.00          | 14.48       | 311       | PK       | Horizontal | PASS    |
| 104.35          | 63.6           | 34.14          | -29.490       | 43.50          | 9.36        | 318       | PK       | Horizontal | PASS    |
| 132.00          | 66.2           | 33.96          | -32.260       | 43.50          | 9.54        | 106       | PK       | Horizontal | PASS    |
| 168.04          | 65.9           | 35.02          | -30.910       | 43.50          | 8.48        | 134       | PK       | Horizontal | PASS    |
| 471.76          | 57.3           | 36.16          | -21.110       | 46.00          | 9.84        | 356       | PK       | Horizontal | PASS    |




(Antenna Horizontal, 1GHz to 18GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 2439.49         | 40.4           | 46.24          | 5.810         | -              | -           | 172       | PK       | Horizontal | NA      |
| 2440.29         | 36.8           | 42.59          | 5.820         | -              | -           | 172       | AV       | Horizontal | NA      |
| 7319.27         | 44.7           | 48.98          | 4.270         | 74.00          | 25.02       | 9         | PK       | Horizontal | PASS    |
| 7319.69         | 37.9           | 42.16          | 4.270         | 54.00          | 11.84       | 9         | AV       | Horizontal | PASS    |
| 14680.62        | 27.0           | 47.58          | 20.550        | 54.00          | 6.42        | 184       | AV       | Horizontal | PASS    |
| 14735.05        | 36.0           | 56.25          | 20.290        | 74.00          | 17.75       | 277       | PK       | Horizontal | PASS    |



(Antenna Vertical, 30MHz to 1GHz)


| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 30.68           | 64.3           | 33.59          | -30.740       | 40.00          | 6.41        | 207       | PK       | Vertical | PASS    |
| 41.79           | 63.7           | 34.97          | -28.720       | 40.00          | 5.03        | 96        | PK       | Vertical | PASS    |
| 62.74           | 58.6           | 29.70          | -28.890       | 40.00          | 10.30       | 152       | PK       | Vertical | PASS    |
| 132.00          | 60.6           | 28.38          | -32.260       | 43.50          | 15.12       | 344       | PK       | Vertical | PASS    |
| 174.88          | 60.5           | 29.41          | -31.050       | 43.50          | 14.09       | 54        | PK       | Vertical | PASS    |
| 452.55          | 61.8           | 40.21          | -21.590       | 46.00          | 5.79        | 33        | PK       | Vertical | PASS    |



(Antenna Vertical, 1GHz to 18GHz)


| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2439.89         | 41.1           | 46.91          | 5.820         | -              | -           | 105       | PK       | Vertical | NA      |
| 2440.29         | 37.8           | 43.66          | 5.820         | -              | -           | 105       | AV       | Vertical | NA      |
| 7191.12         | 34.8           | 39.78          | 5.030         | 54.00          | 14.22       | 210       | AV       | Vertical | PASS    |
| 7203.98         | 44.4           | 49.46          | 5.060         | 74.00          | 24.54       | 49        | PK       | Vertical | PASS    |
| 14654.05        | 36.2           | 56.65          | 20.480        | 74.00          | 17.35       | 238       | PK       | Vertical | PASS    |
| 14692.19        | 27.0           | 47.53          | 20.580        | 54.00          | 6.47        | 77        | AV       | Vertical | PASS    |

### Plot for Channel 39




(Antenna Horizontal, 30MHz to 1GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 64.78           | 55.9           | 26.69          | -29.210       | 40.00          | 13.31       | 86        | PK       | Horizontal | PASS    |
| 72.49           | 56.6           | 24.81          | -31.770       | 40.00          | 15.19       | 284       | PK       | Horizontal | PASS    |
| 104.31          | 62.9           | 33.41          | -29.520       | 43.50          | 10.09       | 298       | PK       | Horizontal | PASS    |
| 131.95          | 65.1           | 32.90          | -32.240       | 43.50          | 10.60       | 133       | PK       | Horizontal | PASS    |
| 168.23          | 64.8           | 33.79          | -31.020       | 43.50          | 9.71        | 357       | PK       | Horizontal | PASS    |
| 448.19          | 58.8           | 37.24          | -21.590       | 46.00          | 8.76        | 9         | PK       | Horizontal | PASS    |




(Antenna Horizontal, 1GHz to 18GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity   | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|------------|---------|
| 2462.69         | 40.3           | 46.21          | 5.940         | 74.00          | 27.79       | 97        | PK       | Horizontal | PASS    |
| 2480.30         | 31.1           | 36.96          | 5.890         | -              | -           | 157       | AV       | Horizontal | NA      |
| 7411.41         | 44.0           | 48.67          | 4.710         | 74.00          | 25.33       | 332       | PK       | Horizontal | PASS    |
| 7440.98         | 36.8           | 41.43          | 4.630         | 54.00          | 12.57       | 49        | AV       | Horizontal | PASS    |
| 14683.19        | 26.7           | 47.22          | 20.560        | 54.00          | 6.78        | 347       | AV       | Horizontal | PASS    |
| 14696.91        | 37.3           | 57.86          | 20.590        | 74.00          | 16.14       | 90        | PK       | Horizontal | PASS    |



(Antenna Vertical, 30MHz to 1GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 31.89           | 63.7           | 33.20          | -30.510       | 40.00          | 6.80        | 274       | PK       | Vertical | PASS    |
| 40.72           | 61.1           | 32.20          | -28.880       | 40.00          | 7.80        | 308       | PK       | Vertical | PASS    |
| 51.58           | 59.5           | 31.49          | -28.010       | 40.00          | 8.51        | 66        | PK       | Vertical | PASS    |
| 132.05          | 60.3           | 28.10          | -32.240       | 43.50          | 15.40       | 136       | PK       | Vertical | PASS    |
| 175.70          | 59.5           | 28.57          | -30.900       | 43.50          | 14.93       | 74        | PK       | Vertical | PASS    |
| 468.22          | 60.7           | 39.23          | -21.490       | 46.00          | 6.77        | 31        | PK       | Vertical | PASS    |



(Antenna Vertical, 1GHz to 18GHz)

| Frequency [MHz] | Reading [dBμV] | Level [dBμV/m] | Factor [dB/m] | Limit [dBμV/m] | Margin [dB] | Angle [°] | Detector | Polarity | Verdict |
|-----------------|----------------|----------------|---------------|----------------|-------------|-----------|----------|----------|---------|
| 2476.30         | 40.2           | 46.08          | 5.900         | 74.00          | 27.92       | 88        | PK       | Vertical | PASS    |
| 2480.30         | 32.7           | 38.54          | 5.890         | -              | -           | 98        | AV       | Vertical | NA      |
| 7440.56         | 35.8           | 40.42          | 4.630         | 54.00          | 13.58       | 63        | AV       | Vertical | PASS    |
| 7568.70         | 44.4           | 49.07          | 4.640         | 74.00          | 24.93       | 278       | PK       | Vertical | PASS    |
| 14630.05        | 35.8           | 56.17          | 20.420        | 74.00          | 17.83       | 145       | PK       | Vertical | PASS    |
| 14681.05        | 26.9           | 47.45          | 20.560        | 54.00          | 6.55        | 76        | AV       | Vertical | PASS    |



## Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
  - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
  - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

————— END OF REPORT —————