

FCC Test Report

Client Name : Anker Innovations Limited

Client Address : Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

Product Name : eufy Pet Camera Lite N140 / Dog Camera D605

Report Date : Nov. 03, 2022

Shenzhen Anbotech Compliance Laboratory Limited



Shenzhen Anbotech Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotech.com

Code: AB-RF-05-b



Hotline

400-003-0500

www.anbotech.com.cn



Contents

1. General Information 5

 1.1. Client Information 5

 1.2. Description of Device (EUT) 5

 1.3. Auxiliary Equipment Used During Test 6

 1.4. Description of Test Modes 6

 1.5. List of channels 6

 1.6. Description Of Test Setup 7

 1.7. Test Equipment List 8

 1.8. Measurement Uncertainty 9

 1.9. Description of Test Facility 9

2. Summary of Test Results 10

3. Conducted Emission Test 11

 3.1. Test Standard and Limit 11

 3.2. Test Setup 11

 3.3. Test Procedure 11

 3.4. Test Data 11

4. Radiation Spurious Emission and Band Edge 14

 4.1. Test Standard and Limit 14

 4.2. Test Setup 14

 4.3. Test Procedure 15

 4.4. Test Data 16

5. Antenna Requirement 22

 5.1. Test Standard and Requirement 22

 5.2. Antenna Connected Construction 22

APPENDIX I -- TEST SETUP PHOTOGRAPH 23

APPENDIX II -- EXTERNAL PHOTOGRAPH 23

APPENDIX III -- INTERNAL PHOTOGRAPH 23



TEST REPORT

Applicant : Anker Innovations Limited
Manufacturer : Anker Innovations Limited
Product Name : eufy Pet Camera Lite N140 / Dog Camera D605
Model No. : T7203
Trade Mark : eufy PET
Rating(s) : T7200: DC 12V, 2A (via adapter input: 100-240V~ 50/60Hz 0.65A Max)
T7203: DC 12V, 1A (Via adapter input: 100-240V~ 50/60Hz 0.4A Max)

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB558074 D01 DTS Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Oct. 13, 2022

Date of Test

Oct. 13~24, 2022

Prepared By

Ella Liang

(Ella Liang)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Nov. 03, 2022

Note 1:

This is a Class II application which was based on the original report 18220WC10189101. Adding one more model T7203 which is based on T7200 to:

1. Reduce one motor (motor) and remove its small drive plate;
2. Replace the motor drive chip and delete the shield cover on the drive chip. The drive chip and layout inside the shield cover have changed, and the PCB layout outside the shield cover of the drive chip has not changed at all.
3. Main board: The memory chip is changed from 16G to 4G. The version number of the main board layout may change. The pin pin encapsulation of the chip is the same, and the circuit will not change, just change a chip;
4. For other three motors (motors), add one more source for each motor;
5. Replace the shell with other HB materials;
6. Replace a certified adapter (12V/1A) for T7203
7. Report one more graphic sensor, pin to pin, same specification, no difference in appearance, no change in layout
8. The wireless part has not changed
9. Change rating to DC 12V 1A for T7203
10. Increase crystal oscillator manufacturers

The changes are not related with the other RF parameters, only spurious emission were retested.



1. General Information

1.1. Client Information

Applicant	:	Anker Innovations Limited
Address	:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer	:	Anker Innovations Limited
Address	:	Room 1318-19, Hollywood Plaza, 610 Nathan Road, Mongkok, Kowloon, Hong Kong

1.2. Description of Device (EUT)

Product Name	:	eufy Pet Camera Lite N140 / Dog Camera D605	
Model No.	:	T7200, T7203 (Note: Based on the change made to the device, so we prepare "T7203" for test only.)	
Trade Mark	:	eufy PET	
Test Power Supply	:	AC 120V, 60Hz for adapter	
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)	
Product Description	:	Operation Frequency:	BLE:2402~2480MHz WiFi 2.4G: 2412-2462MHz for 802.11b/g/n(HT20)
	:	Number of Channel:	BLE:40 Channels WiFi 2.4G: 802.11b/ g/ n(HT20): 11 Channels
	:	Modulation Type:	BLE:GFSK WiFi 2.4G: CCK, DQPSK, DBPSK for DSSS; 64QAM, 16QAM, QPSK, BPSK for OFDM
	:	Antenna Type:	BLE&WiFi 2.4G: FPC antenna
	:	Antenna Gain(Peak):	BLE: 3.07 dBi WiFi 2.4G: 3.07 dBi
	:	Adapter:	Model: KA2401A-1202000US Input: 100V-240V~ 50/60Hz 0.4A Max Output: 12V---1000mA
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			



1.3. Auxiliary Equipment Used During Test

N/A	
-----	--

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	
Mode 1	CH00	TX Only
Mode 2	CH19	
Mode 3	CH39	

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

1.5. List of channels



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:

The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.



1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	1 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Nov. 01, 2021	1 Year



1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

During the test, pre-scan all modes, and found the “Low CH” which is the worst case, only the worst case is recorded in the report.



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 24.2℃ Hum.: 48%




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	38.43	9.70	48.13	65.78	-17.65	QP	
2	0.1539	20.77	9.70	30.47	55.78	-25.31	AVG	
3	0.1900	36.38	9.71	46.09	64.03	-17.94	QP	
4	0.1900	17.33	9.71	27.04	54.03	-26.99	AVG	
5	0.3820	24.76	9.71	34.47	58.23	-23.76	QP	
6	0.5020	15.85	9.76	25.61	46.00	-20.39	AVG	
7	0.5060	26.91	9.76	36.67	56.00	-19.33	QP	
8	0.9780	22.93	9.74	32.67	56.00	-23.33	QP	
9	0.9900	7.46	9.74	17.20	46.00	-28.80	AVG	
10	1.5780	8.05	9.73	17.78	46.00	-28.22	AVG	
11	4.1539	31.44	9.73	41.17	56.00	-14.83	QP	
12	4.2339	18.21	9.73	27.94	46.00	-18.06	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Mode 1
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.2℃ Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	19.79	9.69	29.48	55.99	-26.51	AVG	
2	0.1780	34.85	9.71	44.56	64.57	-20.01	QP	
3	0.1900	35.06	9.71	44.77	64.03	-19.26	QP	
4	0.4980	27.02	9.76	36.78	46.03	-9.25	AVG	
5	0.5060	35.39	9.76	45.15	56.00	-10.85	QP	
6	0.6700	14.39	9.75	24.14	46.00	-21.86	AVG	
7	0.9820	15.58	9.74	25.32	46.00	-20.68	AVG	
8	1.1019	25.12	9.74	34.86	56.00	-21.14	QP	
9	2.8220	26.39	9.73	36.12	56.00	-19.88	QP	
10	4.1340	24.00	9.73	33.73	46.00	-12.27	AVG	
11	4.3620	30.46	9.73	40.19	56.00	-15.81	QP	
12	5.2420	14.37	9.74	24.11	50.00	-25.89	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

- (1)The lower limit shall apply at the transition frequency.
- (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

–VBW=10Hz, When duty cycle is no less than 98 percent

– $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS


During the test, pre-scan all the modes, and found the Low channel (TX) which is the worst case, only the worst case is recorded in the report.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.



Test Results (30~1000MHz)

Test Mode: Mode 1
Power Source: AC 120V, 60Hz for adapter
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 24.8°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	31.3992	49.33	-19.76	29.57	40.00	-10.43	peak			
2	528.2458	40.79	-12.64	28.15	46.00	-17.85	peak			
3	601.4265	38.31	-10.53	27.78	46.00	-18.22	peak			
4	744.8661	37.03	-9.30	27.73	46.00	-18.27	peak			
5	836.2443	33.29	-7.70	25.59	46.00	-20.41	peak			
6	938.8326	33.50	-5.77	27.73	46.00	-18.27	peak			



Test Results (30~1000MHz)

Test Mode: Mode 1
Power Source: AC 120V, 60Hz for adapter
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 24.8°C/49%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	39.9942	42.04	-14.56	27.48	40.00	-12.52	QP			
2	50.4089	36.94	-15.92	21.02	40.00	-18.98	QP			
3	84.4054	46.34	-18.64	27.70	40.00	-12.30	QP			
4	99.5281	43.75	-16.63	27.12	43.50	-16.38	QP			
5	110.1816	45.22	-18.21	27.01	43.50	-16.49	QP			
6	631.6884	37.07	-10.62	26.45	46.00	-19.55	QP			



Test Results (1GHz-25GHz)

Test Mode: CH00

Test channel: Lowest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	27.63	15.27	42.90	74.00	-31.10	Vertical
7206.00	27.83	18.09	45.92	74.00	-28.08	Vertical
9608.00	28.40	23.76	52.16	74.00	-21.84	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	27.37	15.27	42.64	74.00	-31.36	Horizontal
7206.00	28.05	18.09	46.14	74.00	-27.86	Horizontal
9608.00	27.76	23.76	51.52	74.00	-22.48	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	15.90	15.27	31.17	54.00	-22.83	Vertical
7206.00	16.88	18.09	34.97	54.00	-19.03	Vertical
9608.00	17.87	23.76	41.63	54.00	-12.37	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	15.70	15.27	30.97	54.00	-23.03	Horizontal
7206.00	17.08	18.09	35.17	54.00	-18.83	Horizontal
9608.00	17.27	23.76	41.03	54.00	-12.97	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH19

Test channel: Middle

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	27.18	15.42	42.60	74.00	-31.40	Vertical
7320.00	27.80	18.02	45.82	74.00	-28.18	Vertical
9760.00	27.90	23.80	51.70	74.00	-22.30	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	27.18	15.42	42.60	74.00	-31.40	Horizontal
7320.00	27.92	18.02	45.94	74.00	-28.06	Horizontal
9760.00	27.48	23.80	51.28	74.00	-22.72	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	
4880.00	15.99	15.42	31.41	54.00	-22.59	polarization
7320.00	16.74	18.02	34.76	54.00	-19.24	Vertical
9760.00	17.72	23.80	41.52	54.00	-12.48	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	15.81	15.42	31.23	54.00	-22.77	Vertical
7320.00	17.43	18.02	35.45	54.00	-18.55	Horizontal
9760.00	17.57	23.80	41.37	54.00	-12.63	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test Mode: CH39

Test channel: Highest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	27.31	15.58	42.89	74.00	-31.11	Vertical
7440.00	27.96	17.93	45.89	74.00	-28.11	Vertical
9920.00	28.60	23.83	52.43	74.00	-21.57	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	27.32	15.58	42.90	74.00	-31.10	Horizontal
7440.00	28.13	17.93	46.06	74.00	-27.94	Horizontal
9920.00	27.86	23.83	51.69	74.00	-22.31	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	17.11	15.58	32.69	54.00	-21.31	Vertical
7440.00	18.01	17.93	35.94	54.00	-18.06	Vertical
9920.00	18.37	23.83	42.20	54.00	-11.80	Vertical
12400.00				54.00		Vertical
14880.00				54.00		Vertical
4960.00	16.99	15.58	32.57	54.00	-21.43	Horizontal
7440.00	18.23	17.93	36.16	54.00	-17.84	Horizontal
9920.00	17.72	23.83	41.55	54.00	-12.45	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1.Result =Read level + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.



5. Antenna Requirement

5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

5.2. Antenna Connected Construction

The antenna is a FPC antenna which permanently attached, and the best case gain of the antenna is 3.07dBi . It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files for Test Setup Photos of the EUT.

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files for External Photos of the EUT.

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files for Internal Photos of the EUT.

----- End of Report -----

