



REPORT No.: SZ18090076W01

TEST REPORT

APPLICANT : Anker Innovations Limited

PRODUCT NAME : HomeBase E

MODEL NAME : T8002

BRAND NAME : eufy Security

FCC ID : 2AOKB-T8002

STANDARD(S) : 47 CFR Part 15 Subpart C

TEST DATE : 2018-09-11 to 2018-10-25

ISSUE DATE : 2018-10-25

Tested by:

Wang Meng

Wang Meng (Test Engineer)

Approved by:

Peng Huarui

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. Test Standards and Results	6
1.4. Environmental Conditions	6
2. 47 CFR Part 15C Requirements	7
2.1. Antenna requirement	7
2.2. Duty Cycle Of Test Signal	7
2.3. Peak Output Power	11
2.4. Bandwidth	13
2.5. Conducted Spurious Emissions and Band Edge	22
2.6. Power spectral density (PSD)	35
2.7. Conducted Emission	43
2.8. Restricted Frequency Bands	47
2.9. Radiated Emission	59
Annex A Test Uncertainty	75
Annex B Testing Laboratory Information	76



REPORT No.: SZ18090076W01

Change History		
Issue	Date	Reason for change
1.0	2018-10-25	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Anker Innovations Limited
Applicant Address:	Room 1318-19,Hollywood Plaza,610 Nathan Road, Mongkok, Kowloon, Hong Kong
Manufacturer:	Anker Innovations Limited
Manufacturer Address:	Room 1318-19,Hollywood Plaza,610 Nathan Road, Mongkok, Kowloon, Hong Kong

1.2. Equipment Under Test (EUT) Description

Product Name:	HomeBase E
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	V02
Software Version:	V1.0.2.2
Modulation Type:	DSSS, OFDM
Operating Frequency Range:	802.11b/g/n-20: 2.412GHz - 2.462GHz 802.11n-40: 2.422GHz - 2.452GHz
Channel Number:	802.11b/g/n-20: 11 802.11n-40: 7
Antenna Type:	Ant0: PCB Antenna; Ant1: PCB Antenna
Antenna Gain:	Ant0: 0 dBi; Ant1: 0 dBi
Directional Gain:	3.01 dBi Note 3

Note 1: The EUT is operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.

For 802.11b/g/n-20MHz (2.4GHz band), the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).

For 802.11n-40MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 \cdot (n-1)$ ($3 \leq n \leq 9$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).



Note 2: The EUT has two identical antennas. Both of the antennas are PCB antenna and the antenna gain is 0dBi. For all modulation mode, the two antennas do not support MIMO function.

Modulation Mode:	TX Function	Relationship between the two output signals
802.11b	2TX	Correlated
802.11g	2TX	Correlated
802.11n	2TX	Correlated

Note 3: According to KDB 662911 D01, the directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

Note 4: For conducted test item Peak Power and Power spectral density of each modulation mode, we recorded the test result of two antennas separately, for other conducted test items both of the two antennas were tested separately, we only recorded the worst test result(Ant1) in this report.

Note 5: All radiation test items for all modulation modes operate at 2TX function during the test.

Note 6: The EUT connected to the serial port of the computer with a serial communication cable, we use the dedicated software to control the EUT continuous transmission.

Note 7: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.203	Antenna Requirement	N/A	N/A	PASS
2	N/A	Duty Cycle Of Test Signal	Oct 25, 2018	Wang Meng	PASS
3	15.247(b)	Peak Output Power	Sep 18, 2018	Wang Meng	PASS
4	15.247(a)	Bandwidth	Sep 18, 2018	Wang Meng	PASS
5	15.247(d)	Conducted Spurious Emission and Band Edge	Sep 18, 2018	Wang Meng	PASS
6	15.247(e)	Power spectral density (PSD)	Oct 25, 2018	Wang Meng	PASS
7	15.207	Conducted Emission	Sep 11, 2018	Peng Xuwei	PASS
8	15.247(d)	Restricted Frequency Bands	Oct 11, 2018	Peng Xuwei	PASS
9	15.209, 15.247(d)	Radiated Emission	Oct 11, 2018	Peng Xuwei	PASS

Note: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2013 and KDB558074 D01 v04 (04/05/2017).

1.4. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle Of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

A. Test Set:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX B(4).


2.2.3. Test Result

A. Test Verdict:


Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
802.11b	100	0
802.11g	100	0
802.11n20	100	0
802.11n40	100	0




B. Test Plots




(Channel 1, 2412MHz, 802.11b)



(Channel 1, 2412MHz, 802.11g)



(Channel 1, 2412MHz, 802.11n20)



(Channel 3, 2422MHz, 802.11n40)

2.3. Peak Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

B. Equipments List:

Please refer ANNEX B(4).

**2.3.3. Test Result**

Mode	Chan.	Freq. (MHz)	Peak Power(dBm)		Total Power (W)	Total Power (dBm)	Limit (dBm)	Verdict
			Ant0	Ant1				
802.11 b	1	2412	24.23	23.61	0.494	26.94	30	PASS
	6	2437	25.76	25.93	0.768	28.86	30	PASS
	11	2462	24.32	24.73	0.568	27.54	30	PASS
802.11 g	1	2412	23.51	23.67	0.457	26.60	30	PASS
	6	2437	25.45	25.80	0.731	28.64	30	PASS
	11	2462	23.72	23.74	0.472	26.74	30	PASS
802.11 n20	1	2412	23.54	23.05	0.428	26.31	30	PASS
	6	2437	25.34	25.63	0.708	28.50	30	PASS
	11	2462	24.31	23.52	0.495	26.94	30	PASS
802.11 n40	3	2422	23.25	23.07	0.414	26.17	30	PASS
	6	2437	25.26	25.47	0.688	28.38	30	PASS
	9	2452	24.7	25.18	0.625	27.96	30	PASS

Mode	Chan.	Freq. (MHz)	Average Power(dBm)		Total Power (W)	Total Power (dBm)	Limit (dBm)	Verdict
			Ant0	Ant1				
802.11 b	1	2412	21.47	21.45	0.280	24.47	30	PASS
	6	2437	23.45	23.83	0.463	26.65	30	PASS
	11	2462	22.62	22.41	0.357	25.53	30	PASS
802.11 g	1	2412	15.10	13.10	0.053	17.22	30	PASS
	6	2437	16.33	14.71	0.073	18.61	30	PASS
	11	2462	14.37	12.87	0.047	16.69	30	PASS
802.11 n20	1	2412	12.49	12.21	0.034	15.36	30	PASS
	6	2437	14.22	14.67	0.056	17.46	30	PASS
	11	2462	16.84	12.94	0.068	18.32	30	PASS
802.11 n40	3	2422	12.14	11.84	0.032	15.00	30	PASS
	6	2437	13.75	14.27	0.050	17.03	30	PASS
	9	2452	13.56	14.11	0.048	16.85	30	PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 8.1 Option 1 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX B(4).




2.4.3. Test Result

2.4.3.1 802.11b Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	10.00	≥500	PASS
6	2437	10.03	≥500	PASS
11	2462	10.02	≥500	PASS


B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 6, 2437 MHz, 802.11b)



(Channel 11, 2462MHz, 802.11b)




2.4.3.2 802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.10	≥500	PASS
6	2437	15.10	≥500	PASS
11	2462	15.09	≥500	PASS


B. Test Plots:



(Channel 1, 2412MHz, 802.11g)



(Channel 6, 2437MHz, 802.11g)



(Channel 11, 2462MHz, 802.11g)




2.4.3.3 802.11n20 Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.10	≥500	PASS
6	2437	15.10	≥500	PASS
11	2462	15.10	≥500	PASS


B. Test Plots:



(Channel 1, 2412MHz, 802.11n20)



(Channel 6, 2437MHz, 802.11n20)



(Channel 11, 2462MHz, 802.11n20)




2.4.3.4 802.11n40 Test mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	35.05	≥500	PASS
6	2437	35.05	≥500	PASS
9	2452	35.04	≥500	PASS


B. Test Plots:



(Channel 3, 2422Mz, 802.11n40)



(Channel 6, 2437MHz, 802.11n40)



(Channel 9, 2452MHz, 802.11n40)


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 11.0 was used in order to prove compliance.

B. Equipments List:

Please refer ANNEX B(4).



2.5.3. Test Result


2.5.3.1 802.11b Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-36.34	14.60	-5.40	PASS
6	2437	-32.25	14.64	-5.36	PASS
11	2462	-32.85	14.82	-5.18	PASS

B. Test Plots:


Note: The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




2.5.3.2 802.11g Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-32.03	10.08	-9.92	PASS
6	2437	-32.49	10.99	-9.01	PASS
11	2462	-32.55	10.07	-9.93	PASS

B. Test Plots:


Note: The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




2.5.3.3 802.11n20 Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-32.08	10.47	-9.53	PASS
6	2437	-31.82	11.76	-8.24	PASS
11	2462	-32.65	10.83	-9.17	PASS

B. Test Plots:


Note: The power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




2.5.3.4 802.11n40 Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-31.81	8.34	-11.66	PASS
6	2437	-35.17	10.74	-9.26	PASS
9	2452	-35.80	9.80	-10.20	PASS

B. Test Plots:


Note: The power of the Module transmitting frequency should be ignored.




(Channel = 3, 30MHz to 25GHz)



(Band Edge, Channel = 3)



(Channel = 6, 30MHz to 25GHz)



(Channel = 9, 30MHz to 25GHz)



(Band Edge, Channel = 9)

2.6. Power spectral density (PSD)

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


2.6.2. Test Description

A. Test procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency.
- b) Set the span to 1.5 times DTS
- c) Set the RBW to 3 kHz
- d) Set the VBW to 10 kHz
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

B. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

KDB 558074 Section 10.2 was used in order to prove compliance.

C. Equipments List:

Please refer ANNEX B(4).



2.6.3. Test Result

A. Test Verdict:


Mode	Chan.	Freq. (MHz)	PSD(dBm/3kHz)		Total PSD (W/3kHz)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
			Ant0	Ant1				
802.11 b	1	2412	-3.11	-1.76	0.00116	0.63	8	PASS
	6	2437	-2.76	0.90	0.00176	2.46	8	PASS
	11	2462	-3.72	-0.54	0.00131	1.16	8	PASS
802.11 g	1	2412	-13.25	-12.61	0.00010	-9.90	8	PASS
	6	2437	-11.52	-9.41	0.00019	-7.33	8	PASS
	11	2462	-13.50	-12.42	0.00010	-9.92	8	PASS
802.11 n20	1	2412	-14.07	-11.35	0.00011	-9.49	8	PASS
	6	2437	-12.20	-8.74	0.00019	-7.12	8	PASS
	11	2462	-14.49	-11.38	0.00011	-9.65	8	PASS
802.11 n40	3	2422	-15.04	-13.11	0.00008	-10.96	8	PASS
	6	2437	-14.13	-12.80	0.00009	-10.40	8	PASS
	9	2452	-13.63	-12.90	0.00009	-10.24	8	PASS

B. Test Plot

Below are the worst case situation test plots:




(Channel = 1, 802.11b, Ant1)




(Channel = 6, 802.11b, Ant1)




(Channel = 11, 802.11b, Ant1)




(Channel = 1, 802.11g, Ant1)




(Channel = 6, 802.11g, Ant1)




(Channel = 11, 802.11g, Ant1)




(Channel = 1, 802.11n20, Ant1)




(Channel = 6, 802.11n20, Ant1)




(Channel = 11, 802.11n20, Ant1)



(Channel = 3, 802.11n40, Ant1)



(Channel = 6, 802.11n40, Ant1)



(Channel = 9, 802.11n40, Ant1)

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



B. Equipments List:

Please refer ANNEX B(4).

2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.


Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test setup:

The EUT configuration of the emission tests is EUT + Link.


Note: The test voltage is AC 120V/60Hz.

B. Test Plots:



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1590	36.82	26.16	65.52	55.52	Line	PASS
2	0.3030	33.54	24.58	60.16	50.16		PASS
3	0.4872	35.75	24.66	56.22	46.22		PASS
4	0.9331	30.95	21.65	56.00	46.00		PASS
5	1.3376	30.74	21.32	56.00	46.00		PASS
6	14.5960	28.04	22.69	60.00	50.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1635	37.75	27.65	65.28	55.28	Neutral	PASS
2	0.2534	36.38	28.43	61.65	51.65		PASS
3	0.5502	29.82	23.25	56.00	46.00		PASS
4	0.8796	30.44	22.59	56.00	46.00		PASS
5	1.3743	29.21	21.55	56.00	46.00		PASS
6	15.0680	32.49	23.55	60.00	50.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

KDB 558074 Section 12.1 was used in order to prove compliance.

**B. Equipments List:**

Please refer ANNEX B(4).

2.8.3. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.6.3.1 802.11b Test mode**A. Test Verdict:**


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2381.46	PK	48.24	-29.67	32.56	51.13	74	PASS
1	2387.28	AV	36.37	-29.67	32.56	39.26	54	PASS
11	2488.14	PK	48.95	-29.67	32.56	51.84	74	PASS
11	2485.74	AV	36.25	-29.67	32.56	39.14	54	PASS




B. Test Plots:



(Channel = 1 PEAK, 802.11b)



(Channel = 1 AVG, 802.11b)



(Channel = 11 PEAK, 802.11b)



(Channel = 11 AVG, 802.11b)




2.6.3.2 802.11g Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
1	2373.06	PK	47.84	-29.67	32.56	50.73	74	PASS
1	2386.50	AV	36.36	-29.67	32.56	39.25	54	PASS
11	2486.66	PK	49.30	-29.67	32.56	52.19	74	PASS
11	2484.03	AV	36.26	-29.67	32.56	39.15	54	PASS


B. Test Plots:



(Channel = 1 PEAK, 802.11g)



(Channel = 1 AVG, 802.11g)



(Channel = 11 PEAK, 802.11g)



(Channel = 11 AVG, 802.11g)


2.6.3.3 802.11n20 Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2372.50	PK	47.88	-29.67	32.56	50.77	74	PASS
1	2388.06	AV	36.37	-29.67	32.56	39.26	54	PASS
11	2485.52	PK	48.27	-29.67	32.56	51.16	74	PASS
11	2486.24	AV	36.25	-29.67	32.56	39.14	54	PASS




B. Test Plots:



(Channel = 1 PEAK, 802.11n20)



(Channel = 1 AVG, 802.11n20)



(Channel = 11 PEAK, 802.11n20)



(Channel = 11 AVG, 802.11n20)




2.6.3.4 802.11n40 Test mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2375.28	PK	48.52	-29.67	32.56	51.41	74	PASS
3	2382.11	AV	36.27	-29.67	32.56	39.16	54	PASS
9	2486.09	PK	49.04	-29.67	32.56	51.93	74	PASS
9	2485.06	AV	36.21	-29.67	32.56	39.10	54	PASS


B. Test Plots:



(Channel = 3 PEAK, 802.11n40)



(Channel = 3 AVG, 802.11n40)



(Channel = 9 PEAK, 802.11n40)



(Channel = 9 AVG, 802.11n40)



2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.9.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

A. Equipments List:

Please refer ANNEX B(4).

2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 25GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


2.8.3.1 802.11b Test mode

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	33.36	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
114.981	30.43	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1907.243	46.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4477.869	46.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8636.879	47.22	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17969.194	49.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
34.856	32.76	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
119.837	28.88	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2100.600	48.97	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5394.399	47.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12148.209	48.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20168.867	50.43	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 6




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	31.26	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
117.409	31.93	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2459.784	48.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3378.032	44.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8001.418	46.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13166.576	46.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	32.83	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
107.697	27.72	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2452.101	47.78	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4241.608	44.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8412.839	46.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13195.090	47.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11


Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.568	31.67	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
102.841	28.40	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2108.283	49.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4705.983	45.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9378.251	46.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
18128.060	48.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
53.066	30.91	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
96.771	28.58	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2415.606	46.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5756.938	47.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9003.492	46.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13081.033	47.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.8.3.2 802.11g Test mode****Plots for Channel = 1**

Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	30.98	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
100.413	28.31	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2404.722	46.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4196.799	45.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8420.986	47.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
17932.533	48.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.712	32.59	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
100.413	27.63	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2451.461	47.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3263.975	45.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5667.321	45.59	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12897.727	47.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	32.13	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
118.623	29.09	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2114.046	48.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5777.305	46.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8034.006	47.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13081.033	47.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	31.44	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
219.387	27.31	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2299.720	48.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4726.350	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12677.760	48.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
20038.516	51.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	31.44	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
119.837	30.43	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2108.283	49.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3357.665	44.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5524.750	47.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12213.384	47.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.712	32.58	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
95.557	27.42	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2108.283	49.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4196.799	44.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5765.085	46.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12135.988	46.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.8.3.3 802.11n20 Test mode****Plots for Channel = 1**

Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.568	31.69	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
116.195	31.56	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2172.949	46.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4502.310	45.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9064.594	46.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12510.747	47.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	32.14	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
96.771	27.86	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2028.251	46.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3834.261	45.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5797.672	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8441.353	46.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	32.52	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
101.627	28.20	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2114.046	49.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4380.105	45.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8469.867	46.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12893.653	47.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	32.74	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
90.701	27.29	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2099.960	49.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4184.579	44.52	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5769.158	45.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12188.943	47.52	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
39.712	31.92	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
114.981	31.65	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2412.405	47.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4714.130	45.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8608.365	46.44	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12905.874	47.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	33.23	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
101.627	28.96	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2457.863	47.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4856.701	44.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7972.904	46.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12881.433	48.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)


**2.8.3.4 802.11n40 Test mode**

Plots for Channel = 3




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	32.07	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
121.051	30.85	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2096.759	46.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4697.836	44.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8640.953	46.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12742.935	47.14	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	32.60	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
101.627	28.23	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2101.240	48.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3312.857	44.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5756.938	46.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8050.300	47.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

Plots for Channel = 6

Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
38.498	31.51	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
96.771	29.86	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2108.283	48.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4710.056	45.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5374.032	46.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10808.038	46.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.070	32.77	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
95.557	29.12	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2107.643	49.49	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3874.995	46.31	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5716.203	47.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12600.364	48.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plots for Channel = 9



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	31.16	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
104.055	29.61	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2108.283	48.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4253.828	44.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5655.101	45.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12148.209	47.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	33.15	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
111.339	28.03	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1793.918	45.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3716.130	44.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5565.485	45.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8449.500	46.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Power Splitter	NW521	1506A	Weinschel	2018.04.17	2019.04.16
Attenuator 1	(N/A.)	10dB	Resnet	2018.04.17	2019.04.16
Attenuator 2	(N/A.)	3dB	Resnet	2018.04.17	2019.04.16
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2017.12.03	2018.12.02
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2018.04.17	2019.04.16
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2018.05.08	2019.05.07
LISN	812744	NSLK 8127	Schwarzbeck	2018.05.08	2019.05.07
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2018.05.08	2019.05.07
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

4.3 Auxiliary Test Equipment

Equipment Name	Model No.	Brand Name	Manufacturer	Cal.Date	Cal.Due Date
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.4 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0

**4.5 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2018.08.04	2019.08.03
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2018.05.18	2019.05.17
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2018.03.03	2019.03.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2018.08.06	2019.08.05
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2018.08.02	2019.08.01
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2018.05.08	2019.05.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

————— END OF REPORT —————