



# TEST REPORT

**FCC ID: 2AOKDSDU0070****Product: SDU-0070****Model No.: SDU-0070-001****Additional Model No: SDU-0070-002 (xxx=002-999)****Trade Mark: ad notam <sup>®</sup>****Report No.: FCC18010018A-WiFi****Issued Date: February 26, 2018**

Issued for:

ad notam AG

**Obere Giesswiesen 11-13, 78247 Hilzingen, Germany**

Issued By:

**World Standardization Certification & Testing Group Co.,Ltd.  
Building A-B, Baoshi Science & Technology Park, Baoshi Road,  
Bao'an District, Shenzhen, Guangdong, China****TEL: +86-755-26996192****FAX: +86-755-86376605**

**Note:** The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.





## TABLE OF CONTENTS

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>1. Test Certification .....</b>                               | <b>3</b>  |
| <b>2. Test Result Summary .....</b>                              | <b>4</b>  |
| <b>3. EUT Description.....</b>                                   | <b>5</b>  |
| <b>4. Genera Information.....</b>                                | <b>7</b>  |
| 4.1. TEST ENVIRONMENT AND MODE .....                             | 7         |
| 4.2. DESCRIPTION OF SUPPORT UNITS .....                          | 8         |
| <b>5. Facilities and Accreditations .....</b>                    | <b>9</b>  |
| 5.1. FACILITIES .....                                            | 9         |
| 5.2. ACCREDITATIONS .....                                        | 9         |
| 5.3 MEASUREMENT UNCERTAINTY .....                                | 10        |
| 5.4 MEASUREMENT INSTRUMENTS .....                                | 11        |
| <b>6. Test Results and Measurement Data .....</b>                | <b>12</b> |
| 6.1. ANTENNA REQUIREMENT .....                                   | 12        |
| 6.2. CONDUCTED EMISSION .....                                    | 13        |
| 6.3. EMISSION BANDWIDTH .....                                    | 24        |
| 6.4. POWER SPECTRAL DENSITY .....                                | 32        |
| 6.5. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT ..... | 40        |
| 6.6. RADIATED SPURIOUS EMISSION MEASUREMENT .....                | 50        |
| <b>7. Appendix A: Photographs of Test Setup .....</b>            | <b>59</b> |
| <b>8. Appendix B: Photographs of EUT .....</b>                   | <b>61</b> |



Report No.: FCC18010018A-WIFI

## 1. Test Certification

|                       |                                                                                                                  |
|-----------------------|------------------------------------------------------------------------------------------------------------------|
| Product:              | SDU-0070                                                                                                         |
| Model No.:            | SDU-0070-001                                                                                                     |
| Additional Model No.: | SDU-0070-002(xxx=002-999)                                                                                        |
| Trade Mark:           | ad notam ®                                                                                                       |
| Applicant:            | ad notam AG                                                                                                      |
| Address:              | Obere Giesswiesen 11-13, 78247 Hilzingen, Germany                                                                |
| Manufacturer:         | Shenzhen KOHO Technology Co., Ltd                                                                                |
| Address:              | F4, Building 3, Fubulun Dingfeng Hi-Tech Industrial Park, Songgang Blvd, Bao'an District, Shenzhen, China 518105 |
| Date of Test:         | February 10, 2018 to February 25, 2018                                                                           |
| Applicable Standards: | FCC CFR Title 47 Part 15 Subpart C Section 15.247<br>KDB 558074 D01 DTS Meas Guidance v04                        |

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wen Quan  
(Wen Quan)Date: 2018.02.26Check By: Li Huaibi  
(Li Huaibi)Date: 2018.02.26Approved By: Wang Fengbing  
(Wang Fengbing)Date: 2018.02.26



## 2. Test Result Summary

| Requirement                      | CFR 47 Section                      | Result |
|----------------------------------|-------------------------------------|--------|
| Antenna requirement              | §15.203/§15.247 (c)                 | PASS   |
| AC Power Line Conducted Emission | §15.207                             | PASS   |
| Conducted Peak Output Power      | §15.247 (b)(3)<br>§2.1046           | PASS   |
| 6dB Emission Bandwidth           | §15.247 (a)(2)<br>§2.1049           | PASS   |
| Power Spectral Density           | §15.247 (e)                         | PASS   |
| Band Edge                        | §15.247(d)<br>§2.1051, §2.1057      | PASS   |
| Spurious Emission                | §15.205/§15.209<br>§2.1053, §2.1057 | PASS   |

### Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.



### 3. EUT Description

|                                                          |                                                                                             |
|----------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Product:</b>                                          | SDU-0070                                                                                    |
| <b>Model No.:</b>                                        | SDU-0070-001                                                                                |
| <b>Additional Model No.:</b>                             | SDU-0070-xxx(xxx=002-999)                                                                   |
| <b>Trade Mark:</b>                                       | ad notam ®                                                                                  |
| <b>Operation Frequency:</b>                              | 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20))                                             |
| <b>Channel Separation:</b>                               | 5MHz                                                                                        |
| <b>Number of Channel:</b>                                | 11 for 802.11b/802.11g/802.11n(HT20)                                                        |
| <b>Modulation Technology:<br/>(IEEE 802.11b)</b>         | Direct Sequence Spread Spectrum (DSSS)                                                      |
| <b>Modulation Technology:<br/>(IEEE 802.11g/802.11n)</b> | Orthogonal Frequency Division Multiplexing(OFDM)                                            |
| <b>Data speed (IEEE<br/>802.11b):</b>                    | 1Mbps, 2Mbps, 5.5Mbps, 11Mbps                                                               |
| <b>Data speed (IEEE<br/>802.11g):</b>                    | 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps,<br>48Mbps, 54Mbps                             |
| <b>Data speed (IEEE<br/>802.11n):</b>                    | Up to 72Mbps                                                                                |
| <b>Antenna Type:</b>                                     | External antenna                                                                            |
| <b>Antenna Gain</b>                                      | 3dBi                                                                                        |
| <b>Power supply:</b>                                     | Adapter: LS-PAB90AL-E<br>Input: 100-240V 50/60Hz 1.5A<br>Output: 12V-7A                     |
| <b>Remark:</b>                                           | Only the model name, the others are the same, so the test data is executed at SDU-0070-001. |

**Operation Frequency each of channel For 802.11b/g/n(HT20)**

| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2       | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3       | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

**Note:**

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

**802.11b/802.11g/802.11n (HT20)**

| Channel             | Frequency |
|---------------------|-----------|
| The lowest channel  | 2412MHz   |
| The middle channel  | 2437MHz   |
| The Highest channel | 2462MHz   |



## 4. Genera Information

### 4.1. Test environment and mode

#### Operating Environment:

|                       |           |
|-----------------------|-----------|
| Temperature:          | 25.0 °C   |
| Humidity:             | 56 % RH   |
| Atmospheric Pressure: | 1010 mbar |

#### Test Mode:

|                   |                                                                                                              |
|-------------------|--------------------------------------------------------------------------------------------------------------|
| Engineering mode: | Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) |
|-------------------|--------------------------------------------------------------------------------------------------------------|

The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. For the full battery state and The output power to the maximum state.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

**Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.**

| Mode         | Data rate |
|--------------|-----------|
| 802.11b      | 1Mbps     |
| 802.11g      | 6Mbps     |
| 802.11n(H20) | 6.5Mbps   |

#### Final Test Mode:

|                 |                                                         |
|-----------------|---------------------------------------------------------|
| Operation mode: | Keep the EUT in continuous transmitting with modulation |
|-----------------|---------------------------------------------------------|

1. For WIFI function, the engineering test program was provided and enabled to make EUT continuous transmit/receive. 2. According to ANSI C63.10 standards, the test results are both the "worst case" and "worst setup" 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20). Duty cycle setting during the transmission is 98.5% with maximum power setting for all modulations.



## 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment | Model No.    | Serial No. | FCC ID | Trade Name |
|-----------|--------------|------------|--------|------------|
| Adapter   | LS-PAB90AL-E | /          | /      | ADAPTER    |

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



## 5. Facilities and Accreditations

### 5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group CO., LTD**

**Registration Number: 366353**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

**USA**

**NVLAP** (The certificate registration number is NVLAP LAB CODE:600142-0)

**Japan**

**VCCI** (The certificate registration number is C-4790, R-3684, G-837)

**Canada**

**INDUSTRY CANADA**

(The certificated registration number is 7700A-1)

**China**

**CNAS** (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>





### 5.3 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                          | MU                        |
|-----|-------------------------------|---------------------------|
| 1   | Conducted Emission Test       | $\pm 3.2\text{dB}$        |
| 2   | RF power, conducted           | $\pm 0.16\text{dB}$       |
| 3   | Spurious emissions, conducted | $\pm 0.21\text{dB}$       |
| 4   | All emissions, radiated(<1G)  | $\pm 4.7\text{dB}$        |
| 5   | All emissions, radiated(>1G)  | $\pm 4.7\text{dB}$        |
| 6   | Temperature                   | $\pm 0.5^{\circ}\text{C}$ |
| 7   | Humidity                      | $\pm 2.0\%$               |



## 5.4 MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT                    | MANUFACTURER           | MODEL        | SERIAL NUMBER | Calibration Date | Calibration Due. |
|--------------------------------------|------------------------|--------------|---------------|------------------|------------------|
| EMI Test Receiver                    | R&S                    | ESCI         | 100005        | 08/19/2017       | 08/18/2018       |
| LISN                                 | AFJ                    | LS16         | 16010222119   | 08/19/2017       | 08/18/2018       |
| LISN(EUT)                            | Mestec                 | AN3016       | 04/10040      | 08/19/2017       | 08/18/2018       |
| Universal Radio Communication Tester | R&S                    | CMU 200      | 1100.0008.02  | 08/19/2017       | 08/18/2018       |
| Coaxial cable                        | Megalon                | LMR400       | N/A           | 08/12/2017       | 08/11/2018       |
| GPIO cable                           | Megalon                | GPIO         | N/A           | 08/12/2017       | 08/11/2018       |
| Spectrum Analyzer                    | R&S                    | FSU          | 100114        | 08/19/2017       | 08/18/2018       |
| Pre Amplifier                        | H.P.                   | HP8447E      | 2945A02715    | 10/13/2017       | 10/12/2018       |
| Pre-Amplifier                        | CDSI                   | PAP-1G18-38  | --            | 10/13/2017       | 10/12/2018       |
| Bi-log Antenna                       | SUNOL Sciences         | JB3          | A021907       | 09/13/2017       | 09/12/2018       |
| 9*6*6 Anechoic                       | --                     | --           | --            | 08/21/2017       | 08/20/2018       |
| Horn Antenna                         | COMPLIANCE ENGINEERING | CE18000      | --            | 09/13/2017       | 09/12/2018       |
| Horn Antenna                         | SCHWARZBECK            | BBHA9120D    | 9120D-631     | 08/23/2017       | 08/22/2018       |
| Cable                                | TIME MICROWAVE         | LMR-400      | N-TYPE04      | 04/25/2017       | 04/24/2018       |
| System-Controller                    | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Turn Table                           | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Antenna Tower                        | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| RF cable                             | Murata                 | MXHQ87WA3000 | -             | 08/21/2017       | 08/20/2018       |
| Loop Antenna                         | EMCO                   | 6502         | 00042960      | 08/22/2017       | 08/21/2018       |
| Horn Antenna                         | SCHWARZBECK            | BBHA 9170    | 1123          | 08/19/2017       | 08/18/2018       |
| Power meter                          | Anritsu                | ML2487A      | 6K00003613    | 08/23/2017       | 08/22/2018       |
| Power sensor                         | Anritsu                | MX248XD      | --            | 08/19/2017       | 08/18/2018       |





## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

**Standard requirement:**

FCC Part15 C Section 15.203 /247(c)

**15.203 requirement:**


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**15.247(c) (1)(i) requirement:**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**E.U.T Antenna:**


The WIFI antenna is a External antenna with the RP SMA Connector. it meets the standards, and the best case gain of the antenna is 3dBi.





## 6.2. Conducted Emission

### 6.2.1. Test Specification


| Test Requirement:        | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method:             | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Frequency Range:         | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Receiver setup:          | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Limits:                  | <table><tr><th rowspan="2">Frequency range<br/>(MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>                                                                                                                                                                                                                                                                                                                                                                                                                                  | Frequency range<br>(MHz) | Limit (dBuV) |  | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range<br>(MHz) | Limit (dBuV)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
|                          | Quasi-peak                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Average                  |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.15-0.5                 | 66 to 56*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 56 to 46*                |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.5-5                    | 56                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 46                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 5-30                     | 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 50                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Setup:              | <div><p>Reference Plane</p><p>40cm 80cm</p><p>E.U.T AC power LISN Filter AC power EMI Receiver</p><p>Test table/Insulation plane</p><p>Remark<br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                        |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Mode:               | Charging + transmitting with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Procedure:          | <ol style="list-style-type: none"><li>1. The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li><li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li><li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li></ol> |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Result:             | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                          |              |  |            |         |          |           |           |       |    |    |      |    |    |



## 6.2.2. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.1539       | 36.01                    | 10.44                   | 46.45                    | 65.78         | -19.33     | QP       |
| 2   |     | 0.1580       | 26.08                    | 10.44                   | 36.52                    | 55.56         | -19.04     | AVG      |
| 3   |     | 0.2060       | 31.16                    | 10.43                   | 41.59                    | 63.36         | -21.77     | QP       |
| 4   |     | 0.2220       | 18.87                    | 10.43                   | 29.30                    | 52.74         | -23.44     | AVG      |
| 5   |     | 0.4260       | 20.00                    | 10.41                   | 30.41                    | 47.33         | -16.92     | AVG      |
| 6   |     | 0.5299       | 34.16                    | 10.40                   | 44.56                    | 56.00         | -11.44     | QP       |
| 7   | *   | 0.5420       | 25.59                    | 10.39                   | 35.98                    | 46.00         | -10.02     | AVG      |
| 8   |     | 0.9060       | 13.69                    | 10.35                   | 24.04                    | 46.00         | -21.96     | AVG      |
| 9   |     | 2.1740       | 22.45                    | 10.29                   | 32.74                    | 56.00         | -23.26     | QP       |
| 10  |     | 2.2020       | 15.23                    | 10.29                   | 25.52                    | 46.00         | -20.48     | AVG      |
| 11  |     | 4.0420       | 18.38                    | 10.25                   | 28.63                    | 56.00         | -27.37     | QP       |
| 12  |     | 13.7180      | 18.12                    | 10.16                   | 28.28                    | 60.00         | -31.72     | QP       |

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.



### Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.1539       | 35.58                    | 10.44                   | 46.02                    | 65.78         | -19.76     | QP       |
| 2   |     | 0.1580       | 19.81                    | 10.44                   | 30.25                    | 55.56         | -25.31     | AVG      |
| 3   |     | 0.2500       | 15.98                    | 10.43                   | 26.41                    | 51.75         | -25.34     | AVG      |
| 4   | *   | 0.5299       | 23.61                    | 10.40                   | 34.01                    | 46.00         | -11.99     | AVG      |
| 5   |     | 0.5380       | 32.64                    | 10.40                   | 43.04                    | 56.00         | -12.96     | QP       |
| 6   |     | 1.1500       | 11.78                    | 10.33                   | 22.11                    | 46.00         | -23.89     | AVG      |
| 7   |     | 1.4060       | 21.51                    | 10.32                   | 31.83                    | 56.00         | -24.17     | QP       |
| 8   |     | 1.9300       | 14.22                    | 10.29                   | 24.51                    | 46.00         | -21.49     | AVG      |
| 9   |     | 2.2100       | 22.00                    | 10.29                   | 32.29                    | 56.00         | -23.71     | QP       |
| 10  |     | 5.6540       | 18.02                    | 10.22                   | 28.24                    | 60.00         | -31.76     | QP       |
| 11  |     | 14.5300      | 10.57                    | 10.15                   | 20.72                    | 50.00         | -29.28     | AVG      |
| 12  |     | 14.6180      | 17.68                    | 10.15                   | 27.83                    | 60.00         | -32.17     | QP       |

#### Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.





### 6.2.3. Maximum Conducted (Average) Output Power

### 6.2.4. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Test Method:</b>      | KDB 558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Limit:</b>            | 30dBm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Test Setup:</b>       |  <p style="text-align: center;">Spectrum Analyzer                      EUT</p>                                                                                                                                                                                                                                                                                                                                             |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Measure the conducted output power and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |



## 6.2.5. Test Data

## 802.11b mode

| Test channel | Maximum Conducted Output Power (dBm) | Limit (dBm) | Result |
|--------------|--------------------------------------|-------------|--------|
| Lowest       | 15.63                                | 30.00       | PASS   |
| Middle       | 16.64                                | 30.00       | PASS   |
| Highest      | 16.53                                | 30.00       | PASS   |

## 802.11g mode

| Test channel | Maximum Conducted Output Power (dBm) | Limit (dBm) | Result |
|--------------|--------------------------------------|-------------|--------|
| Lowest       | 15.59                                | 30.00       | PASS   |
| Middle       | 16.37                                | 30.00       | PASS   |
| Highest      | 16.50                                | 30.00       | PASS   |

## 802.11n(H20) mode


| Test channel | Maximum Conducted Output Power (dBm) | Limit (dBm) | Result |
|--------------|--------------------------------------|-------------|--------|
| Lowest       | 13.45                                | 30.00       | PASS   |
| Middle       | 14.58                                | 30.00       | PASS   |
| Highest      | 14.29                                | 30.00       | PASS   |




Report No.: FCC18010018A-WiFi

**Test plots as follows:  
802.11b Modulation**

**Lowest channel**




**Middle channel**





Report No.: FCC18010018A-WiFi

### Highest channel







Report No.: FCC18010018A-WiFi

## 802.11g Modulation

### Lowest channel



### Middle channel






For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

Report No.: FCC18010018A-WiFi

## Highest channel



世标检测认证股份  
World Standardization Certification & Testing Group Co.,Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com




Report No.: FCC18010018A-WiFi

## 802.11n (HT20) Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi


### Highest channel





## 6.3. Emission Bandwidth

### 6.3.1. Test Specification

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Method:      | KDB 558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Limit:            | >500kHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Test Setup:       | <br>Spectrum Analyzer                      EUT                                                                                                                                                                                                                                                                                                                                                                                                |
| Test Mode:        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement The 6dB bandwidth must be greater than 500 kHz.</li> <li>4. Measure and record the results in the test report.</li> </ol> |
| Test Result:      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |



Report No.: FCC18010018A-WiFi

### 6.3.2. Test data

| Test channel | 6dB Emission Bandwidth (MHz) |         |              |
|--------------|------------------------------|---------|--------------|
|              | 802.11b                      | 802.11g | 802.11n(H20) |
| Lowest       | 9.615                        | 16.533  | 17.436       |
| Middle       | 9.437                        | 15.962  | 17.179       |
| Highest      | 9.167                        | 15.641  | 16.859       |
| Limit:       | >500k                        |         |              |
| Test Result: | PASS                         |         |              |

Test plots as follows:







Report No.: FCC18010018A-WiFi

## 802.11b Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi

### Highest channel







Report No.: FCC18010018A-WiFi

## 802.11g Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi

### Highest channel







Report No.: FCC18010018A-WiFi

## 802.11n (HT20) Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi


### Highest channel





## 6.4. Power Spectral Density

### 6.4.1. Test Specification

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (e)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Method:</b>      | KDB 558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Limit:</b>            | The average power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Test Setup:</b>       | <br>Spectrum Analyzer                      EUT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows Measurement Procedure 10.3 Method AVGPSPD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}</math>. Video bandwidth VBW <math>\geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>5. Detector = RMS, Sweep time = auto couple.</li> <li>6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.</li> <li>6. Measure and record the results in the test report.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



Report No.: FCC18010018A-WiFi

## 6.4.2. Test data

| Test channel | AVG Power Spectral Density (dBm/3kHz) |         |              |
|--------------|---------------------------------------|---------|--------------|
|              | 802.11b                               | 802.11g | 802.11n(H20) |
| Lowest       | -13.30                                | -12.32  | -13.12       |
| Middle       | -13.29                                | -10.66  | -12.71       |
| Highest      | -13.42                                | -10.69  | -14.87       |
| Limit:       | 8dBm/3kHz                             |         |              |
| Test Result: | PASS                                  |         |              |

Test plots as follows:







Report No.: FCC18010018A-WiFi

## 802.11b Modulation

### Lowest channel



### Middle channel






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Report No.: FCC18010018A-WiFi

### Highest channel



世标检测认证股份  
World Standardization Certification & Testing Group Co.,Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com




Report No.: FCC18010018A-WiFi

## 802.11g Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi


### Highest channel






## 802.11n (HT20) Modulation

### Lowest channel




### Middle channel





Report No.: FCC18010018A-WiFi


### Highest channel





## 6.5. Conducted Band Edge and Spurious Emission Measurement

### 6.5.1. Test Specification



|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Requirement:</b> | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Test Method:</b>      | KDB558074                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Limit:</b>            | In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Test Setup:</b>       | <br>Spectrum Analyzer                      EUT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Test Mode:</b>        | Transmitting mode with modulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Test Procedure:</b>   | <ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).</li> <li>5. Measure and record the results in the test report.</li> <li>6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</li> </ol> |
| <b>Test Result:</b>      | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |



Report No.: FCC18010018A-WiFi


## 6.5.2. Test Data

### 802.11b Modulation






### Spurious Emission (Low channel)




### Spurious Emission (Mid channel)







### Spurious Emission (High channel)






Report No.: FCC18010018A-WiFi

## 802.11g Modulation






### Spurious Emission (Low channel)




### Spurious Emission (Mid channel)







### Spurious Emission (High channel)






Report No.: FCC18010018A-WiFi

## 802.11n (HT20) Modulation






### Spurious Emission (Low channel)




### Spurious Emission (Mid channel)





### Spurious Emission (High channel)







## 6.6. Radiated Spurious Emission Measurement

### 6.6.1. Test Specification

|                              |                                    |                                   |                               |               |
|------------------------------|------------------------------------|-----------------------------------|-------------------------------|---------------|
| <b>Test Requirement:</b>     | FCC Part15 C Section 15.209        |                                   |                               |               |
| <b>Test Method:</b>          | ANSI C63.10: 2013                  |                                   |                               |               |
| <b>Frequency Range:</b>      | 9 kHz to 25 GHz                    |                                   |                               |               |
| <b>Measurement Distance:</b> | 3 m                                |                                   |                               |               |
| <b>Antenna Polarization:</b> | Horizontal & Vertical              |                                   |                               |               |
| <b>Operation mode:</b>       | Transmitting mode with modulation  |                                   |                               |               |
| <b>Receiver Setup:</b>       | Frequency                          | Detector                          | RBW                           | VBW           |
|                              | 9kHz- 150kHz                       | Quasi-peak                        | 200Hz                         | 1kHz          |
|                              | 150kHz- 30MHz                      | Quasi-peak                        | 9kHz                          | 30kHz         |
|                              | 30MHz-1GHz                         | Quasi-peak                        | 100KHz                        | 300KHz        |
|                              | Above 1GHz                         | Peak                              | 1MHz                          | 3MHz          |
| <b>Limit:</b>                |                                    | Peak                              | 1MHz                          | 10Hz          |
|                              |                                    |                                   |                               | Average Value |
|                              | Frequency                          | Field Strength (microvolts/meter) | Measurement Distance (meters) |               |
|                              | 0.009-0.490                        | 2400/F(KHz)                       | 300                           |               |
|                              | 0.490-1.705                        | 24000/F(KHz)                      | 30                            |               |
| <b>Test setup:</b>           | 1.705-30                           | 30                                | 30                            |               |
|                              | 30-88                              | 100                               | 3                             |               |
|                              | 88-216                             | 150                               | 3                             |               |
|                              | 216-960                            | 200                               | 3                             |               |
|                              | Above 960                          | 500                               | 3                             |               |
|                              | Frequency                          | Field Strength (microvolts/meter) | Measurement Distance (meters) | Detector      |
|                              | Above 1GHz                         | 500                               | 3                             | Average       |
|                              |                                    | 5000                              | 3                             | Peak          |
|                              | For radiated emissions below 30MHz |                                   |                               |               |
|                              |                                    |                                   |                               |               |
|                              | 30MHz to 1GHz                      |                                   |                               |               |
|                              |                                    |                                   |                               |               |
|                              |                                    |                                   |                               |               |
|                              |                                    |                                   |                               |               |
|                              |                                    |                                   |                               |               |



Above 1GHz



### Test Procedure:

1. For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for




|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | <p>receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>5. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</p> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p> |
| Test results: | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |



## 6.6.2. Test Data

 Please refer to following diagram for individual  
 Below 1GHz

Horizontal:




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|
| 1   | !   | 30.8535      | 30.53                    | 4.47                    | 35.00                      | 40.00           | -5.00      | QP       |
| 2   |     | 46.6664      | 35.94                    | -3.03                   | 32.91                      | 40.00           | -7.09      | QP       |
| 3   |     | 112.1304     | 33.43                    | -2.07                   | 31.36                      | 43.50           | -12.14     | QP       |
| 4   |     | 185.1379     | 43.53                    | -7.11                   | 36.42                      | 43.50           | -7.08      | QP       |
| 5   |     | 550.9479     | 36.66                    | 0.22                    | 36.88                      | 46.00           | -9.12      | QP       |
| 6   | *   | 851.0353     | 37.76                    | 4.75                    | 42.51                      | 46.00           | -3.49      | QP       |



For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Report No.: FCC18010018A-WiFi

Vertical:



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over  |          |
|-----|-----|----------|---------------|----------------|-------------|--------|-------|----------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB    | Detector |
| 1   | *   | 64.4330  | 43.44         | -6.56          | 36.88       | 40.00  | -3.12 | QP       |
| 2   | !   | 110.9570 | 40.58         | -1.96          | 38.62       | 43.50  | -4.88 | QP       |
| 3   | !   | 183.2005 | 46.43         | -7.08          | 39.35       | 43.50  | -4.15 | QP       |
| 4   |     | 274.1938 | 43.36         | -3.49          | 39.87       | 46.00  | -6.13 | QP       |
| 5   | !   | 356.6757 | 42.23         | -1.50          | 40.73       | 46.00  | -5.27 | QP       |
| 6   | !   | 714.1734 | 37.96         | 2.48           | 40.44       | 46.00  | -5.56 | QP       |



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com



## Above 1GHz

## 802.11b Modulation

| Freq.<br>(MHz) | Low channel: 2412MHz |                      |       |                  |    |          |        |
|----------------|----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol              | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                  | PK                   | AV    | PK               | AV | PK       | AV     |
| 4824           | V                    | 59.91                | 39.48 | 74               | 54 | -14.09   | -14.52 |
| 7236           | V                    | 58.28                | 39.86 | 74               | 54 | -15.72   | -14.14 |
| 4824           | H                    | 58.44                | 39.39 | 74               | 54 | -15.56   | -14.61 |
| 7236           | H                    | 59.32                | 40.32 | 74               | 54 | -14.68   | -13.68 |

| Freq.<br>(MHz) | Middle channel: 2437MHz |                      |       |                  |    |          |        |
|----------------|-------------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol                 | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                     | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874           | V                       | 59.33                | 39.68 | 74               | 54 | -14.67   | -14.32 |
| 7311           | V                       | 59.88                | 40.75 | 74               | 54 | -14.12   | -13.25 |
| 4874           | H                       | 59.95                | 39.56 | 74               | 54 | -14.05   | -14.44 |
| 7311           | H                       | 58.10                | 39.10 | 74               | 54 | -15.90   | -14.90 |

| Freq.<br>(MHz) | High channel: 2462MHz |                      |       |                  |    |          |        |
|----------------|-----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol               | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                   | PK                   | AV    | PK               | AV | PK       | AV     |
| 4924           | V                     | 59.32                | 41.85 | 74               | 54 | -14.68   | -12.15 |
| 7386           | V                     | 58.10                | 39.05 | 74               | 54 | -15.90   | -14.95 |
| 4924           | H                     | 59.36                | 40.86 | 74               | 54 | -14.64   | -13.14 |
| 7386           | H                     | 58.69                | 39.69 | 74               | 54 | -15.31   | -14.31 |



Report No.: FCC18010018A-WiFi

**802.11g Modulation**

| Freq.<br>(MHz) | Low channel: 2412MHz |                      |       |                  |    |          |        |
|----------------|----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol              | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                  | PK                   | AV    | PK               | AV | PK       | AV     |
| 4824           | V                    | 58.52                | 40.19 | 74               | 54 | -15.48   | -13.81 |
| 7236           | V                    | 59.45                | 39.19 | 74               | 54 | -14.55   | -14.81 |
| 4824           | H                    | 59.78                | 39.85 | 74               | 54 | -14.22   | -14.15 |
| 7236           | H                    | 58.32                | 39.32 | 74               | 54 | -15.68   | -14.68 |

| Freq.<br>(MHz) | Middle channel: 2437MHz |                      |       |                  |    |          |        |
|----------------|-------------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol                 | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                     | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874           | V                       | 59.77                | 41.58 | 74               | 54 | -14.23   | -12.42 |
| 7311           | V                       | 58.99                | 40.36 | 74               | 54 | -15.01   | -13.64 |
| 4874           | H                       | 58.62                | 40.92 | 74               | 54 | -15.38   | -13.08 |
| 7311           | H                       | 58.51                | 39.51 | 74               | 54 | -15.49   | -14.49 |

| Freq.<br>(MHz) | High channel: 2462MHz |                      |       |                  |    |          |        |
|----------------|-----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol               | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                   | PK                   | AV    | PK               | AV | PK       | AV     |
| 4924           | V                     | 59.85                | 40.58 | 74               | 54 | -14.15   | -13.42 |
| 7386           | V                     | 58.83                | 39.61 | 74               | 54 | -15.17   | -14.39 |
| 4924           | H                     | 58.03                | 39.02 | 74               | 54 | -15.97   | -14.98 |
| 7386           | H                     | 58.70                | 39.70 | 74               | 54 | -15.30   | -14.30 |





## 802.11n (HT20) Modulation

| Freq.<br>(MHz) | Low channel: 2412MHz |                      |       |                  |    |          |        |
|----------------|----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol              | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                  | PK                   | AV    | PK               | AV | PK       | AV     |
| 4824           | V                    | 58.72                | 39.22 | 74               | 54 | -15.28   | -14.78 |
| 7236           | V                    | 59.34                | 40.78 | 74               | 54 | -14.66   | -13.22 |
| 4824           | H                    | 59.28                | 40.30 | 74               | 54 | -14.72   | -13.70 |
| 7236           | H                    | 59.48                | 40.48 | 74               | 54 | -14.52   | -13.52 |

| Freq.<br>(MHz) | Middle channel: 2437MHz |                      |       |                  |    |          |        |
|----------------|-------------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol                 | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                     | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874           | V                       | 58.26                | 39.10 | 74               | 54 | -15.74   | -14.90 |
| 7311           | V                       | 58.54                | 39.95 | 74               | 54 | -15.46   | -14.05 |
| 4874           | H                       | 59.29                | 40.99 | 74               | 54 | -14.71   | -13.01 |
| 7311           | H                       | 58.67                | 39.67 | 74               | 54 | -15.33   | -14.33 |

| Freq.<br>(MHz) | High channel: 2462MHz |                      |       |                  |    |          |        |
|----------------|-----------------------|----------------------|-------|------------------|----|----------|--------|
|                | Ant.Pol               | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|                | H/V                   | PK                   | AV    | PK               | AV | PK       | AV     |
| 4924           | V                     | 59.67                | 40.88 | 74               | 54 | -14.33   | -13.12 |
| 7386           | V                     | 59.37                | 40.11 | 74               | 54 | -14.63   | -13.89 |
| 4924           | H                     | 58.95                | 40.59 | 74               | 54 | -15.05   | -13.41 |
| 7386           | H                     | 58.75                | 39.75 | 74               | 54 | -15.25   | -14.25 |

## Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level+Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



Report No.: FCC18010018A-WiFi


**Restricted Bands Requirements**


Test result for 802.11b Mode (the worst case)

| Frequency    | Reading  | Correct Factor | Emission Level | Limit    | Margin | Polar | Detector |
|--------------|----------|----------------|----------------|----------|--------|-------|----------|
| (MHz)        | (dBuV/m) | dB/m           | (dBuV/m)       | (dBuV/m) | (dB)   | H/V   |          |
| Low Channel  |          |                |                |          |        |       |          |
| 2390         | 66.47    | -8.73          | 57.74          | 74       | -16.26 | H     | PK       |
| 2390         | 51.38    | -8.73          | 42.65          | 54       | -11.35 | H     | AV       |
| 2390         | 65.12    | -8.73          | 56.39          | 74       | -17.61 | V     | PK       |
| 2390         | 49.68    | -8.73          | 40.95          | 54       | -13.05 | V     | AV       |
| High Channel |          |                |                |          |        |       |          |
| 2483.5       | 65.02    | -8.17          | 56.85          | 74       | -17.15 | H     | PK       |
| 2483.5       | 46.43    | -8.17          | 38.26          | 54       | -15.74 | H     | AV       |
| 2483.5       | 66.73    | -8.17          | 58.56          | 74       | -15.44 | V     | PK       |
| 2483.5       | 46.77    | -8.17          | 38.60          | 54       | -15.40 | V     | AV       |



## 7. Appendix A: Photographs of Test Setup







## 8. Appendix B: Photographs of EUT

Appearance photograph of EUT




Appearance photograph of EUT





Appearance photograph of EUT



Appearance photograph of EUT






Appearance photograph of EUT



Appearance photograph of EUT






Appearance photograph of EUT




Internal photograph of EUT






Internal photograph of EUT




Internal photograph of EUT





Report No.: FCC18010018A-WiFi

Internal photograph of EUT



Internal photograph of EUT






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Report No.: FCC18010018A-WiFi

Internal photograph of EUT



Internal photograph of EUT



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com


Member of the WSCT INC.




For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Report No.: FCC18010018A-WiFi

Internal photograph of EUT




Internal photograph of EUT





Internal photograph of EUT



\*\*\*\*\*END OF REPORT\*\*\*\*\*