




Test Report No.:
FCCSZ2024-0007-H

RF Test Report

FCC ID : 2AOKI-AL7663BWGA
EUT : WIFI Module
MODEL : See Section 1
BRAND NAME : N/A
APPLICANT : Sichuan AI-Link Technology Co.,Ltd.
Classification of Test : N/A

CVC Testing Technology (Shenzhen) Co., Ltd.



Client		Name: Sichuan AI-Link Technology Co.,Ltd. Address:Anzhou Industrial Park, Mianyang, Sichuan, P.R.C	
Manufacturer		Name: Sichuan AI-Link Technology Co.,Ltd. Address:Anzhou Industrial Park, Mianyang, Sichuan, P.R.C	
Equipment Under Test		Product Name:WIFI Module Model/Type: See Section 1 Brand Name: N/A Serial NO.: N/A Sample NO.:3-1	
Date of Receipt.	2024.02.21	Date of Testing	2024.02.21~2024.03.20
Test Specification		Test Result	
FCC Part 2 (Section 2.1091) KDB 447498 D04, IEEE C95.3		PASS	
Evaluation of Test Result	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2024.03.20		
Tested by:  <u>Cai Jianyu</u> Name Signature	Reviewed by:  <u>Mo Xianbiao</u> Name Signature	Approved by:  <u>Dong Sanbi</u> Name Signature	
Other Aspects: NONE.			
Abbreviations:OK, Pass= passed Fail = failed N/A= not applicable EUT= equipment, sample(s) under tested			

This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1. GENERAL PRODUCT INFORMATION	5
2. RF EXPOSURE LIMIT	6
3. CLASSIFICATION	7
4. CALCULATION RESULT OF MAXIMUM CONDUCTED PEAK POWER	7



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCCSZ2024-0007-H	Original release	2024.03.20



1. GENERAL PRODUCT INFORMATION

PRODUCT	WIFI Module
BRAND	N/A
MODEL	AL-7663B-WG-A
ADDITIONAL MODEL	AL-7663B-WG-A(FCC); AL-7663B-WG-A-1(FCC); AL-7663B-WG-A-2(FCC); AL-7663B-WG-A-3(FCC); AL-7663B-WG-A-4(FCC); AL-7663B-WG-A-5(FCC);
POWER SUPPLY	DC 5V
STANDARDS	FCC Part 2 (Section 2.1091) KDB 447498 D04, IEEE C95.3
Remark: - For more detailed features description, please refer to the manufacturer's specifications or the User's Manual. - For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report. - EUT photo refer to the report (Report NO.: FCCSZ2024-0007-EUT).	



2. RF EXPOSURE LIMIT

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda / 2 \pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda / 4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF SOURCE FREQUENCY (MHZ)	THRESHOLD ERP(W)
0.3 -1.34	$1,920 R^2$
1.34 - 30	$3,450 R^2 F^2$
30 -300	$3.83 R^2$
300-1500	$0.0128 R^2 F$
1500-100,000	$19.2 R^2$



3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

4. CALCULATION RESULT OF MAXIMUM CONDUCTED PEAK POWER

The measured conducted Peak Power

Mode	Antenna	Power (dBm)
BT-EDR	ANT3	13
BT-LE	ANT3	-2
2.4G WIFI	ANT1	16.22
	ANT2	15.87
5.1G WIFI	ANT1	17.02
	ANT2	17.37
5.3G WIFI	ANT1	17.83
	ANT2	17.33
5.6G WIFI	ANT1	15
	ANT2	16.24
5.8G WIFI	ANT1	16.65
	ANT2	16.46



MAXIMUM PERMISSIBLE EXPOSURE (FCC)

Mode	Frequency (MHz)	Antenna	Max Power (dBm)	Antenna Gain (dBi)	R (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	Threshold ERP(W)	Ratio
BT-EDR	2402-2480	ANT1	13	4.32	20	17.32	15.17	0.033	0.77	0.043
BT-LE	2402-2480	ANT1	-2	4.32	20	2.32	0.17	0.001	0.77	0.001
2.4G WIFI	2412-2472	ANT1	16.22	1.99	20	18.21	16.06	0.040	0.77	0.052
		ANT2	15.87	1.94	20	17.81	15.66	0.037	0.77	0.048
5.1G WIFI	5180-5240	ANT1	17.02	1.96	20	18.98	16.83	0.048	0.77	0.063
		ANT2	17.37	1.96	20	19.33	17.18	0.052	0.77	0.068
5.3G WIFI	5260-5320	ANT1	17.83	1.96	20	19.79	17.64	0.058	0.77	0.075
		ANT2	17.33	1.96	20	19.29	17.14	0.052	0.77	0.067
5.6G WIFI	5500-5720	ANT1	15	1.96	20	16.96	14.81	0.030	0.77	0.039
		ANT2	16.24	1.96	20	18.2	16.05	0.040	0.77	0.052
5.8G WIFI	5745-5825	ANT1	16.65	1.96	20	18.61	16.46	0.044	0.77	0.057
		ANT2	16.46	1.96	20	18.42	16.27	0.042	0.77	0.055
Sum of ratio = BT-EDR + WIFI ANT1+ WIFI ANT2										0.186

Note1: This device can operate simultaneously in BT and WIFI.

Note2: ERP=EIRP-2.15dB

Conclusion:

Therefore, the worst-case situation is 0.186(Sum of Ratios), which is less than "1". This confirmed that the device compliance with FCC RF exposure requirements..

----- End of the Report -----



Important

- (1) The test report is invalid without the official stamp of CVC;
- (2) Any part photocopies of the test report are forbidden without the written permission from CVC;
- (3) The test report is invalid without the signatures of Approval and Reviewer;
- (4) The test report is invalid if altered;
- (5) Objections to the test report must be submitted to CVC within 15 days.
- (6) Generally, commission test is responsible for the tested samples only.
- (7) As for the test result “-” or “N” means “not applicable”, “/” means “not test”, “P” means “pass” and “F” means “fail”

The test data and test results given in this test report should only be used for purposes of scientific research, teaching and internal quality control when the CMA symbol is not presented.

Address: No. 1301, Guanguang Road, Xinlan Community, Guanlan Street,
Longhua District, Shenzhen, Guangdong, 518110, P. R. China

Post Code: 518110 Tel: 0755-23763060-8805

Fax: 0755-23763060 E-mail: sz-kf@cvc.org.cn

<http://www.cvc.org.cn>