

TEST REPORT

Applicant: Sichuan AI-Link Technology Co.,Ltd.
EUT Description: WiFi Module
Model Tested: AL-7663B-WG-XM
Brand: AI-LINK
FCC ID: 2AOKI-AL7663BXM
Standards: FCC 47 CFR Part 15 Subpart C
Date of Receipt: 2026/06/16
Date of Test: 2026/06/16 to 2026/07/16
Date of Issue: 2026/07/16

TOWE tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. Without written approval of TOWE, the test report shall not be reproduced except in full.



Jim Huang
Approved By:



Carey Chen
Reviewed By:

Revision History

Rev.	Issue Date	Description	Revised by
01	2026/07/16	Original	Carey Chen

Summary of Test Results

Clause	FCC Part	Test Items	Result
4.1	§15.203/15.247(b)	Antenna Requirement	PASS
4.2	§15.207	AC Power Line Conducted Emission	Reference report TSWA26010003403
4.3	§15.247 (b)(3)	Output Power	
4.4	§15.247 (a)(2)	Occupied Bandwidth	
4.5	§15.247 (e)	Power Spectral Density	PASS*
4.6	§15.247(d)	Band Edge for Conducted Emissions	Reference report TSWA26010003403
4.7	§15.247(d)	Spurious RF Conducted Emissions	
4.8	§15.205/15.209	Radiated Spurious emissions and Band Edge	PASS
Test Method: ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, KDB 558074 D01 15.247 Mesa Guidance v05r02. Remark: Pass is EUT meets standard requirements. PASS*: The Power Spectral Density data refer to the previous report. Due to the modification of antenna gain, the PSD Limit has also been updated.			

Remark:

In this report the worst data of Radiated Spurious emissions and Band Edge were spot checked, and the other data please refer to the previous report with report number TSWA26010003403.

Table of Contents

1	General Description	5
1.1	Lab Information.....	5
1.1.1	Testing Location	5
1.1.2	Test Facility / Accreditations	5
1.2	Client Information	5
1.2.1	Applicant.....	5
1.2.2	Manufacturer.....	5
1.3	Product Information.....	6
2	Test Configuration	7
2.1	Test Channel	7
2.2	Worst-case configuration and Mode	7
2.3	Support Unit used in test	8
2.4	Test Environment.....	8
2.5	Test RF Cable	8
2.6	Modifications.....	8
2.7	Test Setup Diagram	9
2.7.1	Conducted Configuration	9
2.7.2	Radiated Configuration	10
3	Equipment and Measurement Uncertainty.....	12
3.1	Test Equipment List.....	12
3.2	Measurement Uncertainty	12
4	Test Results.....	13
4.1	Antenna Requirement.....	13
4.2	Power Spectral Density	14
4.3	Radiated Spurious Emissions and Band Edge	15
5	Test Setup Photos.....	17
	Appendix.....	18

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurement tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014

Tel.: +86-755-27212361

Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory.

Test Firm Registration Number: 684095

Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	Sichuan AI-Link Technology Co.,Ltd.
Address:	Anzhou Industrial Park, Mianyang, Sichuan, P.R.C

1.2.2 Manufacturer

Manufacturer:	Sichuan AI-Link Technology Co.,Ltd.
Address:	Anzhou Industrial Park, Mianyang, Sichuan, P.R.C

1.3 Product Information

EUT Description:	WiFi Module		
Model Tested:	AL-7663B-WG-XM		
Model Covered:	AL-7663B-WG-XM-1; AL-7663B-WG-XM-2; AL-7663B-WG-XM-3; AL-7663B-WG-XM-4; AL-7663B-WG-XM-5; AL-7663B-WG-XM-6; AL-7663B-WG-XM-7; AL-7663B-WG-XM-8; AL-7663B-WG-XM-9; AL-7663B-WG-XM1; AL-7663B-WG-XM1-1; AL-7663B-WG-XM1-2; AL-7663B-WG-XM1-3; AL-7663B-WG-XM1-4; AL-7663B-WG-XM1-5; AL-7663B-WG-XM1-6; AL-7663B-WG-XM1-7; AL-7663B-WG-XM1-8; AL-7663B-WG-XM1-9;		
Brand:	AI-LINK		
Hardware Version:	V1.0		
Software Version:	V.0.0.2.5		
Modulation Type:	802.11b:	DSSS-DBPSK, DQPSK, CCK	
	802.11g/n:	OFDM-BPSK, QPSK, 16QAM, 64QAM	
Smart System:	☐ SISO	802.11b/g/n	/
	☒ MIMO	802.11n	(2)TX(2)RX
	☒ CDD	802.11b/g	(2)TX(2)RX
Frequency Range:	2400 ~ 2483.5MHz		
Channel Frequency:	20M bandwidth Channel: 2412 ~ 2462MHz 40M bandwidth Channel: 2422 ~ 2452MHz		
Channel Number:	11:	802.11b/g/n20	
	7:	802.11n40	
Antenna Type:	☒ External		
Antenna Gain:	Ant1, Ant2 (dBi)		
	3.93		
Remark: 1. The above EUT's information was declared by applicant, please refer to the specifications or user's manual for more detailed description. 2. Please refer to the “Model Declaration Letter” provided by the client for specific model differences.			

2 Test Configuration

2.1 Test Channel

Frequency Channels							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	
Remark: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:							
Modulation Type		Test Channel		Test Frequency			
802.11b/g/n20		The Lowest channel (CH1)		2412MHz			
		The Middle channel (CH6)		2437MHz			
		The Highest channel (CH11)		2462MHz			
Modulation Type		Test Channel		Test Frequency			
802.11n40		The Lowest channel (CH3)		2422MHz			
		The Middle channel (CH6)		2437MHz			
		The Highest channel (CH9)		2452MHz			

2.2 Worst-case configuration and Mode

Modulation Type	SISO - Data Rate	CDD/MIMO(2)TX(2)RX Data Rate
802.11b	N/A	2 Mbps
802.11g	N/A	12 Mbps
802.11n20	N/A	MCS0 (13 Mbps)
802.11n40	N/A	MCS0 (27 Mbps)
Transmitting mode:	Keep the EUT was programmed to be in continuously transmitting mode.	
Normal Link:	Keep the EUT operation to normal function.	

2.3 Support Unit used in test

Description	Manufacturer	Model	Serial Number
Laptop	Lenovo	Thinkbook 14 G4+IAP	YX05AZ13

2.4 Test Environment

Temperature:	Normal: 15°C ~ 35°C
Humidity:	45 ~ 56 % RH Ambient
Voltage:	DC 3.3V
Remark: The testing environment is within the scope of the EUT user manual and meets the requirements of the standard testing environment.	

2.5 Test RF Cable

For all conducted test items: The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.


Offset = RF cable loss + attenuator factor.

2.6 Modifications


No modifications were made during testing.

2.7 Test Setup Diagram

2.7.1 Conducted Configuration



2.7.2 Radiated Configuration



Directional gain calculations:

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

If all antennas have the same gain, G_{ANT} , Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices

$$\text{Array Gain} = 10 \log(N_{ANT}/N_{SS}=1) \text{ dB}$$

- For power measurements on IEEE 802.11 devices:

$$\text{Array Gain} = 0 \text{ dB (i.e., no array gain) for } N_{ANT} \leq 4;$$

$$\text{Array Gain} = 0 \text{ dB (i.e., no array gain) for channel widths } \geq 40 \text{ MHz for any } N_{ANT};$$

$$\text{Array Gain} = 5 \log(N_{ANT}/N_{SS}=1) \text{ dB or } 3 \text{ dB, whichever is less, for 20-MHz channel widths with } N_{ANT} \geq 5.$$

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain.

Unequal antenna gains, with equal transmit powers. For antenna gains given by $G_1, G_2, \dots, G_N$ dBi

- If transmit signals are correlated, then

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]}$$

- If all transmit signals are completely uncorrelated, then

$$\text{Directional gain} = 10 \log[(10^{G_1/10} + 10^{G_2/10} + \dots + 10^{G_N/10}) / N_{ANT}] \text{ dBi}$$

The Power and PSD limit should be modified if the directional gain of EUT is over 6dBi.

The EUT supports CDD System.

Unequal antenna gain:

Transmit signals are completely correlated					
ANT Gain1 (dBi)	ANT Gain2 (dBi)	Directional gain For Power (dBi)	Directional gain For PSD (dBi)	Power Limit Reduction (dBm)	PSD Limit Reduction (dBm)
3.93	3.93	3.93	6.94	0	0.94

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) = 0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain > 6dBi) = 6.94 – 6 = 0.94

3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable to recognized national standards.

3.1 Test Equipment List

Radiated Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
Double-Ridged Horn Antennas	Tonscend	HA32-18	806HA003608251015	2025/12/13	2028/12/12
Biconic Logarithmic Periodic Antennas	Tonscend	BLA32-30	80SBLA001011251010	2025/12/13	2028/12/12
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	1290	2023/06/25	2026/06/24
				2026/06/18	2029/06/17
Loop Antenna	Schwarzbeck	FMZB 1519C	1519C-028	2026/06/13	2029/06/12
Signal Analyzer	Keysight	N9020A	MY57120015	2026/01/19	2028/01/18
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2026/05/29	2027/05/28
EMI Tester Receiver	Rohde & Schwarz	ESR7	102719	2026/05/28	2027/05/27
Low Noise Amplifier	Tonscend	TAP9K3G40	806JSAP044710251054	2026/01/19	2028/01/18
Low Noise Amplifier	Tonscend	TAP01018050	806JSAF044509251052	2026/01/19	2028/01/18
Low Noise Amplifier	Tonscend	TAP18040048	AP22G806247	2025/03/11	2027/03/10
Hygrometer	BINGYU	HTC-1	N/A	2025/07/25	2026/07/24
Radio Frequency Switch	Townshend	JS0806s	806JSSX019811251028	N/A	N/A
Test Software	Tonscend	TS+	Version: 5.0.0	N/A	N/A

3.2 Measurement Uncertainty

Parameter	U _{lab}
Radiated Emissions(9kHz~30MHz)	2.40dB
Radiated Emissions(30MHz~1000MHz)	4.66dB
Radiated Emissions(1GHz~18GHz)	5.42dB
Radiated Emissions(18GHz~40GHz)	5.46dB

Uncertainty figures are valid to a confidence level of 95%

4 Test Results

4.1 Antenna Requirement

Standard Applicable:	47 CFR Part 15C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
The antenna gain and type as provided by the manufacturer are as follows: The antenna Type is External. With Antenna gain is 3.93dBi (Ant1&Ant2); Antenna Anti-Replacement Construction: An embedded-in antenna design is used.	

4.2 Power Spectral Density

Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 11.10.2(PKPSD)

Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously
2. The transmitter output is connected to a spectrum analyzer
3. $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$
(If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.)
4. $\text{VBW} \geq 3$ times the RBW
5. Span = 1.5 times the DTS bandwidth
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report.

Test Setup

Refer to section 2.7.1 Setup 2 for details.

Test Result

The detailed test data see: **Appendix**.

Remark: The Power Spectral Density data refer to the previous report. Due to the modification of antenna gain, the PSD Limit has also been updated.

4.3 Radiated Spurious Emissions and Band Edge

Limits

Spurious emissions are permitted in an of the frequency bands:

MHz	MHz	MHz	MHz	GHz	GHz
0.090 - 0.110	12.29 - 12.293	149.9 - 150.05	1660 - 1710	4.5 - 5.15	14.47 - 14.5
0.495 - 0.505	12.51975 - 12.52025	156.52475 - 156.52525	1718.8 - 1722.2	5.35 - 5.46	15.35 - 16.2
2.1735 - 2.1905	12.5767 - 12.57725	156.7 - 156.9	2200 - 2300	7.25 - 7.75	17.7 - 21.4
4.125 - 128	13.36 - 13.41	162.0125 - 167.17	2310 - 2390	8.025 - 8.5	22.01 - 23.12
4.17725 - 4.17775	16.42 - 16.423	167.72 - 173.2	2483.5 - 2500	9.0 - 9.2	23.6 - 24.0
4.20725 - 4.20775	16.69475 - 16.69525	240 - 285	2655 - 2900	9.3 - 9.5	31.2 - 31.8
6.215 - 6.218	1680425 - 1680475	322 - 335.4	3260 - 3267	10.6 - 12.7	36.43 - 36.5
6.26775 - 6.26825	25.5 - 25.67	399.9 - 410	3332 - 3339	13.25 - 13.4	
6.31175 - 6.31225	37.5 - 38.25	608 - 614	3345.8 - 3358		
8.291 - 8.294	73 - 74.6	960 - 1240	3600 - 4400		
8.362 - 8.366	74.8 - 75.2	1300 - 1427			
8.37625 - 8.38675	108 - 121.94	1435 - 1626.5			
8.41425 - 8.41475	123 - 138	1645.5 - 1646.5			

Radiated disturbance of an intentional radiator:

Frequency	Field strength (μV/m)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	74.0	Peak	3
		54.0	Average	

Test Procedure

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 Section 6.4 & 6.5 & 6.6 & 11.11&11.12

Test Settings

- For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
- For radiated emissions measurements performed at frequencies above 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 150cm above the ground plane.
- Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.
- For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
- Set to the maximum power setting and enable the EUT transmit continuously.
- The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
- spectrum analyzer setting:
Measurements 30MHz ~ 1000MHz: RBW = 120 kHz; VBW ≥ 300 kHz; Detector = Peak

Measurements Above 1000MHz: RBW = 1 MHz; VBW $\geq$ 3 MHz; Detector = Peak

Average Measurements Above 1000MHz:

RBW = 1 MHz; VBW $\geq$ 3 MHz; Detector = RMS; Trace (RMS) averaging was performed over at least 100 traces.

8. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:

Level = Reading(dB μ V) + Factor(dB):

Factor = Cable Factor(dB) + AF(dB/m) - Preamplifier gain(dB)

AF = Antenna Factor(dB/m)

Margin = Limit(dB μ V/m) – Level(dB μ V/m)

9. Repeat above procedures until all frequencies measured was complete.
10. Measure and record the results in the test report.

Test Notes

1. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
2. Radiated spurious emissions were investigated from 9kHz to 30MHz, 30MHz-1GHz and above 1GHz. the disturbance between 9kHz to 30MHz and 18GHz to 40GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be recorded, so only the harmonics had been displayed.
3. These frequencies which near "-" should be ignored because they are Fundamental frequency.

Test Setup

Refer to section 2.7.2 for details.

Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

Test Result

The detailed test data see: **Appendix**.

5 Test Setup Photos

For detailed test setup photos, see **Appendix A - WIFI Setup Photos**

Appendix

Maximum power spectral density Test Result

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11b-CDD	Ant1	2412	-4.11	≤7.06	PASS
11b-CDD	Ant2	2412	-4.28	≤7.06	PASS
11b-CDD	total	2412	-1.18	≤7.06	PASS
11b-CDD	Ant1	2437	-3.92	≤7.06	PASS
11b-CDD	Ant2	2437	-4.54	≤7.06	PASS
11b-CDD	total	2437	-1.21	≤7.06	PASS
11b-CDD	Ant1	2462	-2.37	≤7.06	PASS
11b-CDD	Ant2	2462	-4.44	≤7.06	PASS
11b-CDD	total	2462	-0.27	≤7.06	PASS
11g-CDD	Ant1	2412	-5.70	≤7.06	PASS
11g-CDD	Ant2	2412	-6.04	≤7.06	PASS
11g-CDD	total	2412	-2.86	≤7.06	PASS
11g-CDD	Ant1	2437	-5.61	≤7.06	PASS
11g-CDD	Ant2	2437	-6.10	≤7.06	PASS
11g-CDD	total	2437	-2.84	≤7.06	PASS
11g-CDD	Ant1	2462	-6.65	≤7.06	PASS
11g-CDD	Ant2	2462	-6.67	≤7.06	PASS
11g-CDD	total	2462	-3.65	≤7.06	PASS
11n20MIMO	Ant1	2412	-7.08	≤7.06	PASS
11n20MIMO	Ant2	2412	-7.91	≤7.06	PASS
11n20MIMO	total	2412	-4.46	≤7.06	PASS
11n20MIMO	Ant1	2437	-7.55	≤7.06	PASS
11n20MIMO	Ant2	2437	-7.45	≤7.06	PASS
11n20MIMO	total	2437	-4.49	≤7.06	PASS
11n20MIMO	Ant1	2462	-6.66	≤7.06	PASS
11n20MIMO	Ant2	2462	-7.74	≤7.06	PASS
11n20MIMO	total	2462	-4.16	≤7.06	PASS
11n40MIMO	Ant1	2422	-10.07	≤7.06	PASS
11n40MIMO	Ant2	2422	-10.57	≤7.06	PASS
11n40MIMO	total	2422	-7.30	≤7.06	PASS
11n40MIMO	Ant1	2437	-9.97	≤7.06	PASS
11n40MIMO	Ant2	2437	-9.93	≤7.06	PASS
11n40MIMO	total	2437	-6.94	≤7.06	PASS
11n40MIMO	Ant1	2452	-10.46	≤7.06	PASS
11n40MIMO	Ant2	2452	-9.74	≤7.06	PASS
11n40MIMO	total	2452	-7.07	≤7.06	PASS


Radiated Spurious Emissions

Test for spot check:

Test Result


Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
SN:	-	Engineer:	Tian shuo
Remark:	Powersetting 1F		

Test Graph



Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity	Verdict
1	4924.50	48.28	-6.06	42.22	54.00	11.78	RMS	Horizontal	PASS
2	6566.00	45.67	-2.12	43.55	54.00	10.45	RMS	Horizontal	PASS
3	17960.00	29.89	16.72	46.61	54.00	7.39	RMS	Horizontal	PASS
4	2461.20	101.32	2.44	103.76	-	-	PK	Horizontal	NA
5	4924.00	50.47	-6.06	44.41	74.00	29.59	PK	Horizontal	PASS
6	6565.50	49.20	-2.13	47.07	74.00	26.93	PK	Horizontal	PASS
7	17967.50	37.72	16.82	54.54	74.00	19.46	PK	Horizontal	PASS

Project Information			
Mode:	802.11b	Band:	-
Bandwidth	20MHz	Channel	11
SN:	-	Engineer:	Tian shuo
Remark:	Powersetting 1F		

Test Graph**Data List**

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity	Verdict
1	4924.50	48.10	-6.06	42.04	54.00	11.96	RMS	Vertical	PASS
2	6566.00	44.43	-2.12	42.31	54.00	11.69	RMS	Vertical	PASS
3	17978.00	29.28	16.97	46.25	54.00	7.75	RMS	Vertical	PASS
4	2462.93	103.22	2.47	105.69	-	-	PK	Vertical	NA
5	4924.00	51.36	-6.06	45.30	74.00	28.70	PK	Vertical	PASS
6	6565.00	48.68	-2.13	46.55	74.00	27.45	PK	Vertical	PASS
7	17975.00	37.58	16.93	54.51	74.00	19.49	PK	Vertical	PASS


Radiated Band Edge

Test for spot check:

Test Result


Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	9
SN:	-	Engineer:	Tian shuo
Remark:	Powersetting 1B		

Test Graph



Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity	Verdict
1	2484.42	42.61	2.70	45.31	54.00	8.69	RMS	Horizontal	PASS
2	2487.58	41.56	2.73	44.29	54.00	9.71	RMS	Horizontal	PASS
3	2496.33	40.09	2.83	42.92	54.00	11.08	RMS	Horizontal	PASS
4	2484.18	54.87	2.70	57.57	74.00	16.43	PK	Horizontal	PASS
5	2486.53	54.21	2.72	56.93	74.00	17.07	PK	Horizontal	PASS
6	2496.60	52.31	2.83	55.14	74.00	18.86	PK	Horizontal	PASS

Project Information			
Mode:	802.11n40	Band:	-
Bandwidth	40MHz	Channel	9
SN:	-	Engineer:	Tian shuo
Remark:	Powersetting 1B		

Test Graph

Data List									
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity	Verdict
1	2484.49	44.74	2.70	47.44	54.00	6.56	RMS	Vertical	PASS
2	2488.26	43.22	2.73	45.95	54.00	8.05	RMS	Vertical	PASS
3	2491.80	42.21	2.78	44.99	54.00	9.01	RMS	Vertical	PASS
4	2484.01	56.09	2.69	58.78	74.00	15.22	PK	Vertical	PASS
5	2488.57	56.03	2.73	58.76	74.00	15.24	PK	Vertical	PASS
6	2491.39	55.39	2.77	58.16	74.00	15.84	PK	Vertical	PASS

~The End~