











11AX20SISO-Ant1-6535-Center-6535-OFF-PASS











11AX20SISO-Ant1-6935-Center-6935-OFF-PASS



















11AX80MIMO-Ant1-6625-Low-6591.5088-OFF-PASS



11AX80MIMO-Ant1-6865-Low-6831.5703-OFF-PASS



8.6 RADIATED SPURIOUS EMISSION

8.6.1 Applicable Standard

According to FCC Part 15.407 (b), 15.209, 15.205
 According to 789033 D02 Section II.G
 According to 987594 D02 Section II.G
 According to RSS-GEN 8.9, 8.10 and 6.13
 According to RSS-248 4.7

8.6.2 Conformance Limit

For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an e.i.r.p. of -27 dBm/MHz.
 Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
 The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.6.3 Test Configuration

Test according to clause 7.2 radio frequency test setup

8.6.4 Test Procedure

■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

Set RBW=120kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for $f < 30$ MHz(150KHz to 30MHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2020/Cor 1-2021 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Repeat above procedures until all frequency measured was complete.

■ Unwanted Maximum peak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW ≥ 3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

■ Unwanted Average Emissions Measurements above 1000 MHz

Method AD (Average Detection): Primary method

RBW = 1 MHz.

VBW ≥ 3 MHz.

Detector = power averaging (rms), if $\text{span}/(\# \text{ of points in sweep}) \leq \text{RBW}/2$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, the detector mode shall be set to peak.

Averaging type = power averaging (rms)

Sweep time = auto.

Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, the number of traces shall be increased by a factor of $1/x$, where x is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—rather than turning on and off with the transmit cycle, at least 100 traces shall be averaged.)

If tests are performed with the EUT transmitting at a duty cycle less than 98%, a correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is $10 \log (1/x)$, where x is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB must be added to the measured emission levels.

8.6.5 Test Results

PASS

Temperature :	25℃	ATM Pressure:	1011 mbar
Humidity :	45 %	Test Engineer:	HZB

■ Spurious Emission below 30MHz(9KHz to 30MHz)

For Spurious Emission below 30MHz (9KHz to 30MHz), was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



■ Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 5 Band (5925 ~ 6425MHz)								
Test mode:			802.11AX(20)		Frequency(MHz):		5955	

Suspected Data List								
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4679.83	50.65	-8.02	74.00	23.35	PK	Vertical	100
2	8306.11	58.44	-0.54	74.00	15.56	PK	Vertical	120
3	17453.4	66.90	14.05	74.00	7.10	PK	Vertical	180

AV Final Data List							
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4679.834	34.66	54.00	19.34	AV	Vertical	105
2	8306.115	38.38	54.00	15.62	AV	Vertical	129
3	17453.42	49.99	54.00	4.01	AV	Vertical	170

Suspected Data List								
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4712.13	51.23	-8.06	74.00	22.77	PK	Horizontal	105
2	8327.36	57.75	-0.49	74.00	16.25	PK	Horizontal	129
3	17325.9	66.94	12.77	74.00	7.06	PK	Horizontal	178

AV Final Data List							
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4712.135	34.21	54.00	19.79	AV	Horizontal	105
2	8327.366	38.11	54.00	15.89	AV	Horizontal	150
3	17325.91	48.28	54.00	5.72	AV	Horizontal	170

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6175

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4661.98	50.91	-8.13	74.00	23.09	PK	Vertical	109
2	8298.46	59.12	-0.59	74.00	14.88	PK	Vertical	129
3	17625.1	66.91	14.58	74.00	7.09	PK	Vertical	170

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4661.983	34.21	54.00	19.79	AV	Vertical	105
2	8298.464	38.11	54.00	15.89	AV	Vertical	159
3	17625.13	49.84	54.00	4.16	AV	Vertical	178

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4656.03	51.20	-8.17	74.00	22.80	PK	Horizontal	120
2	8423.42	59.12	-0.69	74.00	14.88	PK	Horizontal	155
3	17905.6	66.82	11.74	74.00	7.18	PK	Horizontal	178

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4656.032	34.73	54.00	19.27	AV	Horizontal	119
2	8423.421	37.54	54.00	16.46	AV	Horizontal	129
3	17905.64	47.20	54.00	6.80	AV	Horizontal	172

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20) Frequency(MHz): 6415

Suspected Data List								Antenna Height (cm)
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	4688.33	51.20	-7.97	74.00	22.80	PK	Vertical	110
2	8363.06	58.28	-0.44	74.00	15.72	PK	Vertical	129
3	16383.2	67.47	12.28	74.00	6.53	PK	Vertical	170

AV Final Data List							Antenna Height (cm)
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	
1	4688.334	34.21	54.00	19.79	AV	Vertical	117
2	8363.068	37.80	54.00	16.20	AV	Vertical	129
3	16383.21	47.42	54.00	6.58	AV	Vertical	180

Suspected Data List								Antenna Height (cm)
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	4667.08	50.98	-8.10	74.00	23.02	PK	Horizontal	119
2	8314.61	58.07	-0.52	74.00	15.93	PK	Horizontal	129
3	17683.7	66.96	13.52	74.00	7.04	PK	Horizontal	170

AV Final Data List							Antenna Height (cm)
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	
1	4667.083	34.70	54.00	19.30	AV	Horizontal	112
2	8314.615	38.45	54.00	15.55	AV	Horizontal	130
3	17683.78	48.52	54.00	5.48	AV	Horizontal	172

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20) Frequency(MHz): 6435

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4670.48	50.57	-8.08	74.00	23.43	PK	Vertical	135
2	8420.02	58.69	-0.66	74.00	15.31	PK	Vertical	201
3	17399.8	66.95	13.34	74.00	7.05	PK	Vertical	110

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4670.483	34.71	54.00	19.29	AV	Vertical	138
2	8420.021	37.49	54.00	16.51	AV	Vertical	205
3	17399.87	48.59	54.00	5.41	AV	Vertical	115

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4647.53	50.88	-8.21	74.00	23.12	PK	Horizontal	130
2	8311.21	58.59	-0.53	74.00	15.41	PK	Horizontal	190
3	17059.0	66.87	13.42	74.00	7.13	PK	Horizontal	109

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4647.532	34.67	54.00	19.33	AV	Horizontal	141
2	8311.215	38.34	54.00	15.66	AV	Horizontal	199
3	17059.00	49.06	54.00	4.94	AV	Horizontal	120

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6475

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4722.33	51.52	-8.19	74.00	22.48	PK	Vertical	145
2	8357.96	57.99	-0.44	74.00	16.01	PK	Vertical	180
3	16781.8	66.88	12.01	74.00	7.12	PK	Vertical	125

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4722.336	34.11	54.00	19.89	AV	Vertical	150
2	8357.967	37.97	54.00	16.03	AV	Vertical	185
3	16781.88	47.12	54.00	6.88	AV	Vertical	130

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4660.28	51.83	-8.14	74.00	22.17	PK	Horizontal	148
2	8294.21	58.29	-0.71	74.00	15.71	PK	Horizontal	191
3	17658.2	66.90	13.98	74.00	7.10	PK	Horizontal	130

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4660.283	34.39	54.00	19.61	AV	Horizontal	151
2	8294.214	37.83	54.00	16.17	AV	Horizontal	185
3	17658.28	49.82	54.00	4.18	AV	Horizontal	125

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6515

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4712.98	50.82	-8.07	74.00	23.18	PK	Vertical	130
2	8409.82	59.61	-0.54	74.00	14.39	PK	Vertical	178
3	17410.9	66.94	13.48	74.00	7.06	PK	Vertical	119

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4712.985	34.35	54.00	19.65	AV	Vertical	139
2	8409.820	37.95	54.00	16.05	AV	Vertical	180
3	17410.92	49.44	54.00	4.56	AV	Vertical	110

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4623.73	50.82	-8.36	74.00	23.18	PK	Horizontal	139
2	8284.01	58.70	-1.00	74.00	15.30	PK	Horizontal	180
3	17555.4	66.94	14.87	74.00	7.06	PK	Horizontal	110

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4623.731	33.69	54.00	20.31	AV	Horizontal	136
2	8284.014	37.39	54.00	16.61	AV	Horizontal	183
3	17555.42	50.12	54.00	3.88	AV	Horizontal	121

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6535

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4655.18	50.81	-8.17	74.00	23.19	PK	Vertical	139
2	8326.51	59.00	-0.49	74.00	15.00	PK	Vertical	110
3	17194.1	66.95	14.21	74.00	7.05	PK	Vertical	150

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4655.182	34.69	54.00	19.31	AV	Vertical	128
2	8326.516	37.58	54.00	16.42	AV	Vertical	118
3	17194.15	49.47	54.00	4.53	AV	Vertical	159

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4619.48	50.68	-8.38	74.00	23.32	PK	Horizontal	130
2	8374.96	58.30	-0.44	74.00	15.70	PK	Horizontal	110
3	17108.3	66.89	13.33	74.00	7.11	PK	Horizontal	168

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4619.481	34.37	54.00	19.63	AV	Horizontal	141
2	8374.968	38.31	54.00	15.69	AV	Horizontal	128
3	17108.30	49.17	54.00	4.83	AV	Horizontal	160

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6695

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4535.32	50.73	-8.69	74.00	23.27	PK	Vertical	140
2	8301.01	58.85	-0.55	74.00	15.15	PK	Vertical	119
3	17348.0	66.97	12.94	74.00	7.03	PK	Vertical	141

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4535.326	33.75	54.00	20.25	AV	Vertical	145
2	8301.015	38.05	54.00	15.95	AV	Vertical	116
3	17348.01	48.83	54.00	5.17	AV	Vertical	139

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4668.78	51.99	-8.08	74.00	22.01	PK	Horizontal	133
2	8335.01	59.14	-0.47	74.00	14.86	PK	Horizontal	110
3	17033.5	66.92	13.53	74.00	7.08	PK	Horizontal	131

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4668.783	34.23	54.00	19.77	AV	Horizontal	140
2	8335.016	38.24	54.00	15.76	AV	Horizontal	115
3	17033.50	49.42	54.00	4.58	AV	Horizontal	130

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6855

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4684.08	50.80	-7.99	74.00	23.20	PK	Vertical	122
2	8301.86	57.86	-0.55	74.00	16.14	PK	Vertical	130
3	17275.7	66.87	12.98	74.00	7.13	PK	Vertical	156

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4684.084	34.90	54.00	19.10	AV	Vertical	120
2	8301.865	37.57	54.00	16.43	AV	Vertical	138
3	17275.76	48.17	54.00	5.83	AV	Vertical	150

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4703.63	51.27	-7.95	74.00	22.73	PK	Horizontal	120
2	8313.76	58.62	-0.52	74.00	15.38	PK	Horizontal	138
3	17226.4	66.93	13.82	74.00	7.07	PK	Horizontal	150

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4703.635	34.49	54.00	19.51	AV	Horizontal	128
2	8313.765	37.79	54.00	16.21	AV	Horizontal	150
3	17226.46	49.65	54.00	4.35	AV	Horizontal	132

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6895

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4529.37	50.53	-8.71	74.00	23.47	PK	Vertical	151
2	8354.56	58.48	-0.44	74.00	15.52	PK	Vertical	136
3	17166.1	66.88	13.92	74.00	7.12	PK	Vertical	150

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4529.376	33.32	54.00	20.68	AV	Vertical	160
2	8354.567	37.97	54.00	16.03	AV	Vertical	150
3	17166.10	49.63	54.00	4.37	AV	Vertical	120

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4653.48	50.79	-8.18	74.00	23.21	PK	Horizontal	167
2	8322.26	58.57	-0.51	74.00	15.43	PK	Horizontal	150
3	16461.4	66.89	11.53	74.00	7.11	PK	Horizontal	120

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4653.482	34.21	54.00	19.79	AV	Horizontal	160
2	8322.266	37.74	54.00	16.26	AV	Horizontal	155
3	16461.42	47.19	54.00	6.81	AV	Horizontal	123

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20) Frequency(MHz): 6995

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4583.77	51.10	-8.55	74.00	22.90	PK	Vertical	166
2	8357.11	59.08	-0.44	74.00	14.92	PK	Vertical	131
3	17089.6	66.95	13.29	74.00	7.05	PK	Vertical	100

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4583.779	34.10	54.00	19.90	AV	Vertical	155
2	8357.117	37.58	54.00	16.42	AV	Vertical	129
3	17089.60	48.63	54.00	5.37	AV	Vertical	101

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4718.93	50.73	-8.15	74.00	23.27	PK	Horizontal	169
2	10091.2	60.99	3.81	74.00	13.01	PK	Horizontal	130
3	16288.0	67.75	10.39	74.00	6.25	PK	Horizontal	105

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4718.935	34.35	54.00	19.65	AV	Horizontal	156
2	10091.20	41.92	54.00	12.08	AV	Horizontal	135
3	16288.01	45.65	54.00	8.35	AV	Horizontal	100

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

b

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 7115

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4662.83	51.51	-8.12	74.00	22.49	PK	Vertical	148
2	8295.06	58.70	-0.69	74.00	15.30	PK	Vertical	137
3	17064.1	66.65	13.39	74.00	7.35	PK	Vertical	105

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	4662.833	34.39	54.00	19.61	AV	Vertical	146
2	8295.064	37.49	54.00	16.51	AV	Vertical	130
3	17064.10	48.87	54.00	5.13	AV	Vertical	110

Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	3619.83	48.79	-10.65	74.00	25.21	PK	Horizontal	140
2	7831.79	56.11	-2.36	74.00	17.89	PK	Horizontal	120
3	16641.6	66.57	10.91	74.00	7.43	PK	Horizontal	105

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity	Antenna Height (cm)
1	3619.831	31.54	54.00	22.46	AV	Horizontal	150
2	7831.791	35.82	54.00	18.18	AV	Horizontal	120
3	16641.63	46.69	54.00	7.31	AV	Horizontal	100

Remark: The radiation measurements are performed in X, Y, Z axis positioning for transmitting mode, and found the X axis positioning which it is the worst case, only the worst data is recorded in the report.

Note:	(1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.
-------	--

■ Undesirable radiated Undesirable radiated Spurious Emission in Band Edge

● For U-NII 5

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20) Frequency(MHz): 5955

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5888.36	56.39	40.84	68.20	11.81	PK	Vertical
2	7199.91	60.69	45.34	68.20	7.51	PK	Vertical
1	5918.01	61.69	41.01	68.20	6.51	PK	Horizontal
2	7210.03	60.78	45.27	68.20	7.42	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20) Frequency(MHz): 6415


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5918.01	56.25	41.01	68.20	11.95	PK	Vertical
2	7222.10	60.47	45.18	68.20	7.73	PK	Vertical
1	5919.43	57.40	41.01	68.20	10.80	PK	Horizontal
2	7188.55	61.26	45.17	68.20	6.94	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 5955

Ant.Pol: V




U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 5955

Ant.Pol: H




U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6415

Ant.Pol: V




U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6415

Ant.Pol: H



● For U-NII 6

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 6435

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5885.52	56.42	40.82	68.20	11.78	PK	Vertical
2	7194.59	60.68	45.26	68.20	7.52	PK	Vertical
1	5829.97	56.60	40.22	68.20	11.60	PK	Horizontal
2	7154.65	60.41	44.66	68.20	7.79	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 6515


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5924.22	56.13	41.02	68.20	12.07	PK	Vertical
2	7179.85	60.68	45.04	68.20	7.52	PK	Vertical
1	5877.89	56.55	40.74	68.20	11.65	PK	Horizontal
2	7180.92	60.30	45.06	68.20	7.90	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6435

Ant.Pol: V




U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6435

Ant.Pol: H




U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6515

Ant.Pol: V




U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6515

Ant.Pol: H



● For U-NII 7

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 6535

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5909.84	55.78	40.98	68.20	12.42	PK	Vertical
2	7166.54	61.04	44.84	68.20	7.16	PK	Vertical
1	5895.64	56.04	40.92	68.20	12.16	PK	Horizontal
2	7199.91	60.51	45.34	68.20	7.69	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 6855


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5887.65	55.93	40.84	68.20	12.27	PK	Vertical
2	7173.82	61.10	44.95	68.20	7.10	PK	Vertical
1	5896.88	56.24	40.93	68.20	11.96	PK	Horizontal
2	7158.91	61.03	44.73	68.20	7.17	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11n(20)

Frequency(MHz): 6535

Ant.Pol: V




U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11n(20)

Frequency(MHz): 6535

Ant.Pol: H




U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6855

Ant.Pol: V




U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6855

Ant.Pol: H



● For U-NII 8

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 6895

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5920.14	56.41	41.01	68.20	11.79	PK	Vertical
2	7173.29	60.73	44.94	68.20	7.47	PK	Vertical
1	5919.25	56.41	41.01	68.20	11.79	PK	Horizontal
2	7228.84	61.23	45.14	68.20	6.97	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20) **Frequency(MHz):** 7115


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5915.34	56.16	40.99	68.20	12.04	PK	Vertical
2	7200.09	60.24	45.34	68.20	7.96	PK	Vertical
1	5893.87	56.65	40.90	68.20	11.55	PK	Horizontal
2	7192.10	60.84	45.22	68.20	7.36	PK	Horizontal
Note: (1) Peak RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = Peak; (2) Avg RBW = 1 MHz, VBW ≥ 3 × RBW, Detector = RMS; (3) Corrected Reading = Reading Level + Correct Factor; (4) Correct Factor = Ant_F + Cab_L - Preamp; (5) Margin = Limit - Corrected Reading; (6) If the emissions less than the peak limit, it also complied with the -47dBm/MHz (88.2dBuV/m) limit. (7) If the emissions less than the average limit, it also complied with the -27dBm/MHz (68.2dBuV/m) limit.							

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6895

Ant.Pol: V




U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 6895

Ant.Pol: H




U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 7115

Ant.Pol: V




U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11AX(20)

Frequency(MHz): 7115

Ant.Pol: H




■ Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All antennas and modulation modes are tested, the data of the worst mode is described as below.

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 5955




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	57.1872	26.54	-9.53	17.01	PK	40.00	22.99	Vertical
2	66.8969	30.46	-10.79	19.67	PK	40.00	20.33	Vertical
3	70.7808	29.36	-11.30	18.06	PK	40.00	21.94	Vertical
4	605.785	23.93	0.24	24.17	PK	46.00	21.83	Vertical
5	704.824	26.94	0.99	27.93	PK	46.00	18.07	Vertical
6	722.302	29.94	1.05	30.99	PK	46.00	15.01	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	57.1872	-9.53	16.23	40.00	23.77
2	66.8969	-10.79	18.73	40.00	21.27
3	70.7808	-11.30	17.12	40.00	22.88
4	605.7858	0.24	23.59	46.00	22.41
5	704.8248	0.99	27.35	46.00	18.65
6	722.3023	1.05	30.24	46.00	15.76



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	24.70	-9.15	15.55	PK	40.00	24.45	Horizontal
2	459.169	24.48	-3.18	21.30	PK	46.00	24.70	Horizontal
3	592.192	24.57	0.22	24.79	PK	46.00	21.21	Horizontal
4	697.057	24.15	0.77	24.92	PK	46.00	21.08	Horizontal
5	812.602	24.24	1.62	25.86	PK	46.00	20.14	Horizontal
6	945.625	24.92	3.16	28.08	PK	46.00	17.92	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-9.15	14.74	40.00	25.26
2	459.1692	-3.18	20.49	46.00	25.51
3	592.1922	0.22	23.82	46.00	22.18
4	697.0571	0.77	23.95	46.00	22.05
5	812.6026	1.62	25.25	46.00	20.75
6	945.6256	3.16	27.47	46.00	18.53

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6175




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	26.28	-9.15	17.13	PK	40.00	22.87	Vertical
2	65.9259	31.00	-10.67	20.33	PK	40.00	19.67	Vertical
3	72.7227	29.69	-11.60	18.09	PK	40.00	21.91	Vertical
4	600.930	24.73	0.55	25.28	PK	46.00	20.72	Vertical
5	629.089	25.38	-0.55	24.83	PK	46.00	21.17	Vertical
6	839.789	24.55	2.16	26.71	PK	46.00	19.29	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-9.15	16.65	40.00	23.35
2	65.9259	-10.67	19.85	40.00	20.15
3	72.7227	-11.60	17.45	40.00	22.55
4	600.9309	0.55	24.64	46.00	21.36
5	629.0891	-0.55	24.55	46.00	21.45
6	839.7898	2.16	26.43	46.00	19.57



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	57.1872	24.73	-9.53	15.20	PK	40.00	24.80	Horizontal
2	509.659	23.96	-2.88	21.08	PK	46.00	24.92	Horizontal
3	587.337	25.05	0.00	25.05	PK	46.00	20.95	Horizontal
4	705.795	40.69	1.00	41.69	PK	46.00	4.31	Horizontal
5	830.080	23.99	1.94	25.93	PK	46.00	20.07	Horizontal
6	910.670	25.30	3.38	28.68	PK	46.00	17.32	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	57.1872	-9.53	14.49	40.00	25.51
2	509.6597	-2.88	20.37	46.00	25.63
3	587.3373	0.00	24.18	46.00	21.82
4	705.7958	1.00	41.18	46.00	4.82
5	830.0801	1.94	25.42	46.00	20.58
6	910.6707	3.38	28.17	46.00	17.83

U-NII 5 Band (5925 ~ 6425MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6415




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	58.1582	26.34	-9.67	16.67	PK	40.00	23.33	Vertical
2	65.9259	29.68	-10.67	19.01	PK	40.00	20.99	Vertical
3	70.7808	28.49	-11.30	17.19	PK	40.00	22.81	Vertical
4	601.901	24.54	0.49	25.03	PK	46.00	20.97	Vertical
5	691.231	24.47	0.53	25.00	PK	46.00	21.00	Vertical
6	833.964	25.18	2.03	27.21	PK	46.00	18.79	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	58.1582	-9.67	16.02	40.00	23.98
2	65.9259	-10.67	18.36	40.00	21.64
3	70.7808	-11.30	16.90	40.00	23.10
4	601.9019	0.49	24.74	46.00	21.26
5	691.2312	0.53	24.71	46.00	21.29
6	833.964	2.03	26.28	46.00	19.72



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	53.3033	23.59	-9.03	14.56	PK	40.00	25.44	Horizontal
2	499.95	23.92	-3.07	20.85	PK	46.00	25.15	Horizontal
3	595.105	24.07	0.37	24.44	PK	46.00	21.56	Horizontal
4	698.999	24.83	0.86	25.69	PK	46.00	20.31	Horizontal
5	832.993	24.62	2.01	26.63	PK	46.00	19.37	Horizontal
6	981.551	24.61	3.82	28.43	PK	54.00	25.57	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	53.3033	-9.03	13.96	40.00	26.04
2	499.95	-3.07	20.25	46.00	25.75
3	595.1051	0.37	23.67	46.00	22.33
4	698.999	0.86	24.92	46.00	21.08
5	832.993	2.01	26.22	46.00	19.78
6	981.5516	3.82	28.02	54.00	25.98

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6435




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	63.984	30.32	-10.42	19.90	PK	40.00	20.10	Vertical
2	72.7227	29.28	-11.60	17.68	PK	40.00	22.32	Vertical
3	590.250	24.34	0.12	24.46	PK	46.00	21.54	Vertical
4	713.563	24.57	1.05	25.62	PK	46.00	20.38	Vertical
5	831.051	23.94	1.96	25.90	PK	46.00	20.10	Vertical
6	948.538	25.05	3.33	28.38	PK	46.00	17.62	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	63.984	-10.42	19.82	40.00	20.18
2	72.7227	-11.60	17.44	40.00	22.56
3	590.2503	0.12	24.22	46.00	21.78
4	713.5636	1.05	24.73	46.00	21.27
5	831.0511	1.96	25.01	46.00	20.99
6	948.5385	3.33	27.85	46.00	18.15



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	49.4194	23.65	-8.69	14.96	PK	40.00	25.04	Horizontal
2	55.2452	24.49	-9.28	15.21	PK	40.00	24.79	Horizontal
3	504.804	24.44	-2.97	21.47	PK	46.00	24.53	Horizontal
4	597.047	24.72	0.46	25.18	PK	46.00	20.82	Horizontal
5	683.463	24.93	0.25	25.18	PK	46.00	20.82	Horizontal
6	808.718	24.30	1.59	25.89	PK	46.00	20.11	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	49.4194	-8.69	14.60	40.00	25.40
2	55.2452	-9.28	15.21	40.00	24.79
3	504.8048	-2.97	21.30	46.00	24.70
4	597.047	0.46	25.01	46.00	20.99
5	683.4635	0.25	24.37	46.00	21.63
6	808.7187	1.59	25.08	46.00	20.92

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6475




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	64.955	30.55	-10.54	20.01	PK	40.00	19.99	Vertical
2	70.7808	29.64	-11.30	18.34	PK	40.00	21.66	Vertical
3	143.603	33.86	-11.98	21.88	PK	43.50	21.62	Vertical
4	596.076	24.10	0.41	24.51	PK	46.00	21.49	Vertical
5	708.708	23.64	1.05	24.69	PK	46.00	21.31	Vertical
6	734.924	24.47	1.25	25.72	PK	46.00	20.28	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	64.955	-10.54	19.62	40.00	20.38
2	70.7808	-11.30	17.95	40.00	22.05
3	143.6036	-11.98	21.85	43.50	21.65
4	596.0761	0.41	23.84	46.00	22.16
5	708.7087	1.05	24.02	46.00	21.98
6	734.9249	1.25	25.05	46.00	20.95



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	49.4194	23.15	-8.69	14.46	PK	40.00	25.54	Horizontal
2	53.3033	24.28	-9.03	15.25	PK	40.00	24.75	Horizontal
3	461.111	24.32	-3.16	21.16	PK	46.00	24.84	Horizontal
4	583.453	24.70	-0.16	24.54	PK	46.00	21.46	Horizontal
5	709.679	23.77	1.06	24.83	PK	46.00	21.17	Horizontal
6	828.138	24.64	1.88	26.52	PK	46.00	19.48	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	49.4194	-8.69	14.31	40.00	25.69
2	53.3033	-9.03	14.93	40.00	25.07
3	461.1111	-3.16	20.84	46.00	25.16
4	583.4535	-0.16	23.58	46.00	22.42
5	709.6797	1.06	23.87	46.00	22.13
6	828.1381	1.88	25.92	46.00	20.08

U-NII 6 Band (6425 ~ 6525MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6515




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	53.3033	25.58	-9.03	16.55	PK	40.00	23.45	Vertical
2	68.8388	32.40	-11.04	21.36	PK	40.00	18.64	Vertical
3	70.7808	29.35	-11.30	18.05	PK	40.00	21.95	Vertical
4	573.743	26.08	-0.68	25.40	PK	46.00	20.60	Vertical
5	702.882	23.61	0.95	24.56	PK	46.00	21.44	Vertical
6	836.876	24.07	2.09	26.16	PK	46.00	19.84	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	53.3033	-9.03	15.76	40.00	24.24
2	68.8388	-11.04	20.57	40.00	19.43
3	70.7808	-11.30	17.62	40.00	22.38
4	573.7437	-0.68	24.97	46.00	21.03
5	702.8829	0.95	24.49	46.00	21.51
6	836.8769	2.09	26.09	46.00	19.91



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	47.4775	23.69	-9.00	14.69	PK	40.00	25.31	Horizontal
2	397.027	25.12	-4.05	21.07	PK	46.00	24.93	Horizontal
3	477.617	24.28	-3.06	21.22	PK	46.00	24.78	Horizontal
4	596.076	23.65	0.41	24.06	PK	46.00	21.94	Horizontal
5	690.260	24.23	0.49	24.72	PK	46.00	21.28	Horizontal
6	845.615	24.48	2.39	26.87	PK	46.00	19.13	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	47.4775	-9.00	14.48	40.00	25.52
2	397.027	-4.05	20.22	46.00	25.78
3	477.6176	-3.06	20.37	46.00	25.63
4	596.0761	0.41	24.04	46.00	21.96
5	690.2603	0.49	24.70	46.00	21.30
6	845.6156	2.39	26.21	46.00	19.79

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6535




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	65.9259	30.77	-10.67	20.10	PK	40.00	19.90	Vertical
2	71.7518	28.69	-11.45	17.24	PK	40.00	22.76	Vertical
3	207.687	32.70	-9.46	23.24	PK	43.50	20.26	Vertical
4	593.163	24.14	0.27	24.41	PK	46.00	21.59	Vertical
5	608.698	24.88	0.06	24.94	PK	46.00	21.06	Vertical
6	749.489	25.59	0.81	26.40	PK	46.00	19.60	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	65.9259	-10.67	19.66	40.00	20.34
2	71.7518	-11.45	16.80	40.00	23.20
3	207.6877	-9.46	23.16	43.50	20.34
4	593.1632	0.27	24.33	46.00	21.67
5	608.6987	0.06	24.70	46.00	21.30
6	749.4895	0.81	26.16	46.00	19.84



Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Detector	Limit [dBµV/m]	Margin [dB]	Polarity
1	49.4194	23.19	-8.69	14.50	PK	40.00	25.50	Horizontal
2	55.2452	24.62	-9.28	15.34	PK	40.00	24.66	Horizontal
3	485.385	24.31	-3.03	21.28	PK	46.00	24.72	Horizontal
4	591.221	23.95	0.17	24.12	PK	46.00	21.88	Horizontal
5	688.318	24.55	0.42	24.97	PK	46.00	21.03	Horizontal
6	832.022	24.81	1.98	26.79	PK	46.00	19.21	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]
1	49.4194	-8.69	14.30	40.00	25.70
2	55.2452	-9.28	15.14	40.00	24.86
3	485.3854	-3.03	20.92	46.00	25.08
4	591.2212	0.17	23.76	46.00	22.24
5	688.3183	0.42	24.97	46.00	21.03
6	832.022	1.98	26.79	46.00	19.21

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6695




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	57.1872	25.87	-9.53	16.34	PK	40.00	23.66	Vertical
2	66.8969	30.59	-10.79	19.80	PK	40.00	20.20	Vertical
3	70.7808	29.23	-11.30	17.93	PK	40.00	22.07	Vertical
4	597.047	24.60	0.46	25.06	PK	46.00	20.94	Vertical
5	709.679	23.32	1.06	24.38	PK	46.00	21.62	Vertical
6	832.022	24.42	1.98	26.40	PK	46.00	19.60	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	57.1872	-9.53	16.31	40.00	23.69
2	66.8969	-10.79	19.13	40.00	20.87
3	70.7808	-11.30	17.26	40.00	22.74
4	597.047	0.46	24.22	46.00	21.78
5	709.6797	1.06	23.54	46.00	22.46
6	832.022	1.98	25.92	46.00	20.08



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	24.91	-9.15	15.76	PK	40.00	24.24	Horizontal
2	460.140	24.64	-3.16	21.48	PK	46.00	24.52	Horizontal
3	588.308	23.98	0.05	24.03	PK	46.00	21.97	Horizontal
4	700.940	24.00	0.92	24.92	PK	46.00	21.08	Horizontal
5	842.702	23.69	2.27	25.96	PK	46.00	20.04	Horizontal
6	917.467	24.76	3.44	28.20	PK	46.00	17.80	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-9.15	15.50	40.00	24.50
2	460.1401	-3.16	20.58	46.00	25.42
3	588.3083	0.05	23.97	46.00	22.03
4	700.9409	0.92	24.86	46.00	21.14
5	842.7027	2.27	25.90	46.00	20.10
6	917.4675	3.44	27.49	46.00	18.51

U-NII 7 Band (6525 ~ 6875MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6855




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	66.8969	30.31	-10.79	19.52	PK	40.00	20.48	Vertical
2	73.6937	29.53	-11.74	17.79	PK	40.00	22.21	Vertical
3	202.832	35.22	-9.75	25.47	PK	43.50	18.03	Vertical
4	590.250	24.75	0.12	24.87	PK	46.00	21.13	Vertical
5	697.057	25.36	0.77	26.13	PK	46.00	19.87	Vertical
6	746.576	24.85	0.97	25.82	PK	46.00	20.18	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	66.8969	-10.79	18.59	40.00	21.41
2	73.6937	-11.74	17.22	40.00	22.78
3	202.8328	-9.75	24.90	43.50	18.60
4	590.2503	0.12	24.13	46.00	21.87
5	697.0571	0.77	25.75	46.00	20.25
6	746.5766	0.97	25.44	46.00	20.56



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	49.4194	24.13	-8.69	15.44	PK	40.00	24.56	Horizontal
2	508.688	24.13	-2.90	21.23	PK	46.00	24.77	Horizontal
3	592.192	24.28	0.22	24.50	PK	46.00	21.50	Horizontal
4	715.505	24.04	1.03	25.07	PK	46.00	20.93	Horizontal
5	831.051	24.09	1.96	26.05	PK	46.00	19.95	Horizontal
6	987.377	24.74	3.84	28.58	PK	54.00	25.42	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	49.4194	-8.69	14.84	40.00	25.16
2	508.6887	-2.90	20.46	46.00	25.54
3	592.1922	0.22	23.73	46.00	22.27
4	715.5055	1.03	24.66	46.00	21.34
5	831.0511	1.96	25.64	46.00	20.36
6	987.3774	3.84	28.53	54.00	25.47

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6895




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	54.2743	25.52	-9.15	16.37	PK	40.00	23.63	Vertical
2	64.955	30.03	-10.54	19.49	PK	40.00	20.51	Vertical
3	73.6937	29.96	-11.74	18.22	PK	40.00	21.78	Vertical
4	584.424	24.53	-0.12	24.41	PK	46.00	21.59	Vertical
5	702.882	23.49	0.95	24.44	PK	46.00	21.56	Vertical
6	826.196	24.17	1.82	25.99	PK	46.00	20.01	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	54.2743	-9.15	16.29	40.00	23.71
2	64.955	-10.54	19.41	40.00	20.59
3	73.6937	-11.74	17.50	40.00	22.50
4	584.4244	-0.12	23.69	46.00	22.31
5	702.8829	0.95	23.55	46.00	22.45
6	826.1962	1.82	25.10	46.00	20.90



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	48.4484	24.37	-8.84	15.53	PK	40.00	24.47	Horizontal
2	54.2743	24.69	-9.15	15.54	PK	40.00	24.46	Horizontal
3	597.047	23.97	0.46	24.43	PK	46.00	21.57	Horizontal
4	715.505	28.61	1.03	29.64	PK	46.00	16.36	Horizontal
5	835.905	25.70	2.07	27.77	PK	46.00	18.23	Horizontal
6	908.728	26.01	3.35	29.36	PK	46.00	16.64	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	48.4484	-8.84	14.78	40.00	25.22
2	54.2743	-9.15	14.62	40.00	25.38
3	597.047	0.46	23.51	46.00	22.49
4	715.5055	1.03	29.08	46.00	16.92
5	835.9059	2.07	27.21	46.00	18.79
6	908.7287	3.35	29.16	46.00	16.84

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 6995




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	65.9259	30.73	-10.67	20.06	PK	40.00	19.94	Vertical
2	71.7518	29.85	-11.45	18.40	PK	40.00	21.60	Vertical
3	104.764	41.94	-9.83	32.11	PK	43.50	11.39	Vertical
4	598.018	25.47	0.51	25.98	PK	46.00	20.02	Vertical
5	708.708	23.96	1.05	25.01	PK	46.00	20.99	Vertical
6	828.138	24.37	1.88	26.25	PK	46.00	19.75	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	65.9259	-10.67	19.17	40.00	20.83
2	71.7518	-11.45	17.87	40.00	22.13
3	104.7648	-9.83	31.58	43.50	11.92
4	598.018	0.51	25.81	46.00	20.19
5	708.7087	1.05	24.84	46.00	21.16
6	828.1381	1.88	25.91	46.00	20.09



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	67.8679	31.08	-10.92	20.16	PK	40.00	19.84	Horizontal
2	77.5776	30.12	-12.32	17.80	PK	40.00	22.20	Horizontal
3	504.804	25.09	-2.97	22.12	PK	46.00	23.88	Horizontal
4	597.047	23.46	0.46	23.92	PK	46.00	22.08	Horizontal
5	715.505	24.45	1.03	25.48	PK	46.00	20.52	Horizontal
6	828.138	24.25	1.88	26.13	PK	46.00	19.87	Horizontal


Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	67.8679	-10.92	19.85	40.00	20.15
2	77.5776	-12.32	16.85	40.00	23.15
3	504.8048	-2.97	21.17	46.00	24.83
4	597.047	0.46	23.80	46.00	22.20
5	715.5055	1.03	25.36	46.00	20.64
6	828.1381	1.88	25.37	46.00	20.63

U-NII 8 Band (6875 ~ 7125MHz)

Test mode: 802.11ax(20)

Frequency(MHz): 7115




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	64.955	29.74	-10.54	19.20	PK	40.00	20.80	Vertical
2	203.803	30.83	-9.69	21.14	PK	43.50	22.36	Vertical
3	589.279	24.66	0.08	24.74	PK	46.00	21.26	Vertical
4	661.131	25.84	0.09	25.93	PK	46.00	20.07	Vertical
5	829.109	24.15	1.91	26.06	PK	46.00	19.94	Vertical
6	917.467	24.89	3.44	28.33	PK	46.00	17.67	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	64.955	-10.54	18.57	40.00	21.43
2	203.8038	-9.69	20.35	43.50	23.15
3	589.2793	0.08	23.95	46.00	22.05
4	661.1311	0.09	25.50	46.00	20.50
5	829.1091	1.91	25.63	46.00	20.37
6	917.4675	3.44	27.90	46.00	18.10



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	52.3323	24.35	-8.90	15.45	PK	40.00	24.55	Horizontal
2	463.053	24.56	-3.15	21.41	PK	46.00	24.59	Horizontal
3	602.872	23.54	0.43	23.97	PK	46.00	22.03	Horizontal
4	706.766	23.76	1.02	24.78	PK	46.00	21.22	Horizontal
5	836.876	24.20	2.09	26.29	PK	46.00	19.71	Horizontal
6	967.958	25.34	3.86	29.20	PK	54.00	24.80	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	52.3323	-8.90	14.63	40.00	25.37
2	463.0531	-3.15	20.59	46.00	25.41
3	602.8729	0.43	23.51	46.00	22.49
4	706.7668	1.02	24.68	46.00	21.32
5	836.8769	2.09	26.19	46.00	19.81
6	967.958	3.86	29.10	54.00	24.90

8.7 POWER LINE CONDUCTED EMISSIONS

8.7.1 Applicable Standard

According to FCC Part 15.207(a)

According to IC RSS-Gen 8.8

8.7.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.7.3 Test Configuration

Test according to clause 7.3 conducted emission test setup.

8.7.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.7.5 Test Results

N/A

Not applicable, since EUT is DC power.

8.8 ANTENNA REQUIREMENT

8.8.1 Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

8.8.2 Result

PASS

Temperature :	25 °C	ATM Pressure:	1011 mbar
Humidity :	45 %	Test Engineer:	LHJ

- ☒ Antenna use a permanently attached antenna which is not replaceable.
- ☐ Not using a standard antenna jack or electrical connector for antenna replacement
- ☐ The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached document Internal Photos to show the antenna connector.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

--- End of Report ---

声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效。
1. This report is invalid without the signature of the authorized approver and "special seal for testing".
2. 未经许可本报告不得部分复制。
2. This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责。
3. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用。
4. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外。
5. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检验报告若有异议，请于收到报告之日起 20 日内提出。
6. Objections shall be raised within 20 days from the date receiving the report.