

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Tablet

Trademark : HOTWAV

Model Name : Pad 8

Family Model : P2203, Pad

FCC ID : 2AOKUPAD8

Report No. : S23050501503001

Prepared for

SHENZHEN TUGAO INTELLIGENT CO.,LTD
8th Floor, Bldg A, Jinggang Science&Technology Park, Fuyong,
Bao'an District, Shenzhen, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name..... SHENZHEN TUGAO INTELLIGENT CO.,LTD
Address 8th Floor, Bldg A, Jinggang Science&Technology Park, Fuyong,
Bao'an District, Shenzhen, China

Manufacturer's Name..... SHENZHEN TUGAO INTELLIGENT CO.,LTD
Address 8th Floor, Bldg A, Jinggang Science&Technology Park, Fuyong,
Bao'an District, Shenzhen, China

Product description

Product name..... Tablet
Trademark HOTWAV
Model Name Pad 8
Family Model..... P2203, Pad
FCC 47 CFR Part 2(2.1093);
ANSI/IEEE C95.1-1992

Standards..... IEEE Std 1528-2013;
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number S230505015004

Date of Test

Date (s) of performance of tests..... May 06, 2023 ~ May 23, 2023

Date of Issue Jun. 16, 2023

Test Result **Pass**

Prepared By :
(Test Engineer)

Jack Li

(Jack Li)

Approved By :
(Lab Manager)

Alex

(Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Jun. 16, 2023	Jack Li

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	8
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan.....	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results.....	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability.....	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Tablet host platform exposure conditions.....	27
7. RF Output Power	28
7.1. GSM Conducted Power	28
7.2. WCDMA Conducted Power	29
7.3. LTE Conducted Power	29
7.4. WLAN & Bluetooth Output Power	44
7.4.1. Output Power Results Of WLAN	44
7.4.2. Output Power Results Of Bluetooth	45
8. Antenna Location.....	47
9. Stand-alone SAR test exclusion.....	56

10.	SAR Results	56
10.1.	SAR measurement results.....	56
10.1.1.	SAR measurement Result of GSM850.....	56
10.1.2.	SAR measurement Result of GSM1900.....	57
10.1.3.	SAR measurement Result of WCDMA Band 2.....	58
10.1.4.	SAR measurement Result of WCDMA Band 5.....	59
10.1.5.	SAR measurement Result of LTE Band 2	59
10.1.6.	SAR measurement Result of LTE Band 5	61
10.1.7.	SAR measurement Result of LTE Band 7	62
10.1.8.	SAR measurement Result of LTE Band 12	63
10.1.9.	SAR measurement Result of LTE Band 17	64
10.1.10.	SAR measurement Result of LTE Band 38	65
10.1.11.	SAR measurement Result of LTE Band 40A.....	67
10.1.12.	SAR measurement Result of LTE Band 40B	68
10.1.13.	SAR measurement Result of LTE Band 41	69
10.1.14.	SAR measurement Result of WLAN 2.4G	70
10.1.15.	SAR measurement Result of WLAN 5.2G	70
10.1.16.	SAR measurement Result of WLAN 5.8G	71
10.2.	SAR Summation Scenario.....	72
11.	Appendix A. Photo documentation	73
12.	Appendix B. System Check Plots.....	74
13.	Appendix C. Plots of High SAR Measurement.....	93
14.	Appendix D. Calibration Certificate	126

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Pad 8 are as follows.

RF Exposure Conditions		Max Reported SAR Value(W/kg)
1-g Body-Worn (Separation distance of 0mm)		1.195
1-g Hotspot (Separation distance of 0mm)		1.195
Max Simultaneous Tx	Body-Worn	1.408
	Hotspot	1.408

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Tablet		
Trade Name	HOTWAV		
Model Name	Pad 8		
Family Model	P2203, Pad		
Model Difference	All the model are the same circuit and RF module,except the model names.		
FCC ID	2AOKUPAD8		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna	PIFA Antenna		
Battery	DC 3.8V, 7500mAh		
Hardware version	KEP_P30A_V1.0		
Software version	HOTWAV_Pad 8_V01_20230525		
Device Operating Configurations			
Supporting Mode(s)	GSM 850/1900, WCDMA Band 2/4/5, LTE Band 2/5/7/12/17/38/40A/40B/41, WLAN 2.4G/5G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 5	824-849	869-894

	LTE Band 2	1850-1910	1930-1990
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 38	2570-2620	
	LTE Band 40A	2305-2315	
	LTE Band 40B	2350-2360	
	LTE Band 41	2540-2650	
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control "all 1"(WCDMA Band 2)		
	3, tested with power control "all 1"(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
	3, tested with power control all Max.(LTE Band 38)		
	3, tested with power control all Max.(LTE Band 40A)		
	3, tested with power control all Max.(LTE Band 40B)		
	3, tested with power control all Max.(LTE Band 41)		

1.4. Test specification(s)

FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting

KDB 447498 D01 General RF Exposure Guidance

KDB 248227 D01 802.11 Wi-Fi SAR

KDB 941225 D01 3G SAR Procedures

KDB 941225 D05 SAR for LTE Devices


KDB 616217 D04 SAR for laptop and tablets

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 2.5 mm
- Distance between probe tip and sensor center: 1 mm
- Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
- Probe linearity: ± 0.08 dB
- Axial isotropy: ± 0.01 dB
- Hemispherical Isotropy: ± 0.01 dB
- Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
- Lower detection limit: 8mW/kg

Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Jan. 10, 2023	Jan. 09, 2024
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Jun. 17, 2022	Jun. 16, 2023
☒	R&S	Wideband radio communication tester	CMW500	103917	Jun. 17, 2022	Jun. 16, 2023
☒	HP	Network Analyzer	8753D	3410J01136	Jun. 17, 2022	Jun. 16, 2023

☒	Agilent	MXG Vector Signal Generator	N5182A	MY47070317	Jun. 16, 2022	Jun. 15, 2023
☒	Agilent	Power meter	E4419B	MY45102538	Jun. 17, 2022	Jun. 16, 2023
☒	Agilent	Power sensor	E9301A	MY41495644	Jun. 17, 2022	Jun. 16, 2023
☒	Agilent	Power sensor	E9301A	US39212148	Jun. 17, 2022	Jun. 16, 2023
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023
☒	N/A	Thermometer	N/A	LES-085	Mar. 27, 2023	Mar. 26, 2026
☒	MVG	SAM Phantom	SSM2	SN 16/15 SAM119	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 16/15 MSH100	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 750	Head 750	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 835	Head 835	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1800	Head 1800	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1900	Head 1900	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 2300	Head 2300	NCR	NCR
☒	Shenzhen Tianxu	Human Simulating Liquid	Head 2450	Head 2450	NCR	NCR

	Communication Technology Co., Ltd.					
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 2600	Head 2600	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5200	Head 5200	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5800	Head 5800	NCR	NCR

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scans to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.


4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue								
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5000
Water	34.40	34.40	34.40	55.36	55.36	71.88	71.88	71.88	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	17.24
DGBE	0.00	0.00	0.00	13.84	13.84	7.99	7.99	7.99	0.00

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.



4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	40.46	0.90	21.5 °C	May. 11, 2023
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	40.85	0.91	21.5 °C	May. 22, 2023
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.94	1.41	21.7 °C	May. 12, 2023
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.26	1.46	21.5 °C	May. 23, 2023
Head 2300	2300	39.47 (37.50~41.44)	1.66 (1.58~1.74)	37.56	1.71	21.7 °C	May. 16, 2023
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.07	1.77	21.5 °C	May. 06, 2023
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.10	1.99	21.4 °C	May. 17, 2023
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	35.39	4.60	21.5 °C	May. 18, 2023
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	33.97	5.10	21.9 °C	May. 19, 2023

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W)		Measured SAR		Liquid Temp.	Delta (%)		Test Date
	(±10%)		(Normalized to 1W)					
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		1-g (±10%)	10-g (±10%)	
750MHz	8.53	5.56	8.75	5.69	21.5 °C	2.58%	2.34%	May. 11, 2023
	(7.68~9.38)	(5.01~6.11)						
835MHz	9.84	6.22	9.33	5.89	21.5 °C	-5.18%	-5.31%	May. 22, 2023
	(8.86~10.82)	(5.60~6.84)						
1800MHz	37.96	19.81	38.84	19.4	21.7 °C	2.32%	-2.07%	May. 12, 2023
	(34.17~41.75)	(17.83~21.79)						
1900MHz	40.37	20.48	43.10	20.85	21.5 °C	7.26%	1.81%	May. 23, 2023
	(36.34~44.40)	(18.44~22.52)						
2300MHz	50.65	23.55	50.35	23.59	21.7 °C	-0.59%	0.17%	May. 16, 2023
	(45.59~55.71)	(21.20~25.90)						
2450MHz	53.69	23.94	58.62	25.84	21.5 °C	9.18%	7.94%	May. 06, 2023
	(48.33~59.05)	(21.55~26.33)						
2600MHz	55.83	24.19	57.97	22.93	21.4 °C	3.83%	-5.21%	May. 17, 2023
	(50.25~61.41)	(21.78~26.60)						
5200MHz	162.34	55.42	174.89	59.9	21.5 °C	7.73%	8.08%	May. 18, 2023
	(146.11~178.57)	(49.88~60.96)						
5800MHz	178.89	59.32	163.67	54.32	21.9 °C	-8.51%	-8.43%	May. 19, 2023
	(161.01~196.77)	(53.39~65.25)						

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Tablet host platform exposure conditions

Refer to KDB616217 D04, when the modular approach is used, transmitters and modules must be initially tested for standalone operations in generic host conditions according to the following minimum test separation distance and antenna installation requirements for incorporation in the tablet platform. The separation distance required for incorporation in qualified hosts is described in KDB 447498; item 5) of section 4.1 and item 1) of section 5.2.2 etc.

- ≤ 5 mm between the antenna and user for both back surface and edge exposure conditions
- the antennas used by the host must have been tested for equipment approval or qualify for SAR test exclusion
- the antenna polarization, physical orientation, rotation and installation configurations used by the host must have been tested for compliance or qualify for test exclusion
- when the *SAR Test Exclusion Threshold* in KDB 447498 applies, a *test separation distance* of 5 mm is required to determine test exclusion for the tablet platform

The antennas embedded in tablets are typically ≤ 5 mm from the outer housing. The required antenna to user test separation distance is a “not to exceed test” distance required to apply the modular approach. Instead of the typical zero gap tablet edge test requirement between the edge of a tablet and the user, when an antenna has been tested at ≤ 5 mm according to the modular approach it can be incorporated into tablets with at least twice the tested distance from the outer housing of the tablet edge; otherwise, the tablet edge zero gap test requirement applies. When the dedicated host approach is applied, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune -	128	189	251	Tune -	128	189	251
Frequency (MHz)	up (dBm)	824.2	836.4	848.8	up (dBm)	824.2	836.4	848.8
GSM (GMSK)	34.00	33.55	33.71	33.63	24.97	24.52	24.68	24.60
GPRS(GMSK, 1 TS)	34.00	33.49	33.68	33.59	24.97	24.46	24.65	24.56
GPRS(GMSK, 2 TS)	32.00	31.59	31.62	31.40	25.98	25.57	25.60	25.38
GPRS(GMSK, 3 TS)	31.50	31.45	31.50	31.47	27.24	27.19	27.24	27.21
GPRS(GMSK, 4 TS)	27.50	27.37	27.40	27.27	24.49	24.36	24.39	24.26
EGPRS(8PSK, 1 TS)	26.50	26.20	26.19	26.45	17.47	17.17	17.16	17.42
EGPRS(8PSK, 2 TS)	25.50	25.06	25.21	25.07	19.48	19.04	19.19	19.05
EGPRS(8PSK, 3 TS)	23.50	22.78	23.45	23.00	19.24	18.52	19.19	18.74
EGPRS(8PSK, 4 TS)	21.00	20.29	20.66	20.10	17.99	17.28	17.65	17.09
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune -	512	661	810	Tune -	512	661	810
Frequency (MHz)	up (dBm)	1850.2	1880	1909.8	up (dBm)	1850.2	1880	1909.8
GSM (GMSK)	31.00	30.78	30.77	30.73	21.97	21.75	21.74	21.70
GPRS(GMSK, 1 TS)	31.00	30.73	30.75	30.68	21.97	21.70	21.72	21.65
GPRS(GMSK, 2 TS)	29.00	28.69	28.52	28.29	22.98	22.67	22.50	22.27
GPRS(GMSK, 3 TS)	27.50	27.08	26.93	26.69	23.24	22.82	22.67	22.43
GPRS(GMSK, 4 TS)	25.00	24.96	24.77	24.50	21.99	21.95	21.76	21.49
EGPRS(8PSK, 1 TS)	27.50	27.47	27.33	26.98	18.47	18.44	18.30	17.95
EGPRS(8PSK, 2 TS)	25.50	25.27	25.01	24.32	19.48	19.25	18.99	18.30
EGPRS(8PSK, 3 TS)	24.50	24.08	23.83	23.78	20.24	19.82	19.57	19.52
EGPRS(8PSK, 4 TS)	23.00	22.92	22.19	21.12	19.99	19.91	19.18	18.11

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots. The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3.01 dB

7.2. WCDMA Conducted Power

WCDMA Band 2		Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538	
Frequency (MHz)		1852.4	1880	1907.6	
RMC12.2K	24.00	23.87	23.84	23.89	
HSDPA Sub 1	24.00	23.91	23.89	23.94	
HSDPA Sub 2	24.00	23.90	23.89	23.93	
HSDPA Sub 3	24.00	23.92	23.88	23.95	
HSDPA Sub 4	24.00	23.91	23.90	23.95	
HSUPA Sub 1	24.00	23.58	23.41	23.38	
HSUPA Sub 2	24.00	23.64	23.50	23.46	
HSUPA Sub 3	23.50	23.48	23.02	23.10	
HSUPA Sub 4	24.00	23.67	23.38	23.36	
HSUPA Sub 5	23.50	23.32	23.10	23.24	
WCDMA Band 5		Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233	
Frequency (MHz)		826.4	836.4	846.6	
RMC12.2K	24.00	23.65	23.52	23.44	
HSDPA Sub 1	23.50	23.08	22.87	23.12	
HSDPA Sub 2	23.00	22.74	22.69	22.83	
HSDPA Sub 3	23.00	22.56	22.13	22.70	
HSDPA Sub 4	22.50	22.31	22.12	22.25	
HSUPA Sub 1	23.50	23.02	22.80	22.79	
HSUPA Sub 2	23.00	23.00	22.76	22.94	
HSUPA Sub 3	23.00	22.67	22.62	22.68	
HSUPA Sub 4	23.00	22.95	22.76	22.89	
HSUPA Sub 5	23.00	22.86	22.73	22.90	

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	26.50	26.06	25.79	26.16
			1	2	26.50	26.08	25.83	26.07
			1	5	26.50	26.04	25.86	26.17

				3	0	26.00	25.89	25.77	25.90
				3	1	26.00	25.92	25.68	25.93
				3	2	26.00	25.88	25.70	25.93
				6	0	25.00	24.78	24.60	24.85
			16QAM	1	0	26.00	25.83	24.11	24.82
				1	2	26.00	25.79	24.08	24.82
				1	5	26.00	25.87	24.15	24.77
				3	0	25.50	25.13	24.57	24.96
				3	1	25.50	25.18	24.57	24.88
				3	2	25.50	25.14	24.53	24.90
				6	0	24.50	24.11	23.83	23.90
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5	
LTE Band 2	3MHz	QPSK	1	0	26.50	25.91	25.84	26.09	
			1	7	26.50	25.93	25.83	26.13	
			1	14	26.50	25.86	25.77	26.10	
			8	0	25.00	24.98	24.60	24.75	
			8	4	25.00	24.98	24.66	24.93	
			8	7	25.00	24.88	24.64	24.80	
			15	0	25.00	24.85	24.64	24.79	
		16QAM	1	0	26.50	26.01	24.78	24.79	
			1	7	26.50	25.95	24.76	24.79	
			1	14	26.50	25.97	24.72	24.80	
			8	0	24.00	23.89	23.73	23.83	
			8	4	24.00	23.92	23.69	23.84	
			8	7	24.00	23.89	23.69	23.86	
			15	0	24.50	24.07	23.74	23.96	
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5	
LTE Band 2	5MHz	QPSK	1	0	26.00	25.85	25.73	25.73	
			1	12	26.00	25.84	25.75	25.72	
			1	24	26.00	25.87	25.74	25.90	
			12	0	25.00	24.95	24.70	24.92	
			12	6	25.00	24.92	24.66	24.75	

			12	11	25.00	24.95	24.75	24.86
			25	0	25.00	24.91	24.74	24.84
		16QAM	1	0	25.50	24.97	24.78	25.29
			1	12	25.50	24.99	24.75	25.33
			1	24	25.50	25.00	24.76	25.34
			12	0	24.00	23.91	23.56	23.86
			12	6	24.00	23.84	23.52	23.87
			12	11	24.00	23.92	23.52	23.77
			25	0	24.50	24.10	23.73	24.01
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	26.50	25.91	25.62	25.85
			1	24	26.50	25.89	25.64	25.99
			1	49	26.50	25.94	25.65	26.14
			25	0	25.00	24.89	24.63	24.66
			25	12	25.00	24.85	24.70	24.68
			25	24	25.00	24.97	24.78	24.84
			50	0	25.00	24.81	24.66	24.79
		16QAM	1	0	26.00	25.99	25.41	24.57
			1	24	26.00	25.94	25.38	24.69
			1	49	26.00	25.90	25.38	24.76
			25	0	24.00	24.00	23.76	23.66
			25	12	24.00	23.94	23.79	23.74
			25	24	24.00	23.93	23.74	23.87
			50	0	24.00	24.00	23.79	23.80
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	26.00	25.78	25.67	25.55
			1	37	26.00	25.81	25.78	25.46
			1	74	26.00	25.72	25.72	25.69
			36	0	25.00	24.87	24.62	24.69
			36	18	25.00	24.92	24.63	24.75
			36	37	25.00	24.80	24.65	24.86
			75	0	25.00	24.93	24.72	24.62

		16QAM	1	0	26.00	25.96	25.44	25.49
			1	37	26.00	25.95	25.45	25.48
			1	74	26.00	25.85	25.40	25.67
			36	0	24.00	23.91	23.87	23.62
			36	18	24.00	23.97	23.90	23.69
			36	37	24.00	23.96	23.90	23.77
			75	0	24.00	23.90	23.75	23.70
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	26.50	26.04	25.87	25.59
			1	49	26.50	25.99	25.83	25.62
			1	99	26.50	25.91	25.98	25.82
			50	0	25.00	24.91	24.64	24.74
			50	24	25.00	24.88	24.78	24.67
			50	49	25.00	24.87	24.57	24.62
			100	0	25.00	24.90	24.72	24.70
		16QAM	1	0	25.50	24.95	24.26	24.88
			1	49	25.50	24.89	24.32	24.86
			1	99	25.50	24.79	24.35	25.08
			50	0	24.00	23.94	23.76	23.72
			50	24	24.00	23.95	23.76	23.71
			50	49	24.00	23.90	23.73	23.77
			100	0	24.00	23.98	23.76	23.70

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	25.00	23.90	23.70	24.31
			1	2	25.00	23.91	23.72	24.34
			1	5	25.00	23.88	23.73	24.56
			3	0	24.50	23.81	23.75	24.04
			3	1	24.50	23.81	23.70	24.04
			3	2	24.50	23.77	23.69	24.02
			6	0	23.50	22.71	22.70	23.06
		16QAM	1	0	24.00	23.73	22.74	23.03
			1	2	24.00	23.72	22.68	23.06

			1	5	24.00	23.80	22.75	23.08
			3	0	23.50	23.07	22.75	22.81
			3	1	23.50	23.03	22.69	22.88
			3	2	23.50	22.98	22.72	22.98
			6	0	22.50	21.84	21.87	22.05
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.50	23.72	23.65	24.32
			1	7	24.50	23.74	23.80	24.24
			1	14	24.50	23.60	23.75	24.29
			8	0	23.50	22.84	22.64	22.89
			8	4	23.50	22.74	22.73	22.80
			8	7	23.50	22.68	22.73	23.03
			15	0	23.00	22.77	22.90	22.94
		16QAM	1	0	24.00	23.67	22.69	23.01
			1	7	24.00	23.63	22.72	22.99
			1	14	24.00	23.52	22.74	23.08
			8	0	22.50	21.54	21.72	22.01
			8	4	22.50	21.54	21.72	21.97
			8	7	22.50	21.45	21.69	22.07
			15	0	22.50	21.83	21.70	22.01
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.00	23.67	23.71	23.77
			1	12	24.00	23.61	23.71	23.85
			1	24	24.00	23.61	23.78	23.84
			12	0	23.00	22.73	22.63	22.84
			12	6	23.00	22.64	22.80	22.91
			12	11	23.00	22.60	22.67	22.87
			25	0	23.00	22.59	22.74	22.88
		16QAM	1	0	23.50	22.83	22.38	23.38
			1	12	23.50	22.74	22.35	23.40
			1	24	23.50	22.87	22.46	23.48
			12	0	22.50	21.57	21.48	22.34
			12	6	22.50	21.53	21.55	21.85
			12	11	22.50	21.51	21.61	21.83

			25	0	22.50	21.74	21.62	22.01
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	24.50	23.66	23.52	23.87
			1	24	24.50	23.63	23.62	23.96
			1	49	24.50	23.70	23.73	24.18
			25	0	23.00	22.61	22.68	22.74
			25	12	23.00	22.74	22.72	22.80
			25	24	23.00	22.76	22.80	22.86
			50	0	23.00	22.66	22.71	22.77
		16QAM	1	0	24.00	23.51	23.29	22.98
			1	24	24.00	23.55	23.30	23.08
			1	49	24.00	23.50	23.36	23.25
			25	0	22.00	21.59	21.69	21.70
			25	12	22.00	21.75	21.74	21.76
			25	24	22.00	21.73	21.78	21.96
			50	0	22.00	21.72	21.78	21.70

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	26.50	26.03	25.90	26.28
			1	12	26.50	26.02	25.91	26.26
			1	24	26.50	26.07	25.99	26.33
			12	0	25.50	24.91	25.07	25.27
			12	6	25.50	25.07	25.02	25.31
			12	11	25.50	25.00	25.13	25.37
			25	0	25.50	24.98	25.16	25.38
		16QAM	1	0	26.00	25.08	25.16	25.66
			1	12	26.00	25.10	25.19	25.66
			1	24	26.00	25.10	25.24	25.66
			12	0	24.50	23.90	24.19	24.36
			12	6	24.50	23.93	24.27	24.34
			12	11	24.50	24.01	24.19	24.42
			25	0	25.00	24.11	24.21	24.52
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		

			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	27.00	25.89	26.06	26.52
			1	24	27.00	25.85	26.11	26.67
			1	49	27.00	26.02	26.16	26.66
			25	0	25.50	24.90	24.99	25.33
			25	12	25.50	24.90	25.10	25.30
			25	24	25.50	24.96	25.13	25.34
			50	0	25.50	24.96	25.10	25.34
		16QAM	1	0	26.50	25.94	25.85	25.33
			1	24	26.50	26.02	25.83	25.36
			1	49	26.50	26.06	25.80	25.45
			25	0	24.50	24.06	24.21	24.45
			25	12	24.50	23.98	24.31	24.48
			25	24	24.50	23.96	24.30	24.47
			50	0	24.50	24.05	24.25	24.45
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	26.50	25.82	26.09	26.21
			1	37	26.50	25.88	26.14	26.26
			1	74	26.50	25.94	26.28	26.37
			36	0	25.50	24.94	24.97	25.39
			36	18	25.50	24.97	25.09	25.25
			36	37	25.50	25.00	25.15	25.41
			75	0	25.50	24.96	25.17	25.25
		16QAM	1	0	26.50	25.95	25.09	26.19
			1	37	26.50	26.01	25.21	26.25
			1	74	26.50	26.16	25.26	26.34
			36	0	24.50	24.10	24.29	24.41
			36	18	24.50	24.06	24.29	24.49
			36	37	24.50	24.17	24.38	24.45
			75	0	24.50	24.11	24.27	24.44
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band	20MHz	QPSK	1	0	26.50	25.89	26.05	26.20
			1	49	26.50	26.01	26.11	26.21

7			1	99	26.50	26.04	26.30	26.32
			50	0	25.50	24.91	25.09	25.28
			50	24	25.50	25.08	25.19	25.31
			50	49	25.50	25.10	25.09	25.38
			100	0	25.50	24.98	25.12	25.35
		16QAM	1	0	26.00	24.72	25.10	25.68
			1	49	26.00	24.81	25.21	25.79
			1	99	26.00	24.88	25.31	25.95
			50	0	25.00	24.13	24.18	24.46
			50	24	25.00	24.20	24.31	24.52
			50	49	25.00	24.28	24.28	24.51
			100	0	25.00	24.07	24.25	24.50

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	24.50	24.44	24.03	24.28
			1	2	24.50	24.42	24.06	24.20
			1	5	24.50	24.40	24.07	24.19
			3	0	24.50	24.30	24.04	24.07
			3	1	24.50	24.35	24.05	23.98
			3	2	24.50	24.35	24.01	23.96
			6	0	23.50	23.12	22.98	22.92
		16QAM	1	0	24.50	24.37	23.05	22.97
			1	2	24.50	24.30	23.08	22.92
			1	5	24.50	24.38	23.06	22.84
			3	0	24.00	23.50	22.93	22.92
			3	1	24.00	23.44	22.96	22.82
			3	2	24.00	23.54	22.98	22.89
			6	0	22.50	22.24	22.13	21.90
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.50	24.18	24.04	24.36
			1	7	24.50	24.17	24.11	24.27
			1	14	24.50	24.17	24.07	24.17
			8	0	23.50	23.25	23.07	23.03
			8	4	23.50	23.18	22.94	22.95

				8	7	23.50	23.24	23.02	22.99
				15	0	23.50	23.25	23.01	23.02
				1	0	24.50	24.23	23.21	23.11
				1	7	24.50	24.18	23.07	23.00
				1	14	24.50	24.17	23.03	22.90
				8	0	22.50	21.95	22.04	21.95
				8	4	22.50	22.08	22.02	21.99
				8	7	22.50	22.10	22.03	21.92
				15	0	22.50	22.21	21.87	22.05
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5	
LTE Band 12	5MHz	QPSK	1	0	24.50	24.23	24.10	24.00	
			1	12	24.50	24.10	24.09	23.98	
			1	24	24.50	24.06	24.17	23.79	
			12	0	23.50	23.24	23.21	23.09	
			12	6	23.50	23.14	23.04	23.01	
			12	11	23.50	23.13	22.99	22.95	
			25	0	23.50	23.14	22.97	23.03	
		16QAM	1	0	24.00	23.24	23.18	23.65	
			1	12	24.00	23.31	23.06	23.47	
			1	24	24.00	23.28	23.19	23.34	
			12	0	22.50	22.02	21.88	22.03	
			12	6	22.50	22.03	21.89	21.98	
			12	11	22.50	22.08	21.86	21.84	
			25	0	22.50	22.31	21.96	22.00	
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		23060/704	23095/707.5	23130/711	
LTE Band 12	10MHz	QPSK	1	0	24.50	24.33	24.14	24.34	
			1	24	24.50	24.21	24.09	24.37	
			1	49	24.50	24.16	24.23	24.17	
			25	0	23.50	23.24	23.20	23.03	
			25	12	23.50	23.18	23.08	23.11	
			25	24	23.50	23.22	23.15	23.00	
			50	0	23.50	23.11	23.02	23.09	
		16QAM	1	0	24.50	24.01	23.72	23.09	
			1	24	24.50	24.01	23.68	23.06	

			1	49	24.50	23.89	23.83	22.76
			25	0	22.50	22.20	22.17	22.04
			25	12	22.50	22.27	22.03	22.12
			25	24	22.50	22.05	22.16	22.11
			50	0	22.50	22.34	21.97	22.05

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	24.50	24.04	24.27	24.19
			1	12	24.50	24.03	24.28	24.06
			1	24	24.50	23.93	24.21	23.91
			12	0	23.50	23.23	23.03	23.14
			12	6	23.50	23.28	23.14	23.10
			12	11	23.50	23.06	23.09	22.99
			25	0	23.50	23.21	23.25	23.04
		16QAM	1	0	24.00	23.81	23.23	23.11
			1	12	24.00	23.73	23.34	23.10
			1	24	24.00	23.67	23.38	22.97
			12	0	22.50	22.16	21.85	21.93
			12	6	22.50	22.11	22.04	21.87
			12	11	22.50	22.05	22.04	21.80
			25	0	22.50	22.24	22.19	22.00

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	24.50	24.21	24.19	24.31
			1	24	24.50	24.10	24.13	24.40
			1	49	24.50	24.15	24.04	24.18
			25	0	23.50	23.22	23.06	23.04
			25	12	23.50	23.09	23.17	23.10
			25	24	23.50	23.28	23.05	23.08
			50	0	23.50	23.00	23.16	23.15
		16QAM	1	0	24.50	24.02	23.17	23.48
			1	24	24.50	23.75	23.21	23.64
			1	49	24.50	23.89	23.05	23.36
			25	0	22.50	22.10	22.03	22.03
			25	12	22.50	21.98	22.24	22.15

			25	24	22.50	22.17	22.14	22.08
			50	0	22.50	22.07	22.27	22.08

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37775/2572.5	38000/2595	38225/2617.5
LTE Band 38	5MHz	QPSK	1	0	26.50	26.17	26.09	26.29
			1	12	26.50	26.12	26.00	26.26
			1	24	26.50	26.18	25.95	26.33
			12	0	25.50	25.33	25.27	25.17
			12	6	25.50	25.24	25.27	25.13
			12	11	25.50	25.22	25.28	25.13
			25	0	25.50	25.23	25.30	25.00
		16QAM	1	0	26.00	25.12	25.91	24.80
			1	12	26.00	25.07	25.83	24.76
			1	24	26.00	25.09	25.89	24.66
			12	0	24.50	24.32	24.31	24.04
			12	6	24.50	24.34	24.32	24.01
			12	11	24.50	24.46	24.44	24.13
			25	0	25.00	24.39	24.55	24.26

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37800/2575	38000/2595	38200/2615
LTE Band 38	10MHz	QPSK	1	0	26.50	26.42	26.14	25.95
			1	24	26.50	26.38	26.17	26.04
			1	49	26.50	26.30	26.19	26.04
			25	0	25.50	25.25	25.19	25.09
			25	12	25.50	25.33	25.22	25.12
			25	24	25.50	25.33	25.26	25.10
			50	0	25.00	24.92	24.84	24.76
		16QAM	1	0	26.00	25.71	25.44	25.51
			1	24	26.00	25.91	25.53	25.51
			1	49	26.00	25.92	25.46	25.53
			25	0	25.00	24.33	24.55	24.35
			25	12	25.00	24.41	24.47	24.24
			25	24	25.00	24.33	24.55	24.36
			50	0	24.50	24.18	24.08	23.81

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37825/2577.5	38000/2595	38175/2612.5

LTE Band 38	15MHz	QPSK	1	0	26.50	26.35	26.12	26.11
			1	37	26.50	26.36	26.13	26.07
			1	74	26.50	26.41	26.07	26.07
			36	0	25.50	25.21	25.32	25.25
			36	18	25.50	25.27	25.17	25.09
			36	37	25.50	25.37	25.30	25.13
			75	0	25.00	24.89	24.83	24.77
		16QAM	1	0	26.00	25.79	25.59	25.31
			1	37	26.00	25.73	25.47	25.19
			1	74	26.00	25.86	25.46	25.22
			36	0	24.50	24.45	24.29	24.22
			36	18	24.50	24.36	24.30	24.21
			36	37	24.50	24.46	24.43	24.23
			75	0	24.50	23.98	24.08	23.89
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		37850/2580	38000/2595	38150/2610
LTE Band 38	20MHz	QPSK	1	0	27.00	26.16	26.57	25.97
			1	49	27.00	26.23	26.56	26.00
			1	99	27.00	26.25	26.52	25.89
			50	0	25.50	25.24	25.26	25.21
			50	24	25.50	25.20	25.16	25.05
			50	49	25.50	25.29	25.35	25.22
			100	0	25.00	24.92	24.92	24.82
		16QAM	1	0	26.00	25.24	25.41	24.99
			1	49	26.00	25.29	25.34	24.74
			1	99	26.00	25.42	25.87	24.92
			50	0	25.00	24.52	24.33	24.35
			50	24	25.00	24.55	24.21	24.22
			50	49	25.00	24.51	24.32	24.32
			100	0	24.00	23.98	23.98	23.94

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		38725/2307.5	38750/2310	38775/2312.5
LTE Band 40A	5MHz	QPSK	1	0	24.50	23.82	23.74	23.84
			1	12	24.50	24.12	24.06	24.12
			1	24	24.50	23.80	23.73	23.84
			12	0	23.00	22.90	22.87	22.88

				12	6	23.00	22.96	22.95	22.95
				12	11	23.00	22.91	22.89	22.91
				25	0	23.00	22.94	22.90	22.91
			16QAM	1	0	24.00	23.20	23.21	23.54
				1	12	24.00	23.45	23.47	23.79
				1	24	24.00	23.20	23.11	23.57
				12	0	22.50	21.94	21.99	21.95
				12	6	22.50	22.00	22.05	22.03
				12	11	22.50	21.95	21.95	21.98
				25	0	22.50	22.01	21.95	21.94
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		N/A	38750/2310	N/A	
LTE Band 40A	10MHz	QPSK	1	0	24.50	N/A	23.82	N/A	
			1	24	24.50	N/A	24.00	N/A	
			1	49	24.50	N/A	23.82	N/A	
			25	0	23.00	N/A	22.97	N/A	
			25	12	23.00	N/A	22.94	N/A	
			25	24	23.00	N/A	22.96	N/A	
			50	0	23.00	N/A	22.97	N/A	
		16QAM	1	0	24.00	N/A	23.45	N/A	
			1	24	24.00	N/A	23.62	N/A	
			1	49	24.00	N/A	23.47	N/A	
			25	0	22.50	N/A	22.07	N/A	
			25	12	22.50	N/A	22.06	N/A	
			25	24	22.50	N/A	22.05	N/A	
			50	0	22.50	N/A	22.05	N/A	

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		39175/2352.5	39200/2355	39225/2357.5
LTE Band 40B	5MHz	QPSK	1	0	24.50	23.92	23.91	23.85
			1	12	24.50	24.17	24.14	24.11
			1	24	24.50	23.90	23.86	23.82
			12	0	23.50	22.98	22.96	22.97
			12	6	23.50	23.04	23.03	23.02
			12	11	23.50	22.98	22.97	22.97
			25	0	23.00	22.98	22.97	22.98

		16QAM	1	0	24.00	23.65	23.25	23.29
			1	12	24.00	23.92	23.53	23.57
			1	24	24.00	23.61	23.24	23.28
			12	0	22.50	22.06	21.96	22.07
			12	6	22.50	22.10	22.03	22.13
			12	11	22.50	22.07	21.99	22.06
			25	0	22.50	22.03	22.06	22.04
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		N/A	39200/2355	N/A
LTE Band 40B	10MHz	QPSK	1	0	24.50	N/A	23.91	N/A
			1	24	24.50	N/A	24.12	N/A
			1	49	24.50	N/A	23.94	N/A
			25	0	23.50	N/A	23.04	N/A
			25	12	23.50	N/A	23.01	N/A
			25	24	23.50	N/A	23.02	N/A
			50	0	23.50	N/A	23.03	N/A
		16QAM	1	0	24.00	N/A	23.55	N/A
			1	24	24.00	N/A	23.73	N/A
			1	49	24.00	N/A	23.49	N/A
			25	0	22.50	N/A	22.13	N/A
			25	12	22.50	N/A	22.14	N/A
			25	24	22.50	N/A	22.13	N/A
			50	0	22.50	N/A	22.11	N/A

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		40115/2542.5	40640/2595	41165/2647.5
LTE Band 41	5MHz	QPSK	1	0	25.50	24.50	24.57	24.96
			1	12	25.50	24.56	24.62	24.95
			1	24	25.50	24.41	24.67	25.07
			12	0	24.00	23.51	23.67	23.87
			12	6	24.00	23.52	23.64	23.84
			12	11	24.00	23.49	23.61	23.76
			25	0	24.00	23.51	23.63	23.83
		16QAM	1	0	24.00	23.24	23.92	23.55
			1	12	24.00	23.14	23.96	23.50
			1	24	24.00	23.21	23.97	23.57

			12	0	23.00	22.40	22.70	22.84
			12	6	23.00	22.38	22.71	22.82
			12	11	23.00	22.50	22.69	22.75
			25	0	23.50	22.70	22.86	23.10
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		40140/2545	40640/2595	41140/2645
LTE Band 41	10MHz	QPSK	1	0	25.00	24.47	24.40	24.80
			1	24	25.00	24.55	24.57	24.82
			1	49	25.00	24.62	24.53	24.86
			25	0	24.00	23.38	23.58	23.81
			25	12	24.00	23.45	23.65	23.78
			25	24	24.00	23.58	23.61	23.82
			50	0	23.50	23.21	23.33	23.46
		16QAM	1	0	24.50	23.87	22.83	24.28
			1	24	24.50	23.82	22.91	24.11
			1	49	24.50	23.90	22.96	24.41
			25	0	23.00	22.57	22.75	22.83
			25	12	23.00	22.53	22.67	22.92
			25	24	23.00	22.66	22.81	22.84
			50	0	23.00	22.25	22.41	22.59
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		40165/2547.5	40640/2595	41115/2642.5
LTE Band 41	15MHz	QPSK	1	0	25.00	24.49	24.40	24.58
			1	37	25.00	24.54	24.50	24.63
			1	74	25.00	24.56	24.55	24.63
			36	0	24.00	23.48	23.68	23.79
			36	18	24.00	23.50	23.74	23.76
			36	37	24.00	23.49	23.74	23.82
			75	0	23.50	23.15	23.33	23.45
		16QAM	1	0	24.50	23.91	22.77	23.76
			1	37	24.50	24.07	22.82	23.92
			1	74	24.50	24.09	22.94	24.23
			36	0	23.00	22.66	22.91	22.85
			36	18	23.00	22.68	22.90	22.71
			36	37	23.00	22.57	22.96	22.75
			75	0	23.00	22.32	22.48	22.67

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		40190/2550	40640/2595	41090/2640
LTE Band 41	20MHz	QPSK	1	0	25.00	24.22	24.75	24.67
			1	49	25.00	24.43	24.77	24.74
			1	99	25.00	24.52	24.87	24.74
			50	0	24.00	23.53	23.68	23.79
			50	24	24.00	23.48	23.69	23.77
			50	49	24.00	23.56	23.73	23.81
			100	0	23.50	23.23	23.24	23.48
		16QAM	1	0	24.00	23.08	23.21	23.64
			1	49	24.00	23.25	23.28	23.25
			1	99	24.00	23.24	23.36	23.55
			50	0	23.50	22.69	22.67	23.04
			50	24	23.50	22.74	22.70	22.90
			50	49	23.50	22.78	22.80	22.95
			100	0	23.00	22.28	22.51	22.59

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	15.50	15.15
	6	2437	15.50	14.41
	11	2462	15.50	15.11
802.11g	1	2412	14.00	13.52
	6	2437	14.00	13.89
	11	2462	14.00	13.17
802.11n HT20	1	2412	12.50	12.03
	6	2437	12.50	12.30
	11	2462	12.50	11.30
802.11n HT40	3	2422	12.50	12.06
	6	2437	12.50	11.74
	9	2452	12.50	11.56

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	36	5180	10.50	9.97
	40	5200	10.50	10.13
	48	5240	10.50	9.55
802.11n HT20	36	5180	10.50	9.94
	40	5200	10.50	10.16
	48	5240	10.50	9.58
802.11n HT40	38	5190	11.00	10.77
	46	5230	11.00	10.15
802.11ac VHT20	36	5180	10.50	9.91
	40	5200	10.50	10.11
	48	5240	10.50	9.57
802.11ac VHT40	38	5190	11.00	10.73
	46	5230	11.00	10.15
802.11ac VHT80	42	5210	11.00	10.69

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	149	5745	10.00	9.33
	157	5785	10.00	9.91
	165	5825	10.00	9.62
802.11n HT20	149	5745	10.00	9.43
	157	5785	10.00	9.94
	165	5825	10.00	9.70
802.11n HT40	151	5755	11.00	10.59
	159	5795	11.00	10.19
802.11ac VHT20	149	5745	10.00	9.42
	157	5785	10.00	9.95
	165	5825	10.00	9.70
802.11ac VHT40	151	5755	10.50	10.46
	159	5795	10.50	10.17
802.11ac VHT80	155	5775	10.50	10.21

NOTE: Power measurement results of WLAN 5.8G.


7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)
--------	--------------------

	Data Rates	Tune-up (dBm)	Channel		
			0CH	39CH	78CH
	1M	5	4.22	3.02	4.75
	2M	7	6.12	5.14	6.86
	3M	7.5	6.31	5.76	7.50

BLE	Channel	Tune-up (dBm)	Output Power (dBm)	
			1M	2M
	0CH	-2.00	-2.71	-2.85
	19CH	-1.00	-1.71	-1.9
	39CH	-2.00	-2.90	-3.07

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WLAN & Bluetooth	5	5	137	63	5	147
WWAN	5	5	69	120	5	146

Note: When the minimum separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Positions for SAR tests		
Test separation distances $\leq$ 50 mm		
Exposure Positions	Tune-up Maximum power of WLAN 2.4G	
	15.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	11.14
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	11.14
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	11.14
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WLAN 5.2G	

	11.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	5.76
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	5.76
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	5.76
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WLAN 5.8G	
	11.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.08
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.08
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	6.08
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM 850	
	32.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	291.87
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	291.87
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	291.87
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM 1900	
	27.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	155.39
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	155.39
	SAR testing required?	YES

Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	155.39
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WCDMA Band 2	
	24.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.39
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.39
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	69.39
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of WCDMA Band 5	
	24.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	41.20
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	41.20
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	41.20
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 2	
	26.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	123.14
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	123.14
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	123.14
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 5	
	24.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	51.79

	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	51.79
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	51.79
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 7	
	26.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	142.94
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	142.94
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	142.94
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 12	
	24.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 17	
	24.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	47.53
	SAR testing required?	YES

Exposure Positions	Tune-up Maximum power of LTE Band 38	
	27.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	161.94
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	161.94
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	161.94
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 40A/B	
	24.50dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	77.67
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	77.67
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	77.67
	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of LTE Band 41	
	25.00dBm	
Front Side	Antenna to user(mm)	5
	SAR exclusion threshold	103.54
	SAR testing required?	YES
Back Side	Antenna to user(mm)	5
	SAR exclusion threshold	103.54
	SAR testing required?	YES
Top Side	Antenna to user(mm)	5
	SAR exclusion threshold	103.54
	SAR testing required?	YES

NOTE: Refer to section 4.3.1 of KDB 447498 D01.

Positions for SAR tests		
Test separation distances > 50 mm		
Exposure Positions	Tune-up Maximum power of WLAN 2.4G	
	15.50 dBm	35.48 mV
Left Side	Antenna to user(mm)	69

	SAR exclusion threshold(mW)	286
	SAR testing required?	NO
Right Side	Antenna to user(mm)	120
	SAR exclusion threshold(mW)	796
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	146
	SAR exclusion threshold(mW)	1056
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WLAN 5.2G	
	11.00 dBm	12.59 mV
Left Side	Antenna to user(mm)	69
	SAR exclusion threshold(mW)	256
	SAR testing required?	NO
Right Side	Antenna to user(mm)	120
	SAR exclusion threshold(mW)	766
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	146
	SAR exclusion threshold(mW)	1026
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WLAN 5.8G	
	11.00 dBm	12.59 mV
Left Side	Antenna to user(mm)	69
	SAR exclusion threshold(mW)	252
	SAR testing required?	NO
Right Side	Antenna to user(mm)	120
	SAR exclusion threshold(mW)	762
	SAR testing required?	NO
Bottom Side	Antenna to user(mm)	146
	SAR exclusion threshold(mW)	1022
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of GSM 850	
	32.00 dBm	1584.89 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	648
	SAR testing required?	YES
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	236
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	704

	SAR testing required?	YES
Exposure Positions	Tune-up Maximum power of GSM 1900	
	27.50 dBm	562.34 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	979
	SAR testing required?	YES
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	239
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1079
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WCDMA Band 2	
	24.00 dBm	251.19 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	979
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	239
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1079
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of WCDMA Band 5	
	24.00 dBm	251.19 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	648
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	236
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	704
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 2	
	26.50 dBm	446.68 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	979
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63

	SAR exclusion threshold(mW)	239
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1079
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 5	
	24.50 dBm	281.84 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	648
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	236
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	704
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 7	
	26.50 dBm	354.81 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	966
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	226
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1066
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 12	
	24.50 dBm	281.84 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	648
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	236
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	704
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 17	
	24.50 dBm	281.84 mV

Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	648
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	236
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	704
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 38	
	27.00 dBm	501.19 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	966
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	226
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1066
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 40A/B	
	24.50 dBm	281.84 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	966
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	226
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147
	SAR exclusion threshold(mW)	1066
	SAR testing required?	NO
Exposure Positions	Tune-up Maximum power of LTE Band 41	
	25.00 dBm	316.23 mV
Left Side	Antenna to user(mm)	137
	SAR exclusion threshold(mW)	966
	SAR testing required?	NO
Right Side	Antenna to user(mm)	63
	SAR exclusion threshold(mW)	226
	SAR testing required?	YES
Bottom Side	Antenna to user(mm)	147

	SAR exclusion threshold(mW)	1066
	SAR testing required?	NO

NOTE: Refer to section 4.3.1 of KDB 447498 D01.

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	7.50	5.62	5	2.480	1.76	3	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Body	7.50	5.62	5	2.48	7.5	0.235
Bluetooth	Hotspot	7.50	5.62	5	2.48	7.5	0.235

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR	Date	Plot
---------------------	-----------------	-----------	---------------------	----------------	--------------------	------------------	---------------	------	------

Body-Worn with 0mm	/Freq.		1g	10g	(±5%)	(dBm)	(dBm)	1g (W/Kg)		
Front Side	189/836.4	GPRS(GMSK 3TS)	0.408	0.222	-0.46	31.50	31.50	0.408	2023/5/22	
Back Side	189/836.4	GPRS(GMSK 3TS)	0.655	0.364	-0.49	31.50	31.50	0.655	2023/5/22	1#

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	189/836.4	GPRS(GMSK 3TS)	0.408	0.222	-0.46	31.50	31.50	0.408	2023/5/22	
Back Side	189/836.4	GPRS(GMSK 3TS)	0.655	0.364	-0.49	31.50	31.50	0.655	2023/5/22	1#
Left Side	189/836.4	GPRS(GMSK 3TS)	0.204	0.112	-2.39	31.50	31.50	0.204	2023/5/22	
Right Side	189/836.4	GPRS(GMSK 3TS)	0.207	0.109	-2.32	31.50	31.50	0.207	2023/5/22	
Top Side	189/836.4	GPRS(GMSK 3TS)	0.341	0.174	0.12	31.50	31.50	0.341	2023/5/22	
Bottom Side	189/836.4	GPRS(GMSK 3TS)	0.350	0.185	-0.11	31.50	31.50	0.350	2023/5/22	

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 3TS)	0.318	0.129	0.98	26.93	27.50	0.363	2023/5/23	
Back Side	661/1880	GPRS(GMSK 3TS)	0.525	0.218	0.71	26.93	27.50	0.599	2023/5/23	2#

NOTE: Body-Worn SAR test results of GSM1900

Test Position of	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g	Date	Plot
			1-g	10-g						

Hotspot with 0mm								(W/Kg)		
Front Side	661/1880	GPRS(GMSK 3TS)	0.318	0.129	0.98	26.93	27.50	0.363	2023/5/23	
Back Side	661/1880	GPRS(GMSK 3TS)	0.525	0.218	0.71	26.93	27.50	0.599	2023/5/23	2#
Left Side	661/1880	GPRS(GMSK 3TS)	0.171	0.067	-3.48	26.93	27.50	0.195	2023/5/23	
Right Side	661/1880	GPRS(GMSK 3TS)	0.171	0.069	-3.08	26.93	27.50	0.195	2023/5/23	
Top Side	661/1880	GPRS(GMSK 3TS)	0.285	0.115	2.39	26.93	27.50	0.325	2023/5/23	

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	9400/1880	RMC12.2K	0.468	0.201	-2.98	23.84	24.00	0.486	2023/5/23	
Back Side	9400/1880	RMC12.2K	0.778	0.344	-0.38	23.84	24.00	0.807	2023/5/23	3#
Back Side	9262/1852.4	RMC12.2K	0.745	0.320	0.12	23.87	24.00	0.768	2023/5/23	
Back Side	9538/1907.6	RMC12.2K	0.712	0.312	0.15	23.89	24.00	0.730	2023/5/23	
BackSide Repeated	9400/1880	RMC12.2K	0.760	0.340	1.54	23.84	24.00	0.789	2023/5/23	

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	9400/1880	RMC12.2K	0.468	0.201	-2.98	23.84	24.00	0.486	2023/5/23	
Back Side	9400/1880	RMC12.2K	0.778	0.344	-0.38	23.84	24.00	0.807	2023/5/23	3#
Right Side	9400/1880	RMC12.2K	0.243	0.104	2.73	23.84	24.00	0.252	2023/5/23	
Top Side	9400/1880	RMC12.2K	0.405	0.170	-1.06	23.84	24.00	0.420	2023/5/23	

Back Side	9262/1852.4	RMC12.2K	0.745	0.320	0.12	23.87	24.00	0.768	2023/5/23	
Back Side	9538/1907.6	RMC12.2K	0.712	0.312	0.15	23.89	24.00	0.730	2023/5/23	
BackSide Repeated	9400/1880	RMC12.2K	0.760	0.340	1.54	23.84	24.00	0.789	2023/5/23	

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 5

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.402	0.242	3.52	23.52	24.00	0.449	2023/5/22	
Back Side	4182/836.4	RMC12.2K	0.626	0.384	-0.38	23.52	24.00	0.699	2023/5/22	4#

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.402	0.242	3.52	23.52	24.00	0.449	2023/5/22	
Back Side	4182/836.4	RMC12.2K	0.626	0.384	-0.38	23.52	24.00	0.699	2023/5/22	4#
Right Side	4182/836.4	RMC12.2K	0.189	0.114	1.97	23.52	24.00	0.211	2023/5/22	
Top Side	4182/836.4	RMC12.2K	0.325	0.199	-2.22	23.52	24.00	0.363	2023/5/22	

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.5. SAR measurement Result of LTE Band 2

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			(W/kg)							
			1-g	10-g						
1RB										
Front Side	18900/1880	20M QPSK(1,0)	0.564	0.251	1.84	25.87	26.50	0.652	2023/5/23	
Back Side	18900/1880	20M QPSK(1,0)	0.913	0.406	-0.48	25.87	26.50	1.056	2023/5/23	8#
Back Side	18700/1860	20M	0.902	0.405	-0.24	26.04	26.50	1.003	2023/5/23	

		QPSK(1,0)								
Back Side	19100/1900	20M QPSK(1,0)	0.782	0.345	-0.12	25.59	26.50	0.964	2023/5/23	
BackSide Repeated	18900/1880	20M QPSK(1,0)	0.908	0.401	0.23	25.87	26.50	1.050	2023/5/23	
50%RB										
Front Side	18900/1880	20M QPSK(50,0)	0.301	0.143	1.90	24.64	25.00	0.327	2023/5/23	
Back Side	18900/1880	20M QPSK(50,0)	0.491	0.230	-4.56	24.64	25.00	0.533	2023/5/23	

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	18900/1880	20M QPSK(1,0)	0.564	0.251	1.84	25.87	26.50	0.652	2023/5/23	
Back Side	18900/1880	20M QPSK(1,0)	0.913	0.406	-0.48	25.87	26.50	1.056	2023/5/23	8#
Right Side	18900/1880	20M QPSK(1,0)	0.276	0.118	-2.98	25.87	26.50	0.319	2023/5/23	
Top Side	18900/1880	20M QPSK(1,0)	0.480	0.209	3.13	25.87	26.50	0.555	2023/5/23	
Back Side	18700/1860	20M QPSK(1,0)	0.902	0.405	-0.24	26.04	26.50	1.003	2023/5/23	
Back Side	19100/1900	20M QPSK(1,0)	0.782	0.345	-0.12	25.59	26.50	0.964	2023/5/23	
BackSide Repeated	18900/1880	20M QPSK(1,0)	0.908	0.401	0.23	25.87	26.50	1.050	2023/5/23	
50%RB										
Front Side	18900/1880	20M QPSK(50,0)	0.301	0.143	1.90	24.64	25.00	0.327	2023/5/23	
Back Side	18900/1880	20M QPSK(50,0)	0.491	0.230	-4.56	24.64	25.00	0.533	2023/5/23	
Right Side	18900/1880	20M QPSK(50,0)	0.140	0.060	3.20	24.64	25.00	0.152	2023/5/23	
Top Side	18900/1880	20M QPSK(50,0)	0.280	0.117	0.79	24.64	25.00	0.304	2023/5/23	
100%RB										
Back Side	18900/1880	20M QPSK(100,0)	0.312	0.187	0.23	23.76	24.00	0.330	2023/5/23	

NOTE: Hotspot SAR test results of LTE Band 2

10.1.6. SAR measurement Result of LTE Band 5

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,49)	0.420	0.250	-1.46	23.73	24.50	0.501	2023/5/22	
Back Side	20525/836.5	10M QPSK(1,49)	0.650	0.399	-0.69	23.73	24.50	0.776	2023/5/22	9#
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.250	0.144	-4.58	22.80	23.00	0.262	2023/5/22	
Back Side	20525/836.5	10M QPSK(25,24)	0.367	0.204	-4.82	22.80	23.00	0.384	2023/5/22	

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,49)	0.420	0.250	-1.46	23.73	24.50	0.501	2023/5/22	
Back Side	20525/836.5	10M QPSK(1,49)	0.650	0.399	-0.69	23.73	24.50	0.776	2023/5/22	9#
Right Side	20525/836.5	10M QPSK(1,49)	0.195	0.114	0.98	23.73	24.50	0.233	2023/5/22	
Top Side	20525/836.5	10M QPSK(1,49)	0.350	0.215	-0.73	23.73	24.50	0.418	2023/5/22	
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.250	0.144	-4.58	22.80	23.00	0.262	2023/5/22	
Back Side	20525/836.5	10M QPSK(25,24)	0.367	0.204	-4.82	22.80	23.00	0.384	2023/5/22	
Right Side	20525/836.5	10M QPSK(25,24)	0.107	0.059	-0.54	22.80	23.00	0.112	2023/5/22	
Top Side	20525/836.5	10M QPSK(25,24)	0.184	0.111	2.21	22.80	23.00	0.193	2023/5/22	

NOTE: Hotspot SAR test results of LTE Band 5

10.1.7. SAR measurement Result of LTE Band 7

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,99)	0.528	0.212	0.23	26.30	26.50	0.553	2023/5/17	
Back Side	21100/2535	20M QPSK(1,99)	0.835	0.342	-0.45	26.30	26.50	0.874	2023/5/17	10#
Back Side	20850/2510	20M QPSK(1,99)	0.781	0.290	0.12	26.04	26.50	0.868	2023/5/17	
Back Side	21350/2560	20M QPSK(1,99)	0.791	0.306	0.20	26.32	26.50	0.824	2023/5/17	
BackSide Repeated	21100/2535	20M QPSK(1,99)	0.830	0.337	1.54	26.30	26.50	0.869	2023/5/17	
50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.297	0.117	1.03	25.09	25.50	0.326	2023/5/17	
Back Side	21100/2535	20M OPSK(50,49)	0.431	0.188	3.41	25.09	25.50	0.474	2023/5/17	

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,99)	0.528	0.212	0.23	26.30	26.50	0.553	2023/5/17	
Back Side	21100/2535	20M QPSK(1,99)	0.835	0.342	-0.45	26.30	26.50	0.874	2023/5/17	10#
Right Side	21100/2535	20M QPSK(1,99)	0.258	0.103	-3.74	26.30	26.50	0.270	2023/5/17	
Top Side	21100/2535	20M QPSK(1,99)	0.440	0.171	3.75	26.30	26.50	0.461	2023/5/17	
Back Side	20850/2510	20M QPSK(1,99)	0.781	0.290	0.12	26.04	26.50	0.868	2023/5/17	
Back Side	21350/2560	20M QPSK(1,99)	0.791	0.306	0.20	26.32	26.50	0.824	2023/5/17	
BackSide Repeated	21100/2535	20M QPSK(1,99)	0.830	0.337	1.54	26.30	26.50	0.869	2023/5/17	

50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.297	0.117	1.03	25.09	25.50	0.326	2023/5/17	
Back Side	21100/2535	20M QPSK(50,49)	0.431	0.188	3.41	25.09	25.50	0.474	2023/5/17	
Right Side	21100/2535	20M QPSK(50,49)	0.134	0.058	4.16	25.09	25.50	0.147	2023/5/17	
Top Side	21100/2535	20M QPSK(50,49)	0.253	0.100	0.98	25.09	25.50	0.278	2023/5/17	

NOTE: Hotspot SAR test results of LTE Band 7

10.1.8. SAR measurement Result of LTE Band 12

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,24)	0.654	0.376	0.64	24.09	24.50	0.719	2023/5/11	
Back Side	23095/707.5	10M QPSK(1,24)	1.054	0.619	0.43	24.09	24.50	1.158	2023/5/11	
Back Side	23060/704	10M QPSK(1,24)	1.112	0.621	0.65	24.21	24.50	1.189	2023/5/11	
Back Side	23130/711	10M QPSK(1,24)	1.160	0.659	0.39	24.37	24.50	1.195	2023/5/11	11#
BackSide Repeated	23130/711	10M QPSK(1,24)	1.150	0.642	0.12	24.37	24.50	1.185	2023/5/11	
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.350	0.203	-3.80	23.20	23.50	0.375	2023/5/11	
Back Side	23095/707.5	10M QPSK(25,0)	0.628	0.323	-0.39	23.20	23.50	0.673	2023/5/11	

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,24)	0.654	0.376	0.64	24.09	24.50	0.719	2023/5/11	
Back Side	23095/707.5	10M QPSK(1,24)	1.054	0.619	0.43	24.09	24.50	1.158	2023/5/11	
Right Side	23095/707.5	10M	0.318	0.177	0.75	24.09	24.50	0.349	2023/5/11	

		QPSK(1,24)								
Top Side	23095/707.5	10M QPSK(1,24)	0.550	0.320	1.33	24.09	24.50	0.604	2023/5/11	
Back Side	23060/704	10M QPSK(1,24)	1.112	0.621	0.65	24.21	24.50	1.189	2023/5/11	
Back Side	23130/711	10M QPSK(1,24)	1.160	0.659	0.39	24.37	24.50	1.195	2023/5/11	11#
BackSide Repeated	23095/707.5	10M QPSK(1,24)	1.150	0.642	0.12	24.37	24.50	1.185	2023/5/11	
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.350	0.203	-3.80	23.20	23.50	0.375	2023/5/11	
Back Side	23095/707.5	10M QPSK(25,0)	0.628	0.323	-0.39	23.20	23.50	0.673	2023/5/11	
Right Side	23095/707.5	10M QPSK(25,0)	0.172	0.090	2.18	23.20	23.50	0.184	2023/5/11	
Top Side	23095/707.5	10M QPSK(25,0)	0.291	0.164	1.63	23.20	23.50	0.312	2023/5/11	
100%RB										
Back Side	23095/707.5	10M QPSK(25,0)	0.402	0.274	0.12	23.02	23.50	0.449	2023/5/11	

NOTE: Hotspot SAR test results of LTE Band 12

10.1.9. SAR measurement Result of LTE Band 17

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.612	0.349	3.74	24.13	24.50	0.666	2023/5/11	
Back Side	23790/710	10M QPSK(1,24)	0.982	0.573	1.70	24.13	24.50	1.069	2023/5/11	
Back Side	23780/709	10M QPSK(1,24)	0.922	0.532	-0.96	24.10	24.50	1.011	2023/5/11	
Back Side	23800/711	10M QPSK(1,24)	1.048	0.602	-0.30	24.40	24.50	1.072	2023/5/11	12#
BackSide Repeated	23800/711	10M QPSK(1,24)	1.042	0.595	0.14	24.40	24.50	1.066	2023/5/11	
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.319	0.190	0.33	23.05	23.50	0.354	2023/5/11	

Back Side	23790/710	10M QPSK(25,0)	0.508	0.323	-1.64	23.05	23.50	0.563	2023/5/11	
-----------	-----------	-------------------	-------	-------	-------	-------	-------	-------	-----------	--

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.612	0.349	3.74	24.13	24.50	0.666	2023/5/11	
Back Side	23790/710	10M QPSK(1,24)	0.982	0.573	1.70	24.13	24.50	1.069	2023/5/11	
Right Side	23790/710	10M QPSK(1,24)	0.300	0.166	2.24	24.13	24.50	0.327	2023/5/11	
Top Side	23790/710	10M QPSK(1,24)	0.515	0.288	-0.79	24.13	24.50	0.561	2023/5/11	
Back Side	23780/709	10M QPSK(1,24)	0.922	0.532	-0.96	24.10	24.50	1.011	2023/5/11	
Back Side	23800/711	10M QPSK(1,24)	1.048	0.602	-0.30	24.40	24.50	1.072	2023/5/11	12#
BackSide Repeated	23800/711	10M QPSK(1,24)	1.042	0.595	0.14	24.40	24.50	1.066	2023/5/11	
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.319	0.190	0.33	23.05	23.50	0.354	2023/5/11	
Back Side	23790/710	10M QPSK(25,0)	0.508	0.323	-1.64	23.05	23.50	0.563	2023/5/11	
Right Side	23790/710	10M QPSK(25,0)	0.152	0.087	1.04	23.05	23.50	0.169	2023/5/11	
Top Side	23790/710	10M QPSK(25,0)	0.272	0.169	3.89	23.05	23.50	0.302	2023/5/11	
100%RB										
Back Side	23790/710	10M QPSK(25,0)	0.354	0.278	0.12	23.16	23.50	0.383	2023/5/11	

NOTE: Hotspot SAR test results of LTE Band 17

10.1.10. SAR measurement Result of LTE Band 38

Test Position of Body-Worn	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date	Plot
			1-g	10-g						

with 0mm								(W/Kg)		
1RB										
Front Side	38000/2595	20M QPSK(1,0)	0.492	0.205	2.62	26.57	27.00	0.543	2023/5/17	
Back Side	38000/2595	20M QPSK(1,0)	0.772	0.321	-0.75	26.57	27.00	0.852	2023/5/17	13#
Back Side	37850/2580	20M QPSK(1,0)	0.652	0.302	0.12	26.16	27.00	0.791	2023/5/17	
Back Side	38150/2610	20M QPSK(1,0)	0.662	0.300	1.56	25.97	27.00	0.839	2023/5/17	
BackSide Repeated	38000/2595	20M QPSK(1,0)	0.752	0.315	2.01	26.57	27.00	0.830	2023/5/17	
50%RB										
Front Side	38000/2595	20M QPSK(50,49)	0.264	0.108	0.77	25.35	23.50	0.172	2023/5/17	
Back Side	38000/2595	20M QPSK(50,49)	0.414	0.170	-0.41	25.35	23.50	0.270	2023/5/17	

NOTE: Body-Worn SAR test results of LTE Band 41

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	38000/2595	20M QPSK(1,0)	0.492	0.205	2.62	26.57	27.00	0.543	2023/5/17	
Back Side	38000/2595	20M QPSK(1,0)	0.772	0.321	-0.75	26.57	27.00	0.852	2023/5/17	13#
Right Side	38000/2595	20M QPSK(1,0)	0.234	0.095	-1.96	26.57	27.00	0.258	2023/5/17	
Top Side	38000/2595	20M QPSK(1,0)	0.410	0.169	-3.41	26.57	27.00	0.453	2023/5/17	
Back Side	37850/2580	20M QPSK(1,0)	0.652	0.302	0.12	26.16	27.00	0.791	2023/5/17	
Back Side	38150/2610	20M QPSK(1,0)	0.662	0.300	1.56	25.97	27.00	0.839	2023/5/17	
BackSide Repeated	38000/2595	20M QPSK(1,0)	0.752	0.315	2.01	26.57	27.00	0.830	2023/5/17	
50%RB										
Front Side	38000/2595	20M QPSK(50,49)	0.264	0.108	0.77	25.35	23.50	0.172	2023/5/17	

Back Side	38000/2595	20M QPSK(50,49)	0.414	0.170	-0.41	25.35	23.50	0.270	2023/5/17	
Right Side	38000/2595	20M QPSK(50,49)	0.129	0.050	-1.30	25.35	23.50	0.084	2023/5/17	
Top Side	38000/2595	20M QPSK(50,49)	0.232	0.088	-4.87	25.35	23.50	0.152	2023/5/17	
100%RB										
Back Side	38000/2595	20M QPSK(100,0)	0.312	0.120	0.58	24.92	25.00	0.318	2023/5/17	

NOTE: Hotspot SAR test results of LTE Band 38

10.1.11. SAR measurement Result of LTE Band 40A

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	38750/2310	10M QPSK(1,24)	0.365	0.154	0.54	24.00	24.50	0.410	2023/5/16	
Back Side	38750/2310	10M QPSK(1,24)	0.405	0.188	-0.21	24.00	24.50	0.454	2023/5/16	15#
50%RB										
Front Side	38750/2310	10M QPSK(25,0)	0.312	0.130	1.20	22.97	23.00	0.314	2023/5/16	
Back Side	38750/2310	10M QPSK(25,0)	0.374	0.150	0.36	22.97	23.00	0.377	2023/5/16	

NOTE: Body-Worn SAR test results of LTE Band 40A

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	38750/2310	10M QPSK(1,24)	0.365	0.154	0.54	24.00	24.50	0.410	2023/5/16	
Back Side	38750/2310	10M QPSK(1,24)	0.405	0.188	-0.21	24.00	24.50	0.454	2023/5/16	15#
Right Side	38750/2310	10M QPSK(1,24)	0.291	0.132	3.02	24.00	24.50	0.327	2023/5/16	

Top Side	38750/2310	10M QPSK(1,24)	0.265	0.115	0.12	24.00	24.50	0.297	2023/5/16	
50%RB										
Front Side	38750/2310	10M QPSK(25,0)	0.312	0.130	1.20	22.97	23.00	0.314	2023/5/16	
Back Side	38750/2310	10M QPSK(25,0)	0.374	0.150	0.36	22.97	23.00	0.377	2023/5/16	
Right Side	38750/2310	10M QPSK(25,0)	0.274	0.112	0.23	22.97	23.00	0.276	2023/5/16	
Top Side	38750/2310	10M QPSK(25,0)	0.257	0.103	1.24	22.97	23.00	0.259	2023/5/16	

NOTE: Hotspot SAR test results of LTE Band 40A

10.1.12. SAR measurement Result of LTE Band 40B

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	39200/2355	10M QPSK(1,24)	0.356	0.128	0.25	24.12	24.50	0.389	2023/5/16	
Back Side	39200/2355	10M QPSK(1,24)	0.406	0.173	0.01	24.12	24.50	0.443	2023/5/16	16#
50%RB										
Front Side	39200/2355	10M QPSK(25,0)	0.289	0.102	0.12	23.04	23.50	0.321	2023/5/16	
Back Side	39200/2355	10M QPSK(25,0)	0.378	0.136	0.56	23.04	23.50	0.420	2023/5/16	

NOTE: Body-Worn SAR test results of LTE Band 40B

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	39200/2355	10M QPSK(1,24)	0.356	0.128	0.25	24.12	24.50	0.389	2023/5/16	
Back	39200/2355	10M	0.406	0.173	0.01	24.12	24.50	0.443	2023/5/16	16#

Side		QPSK(1,24)								
Right Side	39200/2355	10M QPSK(1,24)	0.245	0.091	0.65	24.12	24.50	0.267	2023/5/16	
Top Side	39200/2355	10M QPSK(1,24)	0.187	0.075	3.20	24.12	24.50	0.204	2023/5/16	
50%RB										
Front Side	39200/2355	10M QPSK(25,0)	0.289	0.102	0.12	23.04	23.50	0.321	2023/5/16	
Back Side	39200/2355	10M QPSK(25,0)	0.378	0.136	0.56	23.04	23.50	0.420	2023/5/16	
Right Side	39200/2355	10M QPSK(25,0)	0.210	0.074	0.15	23.04	23.50	0.233	2023/5/16	
Top Side	39200/2355	10M QPSK(25,0)	0.170	0.057	2.14	23.04	23.50	0.189	2023/5/16	

NOTE: Hotspot SAR test results of LTE Band 40B

10.1.13. SAR measurement Result of LTE Band 41

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	40640/2595	20M QPSK(1,99)	0.486	0.196	-3.05	24.87	25.00	0.501	2023/5/17	
Back Side	40640/2595	20M QPSK(1,99)	0.766	0.319	-0.67	24.87	25.00	0.789	2023/5/17	14#
50%RB										
Front Side	40640/2595	20M QPSK(50,0)	0.288	0.113	4.91	23.73	24.00	0.306	2023/5/17	
Back Side	40640/2595	20M QPSK(50,0)	0.386	0.182	0.62	23.73	24.00	0.411	2023/5/17	

NOTE: Body-Worn SAR test results of LTE Band 41

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										

Front Side	40640/2595	20M QPSK(1,99)	0.486	0.196	-3.05	24.87	25.00	0.501	2023/5/17	
Back Side	40640/2595	20M QPSK(1,99)	0.766	0.319	-0.67	24.87	25.00	0.789	2023/5/17	14#
Right Side	40640/2595	20M QPSK(1,99)	0.231	0.091	-3.40	24.87	25.00	0.238	2023/5/17	
Top Side	40640/2595	20M QPSK(1,99)	0.385	0.157	-1.96	24.87	25.00	0.397	2023/5/17	
50%RB										
Front Side	40640/2595	20M QPSK(50,0)	0.288	0.113	4.91	23.73	24.00	0.306	2023/5/17	
Back Side	40640/2595	20M QPSK(50,0)	0.386	0.182	0.62	23.73	24.00	0.411	2023/5/17	
Right Side	40640/2595	20M QPSK(50,0)	0.137	0.047	-0.56	23.73	24.00	0.146	2023/5/17	
Top Side	40640/2595	20M QPSK(50,0)	0.203	0.093	0.89	23.73	24.00	0.216	2023/5/17	

NOTE: Hotspot SAR test results of LTE Band 41

10.1.14. SAR measurement Result of WLAN 2.4G

Test Position of Body-Worn with 0mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.132	0.021	0.25	15.15	15.50	0.143	2023/5/06	
Back Side	1/2412	802.11b	0.172	0.061	-0.07	15.15	15.50	0.186	2023/5/06	5#

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 0mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.132	0.021	0.25	15.15	15.50	0.143	2023/5/06	
Back Side	1/2412	802.11b	0.172	0.061	-0.07	15.15	15.50	0.186	2023/5/06	5#
Top Side	1/2412	802.11b	0.071	0.016	1.23	15.15	15.50	0.077	2023/5/06	

NOTE: Hotspot SAR test results of WLAN 2.4G

10.1.15. SAR measurement Result of WLAN 5.2G

Test Position of	Test channel	Mode	SAR Value (W/kg)	Power Drift(%)	Conducted Power	Tune-up Power	Scaled SAR	Date	Plot
------------------	--------------	------	------------------	----------------	-----------------	---------------	------------	------	------

Body-Worn with 0mm	/Freq		1-g	10-g		(dBm)	(dBm)	1-g (W/Kg)		
Front Side	38/5190	802.11n HT40	0.120	0.027	0.58	10.77	11.00	0.127	2023/5/18	
Back Side	38/5190	802.11n HT40	0.149	0.035	-1.62	10.77	11.00	0.157	2023/5/18	6#

NOTE: Body-Worn SAR test results of WLAN 5.2G

Test Position of Hotspot with 0mm	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	38/5190	802.11n HT40	0.120	0.027	0.58	10.77	11.00	0.127	2023/5/18	
Back Side	38/5190	802.11n HT40	0.149	0.035	-1.62	10.77	11.00	0.157	2023/5/18	6#
Top Side	38/5190	802.11n HT40	0.064	0.020	1.14	10.77	11.00	0.067	2023/5/18	

NOTE: Hotspot SAR test results of WLAN 5.2G

10.1.16. SAR measurement Result of WLAN 5.8G

Test Position of Body-Worn with 0mm	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	151/5755	802.11n HT40	0.142	0.036	0.25	10.59	11.00	0.156	2023/5/19	
Back Side	151/5755	802.11n HT40	0.194	0.045	-0.40	10.59	11.00	0.213	2023/5/19	7#

NOTE: Body-Worn SAR test results of WLAN 5.8G

Test Position of Hotspot with 0mm	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	151/5755	802.11n HT40	0.142	0.036	0.25	10.59	11.00	0.156	2023/5/19	

Back Side	151/5755	802.11n HT40	0.194	0.045	-0.40	10.59	11.00	0.213	2023/5/19	7#
Top Side	151/5755	802.11n HT40	0.078	0.020	2.30	10.59	11.00	0.086	2023/5/19	

NOTE: Hotspot SAR test results of WLAN 5.8G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- Scalar SAR summation $< 1.6\text{W/kg}$.
- $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Body-Worn	Front Side	0.719	0.143	0.862	N/A	N/A
	Back Side	1.195	0.186	1.381	N/A	N/A
Body	Front Side	0.719	0.143	0.862	N/A	N/A
	Back Side	1.195	0.186	1.381	N/A	N/A
	Left Side	0.204	N/A	0.204	N/A	N/A
	Right Side	0.349	N/A	0.349	N/A	N/A
	Top Side	0.604	0.077	0.681	N/A	N/A
	Bottom Side	N/A	N/A	N/A	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Body-Worn	Front Side	0.719	0.156	0.875	N/A	N/A
	Back Side	1.195	0.213	1.408	N/A	N/A
Body	Front Side	0.719	0.156	0.875	N/A	N/A
	Back Side	1.195	0.213	1.408	N/A	N/A
	Left Side	0.204	N/A	0.204	N/A	N/A
	Right Side	0.349	N/A	0.349	N/A	N/A
	Top Side	0.604	0.086	0.690	N/A	N/A
	Bottom Side	N/A	N/A	N/A	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Body-Worn	Front Side	0.719	0.235	0.954	N/A	N/A

	Back Side	1.195	0.235	1.430	N/A	N/A
Body	Front Side	0.719	0.235	0.954	N/A	N/A
	Back Side	1.195	0.235	1.430	N/A	N/A
	Left Side	0.204	N/A	0.204	N/A	N/A
	Right Side	0.349	N/A	0.349	N/A	N/A
	Top Side	0.604	0.235	0.839	N/A	N/A
	Bottom Side	N/A	N/A	N/A	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2300MHz
MEASUREMENT 6 System Performance Check - 2450MHz
MEASUREMENT 7 System Performance Check - 2600MHz
MEASUREMENT 8 System Performance Check - 5200MHz
MEASUREMENT 9 System Performance Check - 5800MHz

MEASUREMENT 1


Date of measurement: 11/5/2023

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	40.462777
Relative permittivity (imaginary part)	21.618986
Conductivity (S/m)	0.900791
Variation (%)	-2.160000



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.569318
SAR 1g (W/Kg)	0.875339



MEASUREMENT 2


Date of measurement: 22/5/2023

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.50</u>

B. SAR Measurement Results


Frequency (MHz)	835.000000
Relative permittivity (real part)	40.851013
Relative permittivity (imaginary part)	19.567467
Conductivity (S/m)	0.907713
Variation (%)	-0.780000




Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg


SAR 10g (W/Kg)	0.589115
SAR 1g (W/Kg)	0.933057



3D screen shot



Hot spot position



MEASUREMENT 3


Date of measurement: 12/5/2023

A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.73</u>

B. SAR Measurement Results


Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.939563
Relative permittivity (imaginary part)	14.081262
Conductivity (S/m)	1.408126
Variation (%)	-3.570000




Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg


SAR 10g (W/Kg)	1.940138
SAR 1g (W/Kg)	3.884120



3D screen shot



Hot spot position



MEASUREMENT 4

Date of measurement: 23/5/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1900</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.255627
Relative permittivity (imaginary part)	13.812378
Conductivity (S/m)	1.457973
Variation (%)	-1.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.085012
SAR 1g (W/Kg)	4.310167



MEASUREMENT 5

Date of measurement: 16/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2300</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.92</u>


B. SAR Measurement Results

Frequency (MHz)	2300.000000
Relative permittivity (real part)	37.559409
Relative permittivity (imaginary part)	13.373406
Conductivity (S/m)	1.708824
Variation (%)	-0.280000

SURFACE SAR




VOLUME SAR




Maximum location: X=1.00, Y=1.00

SAR Peak: 7.04 W/kg


SAR 10g (W/Kg)	2.359331
SAR 1g (W/Kg)	5.035268



3D screen shot



Hot spot position



MEASUREMENT 6

Date of measurement: 6/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2450</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.070413
Relative permittivity (imaginary part)	12.978579
Conductivity (S/m)	1.766529
Variation (%)	2.500000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=-1.00

SAR Peak: 9.83 W/kg

SAR 10g (W/Kg)	2.584105
SAR 1g (W/Kg)	5.862294



MEASUREMENT 7

Date of measurement: 17/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2600</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.103742
Relative permittivity (imaginary part)	13.779907
Conductivity (S/m)	1.990431
Variation (%)	-2.070000

SURFACE SAR




VOLUME SAR




Maximum location: X=3.00, Y=-11.00

SAR Peak: 10.29 W/kg


SAR 10g (W/Kg)	2.293258
SAR 1g (W/Kg)	5.797367



3D screen shot



Hot spot position



MEASUREMENT 8


Date of measurement: 18/5/2023

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.80</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	35.392120
Relative permittivity (imaginary part)	15.926808
Conductivity (S/m)	4.601078
Variation (%)	3.790000



Maximum location: X=0.00, Y=6.00

SAR Peak: 40.06 W/kg

SAR 10g (W/Kg)	5.990217
SAR 1g (W/Kg)	17.489024



MEASUREMENT 9


Date of measurement: 19/5/2023

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.07</u>

B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative permittivity (real part)	33.971037
Relative permittivity (imaginary part)	15.828369
Conductivity (S/m)	5.100252
Variation (%)	-1.540000




Maximum location: X=0.00, Y=6.00


SAR Peak: 57.37 W/kg

SAR 10g (W/Kg)	5.432177
SAR 1g (W/Kg)	16.367230


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SA R (W/ Kg)	54.0 86	31.9 68	16.1 33	8.17 88	4.08 88	2.05 75	1.03 36	0.51 12	0.27 70	0.15 30	0.07 74	0.04 74



3D screen shot



Hot spot position



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Body
MEASUREMENT 2 GSM 1900 Body
MEASUREMENT 3 WCDMA Band 2 Body
MEASUREMENT 4 WCDMA Band 5 Body
MEASUREMENT 5 WLAN 2.4G Body
MEASUREMENT 6 WLAN 5.2G Body
MEASUREMENT 7 WLAN 5.8G Body
MEASUREMENT 8 LTE Band 2 Body
MEASUREMENT 9 LTE Band 5 Body
MEASUREMENT 10 LTE Band 7 Body
MEASUREMENT 11 LTE Band 12 Body
MEASUREMENT 12 LTE Band 17 Body
MEASUREMENT 13 LTE Band 38 Body
MEASUREMENT 14 LTE Band 41 Body
MEASUREMENT 15 LTE Band 40A Body
MEASUREMENT 16 LTE Band 40B Body

MEASUREMENT 1

Date of measurement: 22/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.766674
Relative permittivity (imaginary part)	19.593307
Conductivity (S/m)	0.910436
Variation (%)	-0.490000

SURFACE SAR





VOLUME SAR



Maximum location: X=-12.00, Y=22.00

SAR Peak: 1.11 W/kg

SAR 10g (W/Kg)	0.364272
SAR 1g (W/Kg)	0.654743



MEASUREMENT 2

Date of measurement: 23/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 8.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.342026
Relative permittivity (imaginary part)	13.830178
Conductivity (S/m)	1.444485
Variation (%)	0.710000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=-9.00

SAR Peak: 1.02 W/kg

SAR 10g (W/Kg)	0.218260
SAR 1g (W/Kg)	0.525271



MEASUREMENT 3

Date of measurement: 23/5/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band2 WCDMA1900</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.342026
Relative permittivity (imaginary part)	13.830178
Conductivity (S/m)	1.444485
Variation (%)	-0.380000

SURFACE SAR




VOLUME SAR




Maximum location: X=-10.00, Y=-9.00

SAR Peak: 1.47 W/kg


SAR 10g (W/Kg)	0.343888
SAR 1g (W/Kg)	0.777571



3D screen shot



Hot spot position



MEASUREMENT 4

Date of measurement: 22/5/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band5 WCDMA850</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.766674
Relative permittivity (imaginary part)	19.593307
Conductivity (S/m)	0.910436
Variation (%)	-0.380000

SURFACE SAR




VOLUME SAR




Maximum location: X=-20.00, Y=24.00

SAR Peak: 0.94 W/kg


SAR 10g (W/Kg)	0.384384
SAR 1g (W/Kg)	0.625767



3D screen shot



Hot spot position



MEASUREMENT 5

Date of measurement: 6/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11b ISM</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.b (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative permittivity (real part)	38.167113
Relative permittivity (imaginary part)	12.927779
Conductivity (S/m)	1.732322
Variation (%)	-0.070000

SURFACE SAR




VOLUME SAR




Maximum location: X=-7.00, Y=-39.00

SAR Peak: 0.38 W/kg


SAR 10g (W/Kg)	0.060851
SAR 1g (W/Kg)	0.172364



3D screen shot



Hot spot position



MEASUREMENT 6

Date of measurement: 18/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11n ISM</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.11n (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	5190.000000
Relative permittivity (real part)	35.306418
Relative permittivity (imaginary part)	15.733231
Conductivity (S/m)	4.536415
Variation (%)	-1.620000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=-13.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.034881
SAR 1g (W/Kg)	0.149094



MEASUREMENT 7

Date of measurement: 19/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11n ISM</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.11n (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	5755.000000
Relative permittivity (real part)	34.147815
Relative permittivity (imaginary part)	15.810142
Conductivity (S/m)	5.054854
Variation (%)	-0.400000

SURFACE SAR





VOLUME SAR



Maximum location: X=-10.00, Y=-13.00

SAR Peak: 0.69 W/kg

SAR 10g (W/Kg)	0.045127
SAR 1g (W/Kg)	0.194412



MEASUREMENT 8

Date of measurement: 23/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.342026
Relative permittivity (imaginary part)	13.830178
Conductivity (S/m)	1.444485
Variation (%)	-0.480000

SURFACE SAR




VOLUME SAR




Maximum location: X=-10.00, Y=-9.00

SAR Peak: 1.71 W/kg


SAR 10g (W/Kg)	0.406435
SAR 1g (W/Kg)	0.912937



3D screen shot



Hot spot position



MEASUREMENT 9

Date of measurement: 22/5/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 5</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	40.769264
Relative permittivity (imaginary part)	19.591967
Conductivity (S/m)	0.910482
Variation (%)	-0.690000

SURFACE SAR





VOLUME SAR



Maximum location: X=-20.00, Y=24.00

SAR Peak: 0.98 W/kg

SAR 10g (W/Kg)	0.398991
SAR 1g (W/Kg)	0.649855



MEASUREMENT 10

Date of measurement: 17/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 7</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.439041
Relative permittivity (imaginary part)	13.647807
Conductivity (S/m)	1.922066
Variation (%)	-0.450000

SURFACE SAR




VOLUME SAR




Maximum location: X=-16.00, Y=27.00

SAR Peak: 1.67 W/kg


SAR 10g (W/Kg)	0.341708
SAR 1g (W/Kg)	0.835488



3D screen shot



Hot spot position



MEASUREMENT 11

Date of measurement: 11/5/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 12</u>
Channels	<u>High</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	711.000000
Relative permittivity (real part)	41.034977
Relative permittivity (imaginary part)	21.854786
Conductivity (S/m)	0.863264
Variation (%)	0.390000

SURFACE SAR




VOLUME SAR




Maximum location: X=5.00, Y=-41.00

SAR Peak: 1.91 W/kg


SAR 10g (W/Kg)	0.658587
SAR 1g (W/Kg)	1.160115



3D screen shot



Hot spot position



MEASUREMENT 12

Date of measurement: 11/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	711.000000
Relative permittivity (real part)	41.034977
Relative permittivity (imaginary part)	21.854786
Conductivity (S/m)	0.863264
Variation (%)	-0.300000

SURFACE SAR




VOLUME SAR




Maximum location: X=-9.00, Y=3.00

SAR Peak: 1.72 W/kg


SAR 10g (W/Kg)	0.601891
SAR 1g (W/Kg)	1.047881



3D screen shot



Hot spot position



MEASUREMENT 13

Date of measurement: 17/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 38</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2595.000000
Relative permittivity (real part)	38.071140
Relative permittivity (imaginary part)	13.861607
Conductivity (S/m)	1.998382
Variation (%)	-0.750000

SURFACE SAR




VOLUME SAR




Maximum location: X=-5.00, Y=-2.00

SAR Peak: 1.52 W/kg


SAR 10g (W/Kg)	0.321172
SAR 1g (W/Kg)	0.772064



3D screen shot



Hot spot position



MEASUREMENT 14

Date of measurement: 17/5/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>LTE band 41</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2595.000000
Relative permittivity (real part)	38.071142
Relative permittivity (imaginary part)	13.861607
Conductivity (S/m)	1.998382
Variation (%)	-0.670000

SURFACE SAR




VOLUME SAR




Maximum location: X=-5.00, Y=-2.00

SAR Peak: 1.52 W/kg


SAR 10g (W/Kg)	0.318552
SAR 1g (W/Kg)	0.765708



3D screen shot



Hot spot position



MEASUREMENT 15

Date of measurement: 16/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 40A</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2310.000000
Relative permittivity (real part)	37.845971
Relative permittivity (imaginary part)	13.093176
Conductivity (S/m)	1.680291
Variation (%)	-0.210000

SURFACE SAR




VOLUME SAR




Maximum location: X=17.00, Y=-11.00

SAR Peak: 0.73 W/kg


SAR 10g (W/Kg)	0.188361
SAR 1g (W/Kg)	0.404913



3D screen shot



Hot spot position



MEASUREMENT 16

Date of measurement: 16/5/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 40B</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2355.000000
Relative permittivity (real part)	37.728771
Relative permittivity (imaginary part)	13.232376
Conductivity (S/m)	1.731236
Variation (%)	0.010000

SURFACE SAR




VOLUME SAR




Maximum location: X=20.00, Y=-12.00

SAR Peak: 0.78 W/kg


SAR 10g (W/Kg)	0.172691
SAR 1g (W/Kg)	0.405961



3D screen shot



Hot spot position



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 08/16 EPGO287
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2300 MHz Dipole - SN 03/16 DIP 2G300-358
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 13/14 WGA 33
Extended Calibration Certificate



COMOSAR E-Field Probe Calibration Report

Ref : ACR.60.1.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 08/16 EPG0287

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 01/10/2023



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	1/10/2023	
Checked by :	Jérôme Luc	Technical Manager	1/10/2023	
Approved by :	Yann Toutain	Laboratory Director	1/10/2023	

Modèle d'emploi

2023.01.10

11:27:33

+01'00'

PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	1/10/2023	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPG0287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.211 MΩ Dipole 2: R2=0.199 MΩ Dipole 3: R3=0.199 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.72	0.66	0.77

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
107	110	110

Calibration curves $e_i=f(V)$ ($i=1,2,3$) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.60.1.21.MVGB.A

Calibration curves



5.2 LINEARITY

Linearity



Linearity: +/-1.90% (+/-0.08dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.3 SENSITIVITY IN LIQUID

<u>Liquid</u>	<u>Frequency</u> <u>(MHz +/-</u> <u>100MHz)</u>	<u>ConvF</u>
HL750	750	1.49
HL850	835	1.50
HL900	900	1.61
HL1800	1800	1.73
HL1900	1900	1.91
HL2000	2000	1.97
HL2300	2300	1.92
HL2450	2450	1.98
HL2600	2600	1.87
HL3300	3300	1.79
HL3500	3500	1.85
HL3700	3700	1.79
HL3900	3900	2.07
HL4200	4200	2.21
HL4600	4600	2.25
HL4900	4900	2.05
HL5200	5200	1.80
HL5400	5400	2.05
HL5600	5600	2.16
HL5800	5800	2.07

LOWER DETECTION LIMIT: 8mW/kg




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.4 ISOTROPY

HL1800 MHz





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2022	05/2025
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2022	05/2025
Multimeter	Keithley 2000	1160271	02/2022	02/2025
Signal Generator	Rohde & Schwarz SMB	106589	04/2022	04/2025
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2022	05/2025
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.2.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 750 MHZ

SERIAL NO.: SN 03/15 DIP0G750-355

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21.MVGB.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme Luc	Technical Manager	3/1/2021	
<i>Checked by :</i>	Jérôme Luc	Technical Manager	3/1/2021	
<i>Approved by :</i>	Yann Toutain	Laboratory Director	3/1/2021	

2021.03.0
 1 13:08:18
 +01'00'

	<i>Customer Name</i>
<i>Distribution :</i>	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 03/15 DIP0G750-355
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
-------------	----------------------

Page: 5/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-23.80	-20	56.4 Ω - 0.1 j Ω

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 $\pm$ 1 %.		250.0 $\pm$ 1 %.		6.35 $\pm$ 1 %.	
450	290.0 $\pm$ 1 %.		166.7 $\pm$ 1 %.		6.35 $\pm$ 1 %.	
750	176.0 $\pm$ 1 %.	-	100.0 $\pm$ 1 %.	-	6.35 $\pm$ 1 %.	-
835	161.0 $\pm$ 1 %.		89.8 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
900	149.0 $\pm$ 1 %.		83.3 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1450	89.1 $\pm$ 1 %.		51.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1500	80.5 $\pm$ 1 %.		50.0 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1640	79.0 $\pm$ 1 %.		45.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1750	75.2 $\pm$ 1 %.		42.9 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1800	72.0 $\pm$ 1 %.		41.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1900	68.0 $\pm$ 1 %.		39.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1950	66.3 $\pm$ 1 %.		38.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2000	64.5 $\pm$ 1 %.		37.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2100	61.0 $\pm$ 1 %.		35.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2300	55.5 $\pm$ 1 %.		32.6 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2450	51.5 $\pm$ 1 %.		30.4 $\pm$ 1 %.		3.6 $\pm$ 1 %.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Head Liquid Values: ϵ_p : 41.8 σ : 0.82
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	750750 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r)		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %	41.8	0.89 ±10 %	0.82
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21.MVGB.A

2100	39.8 ±10 %		1.49 ±10 %	
2300	39.5 ±10 %		1.67 ±10 %	
2450	39.2 ±10 %		1.80 ±10 %	
2600	39.0 ±10 %		1.96 ±10 %	
3000	38.5 ±10 %		2.40 ±10 %	
3500	37.9 ±10 %		2.91 ±10 %	

7.3 MEASUREMENT RESULT



The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.53 (0.85)	5.55	5.56 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.3.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 835 MHZ

SERIAL NO.: SN 03/15 DIP0G835-347

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Jérôme Luc	Technical Manager	3/1/2021	
<i>Checked by :</i>	Jérôme Luc	Technical Manager	3/1/2021	
<i>Approved by :</i>	Yann Toutain	Laboratory Director	3/1/2021	

Made d'emploi: 2021.03.0
 1 13:09:12
 +01'00'
 PHILIPS

	<i>Customer Name</i>
<i>Distribution :</i>	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 835 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID835
Serial Number	SN 03/15 DIP0G835-347
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole