



SAR TEST REPORT

Product Name: TABLET

Model Number: TAB R11 Pro, TAB R11, TAB R11 Plus, TAB R11 Ultra,
TAB R12, TAB R12 Plus, TAB R12 Ultra, TAB R12 Pro, TAB R13, TAB R13
Plus, TAB R13 Ultra, TAB R13 Pro, TAB R15, TAB R15 Plus, TAB R15 Pro,
TAB R15 Ultra

FCC ID: 2AOKUTABR11PRO

Issued For : SHENZHEN TUGAO INTELLIGENT CO.,LTD

8th Floor, Bldg A, Jinggang Science&Technology Park,
Fuyong, Bao'an District, Shenzhen, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street,
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT25L088HA01

Sample Received Date: Nov. 12, 2025

Date of Test Nov. 12, 2025 ~Dec. 11, 2025

Date of Issue Dec. 11, 2025

Head: 0.475 W/kg

Max. SAR (1g)

Body: 1.000 W/kg

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	15
5.1 Validation System	15
5.2 Validation Result	16
6. SAR Evaluation Procedures	17
7. EUT Antenna Location Sketch	18
7.1 SAR test exclusion consider table	19
8. EUT Test Position	25
8.1 Define Two Imaginary Lines on the Handset	25
8.2 Hotspot mode exposure position condition	26
9. Uncertainty	27
9.1 Measurement Uncertainty	27
9.2 System validation Uncertainty	28
10. Conducted Power Measurement	29
10.1 Test Result	29
11. EUT and Test Setup Photo	64
11.1 EUT Photos	64
11.2 Setup Photos	67
12. SAR Result Summary	72
12.1 Head SAR	72
12.3 Repeated SAR	81
12.4 Repeated SAR measurement	82
12.5 Simultaneous Multi-band Transmission Evaluation	83
13. Equipment List	86
Appendix A. System Validation Plots	87
Appendix B. SAR Test Plots	133



Revision History

Rev.	Issue Date	Contents
00	Dec. 11, 2025	Initial Issue



TEST REPORT CERTIFICATION

Applicant SHENZHEN TUGAO INTELLIGENT CO.,LTD
Address 8th Floor, Bldg A, Jinggang Science&Technology Park,
Fuyong, Bao'an District, Shenzhen, China
Manufacture SHENZHEN TUGAO INTELLIGENT CO.,LTD
Address 8th Floor, Bldg A, Jinggang Science&Technology Park,
Fuyong, Bao'an District, Shenzhen, China
Product Name TABLET
Trademark HOTWAV
Model Number TAB R11 Pro, TAB R11, TAB R11 Plus, TAB R11 Ultra, TAB
R12, TAB R12 Plus, TAB R12 Ultra, TAB R12 Pro, TAB R13,
TAB R13 Plus, TAB R13 Ultra, TAB R13 Pro, TAB R15, TAB
R15 Plus, TAB R15 Pro, TAB R15 Ultra
Sample number LGT2511027

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
ANSI/IEEE Std. C95.1-2019 FCC 47 CFR Part 2 (2.1093) IEEE 1528: 2013	PASS

Prepared by:

Deng Deng

Deng Deng
Engineer

Approved by:

Vita Li

Vita Li
Manager





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	TABLET
Test Model Number	TAB R11 Pro
Series Number	TAB R11, TAB R11 Plus, TAB R11 Ultra, TAB R12, TAB R12 Plus, TAB R12 Ultra, TAB R12 Pro, TAB R13, TAB R13 Plus, TAB R13 Ultra, TAB R13 Pro, TAB R15, TAB R15 Plus, TAB R15 Pro, TAB R15 Ultra
Model Difference	Only Model differences
Device Category	Portable
Product stage	Production unit
RF Exposure Environment	General Population / Uncontrolled
Hardware Version	N/A
Software Version	N/A
Frequency Range	GSM 850: 824 ~ 849 MHz PCS 1900: 1850 ~ 1910 MHz WCDMA Band II: 1850 ~ 1910 MHz WCDMA Band IV: 1710 ~ 1755 MHz WCDMA Band V: 824 ~ 849 MHz LTE Band 2: 1850 ~ 1910 MHz LTE Band 4: 1710 ~ 1755 MHz LTE Band 5: 824 ~ 849 MHz LTE Band 7: 2500 ~ 2570 MHz LTE Band 12: 699 ~ 716 MHz LTE Band 13: 777 ~ 787 MHz LTE Band 17: 704 ~ 716 MHz LTE Band 25: 1850 ~ 1915 MHz LTE Band 26: 814 ~ 824 MHz / 824 ~ 849 MHz LTE Band 38: 2570 ~ 2620 MHz LTE Band 40: 2305 ~ 2315 MHz / 2350 ~ 2360 MHz LTE Band 66: 1710 ~ 1780 MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz Bluetooth: 2402 ~ 2480 MHz NFC: 13.56 MHz



Max. Reported SAR(1g): (Limit:1.6W/kg) Test distance: Head:0mm Body:0mm	Mode	Head (W/ kg)	Body Worn and Hotspot (W/ kg)
	GSM 850	0.087	0.457
	PCS 1900	0.134	0.935
	WCDMA Band II	0.120	0.849
	WCDMA Band IV	0.137	0.996
	WCDMA Band V	0.057	0.261
	LTE Band 2	0.159	0.854
	LTE Band 4	0.135	0.886
	LTE Band 5	0.083	0.799
	LTE Band 7	0.191	1.000
	LTE Band 12	0.038	0.817
	LTE Band 13	0.057	0.699
	LTE Band 17	0.104	0.260
	LTE Band 25	0.149	0.804
	LTE Band 26	0.123	0.217
	LTE Band 38	0.130	0.620
	LTE Band 40	0.183	0.726
	LTE Band 66	0.214	0.600
	2.4G WLAN	0.171	0.307
	5.2G WLAN	0.237	0.365
	5.3G WLAN	0.362	0.401
	5.6G WLAN	0.327	0.106
	5.8G WLAN	0.475	0.266
Bluetooth ^{Note1}	0.113	0.113	
NFC ^{Note2}	0.0000006	0.0000006	
1-g Sum SAR		0.689	1.401
Battery	Rated Voltage:3.89V Capacity: 10150mAh		
Description test modes	SIM 1 and SIM 2 is a chipset unit and tested as single chipset, SIM 1 is used to tested.		
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS): CCK, DQPSK, DBPSK 802.11g(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 5G WLAN: 802.11a(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK, QPSK,16-QAM,64-QAM 802.11ac (OFDM): BPSK, QPSK,16-QAM,64-QAM,256-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK NFC: ASK		
Antenna Specification	GSM/WCDMA/LTE: PIFA Antenna Bluetooth/WLAN: PIFA Antenna NFC: Coil Antenna		
Operating Mode	Maximum continuous output		
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot trans mitting at the same time		
Hotspot Mode	Support		
DTM Mode	Not Support		
Note 1: The BT value was Estimated.			
Note 2: The NFC value was Estimated.			



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	FCC Registration No.: 746540
	CAB ID: CN0136



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.4 8.0 20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.08 1.6 4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg



3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue;

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 1g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe 2225-EPGO-450 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 600 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°




Figure 1-MVG COMOSAR Dosimetric E field Probe



3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



Figure-SN 06/22 SAM 148



Figure-SN 06/22 ELLI 51

3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



LIQUID MEASUREMENT RESULTS

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2025-11-27	23.3	42	750	23.1	Permittivity	41.90	41.49	-0.98	±5
					Conductivity	0.89	0.92	3.37	±5
2025-11-30	23.4	57	750	23.2	Permittivity	41.90	42.61	1.69	±5
					Conductivity	0.89	0.90	1.12	±5
2025-11-28	23.4	43	835	23.2	Permittivity	41.50	41.68	0.43	±5
					Conductivity	0.90	0.89	-1.11	±5
2025-12-03	22.4	53	835	22.1	Permittivity	41.50	42.20	1.69	±5
					Conductivity	0.90	0.92	2.22	±5
2025-11-28	23.5	43	1800	23.2	Permittivity	40.00	40.85	2.13	±5
					Conductivity	1.40	1.39	-0.71	±5
2025-12-01	23.3	54	1800	23	Permittivity	40.00	40.65	1.63	±5
					Conductivity	1.40	1.45	3.57	±5
2025-11-27	23.3	42	1900	23	Permittivity	40.00	40.47	1.18	±5
					Conductivity	1.40	1.39	-0.71	±5
2025-12-02	23.3	55	1900	23.1	Permittivity	40.00	40.04	0.10	±5
					Conductivity	1.40	1.43	2.14	±5
2025-12-05	21.6	44	1900	21.3	Permittivity	40.00	41.08	2.70	±5
					Conductivity	1.40	1.42	1.43	±5
2025-11-26	20.1	46	2300	19.7	Permittivity	39.47	40.22	1.90	±5
					Conductivity	1.67	1.65	-1.20	±5
2025-12-04	21.9	47	2300	21.7	Permittivity	39.47	39.81	0.87	±5
					Conductivity	1.67	1.64	-1.60	±5
2025-11-22	21.4	42	2450	21.1	Permittivity	39.20	40.45	3.19	±5
					Conductivity	1.80	1.81	0.56	±5
2025-11-30	23.4	57	2450	23.1	Permittivity	39.20	40.59	3.55	±5
					Conductivity	1.80	1.83	1.67	±5
2025-11-19	23.9	50	2600	23.6	Permittivity	39.00	40.04	2.67	±5
					Conductivity	1.96	2.02	3.06	±5
2025-12-04	21.9	47	2600	21.6	Permittivity	39.00	39.29	0.74	±5
					Conductivity	1.96	1.97	0.51	±5
2025-11-17	21.7	43	5200	21.4	Permittivity	36.00	36.70	1.94	±5
					Conductivity	4.66	4.58	-1.72	±5
2025-12-05	21.7	44	5200	21.3	Permittivity	36.00	36.52	1.44	±5
					Conductivity	4.66	4.67	0.21	±5
2025-11-17	21.3	40	5400	23.1	Permittivity	35.80	36.36	1.56	±5
					Conductivity	4.86	4.83	-0.62	±5
2025-12-05	21.6	44	5400	21.3	Permittivity	35.80	36.04	0.67	±5
					Conductivity	4.86	4.91	1.03	±5



2025-11-29	21.5	51	5600	21.2	Permittivity	35.55	36.97	3.99	±5
					Conductivity	5.07	5.07	0.10	±5
2025-12.06	22.2	49	5600	21.9	Permittivity	35.55	35.85	0.84	±5
					Conductivity	5.07	5.03	-0.69	±5
2025-11-29	21.6	51	5800	21.3	Permittivity	35.30	35.68	1.08	±5
					Conductivity	5.27	5.28	0.19	±5
2025-12.06	22.3	49	5800	22	Permittivity	35.30	35.81	1.44	±5
					Conductivity	5.27	5.26	-0.19	±5




5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of $\pm 10\%$.

Date	Freq.	Power	Tested Value	Normalized SAR	Target SAR	Tolerance	Limit
	(MHz)	(mW)	(W/Kg)	(W/kg)	1g(W/kg)	(%)	(%)
2025-11-27	750	100	0.869	8.69	8.51	2.12	10
2025-11-30	750	100	0.814	8.14	8.51	-4.35	10
2025-11-28	835	100	0.964	9.64	9.63	0.10	10
2025-12-03	835	100	1.005	10.05	9.63	4.36	10
2025-11-28	1800	100	3.670	36.70	36.60	0.27	10
2025-12-01	1800	100	3.617	36.17	36.60	-1.17	10
2025-11-27	1900	100	4.034	40.34	40.20	0.35	10
2025-12-02	1900	100	4.047	40.47	40.20	0.67	10
2025-12-05	1900	100	4.035	40.35	40.20	0.37	10
2025-11-26	2300	100	5.135	51.35	49.29	4.18	10
2025-12-04	2300	100	4.830	48.30	49.29	-2.01	10
2025-11-22	2450	100	5.308	53.08	52.98	0.19	10
2025-11-30	2450	100	5.210	52.10	52.98	-1.66	10
2025-11-19	2600	100	5.637	56.37	56.15	0.39	10
2025-12-04	2600	100	5.534	55.34	56.15	-1.44	10
2025-11-17	5200	100	7.812	78.12	77.84	0.36	10
2025-12-05	5200	100	7.689	76.89	77.84	-1.22	10
2025-11-17	5400	100	7.678	76.78	76.82	-0.05	10
2025-12-05	5400	100	7.562	75.62	76.82	-1.56	10
2025-11-29	5600	100	8.124	81.24	82.15	-1.11	10
2025-12.06	5600	100	8.329	83.29	82.15	1.39	10
2025-11-29	5800	100	8.163	81.63	80.51	1.39	10
2025-12.06	5800	100	8.203	82.03	80.51	1.89	10

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan & Zoom Scan


First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



7. EUT Antenna Location Sketch

It is a TABLET, support GSM/WCDMA/LTE/WLAN/BT mode.



Antenna Separation Distance(mm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤5	≤5	67	40	≤5	208
WWAN	≤5	≤5	32	40	208	≤5

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
	Calculated Frequency (MHz)	848.8	1880	1852.4	1712.6	846.6
	Maximum Turn-up power (dBm)	32	29.5	24.3	25	24.5
	Maximum rated power(mW)	1584.89	891.25	269.15	316.23	281.84
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	32	32	32	32	32
	exclusion threshold(mW)	104.20	70.02	70.53	73.36	104.34
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	40	40	40	40	40
	exclusion threshold(mW)	130.25	87.52	88.17	91.70	130.42
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	208	208	208	208	208
	exclusion threshold(mW)	1056.88	1689.40	1690.21	1694.62	1054.78
	Testing required?	YES	NO	NO	NO	NO
Bottom Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.28	10.94	11.02	11.46	16.30
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12
	Calculated Frequency (MHz)	1860	1720	844	2510	711
	Maximum Turn-up power (dBm)	21	24.7	24.6	23.9	24.5
	Maximum rated power(mW)	125.89	295.12	288.40	245.47	281.84
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	9.47	17.79
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	9.47	17.79
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	32	32	32	32	32
	exclusion threshold(mW)	70.39	73.20	104.50	60.59	113.85
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	40	40	40	40	40
	exclusion threshold(mW)	87.99	91.50	130.62	75.74	142.31
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	208	208	208	208	208
	exclusion threshold(mW)	1689.99	1694.37	1052.29	1674.68	926.81
	Testing required?	NO	NO	NO	NO	NO
Bottom Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	11.00	11.44	16.33	9.47	17.79
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 13	LTE Band 17	LTE Band 25	LTE Band 26	LTE Band 38
	Calculated Frequency (MHz)	782	710	1860	844	2610
	Maximum Turn-up power (dBm)	24.5	24.5	24.2	24.7	24.5
	Maximum rated power(mW)	281.84	281.84	263.03	295.12	281.84
Back Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	11.00	16.33	9.28
	Testing required?	YES	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	11.00	16.33	9.28
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	32	32	32	32	32
	exclusion threshold(mW)	108.56	113.93	70.39	104.50	59.42
	Testing required?	YES	YES	YES	YES	YES
Right Edge	Separation distance (mm)	40	40	40	40	40
	exclusion threshold(mW)	135.70	142.41	87.99	130.62	74.28
	Testing required?	YES	YES	YES	YES	YES
Top Edge	Separation distance (mm)	208	208	208	208	208
	exclusion threshold(mW)	993.33	925.88	1689.99	1052.29	1672.85
	Testing required?	NO	NO	NO	NO	NO
Bottom Edge	Separation distance (mm)	5	5	5	5	5
	exclusion threshold(mW)	16.96	17.80	11.00	16.33	9.28
	Testing required?	YES	YES	YES	YES	YES



Exposure Position	Wireless Interface	LTE Band 40	LTE Band 66	BT	2.4G WLAN
	Calculated Frequency (MHz)	2310	1745	2480	2462
	Maximum Turn-up power (dBm)	24	24.6	4.3	16.3
	Maximum rated power(mW)	251.19	288.40	2.69	42.66
Back Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	9.87	11.36	9.53	9.56
	Testing required?	YES	YES	NO	YES
Front Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	9.87	11.36	9.53	9.56
	Testing required?	YES	YES	NO	YES
Left Edge	Separation distance (mm)	32	32	67	67
	exclusion threshold(mW)	63.16	72.67	265.25	265.60
	Testing required?	YES	YES	NO	NO
Right Edge	Separation distance (mm)	40	40	40	40
	exclusion threshold(mW)	78.95	90.84	76.20	76.48
	Testing required?	YES	YES	NO	NO
Top Edge	Separation distance (mm)	208	208	5	5
	exclusion threshold(mW)	1678.69	1693.55	9.53	9.56
	Testing required?	NO	NO	NO	YES
Bottom Edge	Separation distance (mm)	5	5	208	208
	exclusion threshold(mW)	9.87	11.36	1675.25	1675.60
	Testing required?	YES	YES	NO	NO



Exposure Position	Wireless Interface	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
	Calculated Frequency (MHz)	5210	5320	5700	5785
	Maximum Turn-up power (dBm)	13.5	14.3	14.5	15
	Maximum rated power(mW)	22.39	26.92	28.18	31.62
Back Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.57	6.50	6.28	6.24
	Testing required?	YES	YES	YES	YES
Front Side	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.57	6.50	6.28	6.24
	Testing required?	YES	YES	YES	YES
Left Edge	Separation distance (mm)	67	67	67	67
	exclusion threshold(mW)	235.72	235.03	232.83	232.36
	Testing required?	NO	NO	NO	NO
Right Edge	Separation distance (mm)	40	40	40	40
	exclusion threshold(mW)	52.57	52.03	50.26	49.89
	Testing required?	NO	NO	NO	NO
Top Edge	Separation distance (mm)	5	5	5	5
	exclusion threshold(mW)	6.57	6.50	6.28	6.24
	Testing required?	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	208	208	208	208
	exclusion threshold(mW)	1645.72	1645.03	1642.83	1642.36
	Testing required?	NO	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm, 25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance $\leq 50\text{mm}$ are determined by:

$$\frac{[(\text{max.power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance,}]}{}$$



mm)]*[$\sqrt{f(\text{GHz})}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, $f(\text{GHz})$ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare


5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - a)[threshold at 50mm in step 1]+(test separation distance -50mm)*($f(\text{MHz})/150$)]mW, at 100 MHz to 1500 MHz
 - b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at > 1500MHz and $\leq 6\text{GHz}$
6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.

8. EUT Test Position

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

8.1 Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

- 1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- 2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost





Title Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	2.41	2.41	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	1.81	1.81	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device holder uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR Drift Measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		K				20.95	20.69	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	0.71	0.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions- reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of Experimental Source from Numerical Source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR Drift Measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Distance	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		K				20.32	20.06	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	31.68	31.83	31.96	29.07	29.32	29.04
GPRS (GMSK, 1-Slot)	31.65	31.81	31.93	29.08	29.33	29.04
GPRS (GMSK, 2-Slot)	30.98	31.15	31.27	28.40	28.63	28.36
GPRS (GMSK, 3-Slot)	29.05	29.16	29.30	26.37	26.60	26.30
GPRS (GMSK, 4-Slot)	28.01	28.13	28.23	25.26	25.48	25.21
EGPRS (8PSK, 1-Slot)	32.27	31.84	32.65	29.00	28.81	28.81
EGPRS (8PSK, 2-Slot)	31.48	31.17	31.48	28.30	28.31	28.11
EGPRS (8PSK, 3-Slot)	30.67	29.71	30.02	26.54	26.70	26.42
EGPRS (8PSK, 4-Slot)	29.57	28.96	29.57	25.83	25.74	25.51
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	22.65	22.80	22.93	20.04	20.29	20.01
GPRS (GMSK, 1-Slot)	22.62	22.78	22.90	20.05	20.30	20.01
GPRS (GMSK, 2-Slot)	24.96	25.13	25.25	22.38	22.61	22.34
GPRS (GMSK, 3-Slot)	24.79	24.90	25.04	22.11	22.34	22.04
GPRS (GMSK, 4-Slot)	25.00	25.12	25.22	22.25	22.47	22.20
EGPRS (8PSK, 1-Slot)	23.24	22.81	23.62	19.97	19.78	19.78
EGPRS (8PSK, 2-Slot)	25.46	25.15	25.46	22.28	22.29	22.09
EGPRS (8PSK, 3-Slot)	26.41	25.45	25.76	22.28	22.44	22.16
EGPRS (8PSK, 4-Slot)	26.56	25.95	26.56	22.82	22.73	22.50
Remark: 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						



WCDMA

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1450	1513	4132	4182	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.4	846.6
RMC 12.2Kbps	24.15	24.05	23.57	24.73	24.73	24.71	24.03	24.08	24.26
HSDPA Subtest-1	23.23	23.12	22.62	23.81	23.79	23.75	23.09	23.08	23.28
HSDPA Subtest-2	22.79	22.38	21.77	23.56	23.31	23.58	22.28	22.77	22.94
HSDPA Subtest-3	21.77	21.55	21.41	22.14	22.1	21.93	21.91	21.63	21.93
HSDPA Subtest-4	21.45	21.63	21.21	22.05	22.31	22.41	21.68	21.66	21.62
HSUPA Subtest-1	21.73	22.88	22.41	23.21	23.61	23.58	21.96	22.92	23.18
HSUPA Subtest-2	23.01	22.95	22.31	23.68	23.65	23.6	22.92	23.06	23.27
HSUPA Subtest-3	21.51	21.9	20.95	21.85	22.64	22.7	21.55	21.88	22.13
HSUPA Subtest-4	23.19	23.03	22.56	23.77	23.78	23.76	23.08	23.09	23.29
HSUPA Subtest-5	21.75	22.36	21.91	22.14	23.08	23.07	21.64	22.28	22.43

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM (db)	MPR (db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$.For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	0.34	1.08
	39	2441	1.20	1.32
	78	2480	1.34	1.36
$\pi/4$ -QPSK(2Mbps)	0	2402	2.60	1.82
	39	2441	3.49	2.23
	78	2480	3.70	2.34
8DPSK(3Mbps)	0	2402	3.12	2.05
	39	2441	3.91	2.46
	78	2480	4.15	2.60

BLE				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	0.77	1.19
	19	2440	0.03	1.01
	39	2480	-0.31	0.93
GFSK(2Mbps)	0	2402	0.80	1.20
	19	2440	0.09	1.02
	39	2480	-0.26	0.94

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
802.11b	1	2412	15.13	32.58
	7	2437	15.6	36.31
	11	2462	16.13	41.02
802.11g	1	2412	14.67	29.31
	7	2437	15.22	33.27
	11	2462	15.63	36.56
802.11n-HT20	1	2412	14.79	30.13
	7	2437	15.22	33.27
	11	2462	15.65	36.73
802.11n-HT40	3	2422	15.07	32.14
	6	2437	15.11	32.43
	9	2452	15.41	34.75



5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	13.43	22.03
	40	5200	13.21	20.94
	48	5240	13.23	21.04
802.11n-HT20	36	5180	12.12	16.29
	40	5200	12.07	16.11
	48	5240	12.03	15.96
802.11n-HT40	38	5190	13.43	22.03
	46	5230	13.06	20.23
802.11ac-VHT20	36	5180	12.13	16.33
	40	5200	12	15.85
	48	5240	11.95	15.67
802.11ac-VHT40	38	5190	13.33	21.53
	46	5230	13.06	20.23
802.11ac-VHT80	42	5210	13.44	22.08

5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	52	5260	13.69	23.39
	60	5300	14.12	25.82
	64	5320	14.19	26.24
802.11n-HT20	52	5260	12.55	17.99
	60	5300	12.76	18.88
	64	5320	12.87	19.36
802.11n-HT40	54	5270	13.5	22.39
	62	5310	13.12	20.51
802.11ac-VHT20	52	5260	12.43	17.50
	60	5300	12.81	19.10
	64	5320	12.89	19.45
802.11ac-VHT40	54	5270	13.45	22.13
	62	5310	13.09	20.37
802.11ac-VHT80	58	5290	13.69	23.39

NFC		
Mode	Field strength(dBuV/m)	ERP(dBm)
NFC	57.83	-37.37

Note: The power of this EUT NFC is -37.37dBm (0.00018mw), this power is less than the defined low power exclusion level (Pmax: 39 mW), so NFC is exemption.



5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	100	5500	14.07	25.53
	116	5580	13.56	22.70
	140	5700	14.45	27.86
802.11n-HT20	100	5500	12.81	19.10
	116	5580	12.29	16.94
	140	5700	12.02	15.92
802.11n-HT40	102	5510	13.47	22.23
	110	5550	13.36	21.68
	134	5670	12.9	19.50
802.11ac-VHT20	100	5500	12.84	19.23
	116	5580	12.27	16.87
	140	5700	12.33	17.10
802.11ac-VHT40	102	5510	13.52	22.49
	110	5550	13.34	21.58
	134	5670	12.94	19.68
802.11ac-VHT80	106	5530	14.11	25.76
	122	5610	13.62	23.01

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	149	5745	14.62	28.97
	157	5785	14.63	29.04
	165	5825	14.42	27.67
802.11n-HT20	149	5745	13.27	21.23
	157	5785	13.34	21.58
	165	5825	13.16	20.70
802.11n-HT40	151	5755	14.25	26.61
	159	5795	13.96	24.89
802.11ac-VHT20	149	5745	13.29	21.33
	157	5785	13.43	22.03
	165	5825	13.14	20.61
802.11ac-VHT40	151	5755	14.26	26.67
	159	5795	13.95	24.83
802.11ac-VHT80	155	5775	14.44	27.80



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	20.82	20.84	20.24
1.4	1	2		20.80	20.84	20.26
1.4	1	5		20.79	20.84	20.23
1.4	3	0		20.80	20.65	20.21
1.4	3	1		20.79	20.65	20.22
1.4	3	2		20.77	20.66	20.21
1.4	6	0		19.77	19.66	19.20
1.4	1	0	16-QAM	19.74	19.92	19.47
1.4	1	2		19.74	19.90	19.44
1.4	1	5		19.72	19.93	19.47
1.4	3	0		19.93	19.81	19.45
1.4	3	1		19.97	19.84	19.45
1.4	3	2		19.93	19.84	19.42
1.4	6	0		18.91	18.83	18.35
3	1	0	QPSK	20.82	20.84	20.24
3	1	7		20.80	20.84	20.26
3	1	14		20.79	20.84	20.23
3	8	0		20.80	20.65	20.21
3	8	4		20.79	20.65	20.22
3	8	7		20.77	20.66	20.21
3	15	0		19.77	19.66	19.20
3	1	0	16-QAM	19.74	19.92	19.47
3	1	7		19.74	19.90	19.44
3	1	14		19.72	19.93	19.47
3	8	0		19.93	19.81	19.45
3	8	4		19.97	19.84	19.45
3	8	7		19.93	19.84	19.42
3	15	0		18.91	18.83	18.35



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.83	20.66	20.37
5	1	12		20.78	20.78	20.34
5	1	24		20.73	20.82	20.38
5	12	0		19.75	19.68	19.27
5	12	6		19.74	19.73	19.29
5	12	11		19.79	19.78	19.38
5	25	0		19.86	19.80	19.38
5	1	0	16-QAM	20.21	20.26	19.73
5	1	12		20.17	20.36	19.71
5	1	24		20.11	20.40	19.78
5	12	0		18.83	18.71	18.25
5	12	6		18.85	18.75	18.30
5	12	11		18.90	18.80	18.38
5	25	0		18.80	18.70	18.38
10	1	0	QPSK	20.80	20.62	20.51
10	1	24		20.69	20.77	20.45
10	1	49		20.57	20.83	20.39
10	25	0		19.61	19.64	19.38
10	25	12		19.71	19.71	19.38
10	25	24		19.74	19.84	19.49
10	50	0		19.69	19.71	19.46
10	1	0	16-QAM	20.26	19.76	19.38
10	1	24		20.15	19.93	19.30
10	1	49		20.01	20.00	19.27
10	25	0		18.73	18.62	18.38
10	25	12		18.76	18.69	18.34
10	25	24		18.77	18.84	18.49
10	50	0		18.66	18.73	18.38



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.78	20.58	20.58
15	1	37		20.65	20.80	20.45
15	1	74		20.51	20.77	20.41
15	36	0		19.58	19.62	19.52
15	36	18		19.61	19.70	19.43
15	36	39		19.56	19.84	19.45
15	75	0		19.63	19.80	19.51
15	1	0	16-QAM	20.23	19.75	19.68
15	1	38		20.07	19.94	19.57
15	1	75		19.97	19.96	19.46
15	36	0		18.64	18.69	18.51
15	36	18		18.64	18.77	18.39
15	36	39		18.56	18.90	18.41
15	75	0		18.56	18.71	18.50
20	1	0	QPSK	20.90	20.56	20.61
20	1	49		20.65	20.82	20.48
20	1	99		20.65	20.75	20.40
20	50	0		19.55	19.63	19.81
20	50	24		19.62	19.77	19.52
20	50	49		19.39	20.01	19.57
20	100	0		19.50	19.86	19.69
20	1	0	16-QAM	20.12	19.82	20.00
20	1	49		19.91	20.07	19.83
20	1	99		19.91	20.04	19.82
20	50	0		18.52	18.64	18.87
20	50	24		18.62	18.79	18.60
20	50	49		18.40	19.05	18.61
20	100	0		18.46	18.84	18.70



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.23	24.21	24.31
1.4	1	2		24.26	24.23	24.38
1.4	1	5		24.24	24.21	24.33
1.4	3	0		24.16	24.18	24.30
1.4	3	1		24.14	24.19	24.27
1.4	3	2		24.20	24.19	24.30
1.4	6	0		23.22	23.22	23.31
1.4	1	0	16-QAM	23.40	23.47	23.21
1.4	1	2		23.40	23.46	23.23
1.4	1	5		23.41	23.49	23.26
1.4	3	0		23.39	23.44	23.42
1.4	3	1		23.37	23.42	23.40
1.4	3	2		23.36	23.43	23.42
1.4	6	0		22.40	22.40	22.44
3	1	0	QPSK	24.23	24.23	24.19
3	1	7		24.26	24.27	24.24
3	1	14		24.26	24.26	24.24
3	8	0		23.21	23.23	23.28
3	8	4		23.19	23.19	23.28
3	8	7		23.18	23.22	23.29
3	15	0		23.20	23.21	23.29
3	1	0	16-QAM	23.14	23.68	23.45
3	1	7		23.18	23.71	23.49
3	1	14		23.12	23.69	23.48
3	8	0		22.24	22.22	22.28
3	8	4		22.19	22.21	22.30
3	8	7		22.20	22.24	22.29
3	15	0		22.27	22.25	22.22



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.23	24.37	24.32
5	1	12		24.28	24.39	24.39
5	1	24		24.21	24.40	24.42
5	12	0		23.28	23.27	23.32
5	12	6		23.25	23.27	23.31
5	12	11		23.26	23.28	23.35
5	25	0		23.29	23.33	23.37
5	1	0	16-QAM	23.57	23.84	23.72
5	1	12		23.64	23.85	23.80
5	1	24		23.65	23.82	23.85
5	12	0		22.32	22.27	22.28
5	12	6		22.27	22.25	22.28
5	12	11		22.28	22.28	22.31
5	25	0		22.26	22.24	22.37
10	1	0	QPSK	24.26	24.23	24.36
10	1	24		24.26	24.28	24.36
10	1	49		24.25	24.34	24.42
10	25	0		23.31	23.29	23.33
10	25	12		23.27	23.30	23.29
10	25	24		23.29	23.34	23.33
10	50	0		23.30	23.33	23.31
10	1	0	16-QAM	23.72	23.45	23.25
10	1	24		23.69	23.51	23.24
10	1	49		23.72	23.52	23.32
10	25	0		22.31	22.25	22.29
10	25	12		22.25	22.26	22.28
10	25	24		22.27	22.31	22.32
10	50	0		22.28	22.32	22.28



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.31	24.23	24.40
15	1	37		24.30	24.36	24.42
15	1	74		24.28	24.36	24.46
15	36	0		23.29	23.25	23.30
15	36	18		23.26	23.29	23.31
15	36	39		23.27	23.33	23.31
15	75	0		23.29	23.33	23.33
15	1	0	16-QAM	23.72	23.43	23.42
15	1	38		23.76	23.59	23.51
15	1	75		23.75	23.59	23.49
15	36	0		22.33	22.31	22.26
15	36	18		22.30	22.34	22.28
15	36	39		22.31	22.40	22.28
15	75	0		22.31	22.33	22.39
20	1	0	QPSK	24.36	24.26	24.34
20	1	49		24.40	24.35	24.43
20	1	99		24.49	24.37	24.46
20	50	0		23.35	23.32	23.35
20	50	24		23.33	23.38	23.40
20	50	49		23.32	23.42	23.38
20	100	0		23.36	23.38	23.40
20	1	0	16-QAM	23.56	23.55	23.76
20	1	49		23.61	23.70	23.78
20	1	99		23.67	23.72	23.87
20	50	0		22.34	22.35	22.38
20	50	24		22.31	22.40	22.42
20	50	49		22.30	22.44	22.43
20	100	0		22.34	22.36	22.35



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.06	24.31	24.25
1.4	1	2		24.09	24.32	24.23
1.4	1	5		24.08	24.33	24.20
1.4	3	0		24.04	24.18	24.24
1.4	3	1		24.05	24.20	24.22
1.4	3	2		24.04	24.22	24.22
1.4	6	0		23.07	23.21	23.22
1.4	1	0	16-QAM	23.01	23.46	23.50
1.4	1	2		23.00	23.44	23.46
1.4	1	5		23.02	23.46	23.51
1.4	3	0		23.17	23.40	23.46
1.4	3	1		23.18	23.38	23.48
1.4	3	2		23.20	23.38	23.46
1.4	6	0		22.26	22.40	22.43
3	1	0	QPSK	24.05	24.22	24.23
3	1	7		24.11	24.23	24.25
3	1	14		24.10	24.22	24.21
3	8	0		23.07	23.19	23.28
3	8	4		23.01	23.19	23.27
3	8	7		22.98	23.24	23.32
3	15	0		23.09	23.20	23.31
3	1	0	16-QAM	23.00	23.68	23.51
3	1	7		23.02	23.66	23.51
3	1	14		22.98	23.69	23.49
3	8	0		22.12	22.24	22.30
3	8	4		22.06	22.26	22.28
3	8	7		22.02	22.29	22.32
3	15	0		22.13	22.27	22.24



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.16	24.29	24.34
5	1	12		24.18	24.26	24.29
5	1	24		24.38	24.37	24.38
5	12	0		23.18	23.16	23.37
5	12	6		23.13	23.22	23.28
5	12	11		23.29	23.40	23.32
5	25	0		23.22	23.27	23.36
5	1	0	16-QAM	23.45	23.83	23.70
5	1	12		23.34	23.87	23.79
5	1	24		23.51	23.83	23.76
5	12	0		22.19	22.23	22.33
5	12	6		22.13	22.28	22.28
5	12	11		22.11	22.31	22.32
5	25	0		22.14	22.22	22.41
10	1	0	QPSK	23.99	24.38	24.34
10	1	24		23.98	24.38	24.41
10	1	49		24.06	24.37	24.42
10	25	0		23.19	23.19	23.37
10	25	12		23.12	23.24	23.31
10	25	24		23.09	23.28	23.33
10	50	0		23.14	23.31	23.40
10	1	0	16-QAM	23.07	23.72	23.52
10	1	24		23.12	23.74	23.48
10	1	49		23.26	23.78	23.55
10	25	0		22.19	22.23	22.39
10	25	12		22.14	22.32	22.31
10	25	24		22.25	22.41	22.29
10	50	0		22.19	22.26	22.41



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.48	22.74	22.57
5	1	12		23.52	22.80	22.32
5	1	24		23.51	22.75	22.47
5	12	0		22.44	21.75	21.70
5	12	6		22.44	21.77	21.66
5	12	11		22.39	21.80	21.68
5	25	0		22.48	21.82	21.71
5	1	0	16-QAM	22.91	22.05	22.08
5	1	12		22.89	22.20	21.87
5	1	24		22.89	22.23	21.99
5	12	0		21.42	20.83	20.73
5	12	6		21.42	20.84	20.71
5	12	11		21.39	20.89	20.70
5	25	0		21.51	20.79	20.66
10	1	0	QPSK	23.49	22.79	22.73
10	1	24		23.43	22.79	22.29
10	1	49		23.45	22.92	22.29
10	25	0		22.50	21.78	21.74
10	25	12		22.47	21.83	21.61
10	25	24		22.44	21.89	21.51
10	50	0		22.49	21.84	21.64
10	1	0	16-QAM	22.89	22.00	21.62
10	1	24		22.80	22.01	21.38
10	1	49		22.81	22.08	21.33
10	25	0		21.50	20.77	20.73
10	25	12		21.44	20.81	20.72
10	25	24		21.44	20.89	20.73
10	50	0		21.48	20.84	20.69



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.54	22.80	22.79
15	1	37		23.47	22.96	22.73
15	1	74		23.29	23.06	22.24
15	36	0		22.48	21.77	21.76
15	36	18		22.43	21.82	21.71
15	36	39		22.41	21.88	21.63
15	75	0		22.44	21.88	21.77
15	1	0	16-QAM	22.64	22.13	21.99
15	1	38		22.62	22.30	21.86
15	1	75		22.50	22.37	21.72
15	36	0		21.49	20.80	20.83
15	36	18		21.44	20.87	20.79
15	36	39		21.39	20.94	20.80
15	75	0		21.50	20.88	20.77
20	1	0	QPSK	23.61	22.78	22.74
20	1	49		23.54	22.95	22.48
20	1	99		23.45	22.98	22.31
20	50	0		22.52	21.82	21.91
20	50	24		22.47	21.93	21.83
20	50	49		22.40	21.98	21.67
20	100	0		22.49	21.90	21.86
20	1	0	16-QAM	22.96	21.96	22.09
20	1	49		22.78	22.10	22.03
20	1	99		22.68	22.24	21.67
20	50	0		21.58	20.79	20.92
20	50	24		21.52	20.90	20.84
20	50	49		21.42	20.96	20.79
20	100	0		21.47	20.89	20.85



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.27	24.27	24.11
1.4	1	2		24.30	24.31	24.16
1.4	1	5		24.31	24.30	24.14
1.4	3	0		24.23	24.11	24.14
1.4	3	1		24.24	24.12	24.11
1.4	3	2		24.25	24.16	24.14
1.4	6	0		23.25	23.13	23.18
1.4	1	0	16-QAM	23.14	23.41	23.38
1.4	1	2		23.18	23.41	23.39
1.4	1	5		23.26	23.41	23.43
1.4	3	0		23.38	23.32	23.35
1.4	3	1		23.38	23.31	23.37
1.4	3	2		23.37	23.35	23.38
1.4	6	0		22.37	22.36	22.35
3	1	0	QPSK	24.17	24.22	24.17
3	1	7		24.16	24.22	24.18
3	1	14		24.10	24.28	24.18
3	8	0		23.19	23.15	23.22
3	8	4		23.24	23.15	23.16
3	8	7		23.20	23.20	23.13
3	15	0		23.23	23.19	23.19
3	1	0	16-QAM	23.41	23.13	23.54
3	1	7		23.38	23.09	23.58
3	1	14		23.37	23.10	23.59
3	8	0		22.12	22.16	22.22
3	8	4		22.18	22.12	22.14
3	8	7		22.21	22.18	22.10
3	15	0		22.11	22.23	22.17



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.35	24.29	24.16
5	1	12		24.34	24.25	24.26
5	1	24		24.32	24.29	24.25
5	12	0		23.14	23.23	23.22
5	12	6		23.21	23.20	23.23
5	12	11		23.21	23.27	23.16
5	25	0		23.17	23.29	23.19
5	1	0	16-QAM	23.85	23.66	23.49
5	1	12		23.72	23.70	23.47
5	1	24		23.74	23.63	23.62
5	12	0		22.18	22.21	22.27
5	12	6		22.23	22.20	22.23
5	12	11		22.19	22.24	22.15
5	25	0		22.19	22.28	22.19
10	1	0	QPSK	24.27	24.23	24.32
10	1	24		24.24	24.24	24.29
10	1	49		24.26	24.28	24.36
10	25	0		23.30	23.35	23.17
10	25	12		23.34	23.23	23.26
10	25	24		23.23	23.32	23.12
10	50	0		23.32	23.34	23.16
10	1	0	16-QAM	23.78	23.49	23.22
10	1	24		23.66	23.43	23.19
10	1	49		23.75	23.47	23.32
10	25	0		22.25	22.35	22.12
10	25	12		22.18	22.21	22.21
10	25	24		22.21	22.37	22.10
10	50	0		22.29	22.37	22.08



LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.18	24.09	24.11
5	1	12		24.17	24.12	24.11
5	1	24		24.20	24.18	24.15
5	12	0		23.14	23.17	23.11
5	12	6		23.10	23.10	23.08
5	12	11		23.08	23.12	23.15
5	25	0		23.16	23.18	23.18
5	1	0	16-QAM	23.71	23.55	23.50
5	1	12		23.69	23.53	23.48
5	1	24		23.74	23.57	23.51
5	12	0		22.17	22.11	22.15
5	12	6		22.14	22.05	22.17
5	12	11		22.08	22.10	22.22
5	25	0		22.14	22.21	22.13
10	1	0	QPSK	/	24.21	/
10	1	24		/	24.20	/
10	1	49		/	24.26	/
10	25	0		/	23.15	/
10	25	12		/	23.07	/
10	25	24		/	23.18	/
10	50	0		/	23.16	/
10	1	0	16-QAM	/	23.32	/
10	1	24		/	23.32	/
10	1	49		/	23.36	/
10	25	0		/	22.14	/
10	25	12		/	22.05	/
10	25	24		/	22.16	/
10	50	0		/	22.19	/



LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.25	24.14	24.13
5	1	12		24.20	24.17	24.14
5	1	24		24.19	24.18	24.22
5	12	0		23.25	23.07	23.14
5	12	6		23.14	23.06	23.11
5	12	11		23.13	23.15	23.10
5	25	0		23.25	23.21	23.15
5	1	0	16-QAM	23.67	23.54	23.53
5	1	12		23.70	23.57	23.46
5	1	24		23.78	23.56	23.54
5	12	0		22.26	22.09	22.18
5	12	6		22.16	22.16	22.18
5	12	11		22.17	22.13	22.07
5	25	0		22.17	22.17	22.07
10	1	0	QPSK	24.12	24.23	24.18
10	1	24		24.18	24.21	24.16
10	1	49		24.13	24.28	24.27
10	25	0		23.15	23.10	23.00
10	25	12		23.14	23.15	23.15
10	25	24		23.18	23.15	23.15
10	50	0		23.19	23.16	23.10
10	1	0	16-QAM	23.34	23.07	23.65
10	1	24		23.37	23.06	23.63
10	1	49		23.37	23.20	23.68
10	25	0		22.13	22.10	22.11
10	25	12		22.12	22.14	22.18
10	25	24		22.19	22.12	22.09
10	50	0		22.21	22.08	22.06



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.86	23.69	23.18
1.4	1	2		23.85	23.71	23.19
1.4	1	5		23.82	23.70	23.17
1.4	3	0		23.84	23.57	23.20
1.4	3	1		23.82	23.57	23.17
1.4	3	2		23.84	23.61	23.20
1.4	6	0		22.83	22.60	22.22
1.4	1	0	16-QAM	22.80	22.82	22.42
1.4	1	2		22.80	22.78	22.37
1.4	1	5		22.80	22.85	22.42
1.4	3	0		22.95	22.78	22.42
1.4	3	1		22.92	22.76	22.42
1.4	3	2		22.96	22.77	22.45
1.4	6	0		21.99	21.81	21.37
3	1	0	QPSK	23.78	23.66	23.27
3	1	7		23.79	23.72	23.25
3	1	14		23.72	23.70	23.21
3	8	0		22.81	22.61	22.37
3	8	4		22.81	22.61	22.31
3	8	7		22.86	22.66	22.19
3	15	0		22.84	22.64	22.31
3	1	0	16-QAM	23.04	22.62	22.59
3	1	7		23.08	22.62	22.66
3	1	14		22.99	22.63	22.60
3	8	0		21.81	21.63	21.37
3	8	4		21.80	21.59	21.24
3	8	7		21.87	21.64	21.14
3	15	0		21.78	21.69	21.29



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.89	23.59	23.62
5	1	12		23.64	23.78	23.49
5	1	24		23.69	23.81	23.45
5	12	0		22.84	22.62	22.35
5	12	6		22.83	22.65	22.32
5	12	11		22.85	22.70	22.24
5	25	0		22.91	22.73	22.33
5	1	0	16-QAM	23.43	23.03	22.50
5	1	12		23.42	23.10	22.61
5	1	24		23.28	23.14	22.59
5	12	0		21.89	21.61	21.39
5	12	6		21.84	21.64	21.31
5	12	11		21.90	21.71	21.14
5	25	0		21.82	21.74	21.24
10	1	0	QPSK	23.96	23.64	23.33
10	1	24		23.82	23.72	23.24
10	1	49		23.67	23.73	23.33
10	25	0		22.76	22.60	22.19
10	25	12		22.81	22.68	22.27
10	25	24		22.82	22.82	22.17
10	50	0		22.78	22.73	22.22
10	1	0	16-QAM	22.86	23.09	22.50
10	1	24		22.74	23.08	22.48
10	1	49		22.55	23.17	22.46
10	25	0		21.74	21.63	21.17
10	25	12		21.77	21.71	21.29
10	25	24		21.78	21.85	21.13
10	50	0		21.73	21.72	21.15



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.94	23.68	23.49
15	1	37		23.77	23.78	23.52
15	1	74		23.61	23.73	23.42
15	36	0		22.67	22.62	22.36
15	36	18		22.66	22.69	22.34
15	36	39		22.56	22.81	22.32
15	75	0		22.66	22.80	22.36
15	1	0	16-QAM	23.31	22.86	22.56
15	1	38		23.15	22.94	22.55
15	1	75		23.03	22.96	22.47
15	36	0		21.73	21.70	21.33
15	36	18		21.71	21.75	21.31
15	36	39		21.60	21.87	21.32
15	75	0		21.62	21.70	21.38
20	1	0	QPSK	24.00	23.69	23.25
20	1	49		23.98	23.76	23.25
20	1	99		23.94	23.80	23.25
20	50	0		22.63	22.65	22.61
20	50	24		22.68	22.79	22.45
20	50	49		22.51	22.99	22.51
20	100	0		22.57	22.82	22.53
20	1	0	16-QAM	23.20	23.01	22.83
20	1	49		22.94	23.20	22.69
20	1	99		22.95	23.19	22.64
20	50	0		21.67	21.68	21.62
20	50	24		21.69	21.80	21.40
20	50	49		21.49	21.98	21.46
20	100	0		21.54	21.85	21.54



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.16	24.13	24.12
1.4	1	2		24.19	24.14	24.12
1.4	1	5		24.20	24.09	24.18
1.4	3	0		24.15	24.13	24.09
1.4	3	1		24.15	24.12	24.07
1.4	3	2		24.19	24.11	24.08
1.4	6	0		23.19	23.12	23.05
1.4	1	0	16-QAM	23.31	23.36	23.01
1.4	1	2		23.38	23.34	22.98
1.4	1	5		23.38	23.38	23.09
1.4	3	0		23.38	23.37	23.21
1.4	3	1		23.34	23.39	23.20
1.4	3	2		23.34	23.34	23.23
1.4	6	0		22.38	22.34	22.26
3	1	0	QPSK	24.19	24.10	23.98
3	1	7		24.19	24.10	23.99
3	1	14		24.19	24.05	24.05
3	8	0		23.16	23.03	23.09
3	8	4		23.16	23.08	23.05
3	8	7		23.24	23.13	23.01
3	15	0		23.16	23.05	23.04
3	1	0	16-QAM	23.29	23.57	23.24
3	1	7		23.14	23.61	23.23
3	1	14		23.06	23.53	23.33
3	8	0		22.16	22.11	22.12
3	8	4		22.14	22.16	22.08
3	8	7		22.18	22.20	22.03
3	15	0		22.24	22.17	22.03



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.37	24.19	24.13
5	1	12		24.26	24.17	24.04
5	1	24		24.24	24.17	24.17
5	12	0		23.16	23.06	23.09
5	12	6		23.15	23.16	23.11
5	12	11		23.27	23.17	23.08
5	25	0		23.31	23.17	23.14
5	1	0	16-QAM	23.69	23.56	23.48
5	1	12		23.77	23.55	23.43
5	1	24		23.79	23.57	23.47
5	12	0		22.20	22.09	22.16
5	12	6		22.21	22.15	22.13
5	12	11		22.36	22.13	22.08
5	25	0		22.18	22.20	22.08
10	1	0	QPSK	/	24.47	/
10	1	24		/	24.33	/
10	1	49		/	24.45	/
10	25	0		/	22.96	/
10	25	12		/	23.10	/
10	25	24		/	23.16	/
10	50	0		/	23.08	/
10	1	0	16-QAM	/	23.61	/
10	1	24		/	23.61	/
10	1	49		/	23.65	/
10	25	0		/	22.11	/
10	25	12		/	22.16	/
10	25	24		/	22.13	/
10	50	0		/	22.04	/



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.09	24.29	24.31
1.4	1	2		24.08	24.30	24.35
1.4	1	5		24.12	24.28	24.34
1.4	3	0		24.10	24.23	24.29
1.4	3	1		24.09	24.24	24.27
1.4	3	2		24.13	24.24	24.31
1.4	6	0		23.14	23.23	23.31
1.4	1	0	16-QAM	23.32	23.19	23.46
1.4	1	2		23.36	23.17	23.46
1.4	1	5		23.42	23.21	23.50
1.4	3	0		23.33	23.36	23.48
1.4	3	1		23.33	23.38	23.49
1.4	3	2		23.34	23.40	23.47
1.4	6	0		22.29	22.38	22.50
3	1	0	QPSK	24.07	24.26	24.27
3	1	7		24.12	24.29	24.26
3	1	14		24.08	24.31	24.28
3	8	0		23.15	23.18	23.33
3	8	4		23.11	23.25	23.29
3	8	7		23.06	23.29	23.36
3	15	0		23.10	23.26	23.31
3	1	0	16-QAM	23.30	23.16	23.70
3	1	7		23.33	23.22	23.78
3	1	14		23.38	23.17	23.75
3	8	0		22.19	22.19	22.34
3	8	4		22.16	22.21	22.32
3	8	7		22.09	22.28	22.40
3	15	0		22.07	22.31	22.37



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.16	24.32	24.40
5	1	12		24.16	24.37	24.39
5	1	24		24.18	24.40	24.45
5	12	0		23.25	23.22	23.39
5	12	6		23.18	23.27	23.35
5	12	11		23.16	23.33	23.34
5	25	0		23.22	23.32	23.44
5	1	0	16-QAM	23.47	23.84	23.82
5	1	12		23.48	23.88	23.79
5	1	24		23.57	23.88	23.84
5	12	0		22.28	22.26	22.36
5	12	6		22.18	22.30	22.33
5	12	11		22.17	22.36	22.34
5	25	0		22.21	22.25	22.46
10	1	0	QPSK	24.14	24.34	24.34
10	1	24		24.15	24.34	24.34
10	1	49		24.30	24.43	24.42
10	25	0		23.25	23.19	23.46
10	25	12		23.20	23.28	23.42
10	25	24		23.26	23.39	23.34
10	50	0		23.27	23.32	23.37
10	1	0	16-QAM	23.40	23.19	23.76
10	1	24		23.40	23.20	23.80
10	1	49		23.48	23.28	23.85
10	25	0		22.22	22.18	22.43
10	25	12		22.18	22.27	22.34
10	25	24		22.25	22.37	22.29
10	50	0		22.30	22.26	22.39



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.21	24.22	24.36
15	1	37		24.22	24.28	24.44
15	1	74		24.34	24.35	24.51
15	36	0		23.20	23.17	23.25
15	36	18		23.18	23.27	23.30
15	36	39		23.32	23.35	23.26
15	75	0		23.30	23.30	23.24
15	1	0	16-QAM	23.59	23.45	23.41
15	1	38		23.68	23.48	23.44
15	1	75		23.82	23.59	23.52
15	36	0		22.24	22.21	22.18
15	36	18		22.22	22.34	22.28
15	36	39		22.36	22.40	22.23
15	75	0		22.32	22.26	22.33



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.94	23.90	23.79
5	1	12		23.97	24.02	23.82
5	1	24		24.01	23.96	23.79
5	12	0		23.45	23.81	23.69
5	12	6		23.43	23.84	23.67
5	12	11		23.49	23.86	23.72
5	25	0		23.45	23.92	23.68
5	1	0	16-QAM	23.66	23.70	23.58
5	1	12		23.69	23.89	23.60
5	1	24		23.75	23.79	23.59
5	12	0		23.46	23.82	23.67
5	12	6		23.48	23.80	23.57
5	12	11		23.46	23.82	23.60
5	25	0		23.51	23.84	23.69
10	1	0	QPSK	24.09	23.83	23.67
10	1	24		24.10	23.91	23.60
10	1	49		24.18	23.83	23.76
10	25	0		23.48	23.79	23.69
10	25	12		23.48	23.86	23.70
10	25	24		23.53	23.84	23.69
10	50	0		23.54	23.86	23.67
10	1	0	16-QAM	23.49	23.74	23.65
10	1	24		23.50	23.90	23.63
10	1	49		23.60	23.80	23.62
10	25	0		23.51	23.75	23.71
10	25	12		23.53	23.78	23.68
10	25	24		23.58	23.83	23.71
10	50	0		23.49	23.85	23.67



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.58	23.93	23.81
15	1	37		23.65	24.23	23.79
15	1	74		23.58	23.97	23.80
15	36	0		23.52	23.76	23.64
15	36	18		23.58	23.80	23.63
15	36	39		23.55	23.78	23.65
15	75	0		23.56	23.76	23.67
15	1	0	16-QAM	23.48	23.91	23.85
15	1	38		23.57	24.05	23.62
15	1	75		23.49	23.80	23.58
15	36	0		23.62	23.88	23.75
15	36	18		23.64	23.91	23.76
15	36	39		23.60	23.86	23.73
15	75	0		23.64	23.89	23.75
20	1	0	QPSK	23.62	24.03	24.29
20	1	49		23.66	24.08	24.10
20	1	99		23.65	23.92	24.14
20	50	0		23.62	23.80	23.73
20	50	24		23.63	23.86	23.73
20	50	49		23.63	23.81	23.71
20	100	0		23.55	23.85	23.72
20	1	0	16-QAM	23.77	23.89	24.10
20	1	49		23.80	23.96	23.94
20	1	99		23.72	23.69	23.91
20	50	0		23.69	23.88	23.83
20	50	24		23.68	23.83	23.76
20	50	49		23.67	23.80	23.78
20	100	0		23.64	23.83	23.80



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.55	23.61	23.61
5	1	12		23.76	23.76	23.80
5	1	24		23.66	23.72	23.71
5	12	0		22.60	22.62	22.67
5	12	6		22.64	22.70	22.76
5	12	11		22.62	22.70	22.79
5	25	0		22.62	22.69	22.75
5	1	0	16-QAM	23.14	22.89	22.96
5	1	12		23.34	23.06	23.16
5	1	24		23.25	22.98	23.07
5	12	0		21.64	21.62	21.73
5	12	6		21.70	21.71	21.86
5	12	11		21.69	21.71	21.86
5	25	0		21.64	21.76	21.77
10	1	0	QPSK	/	23.59	/
10	1	24		/	23.77	/
10	1	49		/	23.80	/
10	25	0		/	22.61	/
10	25	12		/	22.73	/
10	25	24		/	22.80	/
10	50	0		/	22.76	/
10	1	0	16-QAM	/	23.05	/
10	1	24		/	23.23	/
10	1	49		/	23.28	/
10	25	0		/	21.70	/
10	25	12		/	21.81	/
10	25	24		/	21.91	/
10	50	0		/	21.79	/



LTE Band 40 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.44	23.40	23.50
5	1	12		23.61	23.59	23.68
5	1	24		23.50	23.48	23.56
5	12	0		22.45	22.50	22.54
5	12	6		22.53	22.57	22.55
5	12	11		22.47	22.53	22.54
5	25	0		22.50	22.52	22.54
5	1	0	16-QAM	22.74	22.77	23.09
5	1	12		22.89	22.94	23.29
5	1	24		22.80	22.84	23.17
5	12	0		21.45	21.56	21.60
5	12	6		21.51	21.63	21.59
5	12	11		21.49	21.60	21.61
5	25	0		21.58	21.57	21.58
10	1	0	QPSK	/	23.58	/
10	1	24		/	23.73	/
10	1	49		/	23.69	/
10	25	0		/	22.51	/
10	25	12		/	22.57	/
10	25	24		/	22.53	/
10	50	0		/	22.54	/
10	1	0	16-QAM	/	22.63	/
10	1	24		/	22.77	/
10	1	49		/	22.74	/
10	25	0		/	21.60	/
10	25	12		/	21.64	/
10	25	24		/	21.61	/
10	50	0		/	21.61	/



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.33	24.23	24.12
1.4	1	2		24.29	24.25	24.16
1.4	1	5		24.30	24.25	24.12
1.4	3	0		24.22	24.20	24.07
1.4	3	1		24.19	24.20	24.12
1.4	3	2		24.24	24.22	24.14
1.4	6	0		23.25	23.24	23.12
1.4	1	0	16-QAM	23.42	23.48	22.97
1.4	1	2		23.46	23.45	22.99
1.4	1	5		23.49	23.51	22.99
1.4	3	0		23.44	23.49	23.21
1.4	3	1		23.42	23.52	23.19
1.4	3	2		23.43	23.48	23.24
1.4	6	0		22.49	22.43	22.23
3	1	0	QPSK	24.28	24.29	24.09
3	1	7		24.30	24.31	24.11
3	1	14		24.29	24.28	24.10
3	8	0		23.28	23.26	23.14
3	8	4		23.22	23.26	23.14
3	8	7		23.23	23.28	23.15
3	15	0		23.22	23.31	23.14
3	1	0	16-QAM	23.15	23.79	23.36
3	1	7		23.21	23.76	23.36
3	1	14		23.12	23.70	23.35
3	8	0		22.28	22.31	22.17
3	8	4		22.22	22.28	22.15
3	8	7		22.21	22.32	22.16
3	15	0		22.30	22.33	22.10



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.41	24.31	24.26
5	1	12		24.37	24.36	24.32
5	1	24		24.34	24.34	24.32
5	12	0		23.32	23.36	23.22
5	12	6		23.30	23.32	23.18
5	12	11		23.27	23.33	23.20
5	25	0		23.37	23.41	23.25
5	1	0	16-QAM	23.88	23.71	23.68
5	1	12		23.74	23.78	23.69
5	1	24		23.88	23.73	23.72
5	12	0		22.30	22.36	22.20
5	12	6		22.29	22.34	22.20
5	12	11		22.23	22.39	22.20
5	25	0		22.37	22.36	22.23
10	1	0	QPSK	24.35	24.40	24.38
10	1	24		24.37	24.44	24.32
10	1	49		24.41	24.45	24.37
10	25	0		23.33	23.36	23.26
10	25	12		23.27	23.36	23.26
10	25	24		23.30	23.39	23.21
10	50	0		23.35	23.40	23.25
10	1	0	16-QAM	23.53	23.33	23.62
10	1	24		23.47	23.32	23.62
10	1	49		23.54	23.35	23.69
10	25	0		22.32	22.35	22.26
10	25	12		22.25	22.32	22.21
10	25	24		22.27	22.36	22.17
10	50	0		22.35	22.34	22.21



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.45	24.40	24.28
15	1	37		24.40	24.47	24.24
15	1	74		24.40	24.41	24.22
15	36	0		23.34	23.34	23.25
15	36	18		23.31	23.38	23.23
15	36	39		23.34	23.38	23.20
15	75	0		23.33	23.40	23.24
15	1	0	16-QAM	23.53	23.86	23.52
15	1	38		23.51	23.88	23.46
15	1	75		23.49	23.85	23.46
15	36	0		22.31	22.41	22.36
15	36	18		22.29	22.40	22.27
15	36	39		22.31	22.41	22.26
15	75	0		22.39	22.40	22.28
20	1	0	QPSK	24.32	24.44	24.20
20	1	49		24.26	24.44	24.20
20	1	99		24.33	24.49	24.22
20	50	0		23.43	23.43	23.33
20	50	24		23.42	23.48	23.33
20	50	49		23.41	23.43	23.24
20	100	0		23.43	23.45	23.28
20	1	0	16-QAM	23.73	23.81	23.55
20	1	49		23.71	23.92	23.51
20	1	99		23.71	23.91	23.55
20	50	0		22.44	22.45	22.29
20	50	24		22.44	22.51	22.28
20	50	49		22.43	22.47	22.21
20	100	0		22.42	22.43	22.26

11. EUT and Test Setup Photo

11.1 EUT Photos

Front side




Back side






Right Edge




Left Edge






Top Edge




Bottom Edge






11.2 Setup Photos

Right Touch




Right Tilt





Left Touch



Left Tilt





Body Front side




Body Back side






Body Right side




Body Left side






Top Edge



Bottom Edge





12. SAR Result Summary

12.1 Head SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	GSM	Right Cheek	848.8	0.086	0.05	32.00	31.96	1.009	0.087	1
		Right Tilt	848.8	0.070	3.28	32.00	31.96	1.009	0.071	/
		Left Cheek	848.8	0.078	-2.07	32.00	31.96	1.009	0.079	/
		Left Tilt	848.8	0.063	-0.91	32.00	31.96	1.009	0.064	/
PCS 1900	GSM	Right Cheek	1880	0.118	0.79	29.50	29.32	1.042	0.123	/
		Right Tilt	1880	0.097	1.50	29.50	29.32	1.042	0.101	/
		Left Cheek	1880	0.129	-0.04	29.50	29.32	1.042	0.134	3
		Left Tilt	1880	0.108	1.22	29.50	29.32	1.042	0.113	/
WCDMA Band II	RMC	Right Cheek	1852.4	0.116	2.74	24.30	24.15	1.035	0.120	5
		Right Tilt	1852.4	0.097	-1.75	24.30	24.15	1.035	0.100	/
		Left Cheek	1852.4	0.107	0.53	24.30	24.15	1.035	0.111	/
		Left Tilt	1852.4	0.086	-2.25	24.30	24.15	1.035	0.089	/
WCDMA Band IV	RMC	Right Cheek	1712.6	0.129	-3.61	25.00	24.73	1.064	0.137	7
		Right Tilt	1712.6	0.108	-2.09	25.00	24.73	1.064	0.115	/
		Left Cheek	1712.6	0.116	0.42	25.00	24.73	1.064	0.123	/
		Left Tilt	1712.6	0.094	2.74	25.00	24.73	1.064	0.100	/
WCDMA Band V	RMC	Right Cheek	846.6	0.054	1.01	24.50	24.26	1.057	0.057	9
		Right Tilt	846.6	0.046	3.60	24.50	24.26	1.057	0.049	/
		Left Cheek	846.6	0.049	2.96	24.50	24.26	1.057	0.052	/
		Left Tilt	846.6	0.045	-3.41	24.50	24.26	1.057	0.048	/
2.4G WLAN	802.11b	Right Cheek	2462	0.164	3.41	16.30	16.13	1.040	0.171	11
		Right Tilt	2462	0.135	3.16	16.30	16.13	1.040	0.140	/
		Left Cheek	2462	0.147	2.36	16.30	16.13	1.040	0.153	/
		Left Tilt	2462	0.121	-3.12	16.30	16.13	1.040	0.126	/
5.2G WLAN	802.11ac-VHT80	Right Cheek	5210	0.228	2.30	13.50	13.44	1.014	0.231	/
		Right Tilt	5210	0.186	0.15	13.50	13.44	1.014	0.189	/
		Left Cheek	5210	0.234	-1.82	13.50	13.44	1.014	0.237	13
		Left Tilt	5210	0.188	-1.06	13.50	13.44	1.014	0.191	/
5.3G WLAN	802.11a	Right Cheek	5320	0.330	3.90	14.30	14.19	1.026	0.338	/
		Right Tilt	5320	0.269	3.22	14.30	14.19	1.026	0.276	/
		Left Cheek	5320	0.353	-1.00	14.30	14.19	1.026	0.362	15
		Left Tilt	5320	0.285	1.54	14.30	14.19	1.026	0.292	/
5.6G WLAN	802.11a	Right Cheek	5700	0.303	-2.56	14.50	14.45	1.012	0.307	/
		Right Tilt	5700	0.244	-0.53	14.50	14.45	1.012	0.247	/
		Left Cheek	5700	0.323	-0.68	14.50	14.45	1.012	0.327	17
		Left Tilt	5700	0.260	1.87	14.50	14.45	1.012	0.263	/
5.8G WLAN	802.11a	Right Cheek	5785	0.412	3.94	15.00	14.63	1.089	0.449	/
		Right Tilt	5785	0.333	-1.53	15.00	14.63	1.089	0.363	/
		Left Cheek	5745	0.412	3.61	15.00	14.62	1.091	0.450	/
		Left Cheek	5785	0.436	-2.14	15.00	14.63	1.089	0.475	19
		Left Cheek	5825	0.383	-3.36	15.00	14.42	1.143	0.438	/
		Left Tilt	5785	0.355	1.60	15.00	14.63	1.089	0.387	/



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Right Cheek	1860	0.155	1.27	21.00	20.90	1.023	0.159	21
			50	49	Right Cheek	1880	0.135	-2.66	20.20	20.01	1.045	0.141	/
			1	0	Right Tilt	1860	0.127	-2.78	21.00	20.90	1.023	0.130	/
			50	49	Right Tilt	1880	0.110	-2.11	20.20	20.01	1.045	0.115	/
			1	0	Left Cheek	1860	0.141	-3.77	21.00	20.90	1.023	0.144	/
			50	49	Left Cheek	1880	0.122	-0.83	20.20	20.01	1.045	0.127	/
			1	0	Left Tilt	1860	0.113	-1.24	21.00	20.90	1.023	0.116	/
			50	49	Left Tilt	1880	0.099	-3.25	20.20	20.01	1.045	0.103	/
LTE Band 4	20M	QPSK	1	99	Right Cheek	1720	0.113	-0.23	24.70	24.49	1.050	0.119	/
			50	49	Right Cheek	1732.5	0.089	0.58	23.50	23.42	1.019	0.091	/
			1	99	Right Tilt	1720	0.093	-2.76	24.70	24.49	1.050	0.098	/
			50	49	Right Tilt	1732.5	0.073	-2.22	23.50	23.42	1.019	0.074	/
			1	99	Left Cheek	1720	0.129	0.85	24.70	24.49	1.050	0.135	23
			50	49	Left Cheek	1732.5	0.099	-0.75	23.50	23.42	1.019	0.101	/
			1	99	Left Tilt	1720	0.104	-1.48	24.70	24.49	1.050	0.109	/
			50	49	Left Tilt	1732.5	0.081	1.57	23.50	23.42	1.019	0.083	/
LTE Band 5	10M	QPSK	1	49	Right Cheek	844	0.072	3.93	24.60	24.42	1.042	0.075	/
			25	0	Right Cheek	844	0.058	-2.92	23.50	23.37	1.030	0.060	/
			1	49	Right Tilt	844	0.060	3.01	24.60	24.42	1.042	0.063	/
			25	0	Right Tilt	844	0.048	1.19	23.50	23.37	1.030	0.049	/
			1	49	Left Cheek	844	0.080	1.47	24.60	24.42	1.042	0.083	25
			25	0	Left Cheek	844	0.062	0.44	23.50	23.37	1.030	0.064	/
			1	49	Left Tilt	844	0.070	-3.60	24.60	24.42	1.042	0.073	/
			25	0	Left Tilt	844	0.054	-1.37	23.50	23.37	1.030	0.056	/
LTE Band 7	20M	QPSK	1	0	Right Cheek	2510	0.179	-1.52	23.90	23.61	1.069	0.191	27
			50	0	Right Cheek	2510	0.139	-1.24	22.70	22.52	1.042	0.145	/
			1	0	Right Tilt	2510	0.146	-1.62	23.90	23.61	1.069	0.156	/
			50	0	Right Tilt	2510	0.113	0.15	22.70	22.52	1.042	0.118	/
			1	0	Left Cheek	2510	0.160	3.02	23.90	23.61	1.069	0.171	/
			50	0	Left Cheek	2510	0.126	-1.97	22.70	22.52	1.042	0.131	/
			1	0	Left Tilt	2510	0.132	2.06	23.90	23.61	1.069	0.141	/
			50	0	Left Tilt	2510	0.101	-0.33	22.70	22.52	1.042	0.105	/
	10M	QPSK	1	49	Right Cheek	711	0.035	-0.87	24.50	24.36	1.033	0.036	/



LTE Band 12			25	0	Right Cheek	707.5	0.030	2.66	23.50	23.35	1.035	0.031	/
			1	49	Right Tilt	711	0.033	1.38	24.50	24.36	1.033	0.034	/
			25	0	Right Tilt	707.5	0.026	-1.56	23.50	23.35	1.035	0.027	/
			1	49	Left Cheek	711	0.037	2.56	24.50	24.36	1.033	0.038	29
			25	0	Left Cheek	707.5	0.031	3.16	23.50	23.35	1.035	0.032	/
			1	49	Left Tilt	711	0.032	1.95	24.50	24.36	1.033	0.033	/
			25	0	Left Tilt	707.5	0.024	1.52	23.50	23.35	1.035	0.025	/
LTE Band 13	10M	QPSK	1	49	Right Cheek	782	0.051	2.02	24.50	24.26	1.057	0.054	/
			25	24	Right Cheek	782	0.042	1.73	23.30	23.18	1.028	0.043	/
			1	49	Right Tilt	782	0.045	-1.98	24.50	24.26	1.057	0.048	/
			25	24	Right Tilt	782	0.039	1.61	23.30	23.18	1.028	0.040	/
			1	49	Left Cheek	782	0.054	0.61	24.50	24.26	1.057	0.057	31
			25	24	Left Cheek	782	0.043	3.32	23.30	23.18	1.028	0.044	/
			1	49	Left Tilt	782	0.048	-1.17	24.50	24.26	1.057	0.051	/
			25	24	Left Tilt	782	0.038	3.69	23.30	23.18	1.028	0.039	/
LTE Band 17	10M	QPSK	1	49	Right Cheek	710	0.099	0.10	24.50	24.28	1.052	0.104	33
			25	24	Right Cheek	709	0.076	0.93	23.30	23.18	1.028	0.078	/
			1	49	Right Tilt	710	0.080	-1.58	24.50	24.28	1.052	0.084	/
			25	24	Right Tilt	709	0.062	-0.92	23.30	23.18	1.028	0.064	/
			1	49	Left Cheek	710	0.088	0.54	24.50	24.28	1.052	0.093	/
			25	24	Left Cheek	709	0.071	0.64	23.30	23.18	1.028	0.073	/
			1	49	Left Tilt	710	0.071	0.50	24.50	24.28	1.052	0.075	/
			25	24	Left Tilt	709	0.054	-2.53	23.30	23.18	1.028	0.056	/
LTE Band 25	20M	QPSK	1	0	Right Cheek	1860	0.129	-3.59	24.20	24.00	1.047	0.135	/
			50	49	Right Cheek	1882.5	0.099	-2.78	23.20	22.99	1.050	0.104	/
			1	0	Right Tilt	1860	0.107	-2.38	24.20	24.00	1.047	0.112	/
			50	49	Right Tilt	1882.5	0.082	3.73	23.20	22.99	1.050	0.086	/
			1	0	Left Cheek	1860	0.142	-3.55	24.20	24.00	1.047	0.149	35
			50	49	Left Cheek	1882.5	0.110	-0.63	23.20	22.99	1.050	0.115	/
			1	0	Left Tilt	1860	0.116	3.19	24.20	24.00	1.047	0.121	/
			50	49	Left Tilt	1882.5	0.087	1.66	23.20	22.99	1.050	0.091	/
LTE Band 26	15M	QPSK	1	74	Right Cheek	844	0.118	0.35	24.70	24.51	1.045	0.123	37
			36	39	Right Cheek	831.5	0.091	-1.33	23.50	23.35	1.035	0.094	/
			1	74	Right Tilt	844	0.096	1.48	24.70	24.51	1.045	0.100	/
			36	39	Right Tilt	831.5	0.077	1.43	23.50	23.35	1.035	0.080	/
			1	74	Left Cheek	844	0.104	1.69	24.70	24.51	1.045	0.109	/



			36	39	Left Cheek	831.5	0.083	-3.28	23.50	23.35	1.035	0.086	/
			1	74	Left Tilt	844	0.087	3.73	24.70	24.51	1.045	0.091	/
			36	39	Left Tilt	831.5	0.069	0.95	23.50	23.35	1.035	0.071	/
LTE Band 38	20M	QPSK	1	0	Right Cheek	2610	0.113	-0.36	24.50	24.29	1.050	0.119	/
			50	24	Right Cheek	2595	0.089	-3.83	24.00	23.86	1.033	0.092	/
			1	0	Right Tilt	2610	0.092	-1.63	24.50	24.29	1.050	0.097	/
			50	24	Right Tilt	2595	0.070	-1.94	24.00	23.86	1.033	0.072	/
			1	0	Left Cheek	2610	0.124	3.49	24.50	24.29	1.050	0.130	39
			50	24	Left Cheek	2595	0.097	0.28	24.00	23.86	1.033	0.100	/
			1	0	Left Tilt	2610	0.103	0.35	24.50	24.29	1.050	0.108	/
			50	24	Left Tilt	2595	0.081	1.82	24.00	23.86	1.033	0.084	/
LTE Band 40	10M	QPSK	1	49	Right Cheek	2310	0.175	-2.10	24.00	23.80	1.047	0.183	41
			50	24	Right Cheek	2310	0.136	0.91	23.00	22.80	1.047	0.142	/
			1	49	Right Tilt	2310	0.141	2.52	24.00	23.80	1.047	0.148	/
			50	24	Right Tilt	2310	0.108	1.67	23.00	22.80	1.047	0.113	/
			1	49	Left Cheek	2310	0.154	3.57	24.00	23.80	1.047	0.161	/
			50	24	Left Cheek	2310	0.119	2.97	23.00	22.80	1.047	0.125	/
			1	49	Left Tilt	2310	0.126	-1.45	24.00	23.80	1.047	0.132	/
			50	24	Left Tilt	2310	0.096	-3.22	23.00	22.80	1.047	0.101	/
LTE Band 66	20M	QPSK	1	99	Right Cheek	1745	0.188	0.57	24.60	24.49	1.026	0.193	/
			50	24	Right Cheek	1745	0.147	-1.34	23.60	23.48	1.028	0.151	/
			1	99	Right Tilt	1745	0.154	2.04	24.60	24.49	1.026	0.158	/
			50	24	Right Tilt	1745	0.116	-1.82	23.60	23.48	1.028	0.119	/
			1	99	Left Cheek	1745	0.209	-1.09	24.60	24.49	1.026	0.214	43
			50	24	Left Cheek	1745	0.160	0.15	23.60	23.48	1.028	0.164	/
			1	99	Left Tilt	1745	0.172	1.29	24.60	24.49	1.026	0.176	/
			50	24	Left Tilt	1745	0.131	-0.12	23.60	23.48	1.028	0.135	/

Note:

1. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.

a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

b. Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor

2. Per KDB 865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg.



12.2 Body-worn and Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
GSM850	EGPRS Data-4 Slot	Front Side	824.2	0.224	-2.78	29.70	29.57	1.030	0.231	/
		Back Side	824.2	0.335	-2.98	29.70	29.57	1.030	0.345	/
		Left Side	824.2	0.135	-1.69	29.70	29.57	1.030	0.139	/
		Right Side	824.2	0.102	-2.74	29.70	29.57	1.030	0.105	/
		Top Side	824.2	0.032	0.46	29.70	29.57	1.030	0.033	/
		Bottom Side	824.2	0.444	1.37	29.70	29.57	1.030	0.457	2
PCS 1900	EGPRS Data-4 Slot	Front Side	1850.2	0.768	-1.08	26.00	25.83	1.040	0.799	/
		Back Side	1850.2	0.899	-1.73	26.00	25.83	1.040	0.935	4
		Back Side	1880	0.837	1.38	26.00	25.74	1.062	0.889	/
		Back Side	1909.8	0.801	2.15	26.00	25.51	1.119	0.897	/
		Left Side	1850.2	0.360	-3.81	26.00	25.83	1.040	0.374	/
		Right Side	1850.2	0.274	2.07	26.00	25.83	1.040	0.285	/
		Bottom Side	1850.2	0.543	-1.87	26.00	25.83	1.040	0.565	/
WCDMA Band II	RMC	Front Side	1852.4	0.701	-0.31	24.30	24.15	1.035	0.726	/
		Back Side	1852.4	0.820	2.05	24.30	24.15	1.035	0.849	6
		Back Side	1880	0.783	-1.85	24.30	24.05	1.059	0.829	/
		Back Side	1907.6	0.669	3.79	24.30	23.57	1.183	0.791	/
		Left Side	1852.4	0.329	-0.83	24.30	24.15	1.035	0.341	/
		Right Side	1852.4	0.249	2.55	24.30	24.15	1.035	0.258	/
		Bottom Side	1852.4	0.493	2.22	24.30	24.15	1.035	0.510	/
WCDMA Band IV	RMC	Front Side	1712.6	0.795	-1.72	25.00	24.73	1.064	0.846	/
		Front Side	1740	0.750	3.47	25.00	24.73	1.064	0.798	/
		Front Side	1752.4	0.723	-2.18	25.00	24.71	1.069	0.773	/
		Back Side	1712.6	0.936	0.08	25.00	24.73	1.064	0.996	8
		Back Side	1740	0.907	-2.55	25.00	24.73	1.064	0.965	/
		Back Side	1752.4	0.892	-0.49	25.00	24.71	1.069	0.954	/
		Left Side	1712.6	0.375	3.73	25.00	24.73	1.064	0.399	/
		Right Side	1712.6	0.284	0.95	25.00	24.73	1.064	0.302	/
		Bottom Side	1712.6	0.561	0.36	25.00	24.73	1.064	0.597	/
WCDMA Band V	RMC	Front Side	846.6	0.125	-0.93	24.50	24.26	1.057	0.132	/
		Back Side	846.6	0.187	-3.72	24.50	24.26	1.057	0.198	/
		Left Side	846.6	0.075	-3.13	24.50	24.26	1.057	0.079	/
		Right Side	846.6	0.057	2.71	24.50	24.26	1.057	0.060	/
		Bottom Side	846.6	0.247	-1.34	24.50	24.26	1.057	0.261	10
2.4GHz WLAN	802.11b	Front Side	2462	0.222	2.75	16.30	16.13	1.040	0.231	/
		Back Side	2462	0.295	2.71	16.30	16.13	1.040	0.307	12
		Top Side	2462	0.257	0.50	16.30	16.13	1.040	0.267	/
5.2GHz WLAN	802.11ac-VHT80	Front Side	5210	0.274	-3.10	13.50	13.44	1.014	0.278	/
		Back Side	5210	0.360	0.06	13.50	13.44	1.014	0.365	14
		Top Side	5210	0.312	3.46	13.50	13.44	1.014	0.316	/
5.3GHz WLAN	802.11a	Front Side	5320	0.295	-0.28	14.30	14.19	1.026	0.303	/
		Back Side	5320	0.391	-3.07	14.30	14.19	1.026	0.401	16
		Top Side	5320	0.343	3.11	14.30	14.19	1.026	0.352	/
5.6GHz WLAN	802.11a	Front Side	5700	0.081	-3.22	14.50	14.45	1.012	0.082	/
		Back Side	5700	0.105	3.48	14.50	14.45	1.012	0.106	18
		Top Side	5700	0.091	-1.41	14.50	14.45	1.012	0.092	/
5.8GHz WLAN	802.11a	Front Side	5785	0.186	2.32	15.00	14.63	1.089	0.203	/
		Back Side	5785	0.244	-1.39	15.00	14.63	1.089	0.266	20
		Top Side	5785	0.214	3.84	15.00	14.63	1.089	0.233	/



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Front side	1860	0.710	-2.60	21.00	20.90	1.023	0.727	/
			50	49	Front side	1880	0.607	-3.88	20.20	20.01	1.045	0.634	/
			1	0	Back Side	1860	0.835	3.19	21.00	20.90	1.023	0.854	22
			1	0	Back Side	1880	0.732	3.04	21.00	20.56	1.107	0.810	/
			1	0	Back Side	1900	0.768	2.59	21.00	20.61	1.094	0.840	/
			50	49	Back Side	1880	0.712	3.92	20.20	20.01	1.045	0.744	/
			1	0	Left Side	1860	0.335	1.55	21.00	20.90	1.023	0.343	/
			50	49	Left Side	1880	0.290	0.60	20.20	20.01	1.045	0.303	/
			1	0	Right Side	1860	0.251	-2.48	21.00	20.90	1.023	0.257	/
			50	49	Right Side	1880	0.214	-0.58	20.20	20.01	1.045	0.224	/
			1	0	Bottom Side	1860	0.501	2.32	21.00	20.90	1.023	0.513	/
			50	49	Bottom Side	1880	0.430	-3.58	20.20	20.01	1.045	0.449	/
LTE Band 4	20M	QPSK	1	99	Front side	1720	0.719	-1.64	24.70	24.49	1.050	0.755	/
			50	49	Front side	1732.5	0.542	1.70	23.50	23.42	1.019	0.552	/
			1	99	Back Side	1720	0.844	-0.73	24.70	24.49	1.050	0.886	24
			1	99	Back Side	1732.5	0.768	-2.12	24.70	24.37	1.079	0.829	/
			1	99	Back Side	1745	0.816	1.83	24.70	24.46	1.057	0.862	/
			50	49	Back Side	1732.5	0.634	-1.01	23.50	23.42	1.019	0.646	/
			1	99	Left Side	1720	0.339	0.26	24.70	24.49	1.050	0.356	/
			50	49	Left Side	1732.5	0.256	-1.41	23.50	23.42	1.019	0.261	/
			1	99	Right Side	1720	0.257	-0.17	24.70	24.49	1.050	0.270	/
			50	49	Right Side	1732.5	0.196	-1.37	23.50	23.42	1.019	0.200	/
			1	99	Bottom Side	1720	0.507	-3.91	24.70	24.49	1.050	0.532	/
			50	49	Bottom Side	1732.5	0.382	-1.55	23.50	23.42	1.019	0.389	/
LTE Band 5	10M	QPSK	1	49	Front side	844	0.387	-1.70	24.60	24.42	1.042	0.403	/
			25	0	Front side	844	0.292	0.71	23.50	23.37	1.030	0.301	/
			1	49	Back Side	844	0.580	3.69	24.60	24.42	1.042	0.605	/
			25	0	Back Side	844	0.439	-3.97	23.50	23.37	1.030	0.452	/
			1	49	Left Side	844	0.232	-0.10	24.60	24.42	1.042	0.242	/
			25	0	Left Side	844	0.176	-2.60	23.50	23.37	1.030	0.181	/
			1	49	Right Side	844	0.180	2.16	24.60	24.42	1.042	0.188	/
			25	0	Right Side	844	0.137	2.87	23.50	23.37	1.030	0.141	/
			1	49	Bottom Side	844	0.767	0.19	24.60	24.42	1.042	0.799	26



			25	0	Bottom Side	844	0.580	-3.83	23.50	23.37	1.030	0.598	/
LTE Band 7	20M	QPS K	1	0	Front side	2510	0.798	-2.87	23.90	23.61	1.069	0.853	/
			1	0	Front side	2535	0.582	1.97	23.90	22.78	1.294	0.753	/
			1	0	Front side	2560	0.571	1.62	23.90	22.74	1.306	0.746	/
			50	0	Front side	2510	0.602	-2.91	22.70	22.52	1.042	0.627	/
			1	0	Back Side	2510	0.935	-4.00	23.90	23.61	1.069	1.000	28
			1	0	Back Side	2535	0.734	-0.57	23.90	22.78	1.294	0.950	/
			1	0	Back Side	2560	0.702	-3.88	23.90	22.74	1.306	0.917	/
			50	0	Back Side	2510	0.704	-2.24	22.70	22.52	1.042	0.734	/
			1	0	Left Side	2510	0.374	1.62	23.90	23.61	1.069	0.400	/
			50	0	Left Side	2510	0.285	1.86	22.70	22.52	1.042	0.297	/
			1	0	Right Side	2510	0.284	2.41	23.90	23.61	1.069	0.304	/
			50	0	Right Side	2510	0.215	2.43	22.70	22.52	1.042	0.224	/
			1	0	Bottom Side	2510	0.563	0.57	23.90	23.61	1.069	0.602	/
			50	0	Bottom Side	2510	0.424	-3.75	22.70	22.52	1.042	0.442	/
LTE Band 12	10M	QPS K	1	49	Front side	711	0.398	-1.28	24.50	24.36	1.033	0.411	/
			25	0	Front side	707.5	0.300	0.31	23.50	23.35	1.035	0.311	/
			1	49	Back Side	711	0.593	-1.11	24.50	24.36	1.033	0.612	/
			25	0	Back Side	707.5	0.447	-0.38	23.50	23.35	1.035	0.463	/
			1	49	Left Side	711	0.239	-1.92	24.50	24.36	1.033	0.247	/
			25	0	Left Side	707.5	0.182	-0.47	23.50	23.35	1.035	0.188	/
			1	49	Right Side	711	0.185	-1.86	24.50	24.36	1.033	0.191	/
			25	0	Right Side	707.5	0.140	0.39	23.50	23.35	1.035	0.145	/
			1	49	Bottom Side	704	0.731	-0.69	24.50	24.26	1.057	0.773	/
			1	49	Bottom Side	707.5	0.763	3.90	24.50	24.28	1.052	0.803	/
			1	49	Bottom Side	711	0.791	-2.11	24.50	24.36	1.033	0.817	30
			25	0	Bottom Side	707.5	0.597	1.51	23.50	23.35	1.035	0.618	/
LTE Band 13	10M	QPS K	1	49	Front side	782	0.331	3.98	24.50	24.26	1.057	0.350	/
			25	24	Front side	782	0.250	-1.77	23.30	23.18	1.028	0.257	/
			1	49	Back Side	782	0.498	2.34	24.50	24.26	1.057	0.526	/
			25	24	Back Side	782	0.375	0.51	23.30	23.18	1.028	0.386	/
			1	49	Left Side	782	0.198	0.29	24.50	24.26	1.057	0.209	/
			25	24	Left Side	782	0.153	1.89	23.30	23.18	1.028	0.157	/
			1	49	Right Side	782	0.154	3.65	24.50	24.26	1.057	0.163	/
			25	24	Right Side	782	0.118	1.40	23.30	23.18	1.028	0.121	/



			1	49	Bottom Side	782	0.661	-3.63	24.50	24.26	1.057	0.699	32
			25	24	Bottom Side	782	0.499	1.09	23.30	23.18	1.028	0.513	/
LTE Band 17	10M	QPS K	1	49	Front side	710	0.126	-0.35	24.50	24.28	1.052	0.133	/
			25	24	Front side	709	0.100	0.41	23.30	23.18	1.028	0.103	/
			1	49	Back Side	710	0.187	-0.82	24.50	24.28	1.052	0.197	/
			25	24	Back Side	709	0.145	-2.06	23.30	23.18	1.028	0.149	/
			1	49	Left Side	710	0.075	0.04	24.50	24.28	1.052	0.079	/
			25	24	Left Side	709	0.059	-3.22	23.30	23.18	1.028	0.061	/
			1	49	Right Side	710	0.057	1.91	24.50	24.28	1.052	0.060	/
			25	24	Right Side	709	0.044	1.83	23.30	23.18	1.028	0.045	/
			1	49	Bottom Side	710	0.247	2.36	24.50	24.28	1.052	0.260	34
			25	24	Bottom Side	709	0.191	-3.93	23.30	23.18	1.028	0.196	/
LTE Band 25	20M	QPS K	1	0	Front side	1860	0.655	-1.55	24.20	24.00	1.047	0.686	/
			50	49	Front side	1882.5	0.496	2.13	23.20	22.99	1.050	0.521	/
			1	0	Back Side	1860	0.768	1.71	24.20	24.00	1.047	0.804	36
			1	0	Back Side	1882.5	0.702	-2.31	24.20	23.69	1.125	0.789	/
			1	0	Back Side	1905	0.641	-0.32	24.20	23.25	1.245	0.798	/
			50	49	Back Side	1882.5	0.581	-2.91	23.20	22.99	1.050	0.610	/
			1	0	Left Side	1860	0.308	-2.63	24.20	24.00	1.047	0.323	/
			50	49	Left Side	1882.5	0.232	0.78	23.20	22.99	1.050	0.243	/
			1	0	Right Side	1860	0.231	-3.18	24.20	24.00	1.047	0.242	/
			50	49	Right Side	1882.5	0.179	-2.65	23.20	22.99	1.050	0.188	/
			1	0	Bottom Side	1860	0.461	-2.02	24.20	24.00	1.047	0.483	/
			50	49	Bottom Side	1882.5	0.350	2.26	23.20	22.99	1.050	0.367	/
LTE Band 26	15M	QPS K	1	74	Front side	844	0.105	-2.73	24.70	24.51	1.045	0.110	/
			36	39	Front side	831.5	0.083	-1.88	23.50	23.35	1.035	0.086	/
			1	74	Back Side	844	0.160	1.06	24.70	24.51	1.045	0.167	/
			36	39	Back Side	831.5	0.126	2.59	23.50	23.35	1.035	0.130	/
			1	74	Left Side	844	0.066	-0.26	24.70	24.51	1.045	0.069	/
			36	39	Left Side	831.5	0.055	0.72	23.50	23.35	1.035	0.057	/
			1	74	Right Side	844	0.050	-0.02	24.70	24.51	1.045	0.052	/
			36	39	Right Side	831.5	0.041	3.92	23.50	23.35	1.035	0.042	/
			1	74	Bottom Side	844	0.208	-1.27	24.70	24.51	1.045	0.217	38
			36	39	Bottom Side	831.5	0.159	0.36	23.50	23.35	1.035	0.165	/
	20M	QPS K	1	0	Front side	2610	0.503	-2.66	24.50	24.29	1.050	0.528	/



LTE Band 38			50	24	Front side	2595	0.378	-3.52	24.00	23.86	1.033	0.390	/
			1	0	Back Side	2610	0.591	-3.70	24.50	24.29	1.050	0.620	40
			50	24	Back Side	2595	0.445	3.15	24.00	23.86	1.033	0.460	/
			1	0	Left Side	2610	0.237	-3.77	24.50	24.29	1.050	0.249	/
			50	24	Left Side	2595	0.179	-2.29	24.00	23.86	1.033	0.185	/
			1	0	Right Side	2610	0.179	3.49	24.50	24.29	1.050	0.188	/
			50	24	Right Side	2595	0.135	-3.10	24.00	23.86	1.033	0.139	/
			1	0	Bottom Side	2610	0.356	-3.00	24.50	24.29	1.050	0.374	/
			50	24	Bottom Side	2595	0.269	1.89	24.00	23.86	1.033	0.278	/
LTE Band 40	10M	QPS K	1	49	Front side	2310	0.592	-2.93	24.00	23.80	1.047	0.620	/
			50	24	Front side	2310	0.444	2.97	23.00	22.80	1.047	0.465	/
			1	49	Back Side	2310	0.693	-3.80	24.00	23.80	1.047	0.726	42
			50	24	Back Side	2310	0.523	-3.11	23.00	22.80	1.047	0.548	/
			1	49	Left Side	2310	0.278	-2.65	24.00	23.80	1.047	0.291	/
			50	24	Left Side	2310	0.213	-2.16	23.00	22.80	1.047	0.223	/
			1	49	Right Side	2310	0.210	-3.85	24.00	23.80	1.047	0.220	/
			50	24	Right Side	2310	0.160	0.92	23.00	22.80	1.047	0.168	/
			1	49	Bottom Side	2310	0.419	1.77	24.00	23.80	1.047	0.439	/
			50	24	Bottom Side	2310	0.316	-1.99	23.00	22.80	1.047	0.331	/
LTE Band 66	20M	QPS K	1	99	Front side	1745	0.498	3.84	24.60	24.49	1.026	0.511	/
			50	24	Front side	1745	0.378	-2.75	23.60	23.48	1.028	0.389	/
			1	99	Back Side	1745	0.585	2.43	24.60	24.49	1.026	0.600	44
			50	24	Back Side	1745	0.444	-3.11	23.60	23.48	1.028	0.456	/
			1	99	Left Side	1745	0.236	2.83	24.60	24.49	1.026	0.242	/
			50	24	Left Side	1745	0.182	0.84	23.60	23.48	1.028	0.187	/
			1	99	Right Side	1745	0.176	3.49	24.60	24.49	1.026	0.181	/
			50	24	Right Side	1745	0.136	2.68	23.60	23.48	1.028	0.140	/
			1	99	Bottom Side	1745	0.352	3.69	24.60	24.49	1.026	0.361	/
			50	24	Bottom Side	1745	0.270	1.50	23.60	23.48	1.028	0.278	/

Note:

- The test separation of all above table is 0mm.
- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



12.3 Repeated SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR(W/Kg)
PCS 1900	EGPRS Data-4 Slot	Back Side	1850.2	0.875	-0.34	26.00	25.83	1.040	0.910
		Back Side	1880	0.824	-3.97	26.00	25.74	1.062	0.875
		Back Side	1909.8	0.776	-2.67	26.00	25.51	1.119	0.869
WCDMA Band II	RMC	Back Side	1852.4	0.807	0.43	24.30	24.15	1.035	0.835
		Back Side	1880	0.780	3.40	24.30	24.05	1.059	0.826
WCDMA Band IV	RMC	Front Side	1712.6	0.793	3.35	25.00	24.73	1.064	0.844
		Back Side	1712.6	0.901	1.70	25.00	24.73	1.064	0.959
		Back Side	1740	0.872	-1.36	25.00	24.73	1.064	0.928
		Back Side	1752.4	0.881	2.99	25.00	24.71	1.069	0.942

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR(W/Kg)
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.826	-2.65	21.00	20.90	1.023	0.845
			1	0	Back Side	1880	0.725	1.95	21.00	20.56	1.107	0.802
			1	0	Back Side	1900	0.766	3.61	21.00	20.61	1.094	0.838
LTE Band 4	20M	QPSK	1	99	Back Side	1720	0.840	-0.53	24.70	24.49	1.050	0.882
			1	99	Back Side	1732.5	0.736	1.50	24.70	24.37	1.079	0.794
			1	99	Back Side	1745	0.779	3.51	24.70	24.46	1.057	0.823
LTE Band 7	20M	QPSK	1	0	Front side	2510	0.764	-2.35	23.90	23.61	1.069	0.817
			1	0	Back Side	2510	0.928	-1.73	23.90	23.61	1.069	0.992
			1	0	Back Side	2535	0.705	1.80	23.90	22.78	1.294	0.912
			1	0	Back Side	2560	0.684	-2.50	23.90	22.74	1.306	0.893
LTE Band 12	10M	QPSK	1	49	Bottom Side	707.5	0.758	2.93	24.50	24.28	1.052	0.797
			1	49	Bottom Side	711	0.762	2.05	24.50	24.36	1.033	0.787
LTE Band 25	20M	QPSK	1	0	Back Side	1860	0.752	-3.23	24.20	24.00	1.047	0.787



12.4 Repeated SAR measurement

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio
PCS 1900	EGPRS Data-4 Slot	Back Side	1850	0.899	0.875	1.027
		Back Side	1880	0.837	0.824	1.016
		Back Side	1910	0.801	0.776	1.032
WCDMA Band II	RMC	Back Side	1852	0.820	0.807	1.016
		Back Side	1880	0.783	0.780	1.004
WCDMA Band IV	RMC	Front Side	1713	0.795	0.793	1.003
		Back Side	1713	0.936	0.901	1.039
		Back Side	1740	0.907	0.872	1.040
		Back Side	1752	0.892	0.881	1.012

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg) 1g (W/Kg)	1 st Repeated SAR 1g	Ratio
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.835	0.826	1.011
			1	0	Back Side	1880	0.732	0.725	1.010
			1	0	Back Side	1900	0.768	0.766	1.003
LTE Band 4	20M	QPSK	1	99	Back Side	1720	0.844	0.840	1.005
			1	99	Back Side	1732.5	0.768	0.736	1.044
			1	99	Back Side	1745	0.816	0.779	1.048
LTE Band 7	20M	QPSK	1	0	Front side	2510	0.798	0.764	1.045
			1	0	Back Side	2510	0.935	0.928	1.007
			1	0	Back Side	2535	0.734	0.705	1.041
			1	0	Back Side	2560	0.702	0.684	1.026
LTE Band 12	10M	QPSK	1	49	Bottom Side	707.5	0.763	0.758	1.007
			1	49	Bottom Side	711	0.791	0.762	1.037
LTE Band 25	20M	QPSK	1	0	Back Side	1860	0.768	0.752	1.021

Note:

1. Per KDB 865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/Kg$.
2. Per KDB 865664 D01, if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45W/Kg$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45W/Kg$.
4. The ratio is the difference in percentage between original and repeated measured SAR.



12.5 Simultaneous Multi-band Transmission Evaluation

Application Simultaneous Transmission information:

Position	Simultaneous State
Head	1. GSM + 2.4GHz WLAN/5G WLAN + NFC
	2. GSM + Bluetooth + NFC
	3. WCDMA + 2.4GHz WLAN/5G WLAN + NFC
	4. WCDMA + Bluetooth + NFC
	5. LTE + 2.4GHz WLAN/5G WLAN + NFC
	6. LTE + Bluetooth + NFC
Body	1. GSM + 2.4GHz WLAN/5G WLAN + NFC
	2. GSM + Bluetooth + NFC
	3. WCDMA + 2.4GHz WLAN/5G WLAN + NFC
	4. WCDMA + Bluetooth + NFC
	5. LTE + 2.4GHz WLAN/5G WLAN + NFC
	6. LTE + Bluetooth + NFC

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f} \text{ (GHz)} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;
Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4 W/Kg for 1-g SAR and 1.0 W/Kg for 10-g SAR, when the separation distance is $>50 \text{ mm}$.

Estimated SAR		Maximum Turn-up Power		Antenna to user(mm)	Frequency (GHz)	Stand Alone SAR(1g) [W/kg]
		dBm	mW			
BT	Head	4.3	2.692	5	2.48	0.113
	Body			5	2.48	0.113
NFC	Head	-37	0.000200	5	0.01356	0.0000006
	Body			5	0.01356	0.0000006



Simultaneous Mode	Position	Mode	Max. 1-g SAR	1-g Sum SAR
			(W/kg)	(W/kg)
GSM + 2.4G WLAN + NFC	Head	GSM	0.134	0.305
		NFC	0.0000006	
		2.4G WLAN	0.171	
	Body	GSM	0.935	1.242
		NFC	0.0000006	
		2.4G WLAN	0.307	
GSM + Bluetooth+ NFC	Head	GSM	0.134	0.247
		NFC	0.0000006	
		BT	0.113	
	Body	GSM	0.935	1.048
		NFC	0.0000006	
		BT	0.113	
GSM + 5G WLAN+ NFC	Head	GSM	0.134	0.609
		NFC	0.0000006	
		5G WLAN	0.475	
	Body	GSM	0.935	1.336
		NFC	0.0000006	
		5G WLAN	0.401	
WCDMA + 2.4G WLAN + NFC	Head	WCDMA	0.137	0.308
		NFC	0.0000006	
		2.4G WLAN	0.171	
	Body	WCDMA	0.996	1.303
		NFC	0.0000006	
		2.4G WLAN	0.307	
WCDMA + Bluetooth+ NFC	Head	WCDMA	0.137	0.250
		NFC	0.0000006	
		BT	0.113	
	Body	WCDMA	0.996	1.109
		NFC	0.0000006	
		BT	0.113	
WCDMA + 5G WLAN+ NFC	Head	WCDMA	0.137	0.612
		NFC	0.0000006	
		5G WLAN	0.475	
	Body	WCDMA	0.996	1.397
		NFC	0.0000006	
		5G WLAN	0.401	
LTE + 2.4G WLAN + NFC	Head	LTE	0.214	0.385
		NFC	0.0000006	
		2.4G WLAN	0.171	
	Body	LTE	1.000	1.307
		NFC	0.0000006	
		2.4G WLAN	0.307	
LTE + Bluetooth+ NFC	Head	LTE	0.214	0.327
		NFC	0.0000006	
		BT	0.113	
	Body	LTE	1.000	1.113
		NFC	0.0000006	



		BT	0.113	
LTE + 5G WLAN+ NFC	Head	LTE	0.214	0.689
		NFC	0.0000006	
		5G WLAN	0.475	
	Body	LTE	1.000	1.401
		NFC	0.0000006	
		5G WLAN	0.401	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	DIP0G750	SN 06/22 DIP0G750-638	2025.05.20	2028.05.19
835MHz Dipole	MVG	DIP0G835	SN 06/22 DIP0G835-639	2025.05.20	2028.05.19
1800MHz Dipole	MVG	DIP1G800	SN 06/22 DIP1G800-640	2025.05.20	2028.05.19
1900MHz Dipole	MVG	DIP1G900	SN 06/22 DIP1G900-641	2025.05.20	2028.05.19
2300MHz Dipole	MVG	DIP2G300	SN 06/22 DIP2G100-644	2025.05.20	2028.05.19
2450MHz Dipole	MVG	DIP2G450	SN 06/22 DIP2G450-645	2025.05.20	2028.05.19
2600MHz Dipole	MVG	DIP2G600	SN 06/22 DIP2G600-646	2025.05.20	2028.05.19
5000MHz Dipole	MVG	DIP5G000	SN 06/22 DIP5G000-653	2025.05.22	2028.05.21
E-Field Probe	MVG	SSE2	2225-EPGO-450	2025.06.06	2026.06.05
Liquid Calibration Kit	MVG	OCPG 87	SN 06/22 OCPG87	2025.06.02	2026.06.01
Antenna	MVG	ANTA 73	SN 06/22 ANTA 73	N/A	N/A
Ellipsoid Phantom	MVG	ELLI 51	SN 06/22 ELLI 51	N/A	N/A
Phantom	MVG	SAM 148	SN 06/22 SAM148	N/A	N/A
Phone holder	MVG	MSH 117	SN 06/22 MSH 117	N/A	N/A
Laptop positioner	MVG	LSH 36	SN 06/22 LSH 38	N/A	N/A
Directional coupler	SHW	SHWDCP	202203280013	N/A	N/A
Network Analyzer	ZVL	R&S	116184	2025.03.05	2026.03.04
Multi Meter	DMM6500	Keithley	4527252	2025.03.06	2026.03.05
Signal Generator	Keysight	N5182B	MY59100717	2025.03.05	2026.03.04
Wireless Communication Test Set	R&S	CMW500	137737	2025.03.05	2026.03.04
Power Sensor	R&S	Z11	116184	2025.03.05	2026.03.04
Electronic Temperature hygrometer	N/A	ST-W2318	N/A	2025.03.05	2026.03.04
Temperature hygrometer	N/A	TP101	N/A	2025.03.05	2026.03.04



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-27

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW
Frequency (MHz)	750.000
Relative permittivity	41.49
Conductivity (S/m)	0.92
Probe	2225-EPGO-450
ConvF	1.08
Crest factor:	1:1




Maximum location: X=3.00, Y=2.00 ; SAR Peak: 1.64 W/kg

SAR 10g (W/Kg)	0.577
SAR 1g (W/Kg)	0.869



Z Axis Scan





System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-30

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW
Frequency (MHz)	750.000
Relative permittivity	42.61
Conductivity (S/m)	0.90
Probe	2225-EPGO-450
ConvF	1.08
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 1.19 W/kg

SAR 10g (W/Kg)	0.587
SAR 1g (W/Kg)	0.814



Z Axis Scan





System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-28

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW
Frequency (MHz)	835.000
Relative permittivity	41.68
Conductivity (S/m)	0.89
Probe	2225-EPGO-450
ConvF	1.02
Crest factor:	1:1




Maximum location: X=7.00, Y=6.00 ; SAR Peak: 1.72 W/kg

SAR 10g (W/Kg)	0.642
SAR 1g (W/Kg)	0.964



Z Axis Scan





System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-03

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW
Frequency (MHz)	835.000
Relative permittivity	42.20
Conductivity (S/m)	0.92
Probe	2225-EPGO-450
ConvF	1.02
Crest factor:	1:1




Maximum location: X=1.00, Y=-2.00 ; SAR Peak: 1.33 W/kg

SAR 10g (W/Kg)	0.569
SAR 1g (W/Kg)	1.005



Z Axis Scan





System Performance Check Data (1800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-28

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW
Frequency (MHz)	1800.000
Relative permittivity	40.85
Conductivity (S/m)	1.39
Probe	2225-EPGO-450
ConvF	1.21
Crest factor:	1:1




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 7.12 W/kg

SAR 10g (W/Kg)	1.915
SAR 1g (W/Kg)	3.670



Z Axis Scan





System Performance Check Data (1800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-01

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW
Frequency (MHz)	1800.000
Relative permittivity	40.65
Conductivity (S/m)	1.45
Probe	2225-EPGO-450
ConvF	1.21
Crest factor:	1:1




Maximum location: X=5.00, Y=3.00 ; SAR Peak: 6.92 W/kg

SAR 10g (W/Kg)	1.902
SAR 1g (W/Kg)	3.617



Z Axis Scan





System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-27

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	40.47
Conductivity (S/m)	1.39
Probe	2225-EPGO-450
ConvF	1.34
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.25 W/kg

SAR 10g (W/Kg)	2.037
SAR 1g (W/Kg)	4.034



Z Axis Scan





System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-02

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	40.04
Conductivity (S/m)	1.43
Probe	2225-EPGO-450
ConvF	1.34
Crest factor:	1:1




Maximum location: X=1.00, Y=-1.00 ; SAR Peak: 8.24 W/kg

SAR 10g (W/Kg)	2.070
SAR 1g (W/Kg)	4.047



Z Axis Scan





System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	41.08
Conductivity (S/m)	1.42
Probe	2225-EPGO-450
ConvF	1.34
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.98 W/kg

SAR 10g (W/Kg)	2.097
SAR 1g (W/Kg)	4.035



Z Axis Scan





System Performance Check Data (2300MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-26

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2300
Channels	Middle
Signal	CW
Frequency (MHz)	2300.000
Relative permittivity	40.22
Conductivity (S/m)	1.65
Probe	2225-EPGO-450
ConvF	1.47
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 9.02 W/kg

SAR 10g (W/Kg)	2.287
SAR 1g (W/Kg)	5.135



Z Axis Scan





System Performance Check Data (2300MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-04

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2300
Channels	Middle
Signal	CW
Frequency (MHz)	2300.000
Relative permittivity	39.81
Conductivity (S/m)	1.64
Probe	2225-EPGO-450
ConvF	1.47
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 8.06 W/kg

SAR 10g (W/Kg)	2.295
SAR 1g (W/Kg)	4.830



Z Axis Scan





System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-11-22

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW
Frequency (MHz)	2450.000
Relative permittivity	40.45
Conductivity (S/m)	1.81
Probe	2225-EPGO-450
ConvF	1.51
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 8.89 W/kg

SAR 10g (W/Kg)	2.496
SAR 1g (W/Kg)	5.308



Z Axis Scan





System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-11-30

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW
Frequency (MHz)	2450.000
Relative permittivity	40.59
Conductivity (S/m)	1.83
Probe	2225-EPGO-450
ConvF	1.51
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 7.63 W/kg

SAR 10g (W/Kg)	2.508
SAR 1g (W/Kg)	5.210



Z Axis Scan





System Performance Check Data (2600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2025-11-19

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW
Frequency (MHz)	2600.000
Relative permittivity	40.04
Conductivity (S/m)	2.02
Probe	2225-EPGO-450
ConvF	1.44
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 10.62 W/kg

SAR 10g (W/Kg)	2.559
SAR 1g (W/Kg)	5.637



Z Axis Scan





System Performance Check Data (2600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2025-12-04

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW
Frequency (MHz)	2600.000
Relative permittivity	39.29
Conductivity (S/m)	1.97
Probe	2225-EPGO-450
ConvF	1.44
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 10.15 W/kg

SAR 10g (W/Kg)	2.572
SAR 1g (W/Kg)	5.534



Z Axis Scan





System Performance Check Data (5200MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2025-11-17

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW
Frequency (MHz)	5200.000
Relative permittivity	36.70
Conductivity (S/m)	4.58
Probe	2225-EPGO-450
ConvF	1.58
Crest factor:	1:1




Maximum location: X=1.00, Y=1.00 ; SAR Peak: 21.72 W/kg

SAR 10g (W/Kg)	2.269
SAR 1g (W/Kg)	7.812



Z Axis Scan





System Performance Check Data (5200MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-12-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW
Frequency (MHz)	5200.000
Relative permittivity	36.52
Conductivity (S/m)	4.67
Probe	2225-EPGO-450
ConvF	1.58
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 23.27 W/kg

SAR 10g (W/Kg)	2.281
SAR 1g (W/Kg)	7.689



Z Axis Scan





System Performance Check Data (5400MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2025-11-17

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW
Frequency (MHz)	5400.000
Relative permittivity	36.36
Conductivity (S/m)	4.83
Probe	2225-EPGO-450
ConvF	1.60
Crest factor:	1:1




Maximum location: X=1.00, Y=1.00 ; SAR Peak: 26.39 W/kg

SAR 10g (W/Kg)	2.210
SAR 1g (W/Kg)	7.678



Z Axis Scan





System Performance Check Data (5400MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-12-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW
Frequency (MHz)	5400.000
Relative permittivity	36.04
Conductivity (S/m)	4.91
Probe	2225-EPGO-450
ConvF	1.60
Crest factor:	1:1




Maximum location: X=7.00, Y=2.00 ; SAR Peak: 24.57 W/kg

SAR 10g (W/Kg)	2.224
SAR 1g (W/Kg)	7.562



Z Axis Scan





System Performance Check Data (5600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-11-29

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW
Frequency (MHz)	5600.000
Relative permittivity	36.97
Conductivity (S/m)	5.07
Probe	2225-EPGO-450
ConvF	1.63
Crest factor:	1:1




Maximum location: X=-3.00, Y=3.00 ; SAR Peak: 24.69 W/kg

SAR 10g (W/Kg)	2.388
SAR 1g (W/Kg)	8.124



Z Axis Scan





System Performance Check Data (5600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-12.06

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW
Frequency (MHz)	5600.000
Relative permittivity	35.85
Conductivity (S/m)	5.03
Probe	2225-EPGO-450
ConvF	1.63
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 27.48 W/kg

SAR 10g (W/Kg)	2.362
SAR 1g (W/Kg)	8.329



Z Axis Scan





System Performance Check Data (5800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-11-29

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW
Frequency (MHz)	5800.000
Relative permittivity	35.68
Conductivity (S/m)	5.28
Probe	2225-EPGO-450
ConvF	1.62
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 25.04 W/kg

SAR 10g (W/Kg)	2.319
SAR 1g (W/Kg)	8.163



Z Axis Scan





System Performance Check Data (5800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2025-12.06

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW
Frequency (MHz)	5800.000
Relative permittivity	35.81
Conductivity (S/m)	5.26
Probe	2225-EPGO-450
ConvF	1.62
Crest factor:	1:1




Maximum location: X=5.00, Y=6.00 ; SAR Peak: 25.18 W/kg

SAR 10g (W/Kg)	2.304
SAR 1g (W/Kg)	8.203



Z Axis Scan






Appendix B. SAR Test Plots

Plot 1:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	848.8
SAR 10g (W/Kg)	0.052
SAR 1g (W/Kg)	0.086
ConvF	1.02
Relative permittivity	41.68
Conductivity (S/m)	0.89

Maximum location: X=-39.00, Y=-48.00 ; SAR Peak: 0.22 W/kg






Plot 2:

Test Date	2025-12-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	824.2
SAR 10g (W/Kg)	0.181
SAR 1g (W/Kg)	0.444
ConvF	1.02
Relative permittivity	42.20
Conductivity (S/m)	0.92

Maximum location: X=2.00, Y=25.00 ; SAR Peak: 0.50 W/kg






Plot 3:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1880
SAR 10g (W/Kg)	0.074
SAR 1g (W/Kg)	0.129
ConvF	1.34
Relative permittivity	40.85
Conductivity (S/m)	1.39

Maximum location: X=-48.00, Y=-55.00 ; SAR Peak: 0.25 W/kg






Plot 4:

Test Date	2025-12-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1850.2
SAR 10g (W/Kg)	0.463
SAR 1g (W/Kg)	0.899
ConvF	1.34
Relative permittivity	40.04
Conductivity (S/m)	1.43

Maximum location: X=-30.00, Y=63.00 ; SAR Peak: 1.49 W/kg






Plot 5:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	Band 2 (1900)
Signal	WCDMA
Frequency	1852.4
SAR 10g (W/Kg)	0.052
SAR 1g (W/Kg)	0.116
ConvF	1.34
Relative permittivity	40.47
Conductivity (S/m)	1.39

Maximum location: X=-42.00, Y=-48.00 ; SAR Peak: 0.29 W/kg






Plot 6:

Test Date	2025-12-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 2 (1900)
Signal	WCDMA
Frequency	1852.4
SAR 10g (W/Kg)	0.381
SAR 1g (W/Kg)	0.820
ConvF	1.34
Relative permittivity	40.04
Conductivity (S/m)	1.43

Maximum location: X=8.00, Y=111.00 ; SAR Peak: 1.75 W/kg






Plot 7:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	Band 4 (1700)
Signal	WCDMA
Frequency	1712.6
SAR 10g (W/Kg)	0.074
SAR 1g (W/Kg)	0.129
ConvF	1.21
Relative permittivity	40.85
Conductivity (S/m)	1.39

Maximum location: X=-48.00, Y=-55.00 ; SAR Peak: 0.25 W/kg






Plot 8:

Test Date	2025-12-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 4 (1700)
Signal	WCDMA
Frequency	1712.6
SAR 10g (W/Kg)	0.487
SAR 1g (W/Kg)	0.936
ConvF	1.21
Relative permittivity	40.65
Conductivity (S/m)	1.45

Maximum location: X=-29.00, Y=58.00 ; SAR Peak: 1.54 W/kg






Plot 9:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.028
SAR 1g (W/Kg)	0.054
ConvF	1.02
Relative permittivity	41.68
Conductivity (S/m)	0.89

Maximum location: X=-64.00, Y=-49.00 ; SAR Peak: 0.24 W/kg






Plot 10:

Test Date	2025-12-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.117
SAR 1g (W/Kg)	0.247
ConvF	1.02
Relative permittivity	42.20
Conductivity (S/m)	0.92

Maximum location: X=-5.00, Y=-8.00 ; SAR Peak: 0.48 W/kg






Plot 11:

Test Date	2025-11-22
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	ISM
Signal	IEEE 802.11b
Frequency	2462
SAR 10g (W/Kg)	0.088
SAR 1g (W/Kg)	0.164
ConvF	1.51
Relative permittivity	40.45
Conductivity (S/m)	1.81

Maximum location: X=-15.00, Y=-9.00 ; SAR Peak: 0.37 W/kg






Plot 12:

Test Date	2025-11-30
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back side
Band	ISM
Signal	IEEE 802.11b
Frequency	2462
SAR 10g (W/Kg)	0.127
SAR 1g (W/Kg)	0.295
ConvF	1.51
Relative permittivity	40.59
Conductivity (S/m)	1.83

Maximum location: X=-14.00, Y=-47.00 ; SAR Peak: 0.67 W/kg






Plot 13:

Test Date	2025-11-17
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Left head
Device Position	Cheek
Band	U-NII-1
Signal	IEEE 802.11ac
Frequency	5210
SAR 10g (W/Kg)	0.135
SAR 1g (W/Kg)	0.234
ConvF	1.58
Relative permittivity	36.70
Conductivity (S/m)	4.58

Maximum location: X=-1.00, Y=-7.00 ; SAR Peak: 1.60 W/kg






Plot 14:

Test Date	2025-12-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back side
Band	U-NII-1
Signal	IEEE 802.11ac
Frequency	5210
SAR 10g (W/Kg)	0.155
SAR 1g (W/Kg)	0.360
ConvF	1.58
Relative permittivity	36.52
Conductivity (S/m)	4.67


Maximum location: X=2.00, Y=22.00 ; SAR Peak: 1.44 W/kg



Plot 15:

Test Date	2025-11-17
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Left head
Device Position	Cheek
Band	U-NII-2a
Signal	IEEE 802.11a
Frequency	5320
SAR 10g (W/Kg)	0.122
SAR 1g (W/Kg)	0.353
ConvF	1.60
Relative permittivity	36.36
Conductivity (S/m)	4.83

Maximum location: X=-24.00, Y=-40.00 ; SAR Peak: 2.55 W/kg






Plot 16:

Test Date	2025-12-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2a
Signal	IEEE 802.11a
Frequency	5320
SAR 10g (W/Kg)	0.187
SAR 1g (W/Kg)	0.391
ConvF	1.60
Relative permittivity	36.04
Conductivity (S/m)	4.91

Maximum location: X=1.00, Y=-26.00 ; SAR Peak: 1.54 W/kg






Plot 17:

Test Date	2025-11-29
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Left head
Device Position	Cheek
Band	U-NII-2c
Signal	IEEE 802.11a
Frequency	5700
SAR 10g (W/Kg)	0.116
SAR 1g (W/Kg)	0.323
ConvF	1.63
Relative permittivity	36.97
Conductivity (S/m)	5.07

Maximum location: X=-32.00, Y=-31.00 ; SAR Peak: 1.99 W/kg






Plot 18:

Test Date	2025-12.06
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2c
Signal	IEEE 802.11a
Frequency	5700
SAR 10g (W/Kg)	0.078
SAR 1g (W/Kg)	0.105
ConvF	1.63
Relative permittivity	35.85
Conductivity (S/m)	5.03

Maximum location: X=35.00, Y=95.00 ; SAR Peak: 1.09 W/kg






Plot 19:

Test Date	2025-11-29
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Left head
Device Position	Cheek
Band	U-NII-3
Signal	IEEE 802.11a
Frequency	5785
SAR 10g (W/Kg)	0.124
SAR 1g (W/Kg)	0.436
ConvF	1.62
Relative permittivity	35.68
Conductivity (S/m)	5.28

Maximum location: X=-40.00, Y=1.00 ; SAR Peak: 3.00 W/kg






Plot 20:

Test Date	2025-12.06
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-3
Signal	IEEE 802.11a
Frequency	5785
SAR 10g (W/Kg)	0.103
SAR 1g (W/Kg)	0.244
ConvF	1.62
Relative permittivity	35.81
Conductivity (S/m)	5.26

Maximum location: X=-30.00, Y=7.00 ; SAR Peak: 1.68 W/kg






Plot 21:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	LTE band 2
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.075
SAR 1g (W/Kg)	0.155
ConvF	1.34
Relative permittivity	40.47
Conductivity (S/m)	1.39

Maximum location: X=-47.00, Y=-49.00 ; SAR Peak: 0.33 W/kg






Plot 22:

Test Date	2025-12-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 2
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.381
SAR 1g (W/Kg)	0.835
ConvF	1.34
Relative permittivity	40.04
Conductivity (S/m)	1.43

Maximum location: X=8.00, Y=111.00 ; SAR Peak: 1.75 W/kg






Plot 23:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 4
Signal	LTE FDD
Frequency	1720
SAR 10g (W/Kg)	0.074
SAR 1g (W/Kg)	0.129
ConvF	1.21
Relative permittivity	40.85
Conductivity (S/m)	1.39

Maximum location: X=-48.00, Y=-55.00 ; SAR Peak: 0.25 W/kg






Plot 24:

Test Date	2025-12-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 4
Signal	LTE FDD
Frequency	1720
SAR 10g (W/Kg)	0.450
SAR 1g (W/Kg)	0.844
ConvF	1.21
Relative permittivity	40.65
Conductivity (S/m)	1.45


Maximum location: X=-53.00, Y=1.00 ; SAR Peak: 1.34 W/kg



Plot 25:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 5
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.039
SAR 1g (W/Kg)	0.080
ConvF	1.02
Relative permittivity	41.68
Conductivity (S/m)	0.89

Maximum location: X=-53.00, Y=-14.00 ; SAR Peak: 0.17 W/kg






Plot 26:

Test Date	2025-12-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE band 5
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.411
SAR 1g (W/Kg)	0.767
ConvF	1.02
Relative permittivity	42.20
Conductivity (S/m)	0.92

Maximum location: X=-22.00, Y=16.00 ; SAR Peak: 1.28 W/kg






Plot 27:

Test Date	2025-11-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	LTE band 7
Signal	LTE FDD
Frequency	2510
SAR 10g (W/Kg)	0.087
SAR 1g (W/Kg)	0.179
ConvF	1.44
Relative permittivity	40.04
Conductivity (S/m)	2.02

Maximum location: X=-41.00, Y=-40.00 ; SAR Peak: 0.35 W/kg






Plot 28:

Test Date	2025-12-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 7
Signal	LTE FDD
Frequency	2510
SAR 10g (W/Kg)	0.429
SAR 1g (W/Kg)	0.935
ConvF	1.44
Relative permittivity	39.29
Conductivity (S/m)	1.97

Maximum location: X=18.00, Y=63.00 ; SAR Peak: 1.77 W/kg






Plot 29:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 12
Signal	LTE FDD
Frequency	711
SAR 10g (W/Kg)	0.020
SAR 1g (W/Kg)	0.037
ConvF	1.08
Relative permittivity	41.49
Conductivity (S/m)	0.92

Maximum location: X=-24.00, Y=-1.00 ; SAR Peak: 0.08 W/kg






Plot 30:

Test Date	2025-11-30
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE band 12
Signal	LTE FDD
Frequency	711
SAR 10g (W/Kg)	0.406
SAR 1g (W/Kg)	0.791
ConvF	1.08
Relative permittivity	42.61
Conductivity (S/m)	0.90


Maximum location: X=-6.00, Y=2.00 ; SAR Peak: 1.26 W/kg



Plot 31:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 13
Signal	LTE FDD
Frequency	782
SAR 10g (W/Kg)	0.054
SAR 1g (W/Kg)	0.124
ConvF	1.08
Relative permittivity	41.49
Conductivity (S/m)	0.92

Maximum location: X=-49.00, Y=-8.00 ; SAR Peak: 0.24 W/kg






Plot 32:

Test Date	2025-11-30
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE band 13
Signal	LTE FDD
Frequency	782
SAR 10g (W/Kg)	0.348
SAR 1g (W/Kg)	0.661
ConvF	1.08
Relative permittivity	42.61
Conductivity (S/m)	0.90

Maximum location: X=3.00, Y=2.00 ; SAR Peak: 1.11 W/kg






Plot 33:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	LTE band 17
Signal	LTE FDD
Frequency	710
SAR 10g (W/Kg)	0.041
SAR 1g (W/Kg)	0.099
ConvF	1.08
Relative permittivity	41.49
Conductivity (S/m)	0.92

Maximum location: X=-42.00, Y=-49.00 ; SAR Peak: 0.26 W/kg






Plot 34:

Test Date	2025-11-30
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE band 17
Signal	LTE FDD
Frequency	710
SAR 10g (W/Kg)	0.117
SAR 1g (W/Kg)	0.247
ConvF	1.08
Relative permittivity	42.61
Conductivity (S/m)	0.90


Maximum location: X=-5.00, Y=-8.00 ; SAR Peak: 0.48 W/kg



Plot 35:

Test Date	2025-11-27
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 25
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.079
SAR 1g (W/Kg)	0.142
ConvF	1.34
Relative permittivity	40.47
Conductivity (S/m)	1.39

Maximum location: X=-48.00, Y=-8.00 ; SAR Peak: 0.26 W/kg






Plot 36:

Test Date	2025-12-02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 25
Signal	LTE FDD
Frequency	1860
SAR 10g (W/Kg)	0.342
SAR 1g (W/Kg)	0.768
ConvF	1.34
Relative permittivity	41.08
Conductivity (S/m)	1.42


Maximum location: X=10.00, Y=120.00 ; SAR Peak: 1.39 W/kg



Plot 37:

Test Date	2025-11-28
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 26
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.048
SAR 1g (W/Kg)	0.118
ConvF	1.02
Relative permittivity	41.68
Conductivity (S/m)	0.89

Maximum location: X=-33.00, Y=-9.00 ; SAR Peak: 0.31 W/kg






Plot 38:

Test Date	2025-12-03
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Bottom Side
Band	LTE band 26
Signal	LTE FDD
Frequency	844
SAR 10g (W/Kg)	0.103
SAR 1g (W/Kg)	0.208
ConvF	1.02
Relative permittivity	42.20
Conductivity (S/m)	0.92


Maximum location: X=7.00, Y=7.00 ; SAR Peak: 0.41 W/kg



Plot 39:

Test Date	2025-11-19
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 38
Signal	LTE TDD
Frequency	2610
SAR 10g (W/Kg)	0.054
SAR 1g (W/Kg)	0.124
ConvF	1.44
Relative permittivity	40.04
Conductivity (S/m)	2.02

Maximum location: X=-49.00, Y=-8.00 ; SAR Peak: 0.24 W/kg






Plot 40:

Test Date	2025-12-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 38
Signal	LTE TDD
Frequency	2610
SAR 10g (W/Kg)	0.285
SAR 1g (W/Kg)	0.591
ConvF	1.44
Relative permittivity	39.29
Conductivity (S/m)	1.97

Maximum location: X=58.00, Y=111.00 ; SAR Peak: 1.14 W/kg






Plot 41:

Test Date	2025-11-26
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Right head
Device Position	Cheek
Band	LTE band 40
Signal	LTE TDD
Frequency	2310
SAR 10g (W/Kg)	0.101
SAR 1g (W/Kg)	0.175
ConvF	1.47
Relative permittivity	40.22
Conductivity (S/m)	1.65

Maximum location: X=-48.00, Y=-24.00 ; SAR Peak: 0.38 W/kg






Plot 42:

Test Date	2025-12-04
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 40
Signal	LTE TDD
Frequency	2310
SAR 10g (W/Kg)	0.349
SAR 1g (W/Kg)	0.693
ConvF	1.47
Relative permittivity	39.81
Conductivity (S/m)	1.64

Maximum location: X=-62.00, Y=32.00 ; SAR Peak: 1.27 W/kg






Plot 43:

Test Date	2025-11-29
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 66
Signal	LTE FDD
Frequency	1745
SAR 10g (W/Kg)	0.125
SAR 1g (W/Kg)	0.209
ConvF	1.21
Relative permittivity	40.85
Conductivity (S/m)	1.39

Maximum location: X=-49.00, Y=-34.00 ; SAR Peak: 0.34 W/kg






Plot 44:

Test Date	2025-12-01
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 66
Signal	LTE FDD
Frequency	1745
SAR 10g (W/Kg)	0.306
SAR 1g (W/Kg)	0.585
ConvF	1.21
Relative permittivity	40.65
Conductivity (S/m)	1.45

Maximum location: X=-52.00, Y=40.00 ; SAR Peak: 1.01 W/kg





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※