

FCC PART 15.247 TEST REPORT

For

Gouldin Technologies, LLC

2150 Chenault Dr., Carrollton, Texas 75006 United States

FCC ID: 2AOQ7-WXL

Report Type: Original Report	Product Type: Watchman
Test Engineer:	CK Huang
Report Number:	RXM200522051-00C
Report Date:	2020-06-16
Reviewed By:	Oscar Ye EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
FACTOR & OVER LIMIT CALCULATION.....	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST RESULTS SUMMARY	19
TEST DATA	20
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43

TEST DATA	43
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	68
APPLICABLE STANDARD	68
TEST PROCEDURE	68
TEST DATA	68
FCC §15.247(d) - BAND EDGES TESTING	74
APPLICABLE STANDARD	74
TEST PROCEDURE	74
TEST DATA	74

GENERAL INFORMATION**Product Description for Equipment under Test (EUT)**

Applicant	Gouldin Technologies, LLC
Tested Model	WXL-P
Series Model	WXL-S
Model Difference	See declaration letter
Product Type	Watchman
Power Supply	DC 12V
RF Function	Classic BT
Operating Band/Frequency	2402-2480MHz
Channel Number	79
Channel Separation	1 MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type	FPC Antenna
Maximum Antenna Gain	2.0 dBi

**All measurement and test data in this report was gathered from production sample serial number: 20200522051.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-05-22)*

Objective

This test report is prepared on behalf of *Gouldin Technologies, LLC* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS Submittal with FCC ID: 2AOQ7-WXL
FCC Part 15C DXX Submittal with FCC ID: 2AOQ7-WXL

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test software: adb

GFSK, $\pi/4$ -DQPSK, 8DPSK Power level: Default

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
Chenyang	Adapter	CYSE24-120200C	/
TP-LINK	Router	TL-WDR5620	1188431022424
/	Card Reader	/	/
Schneider Electric	Main Relay	RXM2LB2BD	/
Schneider Electric	Auxiliary Relay	/	/
/	SD Card	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	5	EUT	Notebook
RJ45 Cable	5	EUT	Notebook
HDMI Cable	5	EUT	Notebook
RJ45 Cable	5	EUT	Router
Data Cable	5	EUT	Card Reader
Signal Cable	5	EUT	Main Relay
Signal Cable	5	EUT	Auxiliary Relay
Power Cable	1	EUT	Adapter
Power Cable	1	Adapter	LISN/AC source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/0009	2019-12-14	2020-12-13
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
CellGate	RF Cable	CellGate C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K0 3-101746-zn	2019-08-05	2020-08-04
Rohde & Schwarz	LISN	ENV216	101115	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	357.8810.52	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data (worst case):

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi 802.11b	2412-2462	2.0	1.58	21.50	141.25	20	0.0444	1.00
Wi-Fi 802.11g		2.0	1.58	20.50	112.20	20	0.0353	1.00
Wi-Fi 802.11n-HT20		2.0	1.58	20.00	100.00	20	0.0314	1.00
BLE	2402-2480	2.0	1.58	2.50	1.78	20	0.0006	1.00
Bluetooth	2402-2480	2.0	1.58	4.00	2.51	20	0.0008	1.00

Note: Wi-Fi and BT/BLE cannot transmit simultaneously.

Conclusion: The device meets MPE at distance 20cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a FPC antenna with IPEX connector for Bluetooth, and the antenna gain is 2.0 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa


The testing was performed by CK Huang on 2020-06-08.

EUT operation mode: Transmitting in high channel of BDR(GFSK) mode (Worst case)

AC 120V/60 Hz, Line



		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.163	17.70	19.83	37.53	55.30	-17.77	Average
2	0.163	32.50	19.83	52.33	65.30	-12.97	QP
3	0.199	5.90	19.82	25.72	53.67	-27.95	Average
4	0.199	24.60	19.82	44.42	63.67	-19.25	QP
5	0.256	3.80	19.82	23.62	51.56	-27.94	Average
6	0.256	13.70	19.82	33.52	61.56	-28.04	QP
7	0.561	0.90	19.75	20.65	46.00	-25.35	Average
8	0.561	9.90	19.75	29.65	56.00	-26.35	QP
9	1.276	3.00	19.82	22.82	46.00	-23.18	Average
10	1.276	8.50	19.82	28.32	56.00	-27.68	QP
11	15.801	15.30	19.69	34.99	50.00	-15.01	Average
12	15.801	22.60	19.69	42.29	60.00	-17.71	QP

AC 120V/60 Hz, Neutral

		Read		Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.150	14.30	19.82	34.12	56.00	-21.88 Average
2	0.150	31.60	19.82	51.42	66.00	-14.58 QP
3	0.202	7.80	19.82	27.62	53.54	-25.92 Average
4	0.202	22.80	19.82	42.62	63.54	-20.92 QP
5	0.267	5.40	19.82	25.22	51.20	-25.98 Average
6	0.267	15.00	19.82	34.82	61.20	-26.38 QP
7	0.375	-1.40	19.77	18.37	48.39	-30.02 Average
8	0.375	8.40	19.77	28.17	58.39	-30.22 QP
9	0.564	2.60	19.75	22.35	46.00	-23.65 Average
10	0.564	10.80	19.75	30.55	56.00	-25.45 QP
11	15.885	16.79	19.70	36.49	50.00	-13.51 Average
12	15.885	24.29	19.70	43.99	60.00	-16.01 QP



Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V /m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	24.1~26.5 °C
Relative Humidity:	50~51 %
ATM Pressure:	101.2~101.4 kPa

The testing was performed by CK Huang from 2020-06-03 to 2020-06-08.


EUT operation mode: Transmitting

Spurious Emission Test:

Model: WXL-P

30MHz-1GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of BDR(GFSK) Mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
31.056387	31.02	100.0	V	129.0	-5.1	40.00	8.98
52.414500	30.17	100.0	V	161.0	-18.1	40.00	9.83
86.463250	25.55	100.0	V	231.0	-18.0	40.00	14.45
148.501450	28.66	100.0	V	0.0	-12.8	43.50	14.84
209.794850	29.62	100.0	V	273.0	-12.7	43.50	13.88
375.003350	31.89	200.0	V	0.0	-9.2	46.00	14.11

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) Mode in Z-axis of orientation was recorded

Note:

1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1187.000000	---	39.49	150.0	H	0.0	-18.1	54.00	14.51
1187.000000	43.75	---	150.0	H	0.0	-18.1	74.00	30.25
1583.100000	---	35.29	150.0	H	0.0	-16.0	54.00	18.71
1583.100000	41.20	---	150.0	H	0.0	-16.0	74.00	32.80
1979.200000	---	35.29	150.0	H	351.0	-14.5	54.00	18.71
1979.200000	44.83	---	150.0	H	351.0	-14.5	74.00	29.17
4354.100000	---	36.29	200.0	H	358.0	-6.4	54.00	17.71
4354.100000	45.47	---	200.0	H	358.0	-6.4	74.00	28.53
9729.500000	---	37.37	150.0	H	69.0	2.0	54.00	16.63
9729.500000	47.43	---	150.0	H	69.0	2.0	74.00	26.57
17796.000000	---	48.65	100.0	V	124.0	8.8	54.00	5.35
17796.000000	55.36	---	100.0	V	124.0	8.8	74.00	18.64

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1187.000000	---	40.18	200.0	H	349.0	-18.1	54.00	13.82
1187.000000	44.45	---	200.0	H	349.0	-18.1	74.00	29.55
1583.100000	---	36.68	200.0	H	322.0	-16.0	54.00	17.32
1583.100000	43.30	---	200.0	H	322.0	-16.0	74.00	30.70
1982.600000	---	38.96	200.0	V	0.0	-14.5	54.00	15.04
1982.600000	44.97	---	200.0	V	0.0	-14.5	74.00	29.03
3563.600000	---	34.81	200.0	V	0.0	-8.6	54.00	19.19
3563.600000	43.42	---	200.0	V	0.0	-8.6	74.00	30.58
4352.400000	---	34.82	150.0	H	351.0	-6.4	54.00	19.18
4352.400000	47.15	---	150.0	H	351.0	-6.4	74.00	26.85
17811.300000	---	48.66	150.0	V	62.0	8.8	54.00	5.34
17811.300000	54.40	---	150.0	V	62.0	8.8	74.00	19.60

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1187.000000	---	39.83	150.0	H	4.0	-18.1	54.00	14.17
1187.000000	44.77	---	150.0	H	4.0	-18.1	74.00	29.23
1979.200000	---	36.82	150.0	H	0.0	-14.5	54.00	17.18
1979.200000	46.04	---	150.0	H	0.0	-14.5	74.00	27.96
3563.600000	---	33.18	100.0	V	9.0	-8.6	54.00	20.82
3563.600000	39.22	---	100.0	V	9.0	-8.6	74.00	34.78
4357.500000	---	35.83	150.0	H	351.0	-6.4	54.00	18.17
4357.500000	48.13	---	150.0	H	351.0	-6.4	74.00	25.87
11023.200000	---	40.38	200.0	V	9.0	2.9	54.00	13.62
11023.200000	44.22	---	200.0	V	9.0	2.9	74.00	29.78
17801.100000	---	48.85	150.0	H	351.0	8.8	54.00	5.15
17801.100000	54.02	---	150.0	H	351.0	8.8	74.00	19.98

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case high channel of BDR(GFSK) Mode in Z-axis of orientation was recorded



Date: 5.JUN.2020 19:58:36



Date: 5.JUN.2020 20:16:05

Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) Mode in Z-axis of orientation was recorded


Note:

- Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	47.32	---	150.0	H	55.0	-2.9	74.00	26.68
2390.000000	---	39.62	150.0	H	55.0	-2.9	54.00	14.38
High Channel: 2480MHz								
2483.500000	47.10	---	150.0	H	156.0	-2.5	74.00	26.90
2483.500000	---	40.11	150.0	H	156.0	-2.5	54.00	13.89

Model: WXL-S**30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of BDR(GFSK) Mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
30.866644	31.07	100.0	V	101.0	-5.0	40.00	8.93
40.751750	28.82	100.0	V	150.0	-11.7	40.00	11.18
53.036700	29.95	100.0	V	96.0	-18.1	40.00	10.05
84.053900	25.02	100.0	V	215.0	-18.1	40.00	14.98
209.822250	29.61	100.0	V	285.0	-12.7	43.50	13.89
374.996150	31.73	200.0	V	0.0	-9.2	46.00	14.27

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) Mode in Z-axis of orientation was recorded

Note:

1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1187.000000	---	40.35	150.0	H	347.0	-18.1	54.00	13.65
1187.000000	44.85	---	150.0	H	347.0	-18.1	74.00	29.15
1979.200000	---	40.23	200.0	H	23.0	-14.5	54.00	13.77
1979.200000	50.21	---	200.0	H	23.0	-14.5	74.00	23.79
3567.000000	---	35.56	200.0	V	341.0	-8.6	54.00	18.44
3567.000000	46.22	---	200.0	V	341.0	-8.6	74.00	27.78
4359.200000	---	33.87	150.0	H	0.0	-6.4	54.00	20.13
4359.200000	46.21	---	150.0	H	0.0	-6.4	74.00	27.79
7817.000000	---	38.14	150.0	V	353.0	1.5	54.00	15.86
7817.000000	47.08	---	150.0	V	353.0	1.5	74.00	26.92
17782.400000	---	47.47	200.0	H	0.0	8.8	54.00	6.53
17782.400000	56.57	---	200.0	H	0.0	8.8	74.00	17.43

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1187.000000	---	40.39	150.0	H	0.0	-18.1	54.00	13.61
1187.000000	45.22	---	150.0	H	0.0	-18.1	74.00	28.78
1984.300000	---	36.83	200.0	H	0.0	-14.5	54.00	17.17
1984.300000	47.70	---	200.0	H	0.0	-14.5	74.00	26.30
3565.300000	---	34.93	150.0	H	312.0	-8.6	54.00	19.07
3565.300000	42.07	---	150.0	H	312.0	-8.6	74.00	31.93
4359.200000	---	34.46	150.0	H	296.0	-6.4	54.00	19.54
4359.200000	46.12	---	150.0	H	296.0	-6.4	74.00	27.88
9879.100000	---	39.58	150.0	H	155.0	2.0	54.00	14.42
9879.100000	43.83	---	150.0	H	155.0	2.0	74.00	30.17
17816.400000	---	48.44	200.0	H	145.0	8.8	54.00	5.56
17816.400000	55.40	---	200.0	H	145.0	8.8	74.00	18.60

High Channel: 2480MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1187.000000	---	39.52	100.0	H	351.0	-18.1	54.00	14.48
1187.000000	44.64	---	100.0	H	351.0	-18.1	74.00	29.36
1979.200000	---	35.69	150.0	H	358.0	-14.5	54.00	18.31
1979.200000	45.12	---	150.0	H	358.0	-14.5	74.00	28.88
3568.700000	---	33.88	150.0	H	0.0	-8.6	54.00	20.12
3568.700000	41.27	---	150.0	H	0.0	-8.6	74.00	32.73
4364.300000	---	36.74	150.0	H	351.0	-6.4	54.00	17.26
4364.300000	44.60	---	150.0	H	351.0	-6.4	74.00	29.40
10394.200000	---	40.13	200.0	V	256.0	2.2	54.00	13.87
10394.200000	43.83	---	200.0	V	256.0	2.2	74.00	30.17
17823.200000	---	48.70	150.0	H	117.0	8.8	54.00	5.30
17823.200000	54.62	---	150.0	H	117.0	8.8	74.00	19.38


18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case high channel of BDR(GFSK) Mode in Z-axis of orientation was recorded



Date: 5.JUN.2020 23:34:59

Vertical



Date: 5.JUN.2020 23:55:32

Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) Mode in Z-axis of orientation was recorded

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	45.91	---	150.0	V	198.0	-2.9	74.00	28.09
2390.000000	---	40.17	150.0	V	198.0	-2.9	54.00	13.83
High Channel: 2480MHz								
2483.500000	46.58	---	150.0	V	107.0	-2.5	74.00	27.42
2483.500000	---	40.11	150.0	V	107.0	-2.5	54.00	13.89



Conducted Spurious Emissions at Antenna Port

BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel**EDR ($\pi/4$ -DQPSK): Low Channel**


EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data**Environmental Conditions**

Temperature:	26.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by CK Huang on 2020-06-05.


EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	0.994	0.701	Pass
	Adjacent	2403			
	Middle	2441	0.999	0.697	Pass
	Adjacent	2442			
	High	2480	0.999	0.697	Pass
	Adjacent	2479			
EDR ($\pi/4$ -DQPSK)	Low	2402	0.999	0.886	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.890	Pass
	Adjacent	2442			
	High	2480	0.999	0.890	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	0.999	0.878	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.874	Pass
	Adjacent	2442			
	High	2480	0.999	0.874	Pass
	Adjacent	2479			

Note: For BDR and EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




Date: 5 JUN 2020 11:03:55

BDR (GFSK): High Channel




Date: 5 JUN 2020 11:05:51

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 5 JUN 2020 11:11:14

EDR ($\pi/4$ -DQPSK): Middle Channel





Date: 5 JUN 2020 11:09:02

EDR ($\pi/4$ -DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel

Date: 5 JUN 2020 11:15:08

EDR (8DPSK): High Channel

Date: 5 JUN 2020 11:17:24

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**


Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by CK Huang on 2020-06-04.


EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.052
	Middle	2441	1.046
	High	2480	1.046
EDR ($\pi/4$-DQPSK)	Low	2402	1.329
	Middle	2441	1.335
	High	2480	1.335
EDR (8DPSK)	Low	2402	1.317
	Middle	2441	1.311
	High	2480	1.311



BDR (GFSK): Low Channel

BDR (GFSK): Middle Channel



BDR (GFSK): High Channel



EDR ($\pi/4$ -DQPSK): Low Channel**EDR($\pi/4$ -DQPSK): Middle Channel**

Delta 1 [T1]
 0.47 dB
 1.33466934 MHz

RBW 30 kHz
 VBW 100 kHz
 SWT 8.5 ms

Ref Lvl 20 dBm
 RF Att 20 dB
 Unit dBm

21 dB Offset
 -24.71 dBm
 2.47938377 GHz
 0.47 dB
 1.33466934 MHz

-D1 -4.58 dBm
 1MAX
 -D2 -24.58 dBm
 1

Center 2.48 GHz
 300 kHz/
 Span 3 MHz

Date: 4.JUN.2020 17:47:30

Delta 1 [T1]

Ref Lvl 20 dBm

20 dBm

0.16 dB

1.31663327 MHz

RBW 30 kHz

VBW 100 kHz

SWT 8.5 ms

RF Att 20 dB

Unit dBm

21 dB Offset

-26.24 dBm

2.40139579 GHz

0.16 dB

1.31663327 MHz

D1 -6.09 dBm

1MAX

D2 -26.09 dBm

1

1


Center 2.402 GHz

300 kHz/


Span 3 MHz

Date: 4 JUN 2020 17:48:46

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**

Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa


The testing was performed by CK Huang on 2020-06-04.

EUT operation mode: Hopping


Test Result: Compliant.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	25.4 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by CK Huang on 2020-06-04.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.409	0.131	0.4	Pass
		Middle	0.409	0.131	0.4	Pass
		High	0.409	0.131	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.673	0.268	0.4	Pass
		Middle	1.673	0.268	0.4	Pass
		High	1.679	0.269	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.936	0.313	0.4	Pass
		Middle	2.944	0.314	0.4	Pass
		High	2.944	0.314	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.409	0.131	0.4	Pass
		Middle	0.411	0.132	0.4	Pass
		High	0.415	0.133	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.685	0.270	0.4	Pass
		Middle	1.673	0.268	0.4	Pass
		High	1.679	0.269	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.936	0.313	0.4	Pass
		Middle	2.928	0.312	0.4	Pass
		High	2.944	0.314	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.411	0.132	0.4	Pass
		Middle	0.409	0.131	0.4	Pass
		High	0.411	0.132	0.4	Pass
		Note: 3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.679	0.269	0.4	Pass
		Middle	1.679	0.269	0.4	Pass
		High	1.685	0.270	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.936	0.313	0.4	Pass
		Middle	2.952	0.315	0.4	Pass
		High	2.928	0.312	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




BDR (GFSK): Pulse time, Middle Channel, DH1



BDR (GFSK): Pulse time, High Channel, DH1



BDR (GFSK): Pulse time, Low Channel, DH3



Delta 1 [T1]
 Ref Lvl -4.77 dB
 20 dBm 1.673359 ms
 RBW 500 kHz
 VBW 2 MHz
 SWT 3 ms
 RF Att 20 dB
 Unit dBm

21 dB Offset
 -45.59 dBm
 -18.422846 μ s
 -4.77 dB
 1.673359 ms

Center 2.441 GHz
 300 μ s/

Date: 4.JUN.2020 18:05:10

Ref Lvl 20 dBm

Delta 1 [T1]

-1.31 dB

1.679371 ms

RBW 500 kHz

VBW 2 MHz

SWT 3 ms

RF Att 20 dB

Unit dBm

21 dB Offset

▼1 [T1]

▲1 [T1]

-47.81 dBm

-24.434870 μ s

-1.31 dB

1.679371 ms


TR

Center 2.48 GHz


300 μ s/



Date: 4.JUN.2020 18:05:32



BDR (GFSK): Pulse time, Low Channel, DH5





BDR (GFSK): Pulse time, Middle Channel, DH5




BDR (GFSK): Pulse time, High Channel, DH5**EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1**


EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1**



EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3



EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5**



EDR (8DPSK): Pulse time, Low Channel, 3DH1**EDR (8DPSK): Pulse time, Middle Channel, 3DH1**



EDR (8DPSK): Pulse time, High Channel, 3DH1




EDR (8DPSK): Pulse time, Low Channel, 3DH3



EDR (8DPSK): Pulse time, Middle Channel, 3DH3**EDR (8DPSK): Pulse time, High Channel, 3DH3**

EDR (8DPSK): Pulse time, Low Channel, 3DH5**EDR (8DPSK): Pulse time, Middle Channel, 3DH5**

EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data**Environmental Conditions**


Temperature:	25.1 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by CK Huang on 2020-06-04.


EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	2.64	0.63	125
	2441	3.00	0.69	125
	2480	3.63	0.86	125
EDR ($\pi/4$-DQPSK)	2402	-2.01	0.69	125
	2441	-1.64	0.77	125
	2480	-0.66	0.96	125
EDR (8DPSK)	2402	-1.64	1.84	125
	2441	-1.15	2.00	125
	2480	-0.17	2.31	125

BDR (GFSK): 2402MHz



BDR (GFSK): 2441MHz




BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	25.3-26.2 °C
Relative Humidity:	49-50 %
ATM Pressure:	101.3-101.6 kPa


The testing was performed by CK Huang from 2020-06-04 to 2020-06-05.

EUT operation mode: Transmitting & Hopping


Test Result: Compliant.



Band Edge

BDR (GFSK): Left Side




BDR (GFSK): Right Side





EDR ($\pi/4$ -DQPSK): Left SideEDR ($\pi/4$ -DQPSK): Right Side

EDR (8DPSK): Left Side




EDR (8DPSK): Right Side






BDR (GFSK): Left Side - Hopping

Date: 5 JUN 2020 11:29:18


BDR (GFSK): Right Side- Hopping

Date: 5 JUN 2020 11:26:21

EDR ($\pi/4$ -DQPSK): Left Side- Hopping**EDR ($\pi/4$ -DQPSK): Right Side- Hopping**

EDR (8DPSK): Left Side- Hopping

Date: 5 JUN 2020 11:34:41

EDR (8DPSK): Right Side- Hopping

Date: 5 JUN 2020 11:22:14

******* END OF REPORT *******