

FCC Report (WIFI)

Applicant: Nuvvyo Inc.

Address of Applicant: 555 Legget Drive Tower B Suite 836 Kanata, ON K2K2X3, Canada

Manufacturer: Nuvvyo Inc.

Address of Manufacturer: 555 Legget Drive Tower B Suite 836 Kanata, ON K2K2X3, Canada

Factory: SHENZHEN GIEC DIGITAL CO., LTD

Address of Factory: 1 Building, Factory, .7 District, Dayang Development Areas, Fuyong Street, Bao'an, Shenzhen, Guangdong, China

Equipment Under Test (EUT)

Product Name: OTA streamer

Model No.: TABLO DUAL LITE DVR, TABLO DUAL 64 DVR

FCC ID: 2AOR7-TABLOBOX

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: January 30, 2018

Date of Test: January 31, 2018-March 20, 2018

Date of report issued: March 21, 2018

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 21, 2018	Original

Prepared By:




Date:

March 21, 2018

Project Engineer

Check By:



Date:

March 21, 2018

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	9
7.1 ANTENNA REQUIREMENT	9
7.2 CONDUCTED EMISSIONS	10
7.3 CONDUCTED PEAK OUTPUT POWER	13
7.4 CHANNEL BANDWIDTH	15
7.5 POWER SPECTRAL DENSITY	27
7.6 BAND EDGES	39
7.6.1 Conducted Emission Method	39
7.6.2 Radiated Emission Method	45
7.7 SPURIOUS EMISSION	56
7.7.1 Conducted Emission Method	56
7.7.2 Radiated Emission Method	67
8 TEST SETUP PHOTO	101
9 EUT CONSTRUCTIONAL DETAILS	103

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.4:2014 and ANSI C63.10:2013.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	OTA streamer
Model No.:	TABLO DUAL LITE DVR, TABLO DUAL 64 DVR
Test Model No:	TABLO DUAL LITE DVR
<i>Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are color, model name and storage capacity for commercial purpose. All of the samples with different storage capacity (8GB and 64GB) have been tested, only the worst case 64GB was shown the report.</i>	
Serial No.:	GI-C02097152
Test sample(s) ID:	GTS201801000072-1
Sample(s) Status	Engineer sample
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integral antenna
Antenna gain:	Main Antenna: 6.43dBi Aux Antenna: 5.59dBi
Power supply:	Adapter Model:BSY018B120150U W Input: AC 100-240V, 50/60Hz, 0.4A Output: DC 12V, 1.5A

Remark: 802.11b/g is SISO mode , All other modulations are MIMO mode

Directional gain of MIMO mode : $=10 \log[(10^{G1}/20 + 10^{G2}/20 + \dots + 10^{GN}/20)^2 / NANT]$ dBi

$=10 \log[(10^{6.43}/20 + 10^{5.59}/20)^2 / 2] = 9.03 \text{ dBi}$

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

5.3 Description of Support Units

None

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018. ● Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.
--

5.5 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	July. 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	June 28 2017	June 27 2018
4	Loop Antenna	Zhinan	ZN30900A	GTS534	June 28 2017	June 27 2018
5	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	June 28 2017	June 27 2018
6	Double-ridged horn antenna	SCHWARZBECK	9120D	GTS208	June 28 2017	June 27 2018
7	Horn Antenna	ETS-LINDGREN	3160-09	GTS218	June 28 2017	June 27 2018
8	RF Amplifier	HP	8347A	GTS204	June 28 2017	June 27 2018
9	RF Amplifier	HP	8349B	GTS206	June 28 2017	June 27 2018
10	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	June 28 2017	June 27 2018
11	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	June 28 2017	June 27 2018
12	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
13	Coaxial Cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
14	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
15	Coaxial Cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
16	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
17	Power Meter	Anritsu	ML2495A	GTS540	June 28 2017	June 27 2018
18	Power Sensor	Anritsu	MA2411B	GTS541	June 28 2017	June 27 2018

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May 15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	High voltage probe	SCHWARZBECK	TK9420	GTS537	June 28 2017	June 27 2018
6	ISN	SCHWARZBECK	NTFM 8158	GTS565	June 28 2017	June 27 2018
7	Coaxial Cable	GTS	N/A	GTS227	June 28 2017	June 27 2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018
10	10dB Pulse Limiter	Rohde & Schwarz	N/A	GTS224	June 28 2017	June 27 2018


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
<i>The antenna is integral antenna, the best case gain of the main antenna is 6.43dBi and aux antenna is 5.59dBi</i> 	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	Refer to section 5.2 for details														
Test results:	Pass														


Measurement data

Line:



Freq MHz	Reading level dBuV	1ISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.152	42.44	0.40	0.07	42.91	65.91	-23.00	QP
0.152	30.90	0.40	0.07	31.37	55.91	-24.54	Average
0.182	36.85	0.40	0.10	37.35	64.42	-27.07	QP
0.182	27.49	0.40	0.10	27.99	54.42	-26.43	Average
0.332	34.88	0.38	0.10	35.36	59.40	-24.04	QP
0.332	29.45	0.38	0.10	29.93	49.40	-19.47	Average
0.456	46.28	0.33	0.11	46.72	56.76	-10.04	QP
0.456	42.88	0.33	0.11	43.32	46.76	-3.44	Average
0.759	35.48	0.25	0.13	35.86	56.00	-20.14	QP
0.759	29.73	0.25	0.13	30.11	46.00	-15.89	Average
4.952	33.29	0.20	0.17	33.66	56.00	-22.34	QP
4.952	26.37	0.20	0.17	26.74	46.00	-19.26	Average

Neutral:




Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.153	41.44	0.40	0.07	41.91	65.82	-23.91	QP
0.153	29.65	0.40	0.07	30.12	55.82	-25.70	Average
0.178	38.79	0.40	0.09	39.28	64.59	-25.31	QP
0.178	27.39	0.40	0.09	27.88	54.59	-26.71	Average
0.211	33.01	0.40	0.11	33.52	63.18	-29.66	QP
0.211	17.83	0.40	0.11	18.34	53.18	-34.84	Average
0.456	45.42	0.33	0.11	45.86	56.76	-10.90	QP
0.456	41.13	0.33	0.11	41.57	46.76	-5.19	Average
4.622	32.49	0.20	0.17	32.86	56.00	-23.14	QP
4.622	23.82	0.20	0.17	24.19	46.00	-21.81	Average
4.952	34.97	0.20	0.17	35.34	56.00	-20.66	QP
4.952	25.47	0.20	0.17	25.84	46.00	-20.16	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D01 DTS Meas Guidance V03
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A 'Power Meter' is connected to an 'E.U.T.' (Equipment Under Test) by a red cable. Both the Power Meter and the E.U.T. are positioned on a 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a 'Ground Reference Plane', which is represented by a thick grey horizontal bar at the bottom of the setup.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Main Antenna: Antenna gain=6.43dBi ;Limit=30-(6.43-6)=29.57dBm

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	18.59	19.99	18.15	18.37	29.57	Pass
Middle	18.57	20.37	18.44	18.69		
Highest	18.47	20.43	18.60	18.70		

Aux Antenna:

Test CH	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	21.27	21.50	21.66	21.61	30.00	Pass
Middle	21.79	22.06	22.06	21.73		
Highest	21.75	22.00	22.07	21.80		

MIMO:


Test CH	Peak Output Power (dBm)		Limit(dBm)	Result
	802.11n(HT20)	802.11n(HT40)		
Lowest	$10\log(10^{1.815} + 10^{2.166})=23.26$	$10\log(10^{1.837} + 10^{2.161})=23.30$	26.97	Pass
Middle	$10\log(10^{1.844} + 10^{2.206})=23.63$	$10\log(10^{1.869} + 10^{2.173})=23.48$		
Highest	$10\log(10^{1.860} + 10^{2.207})=23.68$	$10\log(10^{1.870} + 10^{2.180})=23.53$		

NOTE: MIMO output power = ANT main Power+ANT AUX Power

Directional gain=9.03dBi

Limit=30-(9.03-6)=26.97dBm

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 DTS Meas Guidance V03
Limit:	>500KHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Main Antenna:

Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.121	16.380	17.141	35.850	>500	Pass
Middle	10.128	16.377	17.341	35.905		
Highest	10.120	16.404	17.306	35.856		


Aux Antenna:

Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.068	16.368	17.314	35.832	>500	Pass
Middle	10.143	16.359	17.567	35.721		
Highest	9.830	16.377	17.557	36.223		


Test plot as follows:

Main Antenna:


Test mode:	802.11b
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11g
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT20)
------------	---------------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT40)
------------	---------------



Lowest channel




Middle channel




Highest channel

Aux Antenna:


Test mode:	802.11b
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11g
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT20)
------------	---------------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT40)
------------	---------------



Lowest channel




Middle channel



Highest channel

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance V03
Limit:	8dBm/3kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve on its screen, is connected to an E.U.T. (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a table labeled 'Non-Conducted Table'. Below the table is a thick grey bar labeled 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Main Antenna:

Test CH	Power Spectral Density (dBm)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-7.86	-8.55	-11.51	-14.51	8.00	Pass
Middle	-7.93	-8.06	-11.69	-14.28		
Highest	-7.53	-8.07	-11.73	-14.64		

Aux Antenna:

Test CH	Power Spectral Density (dBm)				Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	-4.14	-7.68	-7.40	-10.31	8.00	Pass
Middle	-4.70	-7.42	-7.02	-10.48		
Highest	-4.65	-7.78	-7.09	-10.86		


MIMO:

Test CH	Peak Output Power (dBm)		Limit(dBm)	Result
	802.11n(HT20)	802.11n(HT40)		
Lowest	$10\log(10^{-1.151} + 10^{-0.740}) = -5.98$	$10\log(10^{-1.451} + 10^{-1.031}) = -8.91$	8.00	Pass
Middle	$10\log(10^{-1.169} + 10^{-0.702}) = -5.75$	$10\log(10^{-1.428} + 10^{-1.048}) = -8.97$		
Highest	$10\log(10^{-1.173} + 10^{-0.709}) = -5.81$	$10\log(10^{-1.464} + 10^{-1.086}) = -9.34$		


Test plot as follows:

Main Antenna:


Test mode:	802.11b
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11g
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT20)
------------	---------------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT40)
------------	---------------



Lowest channel




Middle channel




Highest channel

Aux Antenna:


Test mode:	802.11b
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11g
------------	---------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT20)
------------	---------------



Lowest channel




Middle channel




Highest channel


Test mode:	802.11n(HT40)
------------	---------------



Lowest channel




Middle channel



Highest channel


7.6 Band edges



7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance V03
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:


Main Antenna:





Aux Antenna:

Test mode:	802.11b
------------	---------




Lowest channel




Highest channel



Test mode:	802.11g
------------	---------




Lowest channel



Highest channel



7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak RMS	1MHz 1MHz	3MHz 3MHz	Peak Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00 74.00		Average Peak
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Main Antenna:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.07	27.59	5.38	34.01	51.03	74.00	-22.97	Horizontal
2400.00	61.23	27.58	5.39	34.01	60.19	74.00	-13.81	Horizontal
2390.00	53.78	27.59	5.38	34.01	52.74	74.00	-21.26	Vertical
2400.00	63.14	27.58	5.39	34.01	62.10	74.00	-11.90	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.71	27.59	5.38	34.01	37.67	54.00	-16.33	Horizontal
2400.00	47.05	27.58	5.39	34.01	46.01	54.00	-7.99	Horizontal
2390.00	40.57	27.59	5.38	34.01	39.53	54.00	-14.47	Vertical
2400.00	48.21	27.58	5.39	34.01	47.17	54.00	-6.83	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	52.91	27.53	5.47	33.92	51.99	74.00	-22.01	Horizontal
2500.00	48.60	27.55	5.49	29.93	51.71	74.00	-22.29	Horizontal
2483.50	55.26	27.53	5.47	33.92	54.34	74.00	-19.66	Vertical
2500.00	51.19	27.55	5.49	29.93	54.30	74.00	-19.70	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.14	27.53	5.47	33.92	38.22	54.00	-15.78	Horizontal
2500.00	35.16	27.55	5.49	29.93	38.27	54.00	-15.73	Horizontal
2483.50	41.13	27.53	5.47	33.92	40.21	54.00	-13.79	Vertical
2500.00	37.06	27.55	5.49	29.93	40.17	54.00	-13.83	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	51.35	27.59	5.38	34.01	50.31	74.00	-23.69	Horizontal
2400.00	60.27	27.58	5.39	34.01	59.23	74.00	-14.77	Horizontal
2390.00	53.02	27.59	5.38	34.01	51.98	74.00	-22.02	Vertical
2400.00	61.99	27.58	5.39	34.01	60.95	74.00	-13.05	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.20	27.59	5.38	34.01	37.16	54.00	-16.84	Horizontal
2400.00	46.46	27.58	5.39	34.01	45.42	54.00	-8.58	Horizontal
2390.00	40.00	27.59	5.38	34.01	38.96	54.00	-15.04	Vertical
2400.00	47.56	27.58	5.39	34.01	46.52	54.00	-7.48	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.88	27.53	5.47	33.92	50.96	74.00	-23.04	Horizontal
2500.00	47.81	27.55	5.49	29.93	50.92	74.00	-23.08	Horizontal
2483.50	54.08	27.53	5.47	33.92	53.16	74.00	-20.84	Vertical
2500.00	50.26	27.55	5.49	29.93	53.37	74.00	-20.63	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.52	27.53	5.47	33.92	37.60	54.00	-16.40	Horizontal
2500.00	34.68	27.55	5.49	29.93	37.79	54.00	-16.21	Horizontal
2483.50	40.44	27.53	5.47	33.92	39.52	54.00	-14.48	Vertical
2500.00	36.55	27.55	5.49	29.93	39.66	54.00	-14.34	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Aux Antenna:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	52.09	27.59	5.38	34.01	51.05	74.00	-22.95	Horizontal
2400.00	61.25	27.58	5.39	34.01	60.21	74.00	-13.79	Horizontal
2390.00	53.81	27.59	5.38	34.01	52.77	74.00	-21.23	Vertical
2400.00	63.17	27.58	5.39	34.01	62.13	74.00	-11.87	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.73	27.59	5.38	34.01	37.69	54.00	-16.31	Horizontal
2400.00	47.07	27.58	5.39	34.01	46.03	54.00	-7.97	Horizontal
2390.00	40.58	27.59	5.38	34.01	39.54	54.00	-14.46	Vertical
2400.00	48.23	27.58	5.39	34.01	47.19	54.00	-6.81	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	52.94	27.53	5.47	33.92	52.02	74.00	-21.98	Horizontal
2500.00	48.62	27.55	5.49	29.93	51.73	74.00	-22.27	Horizontal
2483.50	55.29	27.53	5.47	33.92	54.37	74.00	-19.63	Vertical
2500.00	51.22	27.55	5.49	29.93	54.33	74.00	-19.67	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.16	27.53	5.47	33.92	38.24	54.00	-15.76	Horizontal
2500.00	35.18	27.55	5.49	29.93	38.29	54.00	-15.71	Horizontal
2483.50	41.14	27.53	5.47	33.92	40.22	54.00	-13.78	Vertical
2500.00	37.07	27.55	5.49	29.93	40.18	54.00	-13.82	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	51.33	27.59	5.38	34.01	50.29	74.00	-23.71	Horizontal
2400.00	60.23	27.58	5.39	34.01	59.19	74.00	-14.81	Horizontal
2390.00	52.99	27.59	5.38	34.01	51.95	74.00	-22.05	Vertical
2400.00	61.95	27.58	5.39	34.01	60.91	74.00	-13.09	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.18	27.59	5.38	34.01	37.14	54.00	-16.86	Horizontal
2400.00	46.44	27.58	5.39	34.01	45.40	54.00	-8.60	Horizontal
2390.00	39.98	27.59	5.38	34.01	38.94	54.00	-15.06	Vertical
2400.00	47.54	27.58	5.39	34.01	46.50	54.00	-7.50	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.85	27.53	5.47	33.92	50.93	74.00	-23.07	Horizontal
2500.00	47.78	27.55	5.49	29.93	50.89	74.00	-23.11	Horizontal
2483.50	54.04	27.53	5.47	33.92	53.12	74.00	-20.88	Vertical
2500.00	50.23	27.55	5.49	29.93	53.34	74.00	-20.66	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.50	27.53	5.47	33.92	37.58	54.00	-16.42	Horizontal
2500.00	34.66	27.55	5.49	29.93	37.77	54.00	-16.23	Horizontal
2483.50	40.42	27.53	5.47	33.92	39.50	54.00	-14.50	Vertical
2500.00	36.53	27.55	5.49	29.93	39.64	54.00	-14.36	Vertical

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

MIMO:

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	51.57	27.59	5.38	34.01	50.53	74.00	-23.47	Horizontal
2400.00	60.56	27.58	5.39	34.01	59.52	74.00	-14.48	Horizontal
2390.00	53.25	27.59	5.38	34.01	52.21	74.00	-21.79	Vertical
2400.00	62.34	27.58	5.39	34.01	61.30	74.00	-12.70	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.36	27.59	5.38	34.01	37.32	54.00	-16.68	Horizontal
2400.00	46.64	27.58	5.39	34.01	45.60	54.00	-8.40	Horizontal
2390.00	40.17	27.59	5.38	34.01	39.13	54.00	-14.87	Vertical
2400.00	47.76	27.58	5.39	34.01	46.72	54.00	-7.28	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	52.20	27.53	5.47	33.92	51.28	74.00	-22.72	Horizontal
2500.00	48.05	27.55	5.49	29.93	51.16	74.00	-22.84	Horizontal
2483.50	54.44	27.53	5.47	33.92	53.52	74.00	-20.48	Vertical
2500.00	50.55	27.55	5.49	29.93	53.66	74.00	-20.34	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.71	27.53	5.47	33.92	37.79	54.00	-16.21	Horizontal
2500.00	34.83	27.55	5.49	29.93	37.94	54.00	-16.06	Horizontal
2483.50	40.65	27.53	5.47	33.92	39.73	54.00	-14.27	Vertical
2500.00	36.70	27.55	5.49	29.93	39.81	54.00	-14.19	Vertical

Remark:

5. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
6. The emission levels of other frequencies are very lower than the limit and not show in test report.

MIMO:

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	50.73	27.59	5.38	34.01	49.69	74.00	-24.31	Horizontal
2400.00	59.44	27.58	5.39	34.01	58.40	74.00	-15.60	Horizontal
2390.00	52.35	27.59	5.38	34.01	51.31	74.00	-22.69	Vertical
2400.00	60.99	27.58	5.39	34.01	59.95	74.00	-14.05	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	37.76	27.59	5.38	34.01	36.72	54.00	-17.28	Horizontal
2400.00	45.95	27.58	5.39	34.01	44.91	54.00	-9.09	Horizontal
2390.00	39.50	27.59	5.38	34.01	38.46	54.00	-15.54	Vertical
2400.00	47.01	27.58	5.39	34.01	45.97	54.00	-8.03	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	51.00	27.53	5.47	33.92	50.08	74.00	-23.92	Horizontal
2500.00	47.12	27.55	5.49	29.93	50.23	74.00	-23.77	Horizontal
2483.50	53.07	27.53	5.47	33.92	52.15	74.00	-21.85	Vertical
2500.00	49.45	27.55	5.49	29.93	52.56	74.00	-21.44	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.98	27.53	5.47	33.92	37.06	54.00	-16.94	Horizontal
2500.00	34.26	27.55	5.49	29.93	37.37	54.00	-16.63	Horizontal
2483.50	39.85	27.53	5.47	33.92	38.93	54.00	-15.07	Vertical
2500.00	36.11	27.55	5.49	29.93	39.22	54.00	-14.78	Vertical

Remark:

5. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
6. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.7 Spurious Emission

7.7.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance V03
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Main Antenna:


Test mode:	802.11b
------------	---------

Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11g
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11n(HT20)
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11n(HT40)
Lowest channel	




30MHz~25GHz

Middle channel



30MHz~25GHz


Highest channel



30MHz~25GHz


Aux Antenna:

Test mode:	802.11b
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11g
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11n(HT20)
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test mode:	802.11n(HT40)
Lowest channel	




30MHz~25GHz

Middle channel




30MHz~25GHz


Highest channel



30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	30MHz-88MHz		40.00		Quasi-peak
	88MHz-216MHz		43.50		Quasi-peak
	216MHz-960MHz		46.00		Quasi-peak
	960MHz-1GHz		54.00		Quasi-peak
	Above 1GHz	54.00		Average	
		74.00		Peak	
Test setup:	Below 1GHz				
					
	Above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table(0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement Data


■ Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
33.211	52.40	11.27	0.59	35.23	29.03	40.00	-10.97	QP
77.051	59.65	7.43	1.00	36.52	31.56	40.00	-8.44	QP
85.598	59.95	9.30	1.07	36.60	33.72	40.00	-6.28	QP
86.503	60.28	9.56	1.08	36.61	34.31	40.00	-5.69	QP
87.725	59.62	9.94	1.09	36.62	34.03	40.00	-5.97	QP
340.782	54.69	14.37	2.57	37.46	34.17	46.00	-11.83	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
30.105	58.94	11.20	0.55	35.01	35.68	40.00	-4.32	QP
31.843	59.33	11.24	0.57	35.14	36.00	40.00	-4.00	QP
34.639	57.32	11.29	0.61	35.33	33.89	40.00	-6.11	QP
37.945	56.00	11.86	0.64	35.54	32.96	40.00	-7.04	QP
87.418	58.59	9.81	1.09	36.62	32.87	40.00	-7.13	QP
336.035	60.78	14.29	2.55	37.46	40.16	46.00	-5.84	QP

■ Above 1GHz

Main Antenna:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	41.14	31.79	8.62	32.10	49.45	74.00	-24.55	Vertical
7236.00	34.75	36.19	11.68	31.97	50.65	74.00	-23.35	Vertical
9648.00	33.10	38.07	14.16	31.56	53.77	74.00	-20.23	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	39.67	31.79	8.62	32.10	47.98	74.00	-26.02	Horizontal
7236.00	34.43	36.19	11.68	31.97	50.33	74.00	-23.67	Horizontal
9648.00	32.64	38.07	14.16	31.56	53.31	74.00	-20.69	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	30.15	31.79	8.62	32.10	38.46	54.00	-15.54	Vertical
7236.00	23.60	36.19	11.68	31.97	39.50	54.00	-14.50	Vertical
9648.00	23.43	38.07	14.16	31.56	44.10	54.00	-9.90	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	29.17	31.79	8.62	32.10	37.48	54.00	-16.52	Horizontal
7236.00	23.00	36.19	11.68	31.97	38.90	54.00	-15.10	Horizontal
9648.00	22.38	38.07	14.16	31.56	43.05	54.00	-10.95	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	40.05	31.85	8.66	32.12	48.44	74.00	-25.56	Vertical
7311.00	34.73	36.37	11.71	31.91	50.90	74.00	-23.10	Vertical
9748.00	34.05	38.27	14.25	31.56	55.01	74.00	-18.99	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.42	31.85	8.66	32.12	48.81	74.00	-25.19	Horizontal
7311.00	33.32	36.37	11.71	31.91	49.49	74.00	-24.51	Horizontal
9748.00	33.91	38.27	14.25	31.56	54.87	74.00	-19.13	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.85	31.85	8.66	32.12	39.24	54.00	-14.76	Vertical
7311.00	23.03	36.37	11.71	31.91	39.20	54.00	-14.80	Vertical
9748.00	23.29	38.27	14.25	31.56	44.25	54.00	-9.75	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.49	31.85	8.66	32.12	38.88	54.00	-15.12	Horizontal
7311.00	22.39	36.37	11.71	31.91	38.56	54.00	-15.44	Horizontal
9748.00	23.62	38.27	14.25	31.56	44.58	54.00	-9.42	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	46.08	31.90	8.70	32.15	54.53	74.00	-19.47	Vertical
7386.00	35.72	36.49	11.76	31.83	52.14	74.00	-21.86	Vertical
9848.00	37.57	38.62	14.31	31.77	58.73	74.00	-15.27	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	45.20	31.90	8.70	32.15	53.65	74.00	-20.35	Horizontal
7386.00	34.53	36.49	11.76	31.83	50.95	74.00	-23.05	Horizontal
9848.00	33.70	38.62	14.31	31.77	54.86	74.00	-19.14	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	36.90	31.90	8.70	32.15	45.35	54.00	-8.65	Vertical
7386.00	25.61	36.49	11.76	31.83	42.03	54.00	-11.97	Vertical
9848.00	26.05	38.62	14.31	31.77	47.21	54.00	-6.79	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	35.50	31.90	8.70	32.15	43.95	54.00	-10.05	Horizontal
7386.00	23.90	36.49	11.76	31.83	40.32	54.00	-13.68	Horizontal
9848.00	22.94	38.62	14.31	31.77	44.10	54.00	-9.90	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	41.03	31.79	8.62	32.10	49.34	74.00	-24.66	Vertical
7236.00	34.69	36.19	11.68	31.97	50.59	74.00	-23.41	Vertical
9648.00	33.05	38.07	14.16	31.56	53.72	74.00	-20.28	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	39.59	31.79	8.62	32.10	47.90	74.00	-26.10	Horizontal
7236.00	34.38	36.19	11.68	31.97	50.28	74.00	-23.72	Horizontal
9648.00	32.60	38.07	14.16	31.56	53.27	74.00	-20.73	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	30.06	31.79	8.62	32.10	38.37	54.00	-15.63	Vertical
7236.00	23.54	36.19	11.68	31.97	39.44	54.00	-14.56	Vertical
9648.00	23.38	38.07	14.16	31.56	44.05	54.00	-9.95	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	29.09	31.79	8.62	32.10	37.40	54.00	-16.60	Horizontal
7236.00	22.95	36.19	11.68	31.97	38.85	54.00	-15.15	Horizontal
9648.00	22.34	38.07	14.16	31.56	43.01	54.00	-10.99	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	39.96	31.85	8.66	32.12	48.35	74.00	-25.65	Vertical
7311.00	34.68	36.37	11.71	31.91	50.85	74.00	-23.15	Vertical
9748.00	34.01	38.27	14.25	31.56	54.97	74.00	-19.03	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.35	31.85	8.66	32.12	48.74	74.00	-25.26	Horizontal
7311.00	33.27	36.37	11.71	31.91	49.44	74.00	-24.56	Horizontal
9748.00	33.88	38.27	14.25	31.56	54.84	74.00	-19.16	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.77	31.85	8.66	32.12	39.16	54.00	-14.84	Vertical
7311.00	22.98	36.37	11.71	31.91	39.15	54.00	-14.85	Vertical
9748.00	23.25	38.27	14.25	31.56	44.21	54.00	-9.79	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.43	31.85	8.66	32.12	38.82	54.00	-15.18	Horizontal
7311.00	22.35	36.37	11.71	31.91	38.52	54.00	-15.48	Horizontal
9748.00	23.58	38.27	14.25	31.56	44.54	54.00	-9.46	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	45.93	31.90	8.70	32.15	54.38	74.00	-19.62	Vertical
7386.00	35.63	36.49	11.76	31.83	52.05	74.00	-21.95	Vertical
9848.00	37.51	38.62	14.31	31.77	58.67	74.00	-15.33	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	45.08	31.90	8.70	32.15	53.53	74.00	-20.47	Horizontal
7386.00	34.45	36.49	11.76	31.83	50.87	74.00	-23.13	Horizontal
9848.00	33.64	38.62	14.31	31.77	54.80	74.00	-19.20	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	36.77	31.90	8.70	32.15	45.22	54.00	-8.78	Vertical
7386.00	25.52	36.49	11.76	31.83	41.94	54.00	-12.06	Vertical
9848.00	25.99	38.62	14.31	31.77	47.15	54.00	-6.85	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	35.38	31.90	8.70	32.15	43.83	54.00	-10.17	Horizontal
7386.00	23.82	36.49	11.76	31.83	40.24	54.00	-13.76	Horizontal
9848.00	22.88	38.62	14.31	31.77	44.04	54.00	-9.96	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Aux Antenna:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	41.26	31.79	8.62	32.10	49.57	74.00	-24.43	Vertical
7236.00	34.83	36.19	11.68	31.97	50.73	74.00	-23.27	Vertical
9648.00	33.15	38.07	14.16	31.56	53.82	74.00	-20.18	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	39.78	31.79	8.62	32.10	48.09	74.00	-25.91	Horizontal
7236.00	34.50	36.19	11.68	31.97	50.40	74.00	-23.60	Horizontal
9648.00	32.70	38.07	14.16	31.56	53.37	74.00	-20.63	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	30.27	31.79	8.62	32.10	38.58	54.00	-15.42	Vertical
7236.00	23.68	36.19	11.68	31.97	39.58	54.00	-14.42	Vertical
9648.00	23.48	38.07	14.16	31.56	44.15	54.00	-9.85	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	29.27	31.79	8.62	32.10	37.58	54.00	-16.42	Horizontal
7236.00	23.07	36.19	11.68	31.97	38.97	54.00	-15.03	Horizontal
9648.00	22.43	38.07	14.16	31.56	43.10	54.00	-10.90	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	40.15	31.85	8.66	32.12	48.54	74.00	-25.46	Vertical
7311.00	34.80	36.37	11.71	31.91	50.97	74.00	-23.03	Vertical
9748.00	34.09	38.27	14.25	31.56	55.05	74.00	-18.95	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.50	31.85	8.66	32.12	48.89	74.00	-25.11	Horizontal
7311.00	33.37	36.37	11.71	31.91	49.54	74.00	-24.46	Horizontal
9748.00	33.96	38.27	14.25	31.56	54.92	74.00	-19.08	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.94	31.85	8.66	32.12	39.33	54.00	-14.67	Vertical
7311.00	23.09	36.37	11.71	31.91	39.26	54.00	-14.74	Vertical
9748.00	23.33	38.27	14.25	31.56	44.29	54.00	-9.71	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.58	31.85	8.66	32.12	38.97	54.00	-15.03	Horizontal
7311.00	22.45	36.37	11.71	31.91	38.62	54.00	-15.38	Horizontal
9748.00	23.66	38.27	14.25	31.56	44.62	54.00	-9.38	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	46.26	31.90	8.70	32.15	54.71	74.00	-19.29	Vertical
7386.00	35.84	36.49	11.76	31.83	52.26	74.00	-21.74	Vertical
9848.00	37.65	38.62	14.31	31.77	58.81	74.00	-15.19	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	45.35	31.90	8.70	32.15	53.80	74.00	-20.20	Horizontal
7386.00	34.63	36.49	11.76	31.83	51.05	74.00	-22.95	Horizontal
9848.00	33.77	38.62	14.31	31.77	54.93	74.00	-19.07	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	37.07	31.90	8.70	32.15	45.52	54.00	-8.48	Vertical
7386.00	25.72	36.49	11.76	31.83	42.14	54.00	-11.86	Vertical
9848.00	26.13	38.62	14.31	31.77	47.29	54.00	-6.71	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	35.64	31.90	8.70	32.15	44.09	54.00	-9.91	Horizontal
7386.00	23.99	36.49	11.76	31.83	40.41	54.00	-13.59	Horizontal
9848.00	23.01	38.62	14.31	31.77	44.17	54.00	-9.83	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	41.23	31.79	8.62	32.10	49.54	74.00	-24.46	Vertical
7236.00	34.81	36.19	11.68	31.97	50.71	74.00	-23.29	Vertical
9648.00	33.14	38.07	14.16	31.56	53.81	74.00	-20.19	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	39.75	31.79	8.62	32.10	48.06	74.00	-25.94	Horizontal
7236.00	34.48	36.19	11.68	31.97	50.38	74.00	-23.62	Horizontal
9648.00	32.68	38.07	14.16	31.56	53.35	74.00	-20.65	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	30.24	31.79	8.62	32.10	38.55	54.00	-15.45	Vertical
7236.00	23.66	36.19	11.68	31.97	39.56	54.00	-14.44	Vertical
9648.00	23.47	38.07	14.16	31.56	44.14	54.00	-9.86	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	29.24	31.79	8.62	32.10	37.55	54.00	-16.45	Horizontal
7236.00	23.05	36.19	11.68	31.97	38.95	54.00	-15.05	Horizontal
9648.00	22.42	38.07	14.16	31.56	43.09	54.00	-10.91	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	40.12	31.85	8.66	32.12	48.51	74.00	-25.49	Vertical
7311.00	34.78	36.37	11.71	31.91	50.95	74.00	-23.05	Vertical
9748.00	34.08	38.27	14.25	31.56	55.04	74.00	-18.96	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.48	31.85	8.66	32.12	48.87	74.00	-25.13	Horizontal
7311.00	33.36	36.37	11.71	31.91	49.53	74.00	-24.47	Horizontal
9748.00	33.95	38.27	14.25	31.56	54.91	74.00	-19.09	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.92	31.85	8.66	32.12	39.31	54.00	-14.69	Vertical
7311.00	23.08	36.37	11.71	31.91	39.25	54.00	-14.75	Vertical
9748.00	23.32	38.27	14.25	31.56	44.28	54.00	-9.72	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.55	31.85	8.66	32.12	38.94	54.00	-15.06	Horizontal
7311.00	22.43	36.37	11.71	31.91	38.60	54.00	-15.40	Horizontal
9748.00	23.65	38.27	14.25	31.56	44.61	54.00	-9.39	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	46.21	31.90	8.70	32.15	54.66	74.00	-19.34	Vertical
7386.00	35.81	36.49	11.76	31.83	52.23	74.00	-21.77	Vertical
9848.00	37.63	38.62	14.31	31.77	58.79	74.00	-15.21	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	45.31	31.90	8.70	32.15	53.76	74.00	-20.24	Horizontal
7386.00	34.60	36.49	11.76	31.83	51.02	74.00	-22.98	Horizontal
9848.00	33.76	38.62	14.31	31.77	54.92	74.00	-19.08	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	37.02	31.90	8.70	32.15	45.47	54.00	-8.53	Vertical
7386.00	25.70	36.49	11.76	31.83	42.12	54.00	-11.88	Vertical
9848.00	26.11	38.62	14.31	31.77	47.27	54.00	-6.73	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	35.61	31.90	8.70	32.15	44.06	54.00	-9.94	Horizontal
7386.00	23.97	36.49	11.76	31.83	40.39	54.00	-13.61	Horizontal
9848.00	22.99	38.62	14.31	31.77	44.15	54.00	-9.85	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

MIMO:

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	40.86	31.79	8.62	32.10	49.17	74.00	-24.83	Vertical
7236.00	34.57	36.19	11.68	31.97	50.47	74.00	-23.53	Vertical
9648.00	32.97	38.07	14.16	31.56	53.64	74.00	-20.36	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	39.44	31.79	8.62	32.10	47.75	74.00	-26.25	Horizontal
7236.00	34.28	36.19	11.68	31.97	50.18	74.00	-23.82	Horizontal
9648.00	32.53	38.07	14.16	31.56	53.20	74.00	-20.80	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	29.90	31.79	8.62	32.10	38.21	54.00	-15.79	Vertical
7236.00	23.43	36.19	11.68	31.97	39.33	54.00	-14.67	Vertical
9648.00	23.30	38.07	14.16	31.56	43.97	54.00	-10.03	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	28.95	31.79	8.62	32.10	37.26	54.00	-16.74	Horizontal
7236.00	22.85	36.19	11.68	31.97	38.75	54.00	-15.25	Horizontal
9648.00	22.27	38.07	14.16	31.56	42.94	54.00	-11.06	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	39.82	31.85	8.66	32.12	48.21	74.00	-25.79	Vertical
7311.00	34.58	36.37	11.71	31.91	50.75	74.00	-23.25	Vertical
9748.00	33.94	38.27	14.25	31.56	54.90	74.00	-19.10	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.22	31.85	8.66	32.12	48.61	74.00	-25.39	Horizontal
7311.00	33.19	36.37	11.71	31.91	49.36	74.00	-24.64	Horizontal
9748.00	33.82	38.27	14.25	31.56	54.78	74.00	-19.22	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.63	31.85	8.66	32.12	39.02	54.00	-14.98	Vertical
7311.00	22.89	36.37	11.71	31.91	39.06	54.00	-14.94	Vertical
9748.00	23.19	38.27	14.25	31.56	44.15	54.00	-9.85	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.31	31.85	8.66	32.12	38.70	54.00	-15.30	Horizontal
7311.00	22.27	36.37	11.71	31.91	38.44	54.00	-15.56	Horizontal
9748.00	23.52	38.27	14.25	31.56	44.48	54.00	-9.52	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	45.68	31.90	8.70	32.15	54.13	74.00	-19.87	Vertical
7386.00	35.47	36.49	11.76	31.83	51.89	74.00	-22.11	Vertical
9848.00	37.39	38.62	14.31	31.77	58.55	74.00	-15.45	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	44.86	31.90	8.70	32.15	53.31	74.00	-20.69	Horizontal
7386.00	34.31	36.49	11.76	31.83	50.73	74.00	-23.27	Horizontal
9848.00	33.53	38.62	14.31	31.77	54.69	74.00	-19.31	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	36.53	31.90	8.70	32.15	44.98	54.00	-9.02	Vertical
7386.00	25.37	36.49	11.76	31.83	41.79	54.00	-12.21	Vertical
9848.00	25.88	38.62	14.31	31.77	47.04	54.00	-6.96	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	35.18	31.90	8.70	32.15	43.63	54.00	-10.37	Horizontal
7386.00	23.69	36.49	11.76	31.83	40.11	54.00	-13.89	Horizontal
9848.00	22.78	38.62	14.31	31.77	43.94	54.00	-10.06	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

MIMO:

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	40.84	31.81	8.63	32.11	49.17	74.00	-24.83	Vertical
7266.00	34.56	36.28	11.69	31.94	50.59	74.00	-23.41	Vertical
9688.00	32.96	38.13	14.21	31.52	53.78	74.00	-20.22	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4844.00	39.42	31.81	8.63	32.11	47.75	74.00	-26.25	Horizontal
7266.00	34.27	36.28	11.69	31.94	50.30	74.00	-23.70	Horizontal
9688.00	32.52	38.13	14.21	31.52	53.34	74.00	-20.66	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	29.88	31.81	8.63	32.11	38.21	54.00	-15.79	Vertical
7266.00	23.42	36.28	11.69	31.94	39.45	54.00	-14.55	Vertical
9688.00	23.30	38.13	14.21	31.52	44.12	54.00	-9.88	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4844.00	28.93	31.81	8.63	32.11	37.26	54.00	-16.74	Horizontal
7266.00	22.84	36.28	11.69	31.94	38.87	54.00	-15.13	Horizontal
9688.00	22.26	38.13	14.21	31.52	43.08	54.00	-10.92	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is too weak, instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	39.80	31.85	8.66	32.12	48.19	74.00	-25.81	Vertical
7311.00	34.57	36.37	11.71	31.91	50.74	74.00	-23.26	Vertical
9748.00	33.94	38.27	14.25	31.56	54.90	74.00	-19.10	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	40.21	31.85	8.66	32.12	48.60	74.00	-25.40	Horizontal
7311.00	33.18	36.37	11.71	31.91	49.35	74.00	-24.65	Horizontal
9748.00	33.81	38.27	14.25	31.56	54.77	74.00	-19.23	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	30.62	31.85	8.66	32.12	39.01	54.00	-14.99	Vertical
7311.00	22.88	36.37	11.71	31.91	39.05	54.00	-14.95	Vertical
9748.00	23.18	38.27	14.25	31.56	44.14	54.00	-9.86	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	30.30	31.85	8.66	32.12	38.69	54.00	-15.31	Horizontal
7311.00	22.26	36.37	11.71	31.91	38.43	54.00	-15.57	Horizontal
9748.00	23.52	38.27	14.25	31.56	44.48	54.00	-9.52	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	45.66	31.88	8.68	32.13	54.09	74.00	-19.91	Vertical
7356.00	35.46	36.45	11.75	31.86	51.80	74.00	-22.20	Vertical
9808.00	37.38	38.43	14.29	31.68	58.42	74.00	-15.58	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4904.00	44.84	31.88	8.68	32.13	53.27	74.00	-20.73	Horizontal
7356.00	34.29	36.45	11.75	31.86	50.63	74.00	-23.37	Horizontal
9808.00	33.52	38.43	14.29	31.68	54.56	74.00	-19.44	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	36.51	31.88	8.68	32.13	44.94	54.00	-9.06	Vertical
7356.00	25.35	36.45	11.75	31.86	41.69	54.00	-12.31	Vertical
9808.00	25.87	38.43	14.29	31.68	46.91	54.00	-7.09	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4904.00	35.16	31.88	8.68	32.13	43.59	54.00	-10.41	Horizontal
7356.00	23.67	36.45	11.75	31.86	40.01	54.00	-13.99	Horizontal
9808.00	22.77	38.43	14.29	31.68	43.81	54.00	-10.19	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

8 Test Setup Photo


Radiated Emission




Conducted Emission






9 EUT Constructional Details

























-----End-----