FCC Radio Test Report

FCC ID: 2AOT7-LX7

Original Grant

Report No.	:	TB-FCC158326
Applicant	:	Luxson Hi-precision Technology Co.Ltd.
Equipment Under Test (EUT)		
EUT Name	:	Mini Smart Socket
Model No.	:	LX7
Series Model No.	:	N/A
Brand Name	:	N/A
Receipt Date	:	2018-01-27
Test Date	:	2018-01-28 to 2018-02-26
Issue Date	:	2018-02-27
Standards	:	FCC Part 15, Subpart C (15.247: 2017)
Test Method	:	ANSI C63.10: 2013
Conclusions	:	**PASS**
		In the configuration tested, the EUT complied with the standards specified above, The EUT technically complies with the FCC and IC requirements
Test/Witness Engineer	:	WAN SU
Approved& Authorized	:	Ray Li

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, China
Tel: +86 75526509301 Fax: +86 75526509195

Contents

CONTENTS 2
1. GENERAL INFORMATION ABOUT EUT 4
1.1 Client Information 5
1.2 General Description of EUT (Equipment Under Test) 5
1.3 Block Diagram Showing the Configuration of System Tested 6
1.4 Description of Support Units 6
1.5 Description of Test Mode 6
1.6 Description of Test Software Setting 8
1.7 Measurement Uncertainty 8
1.8 Test Facility 9
2. TEST SUMMARY 10
3. TEST EQUIPMENT 11
4. CONDUCTED EMISSION TEST 12
4.1 Test Standard and Limit 12
4.2 Test Setup 12
4.3 Test Procedure 12
4.4 EUT Operating Mode 13
4.5 Test Data 13
5. RADIATED EMISSION TEST 14
5.1 Test Standard and Limit 14
5.2 Test Setup 15
5.3 Test Procedure 16
5.4 EUT Operating Condition 16
5.5 Test Data 17
6. RESTRICTED BANDS REQUIREMENT 18
6.1 Test Standard and Limit 18
6.2 Test Setup 18
6.3 Test Procedure 18
6.4 EUT Operating Condition 19
6.5 Test Data 19
7. BANDWIDTH TEST 20
7.1 Test Standard and Limit 20
7.2 Test Setup 20
7.3 Test Procedure 20
7.4 EUT Operating Condition 20
7.5 Test Data 20
8. PEAK OUTPUT POWER TEST 21
8.1 Test Standard and Limit 21
8.2 Test Setup 21

8.3 Test Procedure 21
8.4 EUT Operating Condition 21
8.5 Test Data 21
9. POWER SPECTRAL DENSITY TEST 22
9.1 Test Standard and Limit 22
9.2 Test Setup 22
9.3 Test Procedure 22
9.4 EUT Operating Condition 22
9.5 Test Data 22
10. ANTENNA REQUIREMENT 23
10.1 Standard Requirement 23
10.2 Antenna Connected Construction 23
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA 24
ATTACHMENT B-- RADIATED EMISSION TEST DATA 28
ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA 48
ATTACHMENT D-- BANDWIDTH TEST DATA 63
ATTACHMENT E-- PEAK OUTPUT POWER TEST DATA 69
ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA 72

Revision History

Report No.	Version	Description	Issued Date
TB-FCC158326	Rev.01	Initial issue of report	2018-02-27

1. General Information about EUT

1.1 Client Information

Applicant	:	Luxson Hi-precision Technology Co.Ltd.
Address	:	Room 1-10B, Block 9, Section 11, Tao Yuan Ju, Qian Jin Road 2, Bao An District, Shenzhen City, Guangdong Province, China, P.R.C
Manufacturer	:	Luxson Hi-precision Technology Co.Ltd.
Address	:	Room 1-10B, Block 9, Section 11, Tao Yuan Ju, Qian Jin Road 2, Bao An District, Shenzhen City, Guangdong Province, China, P.R.C

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Mini Smart Socket	
Models No.	:	LX7	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels **see note(3)**
		RF Output Power:	802.11b: 16.89dBm 802.11g: 15.64dBm 802.11n (HT20): 13.56dBm
		Antenna Gain:	1dBi PCB Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Supply	:	AC Voltage supplied	
Power Rating	:	Input: AC 100-250V, 50/60Hz, 10A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

(1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v04.

(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	**2412**	05	2432	09	2452
02	2417	**06**	**2437**	10	2457
03	2422	07	2442	**11**	**2462**
04	2427	08	2447		
Note: CH 01~CH 11 for 802.11b/g/n(HT20)					

(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

Normal Working Mode



TX Mode



1.4 Description of Support Units

The EUT has been tested as an independent unit.

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test

Final Test Mode	Description
Mode 1	Normal Working with TX B Mode

For Radiated Test	
Final Test Mode	**Description**
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK (1 Mbps)
802.11g Mode: OFDM (6 Mbps)
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	SecureCRT.exe		
Channel	**CH 01**	**CH 06**	**CH 11**
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	 ±3.42 dB ±3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	±4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	±4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	±4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)
The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01
The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025：2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

IC Registration No.: (11950A-1)
The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: "/" for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 20, 2017	Jul. 19, 2018
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 20, 2017	Jul. 19, 2018
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 20, 2017	Jul. 19, 2018
LISN	Rohde & Schwarz	ENV216	101131	Jul. 20, 2017	Jul. 19, 2018
Radiation Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 20, 2017	Jul. 19, 2018
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 20, 2017	Jul. 19, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.24, 2017	Mar. 23, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.24, 2017	Mar. 23, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.25, 2017	Mar. 24, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.24, 2017	Mar. 23, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 20, 2017	Jul. 19, 2018
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 20, 2017	Jul. 19, 2018
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 26, 2017	Oct. 25, 2018
Vector Signal Generator	Agilent	N5182A	MY50141294	Oct. 26, 2017	Oct. 25, 2018
Analog Signal Generator	Agilent	N5181A	MY50141953	Oct. 26, 2017	Oct. 25, 2018
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Oct. 26, 2017	Oct. 25, 2018

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:
(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequencies.
(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please refer to the Attachment A.

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

(1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

(3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

(4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

(5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.

(6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

(7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.247(d)
FCC Part 15.209
FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

(2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
(4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
(5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
(6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
(7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
(8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please refer to the Attachment C.

7. Bandwidth Test

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	**Limit**	**Frequency Range(MHz)**
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup



7.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.

(3)Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

7.5 Test Data

Please refer to the Attachment D.

8. Peak Output Power Test

8.1 Test Standard and Limit

8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	**Limit**	**Frequency Range(MHz)**
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v04. The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data

Please refer to the Attachment E.

9. Power Spectral Density Test

9.1 Test Standard and Limit

9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	**Limit**	**Frequency Range(MHz)**
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v04.

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
(2) Set analyser center frequency to DTS channel center frequency.
(3) Set the span to 1.5 times the DTS bandwidth.
(4) Set the RBW to: 3 kHz
(5) Set the VBW to: 10 kHz
(6) Detector: peak
(7) Sweep time: auto
(8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

9.5 Test Data

Please refer to the Attachment F.

10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 1dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
☒Permanent attached antenna
☐Unique connector antenna
☐Professional installation antenna

Attachment A-- Conducted Emission Test Data

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Normal working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1620	43.56	9.58	53.14	65.36	-12.22	QP
2		0.1620	28.04	9.58	37.62	55.36	-17.74	AVG
3		0.1860	42.67	9.58	52.25	64.21	-11.96	QP
4		0.1860	27.74	9.58	37.32	54.21	-16.89	AVG
5		0.2072	42.51	9.58	52.09	63.31	-11.22	QP
6		0.2072	28.01	9.58	37.59	53.31	-15.72	AVG
7		0.2100	41.71	9.58	51.29	63.20	-11.91	QP
8		0.2100	27.13	9.58	36.71	53.20	-16.49	AVG
9		0.2340	40.34	9.58	49.92	62.30	-12.38	QP
10		0.2340	25.80	9.58	35.38	52.30	-16.92	AVG
11	*	0.2521	41.09	9.59	50.68	61.68	-11.00	QP
12		0.2521	27.05	9.59	36.64	51.68	-15.04	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	Normal working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1650	40.59	9.58	50.17	65.20	-15.03	QP
2		0.1650	24.45	9.58	34.03	55.20	-21.17	AVG
3		0.1884	39.76	9.58	49.34	64.10	-14.76	QP
4		0.1884	23.93	9.58	33.51	54.10	-20.59	AVG
5		0.2140	35.81	9.58	45.39	63.04	-17.65	QP
6		0.2140	17.92	9.58	27.50	53.04	-25.54	AVG
7	*	0.2540	40.31	9.59	49.90	61.62	-11.72	QP
8		0.2540	26.60	9.59	36.19	51.62	-15.43	AVG
9		0.2779	39.23	9.59	48.82	60.88	-12.06	QP
10		0.2779	25.86	9.59	35.45	50.88	-15.43	AVG
11		0.3020	38.21	9.59	47.80	60.19	-12.39	QP
12		0.3020	24.92	9.59	34.51	50.19	-15.68	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 240V/50Hz		
Terminal:	Line		
Test Mode:	Normal working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	42.93	9.58	52.51	65.15	-12.64	QP
2		0.1660	25.67	9.58	35.25	55.15	-19.90	AVG
3		0.1860	41.75	9.58	51.33	64.21	-12.88	QP
4		0.1860	24.70	9.58	34.28	54.21	-19.93	AVG
5		0.2140	39.59	9.58	49.17	63.04	-13.87	QP
6		0.2140	23.24	9.58	32.82	53.04	-20.22	AVG
7		0.2380	38.85	9.58	48.43	62.16	-13.73	QP
8		0.2380	19.24	9.58	28.82	52.16	-23.34	AVG
9		0.2580	37.88	9.59	47.47	61.49	-14.02	QP
10		0.2580	20.37	9.59	29.96	51.49	-21.53	AVG
11	*	0.3500	38.99	9.59	48.58	58.96	-10.38	QP
12		0.3500	27.24	9.59	36.83	48.96	-12.13	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 240V/50Hz		
Terminal:	Neutral		
Test Mode:	Normal working with TX B Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2700	38.84	9.59	48.43	61.12	-12.69	QP
2		0.2700	23.62	9.59	33.21	51.12	-17.91	AVG
3	*	0.3339	39.24	9.59	48.83	59.35	-10.52	QP
4		0.3339	25.24	9.59	34.83	49.35	-14.52	AVG
5		0.9580	27.41	9.60	37.01	56.00	-18.99	QP
6		0.9580	18.38	9.60	27.98	46.00	-18.02	AVG
7		1.9660	30.77	9.61	40.38	56.00	-15.62	QP
8		1.9660	22.59	9.61	32.20	46.00	-13.80	AVG
9		3.6140	22.45	9.67	32.12	56.00	-23.88	QP
10		3.6140	7.48	9.67	17.15	46.00	-28.85	AVG
11		4.0180	30.35	9.68	40.03	56.00	-15.97	QP
12		4.0180	21.17	9.68	30.85	46.00	-15.15	AVG

Emission Level= Read Level+ Correct Factor

Attachment B-- Radiated Emission Test Data

9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		33.4449	33.92	-15.58	18.34	40.00	-21.66	QP
2	*	55.8047	45.53	-23.88	21.65	40.00	-18.35	QP
3		62.4314	39.01	-23.72	15.29	40.00	-24.71	QP
4		151.5972	31.37	-20.40	10.97	43.50	-32.53	QP
5		370.7023	33.63	-13.44	20.19	46.00	-25.81	QP
6		640.6110	32.66	-7.64	25.02	46.00	-20.98	QP

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		37.0248	45.25	-17.78	27.47	40.00	-12.53	QP
2	*	53.1313	55.16	-23.84	31.32	40.00	-8.68	QP
3		79.8003	37.74	-22.74	15.00	40.00	-25.00	QP
4		116.9495	35.84	-21.71	14.13	43.50	-29.37	QP
5		151.0666	33.44	-20.44	13.00	43.50	-30.50	QP
6		480.5276	42.15	-10.73	31.42	46.00	-14.58	QP

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.870	36.52	14.71	51.23	54.00	-2.77	AVG
2		4824.335	49.85	14.71	64.56	74.00	-9.44	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4824.050	49.04	14.71	63.75	74.00	-10.25	peak
2	*	4826.240	34.26	14.73	48.99	54.00	-5.01	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.865	36.02	15.10	51.12	54.00	-2.88	AVG
2		4874.130	49.79	15.10	64.89	74.00	-9.11	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4876.150	48.78	15.11	63.89	74.00	-10.11	peak
2	*	4876.240	34.88	15.11	49.99	54.00	-4.01	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.870	36.19	15.48	51.67	54.00	-2.33	AVG
2		4924.205	49.99	15.48	65.47	74.00	-8.53	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4921.960	49.75	15.47	65.22	74.00	-8.78	peak
2	*	4924.660	35.06	15.48	50.54	54.00	-3.46	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4825.425	49.54	14.72	64.26	74.00	-9.74	peak
2	*	4826.500	34.37	14.73	49.10	54.00	-4.90	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4824.765	48.40	14.71	63.11	74.00	-10.89	peak
2	*	4826.500	34.32	14.73	49.05	54.00	-4.95	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4872.630	48.33	15.08	63.41	74.00	-10.59	peak
2	*	4876.230	34.16	15.11	49.27	54.00	-4.73	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.075	49.80	15.09	64.89	74.00	-9.11	peak
2	*	4874.920	34.90	15.10	50.00	54.00	-4.00	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4922.445	49.25	15.47	64.72	74.00	-9.28	peak
2	*	4925.185	34.97	15.50	50.47	54.00	-3.53	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4922.575	48.89	15.47	64.36	74.00	-9.64	peak
2	*	4925.975	35.02	15.50	50.52	54.00	-3.48	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4826.240	34.33	14.73	49.06	54.00	-4.94	AVG
2		4826.340	48.26	14.73	62.99	74.00	-11.01	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4822.995	48.37	14.70	63.07	74.00	-10.93	peak
2	*	4826.500	34.27	14.73	49.00	54.00	-5.00	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.595	48.93	15.10	64.03	74.00	-9.97	peak
2	*	4876.030	34.89	15.11	50.00	54.00	-4.00	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4876.055	49.39	15.11	64.50	74.00	-9.50	peak
2	*	4876.235	34.89	15.11	50.00	54.00	-4.00	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4822.130	48.48	14.70	63.18	74.00	-10.82	peak
2	*	4826.235	34.32	14.73	49.05	54.00	-4.95	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.090	49.14	15.48	64.62	74.00	-9.38	peak
2	*	4925.975	35.04	15.50	50.54	54.00	-3.46	AVG

Emission Level= Read Level+ Correct Factor

Attachment C-- Restricted Bands Requirement Test Data

(1) Radiation Test

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	50.28	0.97	51.25	74.00	-22.75	peak
2		2390.000	39.18	0.97	40.15	54.00	-13.85	AVG
3	*	2411.200	88.24	1.07	89.31	Fundamental Frequency		AVG
4	X	2413.100	97.85	1.07	98.92	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	46.98	0.97	47.95	74.00	-26.05	peak
2		2390.000	36.78	0.97	37.75	54.00	-16.25	AVG
3	*	2412.900	83.14	1.07	84.21	Fundamental Frequency		AVG
4	X	2413.400	92.87	1.07	93.94	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2460.900	101.02	1.29	102.31	Fundamental Frequency		peak
2	*	2461.100	91.73	1.29	93.02	Fundamental Frequency		AVG
3		2483.500	47.69	1.40	49.09	74.00	-24.91	peak
4		2483.500	37.95	1.40	39.35	54.00	-14.65	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2462.800	85.89	1.30	87.19	Fundamental Frequency		AVG
2	X	2463.400	95.56	1.30	96.86	Fundamental Frequency		peak
3		2483.500	46.89	1.40	48.29	74.00	-25.71	peak
4		2483.500	35.97	1.40	37.37	54.00	-16.63	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	58.87	0.97	59.84	74.00	-14.16	peak
2		2390.000	37.12	0.97	38.09	54.00	-15.91	AVG
3	X	2409.300	94.41	1.06	95.47	Fundamental Frequency		peak
4	*	2410.600	78.09	1.07	79.16	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	55.41	0.97	56.38	74.00	-17.62	peak
2		2390.000	35.50	0.97	36.47	54.00	-17.53	AVG
3	X	2414.400	89.49	1.08	90.57	Fundamental Frequency		peak
4	*	2414.500	73.32	1.08	74.40	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2455.800	81.58	1.27	82.85	Fundamental Frequency		AVG
2	X	2460.200	97.66	1.29	98.95	Fundamental Frequency		peak
3		2483.500	63.41	1.40	64.81	74.00	-9.19	peak
4		2483.500	37.27	1.40	38.67	54.00	-15.33	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2467.500	93.01	1.33	94.34	Fundamental Frequency		peak
2	*	2469.200	76.77	1.34	78.11	Fundamental Frequency		AVG
3		2483.500	60.38	1.40	61.78	74.00	-12.22	peak
4		2483.500	35.74	1.40	37.14	54.00	-16.86	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	55.93	0.97	56.90	74.00	-17.10	peak
2		2390.000	36.80	0.97	37.77	54.00	-16.23	AVG
3	*	2410.800	75.29	1.07	76.36	Fundamental Frequency		AVG
4	X	2414.700	91.47	1.08	92.55	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	54.49	0.97	55.46	74.00	-18.54	peak
2		2390.000	35.33	0.97	36.30	54.00	-17.70	AVG
3	X	2414.800	86.75	1.08	87.83	Fundamental Frequency		peak
4	*	2415.100	70.57	1.08	71.65	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2454.700	78.70	1.27	79.97	Fundamental Frequency		AVG
2	X	2455.500	95.26	1.27	96.53	Fundamental Frequency		peak
3		2483.500	61.40	1.40	62.80	74.00	-11.20	peak
4		2483.500	36.71	1.40	38.11	54.00	-15.89	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2467.900	73.86	1.33	75.19	Fundamental Frequency		AVG
2	X	2469.400	90.15	1.34	91.49	Fundamental Frequency		peak
3		2483.500	59.83	1.40	61.23	74.00	-12.77	peak
4		2483.500	35.31	1.40	36.71	54.00	-17.29	AVG

Emission Level= Read Level+ Correct Factor

(2) Conducted Test

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		





Attachment D-- Bandwidth Test Data

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode		

Channel frequency (MHz)	**6dB Bandwidth (MHz)**	**99% Bandwidth (MHz)**	**Limit (MHz)**
2412	8.069	10.505	>=0.5
2437	8.093	10.458	
2462	8.081	10.437	

802.11B Mode

2412 MHz



802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.34	16.461	>=0.5
2437	16.33	16.470	
2462	16.35	16.460	

802.11G Mode

2412 MHz



802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.57	17.765	>=0.5
2437	17.57	17.773	
2462	17.58	17.769	

802.11N(HT20) Mode

2412 MHz



802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



Attachment E-- Peak Output Power Test Data

Test Conditions:	Continuous transmitting Mode		
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		

Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	16.44	30
	2437	16.89	
	2462	16.32	
802.11g	2412	15.64	
	2437	15.22	
	2462	15.31	
802.11n (HT20)	2412	13.56	
	2437	13.26	
	2462	12.96	
Result: PASS			

Duty Cycle		
Mode	**Channel frequency (MHz)**	**Test Result**
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
Please see below plots		

802.11 B Mode 2437 MHz



802.11 G Mode 2437 MHz



802.11 N(HT20) Mode 2437 MHz



Attachment F-- Power Spectral Density Test Data

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode		

Channel Frequency (MHz)	Power Density (dBm/3 kHz)	Limit (dBm)
2412	-9.214	**8**
2437	-8.784	
2462	-9.198	

802.11B Mode

2412 MHz



802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



Temperature:	25 ℃	**Temperature:**	25 ℃
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode		

Channel Frequency (MHz)	**Power Density (dBm/3 kHz)**	**Limit (dBm)**
2412	-14.969	**8**
2437	-15.043	
2462	-15.066	

802.11G Mode

2412 MHz



802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



Temperature:	25 ℃	**Temperature:**	25 ℃
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT20) Mode		

Channel Frequency (MHz)	**Power Density (dBm/3 kHz)**	**Limit (dBm)**
2412	-18.501	**8**
2437	-18.106	
2462	-18.660	

802.11N(HT20) Mode

2412 MHz



802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



-----END OF REPORT-----