11. Radio Frequency Exposure

11.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in

FCC Part 2 (Section 2.1091)

KDB 447498

11.2 EUT Specification

Frequency band (Operating)	☒ WLAN: 2412MHz ~ 2462MHz ☐ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☐ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm^2) ☒ General Population/Uncontrolled exposure (S=1mW/cm^2)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:

1. *The maximum output power is 22.75dBm (188.365mW) at 2412MHz (with numeric 3.66 antenna gain.)*
2. *DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.*
3. *For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.*

11.3 Test Results

No non-compliance noted.

11.4 Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where *E = Field strength in Volts / meter*

P = Power in Watts
G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and
d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$ ***Equation 1***

Where *d = Distance in cm*
P = Power in mW
G = Numeric antenna gain
S = Power density in mW / cm²

11.5 Maximum Permissible Exposure

Max. output power	Band: 2412MHz ~ 2462MHz 802.11b: 17.63 dBm (57.943mW) 802.11g: 22.67 dBm (184.927mW) 802.11n HT20: 22.75 dBm (188.365mW)
Antenna gain (Max)	3.66 dBi

Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	17.63	3.66	20	0.0268	1
802.11g	2412-2462	22.67	3.66	20	0.0855	1
802.11n HT20	2412-2462	22.75	3.66	20	0.0870	1