

FCC RF EXPOSURE REPORT

FCC ID: 2AOVE-MD006

Project No. : 1711C012B
Equipment : MOORE TAG
Model : MD006
Applicant : Mooredoll Inc.
Address : 2F., No.29, Sec. 3, Nanjing E. Rd., Zhongshan
Dist., Taipei City 104, Taiwan

According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	printed	N/A	-10.7

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
0.09	1.0209	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 1.0209mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold