


RF Exposure Evaluation Report

APPLICANT : Shenzhen SEI Robotics Co., Ltd.
EQUIPMENT : OTT Box
BRAND NAME : DIRECTV
MODEL NAME : C81KW-650
FCC ID : 2AOVU-C81KW
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 V06

The product evaluation date was started from May 20, 2026 and completed on May 20, 2026. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Hank Huang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8
5.2. Collocated Power Density Calculation.....	8

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA631917	Rev. 01	Initial issue of report.	May 29, 2026



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	Shenzhen SEI Robotics Co., Ltd.
Address	11th Floor, Kangtai Group Building, No. 222 Kefa Road, Science and Technology Park Community, Yuehai Street, Nanshan District, Shenzhen

Manufacturer	
Company Name	Shenzhen SEI Robotics Co., Ltd.
Address	11th Floor, Kangtai Group Building, No. 222 Kefa Road, Science and Technology Park Community, Yuehai Street, Nanshan District, Shenzhen

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	OTT Box
Brand Name	DIRECTV
Model Name	C81KW-650
FCC ID	2AOVU-C81KW
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz : 802.11b/g/n HT20/HT40 WLAN 2.4GHz : 802.11ac/ax VHT20/VHT40/HE20/HE40 WLAN 5GHz : 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac/ax VHT20/VHT40/VHT80/HE20/HE40/HE80 Bluetooth BR/EDR/LE
Antenna Gain	ANT1: WLAN2.4GHz: 3.35 dBi WLAN 5.2GHz: 5.31 dBi WLAN 5.3GHz: 5.45 dBi WLAN 5.5GHz: 4.85 dBi WLAN 5.8GHz: 4.94 dBi ANT2: WLAN2.4GHz: 3.25 dBi WLAN 5.2GHz: 4.23 dBi WLAN 5.3GHz: 4.96 dBi WLAN 5.5GHz: 5.82 dBi WLAN 5.8GHz: 5.94 dBi ANT3: Bluetooth: 5.43 dBi
Antenna Type	WLAN: PCB Dual Band Antennas Bluetooth: PCB Antenna
EUT Stage	Identical Prototype

Remark:

- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

- The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
- The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF average output tune up power among production units

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)		
		Ant 1	Ant 2	MIMO
2.4GHz	802.11b	20.00	20.00	23.00
	802.11g	20.00	20.00	23.00
	802.11n-HT20	19.00	19.00	22.00
	802.11n-HT40	19.00	19.00	22.00
	802.11ac-VHT20	19.00	19.00	22.00
	802.11ac-VHT40	19.00	19.00	22.00
	802.11ax-HE20	19.00	19.00	22.00
	802.11ax-HE40	19.00	19.00	22.00

<Bluetooth>

Mode		Maximum Average power(dBm)
Bluetooth	BR/EDR	9.00
	LE	9.00

<WLAN 5GHz>

Mode		Maximum Average Power (dBm)		
		Ant 1	Ant 2	MIMO
WLAN 5.2GHz	802.11a	18.00	18.00	20.00
	802.11n-HT20	18.00	18.00	20.00
	802.11n-HT40	18.00	18.00	20.00
	802.11ac-VHT20	18.00	18.00	20.00
	802.11ac-VHT40	18.00	18.00	20.00
	802.11ac-VHT80	15.00	15.00	17.00
	802.11ax-HE20	18.00	18.00	20.00
	802.11ax-HE40	18.00	18.00	20.00
	802.11ax-HE80	15.00	15.00	17.00
WLAN 5.3GHz	802.11a	18.00	18.00	19.00
	802.11n-HT20	18.00	18.00	19.00
	802.11n-HT40	18.00	18.00	21.00
	802.11ac-VHT20	18.00	18.00	19.00
	802.11ac-VHT40	18.00	18.00	21.00
	802.11ac-VHT80	15.00	15.00	17.00
	802.11ax-HE20	18.00	18.00	19.00
	802.11ax-HE40	18.00	18.00	21.00
	802.11ax-HE80	15.00	15.00	17.00
WLAN 5.5GHz	802.11a	18.00	18.00	19.00
	802.11n-HT20	18.00	18.00	19.00
	802.11n-HT40	18.00	18.00	21.00
	802.11ac-VHT20	18.00	18.00	19.00
	802.11ac-VHT40	18.00	18.00	21.00
	802.11ac-VHT80	18.00	18.00	21.00
	802.11ax-HE20	18.00	18.00	19.00
	802.11ax-HE40	18.00	18.00	21.00
	802.11ax-HE80	18.00	18.00	21.00
WLAN 5.8GHz	802.11a	18.00	18.00	21.00
	802.11n-HT20	18.00	18.00	21.00
	802.11n-HT40	18.00	18.00	21.00

	802.11ac-VHT20	18.00	18.00	21.00
	802.11ac-VHT40	18.00	18.00	21.00
	802.11ac-VHT80	18.00	18.00	21.00
	802.11ax-HE20	18.00	18.00	21.00
	802.11ax-HE40	18.00	18.00	21.00
	802.11ax-HE80	18.00	18.00	21.00

Note: WLAN supports SISO/MIMO mode. Since the MIMO power is higher, only the MIMO tune-up power was selected to perform MPE calculation conservatively.

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
Bluetooth	2402.0	5.43	9.00	14.430	27.733	0.006	1.000	0.006
2.4GHz WLAN	2412.0	3.35	23.00	26.350	431.519	0.086	1.000	0.086
5.2GHz WLAN	5180.0	5.31	20.00	25.310	339.625	0.068	1.000	0.068
5.3GHz WLAN	5260.0	5.45	21.00	26.450	441.570	0.088	1.000	0.088
5.5GHz WLAN	5500.0	5.82	21.00	26.820	480.839	0.096	1.000	0.096
5.8GHz WLAN	5745.0	5.94	21.00	26.940	494.311	0.098	1.000	0.098

Note:

1. For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum RF output tune up power and the maximum antenna gain of all antennas among same frequency WLAN/BT bands to perform MPE calculation conservatively.
3. The MIMO mode is completely uncorrelated, so selected the higher SISO gain among all antennas as MIMO gain to perform MPE calculation.

5.2. Collocated Power Density Calculation

Maximum Bluetooth Power Density / Limit	Maximum WLAN 2.4GHz Power Density / Limit	Σ (Power Density / Limit) of Bluetooth + WLAN 2.4GHz
0.006	0.086	0.092

Maximum Bluetooth Power Density / Limit	Maximum WLAN 5GHz Power Density / Limit	Σ (Power Density / Limit) of Bluetooth + WLAN 5GHz
0.006	0.098	0.104

Note:

1. According to the EUT characteristic, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.
2. According to the EUT characteristic, Bluetooth and WLAN 2.4GHz can transmit simultaneously.
3. According to the EUT characteristic, Bluetooth and WLAN 5GHz can transmit simultaneously.
4. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for Bluetooth + WLAN 2.4G/5GHz.
5. Considering all transmitters of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE collocated transmitters is compliant.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----