FCC TEST REPORT

Test report
On Behalf of
Shenzhen SEI Robotics Co., Ltd.
For
4K ATV Stick
Model No.: SN8B6BX(X=A TO Z)

FCC ID: 2AOVU-SN8B6BB

Prepared for :	**Shenzhen SEI Robotics Co., Ltd.** 3F(East), Block D, SDG Infoport, No.2 Kefeng Road, Nanshan District, Shenzhen, P.R. China
Prepared By :	**Shenzhen HUAK Testing Technology Co., Ltd.** **1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China**

Date of Test:	**June 07, 2018~ June 30, 2018**
Date of Report:	**June 30, 2018**
Report Number:	**HUAK180609519E1**

TEST RESULT CERTIFICATION

Applicant's name ..... :	**Shenzhen SEI Robotics Co., Ltd.**
Address ..... :	3F(East), Block D, SDG Infoport, No.2 Kefeng Road, Nanshan District, Shenzhen, P.R. China
Manufacture's Name ..... :	**Shenzhen SEI Robotics Co., Ltd.**
Address ..... :	3F(East), Block D, SDG Infoport, No.2 Kefeng Road, Nanshan District, Shenzhen, P.R. China
Product description	
Trade Mark:	N/A
Product name ..... :	4K ATV Stick
Model and/or type reference :	SN8B6BX(X=A TO Z)
Standards..... :	FCC Rules and Regulations Part 15 Subpart C Section 15.247 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test ..... :	
Date (s) of performance of tests..... :	June 07, 2018~ June 30, 2018
Date of Issue ..... :	June 30, 2018
Test Result..... :	**Pass**

Testing Engineer : Gary Qian

(Gary Qian)

Technical Manager : Eden Hu

(Eden Hu)

Authorized Signatory : Jason Zhou

(Jason Zhou)

Revision History

Revision	Issue Date	Revisions	Revised By
00	June 30, 2018	Initial Issue	Jason Zhou

TABLE OF CONTENTS

1. GENERAL INFORMATION **5**
1.1. DESCRIPTION OF DEVICE (EUT) 5
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS 6
1.3. EXTERNAL I/O CABLE 6
1.4. DESCRIPTION OF TEST FACILITY 6
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY 6
1.6. MEASUREMENT UNCERTAINTY 7
1.7. DESCRIPTION OF TEST MODES 8
2. TEST METHODOLOGY **9**
2.1. EUT CONFIGURATION 9
2.2. EUT EXERCISE 9
2.3. GENERAL TEST PROCEDURES 9
3. SYSTEM TEST CONFIGURATION **10**
3.1. JUSTIFICATION 10
3.2. EUT EXERCISE SOFTWARE 10
3.3. SPECIAL ACCESSORIES 10
3.4. BLOCK DIAGRAM/SCHEMATICS 10
3.5. EQUIPMENT MODIFICATIONS 10
3.6. TEST SETUP 10
4. SUMMARY OF TEST RESULTS **11**
5. TEST RESULT **12**
5.1. ON TIME AND DUTY CYCLE 12
5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT 14
5.3. POWER SPECTRAL DENSITY MEASUREMENT 16
5.5. RADIATED EMISSIONS MEASUREMENT 28
5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST 41
5.7. POWER LINE CONDUCTED EMISSIONS 58
5.8. BAND-EDGE MEASUREMENTS FOR RADIATED EMISSIONS 61
5.9. ANTENNA REQUIREMENTS 66
6. LIST OF MEASURING EQUIPMENTS **68**
7. TEST SETUP PHOTOGRAPHS OF EUT **69**
8. EXTERIOR PHOTOGRAPHS OF THE EUT **69**
9. INTERIOR PHOTOGRAPHS OF THE EUT **69**

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	4K ATV Stick
Model Number	:	SN8B6BX(X=A TO Z)
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, Only models name is different for these models.
Test Model	:	SN8B6BB
Power Supply	:	DC 5V by adapter
Hardware version	:	SMB.189.04
Software version	:	8.0.0
Bluetooth Version	:	V4.1
Channel Number	:	79 Channels for Bluetooth V3.0(DSS) 40 Channels for Bluetooth V4.1(DTS)
Modulation Technology	:	GFSK, π/4-DQPSK, 8-DPSK for Bluetooth V3.0(DSS) GFSK for Bluetooth V4.1(DTS)
Data Rates	:	Bluetooth V3.0(DSS): 1~3Mbps Bluetooth V4.1(DTS): 1Mbps
WLAN	:	Supported IEEE 802.11a/b/g/n/ac
WLAN FCC Operation Frequency	:	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz / 5180-5240MHz / 5745-5825MHz IEEE 802.11n HT40:2422-2452MHz / 5190-5230MHz / 5755-5795MHz IEEE 802.11a: 5180-5240MHz / 5745-5825MHz IEEE 802.11ac VHT20: 5180-5240MHz / 5745-5825MHz IEEE 802.11ac VHT40: 5190-5230MHz / 5755-5795MHz IEEE 802.11ac VHT80: 5210MHz / 5775MHz
WLAN Channel Number	:	11 Channels for 2412-2462MHz(IEEE 802.11b/g/n HT20) 7 Channels for 2422-2452MHz(IEEE 802.11n HT40) 4 Channels for 5180-5240MHz (IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5190-5230MHz (IEEE 802.11ac VHT40/n HT40) 1 Channels for 5210MHz (IEEE 802.11ac VHT80) 5 Channels for 5745-5825MHz(IEEE 802.11a/ac VHT20/n HT20) 2 Channels for 5755-5795MHz(IEEE 802.11ac VHT40/n HT40) 1 Channels for 5775MHz(IEEE 802.11ac VHT80)
WLAN Modulation Technology	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type And Gain	:	Three Antennas: Internal Antenna 0: 1.4dBi(Max.), for TX/RX (WLAN 2.4G Band), 2.0 dBi(Max.), for TX/RX (WLAN 5G Band) Internal Antenna 1: 1.1dBi(Max.), for TX/RX (WLAN 2.4G Band), 2.58 dBi(Max.), for TX/RX (WLAN 5G Band) Internal Antenna 2: 1.76dBi(Max.), for TX/RX (Bluetooth),

802.11n/ac support 2T2R.[Antenna 0 and Antenna 1]

Directional Gain : 4.26 dBi for MIMO(2.4G Band)
5.31 dBi for MIMO(5G Band)



1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
SUNUN	Adapter	SA69-050200U	A69-84	N/A

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
USB Port	1	1m, unshielded
HDMI Port	1	N/A

1.4. Description of Test Facility

Designation Number: CN1229
Test Firm Registration Number: 616276

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the HUAK quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	±3.08dB	(1)
		30MHz~1000MHz	±4.42dB	(1)
		1GHz~40GHz	±4.06dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	±2.23dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

AC power line conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, that was determined to be 802.11n HT40 mode(Low Channel, Chain 0+Chain 1).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 802.11n HT40 mode(Low Channel, Chain 0+Chain 1).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

IEEE 802.11b Mode: 1 Mbps, DSSS.
IEEE 802.11g Mode: 6 Mbps, OFDM.
IEEE 802.11n Mode HT20: MCS0, OFDM.
IEEE 802.11n Mode HT40: MCS0, OFDM.

Antenna & Bandwidth

Antenna	Antenna 0		Antenna 1		Simultaneously
Bandwidth Mode	20MHz	40MHz	20MHz	40MHz	/
IEEE 802.11b	☑	☐	☑	☐	☐
IEEE 802.11g	☑	☐	☑	☐	☐
IEEE 802.11n	☑	☑	☑	☑	☑

Channel List & Frequency

IEEE 802.11b/g/n HT20

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2412~2462MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	--	--

IEEE 802.11n HT40

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
2422~2452MHz	1	--	7	2442
	2	--	8	2447
	3	2422	9	2452
	4	2427	10	--
	5	2432	11	--
	6	2437	--	--

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen HUAK Testing Technology Co., Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB 558074 D01 DTS Meas Guidance v04 and KDB 662911 D01 Multiple Transmitter Output v02r01 are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (MPTool) provided by application.

3.3. Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
1	TV	AOC	280LM00003	JVVGJA000307	/	/	/

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen HUAK Testing Technology Co., Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
/	Duty Cycle	Compliant
§15.247(b)	Maximum Conducted Output Power	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(a)	Occupied Bandwidth	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
§15.247(i)§2.1093	RF Exposure	Compliant

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.

5.1.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the centre frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=10MHz, VBW=10MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout



5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

Mode	On Time B (ms)	Period (ms)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW(KHz)
IEEE 802.11b	5	5	1	100	0	0.010
IEEE 802.11g	5	5	1	100	0	0.010
IEEE 802.11n HT20	5	5	1	100	0	0.010
IEEE 802.11n HT40	5	5	1	100	0	0.010

Remark:

1. Measured duty cycle for WLAN at antenna 0 and antenna 1 port, the two antenna ports results were same, just recorded results at antenna 0;

On Time and Duty Cycle



IEEE 802.11b



IEEE 802.11g



IEEE 802.11n HT20



IEEE 802.11n HT40

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

According to §15.247(b): For systems using digital modulation in the 2400-2483.5 MHz and 5725-5850 MHz band, the limit for maximum peak conducted output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter peak output power.

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the power meter.

5.2.3. Test Procedures

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.2 the maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

According to KDB558074 D01 DTS Measurement Guidance Section 9.2 Maximum average conducted output power, 9.2.3.1 Method AVGPM (Measurement using an RF average power meter)

(a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.

2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.

3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

(c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(d) Adjust the measurement in dBm by adding 10log (1/x), where x is the duty cycle to the measurement result.

5.2.4. Test Setup Layout



5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Test Result of Maximum Conducted Output Power

Temperature	25.1℃	Humidity	52.4%
Test Engineer	Jayden Zhuo	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)			Limits (dBm)	Verdict
			Antenna 0	Antenna 1	Sum		
IEEE 802.11b	1	2412	13.66	15.29	-/-	30	PASS
	6	2437	13.5	14.66	-/-		
	11	2462	13.8	14.76	-/-		
IEEE 802.11g	1	2412	15.59	16.74	-/-	30	PASS
	6	2437	14.96	16.29	-/-		
	11	2462	15.6	16.00	-/-		
IEEE 802.11n HT20	1	2412	16.49	17.20	19.87	30	PASS
	6	2437	15.92	16.75	19.37		
	11	2462	16.38	16.44	19.42		
IEEE 802.11n HT40	3	2422	14.94	15.50	18.24	30	PASS
	6	2437	14.65	16.14	18.47		
	9	2452	14.85	16.46	18.74		

Test Mode	Channel	Frequency (MHz)	Measured Average Output Power (dBm)			Limits (dBm)	Verdict
			Antenna 0	Antenna 1	Sum		
IEEE 802.11b	1	2412	10.61	12.26	-/-	30	PASS
	6	2437	10.45	11.63	-/-		
	11	2462	10.76	11.76	-/-		
IEEE 802.11g	1	2412	9.85	10.88	-/-	30	PASS
	6	2437	9.24	10.45	-/-		
	11	2462	9.85	10.27	-/-		
IEEE 802.11n HT20	1	2412	10.39	11.00	13.72	30	PASS
	6	2437	9.66	10.55	13.14		
	11	2462	10.23	10.42	13.34		
IEEE 802.11n HT40	3	2422	9.15	9.72	12.45	30	PASS
	6	2437	8.83	10.38	12.68		
	9	2452	9.03	10.62	12.91		

Remark:

1. *Measured output power at difference data rate for each mode and recorded worst case for each mode.*
2. *Test results including cable loss;*
3. *Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;*
4. *"-/-" means no need measured or sum as cannot work at MIMO mode;*
5. *Average power is for report only;*

5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.3.2. Measuring Instruments and Setting

Please refer to equipment's list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

1. The transmitter was connected directly to a Spectrum Analyzer.

2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.

3. Set the RBW = 3 KHz~100 KHz.

4. Set the VBW ≥ 3*RBW

5. Set the span to 1.5 times the DTS channel bandwidth.

6. Detector = peak.

7. Sweep time = auto couple.

8. Trace mode = max hold.

9. Allow trace to fully stabilize.

10. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.6. Test Result of Power Spectral Density

Temperature	25.1℃	Humidity	52.4%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/100KHz)			Convert Factor	Report Peak Power Spectral Density	Directional Gain	Limits (dBm/3KHz)	Verdict
			Antenna 0	Antenna 1	Sum					
IEEE 802.11b	1	2412	-0.11	1.59	-/-	-15.23	-13.64	-/-	8.00	PASS
	6	2437	-0.16	1.00	-/-	-15.23	-14.23	-/-		
	11	2462	-0.01	1.10	-/-	-15.23	-14.13	-/-		
IEEE 802.11g	1	2412	-5.70	-4.80	-/-	-15.23	-20.03	-/-	8.00	PASS
	6	2437	-6.22	-4.76	-/-	-15.23	-19.99	-/-		
	11	2462	-5.54	-5.29	-/-	-15.23	-20.52	-/-		
IEEE 802.11n HT20	1	2412	-4.98	-4.69	-1.82	-15.23	-19.92	4.26	8.00	PASS
	6	2437	-4.98	-4.64	-1.80	-15.23	-19.87	4.26		
	11	2462	-4.77	-4.51	-1.63	-15.23	-19.74	4.26		
IEEE 802.11n HT40	3	2422	-8.72	-8.91	-5.80	-15.23	-24.14	4.26	8.00	PASS
	6	2437	-9.49	-7.26	-5.22	-15.23	-22.49	4.26		
	9	2452	-9.30	-7.27	-5.16	-15.23	-22.50	4.26		

Remark:

1. *Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.*
2. *Test results including cable loss;*
3. *Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;*
4. *Please refer to following plots;*
5. *For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;*
   Directional gain = 10 log[$(10^{G1/10} + 10^{G2/10} + \ldots + 10^{GN/10})/N_{ANT}$] dBi,where antenna gains given by G1, G2, …, GN dBi, N_{ANT} is the antennas total Number.
6. *"-/-" means no need measured or sum as cannot work at MIMO mode;*
7. *Convert Factor= 10*log10(3/100) = -15.23 (dB),*
   PSD[dBm/100KHz] + Convert Factor = PSD[dBm/3KHz]

Power Spectral Density	
Antenna 0	Antenna 0
IEEE 802.11b	IEEE 802.11g
 Date: 20.JUN.2018 16:23:07	 Date: 20.JUN.2018 16:27:31
Channel 1 / 2412 MHz	Channel 1 / 2412 MHz
 Date: 20.JUN.2018 16:24:57	 Date: 20.JUN.2018 16:28:57
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
 Date: 20.JUN.2018 16:25:45	 Date: 20.JUN.2018 16:28:57
Channel 11 / 2462 MHz	Channel 11 / 2462 MHz

Power Spectral Density	
Antenna 0	Antenna 0
IEEE 802.11n HT20	IEEE 802.11n HT40
 Date: 20.JUN.2018 16:31:22	 Date: 20.JUN.2018 16:35:50
Channel 1 / 2412 MHz	Channel 3 / 2422 MHz
 Date: 20.JUN.2018 16:32:49	 Date: 20.JUN.2018 16:37:13
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
 Date: 20.JUN.2018 16:33:24	 Date: 20.JUN.2018 16:37:45
Channel 11 / 2462 MHz	Channel 9 / 2452 MHz

Power Spectral Density	
Antenna 1	Antenna 1
IEEE 802.11b	IEEE 802.11g
 Date: 20.JUN.2018 16:52:05	 Date: 20.JUN.2018 16:55:32
Channel 1 / 2412 MHz	Channel 1 / 2412 MHz
 Date: 20.JUN.2018 16:53:43	 Date: 20.JUN.2018 16:57:00
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
 Date: 20.JUN.2018 16:54:13	 Date: 20.JUN.2018 16:57:36
Channel 11 / 2462 MHz	Channel 11 / 2462 MHz

Power Spectral Density	
Antenna 1	Antenna 1
IEEE 802.11n HT20	IEEE 802.11n HT40
 Date: 20.JUN.2018 16:59:05	 Date: 20.JUN.2018 17:02:25
Channel 1 / 2412 MHz	Channel 3 / 2422 MHz
 Date: 20.JUN.2018 17:00:32	 Date: 20.JUN.2018 17:03:49
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
 Date: 20.JUN.2018 17:01:07	 Date: 20.JUN.2018 17:04:33
Channel 11 / 2462 MHz	Channel 9 / 2452 MHz

5.4. 6 dB Spectrum Bandwidth Measurement

5.4.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting

Please refer to equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.6. Test Result of 6dB Spectrum Bandwidth

Temperature	25.1℃	Humidity	52.4%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Limits (MHz)	Verdict
			Antenna 0	Antenna 1		
IEEE 802.11b	1	2412	9.280	9.280	0.500	PASS
	6	2437	9.280	9.280		
	11	2462	9.280	9.280		
IEEE 802.11g	1	2412	16.800	16.800	0.500	PASS
	6	2437	16.800	16.800		
	11	2462	16.800	16.800		
IEEE 802.11n HT20	1	2412	18.000	18.000	0.500	PASS
	6	2437	17.920	18.000		
	11	2462	18.000	17.920		
IEEE 802.11n HT40	3	2422	36.720	36.720	0.500	PASS
	6	2437	36.720	36.360		
	9	2452	36.720	36.240		

Remark:

1. *Measured 6dB Bandwidth at difference data rate for each mode and recorded worst case for each mode.*
2. *Test results including cable loss;*
3. *Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;*
4. *Please refer to following plots;*

6 dB Bandwidth	
Antenna 0	*Antenna 0*
IEEE 802.11b	*IEEE 802.11g*
 Date: 20.JUN.2018 16:23:07	 Date: 20.JUN.2018 16:27:31
Channel 1 / 2412 MHz	*Channel 1 / 2412 MHz*
 Date: 20.JUN.2018 16:24:57	 Date: 20.JUN.2018 16:28:57
Channel 6 / 2437 MHz	*Channel 6 / 2437 MHz*
 Date: 20.JUN.2018 16:25:45	 Date: 20.JUN.2018 16:29:56
Channel 11 / 2462 MHz	*Channel 11 / 2462 MHz*

6 dB Bandwidth	
Antenna 0	Antenna 0
IEEE 802.11n HT20	IEEE 802.11n HT40
 Date: 20.JUN.2018 16:31:22	 Date: 20.JUN.2018 16:35:50
Channel 1 / 2412 MHz	Channel 3 / 2422 MHz
 Date: 20.JUN.2018 16:32:49	 Date: 20.JUN.2018 16:37:13
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
 Date: 20.JUN.2018 16:33:24	 Date: 20.JUN.2018 16:37:45
Channel 11 / 2462 MHz	Channel 9 / 2452 MHz

6 dB Bandwidth	
Antenna 1	*Antenna 1*
IEEE 802.11b	*IEEE 802.11g*
 Date: 20.JUN.2018 16:52:05	 Date: 20.JUN.2018 16:55:32
Channel 1 / 2412 MHz	*Channel 1 / 2412 MHz*
 Date: 20.JUN.2018 16:53:43	 Date: 20.JUN.2018 16:57:00
Channel 6 / 2437 MHz	*Channel 6 / 2437 MHz*
 Date: 20.JUN.2018 16:54:13	 Date: 20.JUN.2018 16:57:36
Channel 11 / 2462 MHz	*Channel 11 / 2462 MHz*

6 dB Bandwidth

Antenna 1	Antenna 1
IEEE 802.11n HT20	IEEE 802.11n HT40
	
Date: 20.JUN.2018 16:59:05	Date: 20.JUN.2018 17:02:25
Channel 1 / 2412 MHz	Channel 3 / 2422 MHz
	
Date: 20.JUN.2018 17:00:32	Date: 20.JUN.2018 17:03:49
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
	
Date: 20.JUN.2018 17:01:07	Date: 20.JUN.2018 17:04:33
Channel 11 / 2462 MHz	Channel 9 / 2452 MHz

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions.

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna height is 1.5 meter.

--- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

--- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

Premeasurement:

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height scan range is 1 meter to 2.5 meter.

--- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.

--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.

--- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 1 meter.

--- The EUT was set into operation.

Premeasurement:

--- The antenna is moved spherical over the EUT in different polarizations of the antenna.

Final measurement:

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

5.5.4. Test Setup Layout

For radiated emissions below 30MHz



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade form 3m to 1m.

Distance extrapolation factor = 20 log (specific distanc [3m] / test distance [1m]) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Results of Radiated Emissions (9 KHz~30MHz)

Temperature	24.5℃	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n
Test Date	June 26, 2018		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	24.5℃	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	802.11n HT40 Low Channel, Chain 0+Chain 1
Test Date	June 26, 2018		

The Worst Test result for 802.11n HT40 (Low Channel) @Chain 0+Chain 1

Vertical



NO.	Freq. [MHz]	Result Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle[°]	Polarity
1	32.425	34.89	-16.15	40.00	5.11	100	160	Vertical
2	53.280	36.99	-14.66	40.00	3.01	100	193	Vertical
3	69.770	36.87	-18.15	40.00	3.13	100	152	Vertical
4	103.720	34.99	-15.99	43.50	8.51	100	36	Vertical
5	407.330	31.73	-9.89	46.50	14.77	100	301	Vertical
6	628.490	36.14	-5.24	46.50	10.36	100	318	Vertical

Horizontal



NO.	Freq. [MHz]	Result Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle[°]	Polarity
1	60.070	24.7	-15.67	40.00	15.30	100	243	Horizontal
2	103.235	25.76	-15.99	43.50	17.74	100	235	Horizontal
3	162.890	20.05	-18.21	43.50	23.45	100	354	Horizontal
4	230.790	28.05	-15.10	46.50	18.45	100	163	Horizontal
5	278.320	26.52	-13.70	46.50	19.98	100	177	Horizontal
6	657.590	37.42	-4.88	46.50	9.08	100	309	Horizontal

Note:
1). Pre-scan all modes and recorded the worst case results in this report (IEEE 802.11n HT40 (Low Channel) @ Chain 0+Chain 1
2). Emission level (dBuV/m) = 20 log Emission level (uV/m).
3). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

5.5.8. Results for Radiated Emissions (Above 1GHz)

IEEEE 802.11b

Antenna 0

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	57.67	33.06	35.04	3.94	59.63	74.00	14.37	Peak	Horizontal
4824.00	45.08	33.06	35.04	3.94	47.04	54.00	6.96	Average	Horizontal
4824.00	56.25	33.06	35.04	3.94	58.21	74.00	15.79	Peak	Vertical
4824.00	45.91	33.06	35.04	3.94	47.87	54.00	6.13	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	56.15	33.16	35.15	3.96	58.12	74.00	15.88	Peak	Horizontal
4874.00	41.29	33.16	35.15	3.96	43.26	54.00	10.74	Average	Horizontal
4874.00	58.25	33.16	35.15	3.96	60.22	74.00	13.78	Peak	Vertical
4874.00	44.37	33.16	35.15	3.96	46.34	54.00	7.66	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	57.63	33.26	35.14	3.98	59.73	74.00	14.27	Peak	Horizontal
4924.00	42.13	33.26	35.14	3.98	44.23	54.00	9.77	Average	Horizontal
4924.00	59.11	33.26	35.14	3.98	61.21	74.00	12.79	Peak	Vertical
4924.00	43.47	33.26	35.14	3.98	45.57	54.00	8.43	Average	Vertical

IEEEE 802.11g

Antenna 0

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	58.23	33.06	35.04	3.94	60.19	74.00	13.81	Peak	Horizontal
4824.00	42.26	33.06	35.04	3.94	44.22	54.00	9.78	Average	Horizontal
4824.00	57.55	33.06	35.04	3.94	59.51	74.00	14.49	Peak	Vertical
4824.00	45.19	33.06	35.04	3.94	47.15	54.00	6.85	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	58.76	33.16	35.15	3.96	60.73	74.00	13.27	Peak	Horizontal
4874.00	42.71	33.16	35.15	3.96	44.68	54.00	9.32	Average	Horizontal
4874.00	56.69	33.16	35.15	3.96	58.66	74.00	15.34	Peak	Vertical
4874.00	43.82	33.16	35.15	3.96	45.79	54.00	8.21	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	59.44	33.26	35.14	3.98	61.54	74.00	12.46	Peak	Horizontal
4924.00	45.08	33.26	35.14	3.98	47.18	54.00	6.82	Average	Horizontal
4924.00	56.20	33.26	35.14	3.98	58.30	74.00	15.70	Peak	Vertical
4924.00	40.59	33.26	35.14	3.98	42.69	54.00	11.31	Average	Vertical

IEEE 802.11n HT20

Combined Antenna 0, Antenna 1 and Antenna 2

Channel 1 / 2412 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4824.00	58.69	33.06	35.04	3.94	60.65	74.00	13.35	Peak	Horizontal
4824.00	43.31	33.06	35.04	3.94	45.27	54.00	8.73	Average	Horizontal
4824.00	56.09	33.06	35.04	3.94	58.05	74.00	15.95	Peak	Vertical
4824.00	43.82	33.06	35.04	3.94	45.78	54.00	8.22	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	58.07	33.16	35.15	3.96	60.04	74.00	13.96	Peak	Horizontal
4874.00	40.79	33.16	35.15	3.96	42.76	54.00	11.24	Average	Horizontal
4874.00	58.93	33.16	35.15	3.96	60.90	74.00	13.10	Peak	Vertical
4874.00	40.19	33.16	35.15	3.96	42.16	54.00	11.84	Average	Vertical

Channel 11 / 2462 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4924.00	59.31	33.26	35.14	3.98	61.41	74.00	12.59	Peak	Horizontal
4924.00	41.51	33.26	35.14	3.98	43.61	54.00	10.39	Average	Horizontal
4924.00	57.97	33.26	35.14	3.98	60.07	74.00	13.93	Peak	Vertical
4924.00	41.70	33.26	35.14	3.98	43.80	54.00	10.20	Average	Vertical

IEEE 802.11n HT40

Combined Antenna 0, Antenna 1 and Antenna 2

Channel 3 / 2422 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4844.00	59.56	33.06	35.04	3.94	61.52	74.00	12.48	Peak	Horizontal
4844.00	43.25	33.06	35.04	3.94	45.21	54.00	8.79	Average	Horizontal
4844.00	56.28	33.06	35.04	3.94	58.24	74.00	15.76	Peak	Vertical
4844.00	43.49	33.06	35.04	3.94	45.45	54.00	8.55	Average	Vertical

Channel 6 / 2437 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4874.00	59.94	33.16	35.15	3.96	61.91	74.00	12.09	Peak	Horizontal
4874.00	43.65	33.16	35.15	3.96	45.62	54.00	8.38	Average	Horizontal
4874.00	56.14	33.16	35.15	3.96	58.11	74.00	15.89	Peak	Vertical
4874.00	40.98	33.16	35.15	3.96	42.95	54.00	11.05	Average	Vertical

Channel 9 / 2452 MHz

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4904.00	56.88	33.26	35.14	3.98	58.98	74.00	15.02	Peak	Horizontal
4904.00	44.10	33.26	35.14	3.98	46.20	54.00	7.80	Average	Horizontal
4904.00	59.78	33.26	35.14	3.98	61.88	74.00	12.12	Peak	Vertical
4904.00	44.65	33.26	35.14	3.98	46.75	54.00	7.25	Average	Vertical

Notes:

1. *Measuring frequencies from 9 KHz - 10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.*
2. *Radiated emissions measured in frequency range from 9 KHz ~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.*
3. *Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20;*

13.5Mbps at IEEE 802.11n HT40;

5. *Pre-scan at Antenna 0 and Antenna 1 for IEEE 802.11b and IEEE 802.11g mode, pre-scan at Antenna 0, Antenna 1and Combined Antenna 0 and Antenna 1 for IEEE 802.11n mode, recorded worst case;*

5.6. Conducted Spurious Emissions and Band Edges Test

5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.6.2. Measuring Instruments and Setting

Please refer to section 6 of equipment list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Detector	Peak
Attenuation	Auto
RB / VB (Emission in restricted band)	100KHz/300KHz
RB / VB (Emission in non-restricted band)	100KHz/300KHz

5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 26.5GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

5.6.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.6. Test Results of Conducted Spurious Emissions

Temperature	24.5℃	Humidity	56.2%
Test Engineer	Gary Qian	Configurations	IEEE 802.11b/g/n

Test Mode	Channel	Frequency (MHz)	Measured Frequency Range	Spurious RF Conducted Emission (dBc)			Limits (dBc)	Verdict
				Antenna 0	Antenna 1	Antenna 2		
IEEE 802.11b	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11g	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11n HT20	1	2412	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	11	2462	9 KHz – 26.5 GHz	<-20	<-20	<-20		
IEEE 802.11n HT40	3	2422	9 KHz – 26.5 GHz	<-20	<-20	<-20	-20	PASS
	6	2437	9 KHz – 26.5 GHz	<-20	<-20	<-20		
	9	2452	9 KHz – 26.5 GHz	<-20	<-20	<-20		

Remark:

1. *Measured RF conducted spurious emission at difference data rate for each mode and recorded worst case for each mode.*
2. *Test results including cable loss;*
3. *Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;*
4. *"---"means that the fundamental frequency not for 15.209 limits requirement.*
5. *Not recorded emission values from 9 KHz to 30 MHz as emission level at least 20 dBc lower than limit;*
6. *Please refer to following plots;*

RF Conducted Spurious Emissions	
Antenna 0	Antenna 0
IEEE 802.11b	IEEE 802.11g
Channel 1 / 2412 MHz	Channel 1 / 2412 MHz
	
2392 MHz – 2432 MHz	2392 MHz – 2432 MHz
	
30 MHz – 10 GHz	30 MHz – 10 GHz
	
10 GHz – 26 GHz	10 GHz – 26 GHz

RF Conducted Spurious Emissions	
Antenna 0	Antenna 0
IEEE 802.11b	IEEE 802.11g
Channel 6 / 2437 MHz	Channel 6 / 2437 MHz
	
2417 MHz – 2457 MHz	2417 MHz – 2457 MHz
	
30 MHz – 10 GHz	30 MHz – 10 GHz
	
10 GHz – 26 GHz	10 GHz – 26 GHz

RF Conducted Spurious Emissions	
Antenna 0	Antenna 0
IEEE 802.11b	IEEE 802.11g
Channel 11 / 2462 MHz	Channel 11 / 2462 MHz
	
2442 MHz – 2482 MHz	2442 MHz – 2482 MHz
	
30 MHz – 10 GHz	30 MHz – 10 GHz
	
10 GHz – 26 GHz	10 GHz – 26 GHz