FCC REPORT

Applicant:	Green Start Industries LLC
Address of Applicant:	3305 Fairmount Ave Ocean NJ USA
Equipment Under Test (EUT)	
Product Name:	keyless transmitter
Model No.:	2AOVX-3B, 2AOVX-4B
FCC ID:	2AOVX-T8
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.231(a)
Date of sample receipt:	31 Aug., 2018
Date of Test:	03 Sep., to 13 Sep., 2018
Date of report issue:	14 Sep., 2018
Test Result:	PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*14 Sep., 2018*	*Original*

Prepared By: Zora Lee ***Date:*** *14 Sep., 2018*

Test Engineer

Check By: Winner Zhang ***Date:*** *14 Sep., 2018*

Project Engineer

3 Contents

Page

COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T 5
5.3 TEST MODE 5
5.4 DESCRIPTION OF SUPPORT UNITS 5
5.5 LABORATORY FACILITY 6
5.6 LABORATORY LOCATION 6
5.7 MEASUREMENT UNCERTAINTY 6
5.8 TEST INSTRUMENTS LIST 7

6 TEST RESULTS AND MEASUREMENT DATA 8

6.1 ANTENNA REQUIREMENT 8
6.2 RADIATED EMISSION 9
6.2.1 Field Strength Of The Fundamental Signal 11
6.2.2 Spurious Emissions 17
6.3 20DB BANDWIDTH 27
6.4 DURATION TIME 29

7 TEST SETUP PHOTOS 31

8 EUT CONSTRUCTIONAL PHOTOS 32

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
Field strength of the fundamental signal	15.231 (b)	Pass
Spurious emissions	15.231 (b)/15.209	Pass
20dB Bandwidth	15.231 (c)	Pass
Dwell time	15.231 (a1)	Pass
Conducted Emission	15.207	N/A

Remarks:
N/A: The EUT not applicable of the test item.
Pass: The EUT complies with the essential requirements in the standard.
TEST ACCORDING TO ANSI C63.4:2014 AND ANSI C63.10:2013.

5 General Information

5.1 Client Information

Applicant:	Green Start Industries LLC
Address of Applicant:	3305 Fairmount Ave Ocean NJ USA
Manufacturer:	Green Start Industries LLC
Address of Manufacturer:	3305 Fairmount Ave Ocean NJ USA

5.2 General Description of E.U.T.

Product Name:	keyless transmitter
Model No.:	2AOVX-3B, 2AOVX-4B
Operation Frequency:	312.15MHz, 314.35 MHz
Channel numbers:	2
Modulation type:	FSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi
Power supply:	DC 3V (CR2016 battery)
Remark:	2AOVX-3B, 2AOVX-4B are electrically identical , only except 2AOVX-3B have 3 buttons and 2AOVX-4B have 4 buttons

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation（new battery used）		
Pre-Test Mode:			
CCIS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:			
Axis	X	Y	Z
Field Strength(dBuV/m) 312.15	68.14	68.02	67.89
Field Strength(dBuV/m) 314.35	68.47	68.15	68.23
Final Test Mode:			
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”: X axis (see the test setup photo)			

5.4 Description of Support Units

N/A

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.7 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±2.22 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

5.8 Test Instruments list

Radiated Emission:					
Test Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date (mm-dd-yy)**	**Cal. Due date (mm-dd-yy)**
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	04-28-2018	04-27-2019
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2017	11-20-2018
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2017	11-20-2018
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Simulated Station	Anritsu	MT8820C	6201026545	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT make use of an PCB antenna, The typical gain of the antenna is 0 dBi.	



6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.231(b) and 15.209
Test Method:	ANSI C63.4:2014 ; ANSI C63.10:2013
Test Frequency Range:	30MHz to 5000MHz
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value

Limit:
(Field strength of the fundamental signal)

Frequency	Limit (dBuV/m @3m)	Remark
312.15MHz	75.45	Average Value
	95.45	Peak Value
314.35 MHz	75.59	Average Value
	95.59	Peak Value

Limit:
(Spurious Emissions)

Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Or The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level whichever limit permits higher field strength.

Test Procedure:

a. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test setup:	Below 1GHz  Above 1GHz 
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

6.2.1 Field Strength Of The Fundamental Signal

312.15MHz：

Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Polarization
312.15	34.58	13.86	2.98	0.00	51.42	75.45	-24.03	Vertical
312.15	51.30	13.86	2.98	0.00	68.14	75.45	-7.31	Horizontoal

314.35MHz：

Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor(dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Polarization
314.35	35.27	13.90	2.98	0.00	52.15	75.59	-23.44	Vertical
314.35	51.59	13.90	2.98	0.00	68.47	75.59	-7.12	Horizontoal

312.15 MHz:

T period:



Date: 4.SEP.2018 11:59:00

T 100ms:



Date: 4.SEP.2018 12:01:10

314.35 MHz:

T period:



Date: 7.SEP.2018 14:30:19

T 100ms:



Date: 7.SEP.2018 14:32:04

Duty cycle =100%

Test Plots:

312.15MHz：

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	312.15 MHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 312.15

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	312.074	34.58	13.86	2.98	0.00	51.42	------	------	

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	312.15 MHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 312.15

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	312.154	51.30	13.86	2.98	0.00	68.14	------	------	

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*

314.35MHz：

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	314.35 MHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 314.35

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	314.406	35.27	13.90	2.98	0.00	52.15	------	------	

Remark:

2. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	314.35 MHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 314.35

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	314.406	51.59	13.90	2.98	0.00	68.47	------	------	

Remark:

2. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

6.2.2 Spurious Emissions

312.15MHz:

Below 1GHz (30MHz-1000MHz)								
Peak value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	polarization
625.078	18.65	19.51	3.90	0.00	42.06	55.45	-13.39	Vertical
938.833	16.41	22.38	4.10	0.00	42.89	55.45	-12.56	Vertical
625.078	18.11	19.51	3.90	0.00	41.52	55.45	-13.93	Horizontoal
938.833	16.18	22.38	4.10	0.00	42.66	55.45	-12.79	Horizontoal

Test Plots:

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	45.695	16.76	13.76	1.29	0.00	31.81	40.00	-8.19	QP
2	50.409	16.30	14.02	1.25	0.00	31.57	40.00	-8.43	QP
3	94.428	17.19	10.78	2.01	0.00	29.98	43.50	-13.52	QP
4	138.387	21.77	8.19	2.38	0.00	32.34	43.50	-11.16	QP
5	625.078	18.65	19.51	3.90	0.00	42.06	46.00	-3.94	Peak
6	938.833	16.41	22.38	4.10	0.00	42.89	46.00	-3.11	Peak

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	52.391	17.65	13.66	1.29	0.00	32.60	40.00	-7.40	QP
2	93.768	16.95	10.66	2.02	0.00	29.63	43.50	-13.87	QP
3	195.137	14.86	11.36	2.84	0.00	29.06	43.50	-14.44	QP
4	271.325	15.32	13.43	2.86	0.00	31.61	46.00	-14.39	QP
5	625.078	18.11	19.51	3.90	0.00	41.52	46.00	-4.48	Peak
6	938.833	16.18	22.38	4.10	0.00	42.66	46.00	-3.34	Peak

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 312.15

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1246.691	45.21	24.47	3.38	41.05	34.47	74.00	-39.53	Peak
2	1559.250	45.95	25.36	3.80	41.03	36.31	74.00	-37.69	Peak
3	1873.261	45.19	26.13	4.20	41.37	36.60	74.00	-37.40	Peak
4	2186.248	46.40	26.88	4.49	41.68	38.77	74.00	-35.23	Peak
5	2498.699	46.14	27.61	4.82	41.90	39.51	74.00	-34.49	Peak
6	2810.210	45.77	28.25	5.14	41.65	40.39	74.00	-33.61	Peak
7	3125.149	45.50	28.68	5.39	41.45	41.04	74.00	-32.96	Peak

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 312.15

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1246.691	45.31	24.47	3.38	41.05	34.57	74.00	-39.43	Peak
2	1559.250	45.47	25.36	3.80	41.03	35.83	74.00	-38.17	Peak
3	1873.261	45.55	26.13	4.20	41.37	36.96	74.00	-37.04	Peak
4	2186.248	45.58	26.88	4.49	41.68	37.95	74.00	-36.05	Peak
5	2498.699	45.81	27.61	4.82	41.90	39.18	74.00	-34.82	Peak
6	2810.210	46.24	28.25	5.14	41.65	40.86	74.00	-33.14	Peak
7	3125.149	45.32	28.68	5.39	41.45	40.86	74.00	-33.14	Peak

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

314.35MHz:

Below 1GHz (30MHz-1000MHz)								
Peak value								
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	polarization
629.477	19.21	19.56	3.89	0.00	42.66	55.59	-12.93	Vertical
945.440	16.49	22.39	4.16	0.00	43.04	55.59	-12.55	Vertical
629.477	16.84	19.56	3.89	0.00	40.29	55.59	-15.30	Horizontoal
945.440	15.91	22.39	4.16	0.00	42.46	55.59	-13.13	Horizontoal

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	50.942	16.63	13.93	1.27	0.00	31.83	40.00	-8.17	QP
2	94.428	16.58	10.78	2.01	0.00	29.37	43.50	-14.13	QP
3	134.088	20.04	8.45	2.33	0.00	30.82	43.50	-12.68	QP
4	144.335	20.10	8.32	2.45	0.00	30.87	43.50	-12.63	QP
5	629.477	19.21	19.56	3.89	0.00	42.66	46.00	-3.34	Peak
6	945.440	16.49	22.39	4.16	0.00	43.04	46.00	-2.96	Peak

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	30 MHz ~ 1 GHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	51.121	16.52	13.89	1.27	0.00	31.68	40.00	-8.32	QP
2	56.395	17.01	12.98	1.36	0.00	31.35	40.00	-8.65	QP
3	94.428	16.45	10.78	2.01	0.00	29.24	43.50	-14.26	QP
4	121.123	16.31	10.03	2.18	0.00	28.52	43.50	-14.98	QP
5	629.477	16.84	19.56	3.89	0.00	40.29	46.00	-5.71	Peak
6	945.440	15.91	22.39	4.16	0.00	42.46	46.00	-3.54	Peak

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	**Polarization:**	Vertical
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 314.35

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1256.764	44.93	24.50	3.40	41.05	34.23	74.00	-39.77	Peak
2	1571.848	45.35	25.40	3.81	41.03	35.75	74.00	-38.25	Peak
3	1885.359	45.18	26.15	4.21	41.40	36.59	74.00	-37.41	Peak
4	2200.368	45.87	26.92	4.50	41.68	38.31	74.00	-35.69	Peak
5	2514.837	45.72	27.64	4.84	41.90	39.15	74.00	-34.85	Peak
6	2828.360	46.30	28.28	5.17	41.63	41.01	74.00	-32.99	Peak
7	3145.333	44.79	28.69	5.40	41.44	40.36	74.00	-33.64	Peak

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Keyless transmitter	**Product Model:**	2AOVX-3B
Test By:	Zora	**Test mode:**	Tx mode
Test Frequency:	1 GHz ~ 5 GHz	**Polarization:**	Horizontal
Test Voltage:	DC 3V	**Environment:**	Temp: 24℃ Huni: 57%



: 314.35

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1256.764	45.58	24.50	3.40	41.05	34.88	74.00	-39.12	Peak
2	1571.848	45.03	25.40	3.81	41.03	35.43	74.00	-38.57	Peak
3	1885.359	44.60	26.15	4.21	41.40	36.01	74.00	-37.99	Peak
4	2200.368	45.19	26.92	4.50	41.68	37.63	74.00	-36.37	Peak
5	2514.837	47.56	27.64	4.84	41.90	40.99	74.00	-33.01	Peak
6	2828.360	45.57	28.28	5.17	41.63	40.28	74.00	-33.72	Peak
7	3145.333	45.54	28.69	5.40	41.44	41.11	74.00	-32.89	Peak

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.3 20dB Bandwidth

Test Requirement:	FCC Part15 C Section 15.231 (c)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1kHz, VBW=3kHz, detector: Peak
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

312.15MHz:

20dB bandwidth (MHz)	Limit (MHz)	Results
0.092	0.7804	Passed

Note: Limit= Fundamental frequency×0.25%=312.15×0.25%=0.7804MHz

314.35MHz:

20dB bandwidth (MHz)	Limit (MHz)	Results
0.098	0.7859	Passed

Note: Limit= Fundamental frequency×0.25%=314.35×0.25%=0.7859MHz

Test plot as follows:

312.15MHz:



314.35 MHz:



6.4 Duration Time

Test Requirement:	FCC Part15 C Section 15.231 (a1)
Test Method:	ANSI C63.10: 2013
Receiver setup:	RBW=1MHz, VBW=3MHz, span=0Hz, detector: Peak
Limit:	Not more than 5 seconds
Test mode:	Transmitting mode
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Single scan the transmission, and read the transmission time.
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

312.15MHz:

Duration time (second)	Limit (second)	Result
0.800	<5.0	Pass

314.35 MHz:

Duration time (second)	Limit (second)	Result
0.832	<5.0	Pass

Test plot as follows:

312.15 MHz:



314.35 MHz: