Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

47 CFR FCC Part 15 Subpart C 15.231

Report Reference No.....:	**CTL2206162071-WF**	
Compiled by: (position+printed name+signature)	Happy Guo (File administrators)	Happy Guo
Tested by: (position+printed name+signature)	Gary Gao (Test Engineer)	Gary Gao
Approved by: (position+printed name+signature)	Ivan Xie (Manager)	Ivan Xie

Product Name..... :	433MHz Transceiver with UART interface
Model/Type reference.....:	KTX433
List Model(s).....:	KTX433-UART
Trade Mark..... :	KINGLORD
FCC ID..... :	**2AOW4-433UART**
Applicant's name..... :	**CM GLOBAL**
Address of applicant.....:	1201 N. 4TH STREET, WATERTOWN, WI 53098, USA
Test Firm.....:	**Shenzhen CTL Testing Technology Co., Ltd.**
Address of Test Firm.....:	Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055
Test specification.....:	
Standard..... :	**47 CFR FCC Part 15 Subpart C 15.231**
TRF Originator..... :	Shenzhen CTL Testing Technology Co., Ltd.
Master TRF..... :	Dated 2011-01
Date of receipt of test item..... :	Jul. 01, 2022
Date of sampling..... :	Jul. 01, 2022
Date of Test Date..... :	Jul. 01, 2022- Jul. 27, 2022
Date of Issue.....:	Jul. 27, 2022
Result..... :	**Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2206162071-WF	Jul. 27, 2022 Date of issue

Equipment under Test	:	433MHz Transceiver with UART interface
Sample No.	:	CTL220616207-1-S001 CTL220616207-1-S002
Model /Type	:	KTX433
Listed Models	:	KTX433-UART
Applicant	:	**CM GLOBAL**
Address	:	1201 N. 4TH STREET, WATERTOWN, WI 53098, USA
Manufacturer	:	**KINGLORD ELECTRONICS (HK) LTD.**
Address	:	FLAT 8, 14/F., WAH YIU INDUSTRIAL CENTRE, 30-32 AU PUI WAN STREET, HONG KONG

Test result	Pass *

∗ In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

Version	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2022-07-27	CTL2206162071-WF	Tracy Qi

Table of Contents Page

1. SUMMARY 5

1.1. Test Standards 5
1.2. Test Description 5
1.3. Test Facility 6
1.4. Statement of the measurement uncertainty 6

2. GENERAL INFORMATION 8

2.1. Environmental conditions 8
2.2. General Description of EUT 8
2.3. Description of Test Modes and Test Frequency 8
2.4. Equipments Used during the Test 8
2.5. Related Submittal(s) / Grant (s) 9
2.6. Modifications 9

3. TEST CONDITIONS AND RESULTS 10

3.1. Conducted Emission (AC Main) 10
3.2. Radiated Emission 13
3.3. 20dB Bandwidth 18
3.4. Deactivation Time 20
3.5. Antenna Requirement 22

4. TEST SETUP PHOTOS OF THE EUT 23

5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT 24

1. SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.231: Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

ANSI C63.10:2013 : American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC and IC Requirements		
FCC Part 15.207	Conducted Emission	PASS
FCC Part 15.231(a)(1)	Automatically Deactivate	PASS
FCC Part 15.231(b)	Electric Field Strength of Fundamental Emission	PASS
FCC Part 15.205 &15.209& 15.231(b)	Electric Field Strength of Spurious Emission	PASS
FCC Part 15.231(c)	-20dB bandwidth	PASS

Remark: The measurement uncertainty is not included in the test result.

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.
Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)

Conducted Disturbance0.15~30MHz	±3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95%
(2) confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	433MHz Transceiver with UART interface
Model/Type reference:	KTX433
Hardware version:	01
Software version:	01
Power supply:	DC 5V
Modulation:	ASK
Operation frequency:	432.700MHz~434.900MHz
Channel number:	8
Antenna type:	External Antenna
Antenna gain:	2.5 dBi

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes and Test Frequency

Operation Frequency：

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	**432.700**	5	434.000
2	433.100	6	434.300
3	433.500	7	434.600
4	433.600	**8**	**434.900**

Note1: In section 15.31(m), regards to the operating frequency range less than 10MHz, one near top and one near bottom point in the frequency range of operation should selected to measure.
Note2: The line display in grey was the channel selected for test.

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2022/05/06	2023/05/05
LISN	R&S	ESH2-Z5	860014/010	2022/05/06	2023/05/05
Double Cone logarithmic antenna	Schwarzbeck	VULB 9168	824	2020/04/07	2023/04/06

Active Loop Antenna	Da Ze	ZN30900A	/	2021/05/13	2024/05/12
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2021/12/23	2024/12/22
Horn Antenna	Ocean Microwave	OBH100400	26999002	2019/11/28	2022/11/27
EMI Test Receiver	R&S	ESCI	1166.5950.03	2022/05/06	2023/05/05
Spectrum Analyzer	Agilent	N9020	US46220290	2022/05/07	2023/05/06
Spectrum Analyzer	RS	FSP	1164.4391.38	2022/05/07	2023/05/06
Controller	EM Electronics	EM 1000	060859	2022/05/20	2023/05/19
Amplifier	Agilent	8449B	3008A02306	2022/05/07	2023/05/06
Amplifier	Agilent	8447D	2944A10176	2022/05/06	2023/05/05
Amplifier	Brief&Smart	LNA-4018	2104197	2022/05/07	2023/05/06
Temperature/Humidity Meter	Ji Yu	MC501	/	2022/05/07	2023/05/06
Power Sensor	Agilent	U2021XA	MY55130004	2022/05/07	2023/05/06
Power Sensor	Agilent	U2021XA	MY55130006	2022/05/07	2023/05/06
Power Sensor	Agilent	U2021XA	MY54510008	2022/05/07	2023/05/06
Power Sensor	Agilent	U2021XA	MY55060003	2022/05/07	2023/05/06
High-Pass Filter	micro-tranics	HPM50108	G174	2022/05/07	2023/05/06
High-Pass Filter	micro-tranics	HPM50111	G142	2022/05/07	2023/05/06
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	2022/05/07	2023/05/06
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2022/05/07	2023/05/06
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2022/05/07	2023/05/06
RF Cable	Megalon	RF-A303	N/A	2022/05/07	2023/05/06
RF Control Unit	Tonsecnd	JS0806-2	20J8060323	2022/05/07	2023/05/06
Test Software	Tonsecnd	JS1120-3	2.6.880341	N/A	N/A
Test software	EZ	EZ_EMC	1.1.4.2	N/A	N/A

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.231 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emission (AC Main)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a flood stand system; a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2. Support equipment, if needed, was placed as per ANSI C63.10-2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Test Mode	TX	Line:	L

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL220707019_fin"

7/7/2022 10:05AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
4.033500	34.00	10.3	56	22.0	QP	L1	GND
4.042500	33.80	10.3	56	22.2	QP	L1	GND
4.402500	34.30	10.3	56	21.7	QP	L1	GND
4.749000	31.90	10.3	56	24.1	QP	L1	GND
4.816500	32.90	10.4	56	23.1	QP	L1	GND
4.875000	33.30	10.4	56	22.7	QP	L1	GND

MEASUREMENT RESULT: "CTL220707019_fin2"

7/7/2022 10:05AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
1.005000	19.90	10.2	46	26.1	AV	L1	GND
1.018500	21.80	10.2	46	24.2	AV	L1	GND
1.491000	18.50	10.2	46	27.5	AV	L1	GND
3.453000	20.60	10.3	46	25.4	AV	L1	GND
3.916500	22.80	10.3	46	23.2	AV	L1	GND
4.789500	23.70	10.4	46	22.3	AV	L1	GND

Test Mode	TX	Line:	N

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL220707020_fin"

7/7/2022 10:08AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
3.412500	34.00	10.3	56	22.0	QP	N	GND
3.619500	33.60	10.3	56	22.4	QP	N	GND
3.975000	34.50	10.3	56	21.5	QP	N	GND
4.465500	34.90	10.3	56	21.1	QP	N	GND
4.497000	34.50	10.3	56	21.5	QP	N	GND
4.897500	34.60	10.4	56	21.4	QP	N	GND

MEASUREMENT RESULT: "CTL220707020_fin2"

7/7/2022 10:08AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
2.391000	23.80	10.3	46	22.2	AV	N	GND
2.886000	23.90	10.3	46	22.1	AV	N	GND
3.097500	23.70	10.3	46	22.3	AV	N	GND
3.291000	24.70	10.3	46	21.3	AV	N	GND
3.579000	23.10	10.3	46	22.9	AV	N	GND
3.754500	24.20	10.3	46	21.8	AV	N	GND

Remark: Level(dBuV)=Reading(dBuV)＋Factor(dB)
Margin=Limit(dBuV)-Level(dBuV)

3.2. Radiated Emission

Limit

For intentional device, according to 15.209(a) the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

In addition to the provisions of 15.231(b) and RSS 210-A1.1.2, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66–40.70.	2,250	225
70–130	1,250	125
130–174	[1] 1,250 to 3,750	[1] 125 to 375
174–260	3,750	375
260–470	[1] 3,750 to 12,500	[1] 375 to 1,250
Above 470	12,500	1,250

[1] Linear interpolations.

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 260-470 MHz, μV/m at 3 meters =41.6667(F) - 7083.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

TEST RESULTS

The emissions from 30MHz to 5GHz are measured with PEAK detector; and average level calculated with Duty cycle correction according 15.35(c), detailed test data please see below. Besides, we tested 3 directions and recorded the worst data

Test frequency:432.700MHz

Emission Styles	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Direction (H/V)
Fundamental	432.70	82.15	100.78	18.63	PK	H
Spurious	699.30	30.79	46.00	15.21	PK	H
Harmonics	865.40	60.13	80.78	20.65	PK	H
Harmonics	1298.10	57.75	74.00	16.25	PK	H
--	--	--	--	--	--	--
Fundamental	432.70	80.56	100.78	20.22	PK	V
Spurious	768.74	31.82	46.00	14.18	PK	V
Harmonics	865.40	60.26	80.78	20.52	PK	V
Harmonics	1298.10	57.35	74.00	16.65	PK	V
--	--	--	--	--	--	--

Note: Margin= Limit-Emission level

Emission Styles	Frequency (MHz)	PK Emission Level (dBuV/m)	AV Factor (dB/m)	AV Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Direction (H/V)
Fundamental	432.70	82.15	-6.37	75.78	80.78	5.00	H
Harmonics	865.40	60.13	-6.37	53.76	60.78	7.02	H
Harmonics	1298.10	57.75	-6.37	51.38	54.00	2.62	H
--	--	--	--	--	--	--	--
Fundamental	432.70	80.56	-6.37	74.19	80.78	6.59	V
Harmonics	865.40	60.26	-6.37	53.89	60.78	6.89	V
Harmonics	1298.10	57.35	-6.37	50.98	54.00	3.02	V
--	--	--	--	--	--	--	--

Test frequency:434.900MHz

Emission Styles	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Direction (H/V)
Fundamental	434.90	81.37	100.86	19.49	PK	H
Spurious	848.05	34.24	46.00	11.76	PK	H
Harmonics	869.80	59.82	80.86	21.04	PK	H
Harmonics	1304.70	58.31	74.00	15.69	PK	H
--	--	--	--	--	--	--
Fundamental	434.90	79.90	100.86	20.96	PK	V
Spurious	842.12	33.63	46.00	12.37	PK	V

Harmonics	869.80	60.08	80.86	20.78	PK	V
Harmonics	1304.70	58.75	74.00	15.25	PK	V
--	--	--	--	--	--	--

Note: Margin= Limit-Emission level

Emission Styles	Frequency (MHz)	PK Emission Level (dBuV/m)	AV Factor (dB/m)	AV Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Direction (H/V)
Fundamental	434.90	81.37	-6.37	75.00	80.86	5.86	H
Harmonics	869.80	59.82	-6.37	53.45	60.86	7.41	H
Harmonics	1304.70	58.31	-6.37	51.94	54.00	2.06	H
--	--	--	--	--	--	--	--
Fundamental	434.90	79.90	-6.37	73.53	80.86	7.33	V
Harmonics	869.80	60.08	-6.37	53.71	60.86	7.15	V
Harmonics	1304.70	58.75	-6.37	52.38	54.00	1.62	V
--	--	--	--	--	--	--	--

Note:

1. AV Level (dBuV/m)= PK Emission Level (dBuV/m)+ AV Factor(dB)
2. Duty Cycle= (12.00 *4)/100.0=0.48 (Note: According to C63.10 if the transmit cycle period longer than 100ms, then 100ms is used calculation.)
3. AV Factor=20*log(Duty Cycle)=20*log(0.48)=-6.37

(The plot of Duty Cycle See the follow page)

Duty cycle plots



(Transmit cycle 204.0 ms)

(Total Bursts in a transmit cycle 6pcs)



(12.00ms per burst)

3.3. 20dB Bandwidth

Limit

According to 47 CFR 15.231(c) The bandwidth of the emission shall be no wider than 0.25% of the centre frequency for devices operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20dB down from the modulated carrier.

Test Configuration



Test Procedure

The 20dB bandwidth and 99% bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

The occupied bandwidth (OBW), that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Test Results

Modulation	Channel Frequency (MHz)	99% OBW (KHz)	20dB bandwidth (KHz)	Limit (KHz)	Result
ASK	432.700	213.30	222.1	0.25%*432.700=1081.75	Pass
	434.900	213.76	219.4	0.25%*434.900=1087.25	Pass

Test plot as follows:

432.70MHz

434.90MHz


Keysight Spectrum Analyzer - Occupied BW
Center Freq 434.900000 MHz
Center Freq: 434.900000 MHz
Trig: Free Run
Avg|Hold:>10/10
#Atten: 30 dB
#IFGain:Low
Radio Std: None
Radio Device: BTS
09:00:38 PM Jul 14, 2022
Frequency
15 dB/div
Ref 20.00 dBm
Center 434.9 MHz
#Res BW 10 kHz
#VBW 30 kHz
Span 500 kHz
Sweep 6.2 ms
Center Freq
434.900000 MHz
CF Step
50.000 kHz
Auto
Man
Freq Offset
0 Hz
Occupied Bandwidth
213.76 kHz
Total Power 17.0 dBm
Transmit Freq Error -1.159 kHz
% of OBW Power 99.00 %
x dB Bandwidth 219.4 kHz
x dB -20.00 dB
MSG
STATUS

3.4. Deactivation Time

Limit

According to FCC §15.231(a)(1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

Test Configuration



Test Procedure

1. The EUT was placed on a wooded table which is 0.8m height and close to receiver antenna of spectrum analyzer.
2. The spectrum analyzer resolution bandwidth was set to 1 MHz and video bandwidth was set to 1 MHz to encompass all significant spectral components during the test. The spectrum analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency.

TEST RESULTS

Note : Multiple groups of channels are tested, only the poor frequencies are recorded, other frequencies meet the requirements.

Frequency (MHz)	One transmission time (S)	Limit(S)	Result
432.70	0.6800	5	Pass
434.90	0.5600	5	Pass




Keysight Spectrum Analyzer - Swept SA
Center Freq 434.900000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 2/100
10:49:18 PM Jul 26, 2022
ΔMkr1 560.0 ms
55.691 dB
10 dB/div
Log
Ref 20.00 dBm
1Δ2
Center 434.900000 MHz
Res BW 3.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 10.00 s (1001 pts)
Frequency
Auto Tune
Center Freq
434.900000 MHz
Start Freq
434.900000 MHz
Stop Freq
434.900000 MHz
CF Step
3.000000 MHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin

3.5. Antenna Requirement

Standard Applicable

According to FCC Part 15C 15.203

a) An intentional radiator shall be de-signed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

b) The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is an external antenna, The directional gains of antenna used for transmitting is 2.5dBi.

4. Test Setup Photos of the EUT



5. External and Internal Photos of the EUT

Photos of EUT









********** End of Report **********