

TEST REPORT

Applicant: SHENZHEN 8BITDO TECH CO., LTD.
Address: Room 210, Building 1, Nanhai Ecool, No.6 Xinghua Road, Shekou, Nanshan District, Shenzhen, China
Equipment Type: 8BitDo Pro 3 Bluetooth Gamepad
Model Name: 80GQ
Brand Name: 8BITDO
FCC ID: 2AOWF-PRO3
ISED Number: 29401-PRO3
47 CFR Part 15 Subpart C
Test Standard: RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Feb. 19, 2025
Test Date: Feb. 27, 2025 - Sep. 18, 2025
Date of Issue: Oct. 15, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie Zhu**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Oct. 15, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Test Software List	9
4.4	Measurement Uncertainty	10
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Number of Hopping Frequency	15
5.3	Peak Output Power and E.I.R.P	16
5.4	Occupied Bandwidth	17
5.5	Carrier Frequency Separation	18

5.6	Time of Occupancy (Dwell time)	19
5.7	Conducted Spurious Emission & Authorized-band band-edge.....	20
5.8	Conducted Emission.....	21
5.9	Radiated Spurious Emission	22
5.10	Band Edge (Restricted-band band-edge).....	24
ANNEX A	TEST RESULT	25
A.1	Number of Hopping Frequency.....	25
A.2	Peak Output Power and E.I.R.P	26
A.3	Occupied Bandwidth.....	28
A.4	Hopping Frequency Separation	30
A.5	Time of Occupancy (Dwell time)	31
A.6	Conducted Spurious Emissions & Authorized-band band-edge	32
A.7	Conducted Emissions	36
A.8	Radiated Emission.....	38
A.9	Band Edge (Restricted-band band-edge).....	43
ANNEX B	TEST SETUP PHOTOS	44
ANNEX C	EUT EXTERNAL PHOTOS.....	44
ANNEX D	EUT INTERNAL PHOTOS.....	44

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	SHENZHEN 8BITDO TECH CO., LTD.
Address	Room 210, Building 1, Nanhai Ecool, No.6 Xinghua Road, Shekou, Nanshan District, Shenzhen, China

2.2 Manufacturer Information

Manufacturer	SHENZHEN ONEBITDO TECH CO., LTD.
Address	Room 203, Building 1, Huajian Building, Xinghua Road, Shekou, Shuiwan Community, Zhaoshang Street, Nanshan District, Shenzhen, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	8BitDo Pro 3 Bluetooth Gamepad
Model Name Under Test	80GQ
Series Model Name	N/A
Description of Model name differentiation	N/A
Serial Number	80GQ020 25630 001131
Hardware Version	V3
Software Version	V1.1
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR), 2.4G ISM Band
-----------------------------------	-------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	1 Mbps
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	Low (2402 MHz), Middle (2441 MHz), High (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	0.84 dBi
The Max RF Output power	3.56 dBm
Adaptive or non-adaptive	Non-adaptive

All Channel List:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
1	2402	22	2423	43	2444	64	2465
2	2403	23	2424	44	2445	65	2466
3	2404	24	2425	45	2446	66	2467
4	2405	25	2426	46	2447	67	2468
5	2406	26	2427	47	2448	68	2469
6	2407	27	2428	48	2449	69	2470
7	2408	28	2429	49	2450	70	2471
8	2409	29	2430	50	2451	71	2472
9	2410	30	2431	51	2452	72	2473
10	2411	31	2432	52	2453	73	2474
11	2412	32	2433	53	2454	74	2475
12	2413	33	2434	54	2455	75	2476
13	2414	34	2435	55	2456	76	2477
14	2415	35	2436	56	2457	77	2478
15	2416	36	2437	57	2458	78	2479
16	2417	37	2438	58	2459	79	2480
17	2418	38	2439	59	2460	-	-
18	2419	39	2440	60	2461	-	-
19	2420	40	2441	61	2462	-	-
20	2421	41	2442	62	2463	-	-
21	2422	42	2443	63	2464	-	-

Note: The modulation is GFSK with FHSS, there are total 79 channels (frequency range is 2402-2480 MHz, channel step is 1 MHz, totally 79 channels), when this part works, it will choose 79 channels, each channel band width is 1 MHz, if one channel is chosen, adjacent two channels cannot be chosen to make sure step of working channels is more than 2 MHz. the equipment select the lowest, middle and highest channel from 79 channels, Which are 2402 MHz, 2441 MHz and 2480 MHz. The more information please refer to the manufacturer's instructions.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSS), Frequency Hopping Systems(FHSs) and Licence-Exemp Local Area Network (LE-LAN) Devices
4	ANSI C63.10-2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
5	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (6)	--	Pass ^{Note 1}
2	Number of Hopping Frequency	15.247(a)	RSS-247, 5.1 (4)	ANNEX A.1	Pass
3	Peak Output Power and E.I.R.P	15.247(b)	RSS-247, 5.4 (2)	ANNEX A.2	Pass
4	Occupied Bandwidth	15.247(a)	RSS-247, 5.1 (1)	ANNEX A.3	Pass
5	Hopping Frequency Separation	15.247(a)	RSS-247, 5.1 (2)	ANNEX A.4	Pass
6	Time of Occupancy (Dwell time)	15.247(a)	RSS-247, 5.1 (4)	ANNEX A.5	Pass
7	Conducted Spurious Emission& Authorized-band band-edge	15.247(d)	RSS-247, 5.5	ANNEX A.6	Pass
8	Conducted Emission	15.207	RSS-GEN, 8.8	ANNEX A.7	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	ANNEX A.8	Pass
10	Band Edge (Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	ANNEX A.9	Pass
11	Receiver Spurious Emissions	--	RSS-Gen, 7.1.2	--	N/A ^{Note 2}

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	48% to 61%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+21.8°C to +24.4°C
Working Voltage of the EUT	NV (Normal Voltage)	3.7 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
				2025.06.16	2026.06.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2024.08.01	2025.07.31
				2025.06.16	2026.06.15
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2025.02.22	2028.02.21
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2025.01.03	2028.01.02
Amplifier	COM-MV	LSCX_LNA1-12G-01	180602	2024.08.01	2025.07.31
				2025.06.17	2026.06.16
Amplifier	COM-MV	XKu_LNA7-18G-01	180601	2024.08.01	2025.07.31
				2025.06.17	2026.06.16
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
				2025.06.16	2026.06.15
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31
				2025.06.16	2026.06.15
LISN	SCHWARZBECK	NSLK 8127	8127-687	2024.05.09	2025.05.08
				2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%

4.5 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with “Duty cycle correction factor”.

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.1 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequency

5.2.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (4)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Peak Output Power and E.I.R.P

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (2)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

EIRP= Maximum peak conducted output power +Antenna Gain.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (4)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * \{\text{Number of Hopping Frequency in Period}\}$$

$$\{\text{Period}\} = 0.4\text{s} * \{\text{Number of Hopping Frequency}\}$$

The middle channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.6.4 Test Result

Please refer to ANNEX A.5

5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.9.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Please refer to ANNEX A.8.

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass

Test Plots

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P

Peak Power Test Data


Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	3.56	2.27	30	1000	Pass
Middle	3.35	2.16			Pass
High	2.86	1.93			Pass

E.I.R.P Test Data (For ISSED)


Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	mW	
Low	4.40	2.75	36	4000	Pass
Middle	4.19	2.62			Pass
High	3.70	2.34			Pass

Test Plots


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



A.3 Occupied Bandwidth

Test Data

Test Mode	GFSK	
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	1.425000	1.220900
Middle Channel	1.461000	1.225000
High Channel	1.467000	1.230300

Test Plots

20 dB Bandwidth


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



99% Bandwidth


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL




A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.000	0.978	Pass

Test Plot

GFSK




A.5 Time of Occupancy (Dwell time)

Test Data


GFSK			
Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
1.667	333.400	0.4	Pass

Test Plots

Pulse Width



Total of Dwell



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK Mode:


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-32.62	1.65	-18.35	Pass
Middle	-32.94	1.43	-18.57	Pass
High	-32.59	0.94	-19.06	Pass

Hopping Mode:


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-32.73	1.96	-18.04	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz






GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)



GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHzGFSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz

A.7 Conducted Emissions

Note¹: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.


Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.150	50.23	9.86	66.00	15.77	Peak	L	Pass
1**	0.150	31.28	9.86	56.00	24.72	AV	L	Pass
2	0.260	42.12	9.83	61.43	19.31	Peak	L	Pass
2**	0.260	26.51	9.83	51.43	24.92	AV	L	Pass
3	0.544	37.24	10.08	56.00	18.76	Peak	L	Pass
3**	0.544	25.42	10.08	46.00	20.58	AV	L	Pass
4	2.180	38.31	10.12	56.00	17.69	Peak	L	Pass
4**	2.180	28.16	10.12	46.00	17.84	AV	L	Pass
5	4.094	38.34	10.50	56.00	17.66	Peak	L	Pass
5**	4.094	26.23	10.50	46.00	19.77	AV	L	Pass
6	23.994	40.65	10.80	60.00	19.35	Peak	L	Pass
6**	23.994	27.47	10.80	50.00	22.53	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.166	55.69	9.85	65.16	9.47	Peak	N	Pass
1**	0.166	33.98	9.85	55.16	21.18	AV	N	Pass
2	0.210	47.87	9.84	63.21	15.34	Peak	N	Pass
2**	0.210	32.16	9.84	53.21	21.05	AV	N	Pass
3	0.346	41.03	10.74	59.06	18.03	Peak	N	Pass
3**	0.346	28.10	10.74	49.06	20.96	AV	N	Pass
4	0.482	38.70	10.06	56.30	17.60	Peak	N	Pass
4**	0.482	26.17	10.06	46.30	20.13	AV	N	Pass
5	3.522	40.93	10.20	56.00	15.07	Peak	N	Pass
5**	3.522	26.91	10.20	46.00	19.09	AV	N	Pass
6	19.942	44.90	11.23	60.00	15.10	Peak	N	Pass
6**	19.942	34.68	11.23	50.00	15.32	AV	N	Pass

A.8 Radiated Emission

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

Test Data and Plots

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	289.039	30.34	-25.90	35.5	5.16	Peak	102.00	196	Horizontal	N/A
1*	289.039	27.30	-25.90	35.5	8.20	QP	102.00	196	Horizontal	Pass
2	337.171	25.82	-24.39	35.5	9.68	Peak	259.00	200	Horizontal	Pass
3	480.005	34.54	-20.84	35.5	0.96	Peak	360.00	167	Horizontal	N/A
3*	480.005	32.11	-20.84	35.5	3.39	QP	360.00	167	Horizontal	Pass
4	636.826	27.95	-16.27	35.5	7.55	Peak	166.00	100	Horizontal	Pass
5	880.470	33.05	-11.26	35.5	2.45	Peak	242.00	118	Horizontal	N/A
5*	880.470	28.97	-11.26	35.5	6.53	QP	242.00	118	Horizontal	Pass
6	960.012	35.04	-9.90	35.5	0.46	Peak	193.00	115	Horizontal	N/A
6*	960.012	31.50	-9.90	35.5	4.00	QP	193.00	115	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	67.578	24.85	-28.76	29.5	4.65	Peak	360.00	300	Vertical	Pass
2	192.677	28.93	-28.71	33.0	4.07	Peak	243.00	100	Vertical	Pass
3	322.734	34.47	-25.22	35.5	1.03	Peak	248.00	103	Vertical	N/A
3*	322.734	30.98	-25.22	35.5	4.52	QP	248.00	103	Vertical	Pass
4	479.968	33.48	-20.84	35.5	2.02	Peak	194.00	400	Vertical	N/A
4*	479.968	31.47	-20.84	35.5	4.03	QP	194.00	400	Vertical	Pass
5	880.720	35.19	-11.26	35.5	0.31	Peak	112.00	200	Vertical	N/A
5*	880.720	31.92	-11.26	35.5	3.58	QP	112.00	200	Vertical	Pass
6	959.998	34.11	-9.90	35.5	1.39	Peak	0.00	200	Vertical	N/A
6*	959.998	30.76	-9.90	35.5	4.74	QP	0.00	200	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1446.800	40.44	74.0	33.56	Peak	356.00	400	Horizontal	Pass
1**	1446.800	31.39	54.0	22.61	AV	356.00	400	Horizontal	Pass
2	2402.200	93.23	74.0	-19.23	Peak	23.00	150	Horizontal	N/A
2**	2402.200	91.94	54.0	-37.94	AV	23.00	150	Horizontal	N/A
3	3202.800	51.31	74.0	22.69	Peak	187.00	150	Horizontal	Pass
3**	3202.800	49.63	54.0	4.37	AV	187.00	150	Horizontal	Pass
4	4003.600	49.11	74.0	24.89	Peak	347.00	150	Horizontal	Pass
4**	4003.600	47.34	54.0	6.66	AV	347.00	150	Horizontal	Pass
5	12608.263	48.15	74.0	25.85	Peak	197.00	100	Horizontal	Pass
5**	12608.263	39.04	54.0	14.96	AV	197.00	100	Horizontal	Pass
6	17426.176	51.37	74.0	22.63	Peak	87.00	300	Horizontal	Pass
6**	17426.176	42.24	54.0	11.76	AV	87.00	300	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.400	41.35	74.0	32.65	Peak	115.00	300	Vertical	Pass
1**	1333.400	30.67	54.0	23.33	AV	115.00	300	Vertical	Pass
2	2402.100	81.65	74.0	-7.65	Peak	358.00	150	Vertical	N/A
2**	2402.100	80.94	54.0	-26.94	AV	358.00	150	Vertical	N/A
3	4725.600	48.93	74.0	25.07	Peak	171.00	150	Vertical	Pass
3**	4725.600	38.38	54.0	15.62	AV	171.00	150	Vertical	Pass
4	5323.800	53.19	74.0	20.81	Peak	27.00	300	Vertical	Pass
4**	5323.800	42.29	54.0	11.71	AV	27.00	300	Vertical	Pass
5	12802.237	48.20	74.0	25.80	Peak	31.00	200	Vertical	Pass
5**	12802.237	38.70	54.0	15.30	AV	31.00	200	Vertical	Pass
6	17380.499	51.28	74.0	22.72	Peak	141.00	200	Vertical	Pass
6**	17380.499	42.21	54.0	11.79	AV	141.00	200	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1505.500	40.26	74.0	33.74	Peak	192.00	200	Horizontal	Pass
1**	1505.500	31.95	54.0	22.05	AV	192.00	200	Horizontal	Pass
2	2441.100	93.07	74.0	-19.07	Peak	23.00	200	Horizontal	N/A
2**	2441.100	91.97	54.0	-37.97	AV	23.00	200	Horizontal	N/A
3	3255.000	49.05	74.0	24.95	Peak	204.00	150	Horizontal	Pass
3**	3255.000	48.40	54.0	5.60	AV	204.00	150	Horizontal	Pass
4	4068.400	49.18	74.0	24.82	Peak	360.00	150	Horizontal	Pass
4**	4068.400	46.63	54.0	7.37	AV	360.00	150	Horizontal	Pass
5	12799.088	47.66	74.0	26.34	Peak	223.00	100	Horizontal	Pass
5**	12799.088	38.31	54.0	15.69	AV	223.00	100	Horizontal	Pass
6	17391.000	51.70	74.0	22.30	Peak	334.00	300	Horizontal	Pass
6**	17391.000	41.96	54.0	12.04	AV	334.00	300	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1326.300	40.52	74.0	33.48	Peak	115.00	300	Vertical	Pass
1**	1326.300	31.33	54.0	22.67	AV	115.00	300	Vertical	Pass
2	2440.900	81.30	74.0	-7.30	Peak	208.00	100	Vertical	N/A
2**	2440.900	79.94	54.0	-25.94	AV	208.00	100	Vertical	N/A
3	4976.200	48.67	74.0	25.33	Peak	0.00	150	Vertical	Pass
3**	4976.200	39.78	54.0	14.22	AV	0.00	150	Vertical	Pass
4	6984.400	52.22	74.0	21.78	Peak	313.00	400	Vertical	Pass
4**	6984.400	43.08	54.0	10.92	AV	313.00	400	Vertical	Pass
5	12890.174	48.97	74.0	25.03	Peak	32.00	100	Vertical	Pass
5**	12890.174	38.46	54.0	15.54	AV	32.00	100	Vertical	Pass
6	17480.776	51.10	74.0	22.90	Peak	360.00	300	Vertical	Pass
6**	17480.776	41.61	54.0	12.39	AV	360.00	300	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1503.100	40.29	74.0	33.71	Peak	186.00	400	Horizontal	Pass
1**	1503.100	30.82	54.0	23.18	AV	186.00	400	Horizontal	Pass
2	2479.900	95.06	74.0	-21.06	Peak	92.00	100	Horizontal	N/A
2**	2479.900	94.04	54.0	-40.04	AV	92.00	100	Horizontal	N/A
3	3306.800	48.34	74.0	25.66	Peak	203.00	150	Horizontal	Pass
3**	3306.800	47.07	54.0	6.93	AV	203.00	150	Horizontal	Pass
4	4133.600	48.51	74.0	25.49	Peak	360.00	150	Horizontal	Pass
4**	4133.600	45.48	54.0	8.52	AV	360.00	150	Horizontal	Pass
5	11894.688	47.59	74.0	26.41	Peak	223.00	400	Horizontal	Pass
5**	11894.688	38.21	54.0	15.79	AV	223.00	400	Horizontal	Pass
6	17397.563	51.39	74.0	22.61	Peak	3.00	400	Horizontal	Pass
6**	17397.563	42.94	54.0	11.06	AV	3.00	400	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1560.700	41.03	74.0	32.97	Peak	207.00	100	Vertical	Pass
1**	1560.700	31.46	54.0	22.54	AV	207.00	100	Vertical	Pass
2	2479.900	83.49	74.0	-9.49	Peak	31.00	150	Vertical	N/A
2**	2479.900	82.05	54.0	-28.05	AV	31.00	150	Vertical	N/A
3	4970.200	48.24	74.0	25.76	Peak	122.00	100	Vertical	Pass
3**	4970.200	39.68	54.0	14.32	AV	122.00	100	Vertical	Pass
4	6521.200	52.37	74.0	21.63	Peak	11.00	100	Vertical	Pass
4**	6521.200	42.15	54.0	11.85	AV	11.00	100	Vertical	Pass
5	12476.013	47.96	74.0	26.04	Peak	172.00	300	Vertical	Pass
5**	12476.013	38.49	54.0	15.51	AV	172.00	300	Vertical	Pass
6	16982.813	51.32	74.0	22.68	Peak	251.00	200	Vertical	Pass
6**	16982.813	41.22	54.0	12.78	AV	251.00	200	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2020, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Note ⁵: Both horizontal and vertical directions were pre tested, only the worst configuration has been reported in this report.

Test Data

GFSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2379.000	55.80	74.0	18.20	Peak	5.00	200	Horizontal	Pass
1**	2379.000	43.35	54.0	10.65	AV	5.00	200	Horizontal	Pass
2	2389.833	53.07	74.0	20.93	Peak	22.00	100	Horizontal	Pass
2**	2389.833	43.04	54.0	10.96	AV	22.00	100	Horizontal	Pass

GFSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	68.90	74.0	5.10	Peak	87.00	100	Horizontal	Pass
1**	2483.500	50.97	54.0	3.03	AV	87.00	100	Horizontal	Pass
2	2483.750	68.37	74.0	5.63	Peak	25.00	100	Horizontal	Pass
2**	2483.750	49.87	54.0	4.13	AV	25.00	100	Horizontal	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ24A0553-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ24A0553-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ24A0553-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--