



FCC 47 CFR PART 15 SUBPART C 15.247

TEST REPORT

FOR

THE WEARABLE

Model : TGB003

Issued to

INTELINOVA SOFTWARE, S.L.
CAMINO DE LA GOLETA SN EDIF LA CELULOSA 1 LOCAL IZQ 04007
ALMERIA Spain
Issued by
WH Technology Corp.



Open Site		No.120, Ln. 5, Hudong St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
EMC Test Site	Xizhi Office and Lab	7F., No.262, Sec. 3, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
Tel.: +886-7729-7707 Fax: +886-2- 8648-1311		

Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of WH Technology Corp.. This document may be altered or revised by WH Technology Corp.. Personnel only, and shall be noted in the revision section of the document.



1. GENERAL INFORMATION

Applicant : INTELINOVA SOFTWARE, S.L.
Address : CAMINO DE LA GOLETA SN EDIF LA CELULOSA 1 LOCAL IZQ
04007 ALMERIA Spain
Manufacturer : Trainingym
Address : Camino de la Goleta, 1, 04007 Almeria, España, Spain
Factory : Vexos Dongguan Industrial Company Limited
Address : Plainvim Industrial Park, Zhongxin Avenue, Dongkeng Town,
Dongguan, Guangdong Province, P.R.China
EUT : The wearable
Model Name : TGB003
Trade Name : TGBand
Model : N/A
Differences

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart C and the measurement procedures were according to ANSI C63.10-2013. The said equipment in the configuration described in this report shows the maximum emission levels emanating

FCC part 15 Subpart C


Receipt Date : 07/02/2018

Final Test Date : 07/28/2018

Tested By:

Reviewed by:

July 28, 2018
(Date)


Bing Chang/ Engineer

July 28, 2018
(Date)




Bell Wei / Manager

Designation Number: TW2954



EUT Specification

EUT:	TGBand
M/N:	TGB003
FCC ID:	2AP27-TGB
Frequency band:(Operating)	☒ Bluetooth:2.402GHz~2.480GHz
Device category:	☒ Mobile (>20cm separation)
Antenna diversity:	☒ Single antenna
Antenna Type:	Fractus Antenna
Antenna gain:	0.2dBi
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-1	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is Reached.



Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Antenna gain	Max Tune-UP power (W)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK							
Low	2402	2.53	±0.5	0.2dBi	0.001875	0.000373	1
Middle	2440	2.47	±0.5	0.2dBi	0.001849	0.000367	1
High	2480	1.44	±0.5	0.2dBi	0.001837	0.000365	1

---END---