TEST REPORT

Applicant:	INTERNATIONAL DEVELOPMENT COMPANY
Address of Applicant:	899 Henrietta Creek Road, Roanoke, Texas 76262, United States
Manufacturer/Factory:	1. Zhongshan Quanxin Lighting Electrical Co., Ltd. 2. Solana Smart Lighting Co., Ltd.
Address of Manufacturer/Factory:	1. Hong Ji Street, Shalang, Long Ping Cun, West District, Zhongshan Guangdong 528411 China 2. No.268 Moo 7, Huasamrong Sub-district, Plaengyao District, Chachoengsao Province, Thailand 24190
Equipment Under Test (EUT)	
Product Name:	Solar LED Light
Model No.:	SR32SL02H-08
FCC ID:	2AP35-SR32SL02H-08
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.249
Date of sample receipt:	October 21, 2022
Date of Test:	October 21-28, 2022
Date of report issued:	October 28, 2022
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*October 28, 2022*	*Original*

Prepared By: ***Date:*** *October 28, 2022*

Project Engineer

Check By: ***Date:*** *October 28, 2022*

Reviewer

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

4.1 MEASUREMENT UNCERTAINTY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 6
5.3 DESCRIPTION OF SUPPORT UNITS 6
5.4 DEVIATION FROM STANDARDS 6
5.5 ABNORMALITIES FROM STANDARD CONDITIONS 6
5.6 TEST FACILITY 6
5.7 TEST LOCATION 6
5.8 ADDITIONAL INSTRUCTIONS 6

6 TEST INSTRUMENTS LIST 7

7 TEST RESULTS AND MEASUREMENT DATA 9

7.1 ANTENNA REQUIREMENT 9
7.2 RADIATED EMISSION METHOD 10
7.2.1 Field Strength of The Fundamental Signal 12
7.2.2 Spurious emissions 14
7.2.3 Bandedge emissions 26
7.3 20DB OCCUPY BANDWIDTH 30

8 TEST SETUP PHOTO 32

9 EUT CONSTRUCTIONAL DETAILS 32

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. *Test according to ANSI C63.10: 2013.*
2. *Pass: The EUT complies with the essential requirements in the standard.*

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	Solar LED Light
Model No.:	SR32SL02H-08
Serial No.:	QXSR32SL02H08
Test sample(s) ID:	GTS202210000142-1
Sample(s) Status	Engineered sample
Operation Frequency:	2420MHz, 2450MHz, 2470MHz
Channel numbers:	3
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	1.48dBi(Declared by applicant)
Power supply:	DC 3.7V, 2000mAh for Rechargeable Li-ion Battery The battery is charged by solar panel

The test frequencies are below:

Channel	Frequency
The lowest channel	2420MHz
The middle channel	2450MHz
The Highest channel	2470MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	89.24	90.63	88.16

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

● **IC —Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

● **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 02, 2020	July 01, 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 22, 2022	April 21, 2023
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 21, 2022	March 20, 2023
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June 12, 2022	June 11, 2023
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 23, 2022	June 22, 2023
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	April 22, 2022	April 21, 2023
9	Coaxial Cable	GTS	N/A	GTS211	April 22, 2022	April 21, 2023
10	Coaxial cable	GTS	N/A	GTS210	April 22, 2022	April 21, 2023
11	Coaxial Cable	GTS	N/A	GTS212	April 22, 2022	April 21, 2023
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	April 22, 2022	April 21, 2023
13	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 23, 2022	June 22, 2023
14	Band filter	Amindeon	82346	GTS219	June 23, 2022	June 22, 2023
15	Power Meter	Anritsu	ML2495A	GTS540	June 23, 2022	June 22, 2023
16	Power Sensor	Anritsu	MA2411B	GTS541	June 23, 2022	June 22, 2023
17	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 22, 2022	April 21, 2023
18	Splitter	Agilent	11636B	GTS237	June 23, 2022	June 22, 2023
19	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 30, 2021	Nov. 29, 2022
20	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 22, 2022	April 21, 2023
21	Breitband hornantenna	SCHWARZBECK	BBHA 9170	GTS579	Oct. 16, 2022	Oct. 15, 2023
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 16, 2022	Oct. 15, 2023
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 16, 2022	Oct. 15, 2023
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June 23, 2022	June 22, 2023
25	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 22, 2022	April 21, 2023

RF Conducted Test:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	April 22, 2022	April 21, 2023
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 22, 2022	April 21, 2023
3	Spectrum Analyzer	Agilent	E4440A	GTS536	April 22, 2022	April 21, 2023
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	April 22, 2022	April 21, 2023
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	April 22, 2022	April 21, 2023
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	April 22, 2022	April 21, 2023
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	April 22, 2022	April 21, 2023
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	April 22, 2022	April 21, 2023

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	April 25, 2022	April 24, 2023
2	Barometer	KUMAO	SF132	GTS647	July 26, 2022	July 25, 2023

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is integral antenna, reference to the appendix II for details.	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Remark
9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit: (Field strength of the fundamental signal)

Frequency	Limit (dBuV/m @3m)	Remark
2400MHz-2483.5MHz	94.00	Average Value
	114.00	Peak Value

Limit: (Spurious Emissions)

Frequency	Limit (uV/m)	Remark
0.009MHz-0.490MHz	2400/F(kHz) @300m	Quasi-peak Value
0.490MHz-1.705MHz	24000/F(kHz) @30m	Quasi-peak Value
1.705MHz-30.0MHz	30 @30m	Quasi-peak Value
30MHz-88MHz	100 @3m	Quasi-peak Value
88MHz-216MHz	150 @3m	Quasi-peak Value
216MHz-960MHz	200 @3m	Quasi-peak Value
960MHz-1GHz	500 @3m	Quasi-peak Value
Above 1GHz	500 @3m	Average Value
	5000 @3m	Peak Value

Limit: (band edge)

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	DC 3.7V					
Test results:	Pass					

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2420.00	92.83	27.43	2.93	38.88	84.31	114.00	-29.69	Vertical
2420.00	96.44	27.43	2.93	38.88	87.92	114.00	-26.08	Horizontal
2450.00	95.39	27.55	2.96	38.98	86.92	114.00	-27.08	Vertical
2450.00	99.10	27.55	2.96	38.98	90.63	114.00	-23.37	Horizontal
2470.00	91.33	27.64	2.99	39.05	82.91	114.00	-31.09	Vertical
2470.00	94.40	27.64	2.99	39.05	85.98	114.00	-28.02	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2420.00	84.41	27.43	2.93	38.88	75.89	94.00	-18.11	Vertical
2420.00	86.05	27.43	2.93	38.88	77.53	94.00	-16.47	Horizontal
2450.00	86.06	27.55	2.96	38.98	77.59	94.00	-16.41	Vertical
2450.00	88.16	27.55	2.96	38.98	79.69	94.00	-14.31	Horizontal
2470.00	83.18	27.64	2.99	39.05	74.76	94.00	-19.24	Vertical
2470.00	87.38	27.64	2.99	39.05	78.96	94.00	-15.04	Horizontal

Note: For fundamental frequency , RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value

Test plot as follows:

Only show the worst case: 2450MHz, Vertical



PK detector is for PK value



RMS detector is for AV value

7.2.2 Spurious emissions

■ **Below 30MHz**

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ **Below 1GHz**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
114.114	42.71	10.40	1.31	36.84	17.58	43.50	-25.92	QP
149.486	44.16	12.77	1.56	37.07	21.42	43.50	-22.08	QP
187.753	42.81	10.09	1.78	37.27	17.41	43.50	-26.09	QP
269.428	45.97	11.48	2.22	37.40	22.27	46.00	-23.73	QP
511.835	44.27	16.90	3.36	37.51	27.02	46.00	-18.98	QP
785.093	34.79	22.03	4.40	37.62	23.60	46.00	-22.40	QP

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
40.702	43.81	13.48	0.67	35.70	22.26	40.00	-17.74	QP
69.845	48.97	10.53	0.94	36.44	24.00	40.00	-16.00	QP
111.347	47.88	10.58	1.29	36.81	22.94	43.50	-20.56	QP
147.921	43.22	12.48	1.56	37.06	20.20	43.50	-23.30	QP
291.036	45.21	12.62	2.32	37.41	22.74	46.00	-23.26	QP
938.833	34.50	24.22	4.99	37.56	26.15	46.00	-19.85	QP

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
41.132	39.09	13.19	0.67	35.73	17.22	40.00	-22.78	QP
114.114	41.71	10.40	1.31	36.84	16.58	43.50	-26.92	QP
149.486	46.16	12.77	1.56	37.07	23.42	43.50	-20.08	QP
269.428	45.97	11.48	2.22	37.40	22.27	46.00	-23.73	QP
437.120	42.79	15.66	3.03	37.52	23.96	46.00	-22.04	QP
511.835	45.27	16.90	3.36	37.51	28.02	46.00	-17.98	QP

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
40.702	43.81	13.48	0.67	35.70	22.26	40.00	-17.74	QP
69.845	45.97	10.53	0.94	36.44	21.00	40.00	-19.00	QP
111.347	49.88	10.58	1.29	36.81	24.94	43.50	-18.56	QP
147.921	47.22	12.48	1.56	37.06	24.20	43.50	-19.30	QP
291.036	46.21	12.62	2.32	37.41	23.74	46.00	-22.26	QP
443.294	42.98	16.58	3.06	37.52	25.10	46.00	-20.90	QP

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
41.132	41.09	13.19	0.67	35.73	19.22	40.00	-20.78	QP
114.114	40.71	10.40	1.31	36.84	15.58	43.50	-27.92	QP
151.067	45.50	12.80	1.58	37.08	22.80	43.50	-20.70	QP
187.753	43.81	10.09	1.78	37.27	18.41	43.50	-25.09	QP
269.428	47.97	11.48	2.22	37.40	24.27	46.00	-21.73	QP
511.835	45.27	16.90	3.36	37.51	28.02	46.00	-17.98	QP

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
40.702	41.81	13.48	0.67	35.70	20.26	40.00	-19.74	QP
69.845	50.97	10.53	0.94	36.44	26.00	40.00	-14.00	QP
110.182	48.26	10.50	1.28	36.81	23.23	43.50	-20.27	QP
147.921	44.22	12.48	1.56	37.06	21.20	43.50	-22.30	QP
291.036	42.21	12.62	2.32	37.41	19.74	46.00	-26.26	QP
511.835	39.11	17.82	3.36	37.51	22.78	46.00	-23.22	QP

■ **Above 1GHz**

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	37.91	31.15	4.65	38.37	35.34	74.00	-38.66	Peak
7260.000	39.31	36.02	6.55	38.98	42.90	74.00	-31.10	Peak
9680.000	39.93	37.98	8.00	39.70	46.21	74.00	-27.79	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4840.000	37.97	31.15	4.65	38.37	35.40	74.00	-38.60	Peak
7260.000	37.88	36.02	6.55	38.98	41.47	74.00	-32.53	Peak
9680.000	39.18	37.98	8.00	39.70	45.46	74.00	-28.54	Peak

Test channel:	Middle	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4900.000	37.67	31.32	4.71	38.38	35.32	74.00	-38.68	Peak
7350.000	37.67	36.20	6.67	39.01	41.53	74.00	-32.47	Peak
9800.000	39.34	38.10	8.05	39.74	45.75	74.00	-28.25	Peak

Test channel:	Middle	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4900.000	38.29	31.32	4.71	38.38	35.94	74.00	-38.06	Peak
7350.000	38.53	36.20	6.67	39.01	42.39	74.00	-31.61	Peak
9800.000	38.01	38.10	8.05	39.74	44.42	74.00	-29.58	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4940.000	39.85	31.43	4.77	38.39	37.66	74.00	-36.34	Peak
7410.000	37.92	36.32	6.73	39.02	41.95	74.00	-32.05	Peak
9880.000	40.18	38.18	8.07	39.76	46.67	74.00	-27.33	Peak

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4940.000	37.18	31.43	4.77	38.39	34.99	74.00	-39.01	Peak
7410.000	38.40	36.32	6.73	39.02	42.43	74.00	-31.57	Peak
9880.000	38.58	38.18	8.07	39.76	45.07	74.00	-28.93	Peak

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	28.48	27.17	2.81	38.52	19.94	54.00	-34.06	Average
2310.000	45.20	27.17	2.81	38.52	36.66	74.00	-37.34	Peak
2390.000	39.85	27.27	2.91	38.56	31.47	54.00	-22.53	Average
2390.000	53.77	27.27	2.91	38.56	45.39	74.00	-28.61	Peak
2400.000	45.15	27.28	2.91	38.56	36.78	54.00	-17.22	Average
2400.000	58.25	27.28	2.91	38.56	49.88	74.00	-24.12	Peak

Test channel:	Lowest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	32.25	27.17	2.81	38.52	23.71	54.00	-30.29	Average
2310.000	45.32	27.17	2.81	38.52	36.78	74.00	-37.22	Peak
2390.000	33.25	27.27	2.91	38.56	24.87	54.00	-29.13	Average
2390.000	46.16	27.27	2.91	38.56	37.78	74.00	-36.22	Peak
2400.000	35.64	27.28	2.91	38.56	27.27	54.00	-26.73	Average
2400.000	45.79	27.28	2.91	38.56	37.42	74.00	-36.58	Peak

Test channel:	Highest	Polarization:	Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	44.43	27.38	2.99	38.59	36.21	54.00	-17.79	Average
2483.500	60.40	27.38	2.99	38.59	52.18	74.00	-21.82	Peak
2500.000	30.82	27.40	3.01	38.60	22.63	54.00	-31.37	Average
2500.000	45.99	27.40	3.01	38.60	37.80	74.00	-36.20	Peak

Test channel:	Highest	Polarization:	Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	43.27	27.38	2.99	38.59	35.05	54.00	-18.95	Average
2483.500	58.41	27.38	2.99	38.59	50.19	74.00	-23.81	Peak
2500.000	33.72	27.40	3.01	38.60	25.53	54.00	-28.47	Average
2500.000	49.55	27.40	3.01	38.60	41.36	74.00	-32.64	Peak

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*

7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	8.087	Pass
Middle	7.500	Pass
Highest	7.253	Pass

Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

------End------