



CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

In-cab advanced telematics tracker

MODEL NUMBER: FT750-L430-GL

FCC ID: 2AP3PFT750

REPORT NUMBER: 4789043452.2-2

ISSUE DATE: July 5, 2019

Prepared for

**Flex Industrial, Ltd.
Level 3, Alexander House, 35 Cybercity, Ebene, Mauritius**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake
Hi-Tech Development Zone Dongguan, People's Republic of China
Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com**



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/05/2019	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/IC Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2)	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3)	Pass
3	Power Spectral Density	FCC Part 15.247 (e)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d)	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205	Pass
6	Conducted Emission Test For AC Power Port	FCC Part 15.207	N/A
7	Antenna Requirement	FCC Part 15.203	Pass



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. CHANNEL LIST	9
5.4. TEST CHANNEL CONFIGURATION.....	9
5.5. THE WORST CASE CONFIGURATIONS.....	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	10
5.7. DESCRIPTION OF TEST SETUP.....	11
6. MEASURING INSTRUMENT AND SOFTWARE USED	12
7. MEASUREMENT METHODS	13
8. ANTENNA PORT TEST RESULTS	14
8.1. ON TIME AND DUTY CYCLE.....	14
8.2. 6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH	17
8.2.1. 802.11b MODE	18
8.2.2. 802.11g MODE	22
8.2.3. 802.11n HT20 MODE	26
8.3. PEAK CONDUCTED OUTPUT POWER.....	30
8.3.1. 802.11b MODE	31
8.3.2. 802.11g MODE	31
8.3.3. 802.11n HT20 MODE	31
8.4. POWER SPECTRAL DENSITY	32
8.4.1. 802.11b MODE	33
8.4.2. 802.11g MODE	35
8.4.3. 802.11n HT20 MODE	37
8.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS.....	39
8.5.1. 802.11b MODE	40
8.5.1. 802.11g MODE	46
8.5.1. 802.11n HT20 MODE	52
9. RADIATED TEST RESULTS.....	58



9.1.	RESTRICTED BANDEDGE	64
9.1.1.	802.11b MODE	64
9.1.2.	802.11g MODE	72
9.1.3.	802.11n HT20 MODE	80
9.2.	SPURIOUS EMISSIONS (3~18GHz)	88
9.2.1.	802.11b MODE	88
9.2.2.	802.11g MODE	94
9.2.3.	802.11n HT20 MODE	100
9.3.	SPURIOUS EMISSIONS (1~3GHz)	106
9.3.1.	802.11b MODE	106
9.3.2.	802.11g MODE	112
9.3.3.	802.11n HT20 MODE	118
9.4.	SPURIOUS EMISSIONS (18~26GHz)	124
9.4.1.	802.11b MODE	124
9.5.	SPURIOUS EMISSIONS (0.03 ~ 1 GHz)	126
9.5.1.	802.11b MODE	126
9.6.	SPURIOUS EMISSIONS BELOW 30M	128
9.6.1.	802.11b MODE	128
10.	ANTENNA REQUIREMENTS	131



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Flex Industrial, Ltd.
Address: Level 3, Alexander House, 35 Cybercity, Ebene, Mauritius

Manufacturer Information

Company Name: Flex Industrial, Ltd.
Address: Level 3, Alexander House, 35 Cybercity, Ebene, Mauritius

EUT Information

EUT Name: In-cab advanced telematics tracker
Model: FT750-L430-GL
Sample Status: Normal
Sample ID: 2361606
Sample Received Date: June 14, 2019
Date of Tested: June 19 ~ 28, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Jacky Jiang
Engineer Project Associate

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules IC(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test(include Fundamental emission) (9kHz-30MHz)	2.2dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	5.78dB (1GHz-18Gz)
	5.23dB (18GHz-26Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	In-cab advanced telematics tracker
Model	FT750-L430-GL
Radio Technology	IEEE802.11b/g/n HT20
Operation Description	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	IEEE 802.11b: DSSS(CCK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Rate Input	DC 12V/24V
Battery	3.7V 1300mAh
Hardware Version	P2
Software Version	2.0.14

5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Frequency (MHz)	Channel Number	Max PK Conducted Power (dBm)
1	IEEE 802.11b	2412-2462	1-11[11]	21.71
1	IEEE 802.11g	2412-2462	1-11[11]	17.92
1	IEEE 802.11nHT20	2412-2462	1-11[11]	17.49

5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz



5.5. THE WORST CASE CONFIGURATIONS

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		ESP_RF_test_tool_v1.1.0					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	default	default	default	/		
802.11g	1	20	20	20			
802.11n HT20	1	20	20	20			

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2412-2462	PCB Antenna	1.00

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.



5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
1	PC	Dell	Vostro 3902	8KNDDDB2

I/O CABLES

Item	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB to Serial cable	/	N/A	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



**6. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	EMI Test Receiver	R&S	ESR3	101961	Dec.10,2018	Dec.10,2019
☒	Two-Line V-Network	R&S	ENV216	101983	Dec.10,2018	Dec.10,2019
☒	Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Dec.10,2018	Dec.10,2019
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Conducted disturbance		Farad	EZ-EMC		Ver. UL-3A1
Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec.10,2018	Dec.10,2019
☒	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Sep.17, 2018	Sep.17, 2021
☒	Preamplifier	HP	8447D	2944A09099	Dec.10,2018	Dec.10,2019
☒	EMI Measurement Receiver	R&S	ESR26	101377	Dec.10,2018	Dec.10,2019
☒	Horn Antenna	TDK	HRN-0118	130939	Sep.17, 2018	Sep.17, 2021
☒	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11, 2018	Aug.11, 2021
☒	Preamplifier	TDK	PA-02-0118	TRS-305-00066	Dec.10,2018	Dec.10,2019
☒	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec.10,2018	Dec.10,2019
☒	Loop antenna	Schwarzbeck	1519B	00008	Mar.26,2016	Mar.25, 2019
☒	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.10,2018	Dec.10,2019
☒	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.10,2018	Dec.10,2019
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1
Other instruments						



Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9030A	MY55410512	Dec.10,2018	Dec.10,2019
☒	Power Meter	Keysight	N1911A	MY55416024	Dec.10,2018	Dec.10,2019
☒	Power Sensor	Keysight	U2021XA	MY5100022	Dec.10,2018	Dec.10,2019

7. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Peak Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3/8.3.2.3
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2
8	99% Bandwidth	ANSI C63.10-2013	6.9.3



8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

RESULTS

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (KHz)	Final setting For VBW (KHz)
11b	4.185	4.712	0.888	88.82%	0.5158	0.24	1
11g	0.687	0.795	0.864	86.42%	0.6349	1.46	2
11n20	0.651	0.760	0.857	85.66%	0.6702	1.54	2



Note:


Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.







8.2. 6 dB DTS BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100K For 99% Occupied Bandwidth :1% to 5% of the occupied bandwidth
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth : approximately $3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB and 99% relative to the maximum level measured in the fundamental emission.

TEST SETUP






TEST ENVIRONMENT



Temperature	24.4°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V



RESULTS


8.2.1. 802.11b MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	9.048	11.923	≥500	Pass
Middle	9.027	11.967	≥500	Pass
High	8.572	12.054	≥500	Pass

















8.2.2. 802.11g MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	15.79	16.247	≥500	Pass
Middle	15.80	16.255	≥500	Pass
High	15.80	16.255	≥500	Pass

















8.2.3. 802.11n HT20 MODE

Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Limit (kHz)	Result
Low	15.77	17.135	≥500	Pass
Middle	15.66	17.133	≥500	Pass
High	15.75	17.137	≥500	Pass











8.3. PEAK CONDUCTED OUTPUT POWER


LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
Measure the power of each channel.
Peak Detector use for Peak result.
AVG Detector use for AVG result.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V



RESULTS

8.3.1. 802.11b MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	20.37	18.07	30
Middle	21.71	19.46	30
High	21.16	19.02	30

8.3.2. 802.11g MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	17.92	11.24	30
Middle	17.59	10.93	30
High	17.26	10.60	30

8.3.3. 802.11n HT20 MODE

Test Channel	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(dBm)	(dBm)	dBm
Low	17.49	10.84	30
Middle	17.20	10.57	30
High	16.94	10.31	30



8.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT


Temperature	24.4°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V



RESULTS



8.4.1. 802.11b MODE


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-4.800	8	PASS
Middle	-3.313	8	PASS
High	-3.785	8	PASS







8.4.2. 802.11g MODE


Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-13.722	8	PASS
Middle	-13.969	8	PASS
High	-14.330	8	PASS







**8.4.3. 802.11n HT20 MODE**

Test Channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low	-14.459	8	PASS
Middle	-14.686	8	PASS
High	-14.877	8	PASS







8.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.



TEST SETUP




TEST ENVIRONMENT

Temperature	24.4°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

RESULTS


8.5.1. 802.11b MODE

LOW CH BANDEDGE






LOW CH SPURIOUS EMISSIONS REFERENCE




LOW CH SPURIOUS EMISSIONS 30M-10G






LOW CH SPURIOUS EMISSIONS 10G-26G




MID CH SPURIOUS EMISSIONS REFERENCE






MID CH SPURIOUS EMISSIONS 30M-10G




MID CH SPURIOUS EMISSIONS 10G-26G






HIGH CH BANDEDGE




HIGH CH SPURIOUS EMISSIONS REFERENCE






HIGH CH SPURIOUS EMISSIONS 30M-10G




HIGH CH SPURIOUS EMISSIONS 10G-26G






8.5.1. 802.11g MODE

LOW CH BANDEDGE






LOW CH SPURIOUS EMISSIONS REFERENCE




LOW CH SPURIOUS EMISSIONS 30M-10G






LOW CH SPURIOUS EMISSIONS 10G-26G




MID CH SPURIOUS EMISSIONS REFERENCE






MID CH SPURIOUS EMISSIONS 30M-10G




MID CH SPURIOUS EMISSIONS 10G-26G






HIGH CH BANDEDGE




HIGH CH SPURIOUS EMISSIONS REFERENCE






HIGH CH SPURIOUS EMISSIONS 30M-10G




HIGH CH SPURIOUS EMISSIONS 10G-26G






8.5.1. 802.11n HT20 MODE

LOW CH BANDEDGE






LOW CH SPURIOUS EMISSIONS REFERENCE




LOW CH SPURIOUS EMISSIONS 30M-10G






LOW CH SPURIOUS EMISSIONS 10G-26G




MID CH SPURIOUS EMISSIONS REFERENCE






MID CH SPURIOUS EMISSIONS 30M-10G




MID CH SPURIOUS EMISSIONS 10G-26G






HIGH CH BANDEDGE




HIGH CH SPURIOUS EMISSIONS REFERENCE






HIGH CH SPURIOUS EMISSIONS 30M-10G



HIGH CH SPURIOUS EMISSIONS 10G-26G





9. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.



Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

ABOVE 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 8.1.ON TIME AND DUTY CYCLE.



X axis, Y axis, Z axis positions:



Note : For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	23.1°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 12V




9.1. RESTRICTED BANDEDGE

9.1.1. 802.11b MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2387.280	25.85	32.94	58.79	74.00	-15.21	peak
2	2390.000	25.16	32.94	58.10	74.00	-15.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2390.000	12.39	32.94	45.33	54.00	-8.67	AVG
2	2387.280	13.08	32.94	46.02	54.00	-7.98	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2358.360	25.15	32.83	57.98	74.00	-16.02	peak
2	2390.000	24.65	32.94	57.59	74.00	-16.41	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2358.360	10.74	32.83	43.57	54.00	-10.43	AVG
2	2390.000	10.92	32.94	43.86	54.00	-10.14	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	26.22	33.58	59.80	74.00	-14.20	peak
2	2489.990	26.47	33.63	60.10	74.00	-13.90	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	13.32	33.58	46.90	54.00	-7.10	AVG
2	2487.735	14.18	33.61	47.79	54.00	-6.21	AVG
3	2489.990	12.15	33.63	45.78	54.00	-8.22	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	24.75	33.58	58.33	74.00	-15.67	peak
2	2486.910	24.76	33.61	58.37	74.00	-15.63	peak
3	2498.295	25.80	33.69	59.49	74.00	-14.51	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	11.44	33.58	45.02	54.00	-8.98	AVG
2	2486.910	11.69	33.61	45.30	54.00	-8.70	AVG
3	2498.295	11.15	33.69	44.84	54.00	-9.16	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.1.2. 802.11g MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2389.235	26.74	32.94	59.68	74.00	-14.32	peak
2	2390.000	24.51	32.94	57.45	74.00	-16.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2389.235	12.33	32.94	45.27	54.00	-8.73	AVG
2	2390.000	12.70	32.94	45.64	54.00	-8.36	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2390.000	36.92	32.94	69.86	74.00	-4.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2390.000	16.41	32.94	49.35	54.00	-4.65	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/T_{on}$ where: t_{on} is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.




RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	30.22	33.58	63.80	74.00	-10.20	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	15.52	33.58	49.10	54.00	-4.90	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/T_{on}$ where: t_{on} is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	30.85	33.58	64.43	74.00	-9.57	peak
2	2483.550	31.85	33.58	65.43	74.00	-8.57	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	16.34	33.58	49.92	54.00	-4.08	AVG
2	2483.550	16.11	33.58	49.69	54.00	-4.31	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.1.3. 802.11n HT20 MODE


RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2389.580	27.98	32.94	60.92	74.00	-13.08	peak
2	2390.000	27.44	32.94	60.38	74.00	-13.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**AVG**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2389.580	12.59	32.94	45.53	54.00	-8.47	AVG
2	2390.000	12.83	32.94	45.77	54.00	-8.23	AVG

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2390.000	29.92	32.94	62.86	74.00	-11.14	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2390.000	14.09	32.94	47.03	54.00	-6.97	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	31.03	33.58	64.61	74.00	-9.39	peak
2	2483.850	31.87	33.58	65.45	74.00	-8.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	16.23	33.58	49.81	54.00	-4.19	AVG
2	2483.850	15.93	33.58	49.51	54.00	-4.49	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

PEAK




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	31.05	33.58	64.63	74.00	-9.37	peak
2	2486.300	31.77	33.61	65.38	74.00	-8.62	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2483.500	16.56	33.58	50.14	54.00	-3.86	AVG
2	2486.300	14.37	33.61	47.98	54.00	-6.02	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. AVG: $VBW=1/Ton$ where: ton is transmit duration.
4. For transmit duration, please refer to clause 8.1.
5. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



9.2. SPURIOUS EMISSIONS (3~18GHz)

9.2.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4815.000	52.58	-0.23	52.35	74.00	-21.65	peak
2	8505.000	40.74	8.55	49.29	74.00	-24.71	peak
3	11535.000	36.42	14.10	50.52	74.00	-23.48	peak
4	14415.000	35.18	16.41	51.59	74.00	-22.41	peak
5	16440.000	32.50	18.69	51.19	74.00	-22.81	peak
6	17820.000	28.91	23.21	52.12	74.00	-21.88	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4245.000	50.47	-2.02	48.45	74.00	-25.55	peak
2	6375.000	43.78	4.90	48.68	74.00	-25.32	peak
3	8505.000	41.65	8.55	50.20	74.00	-23.80	peak
4	12255.000	36.39	14.32	50.71	74.00	-23.29	peak
5	15180.000	35.45	15.54	50.99	74.00	-23.01	peak
6	16890.000	32.30	19.93	52.23	74.00	-21.77	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4875.000	49.63	-0.12	49.51	74.00	-24.49	peak
2	7290.000	40.67	7.11	47.78	74.00	-26.22	peak
3	9375.000	37.78	10.14	47.92	74.00	-26.08	peak
4	12285.000	36.53	14.37	50.90	74.00	-23.10	peak
5	16860.000	31.28	19.92	51.20	74.00	-22.80	peak
6	17700.000	29.31	22.24	51.55	74.00	-22.45	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4875.000	46.75	-0.12	46.63	74.00	-27.37	peak
2	6015.000	44.26	3.78	48.04	74.00	-25.96	peak
3	8535.000	43.83	8.49	52.32	74.00	-21.68	peak
4	12270.000	35.75	14.34	50.09	74.00	-23.91	peak
5	13620.000	34.82	16.04	50.86	74.00	-23.14	peak
6	16560.000	32.04	19.18	51.22	74.00	-22.78	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4920.000	47.75	0.02	47.77	74.00	-26.23	peak
2	8265.000	39.24	8.91	48.15	74.00	-25.85	peak
3	11370.000	36.30	13.22	49.52	74.00	-24.48	peak
4	12270.000	35.43	14.34	49.77	74.00	-24.23	peak
5	14370.000	35.23	16.39	51.62	74.00	-22.38	peak
6	17805.000	28.85	23.22	52.07	74.00	-21.93	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4245.000	47.65	-2.02	45.63	74.00	-28.37	peak
2	6360.000	45.12	4.84	49.96	74.00	-24.04	peak
3	8505.000	42.24	8.55	50.79	74.00	-23.21	peak
4	12270.000	35.91	14.34	50.25	74.00	-23.75	peak
5	14430.000	34.21	16.39	50.60	74.00	-23.40	peak
6	17775.000	28.59	22.97	51.56	74.00	-22.44	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.2.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4260.000	49.69	-2.09	47.60	74.00	-26.40	peak
2	4815.000	48.84	-0.23	48.61	74.00	-25.39	peak
3	8220.000	38.01	9.40	47.41	74.00	-26.59	peak
4	11415.000	36.41	13.46	49.87	74.00	-24.13	peak
5	14445.000	34.31	16.37	50.68	74.00	-23.32	peak
6	16725.000	31.52	19.85	51.37	74.00	-22.63	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4245.000	49.53	-2.02	47.51	74.00	-26.49	peak
2	6375.000	43.85	4.90	48.75	74.00	-25.25	peak
3	8520.000	40.05	8.53	48.58	74.00	-25.42	peak
4	12270.000	35.51	14.34	49.85	74.00	-24.15	peak
5	14340.000	34.21	16.36	50.57	74.00	-23.43	peak
6	17805.000	28.66	23.22	51.88	74.00	-22.12	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4245.000	47.18	-2.02	45.16	74.00	-28.84	peak
2	4860.000	46.38	-0.15	46.23	74.00	-27.77	peak
3	8520.000	40.61	8.53	49.14	74.00	-24.86	peak
4	11430.000	36.48	13.57	50.05	74.00	-23.95	peak
5	14355.000	34.23	16.38	50.61	74.00	-23.39	peak
6	16935.000	30.96	20.07	51.03	74.00	-22.97	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4260.000	49.79	-2.09	47.70	74.00	-26.30	peak
2	6375.000	45.22	4.90	50.12	74.00	-23.88	peak
3	8505.000	44.12	8.55	52.67	74.00	-21.33	peak
4	12285.000	35.85	14.37	50.22	74.00	-23.78	peak
5	14415.000	34.25	16.41	50.66	74.00	-23.34	peak
6	16890.000	32.16	19.93	52.09	74.00	-21.91	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4920.000	44.46	0.02	44.48	74.00	-29.52	peak
2	6390.000	43.34	4.97	48.31	74.00	-25.69	peak
3	9420.000	37.91	10.34	48.25	74.00	-25.75	peak
4	11310.000	36.58	12.94	49.52	74.00	-24.48	peak
5	14010.000	34.46	16.34	50.80	74.00	-23.20	peak
6	16725.000	31.19	19.85	51.04	74.00	-22.96	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4260.000	50.71	-2.09	48.62	74.00	-25.38	peak
2	6375.000	44.90	4.90	49.80	74.00	-24.20	peak
3	8490.000	41.21	8.59	49.80	74.00	-24.20	peak
4	12270.000	36.56	14.34	50.90	74.00	-23.10	peak
5	14430.000	34.45	16.39	50.84	74.00	-23.16	peak
6	17700.000	29.41	22.24	51.65	74.00	-22.35	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.2.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4815.000	47.88	-0.23	47.65	74.00	-26.35	peak
2	8565.000	39.03	8.41	47.44	74.00	-26.56	peak
3	10290.000	36.82	11.51	48.33	74.00	-25.67	peak
4	12285.000	35.46	14.37	49.83	74.00	-24.17	peak
5	15165.000	35.21	15.54	50.75	74.00	-23.25	peak
6	16890.000	31.30	19.93	51.23	74.00	-22.77	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	5325.000	44.16	1.57	45.73	74.00	-28.27	peak
2	6015.000	44.60	3.78	48.38	74.00	-25.62	peak
3	8505.000	43.06	8.55	51.61	74.00	-22.39	peak
4	11415.000	36.31	13.46	49.77	74.00	-24.23	peak
5	14355.000	34.55	16.38	50.93	74.00	-23.07	peak
6	17700.000	30.06	22.24	52.30	74.00	-21.70	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4860.000	45.29	-0.15	45.14	74.00	-28.86	peak
2	7875.000	38.98	8.55	47.53	74.00	-26.47	peak
3	9420.000	38.14	10.34	48.48	74.00	-25.52	peak
4	12300.000	35.70	14.39	50.09	74.00	-23.91	peak
5	14445.000	34.99	16.37	51.36	74.00	-22.64	peak
6	17760.000	28.85	22.83	51.68	74.00	-22.32	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4260.000	50.43	-2.09	48.34	74.00	-25.66	peak
2	6015.000	44.47	3.78	48.25	74.00	-25.75	peak
3	8520.000	44.18	8.53	52.71	74.00	-21.29	peak
4	12270.000	36.17	14.34	50.51	74.00	-23.49	peak
5	14400.000	35.02	16.43	51.45	74.00	-22.55	peak
6	17715.000	29.56	22.39	51.95	74.00	-22.05	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4260.000	45.12	-2.09	43.03	74.00	-30.97	peak
2	4920.000	43.46	0.02	43.48	74.00	-30.52	peak
3	7800.000	39.21	8.87	48.08	74.00	-25.92	peak
4	11430.000	37.09	13.57	50.66	74.00	-23.34	peak
5	14400.000	34.87	16.43	51.30	74.00	-22.70	peak
6	16755.000	31.50	19.87	51.37	74.00	-22.63	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	4245.000	49.42	-2.02	47.40	74.00	-26.60	peak
2	6015.000	44.96	3.78	48.74	74.00	-25.26	peak
3	8505.000	47.43	8.55	55.98	74.00	-18.02	peak
4	8505.000	24.08	8.55	32.63	54.00	-21.37	AVG
5	11460.000	35.82	13.79	49.61	74.00	-24.39	peak
6	13965.000	34.66	16.29	50.95	74.00	-23.05	peak
7	17760.000	29.24	22.83	52.07	74.00	-21.93	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.3. SPURIOUS EMISSIONS (1~3GHz)

9.3.1. 802.11b MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1062.000	52.17	-13.79	38.38	74.00	-35.62	peak
2	1596.000	47.87	-11.77	36.10	74.00	-37.90	peak
3	2126.000	55.00	-9.15	45.85	74.00	-28.15	peak
4	2352.000	51.64	-7.99	43.65	74.00	-30.35	peak
5	2560.000	50.53	-7.26	43.27	74.00	-30.73	peak
6	2744.000	50.92	-6.35	44.57	74.00	-29.43	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1064.000	49.07	-12.78	36.29	74.00	-37.71	peak
2	1142.000	46.33	-12.52	33.81	74.00	-40.19	peak
3	1784.000	43.98	-9.63	34.35	74.00	-39.65	peak
4	2352.000	50.53	-7.29	43.24	74.00	-30.76	peak
5	2576.000	49.74	-6.69	43.05	74.00	-30.95	peak
6	2786.000	45.84	-5.51	40.33	74.00	-33.67	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1062.000	47.61	-12.80	34.81	74.00	-39.19	peak
2	1730.000	43.84	-10.32	33.52	74.00	-40.48	peak
3	1932.000	44.02	-9.45	34.57	74.00	-39.43	peak
4	2350.000	51.05	-7.30	43.75	74.00	-30.25	peak
5	2546.000	51.41	-6.54	44.87	74.00	-29.13	peak
6	2686.000	51.26	-7.33	43.93	74.00	-30.07	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1158.000	45.66	-12.52	33.14	74.00	-40.86	peak
2	1608.000	44.14	-10.62	33.52	74.00	-40.48	peak
3	2070.000	44.41	-8.75	35.66	74.00	-38.34	peak
4	2374.000	45.68	-7.21	38.47	74.00	-35.53	peak
5	2434.000	53.19	-6.84	46.35	74.00	-27.65	peak
6	2784.000	44.16	-5.56	38.60	74.00	-35.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1062.000	47.43	-12.80	34.63	74.00	-39.37	peak
2	1804.000	44.28	-9.41	34.87	74.00	-39.13	peak
3	2286.000	45.59	-7.63	37.96	74.00	-36.04	peak
4	2342.000	50.28	-7.33	42.95	74.00	-31.05	peak
5	2562.000	52.22	-6.63	45.59	74.00	-28.41	peak
6	2674.000	51.71	-7.26	44.45	74.00	-29.55	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1134.000	46.41	-12.54	33.87	74.00	-40.13	peak
2	1430.000	45.66	-11.83	33.83	74.00	-40.17	peak
3	1730.000	44.31	-10.32	33.99	74.00	-40.01	peak
4	2128.000	43.97	-8.36	35.61	74.00	-38.39	peak
5	2466.000	55.81	-6.60	49.21	74.00	-24.79	peak
6	2856.000	43.77	-5.17	38.60	74.00	-35.40	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.3.2. 802.11g MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1062.000	47.22	-12.80	34.42	74.00	-39.58	peak
2	1630.000	44.28	-10.64	33.64	74.00	-40.36	peak
3	1902.000	44.60	-9.31	35.29	74.00	-38.71	peak
4	2350.000	51.64	-7.30	44.34	74.00	-29.66	peak
5	2572.000	50.39	-6.67	43.72	74.00	-30.28	peak
6	2670.000	50.97	-7.24	43.73	74.00	-30.27	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1032.000	46.78	-12.94	33.84	74.00	-40.16	peak
2	1632.000	44.34	-10.64	33.70	74.00	-40.30	peak
3	2154.000	43.27	-8.39	34.88	74.00	-39.12	peak
4	2366.000	45.12	-7.23	37.89	74.00	-36.11	peak
5	2674.000	46.18	-7.26	38.92	74.00	-35.08	peak
6	2862.000	43.87	-5.17	38.70	74.00	-35.30	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1064.000	46.90	-12.78	34.12	74.00	-39.88	peak
2	1612.000	44.32	-10.62	33.70	74.00	-40.30	peak
3	2066.000	44.25	-8.81	35.44	74.00	-38.56	peak
4	2348.000	49.63	-7.31	42.32	74.00	-31.68	peak
5	2608.000	50.98	-6.85	44.13	74.00	-29.87	peak
6	2678.000	52.30	-7.28	45.02	74.00	-28.98	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1134.000	46.52	-12.54	33.98	74.00	-40.02	peak
2	1542.000	45.96	-11.18	34.78	74.00	-39.22	peak
3	1994.000	45.10	-9.75	35.35	74.00	-38.65	peak
4	2318.000	43.66	-7.43	36.23	74.00	-37.77	peak
5	2434.000	47.00	-6.84	40.16	74.00	-33.84	peak
6	2920.000	43.81	-5.04	38.77	74.00	-35.23	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1066.000	47.58	-12.78	34.80	74.00	-39.20	peak
2	1542.000	44.22	-11.18	33.04	74.00	-40.96	peak
3	2060.000	43.96	-8.90	35.06	74.00	-38.94	peak
4	2348.000	49.55	-7.31	42.24	74.00	-31.76	peak
5	2598.000	51.75	-6.79	44.96	74.00	-29.04	peak
6	2746.000	50.33	-6.40	43.93	74.00	-30.07	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1150.000	46.78	-12.52	34.26	74.00	-39.74	peak
2	1518.000	45.79	-11.42	34.37	74.00	-39.63	peak
3	2108.000	42.97	-8.33	34.64	74.00	-39.36	peak
4	2466.000	51.32	-6.60	44.72	74.00	-29.28	peak
5	2670.000	45.15	-7.24	37.91	74.00	-36.09	peak
6	2902.000	43.43	-5.13	38.30	74.00	-35.70	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.3.3. 802.11n HT20 MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1064.000	48.01	-12.78	35.23	74.00	-38.77	peak
2	1628.000	44.39	-10.63	33.76	74.00	-40.24	peak
3	1972.000	44.24	-9.65	34.59	74.00	-39.41	peak
4	2350.000	51.25	-7.30	43.95	74.00	-30.05	peak
5	2542.000	50.39	-6.53	43.86	74.00	-30.14	peak
6	2690.000	49.56	-7.37	42.19	74.00	-31.81	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1134.000	46.81	-12.54	34.27	74.00	-39.73	peak
2	1520.000	44.94	-11.40	33.54	74.00	-40.46	peak
3	1976.000	44.94	-9.67	35.27	74.00	-38.73	peak
4	2414.000	48.94	-7.00	41.94	74.00	-32.06	peak
5	2584.000	45.48	-6.73	38.75	74.00	-35.25	peak
6	2884.000	45.09	-5.15	39.94	74.00	-34.06	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1064.000	48.68	-12.78	35.90	74.00	-38.10	peak
2	1448.000	44.32	-11.76	32.56	74.00	-41.44	peak
3	1974.000	44.81	-9.66	35.15	74.00	-38.85	peak
4	2350.000	51.55	-7.30	44.25	74.00	-29.75	peak
5	2548.000	51.17	-6.56	44.61	74.00	-29.39	peak
6	2678.000	53.39	-7.28	46.11	74.00	-27.89	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1100.000	46.85	-12.60	34.25	74.00	-39.75	peak
2	1626.000	44.68	-10.63	34.05	74.00	-39.95	peak
3	1838.000	43.40	-9.37	34.03	74.00	-39.97	peak
4	2152.000	44.13	-8.39	35.74	74.00	-38.26	peak
5	2434.000	53.23	-6.84	46.39	74.00	-27.61	peak
6	2984.000	43.68	-4.68	39.00	74.00	-35.00	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1064.000	47.93	-12.78	35.15	74.00	-38.85	peak
2	1518.000	45.25	-11.42	33.83	74.00	-40.17	peak
3	2140.000	43.57	-8.37	35.20	74.00	-38.80	peak
4	2344.000	49.13	-7.32	41.81	74.00	-32.19	peak
5	2556.000	51.69	-6.59	45.10	74.00	-28.90	peak
6	2720.000	50.77	-6.97	43.80	74.00	-30.20	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	1142.000	46.18	-12.52	33.66	74.00	-40.34	peak
2	1660.000	44.49	-10.67	33.82	74.00	-40.18	peak
3	2128.000	44.48	-8.36	36.12	74.00	-37.88	peak
4	2368.000	44.75	-7.23	37.52	74.00	-36.48	peak
5	2466.000	48.48	-6.60	41.88	74.00	-32.12	peak
6	2924.000	43.30	-5.01	38.29	74.00	-35.71	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for BRF losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.4. SPURIOUS EMISSIONS (18~26GHz)

9.4.1. 802.11b MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18952.000	51.92	-4.89	47.03	74.00	-26.97	peak
2	21152.000	52.70	-5.42	47.28	74.00	-26.72	peak
3	21680.000	52.74	-5.76	46.98	74.00	-27.02	peak
4	22600.000	52.54	-5.77	46.77	74.00	-27.23	peak
5	24328.000	49.91	-3.28	46.63	74.00	-27.37	peak
6	25216.000	47.55	-1.16	46.39	74.00	-27.61	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Proper operation of the transmitter prior to adding the filter to the measurement chain.



SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18784.000	50.55	-4.84	45.71	74.00	-28.29	peak
2	19720.000	50.50	-4.39	46.11	74.00	-27.89	peak
3	20536.000	50.34	-4.98	45.36	74.00	-28.64	peak
4	21848.000	51.76	-5.95	45.81	74.00	-28.19	peak
5	24592.000	49.32	-2.36	46.96	74.00	-27.04	peak
6	25064.000	47.68	-1.11	46.57	74.00	-27.43	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Proper operation of the transmitter prior to adding the filter to the measurement chain.



9.5. SPURIOUS EMISSIONS (0.03 ~ 1 GHz)

9.5.1. 802.11b MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	101.7800	28.32	-21.75	6.57	43.50	-36.93	QP
2	250.1900	32.35	-16.12	16.23	46.00	-29.77	QP
3	320.0300	38.80	-13.63	25.17	46.00	-20.83	QP
4	480.0800	36.39	-10.84	25.55	46.00	-20.45	QP
5	692.5100	25.66	-6.79	18.87	46.00	-27.13	QP
6	904.9400	27.47	-4.05	23.42	46.00	-22.58	QP

Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	27.95	-20.27	7.68	40.00	-32.32	QP
2	250.1900	32.16	-16.12	16.04	46.00	-29.96	QP
3	480.0800	29.21	-10.84	18.37	46.00	-27.63	QP
4	640.1300	25.90	-7.68	18.22	46.00	-27.78	QP
5	736.1599	27.48	-6.14	21.34	46.00	-24.66	QP
6	953.4400	29.08	-3.37	25.71	46.00	-20.29	QP

- Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All test modes have been tested, only the worst data record in the report.



9.6. SPURIOUS EMISSIONS BELOW 30M

9.6.1. 802.11b MODE

SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0091	74.29	-101.33	-27.04	48.28	-75.32	peak
2	0.0193	66.15	-101.35	-35.20	41.89	-77.09	peak
3	0.0250	63.29	-101.37	-38.08	39.64	-77.72	peak
4	0.0361	58.72	-101.42	-42.70	36.45	-79.15	peak
5	0.0646	57.03	-101.54	-44.51	31.40	-75.91	peak
6	0.1226	52.10	-101.73	-49.63	25.83	-75.46	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.




150kHz ~ 490kHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1547	73.31	-101.65	-28.34	23.81	-52.15	peak
2	0.1756	70.84	-101.68	-30.84	22.72	-53.56	peak
3	0.2051	64.31	-101.73	-37.42	21.36	-58.78	peak
4	0.2530	61.59	-101.80	-40.21	19.54	-59.75	peak
5	0.3234	59.48	-101.88	-42.40	17.41	-59.81	peak
6	0.3462	58.24	-101.90	-43.66	16.82	-60.48	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

490kHz ~ 30MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5080	62.35	-62.07	0.28	33.49	-33.21	peak
2	1.6026	53.69	-62.00	-8.31	23.51	-31.82	peak
3	2.0853	52.57	-61.80	-9.23	29.54	-38.77	peak
4	7.6314	50.51	-61.12	-10.61	29.54	-40.15	peak
5	10.5823	50.82	-60.82	-10.00	29.54	-39.54	peak
6	17.1631	50.16	-60.93	-10.77	29.54	-40.31	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT