FCC TEST REPORT

FCC PART 15 SUBPART C 15.249

Test report

On Behalf of

SHENZHEN YINKO TECHNOLOGY CO.,LTD

For

True Wireless Stereo Earbuds

Model No.: BTW001

FCC ID: 2AP4B-BTW001

Prepared for : **SHENZHEN YINKO TECHNOLOGY CO.,LTD**
Floor 3, Building 3, Jinfo Industrial Park, Hezhou Village Hangcheng Street, Bao'an District, Shenzhen, China

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

Date of Test: **Nov.23, 2018 ~ Nov. 29, 2018**
Date of Report: **Dec. 03, 2018**
Report Number: **HK1811221687E**

TEST RESULT CERTIFICATION

Applicant's name	SHENZHEN YINKO TECHNOLOGY CO.,LTD
Address	Floor 3, Building 3, Jinfo Industrial Park, Hezhou Village Hangcheng Street, Bao'an District, Shenzhen, China
Manufacture's Name	SHENZHEN YINKO TECHNOLOGY CO.,LTD
Address	Floor 3, Building 3, Jinfo Industrial Park, Hezhou Village Hangcheng Street, Bao'an District, Shenzhen, China
Factory's Name	SHENZHEN YINKO TECHNOLOGY CO.,LTD
Address	Floor 3, Building 3, Jinfo Industrial Park, Hezhou Village Hangcheng Street, Bao'an District, Shenzhen, China
Product description	
Trade Mark	YINKO, Firacore, blumelody, JUCKBO
Product name	True Wireless Stereo Earbuds
Model and/or type reference	BTW001
Series Model	Firacore F10, Firacore F12, Firacore F18, G350, G450, V7
Difference Description	All the same except for the model name and appearance shape (The first brand name is applicable for the model BTW001,V7, and the second brand name is applicable for Firacore F10, Firacore F12, Firacore F18, and the third brand name is applicable for the model G350, G450, and the fourth brand name is applicable for the model V7)
Standards	FCC Rules and Regulations Part 15 Subpart C Section 15.249 ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :	
Date (s) of performance of tests :	Nov.23, 2018 ~ Nov. 29, 2018
Date of Issue :	Dec. 03, 2018
Test Result :	**Pass**

Testing Engineer : Gary Qian

(Gary Qian)

Technical Manager : Eden Hu

(Eden Hu)

Authorized Signatory : Jason Zhou

(Jason Zhou)

Table of Contents **Page**

1 . TEST SUMMARY 4

2 . GENERAL INFORMATION 5

2.1 GENERAL DESCRIPTION OF EUT 5

2.2 OPERATION OF EUT DURING TESTING 6

2.3 DESCRIPTION OF TEST SETUP 7

2.4 MEASUREMENT INSTRUMENTS LIST 8

3. RADIATED EMISSION 9

3.1. MEASUREMENT PROCEDURE 9

3.2. TEST SETUP 11

3.3. TEST RESULT 12

4. BAND EDGE EMISSION 20

4.1. MEASUREMENT PROCEDURE 20

4.2 TEST SETUP 20

4.3 RADIATED TEST RESULT 21

5. BANDWIDTH 25

5.1. MEASUREMENT PROCEDURE 25

5.2. TEST SETUP 25

5.3. TEST RESULT 26

6. FCC LINE CONDUCTED EMISSION TEST 32

6.1. LIMITS OF LINE CONDUCTED EMISSION TEST 32

6.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 32

6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 33

6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 33

6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 33

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 34

APPENDIX B: PHOTOGRAPHS OF EUT 36

1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249&15.209	Radiated Emission	Compliant
§15.249&15.209	Band Edges Emission	Compliant
§15.215	20dB bandwidth	Compliant
§15.207	Conducted Emission	N/A

Note: N/A means it’s not applicable to this item.

1.2 TEST FACILITY

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

Designation Number: : CN1229

Test Firm Registration Number : 616276

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	=	4.06dB, k=2

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Operation Frequency	2.402 GHz to 2.480GHz
Maximum field strength	99.01dBuV/m(Peak)@3m
Bluetooth Version	V5.0
Modulation	GFSK, π /4-DQPSK, 8DPSK for BR/EDR
Number of channels	79 for BR/EDR
Antenna Gain	2dBi
Antenna Designation	Ceramic Antenna
Hardware Version	V6.0
Software Version	V18
Power Supply	DC 3.7V by battery
Note: 1. The EUT doesn't support BLE. 2. The BT function of EUT doesn't work when charging 3. The EUT comprises left and right channel headsets, both are the same and have been tested. Only the test data of left headset recorded in this report.	

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

2.2 OPERATION OF EUT DURING TESTING

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK

Note:
1. Only the data of the worst case recorded in the test report.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

2.3 DESCRIPTION OF TEST SETUP

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	True Wireless Stereo Earbuds	YINKO	BTW001	EUT
2	Battery	HS	601012	Accessory
3	PC	APPLE	A1465	A.E
4	Control box	AIROHA	N/A	A.E
5	IPOD	APPLE	A1367	A.E
6	USB Cable	N/A	1m unshielded	A.E

2.4 MEASUREMENT INSTRUMENTS LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Item	Equipment	Manufacturer	Model No.	Lab Equipment No.	Last Cal.	Cal. Interval
1.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2017	1 Year
2.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 28, 2017	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 28, 2017	1 Year
4.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 28, 2017	1 Year
5.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2017	1 Year
6.	Horn Antenna	Schewarzbeck	9120D	HKE-013	Dec. 28, 2017	1 Year
7.	Broad-band Horn Antenna	A-INFOMW	LB-180400-KF	HKE-031	Dec. 28, 2017	1 Year
8.	Pre-amplifier	EMCI	EMC051845SE	HKE-015	Dec. 28, 2017	1 Year
9.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 28, 2017	1 Year
10.	Filter (2.4-2.483GHz)	Micro-tronics	087	--	N/A	N/A
11.	Radiation Cable 1	MXT	HK1	R05	N/A	N/A
12.	Radiation Cable 2	MXT	HK1	R06	N/A	N/A

3. RADIATED EMISSION

3.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1.5MHz/5MHz for Peak, 1.5MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP

Test limit for Standard FCC15.249

Fundamental Frequency	**Field Strength of Fundamental (millivolts/meter)**	**Field Strength of Harmonics (microvolts/meter)**
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Test limit for Standard FCC 15.209

Frequency (MHz)	**Distance Meters**	**Field Strengths Limit**	
		μV/m	**dB(μV)/m**
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark: (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.2. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



3.3. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION 30MHz- 1GHZ FOR BR/EDR

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 1	Polarization :	Horizontal



Suspected Data List								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	41.6400	20.60	14.89	40.00	19.40	150	290	Horizontal
2	67.8300	18.92	12.59	40.00	21.08	200	10	Horizontal
3	164.830	21.75	14.45	43.50	21.75	200	80	Horizontal
4	278.320	22.23	16.14	46.00	23.77	150	110	Horizontal
5	418.970	25.54	20.22	46.00	20.46	200	60	Horizontal
6	905.910	35.92	30.16	46.00	10.08	100	170	Horizontal

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 1	Polarization :	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	40.6700	20.15	14.91	40.00	19.85	200	270	Vertical
2	64.9200	19.27	13.09	40.00	20.73	150	350	Vertical
3	138.640	20.49	14.78	43.50	23.01	200	160	Vertical
4	280.260	21.50	16.29	46.00	24.50	100	330	Vertical
5	451.950	26.96	21.03	46.00	19.04	150	350	Vertical
6	808.910	35.05	28.62	46.00	10.95	150	330	Vertical

RESULT: PASS

Note:

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

.

FIELD STRENGTH OF FUNDAMENTAL FOR BR/EDR

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	GFSK	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	84.97	13.46	98.43	114.00	-15.57	peak
2402.021	77.01	13.46	90.47	94.00	-3.53	AVG
2441.021	83.88	13.88	97.76	114.00	-16.24	peak
2441.021	75.93	13.88	89.81	94.00	-4.19	AVG
2480.021	84.90	14.11	99.01	114.00	-14.99	peak
2480.021	76.91	14.11	91.02	94.00	-2.98	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	GFSK	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	84.52	13.46	97.98	114.00	-16.02	peak
2402.021	76.53	13.46	89.99	94.00	-4.01	AVG
2441.021	83.39	13.88	97.27	114.00	-16.73	peak
2441.021	75.41	13.88	89.29	94.00	-4.71	AVG
2480.021	84.46	14.11	98.57	114.00	-15.43	peak
2480.021	76.43	14.11	90.54	94.00	-3.46	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	π /4-DQPSK	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	84.02	13.46	97.48	114.00	-16.52	peak
2402.021	75.99	13.46	89.45	94.00	-4.55	AVG
2441.021	82.93	13.88	96.81	114.00	-17.19	peak
2441.021	74.89	13.88	88.77	94.00	-5.23	AVG
2480.021	83.95	14.11	98.06	114.00	-15.94	peak
2480.021	75.98	14.11	90.09	94.00	-3.91	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	π /4-DQPSK	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	83.49	13.46	96.95	114.00	-17.05	peak
2402.021	75.53	13.46	88.99	94.00	-5.01	AVG
2441.021	82.39	13.88	96.27	114.00	-17.73	peak
2441.021	74.40	13.88	88.28	94.00	-5.72	AVG
2480.021	83.46	14.11	97.57	114.00	-16.43	peak
2480.021	75.43	14.11	89.54	94.00	-4.46	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	8DPSK	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	83.05	13.46	96.51	114.00	-17.49	peak
2402.021	75.01	13.46	88.47	94.00	-5.53	AVG
2441.021	81.95	13.88	95.83	114.00	-18.17	peak
2441.021	73.95	13.88	87.83	94.00	-6.17	AVG
2480.021	82.91	14.11	97.02	114.00	-16.98	peak
2480.021	74.90	14.11	89.01	94.00	-4.99	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Modulation ：	8DPSK	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
2402.021	82.47	13.46	95.93	114.00	-18.07	peak
2402.021	74.50	13.46	87.96	94.00	-6.04	AVG
2441.021	81.44	13.88	95.32	114.00	-18.68	peak
2441.021	73.42	13.88	87.30	94.00	-6.70	AVG
2480.021	82.46	14.11	96.57	114.00	-17.43	peak
2480.021	74.49	14.11	88.60	94.00	-5.40	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

RADIATED EMISSION ABOVE 1GHZ FOR BR/EDR

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 1	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.026	43.37	7.12	50.49	74	-23.51	peak
4804.026	42.17	7.12	49.29	54	-4.71	AVG
7206.039	38.12	9.84	47.96	74	-26.04	peak
7206.039	37.37	9.84	47.21	54	-6.79	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 1	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.026	43.26	7.12	50.38	74	-23.62	peak
4804.026	41.98	7.12	49.1	54	-4.9	AVG
7206.039	39.14	9.84	48.98	74	-25.02	peak
7206.039	36.41	9.84	46.25	54	-7.75	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 2	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.032	43.09	7.12	50.21	74	-23.79	peak
4882.032	40.96	7.12	48.08	54	-5.92	AVG
7323.048	37.14	9.84	46.98	74	-27.02	peak
7323.048	36.38	9.84	46.22	54	-7.78	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 2	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4882.032	42.73	7.12	49.85	74	-24.15	peak
4882.032	39.65	7.12	46.77	54	-7.23	AVG
7323.048	37.85	9.84	47.69	74	-26.31	peak
7323.048	34.83	9.84	44.67	54	-9.33	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 3	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.042	42.19	7.12	49.31	74	-24.69	peak
4960.042	39.43	7.12	46.55	54	-7.45	AVG
7440.063	37.26	9.84	47.10	74	-26.90	peak
7440.063	36.38	9.84	46.22	54	-7.78	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT：	True Wireless Stereo Earbuds	Model Name. ：	BTW001
Temperature：	20 ℃	Relative Humidtity：	48%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V
Test Mode ：	Mode 3	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.042	42.46	7.12	49.58	74	-24.42	peak
4960.042	39.53	7.12	46.65	54	-7.35	AVG
7440.063	37.28	9.84	47.12	74	-26.88	peak
7440.063	35.42	9.84	45.26	54	-8.74	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Note: Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.
The GFSK modulation was the worst case and only the data of worst recorded in this report.

4. BAND EDGE EMISSION

4.1. MEASUREMENT PROCEDURE

1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

Start frequency(MHz)	Stop frequency(MHz)
2200	2405
2478	2500

4.2 TEST SETUP

RADIATED EMISSION TEST SETUP



4.3 RADIATED TEST RESULT

FOR BR/EDR

(Worst modulation: GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2366.733	23.31	13.46	36.77	74.00	-37.23	peak			
2		2390.000	24.17	13.46	37.63	74.00	-36.37	peak			
3		2400.000	34.44	13.46	47.90	74.00	-26.10	peak			
4	X	2402.000	84.85	13.46	98.31	74.00	24.31	peak			
5	*	2402.000	76.86	13.46	90.32	54.00	36.32	AVG	100	147	

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2365.025	22.44	13.46	35.90	74.00	-38.10	peak			
2		2390.000	25.67	13.46	39.13	74.00	-34.87	peak			
3		2400.000	36.44	13.46	49.90	74.00	-24.10	peak			
4	X	2402.000	84.30	13.46	97.76	74.00	23.76	peak			
5	*	2402.000	76.29	13.46	89.75	54.00	35.75	AVG	100	244	

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	X	2480.000	84.78	14.11	98.89	74.00	24.89	peak			
2	*	2480.000	76.85	14.11	90.96	54.00	36.96	AVG	100	132	
3		2483.500	25.16	14.13	39.29	74.00	-34.71	peak			
4		2485.737	23.72	14.14	37.86	74.00	-36.14	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	X	2480.000	84.40	14.11	98.51	74.00	24.51	peak			
2	*	2480.000	76.28	14.11	90.39	54.00	36.39	AVG	100	225	
3		2483.500	23.72	14.13	37.85	74.00	-36.15	peak			
4		2485.187	22.55	14.14	36.69	74.00	-37.31	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

5. BANDWIDTH

5.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2, Set the EUT Work on the operation frequency individually.
3. Set Span = approximately 2 to 5 times the OBW, centered on a hoping channel
   The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately 3* RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

5.2. TEST SETUP



5.3. TEST RESULT

TEST ITEM	20DB BANDWIDTH
TEST MODULATION	GFSK for BR/EDR

Test Data (MHz)		Criteria
Low Channel	1.095	PASS
Middle Channel	1.096	PASS
High Channel	1.083	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



TEST ITEM	20DB BANDWIDTH
TEST MODULATION	π /4-DQPSK for BR/EDR

Test Data (MHz)		Criteria
Low Channel	1.364	PASS
Middle Channel	1.381	PASS
High Channel	1.358	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



TEST ITEM	20DB BANDWIDTH
TEST MODULATION	8DPSK for BR/EDR

Test Data (MHz)		Criteria
Low Channel	1.385	PASS
Middle Channel	1.385	PASS
High Channel	1.386	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



6. FCC LINE CONDUCTED EMISSION TEST

6.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

6.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received DC 3.7V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received DC 3.7V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The BT function of EUT doesn't work when charging.

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP





APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT

BACK VIEW OF EUT

LEFT VIEW OF EUT

RIGHT VIEW OF EUT

Left

VIEW OF EUT (PORT)

OPEN VIEW OF EUT



VIEW OF BATTERY



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



Right

VIEW OF EUT (PORT)



OPEN VIEW OF EUT



VIEW OF BATTERY

INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



Charging Dock

VIEW OF EUT (PORT)-1

VIEW OF EUT (PORT)-2

Series Model

V7

TOTAL VIEW OF EUT

TOP VIEW OF EUT

BOTTOM VIEW OF EUT

FRONT VIEW OF EUT

BACK VIEW OF EUT

LEFT VIEW OF EUT

RIGHT VIEW OF EUT

Left

VIEW OF EUT (PORT)

OPEN VIEW OF EUT



VIEW OF BATTERY



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



Right

VIEW OF EUT (PORT)

OPEN VIEW OF EUT



VIEW OF BATTERY



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



Charging Dock

VIEW OF EUT (PORT)-1

VIEW OF EUT (PORT)-2

----END OF REPORT----