

FCC PART 15.247 TEST REPORT

For

TECHORBITS INC

13805 ALTON PKWY STE D IRVINE California United States 92618

FCC ID: 2AP6SPPI

Report Type: Original Report	Product Type: Wireless Mini Speaker
Test Engineer: <u>Gin Zuo</u>	<i>Gin Zuo</i>
Report Number: <u>RSA180608002-00A</u>	
Report Date: <u>2018-07-16</u>	
Reviewed By: <u>Oscar Ye RF Leader</u>	<i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE	11
MEASUREMENT RESULT	11
FCC §15.203 – ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST RESULTS SUMMARY.....	14
TEST DATA	14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY.....	18
TEST DATA	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36

TEST DATA	36
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST DATA	45
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	61
APPLICABLE STANDARD	61
TEST PROCEDURE	61
TEST DATA	61
FCC §15.247(d) - BAND EDGES TESTING	67
APPLICABLE STANDARD	67
TEST PROCEDURE	67
TEST DATA	67

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	TECHORBITS INC
Tested Model	PPI527
Series Model	PPI634, PPI905
Model Difference	Model names
Product Type	Wireless Mini Speaker
Dimension	60mm (L)* 60 mm (W)*55 mm(H)
Power Supply	DC 3.7V from Battery and DC 5.0V charging by USB Port

**All measurement and test data in this report was gathered from production sample serial number: 20180608002.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2018-06-08)*

Objective

This test report is prepared on behalf of TECHORBITS INC in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	77	2479
39	2441	78	2480

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test tool: FCC Tool

GFSK Power level: 1

π /4-DQPSK Power level: 1

8DPSK Power level: 1

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263

External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.3	EUT	Notebook
Power Cable	1.2	Notebook	Adapter

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Mini-Circuits	Amplifier	ZVA-183W-S+	220701818	2018-05-20	2019-05-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Notch filter	BRM50702	/	2017-08-05	2018-08-04
Narda	Attenuator/10dB	10dB	/	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2017-09-21	2018-09-20
Narda	Attenuator/2dB	10dB	/	2017-08-15	2018-08-14
TECHORBITS INC	RF Cable	/	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ENV216	3560655016	2017-11-15	2018-11-14
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2017-08-15	2018-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right]$$

 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For worst case:

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BT 3.0	2402-2480	-1.00	0.79	5.00	0.20	3.0	Yes

Result: No SAR test is required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna for Bluetooth, which the antenna gain is 2.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Gin Zuo on 2018-07-13.


EUT operation mode: Transmitting in high channel of GFSK mode (Worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.195	40.67	QP	9.000	L1	16.01	64.71	24.04	Compliance
0.195	29.46	AV	9.000	L1	16.01	54.71	25.25	Compliance
0.385	41.69	QP	9.000	L1	16.05	59.29	17.60	Compliance
0.385	27.71	AV	9.000	L1	16.05	49.29	21.58	Compliance
0.770	38.08	QP	9.000	L1	15.93	56.00	17.92	Compliance
0.770	25.06	AV	9.000	L1	15.93	46.00	20.94	Compliance
1.150	37.47	QP	9.000	L1	15.88	56.00	18.53	Compliance
1.150	22.76	AV	9.000	L1	15.88	46.00	23.24	Compliance
2.500	39.27	QP	9.000	L1	15.85	56.00	16.73	Compliance
2.500	27.44	AV	9.000	L1	15.85	46.00	18.56	Compliance
18.800	34.04	QP	9.000	L1	16.38	60.00	25.96	Compliance
18.800	26.74	AV	9.000	L1	16.38	50.00	23.26	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.195	45.83	QP	9.000	N	16.05	64.71	18.88	Compliance
0.195	34.73	AV	9.000	N	16.05	54.71	19.98	Compliance
0.385	42.13	QP	9.000	N	16.09	59.29	17.16	Compliance
0.385	29.16	AV	9.000	N	16.09	49.29	20.13	Compliance
0.600	41.15	QP	9.000	N	16.05	56.00	14.85	Compliance
0.600	25.79	AV	9.000	N	16.05	46.00	20.21	Compliance
1.000	41.27	QP	9.000	N	15.94	56.00	14.73	Compliance
1.000	22.72	AV	9.000	N	15.94	46.00	23.28	Compliance
2.800	38.39	QP	9.000	N	15.90	56.00	17.61	Compliance
2.800	28.96	AV	9.000	N	15.90	46.00	17.04	Compliance
18.650	37.18	QP	9.000	N	16.12	60.00	22.82	Compliance
18.650	29.50	AV	9.000	N	16.12	50.00	20.50	Compliance



Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa


The testing was performed by Gin Zuo on 2018-07-12 to 2018-07-14.

EUT operation mode: Transmitting

Spurious Emission Test:

30MHz-1GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case **high** channel of GFSK Mode in X-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
51.999950	35.40	101.0	V	249.0	-18.1	40.00	4.60
67.735450	29.33	101.0	V	306.0	-17.9	40.00	10.67
134.304050	25.19	101.0	V	311.0	-12.2	43.50	18.31
264.314950	33.49	101.0	H	262.0	-12.1	46.00	12.51
315.339800	30.86	101.0	H	272.0	-10.7	46.00	15.14
950.515200	22.78	101.0	V	57.0	1.2	46.00	23.22

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case **GFSK Mode in X-axis of orientation** was recorded

Note:

1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.600000	---	31.98	150.0	V	281.0	-0.6	54.00	22.02
1591.600000	42.17	---	150.0	V	281.0	-0.6	74.00	31.83
3536.400000	---	37.33	100.0	H	160.0	7.4	54.00	16.67
3536.400000	47.74	---	100.0	H	160.0	7.4	74.00	26.26
4804.000000	---	50.45	200.0	V	264.0	10.7	54.00	3.55
4804.000000	62.02	---	200.0	V	264.0	10.7	74.00	11.98
7206.000000	---	52.75	150.0	V	219.0	15.2	54.00	1.25
7206.000000	61.82	---	150.0	V	219.0	15.2	74.00	12.18
9608.800000	---	48.82	200.0	V	277.0	17.9	54.00	5.18
9608.800000	58.24	---	200.0	V	277.0	17.9	74.00	15.76
17537.600000	---	46.25	100.0	H	11.0	18.5	54.00	7.75
17537.600000	57.10	---	100.0	H	11.0	18.5	74.00	16.90

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1598.400000	---	29.87	150.0	V	224.0	-0.6	54.00	24.13
1598.400000	41.35	---	150.0	V	224.0	-0.6	74.00	32.65
3546.600000	---	38.29	200.0	H	174.0	7.4	54.00	15.71
3546.600000	47.13	---	200.0	H	174.0	7.4	74.00	26.87
4882.000000	---	48.21	150.0	V	231.0	11.1	54.00	5.79
4882.000000	61.06	---	150.0	V	231.0	11.1	74.00	12.94
7323.000000	---	48.57	100.0	V	46.0	15.4	54.00	5.43
7323.000000	59.46	---	100.0	V	46.0	15.4	74.00	14.54
9761.800000	---	46.42	200.0	V	283.0	18.1	54.00	7.58
9761.800000	59.12	---	200.0	V	283.0	18.1	74.00	14.88
17619.200000	---	46.37	150.0	V	161.0	18.6	54.00	7.63
17619.200000	56.39	---	150.0	V	161.0	18.6	74.00	17.61

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V /m)	Average (dB μ V /m)	Height (cm)	Polar (H/V)				
1591.600000	---	30.57	200.0	V	342.0	-0.6	54.00	23.43
1591.600000	42.88	---	200.0	V	342.0	-0.6	74.00	31.12
3312.000000	---	36.06	150.0	V	238.0	6.8	54.00	17.94
3312.000000	47.15	---	150.0	V	238.0	6.8	74.00	26.85
4960.000000	---	48.90	100.0	V	186.0	11.5	54.00	5.10
4960.000000	60.01	---	100.0	V	186.0	11.5	74.00	13.99
7440.000000	---	50.84	150.0	V	97.0	15.6	54.00	3.16
7440.000000	58.68	---	150.0	V	97.0	15.6	74.00	15.32
9921.600000	---	48.03	100.0	V	200.0	18.2	54.00	5.97
9921.600000	61.60	---	100.0	V	200.0	18.2	74.00	12.40
17524.000000	---	45.57	200.0	H	352.0	18.5	54.00	8.43
17524.000000	57.00	---	200.0	H	352.0	18.5	74.00	17.00

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case high channel of GFSK Mode in X-axis of orientation was recorded

Horizontal

Date: 14.JUL.2018 18:35:40

Vertical

Date: 14.JUL.2018 18:46:30

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case GFSK Mode in X-axis of orientation was recorded


Note:

1. The test is performed with a 10dB Attenuator.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB) + Attenuator (dB)
 Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	94.77	---	200.0	V	89.0	12.8	/	/
2402.000000	---	85.32	200.0	V	89.0	12.8	/	/
2402.000000	91.63	---	150.0	H	156.0	12.8	/	/
2402.000000	---	82.42	150.0	H	156.0	12.8	/	/
2356.748000	64.75	---	200.0	V	233.0	12.8	74.00	9.25
2356.748000	---	52.45	200.0	V	233.0	12.8	54.00	1.55
Middle Channel: 2441MHz								
2441.000000	94.52	---	250.0	V	94.0	12.9	/	/
2441.000000	---	85.37	250.0	V	94.0	12.9	/	/
2441.000000	91.06	---	200.0	H	193.0	12.9	/	/
2441.000000	---	82.45	200.0	H	193.0	12.9	/	/
High Channel: 2480MHz								
2480.000000	95.09	---	100.0	V	79.0	13.0	/	/
2480.000000	---	86.85	100.0	V	79.0	13.0	/	/
2480.000000	92.37	---	150.0	H	251.0	13.0	/	/
2480.000000	---	83.16	150.0	H	251.0	13.0	/	/
2525.152000	59.42	---	150.0	V	233.0	13.2	74.00	14.58
2525.152000	---	52.14	150.0	V	233.0	13.2	54.00	1.86

Conducted Spurious Emissions at Antenna Port


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel





EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel



EDR (8DPSK): Low Channel**EDR (8DPSK): Middle Channel**

EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data**Environmental Conditions**

Temperature:	23.4 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Gin Zuo on 2018-07-12.


EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.004	0.860	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.860	Pass
	Adjacent	2442			
	High	2480	1.004	0.860	Pass
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	1.004	0.789	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.789	Pass
	Adjacent	2442			
	High	2480	1.004	0.789	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.004	0.793	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.789	Pass
	Adjacent	2442			
	High	2480	1.004	0.789	Pass
	Adjacent	2479			

Note: For BDR mode, Limit = 20 dB bandwidth; For EDR mode, Limit = 20 dB bandwidth*2/3


BDR (GFSK): Low Channel







BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel**EDR ($\pi/4$ -DQPSK): Middle Channel**

EDR ($\pi/4$ -DQPSK): High Channel**EDR (8DPSK): Low Channel**

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Gin Zuo on 2018-07-12.


EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.860
	Middle	2441	0.860
	High	2480	0.860
EDR ($\pi/4$ -DQPSK)	Low	2402	1.184
	Middle	2441	1.184
	High	2480	1.184
EDR (8DPSK)	Low	2402	1.190
	Middle	2441	1.184
	High	2480	1.184

BDR (GFSK): Low Channel


BDR (GFSK): Middle Channel




BDR (GFSK): High Channel



EDR ($\pi/4$ -DQPSK): Low Channel



EDR($\pi/4$ -DQPSK): Middle Channel



Delta 1 [T1] 1.48 dB RBW 30 kHz RF Att 20 dB
 Ref Lvl 6.5 dBm 1.18436874 MHz VBW 100 kHz Unit dBm
 6.5 dBm 1.18436874 MHz
 10.5 dB Offset
 -23.64 dBm
 -23.23 dBm
 1MAX
 1 [T1] 1.48 dB
 1.18436874 MHz
 1MA
 Center 2.48 GHz 300 kHz/ Span 3 MHz
 Date: 12.JUL.2018 19:50:42

Delta 1 [T1] -0.17 dB
 RBW 30 kHz RF Att 20 dB
 Ref Lvl 6.5 dBm Unit dBm
 1.19038076 MHz
 SWT 8.5 ms
 10.5 dB Offset
 -D1 -3.03 dBm
 -D2 -23.03 dBm
 1MAX
 -22.74 dBm
 2.40143166 GHz
 -0.17 dB
 1.19038076 MHz
 Center 2.402 GHz 300 kHz/ Span 3 MHz
 Date: 12.JUL.2018 22:12:13

Delta 1 [T1] -0.55 dB
 RBW 30 kHz RF Att 20 dB
 Ref Lvl 6.5 dBm 1.18436874 MHz SWT 8.5 ms Unit dBm

10.5 dB Offset
 -D1 -3.28 dBm
 -D2 -23.28 dBm
 1MAX
 1 [T1] -22.65 dBm
 1 [T1] -0.55 dB
 1.18436874 MHz
 2.44043186 GHz
 1MA

Center 2.441 GHz 300 kHz/ Span 3 MHz
 Date: 12.JUL.2018 20:01:12

Delta 1 [T1] RBW 30 kHz RF Att 20 dB
 Ref Lvl -0.54 dB VBW 100 kHz
 6.5 dBm 1.18436874 MHz SWT 8.5 ms Unit dBm

10.5 dB Offset
 -D1 -3.12 dBm
 -D2 -23.12 dBm
 1MAX
 1 [T1] -22.48 dBm
 1 [T1] -0.54 dBm
 1.18436874 MHz
 2.47943166 GHz
 1MA

Center 2.48 GHz 300 kHz/
 Span 3 MHz

Date: 12.JUL.2018 20:02:13

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Gin Zuo on 2018-07-12.


EUT operation mode: Hopping

Test Result: Compliance.


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	23.4 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Gin Zuo on 2018-07-12.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.463	0.148	0.4	Pass
		Middle	0.475	0.152	0.4	Pass
		High	0.471	0.151	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.749	0.280	0.4	Pass
		Middle	1.749	0.280	0.4	Pass
		High	1.743	0.279	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.990	0.319	0.4	Pass
		Middle	3.010	0.321	0.4	Pass
		High	3.030	0.323	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.465	0.149	0.4	Pass
		Middle	0.463	0.148	0.4	Pass
		High	0.475	0.152	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.762	0.282	0.4	Pass
		Middle	1.743	0.279	0.4	Pass
		High	1.737	0.278	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	3.000	0.320	0.4	Pass
		Middle	2.990	0.319	0.4	Pass
		High	3.020	0.322	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.463	0.148	0.4	Pass
		Middle	0.469	0.150	0.4	Pass
		High	0.475	0.152	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.750	0.280	0.4	Pass
		Middle	1.762	0.282	0.4	Pass
		High	1.750	0.280	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	3.016	0.322	0.4	Pass
		Middle	3.000	0.320	0.4	Pass
		High	2.990	0.319	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




BDR (GFSK): Pulse time, Middle Channel, DH1





BDR (GFSK): Pulse time, High Channel, DH1




BDR (GFSK): Pulse time, Low Channel, DH3




BDR (GFSK): Pulse time, Middle Channel, DH3**BDR (GFSK): Pulse time, High Channel, DH3**


BDR (GFSK): Pulse time, Low Channel, DH5




BDR (GFSK): Pulse time, Middle Channel, DH5



BDR (GFSK): Pulse time, High Channel, DH5



EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1





Delta 1 [T1] RBW 1 MHz RF Att 20 dB
 Ref Lvl -3.17 dB VBW 3 MHz
 6.5 dBm 462.925852 μ s SWT 1 ms Unit dBm


10.5 dB Offset
 6.5 dBm
 -3.17 dB
 462.925852 μ s
 -53.26 dBm
 -14.478938 μ s
 -3.17 dB
 462.925852 μ s
 TR
 Center 2.441 GHz 100 μ s/
 Date: 12.JUL.2018 21:52:13

Delta 1 [T1] 0.83 dB
 Ref Lvl 6.5 dBm
 RBW 1 MHz
 RF Att 20 dB
 Unit dBm
 SWT 1 ms
 Center 2.48 GHz
 100 μs/
 Date: 12.JUL.2018 21:51:33


10.5 dB Offset
 -57.79 dBm
 T1
 474.949900 μs
 TR



EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3**EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3**

EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5**

EDR (8DPSK): Pulse time, Low Channel, 3DH1



EDR (8DPSK): Pulse time, Middle Channel, 3DH1



Delta 1 [T1] -1.19 dB

Ref Lvl 6.5 dBm RBW 1 MHz VBW 3 MHz SWT 1 ms RF Att 20 dB Unit dBm

10.5 dB Offset

Center 2.48 GHz 100 uV/s

Date: 12.JUL.2018 21:54:27


Delta 1 [T1] 0.54 dB
 Ref Lvl 6.5 dBm
 1.749499 ms
 RBW 1 MHz
 VBW 3 MHz
 SWT 3 ms
 RF Att 20 dB
 Unit dBm

10.5 dB Offset
 -54.53 dBm
 -34.518038 dB
 0.54 dB
 1.749499 ms
 TR


Center 2.402 GHz
 300 μ s/



Date: 12.JUL.2018 22:00:39

EDR (8DPSK): Pulse time, Middle Channel, 3DH3




EDR (8DPSK): Pulse time, High Channel, 3DH3



EDR (8DPSK): Pulse time, Low Channel, 3DH5**EDR (8DPSK): Pulse time, Middle Channel, 3DH5**

EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions


Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Gin Zuo on 2018-07-12.


EUT operation mode: Transmitting

Test Result: Compliance.


Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	-1.59	0.69	1000
	2441	-1.41	0.72	1000
	2480	-1.35	0.73	1000
EDR ($\pi/4$-DQPSK)	2402	-2.51	0.56	125
	2441	-2.38	0.58	125
	2480	-2.27	0.59	125
EDR (8DPSK)	2402	-2.63	0.55	125
	2441	-2.51	0.56	125
	2480	-2.27	0.59	125

BDR (GFSK): 2402MHz

BDR (GFSK): 2441MHz



BDR (GFSK): 2480MHz



Marker 1 [T1]
 Ref Lvl -2.51 dBm
 6.5 dBm 2.40189479 GHz

RBW 3 MHz
 VBW 10 MHz
 SWT 5 ms

RF Att 20 dB
 Unit dBm

10.5 dB Offset
 1 [T1]
 -2.51 dBm
 2.40189479 GHz

1MAX

Center 2.402 GHz
 500 kHz/
 Span 5 MHz

Date: 12.JUL.2018 20:10:27

Marker 1 [T1]
 -2.38 dBm
 2.44088477 GHz


Ref Lvl 6.5 dBm
 RBW 3 MHz
 RF Att 20 dB
 VSWR 10 MHz
 SWT 5 ms
 Unit dBm

10.5 dB Offset
 1 [T1]
 -2.38 dBm
 2.44088477 GHz
 1MAX


Center 2.441 GHz
 500 kHz/
 Span 5 MHz

Date: 12.JUL.2018 20:11:08


EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Gin Zuo on 2018-07-12.

EUT operation mode: Transmitting & Hopping


Test Result: Compliance.

Band Edge


BDR (GFSK): Left Side




BDR (GFSK): Right Side




EDR ($\pi/4$ -DQPSK): Left Side




EDR ($\pi/4$ -DQPSK): Right Side




EDR (8DPSK): Left Side




EDR (8DPSK): Right Side




BDR (GFSK): Left Side - Hopping




BDR (GFSK): Right Side- Hopping




EDR ($\pi/4$ -DQPSK): Left Side- Hopping




EDR ($\pi/4$ -DQPSK): Right Side- Hopping



EDR (8DPSK): Left Side- Hopping



EDR (8DPSK): Right Side- Hopping



***** END OF REPORT *****