



FCC 47 CFR MPE REPORT

VisionTek Products, LLC

WIRELESS CHARGER

Model Number: 901836

FCC ID: 2AP7W-901836

Applicant:	VisionTek Products, LLC
Address:	3 W College Drive Unit A, Arlington Heights,
	IL 60004 United States
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2607275
Date of Test:	Jun. 29, 2026 to Jul. 14, 2026
Date of Report:	Jul. 20, 2026


Applicant: Address:	VisionTek Products, LLC 3 W College Drive Unit A, Arlington Heights, IL 60004 United States		
Manufacturer: Address:	VisionTek Products, LLC 3 W College Drive Unit A, Arlington Heights, IL 60004 United States		
E.U.T:	WIRELESS CHARGER		
Model Number:	901836		
Power Supply:	INPUT: DC 5V/3A, DC 9V/3A, DC 12V/3A, DC 15V/2.4A Output: 25W Max		
Trade Name:	VisionTek	Sample No.:	EST-260629007-001
Date of Receipt:	Jun. 29, 2026	Date of Test:	Jun. 29, 2026 to Jul. 14, 2026
Test Specification:	FCC CFR 47 Part 1.1307(b)&1.1310 KDB 680106 D01 RF Exposure Wireless Charging Apps v04r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC CFR 47 Part 1.1307(b)&1.1310 requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		

Date: Aug. 31, 2026


Prepared by:

Reviewed by:

Approved by:



Ring Yang / Assistant



Seven Wang / Engineer



Iceman Hu / Manager

Other Aspects:

None.

Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.

1. Summary of test

1.1. Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	Maximum Permissible Exposure	Part 1.1307(b)&1.1310	PASS

1.2. Test Mode

Test Item	Test Mode
Maximum Permissible Exposure	Wireless Charging with 5W
	Wireless Charging with 7.5W
	Wireless Charging with 10W
	Wireless Charging with 15W
	Wireless Charging with 25W
	Standby
Note: All modes have been tested. The report only reflects the worst case of full load test data.	

1.3. Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Electric and Magnetic Field Probe-Analyzer	Narda S.T.S./PMM	EHP-200A	EST-E106	June 11,26	June 10,27
Test Software	Narda	EHP200-TS	Rel 1.92	N/A	N/A
Note: Test uncertainty: ± 1.62 dB (H-field); ± 1.64 dB (E-field) at a level of confidence of 95%.					

1.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
1	Adapter	-	SG-0501000AS	-	-
2	Wireless load	-	YBZ V.3.1	-	-
Note: Don't configuration adapter when it sales on the market, The adapter provided by the laboratory.					

Item	Shielded Type	Ferrite Core	Length	Model Name/Type No.	Note
1	NO	NO	1.0m	-	USB Cable

2. Maximum Permissible Exposure


2.1. Limit

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Note: f = frequency in MHz * = Plane-wave equivalent power density.

2.2. Test Setup



2.3. Test Procedure

- The test was performed on 360 degree turn table in anechoic chamber.
- The probe was placed at 20 cm surrounding, for test setup.
- The highest emission level was recorded and compared with limit as soon as measurement of each point; A, B, C, D, E were completed.

2.4. Test Result for Test setup:

E-field strength						
Frequency range	110.5~205kHz				360kHz	
Test Mode	Idle	5W	7.5W	10W	15W	25W
Position A(V/m)	0.345	2.095	2.079	2.315	3.457	3.341
Position B(V/m)	0.366	1.954	1.642	1.726	3.359	3.458
Position C(V/m)	0.382	1.438	1.468	1.679	3.028	3.368
Position D(V/m)	0.359	1.794	1.869	1.741	3.257	3.198
Position E(V/m)	0.385	2.412	2.457	2.665	4.015	4.184
Limits (V/m)	614					

H-field strength						
Frequency range	110.5~205kHz				360kHz	
Test Mode	Idle	5W	7.5W	10W	15W	25W
Position A(A/m)	0.038	0.044	0.045	0.048	0.079	0.089
Position B(A/m)	0.041	0.039	0.048	0.045	0.074	0.095
Position C(A/m)	0.043	0.038	0.044	0.050	0.075	0.091
Position D(A/m)	0.044	0.046	0.046	0.047	0.066	0.087
Position E(A/m)	0.045	0.052	0.051	0.052	0.085	0.112
Limits (A/m)	1.630					

3. Test photo

Position E



End of Test Report