



MPE ESTIMATION

Test report
On Behalf of
DONGGUAN YEWELINK SMART TECHNOLOGY CO., LTD.
For
Garage Door Smart Switch
Model No.: SGDS-01CKM, SGDS-01CKMW, SGDS-01CKMB,
SACS-01MJW, SACS-01MJB

FCC ID: 2AP8QSGDS-01CKM

Prepared for : **DONGGUAN YEWELINK SMART TECHNOLOGY CO., LTD.**
No.22, Hengzhong First Road, Hengkeng, Beimen Industrial Park, Liaobu
Town, DongGuan City, China

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: **June 06, 2019 ~ June 21, 2019**
Date of Report: **June 21, 2019**
Report Number: **HK1906061250-2E**

**1, Limit for General Population/ Uncontrolled Exposures**

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result**2.4G WIFI**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	13.24	13±1(14)	25.12	1	1.2589	0.00629
11g	12.52	12±1(13)	19.95	1	1.2589	0.00500
11n/HT20	11.81	11±1(12)	15.85	1	1.2589	0.00397
$Pd = \frac{P_{out} * G}{4\pi r^2} ;$						
Note:						
Note: The estimation distance is 20cm						
Note:						
PK Output power= conducted power.						
Conducted power see the test report HK1906061250-1E, antenna gain=1dBi						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.00629mW/cm² which is < 1.0mW/cm², SAR testing is not required.

-----The End-----