

RF EXPOSURE REPORT

FCC ID: 2AP8SK28R

Report Reference No. : 23EFSS05066 04251

Date of issue : 2023-06-16

Applicant's name.....: SIG SAUER INC.

Address.....: 12100 SW Tualatin Road Tualatin, OR 97062, USA.

Manufacturer.....: SIG SAUER INC.

Equipment.....: LASER RANGEFINDER

Trade Mark.....:



Model: KILO2800

Ratings.....: Input: DC 3V

Testing Laboratory: DongGuan ShuoXin Electronic Technology Co., Ltd.

Address.....: Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

According: KDB 447498 D04 Interim General RF Exposure Guidance v01

Test Engineer:

A handwritten signature in blue ink that reads 'Blue Qiu'.

Blue Qiu

Responsible Engineer :

A handwritten signature in black ink that reads 'Smile Wang'.

Smile Wang

Authorized Signatory:

A handwritten signature in black ink that reads 'King Wang'.

King Wang

MPE CALCULATION METHOD:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

Antenna gain = -0.65dBi

MAX Output Power : -7.228dBm@2480MHz

ERP = -7.228 + (-0.65) - 2.15 = -10.028dBm

WORSE CASE:

$10^{-0.7228} = 0.189 \text{ mW} < 3 \text{ mW}$

Then SAR evaluation is not required

END