

TEST REPORT



Dt&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2511-0079(1)

2. Customer

• Name (FCC) : CHIPSEN Inc.

• Address (FCC) : B225,B226,501 ho, M-CLUSTER, 17, Deogan-ro 104beon-gil,
Gwangmyeongsi, Gyeonggi-do, South Korea

3. Use of Report : FCC Original Certification

4. Product Name / Model Name : PLC wireless USB communication device / RCPOR-PLC300A
FCC ID: 2APB6-PLC300A

5. FCC Regulation(s): Part 15.225

Test Method used: ANSI C63.10-2020

6. Date of Test : 2025.09.01 ~ 2025.09.12

7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached Test Result

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : DongHyun Kang (Signature)	Name : JaeJin Lee (Signature)

2025 . 11 . 18 .

Dt&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2511-0079	Nov. 12, 2025	Initial issue	DongHyun Kang	JaeJin Lee
DRTFCC2511-0079(1)	Nov. 18, 2025	Update the address of customer	DongHyun Kang	JaeJin Lee

CONTENTS

1. General Information.....	4
1.1. Description of EUT	4
1.2. Declaration by the applicant / manufacturer	4
1.3. Testing Laboratory.....	5
1.4. Testing Environment.....	5
1.5. Measurement Uncertainty	5
1.6. Test Equipment List.....	6
2. Test Methodology	7
2.1. EUT Configuration.....	7
2.2. EUT Exercise	7
2.3. General Test Procedures.....	7
2.4. Description of Test Mode	7
2.5. Tested frequency	7
3. Antenna Requirements.....	8
4. Summary of Test Result	9
5. Test Result	10
5.1. 20dB bandwidth	10
5.2. In-band emissions	11
5.3. Out-of-band emissions	13
5.4. Frequency Stability.....	15
5.5. AC Power-Line Conducted Emissions	16

1. General Information

1.1. Description of EUT

Equipment Class	Low Power Communications Device Transmitter (DXX)
Product Name	PLC wireless USB communication device
Model Name	RCPORT-PLC300A
Add Model Name	-
Firmware Version Identification Number	1.0.0
EUT Serial Number	No Specified
Power Supply	DC 5 V
Frequency Range	13.56 MHz
Modulation Type	ASK
Antenna Type	PCB Pattern Antenna

1.2. Declaration by the applicant / manufacturer

N/A

1.3. Testing Laboratory

Dt&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948.		
- FCC & ISSED MRA Designation No. : KR0034		
- FCC Test Firm Registration No. : 704742		
- ISSED#: 5740A		
www.dtnet.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.4. Testing Environment

Ambient Condition	
▪ Temperature	+21 °C ~ +23 °C
▪ Relative Humidity	38 % ~ 41 %

1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.10-2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
AC power-line conducted emission	3.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (Below 1 GHz)	5.0 dB (The confidence level is about 95 %, $k = 2$)

1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	KEYSIGHT	N9020A	24/11/27	25/11/27	MY50200265
Spectrum Analyzer	Agilent Technologies	N9020A	24/11/26	25/11/26	MY50410399
DC Power Supply	Agilent Technologies	66332A	24/12/09	25/12/09	GB42110592
Multimeter	FLUKE	17B	24/11/27	25/11/27	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	24/12/10	25/12/10	255571
Signal Generator	KEYSIGHT	M9383A	24/12/10	25/12/10	E76F804A28
Thermohygrometer	BODYCOM	BJ5478	24/12/17	25/12/17	090205-4
Thermohygrometer	BODYCOM	BJ5478	24/12/05	25/12/05	120612-2
Loop Antenna	ETS-Lindgren	6502	24/04/23	26/04/23	00203480
Hybrid Antenna	Schwarzbeck	VULB 9160	24/12/13	25/12/13	3362
PreAmplifier	H.P	8447D	24/12/11	25/12/11	2944A07774
Receiver	Rohde Schwarz	ESC13	25/05/27	26/05/27	100798
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	25/07/10	26/07/10	101333
LISN	SCHWARZBECK	NSLK 8128 RC	24/10/21	25/10/21	8128 RC-387
Digital Thermo Hygrometer	CAS	TE-303N	25/02/13	26/02/13	220502531
Cable	HUBER+SUHNER	SUCOFLEX100	25/01/02	26/01/02	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	25/01/02	26/01/02	M-02
Cable	JUNKOSHA	MWX241/B	25/01/02	26/01/02	M-03
Cable	JUNKOSHA	J12J101757-00	25/01/02	26/01/02	M-07
Cable	HUBER+SUHNER	SUCOFLEX106	25/01/02	26/01/02	M-09
Cable	DT&C	Cable	25/01/02	26/01/02	RFC-46
Test Software (Radiated)	tsj	EMI Measurement	NA	NA	Version 2.00.0185
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0190
3m Semi Anechoic Chamber	SYC	3m-SAC	25/06/13(NSA) 25/06/19(VSWR)	26/06/13(NSA) 26/06/19(VSWR)	3m-SAC-1

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

2. Test Methodology

The tests were performed according to the ANSI C63.10-2020.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the FCC rules.

2.3. General Test Procedures

Conducted Emissions

According to the requirements in Section 6.2 of ANSI C63.10, the EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT are measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

The EUT is placed on a non-conductive table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.3 of ANSI C63.10

2.4. Description of Test Mode

Test mode1	Continuous transmitting mode
-------------------	------------------------------

The EUT has been tested with the operating condition for maximizing the emission characteristics.

2.5. Tested frequency

Channel	Tested Frequency(MHz)
Lowest	13.560
Middle	-
Highest	-

3. Antenna Requirements

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The antenna is attached on the device by means of unique coupling.
Therefore this E.U.T Complies with the requirement of §15.203**

4. Summary of Test Result

FCC part section(s)	Test Description	Limit	Test condition	Status Note 1
15.215(c)	20 dB Bandwidth	-	Radiated	C
15.225(a)	In-Band Emissions	15,848 $\mu\text{V/m}$ @ 30 m 13.553 MHz – 13.567 MHz		C Note 3
15.225(b)	In-Band Emissions	334 $\mu\text{V/m}$ @ 30 m 13.410 MHz – 13.553 MHz 13.567 MHz – 13.710 MHz		C Note 3
15.225(c)	In-Band Emissions	106 $\mu\text{V/m}$ @ 30 m 13.110 MHz – 13.410 MHz 13.710 MHz – 14.010 MHz		C Note 3
15.225(d) 15.209	Out-of Band Emissions	Emissions outside of the specified band (13.110 MHz - 14.010 MHz) must meet the radiated limits detailed in 15.209 (Refer to section 5.3)		C Note 3
15.225(e)	Frequency Stability	± 0.01 % of operating frequency	Temp & Humid Test Chamber	C
15.207	AC Conducted Emissions	Part 15.207 (Refer to section 5.5)	AC Line Conducted	C
15.203	Antenna Requirements	Part 15.203 (Refer to section 3)	-	C
Note 1: C = Comply NC = Not Comply NT = Not Tested NA = Not Applicable Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS. Note 3: This test item was performed in three orthogonal EUT positions and the worst case data was reported.				

5. Test Result


5.1. 20dB bandwidth

- Procedure: ANSI C63.10-2020 Section 6.9.2

The 20 dB Bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

1. Center frequency = EUT channel center frequency
2. Span = 2 ~ 5 times the OBW
3. RBW = 1 % ~ 5 % OBW
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Trace = Max hold
7. The trace was allowed to stabilize
8. Determine the reference value = Set the spectrum analyzer marker to the highest level of the displayed trace
9. Using the marker-delta function of the instrument, determine the “-xx dB down amplitude” using [(reference value) - xx].
10. Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

- Measurement Data: **Comply**




Tested Frequency (MHz)	20 dB BW (MHz)	
13.560	0.432	-

- Minimum Standard: NA

5.2. In-band emissions

- Test Configuration



- **Procedure:** The radiated emission was tested according to the **section 6.4 of the ANSI C63.10-2020**.

The EUT was placed on a 0.8 m high non-conductive table and it was placed at 3m distance from the antenna. Measurements were performed for each of the three antenna orientations. (ie. parallel, perpendicular, and ground-parallel)

Also, measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

RBW = As specified in below table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak

Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9 - 150 kHz	200 - 300 Hz
0.15 - 30 MHz	9 - 10 kHz
30 - 1 000 MHz	100 - 120 kHz
> 1000 MHz	1 MHz

- Minimum Standard: Part 15.225(a), (b), (c)

Frequency Band (MHz)	Limit at 30 m measurement distance	
	(uV/m)	(dBuV/m)
13.553 - 13.567	15,848	84.0
13.410 - 13.553 13.567 - 13.710	334	50.5
13.110 - 13.410 13.710 - 14.010	106	40.5

- Measurement Data:

Test Frequency Band (MHz)	Freq. (MHz)	EUT Axis.	ANT (Note 1)	Reading Level (dBuV)	TF (dB/m)	Field Strength @3 m (dBuV/m)	Field Strength @30 m (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.110 ~ 13.410	13.113	X	P	12.8	10.8	23.6	-16.4	40.5	56.9
13.410 ~ 13.553	13.553	X	P	22.0	10.8	32.8	-7.2	50.5	57.7
13.553 ~ 13.567	13.560	X	P	26.6	10.8	37.4	-2.6	84.0	86.6
13.567 ~ 13.710	13.568	X	P	22.1	10.8	32.9	-7.1	50.5	57.6
13.710 ~ 14.010	13.790	X	P	11.6	10.8	22.4	-17.6	40.5	58.1

Note 1. Loop antenna orientation

“P”: Parallel, “V”: perpendicular, “G”: ground-parallel

Note 2. This test item was performed at 3 m and the data were extrapolated to the specified measurement distance of 30 m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)(2).

▪ Extrapolation Factor = $40 \log(3\text{m} / 30\text{m}) = -40$

Note 3. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 4. Sample Calculation.


Margin = Limit – Field Strength @ 30 m / Field Strength @ 30 m = Field Strength @ 3 m – 40 dB

Field Strength @ 3 m = Reading + TF / TF = AF + CL

Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss

5.3. Out-of-band emissions

- Test configuration



- Procedure: The radiated emission was tested according to the **section 6.4, 6.5 of the ANSI C63.10-2020.**

For below 30 MHz, measurements were performed as described in section 4.2.3.

For above 30 MHz;

The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axes.

RBW = As specified in below table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak

Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9 - 150 kHz	200 - 300 Hz
0.15 - 30 MHz	9 - 10 kHz
30 - 1 000 MHz	100 - 120 kHz
> 1000 MHz	1 MHz

- Minimum Standard: Part 15.209, 225(d)

The field strength of any emissions appearing outside of the 13.110 - 14.010 MHz band shall not exceed the general radiated emission limits as below.

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
0.009 – 0.490	2 400 / F (kHz)	300
0.490 – 1.705	2 4000 / F (kHz)	30
1.705 – 30.0	30	30

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

- Measurement Data:

Frequency (MHz)	EUT Axis.	ANT (Note 1)	Reading (dBuV)	TF (dB/m)	DCF (dB)	Electric Field Strength (dBuV/m)	Limit (dBuV/m)	Margin (dB)
27.120	X	P	14.9	8.9	-40.0	-16.2	29.5	45.7
162.720	X	V	43.1	-6.6	NA	36.5	43.5	7.0
574.360	X	H	26.3	1.9	NA	28.2	46.0	17.8
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-

Note 1. No other spurious and harmonic emissions were reported greater than listed emissions above table.

Note 2. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 3. Loop antenna orientation (30 MHz Below)

“P”= Parallel, “V”= perpendicular, “G”= ground-parallel

Bilog antenna polarization (30 MHz above)

“H”= Horizontal, “V”= Vertical

Note 4. Information of Distance Correction Factor

For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.

In this case, the distance factor is applied to the result.

- Calculation of distance correction factor

At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$

At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$

When distance factor is “N/A”, the measurements were performed at the specified distance and distance factor is not applied.

Note 5. Sample calculation

Margin = Limit(dBuV/m) – Electric Field Strength

Electric Field Strength (dBuV/m) = Reading + TF – DCF

TF = AF + CL – AG

Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,

DCF = Distance Factor

5.4. Frequency Stability

- Procedure:

Part 15.225 requires that devices operating in the 13.553 – 13.567 MHz shall maintain the carrier frequency within 0.01 % of the operating frequency over the temperature variation of -20 degrees to + 50 degrees C at normal supply voltage.

- Measurement Data: **Comply**

Operating Frequency : 13,560,000 Hz

VOLTAGE (%)	POWER (V _{DC})	TEMP (°C)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100%	5.00	+20	13,560,452	452	0.003 333
100%		-20	13,560,511	511	0.003 770
100%		-10	13,560,508	508	0.003 745
100%		0	13,560,490	490	0.003 612
100%		+10	13,560,465	465	0.003 430
100%		+20	13,560,443	443	0.003 264
100%		+30	13,560,424	424	0.003 127
100%		+40	13,560,421	421	0.003 104
100%		+50	13,560,444	444	0.003 272
85%	4.25	+20	13,560,444	444	0.003 271
115%	5.75	+20	13,560,446	446	0.003 292

- Minimum Standard: Part 15. 225(e)

The frequency tolerance of the carrier signal shall be maintained within ± 0.01 % of the operating frequency.

5.5. AC Power-Line Conducted Emissions

- Test Requirements and limit, Part 15.207

An intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5.0	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

- Test Configuration

See test photographs for the actual connections between EUT and support equipment.

- Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10-2020.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

- Measurement Data: **Comply** (refer to the next page)

Measurement Data

Results of Conducted Emission

Date 2025-09-01

Order No.
Model No. RCP0RT-PLC300A
Serial No.
Test Condition NFC

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 °C / 41 %
Operator D.H.KANG

Memo

LIMIT : FCC P15.207 AV
FCC P15.207 QP

Lisn Factor


1. NSLK 8128 RC-387_N_24.10.21
2. NSLK 8128 RC-387_L1_24.10.21

Cable Loss

1. C1_LISN TO RECEIVER_2024-12-11

Pulse Limiter

1. PULSE LIMITER_ESH3-Z2_101333_2025.07.10



Measurement Data

Results of Conducted Emission

Date 2025-09-01

Order No.
Model No. RCP0RT-PLC300A
Serial No.
Test Condition NFC

Reference No.
Power Supply 120 V, 60 Hz
Temp/Humi. 23 °C / 41 %
Operator D.H.KANG

Memo

LIMIT : FCC P15.207 AV
FCC P15.207 QP

Lisn Factor

1. NSLK 8128 RC-387_N_24.10.21
2. NSLK 8128 RC-387_L1_24.10.21

Cable Loss

1. C1_LISN TO RECEIVER_2024-12-11

Pulse Lmitter

1. PULSE LIMITER_ESH3-Z2_101333_2025.07.10

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuA]	CAV [dBuA]		QP [dBuA]	CAV [dBuA]	QP [dBuA]	CAV [dBuA]	QP [dBuA]	CAV [dBuA]	
1	0.168883	40.92	25.20	10.02	50.94	35.22	55.54	55.54	14.60	20.32	N
2	0.168865	37.80	21.48	10.02	47.82	31.50	55.03	55.03	17.21	23.53	N
3	0.50846	28.28	19.22	10.05	38.33	29.27	56.00	46.00	17.67	16.73	N
4	1.69700	18.60	12.66	10.07	28.67	22.73	56.00	46.00	27.33	23.27	N
5	5.39500	14.72	6.02	10.25	24.97	16.27	60.00	50.00	35.03	33.73	N
6	15.84450	13.19	6.16	10.62	23.81	16.75	60.00	50.00	36.19	33.22	N
7	0.16179	40.10	27.80	10.06	50.16	37.86	55.37	55.37	15.21	17.51	L1
8	0.29893	27.42	19.85	10.02	37.44	29.87	60.27	50.27	22.83	20.40	L1
9	0.50279	34.56	25.99	10.05	44.61	36.04	56.00	46.00	11.39	9.96	L1
10	0.62503	24.73	17.76	10.06	34.79	27.82	56.00	46.00	21.21	18.18	L1
11	5.64500	13.87	4.55	10.25	24.12	14.80	60.00	50.00	35.88	35.20	L1
12	15.81540	13.99	7.60	10.62	24.61	15.22	60.00	50.00	35.39	31.78	L1