



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: January 11 ~ February 09, 2018

Test Report S/N: LR500111802C

Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID

IC ID

APPLICANT

2API2-WINIX-QS
23527-WINIXQS
WINIX INC.,

Equipment Class	:	Part 15 Spread Spectrum Transmitter (DSS)
Manufacturing Description	:	Air Purifier
Manufacturer	:	WINIX INC.,
Model name	:	WINIX QS
Test Device Serial No.:	:	Identical prototype
FCC Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C-63.4-2014 / ANSI C-63.10-2013
IC Rule Part(s)	:	RSS-247 and Issue No.2 DATE : 2017
Frequency Range	:	2402 ~ 2480 MHz
RF power	:	Max 7.23 dBm – Conducted (Basic) Max 1.44 dBm – Conducted (EDR)
Data of issue	:	February 12, 2018

This test report is issued under the authority of:

The test was supervised by:

Yong-Cheol Wang, Manager

Jae-Hum Yeon, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
2. INFORMATION ABOUT TEST ITEM	4
3. TEST REPORT	5
3.1 SUMMARY OF TESTS	5
3.2 FREQUENCY HOPPING SYSTEM REQUIREMENTS	6
3.3 TECHNICAL CHARACTERISTICS TEST	8
3.3.1 CARRIER FREQUENCY SEPARATION	8
3.3.2 NUMBER OF HOPPING FREQUENCIES	10
3.3.3 20 dB BANDWIDTH	12
3.3.4 TIME OF OCCUPANCY (Dwell Time)	19
3.3.5 TRANSMITTER OUTPUT POWER	24
3.3.6 BAND EDGE	28
3.3.7 CONDUCTED SPURIOUS EMISSIONS	34
3.3.8 RADIATED SPURIOUS EMISSIONS	39
3.3.9 AC Conducted Emissions	58
3.4 MEASUREMENT UNCERTAINTY	71
 APPENDIX	
APPENDIX TEST EQUIPMENT USED FOR TESTS	72

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	UPDATING	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	C-4948, T-2416, R-4483(10 m), G-847	2020-09-10 2020-09-10 2020-10-15 2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information about test item

2-1 Client & Manufacturer

Company name : WINIX INC.,
 Address : 607, 3na, 295, Gongdan 1-daero, Siheung-si, Gyeonggi-do Seoul, Korea
 Tel / Fax : TEL No : +82-31-499-5088 / FAX No : +82-31-498-2617

2-2 Equipment Under Test (EUT)

Model name : WINIX QS
 Serial number : Identical prototype
 Date of receipt : January 11, 2018
 EUT condition : Pre-production, not damaged
 Antenna type : Monopole Antenna Max Gain 0 dBi
 Frequency Range : 2402 ~ 2480MHz
 RF output power : Max 7.23 dBm – Conducted (Basic)
 : Max 1.44 dBm – Conducted (EDR)
 Number of channels : 79
 Channel spacing : 1 MHz
 Channel Access Protocol : Frequency Hopping Spread Spectrum (FHSS)
 Type of Modulation : Basic Mode(GFSK), EDR Mode(Pi/4 DQPSK, 8DPSK)
 Power Source : AC 110 V
 Firmware Version : V1.0.0

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz) – Basic & EDR	2402	2441	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	$\geq 2/3$ of 20dB BW	Conducted	C
15.247(a)	Number of Hopping Frequencies	≥ 15 channels		C
15.247(a)	20 dB Bandwidth 99% Bandwidth	—		C
15.247(a)	Dwell Time	≤ 0.4 seconds		C
15.247(b)	Transmitter Output Power	≤ 1 W for 1Mbps ≤ 125 mW for 2,3Mbps		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.249 / 15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.109	Field Strength	—		C
15.207 /15.107	AC Conducted Emissions	EN 55022	Line Conducted	C
15.203	Antenna requirement	—	—	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 1: Antenna Requirement

→ The **WINIX Inc.**, FCC ID: **2API2-WINIX-QS** unit complies with the requirement of §15.203.

The antenna type is Monopole Antenna.

The sample was tested according to the following specification:

- *FCC Parts 15.247; ANSI C-63.4-2014;ANSI C-63.10-2013
- *FCC KDB Publication No. 558074 D01 v03r05
- *FCC TCB Workshop 2012, April
- *RSS-247 and Issue No.2 Date:2017

3.2 Frequency Hopping System Requirements

3.2.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

3.2.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence: $2^9 - 1 = 511$ bits

Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

3.2.3 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

*Example for a Bluetooth device using channel numbers would be : Chan 44, 35, 78, 03, 15, 21, 76, 40, 56, 13, 02, 19, 67, 39, 78, 20, 21, 64, 75 etc.

3.3 TECHNICAL CHARACTERISTIC TEST

3.3.1 Carrier Frequency Separation

Procedure:

The test follows DA00-705. The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 2~ 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 10 kHz (1% of the span or more) Sweep = auto

VBW = 10 kHz Detector function = peak

Trace = max hold

Measurement Data:

Test Results	
Carrier Frequency Separation (MHz)	Result
0.999 (Basic)	Complies
1.003 (EDR)	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

The EUT shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of 20 dB bandwidth of the hopping channel, whichever is greater.

Measurement Setup






Figure 1: Measurement setup for the carrier frequency separation

Carrier Frequency Separation
Basic Mode



EDR Mode



3.3.2 Number of Hopping Frequencies

Procedure:

The test follows DA00-705. The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

To get higher resolution, four frequency ranges within the 2400 ~ 2483.5 MHz FH band were examined.

The spectrum analyzer is set to (Bluetooth):

Frequency range	Start = 2400.0 MHz,	Stop = 2483.5 MHz
RBW = 100 kHz (1% of the span or more)	Sweep = auto	
VBW = 100 kHz (VBW ≥ RBW)	Detector function = peak	
Trace = max hold	Span > 40 MHz	

Measurement Data : **Complies**

Total number of Hopping Channels	79 (Basic, EDR)
----------------------------------	-----------------

- See next pages for actual measured spectrum plots.


Minimum Standard:

At least 15 channels


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)

Number of Hopping Frequencies (Basic)



Number of Hopping Frequencies (EDR)



3.3.3 20 dB Bandwidth

Procedure:

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to (Bluetooth):

Center frequency = the highest, middle and the lowest channels

Span = 3 MHz (approximately 2 or 3 times of the 20 dB bandwidth)

RBW = 30 kHz

Sweep = auto

VBW = 30 kHz (VBW $\geq$ RBW)

Detector function = peak

Trace = max hold

Measurement Data: Basic Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	0.803	0.890
2441	39	0.790	0.951
2480	78	0.795	0.951

- See next pages for actual measured spectrum plots.

Measurement Data: EDR Mode

Frequency (MHz)	Channel No.	Test Results(MHz)	
		20dB Bandwidth	99% Bandwidth
2402	0	1.229	1.172
2441	39	1.259	1.172
2480	78	1.259	1.172

- See next pages for actual measured spectrum plots.


Minimum Standard:

N/A


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Channel 0 of Basic mode
20 dB Bandwidth




99% Bandwidth




Channel 39 of Basic mode
20 dB Bandwidth




99% Bandwidth




Channel 78 of Basic mode
20 dB Bandwidth




99% Bandwidth




Channel 1 of EDR mode
20 dB Bandwidth




99% Bandwidth




Channel 39 of EDR mode
20 dB Bandwidth




99% Bandwidth



Channel 78 of EDR mode
20 dB Bandwidth



99% Bandwidth



3.3.4 Time of Occupancy (Dwell Time)

Procedure:

The test follows DA00-705. The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2441 MHz

Span = zero

RBW = 1 MHz

VBW = 1 MHz (VBW $\geq$ RBW)

Trace = max hold

Detector function = peak

Measurement Data (Basic,EDR):

Mode	Number of transmission in a 31.6s (79Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (msec)
DH1	30(Times / 3sec) *10.533 = 315.99	0.464	146.61	400
DH3	15(Times / 3sec) *10.533 = 158.00	1.717	271.29	400
DH5	10(Times / 3sec) *10.533 = 105.33	2.986	314.52	400
3-DH5	10(Times / 3sec) *10.533 = 105.33	2.957	311.46	400

- See next pages for actual measured spectrum plots.
- dwell time = {(number of hopping per second / number of slot) x duration time per channel} x 0.4 ms



Minimum Standard:

0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed



Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)



DH1 at Basic mode





DH3 at Basic mode



DH5 at Basic mode



3-DH5 at EDR mode



3.3.5 Transmitter Output Power

Procedure:

The test follows DA00-705. The peak output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

The spectrum analyzer is set to :

Center frequency = the highest, middle and the lowest channels

Span = 10 MHz (approximately 5 times of the 20 dB bandwidth)

RBW = 3 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 3 MHz (VBW $\geq$ RBW)

Detector function = peak

Trace = max hold

Sweep = auto

Measurement Data : Basic Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	5.61	3.64	Complies
2441	39	6.89	4.89	Complies
2480	78	7.23	5.28	Complies

Measurement Data : EDR Mode

Frequency (MHz)	Ch.	Test Results		
		dBm	mW	Result
2402	0	-1.82	0.66	Complies
2441	39	1.01	1.26	Complies
2480	78	1.44	1.39	Complies


- See next pages for actual measured spectrum plots.

Minimum Standard:	For frequency hopping systems with at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems: 0.125 W.
--------------------------	--


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Channel 1
Basic mode




Channel 39
Basic mode




Channel 79
Basic mode




Channel 1
EDR mode



Channel 39
EDR mode



Channel 79
EDR mode



3.3.6 Band Edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz	VBW = 100 kHz
Span = 10~30 MHz	Detector function = peak
Trace = max hold	Sweep = auto

Measurement Data: **Complies**

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
-------------------	----------

Measurement Setup


Same as the Chapter 3.3.1 (Figure 1)

Band Edge (Basic)

Lower edge




Upper edge




Band Edge- Hopping(Basic)

Lower edge




Upper edge




Band Edge (EDR)


Lower edge




Upper edge



Band Edge- Hopping (EDR)
Lower edge



Upper edge



Radiated Band edges in the restricted band 2310-2390 MHz measurement (Basic)

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor		Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain+CableLoss	AV / Peak		AV / Peak		AV / Peak	
2321.6	32.47	42.05	V	27.88	22.9	54	74	37.45	47.03	16.55	26.97
2317.1	32.51	42.06	V	28.09	23.11	54	74	37.49	47.04	16.51	26.96
2321.8	32.21	41.89	V	27.88	22.9	54	74	37.19	46.87	16.81	27.13

Radiated Band edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor		Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain+CableLoss	AV / Peak		AV / Peak		[MHz]	
2485.2	34.11	44.67	V	27.88	22.9	54	74	39.09	49.65	14.91	24.35
2486.1	33.97	43.47	V	27.88	22.9	54	74	38.95	48.45	15.05	25.55
2486.5	33.92	43.88	V	27.88	22.9	54	74	38.9	48.86	15.1	25.14

Radiated Band edges in the restricted band 2310-2390 MHz measurement (EDR)

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor		Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain+CableLoss	AV / Peak		AV / Peak		AV / Peak	
2377.1	30.26	40.54	V	27.88	22.9	54	74	35.24	45.52	18.76	28.48
2377.9	29.97	39.47	V	27.88	22.9	54	74	34.95	44.45	19.05	29.55
2379.4	29.95	39.52	V	27.88	22.9	54	74	34.93	44.5	19.07	29.5

Radiated Band edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor		Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna	Amp. Gain + CableLoss	AV / Peak		AV / Peak		[MHz]	
2485.7	30.22	40.42	V	27.88	22.9	54	74	35.2	45.4	18.8	28.6
2485.9	30.05	40.37	V	27.88	22.9	54	74	35.03	45.35	18.97	28.65
2486.6	30.31	40.48	V	27.88	22.9	54	74	35.29	45.46	18.71	28.54

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented.

3.3.7 Conducted Spurious Emissions

Procedure:

The test follows DA00-705. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz

Sweep = auto

VBW = 100 kHz

Detector function = peak

Trace = max hold

Measurement Data: **Complies**


- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc
--------------------------	----------


Measurement Setup

Same as the Chapter 3.3.1 (Figure 1)


Unwanted Emission – Low channel (Basic)
Frequency Range = 30 MHz ~ 26.5 GHz





Unwanted Emission – Middle channel
Frequency Range = 30 MHz ~ 26.5 GHz




Unwanted Emission – High channel
Frequency Range = 30 MHz ~ 26.5 GHz



Unwanted Emission – Low channel (EDR)**Frequency Range = 30 MHz ~ 26.5 GHz****Unwanted Emission – Middle channel****Frequency Range = 30 MHz ~ 26.5 GHz**

Unwanted Emission – High channel
Frequency Range = 30 MHz ~ 26.5 GHz



3.3.8 Radiated Spurious Emissions

Procedure:

Radiated emissions from the EUT were measured according to the dictates of DA00-705. The EUT was placed on a 0.8 m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

- (a) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 3 m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30 MHz, Bi-Log Test Antenna (30 MHz to 1 GHz) and Horn Test Antenna (above 1 GHz) are used. Test Antenna is 3 m away from the EUT. Test Antenna height is carried from 1 m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 120 kHz (30 MHz ~ 1 GHz)

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz


Trace = max hold

VBW $\geq$ RBW


Detector function = peak

Sweep = auto


below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: **Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3m
0.009 ~ 0.490	2400/F(kHz) (@ 300m)
0.490 ~ 1.705	24000/F(kHz) (@ 30m)
1.705 ~ 30	30(@ 30m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data : Basic Mode (BDR)

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor	D.C.F	Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna+ (Cable-Amp.Gain)		AV/Peak		AV/Peak		AV / Peak	
10575.54	21.01	32.68	H	26.77	-30.16	54.0	74.0	17.62	29.29	36.38	44.71
7497.66	21.05	33.10	H	26.17	-30.16	54.0	74.0	17.06	29.11	36.96	44.89
10215.02	22.03	32.32	H	26.19	-30.16	54.0	74.0	18.06	28.35	35.94	45.65

- No other emissions were detected at a level greater than 20dB below limit.

- D.C.F (Duty Cycle Correction Factor) = $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(3.101\text{ms}/100\text{ms}) = -30.16$$

Measurement Data : EDR Mode

Frequency [MHz]	Reading [dBuV / m]		Pol.	Correction Factor	D.C.F	Limits [dBuV / m]		Result [dBuV / m]		Margin [dB]	
	AV / Peak			Antenna+ (Cable-Amp.Gain)		AV/Peak		AV/Peak		AV / Peak	
10484.23	21.16	33.27	V	26.57	-30.60	54.0	74.0	17.13	29.24	36.87	44.76
10606.15	21.52	31.23	H	26.85	-30.60	54.0	74.0	17.77	27.48	36.23	46.52
18450.74	22.03	36.05	H	24.96	-30.60	54.0	74.0	16.39	30.41	37.61	43.59

- No other emissions were detected at a level greater than 20dB below limit.

- D.C.F (Duty Cycle Correction Factor) = $20\log(\text{The worst Case DWELL Time}/100\text{ms})$

$$= 20\log(2.949\text{ms}/100\text{ms}) = -30.60$$

Radiated Emissions – Basic mode (below 1GHz)

4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: WINIX QS

Temp/Humi: 25 / 49


Test Mode : BDR mode

Tested by: YEON J H

Data: 668

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-02-08



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.59	-14.43	20.16	40.00	19.84	135	238	HORIZONTAL
907.85	22.69	1.15	23.84	46.00	22.16	203	212	HORIZONTAL
945.68	21.20	2.36	23.56	46.00	22.44	211	197	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: WINIX QS

Temp/Humi: 25 / 49


Test Mode : BDR mode

Tested by: YEON J H

Data: 669

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-02-08



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
37.76	45.19	-14.43	30.76	40.00	9.24	102	302	VERTICAL
41.64	35.70	-14.09	21.61	40.00	18.39	115	321	VERTICAL
500.45	33.47	-6.62	26.85	46.00	19.15	152	299	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions – EDR mode (below 1GHz)

4, Songjiuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: WINIX QS

Temp/Humi: 25 / 49


Test Mode : EDR mode

Tested by: YEON J H

Data: 672

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-02-08



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
37.76	34.49	-14.43	20.06	40.00	19.94	205	79	HORIZONTAL
907.85	23.69	1.15	24.84	46.00	21.16	265	85	HORIZONTAL
945.68	22.25	2.36	24.61	46.00	21.39	201	68	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: WINIX QS

Temp/Humi: 25 / 49


Test Mode : EDR mode

Tested by: YEON J H

Data: 671

File: C:\Program Files (x86)\e3\1706-1.EM6 (1422)

Date: 2018-02-08




Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
37.76	45.19	-14.43	30.76	40.00	9.24	172	215	VERTICAL
41.64	35.75	-14.09	21.66	40.00	18.34	117	205	VERTICAL
500.45	33.92	-6.62	27.30	46.00	18.70	168	203	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: BDR (low) mode
Tested by : YEON J H
Temp/Humi: 23 / 54



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4804.75	43.25	15.54	58.79	74.00	15.21	HORIZONTAL
2 4804.75	30.19	15.54	45.73	54.00	8.27	HORIZONTAL
3 7454.43	32.38	25.72	58.10	74.00	15.90	VERTICAL
4 7454.43	20.08	25.72	45.80	54.00	8.20	VERTICAL
5 7519.35	32.45	26.12	58.57	74.00	15.43	VERTICAL
6 7519.35	20.11	26.12	46.23	54.00	7.77	VERTICAL
7 7584.83	32.49	25.87	58.36	74.00	15.64	VERTICAL
8 7584.83	20.17	25.87	46.04	54.00	7.96	VERTICAL
910333.80	32.54	26.36	58.90	74.00	15.10	HORIZONTAL
1010333.80	20.25	26.36	46.61	54.00	7.39	HORIZONTAL
1110575.54	32.68	26.77	59.45	74.00	14.55	HORIZONTAL
1210575.54	21.01	26.77	47.78	54.00	6.22	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



Test Mode: BDR(low) mode

Temp/Humi: 23 / 54

The plot shows the spectral density of the signal. The y-axis represents the level in dBuV/m, ranging from 0 to 100. The x-axis represents the frequency in MHz, ranging from 18000 to 25000. Two horizontal lines are plotted: a red line at approximately 75 dBuV/m labeled '18G~25G FCC_B(PK)' and a blue line at approximately 55 dBuV/m labeled '18G~25G FCC_B(AV)'. A vertical line at 18000 MHz is labeled '1' and '2'.

Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118192.42	34.58	24.53	59.11	74.00	14.89	HORIZONTAL
218192.42	21.47	24.53	46.00	54.00	8.00	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songju-ro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No.: WINIX QS

Test Mode: BDR(mid) mode

Tested by : YEON J H

Temp/Humi: 23 / 54

Data: 291 File: D:\LTA_e3\3_backup\1GHz 미상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301)
Level (dBuV/m) Date: 2018-02-09



	Freq	Reading	C.F	Result	Limit	Margin	Polarity
	MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1	4884.23	40.07	15.85	55.92	74.00	18.08	HORIZONTAL
2	4884.23	28.17	15.85	44.02	54.00	9.98	HORIZONTAL
3	7497.66	33.10	26.17	59.27	74.00	14.73	VERTICAL
4	7497.66	21.05	26.17	47.22	54.00	6.78	VERTICAL
5	7606.79	33.14	25.79	58.93	74.00	15.07	HORIZONTAL
6	7606.79	21.08	25.79	46.87	54.00	7.13	HORIZONTAL
7	7784.73	33.20	25.12	58.32	74.00	15.68	VERTICAL
8	7784.73	21.15	25.12	46.27	54.00	7.73	VERTICAL
9	8943.27	34.08	25.62	59.70	74.00	14.30	HORIZONTAL
10	8943.27	21.35	25.62	46.97	54.00	7.03	HORIZONTAL
11	9365.58	34.28	25.52	59.80	74.00	14.20	HORIZONTAL
12	9365.58	21.52	25.52	47.04	54.00	6.96	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
 4, Songjuro236Beon-gil, Yangji-myeon,
 Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
 Tel :+82-31-3236008,9 www.ltalab.com
 Fax:+82-31-3236010


EUT/Model No. : WINIX QS

Test Mode: BDR (mid) mode

Tested by : YEON J H

Temp/Humi: 23 / 54

Data: 297 File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301)
 Level (dBuV/m) Date: 2018-02-09



Frequency (MHz)						
Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118275.83	35.47	24.67	60.14	74.00	13.86	HORIZONTAL
218275.83	21.38	24.67	46.05	54.00	7.95	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010


EUT/Model No. : WINIX QS

Test Mode: BDR (high) mode

Tested by : YEON J H

Temp/Humi: 23 / 54

Data: 292 File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301) Date: 2018-02-09
Level (dBuV/m)




Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4960.38	40.05	16.16	56.21	74.00	17.79	VERTICAL
2 4960.38	25.63	16.16	41.79	54.00	12.21	VERTICAL
3 7454.43	32.05	25.72	57.77	74.00	16.23	VERTICAL
4 7454.43	21.70	25.72	47.42	54.00	6.58	VERTICAL
5 7541.11	32.11	26.04	58.15	74.00	15.85	HORIZONTAL
6 7541.11	21.92	26.04	47.96	54.00	6.04	HORIZONTAL
7 8013.02	32.15	24.28	56.43	74.00	17.57	HORIZONTAL
8 8013.02	21.95	24.28	46.23	54.00	7.77	HORIZONTAL
9 9126.06	32.20	25.80	58.00	74.00	16.00	VERTICAL
10 9126.06	21.97	25.80	47.77	54.00	6.23	VERTICAL
11 10215.02	32.32	26.19	58.51	74.00	15.49	HORIZONTAL
12 10215.02	22.03	26.19	48.22	54.00	5.78	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: BDR (high) mode
Tested by : YEON J H
Temp/Humi: 23 / 54



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
11817.7785	35.47	24.51	59.98	74.00	14.02	HORIZONTAL
21817.7785	21.35	24.51	45.86	54.00	8.14	HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: EDR (low) mode
Tested by : YEON J H
Temp/Humi : 23 / 54

Data: 293
Level (dBuV/m)
File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301)
Date: 2018-02-09




Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4804.30	45.60	15.53	61.13	74.00	12.87	HORIZONTAL
2 4804.30	31.20	15.53	46.73	54.00	7.27	HORIZONTAL
3 7497.65	32.80	26.17	58.97	74.00	15.03	HORIZONTAL
4 7497.65	20.70	26.17	46.87	54.00	7.13	HORIZONTAL
5 7584.83	32.82	25.87	58.69	74.00	15.31	VERTICAL
6 7584.83	20.83	25.87	46.70	54.00	7.30	VERTICAL
7 8969.16	32.90	25.76	58.66	74.00	15.34	HORIZONTAL
8 8969.16	20.94	25.76	46.70	54.00	7.30	HORIZONTAL
910393.71	33.02	26.44	59.46	74.00	14.54	VERTICAL
1010393.71	21.08	26.44	47.52	54.00	6.48	VERTICAL
1110484.23	33.27	26.57	59.84	74.00	14.16	VERTICAL
1210484.23	21.16	26.57	47.73	54.00	6.27	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: EDR (low) mode
Tested by : YEON J H
Temp/Humi : 23 / 54



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118245.40	36.77	24.62	61.39	74.00	12.61	HORIZONTAL
218245.40	21.58	24.62	46.20	54.00	7.80	HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: EDR(mid) mode
Tested by : YEON J H
Temp/Humi: 23 / 54

Data: 294
Level (dBuV/m)
File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301)
Date: 2018-02-09




Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4884.70	43.25	15.86	59.11	74.00	14.89	HORIZONTAL
2 4884.70	31.18	15.86	47.04	54.00	6.96	HORIZONTAL
3 7497.65	31.54	26.17	57.71	74.00	16.29	VERTICAL
4 7497.65	21.58	26.17	47.75	54.00	6.25	VERTICAL
5 7673.03	32.24	25.54	57.78	74.00	16.22	HORIZONTAL
6 7673.03	21.66	25.54	47.20	54.00	6.80	HORIZONTAL
7 10484.23	32.23	26.57	58.80	74.00	15.20	VERTICAL
8 10484.23	21.68	26.57	48.25	54.00	5.75	VERTICAL
9 10606.15	31.23	26.85	58.08	74.00	15.92	HORIZONTAL
10 10606.15	21.52	26.85	48.37	54.00	5.63	HORIZONTAL
11 10760.54	31.19	27.22	58.41	74.00	15.59	HORIZONTAL
12 10760.54	20.87	27.22	48.09	54.00	5.91	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: EDR (mid) mode
Tested by : YEON J H
Temp/Humi : 23 / 54



Frequency (MHz)						
Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
118448.29	35.72	24.96	60.68	74.00	13.32	HORIZONTAL
218448.29	21.65	24.96	46.61	54.00	7.39	HORIZONTAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No. : WINIX QS
Test Mode: EDR (high) mode
Tested by : YEON J H
Temp/Humi: 23 / 54

Data: 295
Level (dBuV/m)
File: D:\LTA_e3\3_backup\1GHz 이상\2017\CH1_ABOVE 1GHz_1706-1.EMI (301)
Date: 2018-02-09



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	PK dBuV/m	dBuV/m	dB	
1 4960.37	40.28	16.16	56.44	74.00	17.56	HORIZONTAL
2 4960.37	28.70	16.16	44.86	54.00	9.14	HORIZONTAL
3 7284.04	32.38	23.98	56.36	74.00	17.64	VERTICAL
4 7284.04	20.19	23.98	44.17	54.00	9.83	VERTICAL
5 7541.11	31.25	26.04	57.29	74.00	16.71	VERTICAL
6 7541.11	20.35	26.04	46.39	54.00	7.61	VERTICAL
7 7673.03	30.94	25.54	56.48	74.00	17.52	HORIZONTAL
8 7673.03	20.27	25.54	45.81	54.00	8.19	HORIZONTAL
9 9021.16	30.43	25.92	56.35	74.00	17.65	HORIZONTAL
10 9021.16	20.22	25.92	46.14	54.00	7.86	HORIZONTAL
11 9126.06	30.43	25.80	56.23	74.00	17.77	HORIZONTAL
12 9126.06	20.27	25.80	46.07	54.00	7.93	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



Test Mode: EDR(high) mode

Temp/Humi: 23 / 54

Level (dBuV/m)

Date: 2018-02-09

18G~25G FCC_B(PK)

18G~25G FCC_B(AV)

1

2

18000 20000 25000

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

3.3.9 AC Conducted Emissions

Procedure:

AC power line conducted emissions from the EUT were measured according to the dictates of ANSI C63.4:2003.

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: Complies

- Refer to the next page.
- No other emissions were detected at a level greater than 20dB below limit
- It gave the worse case emissions

Minimum Standard: FCC Part 15.207(a)/EN 55022

Frequency Range (MHz)	Conducted Limit (d. 1t892 𐀀 BuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Conducted Emissions – 2.4 GHz BDR(LOW) mode + LINE

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS

Phase : LINE

Test Mode : BDR low

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 509

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (509)

Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
22.391	11.99	3.77	19.65	31.64	23.42	60.00	50.00	28.36	26.58
23.949	26.29	24.56	19.65	45.94	44.21	60.00	50.00	14.06	5.79
24.744	23.19	21.40	19.66	42.85	41.06	60.00	50.00	17.15	8.94
25.541	22.86	19.46	19.66	42.52	39.12	60.00	50.00	17.48	10.88
26.345	23.31	17.40	19.68	42.99	37.08	60.00	50.00	17.01	12.92
27.936	20.26	17.14	19.69	39.95	36.83	60.00	50.00	20.05	13.17

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz BDR(LOW) mode +NEUTRAL

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS

Phase : NEUTRAL

Test Mode : BDR low

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 512

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (512)

Date: 2018-02-09



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.346	20.03	16.45	19.42	39.45	35.87	59.05	49.05	19.60	13.18
0.350	20.00	16.56	19.42	39.42	35.98	58.95	48.95	19.53	12.97
0.351	20.03	16.59	19.42	39.45	36.01	58.95	48.95	19.50	12.94
23.154	21.95	20.39	19.74	41.69	40.13	60.00	50.00	18.31	9.87
23.986	12.14	3.62	19.74	31.88	23.36	60.00	50.00	28.12	26.64
25.548	21.77	18.50	19.76	41.53	38.26	60.00	50.00	18.47	11.74

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted Emissions – 2.4 GHz BDR(MID) mode + LINE



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS	Phase : LINE
Test Mode : BDR mid	Test Power : 110/60
Temp. / Humi. : 20 / 46	Test Engineer : YEON J H

Data: 516 File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (516) Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.348	20.23	16.58	19.44	39.67	36.02	59.01	49.01	19.34	12.99
0.349	20.21	16.64	19.44	39.65	36.08	58.98	48.98	19.33	12.90
24.000	13.30	3.20	19.65	32.95	22.85	60.00	50.00	27.05	27.15
24.513	6.30	-1.97	19.66	25.96	17.69	60.00	50.00	34.04	32.31
24.526	11.70	-2.30	19.66	31.36	17.36	60.00	50.00	28.64	32.64
28.083	14.03	0.76	19.69	33.72	20.45	60.00	50.00	26.28	29.55

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz BDR(MID) mode + NEUTRAL

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS

Phase : NEUTRAL

Test Mode : BDR high

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 525

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (525)

Date: 2018-02-09



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.348	20.10	16.60	19.42	39.52	36.02	59.00	49.00	19.48	12.98
0.511	14.46	10.27	19.42	33.88	29.69	56.00	46.00	22.12	16.31
0.515	14.33	10.13	19.42	33.75	29.55	56.00	46.00	22.25	16.45
4.031	13.46	9.87	19.46	32.92	29.33	56.00	46.00	23.08	16.67
22.393	11.28	3.98	19.74	31.02	23.72	60.00	50.00	28.98	26.28
23.877	14.07	8.12	19.74	33.81	27.86	60.00	50.00	26.19	22.14

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted Emissions – 2.4 GHz BDR(HIGH) mode + LINE



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS	Phase : LINE
Test Mode : BDR high	Test Power : 110/60
Temp. / Humi. : 20 / 46	Test Engineer : YEON J H

Data: 522 File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (522) Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.348	20.19	16.68	19.44	39.63	36.12	59.00	49.00	19.37	12.88
0.350	20.19	16.66	19.44	39.63	36.10	58.96	48.96	19.33	12.86
0.507	14.39	10.74	19.44	33.83	30.18	56.00	46.00	22.17	15.82
0.592	13.79	10.32	19.43	33.22	29.75	56.00	46.00	22.78	16.25
0.592	13.84	10.29	19.43	33.27	29.72	56.00	46.00	22.73	16.28
28.152	13.93	1.05	19.69	33.62	20.74	60.00	50.00	26.38	29.26

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz BDR(HIGH) mode + NEUTRAL

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS

Phase : NEUTRAL

Test Mode : BDR high

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 525

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (525)

Date: 2018-02-09



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.348	20.10	16.60	19.42	39.52	36.02	59.00	49.00	19.48	12.98
0.511	14.46	10.27	19.42	33.88	29.69	56.00	46.00	22.12	16.31
0.515	14.33	10.13	19.42	33.75	29.55	56.00	46.00	22.25	16.45
4.031	13.46	9.87	19.46	32.92	29.33	56.00	46.00	23.08	16.67
22.393	11.28	3.98	19.74	31.02	23.72	60.00	50.00	28.98	26.28
23.877	14.07	8.12	19.74	33.81	27.86	60.00	50.00	26.19	22.14

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz EDR(LOW) mode + LINE

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel: +82-31-3236008, 9
Fax: +82-31-3236010

EUT / Model No. : WINIX QS

Phase : LINE

Test Mode : EDR low

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 528

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (528)

Date: 2018-02-09



Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB
0.349	19.75	16.75	19.44	39.19	36.19	58.99	48.99	19.80	12.80
0.351	19.81	16.55	19.44	39.25	35.99	58.94	48.94	19.69	12.95
0.356	19.51	16.43	19.44	38.95	35.87	58.82	48.82	19.87	12.95
0.948	12.45	9.52	19.46	31.91	28.98	56.00	46.00	24.09	17.02
26.659	8.12	2.30	19.68	27.80	21.98	60.00	50.00	32.20	28.02
28.093	14.26	1.61	19.69	33.95	21.30	60.00	50.00	26.05	28.70

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted Emissions – 2.4 GHz EDR(LOW) mode + NEUTRAL



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS	Phase : NEUTRAL
Test Mode : EDR low	Test Power : 110/60
Temp. / Humi. : 20 / 46	Test Engineer : YEON J H

Data: 531 File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (531) Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.347	19.69	16.77	19.42	39.11	36.19	59.03	49.03	19.92	12.84
0.509	14.44	10.60	19.42	33.86	30.02	56.00	46.00	22.14	15.98
0.512	14.21	10.13	19.42	33.63	29.55	56.00	46.00	22.37	16.45
4.415	11.90	8.22	19.45	31.35	27.67	56.00	46.00	24.65	18.33
20.286	9.39	3.04	19.71	29.10	22.75	60.00	50.00	30.90	27.25
28.097	14.03	0.68	19.80	33.83	20.48	60.00	50.00	26.17	29.52

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz EDR(MID) mode + LINE

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel: +82-31-3236008, 9
Fax: +82-31-3236010

EUT / Model No. : WINIX QS

Phase : LINE

Test Mode : EDR mid

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 537

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (537)

Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.347	19.73	16.87	19.44	39.17	36.31	59.02	49.02	19.85	12.71
0.348	19.74	16.83	19.44	39.18	36.27	59.02	49.02	19.84	12.75
0.351	19.79	16.63	19.44	39.23	36.07	58.94	48.94	19.71	12.87
0.513	13.90	9.89	19.44	33.34	29.33	56.00	46.00	22.66	16.67
13.863	6.49	1.28	19.60	26.09	20.88	60.00	50.00	33.91	29.12
24.527	12.09	-2.46	19.66	31.75	17.20	60.00	50.00	28.25	32.80

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions – 2.4 GHz EDR(LOW) mode + NEUTRAL

4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel: +82-31-3236008, 9
Fax: +82-31-3236010

EUT / Model No. : WINIX QS

Phase : NEUTRAL

Test Mode : EDR mid

Test Power : 110/60


Temp. / Humi. : 20 / 46

Test Engineer : YEON J H

Data: 534

File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (534)

Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.348	19.63	16.73	19.42	39.05	36.15	59.00	49.00	19.95	12.85
0.350	19.70	16.54	19.42	39.12	35.96	58.95	48.95	19.83	12.99
0.352	19.60	16.43	19.42	39.02	35.85	58.91	48.91	19.89	13.06
0.504	14.38	10.81	19.42	33.80	30.23	56.00	46.00	22.20	15.77
0.520	14.23	10.84	19.42	33.65	30.26	56.00	46.00	22.35	15.74
22.391	11.23	1.72	19.74	30.97	21.46	60.00	50.00	29.03	28.54

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted Emissions – 2.4 GHz EDR(HIGH) mode + LINE



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS	Phase : LINE
Test Mode : EDR high	Test Power : 110/60
Temp. / Humi. : 20 / 46	Test Engineer : YEON J H

Data: 540 File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (540) Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.349	19.76	16.81	19.44	39.20	36.25	59.00	49.00	19.80	12.75
0.504	14.11	10.58	19.44	33.55	30.02	56.00	46.00	22.45	15.98
0.513	13.87	9.87	19.44	33.31	29.31	56.00	46.00	22.69	16.69
0.513	13.92	9.89	19.44	33.36	29.33	56.00	46.00	22.64	16.67
0.596	13.17	10.46	19.43	32.60	29.89	56.00	46.00	23.40	16.11
28.062	14.41	2.13	19.69	34.10	21.82	60.00	50.00	25.90	28.18

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter


Conducted Emissions – 2.4 GHz EDR(HIGH) mode + NEUTRAL



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT / Model No. : WINIX QS	Phase : NEUTRAL
Test Mode : EDR high	Test Power : 110/60
Temp. / Humi. : 20 / 46	Test Engineer : YEON J H

Data: 543 File: D:\Conducted Data\2018\LTA_Conduction_2018_2.EM6 (543) Date: 2018-02-09



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV		QP	AV	QP	AV	QP	AV
	dBuV	dBuV	dB	dBuV	dBuV	dBuV	dBuV	dB	dB
0.349	19.67	16.63	19.42	39.09	36.05	58.98	48.98	19.89	12.93
0.349	19.68	16.63	19.42	39.10	36.05	58.98	48.98	19.88	12.93
0.509	14.49	10.74	19.42	33.91	30.16	56.00	46.00	22.09	15.84
0.509	14.48	10.72	19.42	33.90	30.14	56.00	46.00	22.10	15.86
4.038	13.47	9.96	19.46	32.93	29.42	56.00	46.00	23.07	16.58
24.000	13.39	3.12	19.74	33.13	22.86	60.00	50.00	26.87	27.14

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

3.4 Measurement Uncertainty

Parameter	Uncertainty
Centre Frequency	$\pm 1 \times 10^{-5}$ MHz
Occupied Channel Bandwidth	± 5 %
RF output power, conducted	± 1.5 dB
Power Spectral Density, conducted	± 3 dB
Unwanted Emissions, conducted	± 3 dB
All emissions, radiated	± 6 dB
Temperature	± 1 °C
Humidity	± 5 %
DC and low frequency voltages	± 3 %
Time	± 5 %
Duty Cycle	± 5 %

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2017-09-07
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2017-03-20
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2017-03-20
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2017-09-07
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2017-09-07
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2017-09-07
7	■	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2017-09-07
8	■	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2017-03-21
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2016-08-04
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2016-05-03
11	■	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2016-05-03
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2017-04-17
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2017-03-21
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15		DC Power Supply	6674A	3637A01657	Agilent	-	-
16	■	AC Power Supply	HK-80	LR001	DaeRim	-	-
17	■	Frequency Counter	5342A	2826A12411	HP	1 year	2017-03-21
18		Power Meter	EPM-441A	GB32481702	HP	1 year	2017-03-20
19	■	Power Sensor	8481A	3318A94972	HP	1 year	2017-12-26
20	■	Audio Analyzer	8903B	3729A18901	HP	1 year	2017-09-07
21		Modulation Analyzer	8901B	3749A05878	HP	1 year	2017-09-07
22		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2017-09-07
23		Stop Watch	HS-3	812Q08R	CASIO	2 year	2017-03-21
24		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2017-09-07
25		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2017-03-20
26		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2017-03-20
27		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2017-03-20
28		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2017-03-20
29		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2017-03-21
30	■	Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2017-03-23
31		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2017-03-21
32		Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2017-09-07
32		Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2017-03-20