FCC RF Test Report

APPLICANT	:	MeiG Smart Technology Co., Ltd
EQUIPMENT	:	Smart Module
BRAND NAME	:	MEIGLink
MODEL NAME	:	SLM920
FCC ID	:	2APJ4-SLM920
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	(NII) Unlicensed National Information Infrastructure
TEST DATE(S)	:	Aug. 10, 2023 ~ Aug. 21, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Test Software 7
1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency and Channel 8
2.2 Test Mode 10
2.3 Connection Diagram of Test System 12
2.4 Support Unit used in test configuration and system 12
2.5 EUT Operation Test Setup 13
2.6 Measurement Results Explanation Example 13

3 TEST RESULT **14**

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 14
3.2 Maximum Conducted Output Power Measurement 16
3.3 Power Spectral Density Measurement 18
3.4 Unwanted Emissions Measurement 20
3.5 AC Conducted Emission Measurement 25
3.6 Antenna Requirements 27

4 LIST OF MEASURING EQUIPMENT **28**

5 MEASUREMENT UNCERTAINTY **29**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR372609D	Rev. 01	Initial issue of report	Sep. 06, 2023

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 3.22 dB at 11400.000 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 18.72 dB at 0.440 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

MeiG Smart Technology Co., Ltd
2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

1.2 Manufacturer

MeiG Smart Technology Co., Ltd
2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Module
Brand Name	MEIGLink
Model Name	SLM920
FCC ID	2APJ4-SLM920
IMEI Code	Conducted: 860662054883547 Conduction: 860662054883448 Radiation: 860662054883463
HW Version	V1.03
SW Version	V01-T02
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	**<5180 MHz ~ 5240 MHz>** 802.11a : 15.59 dBm / 0.0362 W 802.11n HT20 : 14.64 dBm / 0.0291W 802.11n HT40 : 13.62 dBm / 0.0230W 802.11ac VHT20: 15.39 dBm / 0.0346W 802.11ac VHT40: 14.59 dBm / 0.0288W 802.11ac VHT80: 12.62 dBm / 0.0183W **<5260 MHz ~ 5320 MHz>** 802.11a : 15.78 dBm / 0.0378 W 802.11n HT20 : 14.89 dBm / 0.0308W 802.11n HT40 : 13.83 dBm / 0.0242W 802.11ac VHT20: 15.78 dBm / 0.0378W

	802.11ac VHT40: 14.99 dBm / 0.0316W 802.11ac VHT80: 12.90 dBm / 0.0195W **<5500 MHz ~ 5720 MHz >** 802.11a : 14.75 dBm / 0.0299 W 802.11n HT20 : 14.54 dBm / 0.0284W 802.11n HT40 : 13.62 dBm / 0.0230W 802.11ac VHT20: 15.34 dBm / 0.0342W 802.11ac VHT40: 14.72 dBm / 0.0296W 802.11ac VHT80: 12.69 dBm / 0.0186W **<5745 MHz ~ 5825 MHz>** 802.11a : 14.96 dBm / 0.0313 W 802.11n HT20 : 13.93 dBm / 0.0247W 802.11n HT40 : 13.27 dBm / 0.0212W 802.11ac VHT20: 14.92 dBm / 0.0310W 802.11ac VHT40: 14.39 dBm / 0.0275W 802.11ac VHT80: 12.12 dBm / 0.0163W
99% Occupied Bandwidth	**<5180 MHz ~ 5240 MHz>** 802.11a : 17.063 MHz 802.11ac VHT20 : 18.182 MHz 802.11ac VHT40 : 36.523 MHz 802.11ac VHT80 : 76.244 MHz **<5260 MHz ~ 5320 MHz>** 802.11a : 16.983 MHz 802.11ac VHT20 : 18.182 MHz 802.11ac VHT40 : 36.523 MHz 802.11ac VHT80 : 75.924 MHz **<5500 MHz ~ 5720 MHz>** 802.11a : 17.023 MHz 802.11ac VHT20 : 18.182 MHz 802.11ac VHT40 : 36.523 MHz 802.11ac VHT80 : 76.084 MHz **<5745 MHz ~ 5825 MHz>** 802.11a : 17.023 MHz 802.11ac VHT20 : 18.182 MHz 802.11ac VHT40 : 36.523 MHz 802.11ac VHT80 : 75.924 MHz
Antenna Type / Gain	**<5180 MHz ~ 5240 MHz> :** Glue Stick Antenna with gain 1.06 dBi **<5260 MHz ~ 5320 MHz> :** Glue Stick Antenna with gain 0.88 dBi **<5500 MHz ~ 5720 MHz> :** Glue Stick Antenna with gain 1.09 dBi **<5745 MHz ~ 5825 MHz> :** Glue Stick Antenna with gain 1.07 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their higher output power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42#	5210	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58#	5290	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106#	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122#	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138#	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link(5G) + charging from test jig

Simultaneous transmission
Wifi 5G 802.11a CH140_(5700MHz)TX + Part 90R B14 BW 5M Link

Remark: The RSE co-location mode is assessed from the worst WLAN TX + WWAN Link mode.

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11a	802.11a	802.11a	802.11a
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT20	802.11ac VHT20	802.11ac VHT20	802.11ac VHT20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT40	802.11ac VHT40	802.11ac VHT40	802.11ac VHT40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	122	-
Straddle		-	-	138	-

2.3 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
5.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.95 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.95 + 10 = 15.95 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

☒	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	1. Set RBW = approximately 1% of the emission bandwidth. **2.** Set the VBW > RBW. **3.** Detector = Peak. **4.** Trace mode = max hold **5.** Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. **6.** For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW. **7.** Measure and record the results in the test report.
☒	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	1. Set RBW = 100kHz. **2.** Set the VBW ≥ 3 x RBW. **3.** Detector = Peak. **4.** Trace mode = max hold **5.** Measure the maximum width of the emission that is 6 dB down from the peak of the emission. **6.** Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section F) Maximum power spectral density.

For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ 2 Span / RBW.

- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

For devices operating in the band 5.725 - 5.85 GHz

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of –27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(3) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log(d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Aug. 15, 2023~ Aug. 18, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Aug. 15, 2023~ Aug. 18, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Aug. 15, 2023~ Aug. 18, 2023	Jan. 04, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max 30dBm	Jan. 05, 2023	Aug. 21, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101932	10kHz~40GHz; Max 30dBm	Oct. 12, 2022	Aug. 21, 2023	Oct. 11, 2023	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 22, 2022	Aug. 21, 2023	Sep. 21, 2023	Radiation (03CH08-KS)
Bilog Antenna	TESEQ& VGT	CBL 61110	59915	30MHz-1GHz	Aug. 26, 2022	Aug. 21, 2023	Aug. 25, 2023	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 18, 2023	Aug. 21, 2023	Mar. 17, 2024	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 05, 2023	Aug. 21, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	Aug. 21, 2023	Jan. 07, 2024	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2023	Aug. 21, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 12, 2022	Aug. 21, 2023	Oct. 11, 2023	Radiation (03CH08-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2023	Aug. 21, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 21, 2023	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Aug. 21, 2023	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Aug. 21, 2023	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Aug. 10, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Aug. 10, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Aug. 10, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Aug. 10, 2023	Oct. 11, 2023	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±2.26 dB
Occupied Channel Bandwidth	±0.1 %
Conducted Power Spectral Density	±0.88 dB

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.28dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26dB

Appendix A. Conducted Test Results

A1. Conducted Test Results

Test Engineer:	Jiang Jun	Temperature:	21~25	°C
Test Date:	2023.8.15~2023.8.18	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail	Power Setting	Restriction
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1	
11a	6Mbps	1	36	5180	0.07	15.15	24.00	1.06		Pass	15	Target
11a	6Mbps	1	44	5220	0.07	15.39	24.00	1.06		Pass	15	Target
11a	6Mbps	1	48	5240	0.07	15.59	24.00	1.06		Pass	15	Target
HT20	MCS0	1	36	5180	0.08	14.18	24.00	1.06		Pass	14	Target
HT20	MCS0	1	44	5220	0.08	14.31	24.00	1.06		Pass	14	Target
HT20	MCS0	1	48	5240	0.08	14.64	24.00	1.06		Pass	14	Target
HT40	MCS0	1	38	5190	0.16	13.37	24.00	1.06		Pass	13	Target
HT40	MCS0	1	46	5230	0.16	13.62	24.00	1.06		Pass	13	Target
VHT20	MCS0	1	36	5180	0.07	15.13	24.00	1.06		Pass	15	Target
VHT20	MCS0	1	44	5220	0.07	15.23	24.00	1.06		Pass	15	Target
VHT20	MCS0	1	48	5240	0.07	15.39	24.00	1.06		Pass	15	Target
VHT40	MCS0	1	38	5190	0.14	13.83	24.00	1.06		Pass	13.5	Target
VHT40	MCS0	1	46	5230	0.14	14.59	24.00	1.06		Pass	14	Target
VHT80	MCS0	1	42	5210	0.34	12.62	24.00	1.06		Pass	12	Target

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting	Restriction
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1	
11a	6Mbps	1	52	5260	0.07	15.62	23.98	0.88	26.99	Pass	15	Target
11a	6Mbps	1	60	5300	0.07	15.78	23.98	0.88	26.99	Pass	15	Target
11a	6Mbps	1	64	5320	0.07	15.73	23.98	0.88	26.99	Pass	15	Target
HT20	MCS0	1	52	5260	0.08	14.60	23.98	0.88	26.99	Pass	14	Target
HT20	MCS0	1	60	5300	0.08	14.79	23.98	0.88	26.99	Pass	14	Target
HT20	MCS0	1	64	5320	0.08	14.89	23.98	0.88	26.99	Pass	14	Target
HT40	MCS0	1	54	5270	0.16	13.83	23.98	0.88	26.99	Pass	13	Target
HT40	MCS0	1	62	5310	0.16	13.74	23.98	0.88	26.99	Pass	13	Target
VHT20	MCS0	1	52	5260	0.07	15.52	23.98	0.88	26.99	Pass	15	Target
VHT20	MCS0	1	60	5300	0.07	15.63	23.98	0.88	26.99	Pass	15	Target
VHT20	MCS0	1	64	5320	0.07	15.78	23.98	0.88	26.99	Pass	15	Target
VHT40	MCS0	1	54	5270	0.14	14.88	23.98	0.88	26.99	Pass	14	Target
VHT40	MCS0	1	62	5310	0.14	14.99	23.98	0.88	26.99	Pass	14	Target
VHT80	MCS0	1	58	5290	0.34	12.90	23.98	0.88	26.99	Pass	12	Target

Report Number : FR372609D

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting	Restriction
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1	
11a	6Mbps	1	100	5500	0.07	14.34	23.98	1.09	26.99	Pass	14	Target
11a	6Mbps	1	116	5580	0.07	13.22	23.98	1.09	26.99	Pass	13	Target
11a	6Mbps	1	140	5700	0.07	13.90	23.98	1.09	26.99	Pass	13.5	Target
HT20	MCS0	1	100	5500	0.08	14.26	23.98	1.09	26.99	Pass	14	Target
HT20	MCS0	1	116	5580	0.08	14.54	23.98	1.09	26.99	Pass	13.5	Target
HT20	MCS0	1	140	5700	0.08	14.07	23.98	1.09	26.99	Pass	14	Target
HT40	MCS0	1	102	5510	0.16	13.62	23.98	1.09	26.99	Pass	13	Target
HT40	MCS0	1	110	5550	0.16	13.52	23.98	1.09	26.99	Pass	13	Target
HT40	MCS0	1	134	5670	0.16	13.61	23.98	1.09	26.99	Pass	13	Target
VHT20	MCS0	1	100	5500	0.07	14.75	23.98	1.09	26.99	Pass	15	Target
VHT20	MCS0	1	116	5580	0.07	14.58	23.98	1.09	26.99	Pass	14.5	Target
VHT20	MCS0	1	140	5700	0.07	15.22	23.98	1.09	26.99	Pass	15	Target
VHT40	MCS0	1	102	5510	0.14	14.59	23.98	1.09	26.99	Pass	14	Target
VHT40	MCS0	1	110	5550	0.14	14.36	23.98	1.09	26.99	Pass	14	Target
VHT40	MCS0	1	134	5670	0.14	14.72	23.98	1.09	26.99	Pass	14	Target
VHT80	MCS0	1	106	5530	0.34	12.03	23.98	1.09	26.99	Pass	12	Target
VHT80	MCS0	1	122	5610	0.34	12.29	23.98	1.09	26.99	Pass	12	Target

FCC U-NII-2C straddle channel single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting	Restriction
					Ant 1	Ant 1	Ant 1	Ant 1			Ant 1	
11a	6Mbps	1	144	5720	0.07	14.75	23.98	1.09	26.99	Pass	14.5	Target
HT20	MCS0	1	144	5720	0.08	13.97	23.98	1.09	26.99	Pass	14	Target
HT40	MCS0	1	142	5710	0.16	13.44	23.98	1.09	26.99	Pass	13	Target
VHT20	MCS0	1	144	5720	0.07	15.34	23.98	1.09	26.99	Pass	15	Target
VHT40	MCS0	1	142	5710	0.14	14.55	23.98	1.09	26.99	Pass	15	Target
VHT80	MCS0	1	138	5690	0.34	12.69	23.98	1.09	26.99	Pass	12	Target

Report Number : FR372609D

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail	Power Setting	Restriction
					Ant 1	Ant 1	Ant 1	Ant 1		Ant 1	
11a	6Mbps	1	149	5745	0.07	13.96	30.00	1.07	Pass	14	Target
11a	6Mbps	1	157	5785	0.07	14.96	30.00	1.07	Pass	15	Target
11a	6Mbps	1	165	5825	0.07	14.94	30.00	1.07	Pass	15	Target
HT20	MCS0	1	149	5745	0.08	13.93	30.00	1.07	Pass	14	Power
HT20	MCS0	1	157	5785	0.08	13.77	30.00	1.07	Pass	14	Target
HT20	MCS0	1	165	5825	0.08	13.45	30.00	1.07	Pass	14	Target
HT40	MCS0	1	151	5755	0.16	13.27	30.00	1.07	Pass	13	Target
HT40	MCS0	1	159	5795	0.16	13.08	30.00	1.07	Pass	13	Target
VHT20	MCS0	1	149	5745	0.07	14.05	30.00	1.07	Pass	14	Target
VHT20	MCS0	1	157	5785	0.07	14.92	30.00	1.07	Pass	15	Target
VHT20	MCS0	1	165	5825	0.07	14.33	30.00	1.07	Pass	15	Target
VHT40	MCS0	1	151	5755	0.14	14.39	30.00	1.07	Pass	14	Target
VHT40	MCS0	1	159	5795	0.14	14.03	30.00	1.07	Pass	14	Target
VHT80	MCS0	1	155	5775	0.34	12.12	30.00	1.07	Pass	12	Target

Emission Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	21.10	5169.70	5190.80	---	---
		5220	21.10	5209.70	5230.80	---	---
		5240	21.10	5229.70	5250.80	---	---
		5260	21.10	5249.70	5270.80	---	---
		5300	21.00	5289.70	5310.70	---	---
		5320	21.50	5309.60	5331.10	---	---
		5500	21.40	5489.60	5511.00	---	---
		5580	21.50	5569.60	5591.10	---	---
		5700	21.20	5689.60	5710.80	---	---
		5720	21.70	5709.00	5730.70	---	---
		5745	21.40	5734.60	5756.00	---	---
		5785	21.10	5774.70	5795.80	---	---
		5825	21.80	5814.00	5835.80	---	---
11AC20SISO	Ant1	5180	21.70	5169.10	5190.80	---	---
		5220	21.90	5209.00	5230.90	---	---
		5240	21.70	5229.20	5250.90	---	---
		5260	21.70	5249.10	5270.80	---	---
		5300	21.70	5289.10	5310.80	---	---
		5320	21.70	5309.10	5330.80	---	---
		5500	22.20	5489.00	5511.20	---	---
		5580	21.70	5569.40	5591.10	---	---
		5700	21.90	5689.10	5711.00	---	---
		5720	22.00	5709.10	5731.10	---	---
		5745	21.70	5734.10	5755.80	---	---
		5785	21.80	5774.00	5795.80	---	---
		5825	21.70	5814.00	5835.70	---	---
11AC40SISO	Ant1	5190	41.20	5169.40	5210.60	---	---
		5230	41.80	5209.40	5251.20	---	---
		5270	41.60	5249.20	5290.80	---	---
		5310	41.20	5289.60	5330.80	---	---
		5510	41.20	5489.60	5530.80	---	---
		5550	41.20	5529.60	5570.80	---	---
		5670	41.20	5649.60	5690.80	---	---
		5710	41.20	5689.60	5730.80	---	---
		5755	41.20	5734.40	5775.60	---	---
		5795	41.20	5774.40	5815.60	---	---
11AC80SISO	Ant1	5210	83.60	5168.40	5252.00	---	---
		5290	83.20	5248.40	5331.60	---	---
		5530	84.00	5488.40	5572.40	---	---
		5610	83.20	5568.40	5651.60	---	---
		5690	83.20	5648.80	5732.00	---	---
		5775	82.80	5733.40	5816.20	---	---

Test Graphs

11A_Ant1_5180



11A_Ant1_5220



11A_Ant1_5240



11A_Ant1_5260



11A_Ant1_5300



11A_Ant1_5320



11A_Ant1_5500



11A_Ant1_5580



11A_Ant1_5700



11A_Ant1_5720



11A_Ant1_5745



11A_Ant1_5785



11A_Ant1_5825



11AC20SISO_Ant1_5180



11AC20SISO_Ant1_5220



Date: 16.AUG.2023 03:07:15

11AC20SISO_Ant1_5240



Date: 16.AUG.2023 03:08:00

11AC20SISO_Ant1_5260



11AC20SISO_Ant1_5300



11AC20SISO_Ant1_5320



11AC20SISO_Ant1_5500



11AC20SISO_Ant1_5580



11AC20SISO_Ant1_5700



11AC20SISO_Ant1_5720



11AC20SISO_Ant1_5745



11AC20SISO_Ant1_5785



11AC20SISO_Ant1_5825



11AC40SISO_Ant1_5190



11AC40SISO_Ant1_5230



11AC40SISO_Ant1_5270



11AC40SISO_Ant1_5310



11AC40SISO_Ant1_5510



11AC40SISO_Ant1_5550



11AC40SISO_Ant1_5670



11AC40SISO_Ant1_5710



11AC40SISO_Ant1_5755



11AC40SISO_Ant1_5795



11AC80SISO_Ant1_5210



11AC80SISO_Ant1_5290



11AC80SISO_Ant1_5530



Date: 16.AUG.2023 03:30:58

11AC80SISO_Ant1_5610



Date: 16.AUG.2023 03:32:02

11AC80SISO_Ant1_5690



11AC80SISO_Ant1_5775



Occupied channel bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	16.983	5171.4885	5188.4715	---	---
		5220	17.063	5211.4486	5228.5115	---	---
		5240	17.023	5231.5285	5248.5514	---	---
		5260	16.983	5251.4885	5268.4715	---	---
		5300	16.943	5291.5285	5308.4715	---	---
		5320	16.983	5311.4885	5328.4715	---	---
		5500	17.023	5491.4885	5508.5115	---	---
		5580	16.943	5571.5285	5588.4715	---	---
		5700	17.023	5691.4885	5708.5115	---	---
		5720	16.983	5711.4885	5728.4715	---	---
		5745	16.943	5736.4885	5753.4316	---	---
		5785	16.983	5776.4486	5793.4316	---	---
		5825	17.023	5816.4086	5833.4316	---	---
11AC20SISO	Ant1	5180	18.142	5170.9690	5189.1109	---	---
		5220	18.182	5210.9291	5229.1109	---	---
		5240	18.142	5231.0090	5249.1508	---	---
		5260	18.102	5250.9690	5269.0709	---	---
		5300	18.142	5290.9690	5309.1109	---	---
		5320	18.182	5310.9291	5329.1109	---	---
		5500	18.142	5490.9291	5509.0709	---	---
		5580	18.142	5570.9690	5589.1109	---	---
		5700	18.182	5690.9291	5709.1109	---	---
		5720	18.182	5710.9291	5729.1109	---	---
		5745	18.182	5735.8891	5754.0709	---	---
		5785	18.142	5775.9291	5794.0709	---	---
		5825	18.142	5815.8891	5834.0310	---	---
11AC40SISO	Ant1	5190	36.444	5171.7782	5208.2218	---	---
		5230	36.523	5211.7782	5248.3017	---	---
		5270	36.523	5251.7782	5288.3017	---	---
		5310	36.364	5291.8581	5328.2218	---	---
		5510	36.444	5491.8581	5528.3017	---	---
		5550	36.444	5531.8581	5568.3017	---	---
		5670	36.523	5651.7782	5688.3017	---	---
		5710	36.444	5691.7782	5728.2218	---	---
		5755	36.444	5736.7782	5773.2218	---	---
		5795	36.523	5776.6983	5813.2218	---	---
11AC80SISO	Ant1	5210	76.244	5171.9580	5248.2018	---	---
		5290	75.924	5252.1179	5328.0420	---	---
		5530	76.084	5492.1179	5568.2018	---	---
		5610	75.924	5571.9580	5647.8821	---	---
		5690	75.924	5652.1179	5728.0420	---	---
		5775	75.924	5736.7982	5812.7223	---	---

Test Graphs

11A_Ant1_5180



11A_Ant1_5220



11A_Ant1_5240



11A_Ant1_5260



11A_Ant1_5300



11A_Ant1_5320



11A_Ant1_5500



11A_Ant1_5580



11A_Ant1_5700



11A_Ant1_5720



11A_Ant1_5745



11A_Ant1_5785



11A_Ant1_5825



11AC20SISO_Ant1_5180



11AC20SISO_Ant1_5220



11AC20SISO_Ant1_5240



11AC20SISO_Ant1_5260



11AC20SISO_Ant1_5300



11AC20SISO_Ant1_5320



11AC20SISO_Ant1_5500



11AC20SISO_Ant1_5580



11AC20SISO_Ant1_5700



11AC20SISO_Ant1_5720



11AC20SISO_Ant1_5745



11AC20SISO_Ant1_5785



11AC20SISO_Ant1_5825



11AC40SISO_Ant1_5190



11AC40SISO_Ant1_5230



11AC40SISO_Ant1_5270



11AC40SISO_Ant1_5310



11AC40SISO_Ant1_5510



11AC40SISO_Ant1_5550



11AC40SISO_Ant1_5670



11AC40SISO_Ant1_5710



11AC40SISO_Ant1_5755



11AC40SISO_Ant1_5795



11AC80SISO_Ant1_5210



11AC80SISO_Ant1_5290